

Form 9600-9
(December 1979)
(formerly 9180-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

ORIGINAL

OF THE
DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
THE SURVEY OF THE SUBDIVISION
AND
A METES-AND-BOUNDS SURVEY
OF CERTAIN SMALL LOTS IN SECTIONS 15 AND 16,
TOWNSHIP 21 NORTH, RANGE 7 EAST

Of the GILA AND SALT RIVER MERIDIAN Meridian,
In the State of ARIZONA

EXECUTED BY

JOHN P. BENNETT SUPERVISORY CADASTRAL SURVEYOR

Under special instructions dated SEPTEMBER 4, 19 81, approved SEPTEMBER 4, 1981,

, which provided for the surveys included under ~~XXXX~~ Survey/Group
Number 624, and assignment instructions dated SEPTEMBER 4, 19 81.

Survey commenced SEPTEMBER 9, 19 81

Survey completed OCTOBER 21, 19 81

INDEX DIAGRAM

Township 21 NORTH, Range 7 EAST

6	5	4	3	2	1
7	8	9	10	11	12
18	17	14 12 16 7 10	8 15 1 6	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 15.....pp. 15 - 19
 Survey of Certain Small Lots in Section 15.....pp. 20 - 29
 Subdivision of Section 16.....pp. 29 - 35
 Survey of Certain Small Lots in Section 16.....pp. 35 - 43

T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, the survey of the subdivision and a metes-and-bounds survey of certain small lots in sections 15 and 16, Township 21 North, Range 7 East, Gila and Salt River Meridian, Arizona.

The subdivisional lines were surveyed by John L. Harris, Deputy Surveyor, in 1878. Certain corners were remonumented by Louis D. Gilbert, Cadastral Surveyor, in 1970.

The boundaries of Lot 5 in sec. 15 were established in compliance with Public Law 96-581. Additional lots were surveyed in sections 15 and 16 at the request of the U.S. Forest Service.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated September 4, 1981.

The directions of lines were determined from triangulation stations of the horizontal control network and refer to the true meridian. Distances and angles were measured with a Zeiss SM-4 electronic instrument.

In initiating the resurvey, retracements of previous surveys were performed and a diligent search made to identify evidence of all previously established corner monuments. Identified corners were remonumented in their original positions and collateral evidence is used to reestablish obliterated corners.

The geographic position of the southeast corner of section 15 as determined from a tie made to U.S.C.&G.S's triangulation station "FLAGSTAFF," is:

Latitude: 35°11'44.72" N. Longitude: 111°37'48.17" W.

The mean magnetic declination is 14½° E.

Dependent Resurvey of a Portion
of the Subdivisional Lines
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

Reestablishment of the survey executed by
John L. Harris, Deputy Surveyor, in 1878

Beginning at the cor. of secs. 14, 15, 22 and 23, monumented with a sandstone, 24 x 9 x 6 ins., set 4 ins. in the ground in a scattered mound of stone, 3 ft. base, mkd. "T" on top.

from which the only remaining evidence of the original bearing trees

A pine stump, 30 ins. diam., bears N. 30° E., 96 lks. dist., with no scribe marks visible.

A pine stump, 34 ins. diam., bears N. 71° W., 129 lks. dist., with no scribe marks visible.

At the corner point

000 K 5 1 7 2

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground, in mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T21N R7E S15 S14 S22 S23 1981</p> <p>from which</p> <p style="padding-left: 40px;">A spike in east side of power pole, bears S. 14° W., 5.5 lks. dist., (lines extending N, S, E and W.)</p> <p style="padding-left: 40px;">An X BO marked on the south face of a rock outcrop, 6 x 6 x 6 ft., exposed, bears N. 24° W., 6.9 lks. dist.</p> <p>Deposit marked stone alongside iron post.</p> <p>Corner is located 1.5 lks. W. of a barbed wire fence, extending N. and S.</p> <p>N. 1°26' W., bet. secs. 14 and 15.</p> <p>Over rolling land through scattering to medium ponderosa pine.</p>
41.23	<p>The 1/4 sec. cor. of secs. 14 and 15, monumented by person(s) unknown, with an "X" marked on top of bedrock, 3 x 5 x 1/2 ft. above ground, at corner of abandoned fences extending S and E.</p> <p>This corner is shown on a 1962 City of Flagstaff, Az., McMillan Heights Development Map and various other plats on file with the City of Flagstaff, and is accepted as a careful and faithful determination of the corner position.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3½ in. stem, in drill hole and secured with concrete base 8 x 8 ins., mkd.</p> <p style="text-align: center;">T21N R7E 1/4 S15 S14 1981</p> <p>from which</p> <p style="padding-left: 40px;">A 5/8 in. rebar, projecting 4 ins. from the ground, bears N. 52° E., 35.7 lks. dist.</p> <p style="padding-left: 40px;">A nail in north side of a ponderosa pine, 8 ins. diam., bears N. 48° W., 22.2 lks. dist.</p> <p>Raise mound of stone, 3 ft. base, 2 ft. high, W of corner.</p> <p style="text-align: center;">—————</p> <p>N. 1°24' W., beginning new measurement.</p>
20.61	<p>The N 1/16 sec. cor. of secs. 14 and 15, identical with Corner 4, Lot 1, monumented with an open end pipe, 18 ins. long, 1½ ins. diam., projecting 2 ins. above ground, and in a scattered mound of stone.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS

This position is shown on various private survey plats on file with the City of Flagstaff, Az, and is accepted as a careful and faithful determination of the corner position.

At the corner point

Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.

T21N R7E
N 1/16
S15 | S14
1981

from which

A nail in the south side of a ponderosa pine, 9 ins. diam., bears S. 61° E., 19 lks. dist.

An X B0 marked on top of a boulder, 3 x 2 x 1 ft. above ground, bears N. 79° W., 37.6 lks. dist.

Deposit open end pipe alongside aluminum post.

N. 1°26' W., beginning new measurement.

20.61 The corner of secs. 10, 11, 14 and 15, identical with Corner 1, Lot 1, monumented with a copperweld 24 ins. long, set in an open end pipe, 20 ins. long, 1 in. diam., 2 ins. below ground, with cap mkd.

CITY
+
1962

This position is shown on various private survey plats on file with the City of Flagstaff, Az., and is accepted as a careful and faithful perpetuation of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, 2½ ins diam., 18 ins. in the ground, in mound of stone, 3 ft. base, to top, with brass cap mkd.

T21N R7E
S10 | S11
S15 | S14
1981

from which

A spike in west side of a power/telephone pole mkd. "MST&T Co. #615", lines extend E and W, bears N. 88°04' E., 77.5 lks. dist.

An X B0 on top of boulder, 5 x 3 x 1 ft. above ground, bears S. 1° E., 21.4 lks. dist.

An X B0 on top of boulder, 5 x 3 x 1 ft. above ground, bears N. 86½° W., 31.0 lks. dist.

Deposit copperweld and pipe inside iron post.

B00 K 5 1 72

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

<p>CHAINS</p> <p>39.86</p> <p>40.21</p>	<p>Corner is located 3 lks. S of power and telephone line, bears E and W.</p> <hr/> <p>From the corner of secs. 14, 15, 22 and 23.</p> <p>S. 89°22' W., bet. secs. 15 and 22.</p> <p>The 1/4 sec. cor. of secs. 15 and 22, monumented with a rebar, 5/8 ins. diam., with an aluminum cap, 1½ ins. diam., buried 3 ins. below ground, mkd.</p> <div style="text-align: center;"> <p>ARENCO</p> <table style="margin: auto;"> <tr> <td>P</td> <td></td> <td>1</td> </tr> <tr> <td>E</td> <td></td> <td>2</td> </tr> <tr> <td>2</td> <td></td> <td>3</td> </tr> <tr> <td>7</td> <td></td> <td>4</td> </tr> <tr> <td></td> <td>1</td> <td>S</td> </tr> <tr> <td></td> <td></td> <td>L</td> </tr> </table> </div> <p>This position is accepted by local surveyors as a perpetuation of the original corner and is accepted as the best available evidence of the original corner position.</p> <p>from which</p> <p style="padding-left: 40px;">The SE corner of a wood frame addition to a house bears N. 10° E., 17.4 lks. dist.</p> <p style="padding-left: 40px;">The SE corner of the foundation of a house bears N. 46° E., 57.3 lks. dist.</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears S. 38° W., 36.7 lks. dist. No blaze taken.</p> <p style="padding-left: 40px;">The corner of a chain line fence, extending N and W, bears N. 88° W., 35.8 lks. dist.</p> <p>Corner is located 3 lks. N of a power and telephone line extending E and W.</p> <p>Corner is located in the backyard of Bublitz residence, 781 E. Hilltop Ave., Flagstaff, Az.</p> <p>Corner not remonumented.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°39' W., beginning new measurement.</p> <p>The corner of secs. 15, 16, 21 and 22, monumented with an open end pipe, ¾ in. diam., set 10 in. below ground in another open end pipe, 1½ ins. diam., set 18 ins. below ground. William June, a former owner of the property, stated the pipe was set prior to 1940 as the section corner.</p> <p>The monumented intersection of San Francisco and E. Phoenix streets bears N. 4°20' E., 3.44 chs. dist. (This closely matches a tie by the City of Flagstaff in 1938 of N. 4°42' E., 3.43 chs. dist.)</p> <p>This position is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., over found pipes, 22 ins. in the ground, with brass cap mkd.</p>	P		1	E		2	2		3	7		4		1	S			L
P		1																	
E		2																	
2		3																	
7		4																	
	1	S																	
		L																	

B00 K 5 1 7 2

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">T21N R7E S16 S15 S21 S22 1981</p> <p>from which</p> <p>The SW corner of a block building, 80 x 40 ft., bears N. 48° E., 170.2 lks. dist., the long side bears N. 24° E.</p> <p>A spike in the side of a power pole bears S. 89 1/4° E., 142.8 lks. dist.</p> <p>The NE corner of a stone foundation to an abandoned sandstone handball court bears S. 31°42' E., 72.1 lks. dist., the long side bears N. 68° W.</p> <p>The NE corner of a block addition to an old building bears S. 54° W., 21.9 lks. dist.</p> <p>Cor. is located at the southernmost corner of a native stone building, sides extending N. 22° E., and N. 68° W.</p>	
	<p>From the corner of secs. 15, 16, 21 and 22.</p> <p>N. 2°54' W., bet. secs. 15 and 16.</p>	
42.68	<p>The 1/4 sec. cor. of secs. 15 and 16, monumented with an unmkd. brass cap, 1 1/4 in. diam., set inside a monument box, 3 ins. below asphalt surface. This monument was set by the City of Flagstaff and is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>from which</p> <p>The NW corner of a stucco house at 510 Humphreys St., bears N. 88°09' E., 63.7 lks. dist.</p> <p>The SW corner of a stucco house at 510 Humphreys St., bears S. 52°12' E., 64.0 lks. dist.</p> <p>The SE corner of a block house at 507 Humphreys St., bears N. 82°43' W., 88.5 lks. dist.</p> <p>The NE corner of a block house at 507 Humphreys St., bears N. 39°40' W., 98.7 lks. dist.</p> <p>Cor. is located 9 lks. E of the center line of Humphreys St., which is also U.S. Hwy. No. 180, bears N. 20° E., and S. 20° W.</p> <p>Cor. not remonumented.</p>	
	<p style="text-align: center;">_____</p> <p>N. 0°11' W., beginning new measurement.</p>	
20.12	<p>Point for the N 1/16 sec. cor. of secs. 15 and 16, located under a cinderblock lot line fence within a private subdivision. Impractical to monument.</p>	
40.24	<p>The corner secs. 9, 10, 15 and 16, monumented with a brass cap, 2 ins. diam., set flush with pavement in a concrete base, 10 ins. diam., mkd.</p>	

B00 K 5 172

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS

CITY OF FLAGSTAFF

T21N R7E

9	10
16	15
1975	

This is accepted as a careful and faithful perpetuation
of the position of the original corner.

from which

A ponderosa pine, 22 ins. diam., bears S. 52 1/4° E.,
180.5 lks. dist., mkd. T21N R7E S15 BT. Core
dating reveals tree age is 70 years, and blazed
near 1940.

Corner is located 90 lks. E of center line intersections
of W. Forest Ave., bears E only, and N. Fort Valley Rd.,
bears N. 30° W. and S. 30° E., curving southerly.

Cor. not remonumented.

From the corner of secs. 10, 11, 14 and 15.

S. 89°47' W., bet. secs. 10 and 15.

Through scattered pine, along powerline.

15.15 Point for Corner 2, Lot 1, identical with Corner 1, Lot
2.

Set an aluminum post, 30 ins. long, 1 in. diam., 18 ins.
in the ground, in mound of stone, 2 1/2 ft. base, to top,
with aluminum cap mkd.

S10	
1	2
Lot 2	Lot 1
S15	
1981	

from which

The marks X B0 on top of a boulder, 4 X 4 X 2 ft.
above ground, bears S. 61°14' E., 102.1 lks. dist.

A nail, in N side of telephone and power pole, mkd.
41, bears N. 78° E., 10.1 lks. dist. (lines extend
E and W).

Cor. is located 3 lks. S of power lines, extending E and
W.

39.51 Point for Corner 2, Lot 2, identical with Corner 1, Lot
4, in center line of Turquoise Dr., asphalt surfaced,
bears N and S.

Set a railroad spike flush with pavement, mkd.

B00 K5 172

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS		
	<div style="text-align: center;"> $\begin{array}{c} \text{S10} \\ \hline 1 \quad 2 \\ \text{Lot 4} \quad \quad \text{Lot 2} \\ \text{S15} \\ 1981 \end{array}$ </div> <p>40.12 The 1/4 sec. cor. of secs. 10 and 15, identical with Corner 2, Lot 4, monumented with a rebar, 5/8 ins. diam., projecting 2 ins. from a concrete filled section of culvert pipe, 12 ins. diam., flush with the ground, with a brass cap, 1 1/2 ins. diam. mkd.</p> <div style="text-align: center;"> <p>CITY + 1962</p> </div> <p>from which the only remaining evidence of the original bearing trees</p> <p style="padding-left: 40px;">A dead and down pine, 31 ins. diam., bears S. 32° E., 617 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A pine stump, 24 ins. diam., bears S. 71° W., 194 lks. dist., no marks visible (record: S.67° W., 182 lks. dist.)</p> <p>This corner is accepted as a careful and faithful perpetuation of the original corner position.</p> <p>from which</p> <p style="padding-left: 40px;">The center of a manhole cover, 2.2 ft. diam., set in concrete, 3.6 ft. diam., and projecting 1 ft. above ground, bears S. 9 1/4° E., 66.7 lks. dist.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>S. 89°50' W., beginning new measurement.</p>	
10.86	Center line of San Francisco St., asphalt surfaced, bears N. 20° E., curving N, and S. 20° W., curving S.	
11.67	<p>Point for Corner 3, Lot 4, identical with Corner 1, Lot 5, at intersection with the W right-of-way of San Francisco St.</p> <p>Set aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{S10} \\ \hline 1 \quad 3 \\ \text{Lot 5} \quad \quad \text{Lot 4} \\ \text{S15} \\ 1981 \end{array}$ </div> <p>from which</p> <p style="padding-left: 40px;">A nail, 12 ins. above ground in the S side of a power and telephone pole, mkd. 798, bears N. 81° E., 18.9 lks. dist.</p> <p style="padding-left: 40px;">A nail, 6 ins. above ground in the W side of a ponderosa pine, 14 ins. diam., bears N. 13° W., 76.7 lks. dist.</p> <p>Corner is located 46 lks. N of the center line of Forest Ave., bears E and W.</p>	

B.O.O. K 5 1 7 2

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS		
20.10	<p>The W 1/16 sec. cor. of secs. 10 and 15, monumented with a rebar, 5/8 ins. diam., 12 ins. long, top buried 3 ins. below surface with an aluminum cap, 1½ in. diam., mkd.</p> <p style="text-align: center;">2007 +</p> <p>Rebar is set directly over an open end pipe, 18 ins. long, 1 in. diam., set 16 ins. below ground in concrete base, 8 ins. diam.</p> <p>This corner is shown on various private survey plats on file with the City of Flagstaff, Az., and is accepted as a careful and faithful determination of the corner position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T21N R7E S10 W 1/16 ————— S15 1981</p> </div> <p>from which</p> <p>The marks X B0, on the SW side of a steel storm sewer grate box, 3 x 2 ft., bears N. 88½° W., 86.5 lks. dist.</p> <p>The top of a fire hydrant valve bears N. 51°43' W., 127.7 lks. dist.</p> <p>A nail, 3 ins. below asphalt surface, at the intersection of the center lines of Beaver St. and Forest Ave., bears N. 45°46' W., 64.0 lks. dist.</p> <p>A railroad spike in W side of telephone pole on NE corner of intersection bears N. 3°22' W., 84.5 lks. dist. Lines extend E, S and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°52' W., beginning new measurement.</p>	
20.11	<p>The corner of secs. 9, 10, 15 and 16, heretofore described.</p>	
39.94	<p>From the corner of secs. 15, 16, 21 and 22.</p> <p>N. 88°22' W., bet. secs 16 and 21.</p> <p>The 1/4 sec. cor. of secs. 16 and 21, monumented with a railroad rail, projecting 4 ins. from the ground, with top mkd. X. This monument is used by local surveyors as the 1/4 sec. cor. and is accepted as a careful and faithful perpetuation of the original corner position.</p> <p>from which</p>	

B O O K 5 1 7 2

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS

A brass tablet, 2 1/4 ins. diam., set flush with pavement in a concrete base, 10 ins. diam., at the intersection of S. Florence St., S. Malpais Lane and W. Clay Ave. bears S. 52½° E., 77 lks. dist., mkd. CITY OF FLAGSTAFF.

United States Coast and Geodetic Survey triangulation station "Flagstaff 1958" bears N. 50°16' W., 22.16 chs. dist., monumented with a standard brass tablet, 3½ ins. diam., set flush with the ground in a 12 in. square concrete base, with top mkd. FLAGSTAFF 1958 and a triangle.

Corner not remonumented.

N. 88°26' W., beginning new measurement.

41.99 The corner of secs. 16, 17, 20 and 21, reestablished from the original bearing trees, and trees marked in the 1970 remonumentation by Louis D. Gilbert, Cadastral Surveyor. A granite stone, 28 x 14 x 7 ins. mkd. X on top, 3 grooves on one face, 4 grooves on another face, found laying loose in bulldozer rubble. The 1970 iron post was bladed out and was not found.

from which the remaining original bearing trees

A pine, 36 ins. diam., bears N. 7° E., 25 lks. dist., with overgrown blaze. (1970 record bearing: N. 12° E.)

A pine, 24 ins. diam., bears S. 34° W., 13 lks. dist. with overgrown blaze. (1970 record dist.: 14 lks.)

A pine, 24 ins. diam., bears N. 60° W., 205 lks. dist. mkd TXXIN RVIIE XVII. (1970 record bearing N. 51° W.)

from which the bearing tree mkd. in 1970

A pine, 11 ins. diam., bears S. 69° E., 80 lks. dist. with overgrown blaze. (record: S. 60° E.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T21N	R7E
<u>S17</u>	<u>S16</u>
S20	S21
1981	

from which

A rebar, ½ in. diam., projecting 3 ins. above ground, bears S. 56° E., 56.1 lks. dist. (Set by Arizona Engineering Company of Flagstaff, Az.)

A rebar, ½ in. diam., projecting 3 ins. above ground, bears S. 36° E., 88 lks. dist. (Set by Arizona Engineering Company of Flagstaff, Az.)

Deposit mkd. stone alongside iron post.

B00 K5 172

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS	
40.53	<p>Raise a mound of stone, $4\frac{1}{2}$ ft. base, 3 ft. high, W. of cor.</p> <p>A very strong magnetic attraction was observed at this corner. All bearings refer to the true meridian.</p> <hr/> <p>From the corner of secs. 16, 17, 20 and 21.</p> <p>N. $0^{\circ}49'$ W., bet. secs. 16 and 17.</p> <p>Over rolling land, through medium to dense pine and scattering oak.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 16 and 17, monumented with a rebar, $\frac{5}{8}$ in. diam., 20 ins. long, projecting 8 ins. above ground, in a scattered mound of stone, with an aluminum cap attached and mkd.</p> <p style="text-align: center;">+ RLS 4321</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A pine stump, 24 ins. diam., bears N. 60° W., 57 lks. dist., mkd. $\frac{1}{4}$ S. (Record bearing: N. 58° W.)</p> <p>This corner was remonumented by Charles W. Dryden, Reg. Land Surveyor No. 4321, AZ.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21N R7E 1/4 S17 S16 1981</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A pine, 9 ins. diam., bears S. 24° W., 25 lks. dist., mkd. X BT at base.</p> <p style="padding-left: 40px;">A pine, 16 ins. diam., bears N. 79° W., 141 lks. dist., mkd. $\frac{1}{4}$ S17 BT.</p> <p>Inserted rebar inside iron post, raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, W. of cor.</p> <p>Corner is located 145 lks. N. of a single lane asphalt road, bears N. 70° E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $1^{\circ}26'$ W., beginning new measurement.</p> <p>Over rolling land, through medium pine and scattered oak.</p>
15.03	<p>The N-S-N $\frac{1}{256}$ sec. cor. of secs. 16 and 17, monumented with a rebar, $\frac{5}{8}$ in. diam., projecting 1 in. above ground, in a concrete base, with a tag attached and mkd. LS 6893. The monument is referred to on a plat on file with Arizona Engineering Company, Flagstaff, Az., and is accepted as a careful and faithful determination of the position of the corner.</p>

BOOK 5172

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS

At the corner point

Set an aluminum cap, 1 in. diam., on to the top of the rebar, in a mound of stone, 3 ft. base to top, mkd.

N S N
1/256
S17 | S16
1981

from which

A ponderosa pine, 8 ins. diam., bears N. $34\frac{1}{4}^{\circ}$ E.,
32.7 lks. dist., mkd. N S N 1/256 S16 BT.

A ponderosa pine, 26 ins. diam., bears N. $60\frac{1}{2}^{\circ}$ W.,
74.5 lks. dist., mkd. N S N 1/256 S17 BT.

Corner is located at the W end of a fence, extends E only.

N. $1^{\circ}26'$ W., beginning new measurement.

5.01 Point for the N 1/16 sec. cor. of secs. 16 and 17.

Set an aluminum post, 20 ins. long, 1 in. diam., 20 ins. in the ground, flush with surface on east edge of road, with aluminum cap mkd.

T21N R7E
N 1/16
S17 | S16
1981

from which

A ponderosa pine, 14 ins. diam., bears N. $30\frac{1}{2}^{\circ}$ E.,
32.0 lks dist., mkd. N 1/16 S16 BT.

A ponderosa pine, 10 ins. diam., bears S. $89\frac{1}{2}^{\circ}$ W.,
23.5 lks. dist., mkd. N 1/16 S17 BT.

Raise a mound of stone, $4\frac{1}{2}$ ft. base, 4 ft. high, E of cor.

Corner is located 8 lks. E of the center of a dirt road, bears N and S, and 22 lks. W of a wire fence, extending N and S.

25.04 The corner of secs. 8, 9, 16 and 17, remonumented by Louis D. Gilbert, Cadastral Surveyor, in 1970, with an iron post, $2\frac{1}{2}$ ins. diam., projecting 6 ins. above ground, with a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, to the west and with a brass cap mkd.

T21N R7E
S8 | S9
S17 | S16
1970

from which the original bearing trees

A pine, 32 ins. diam., bears N. 49° E., 75 lks. dist., with overgrown burnt blaze. (Record: N. 52° E., 72 lks. dist.)

800 K 5 1 7 2

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS

A burnt pine stump, 20 ins. diam., bears S. 7° W.,
105 lks. dist., with no scribe mks. visible
(Record: S. 6½° W., 112 lks. dist.)

A pine, 38 ins. diam., bears N. 78° W., 60 lks.
dist., with overgrown burnt blaze. (Record:
N. 80° W.)

from which the 1970 bearing trees

A pine, 28 ins. diam., bears S. 68° E., 50 lks.
dist., mkd. T21N R7E S16 BT. (Record: S. 70° E.,
51 lks. dist.)

A pine, 12 ins. diam., bears S. 25° W., 26 lks.
dist., mkd. X BT. (Record: S. 23° W., 25 lks. dist.)

From the corner of secs. 9, 10, 15 and 16.

S. 89°28' W., bet. secs. 9 and 16.

Through scattered ponderosa pine and oak.

39.99

The 1/4 sec. cor. of secs. 9 and 16, monumented with a
volcanic stone, 12 x 10 x 8 ins., firmly set 10 ins. in
the ground, mkd. X on top and 1/4 on W. side. An open
end pipe, 14 ins. long, 2 ins. diam., was found firmly
set alongside, projecting 2 ins. from ground.

from which an original bearing tree

A ponderosa pine, 30 ins. diam., bears N. 41° E.,
25 lks. dist., with no mks. visible on open blaze.
(Record: N. 45° E., 23 lks. dist.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in
the ground, in a mound of stone, 2½ ft. base, to top,
with brass cap mkd.

T21N	R7E
S	9
1/4	—————
S	16
	1981

from which

A ponderosa pine, 12 ins. diam., bears S. 47° E.,
66 lks. dist., mkd. 1/4 S16 BT.

Deposit original stone and pipe alongside iron post

Corner is located under a wire mesh fence extending N
and S.

Corner is located 54½ lks. W of the center line of a
cinder road, bears N and S.

N. 89°29' W., beginning new measurement.

Over rolling land through medium to dense pine and scrub
brush.

B00 K 5 1 72

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS		
10.295	<p>Point for the E-W 1/64 sec. cor. of secs. 9 and 16, identical with Corner 3, Lot 4.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground in a mound of stone, 3 ft. base, to top with aluminum cap mkd.</p> <p style="text-align: center;">S9 E-W 1/64 S16 1981</p> <p>from which</p> <p style="padding-left: 40px;">A galvanized nail in the W side of a ponderosa pine, 10 ins. diam., bears S. 22° E., 10.5 lks. dist.</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears S. 44° W., 50 lks. dist., mkd. E-W 1/64 S16 BT.</p>	
20.59	<p>Point for the W 1/16 sec. cor. of secs. 9 and 16, identical with Corner 4, Lot 4.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.</p> <p style="text-align: center;">T21N R7E S 9 W 1/16 ——— S 16 1981</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears S. 21½° E., 21.7 lks. dist., mkd. X BT at the base.</p> <p style="padding-left: 40px;">A fence corner bears S. 2 1/4° E., 68.8 lks. dist. Fence extends West only.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S. 47° W., 36 lks. dist., mkd. W 1/16 S16 BT.</p>	
41.18	<p>The corner of secs. 8, 9, 16 and 17.</p> <hr/> <p>Survey of the Subdivision of Section 15 T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona</p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 15 and 22.</p> <p>N. 1°35' W., on the N and S center line of sec. 15.</p>	
42.01	<p>The center 1/4 sec. cor. of sec 15, monumented with a granite stone, of unknown origin, 12 x 9 x 4 ins., projecting 6 ins. above ground, in a mound of stone 2½ ft. base, 6 ins. high, mkd. X on top and CS 1/4 on W face.</p> <p>This corner is referred to on various private survey plats on file with the City of Flagstaff, Az., and is accepted as a careful and faithful determination of the corner position.</p> <p>At the corner point</p>	

B00 K5 172

Survey of the Subdivision of Section 15,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS

Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, in mound of stone, 2½ ft. base, to top, with aluminum cap mkd.

T21N R7E
C1/4 S15
1981

from which

A galvanized nail on the W side and at base of a ponderosa pine, 12 ins. diam., bears S. 40° W., 15.0 lks. dist.

A galvanized nail on the W side and at base of a ponderosa pine, 10 ins. diam., bears N. 32° W., 23.1 lks. dist.

N. 1°37' W., beginning new measurement.

Over rolling land, through medium ponderosa pine.

20.36 Point for the center N 1/16 sec. cor. of sec. 15, identical with Corner 10, Lot 4.

Set an aluminum post, 28 ins. long, 1 in. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base to top, with aluminum cap mkd.

N 1/16 | C S15
C
1981

from which

A galvanized nail, on N side of ponderosa pine, 8 ins. diam., bears N. 72° E., 30.5 lks. dist.

A rebar, 5/8 ins. diam., projecting 6 ins. above ground, in a mound of stone, 2½ ft. base to top, with an aluminum cap, 1½ in. diam., mkd.

ARENCO
P 1
E 2
9 3
7 4
1 S
L

bears S. 57½° W., 6.2 lks. dist. This monument, referred to on a plat of the Switzer Canyon Waterline survey by Arizona Engineering Company in 1975, on file with the City of Flagstaff, Az, was established using improper procedures and is not utilized in the course of this survey.

A galvanized nail, on E side of ponderosa pine, 8 ins. diam., bears N. 36° W., 57.0 lks. dist.

Corner of abandoned fences, bears S. 57° W., 39 lks. dist. Fences extend N, S and W.

40.73 The 1/4 sec. cor. of secs. 10 and 15.

B00 # 5 172

Survey of the Subdivision of Section 15,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS													
	<p>From the 1/4 sec. cor. of secs. 14 and 15.</p> <p>N. 89°30' W., on the E and W center line of sec. 15.</p>												
39.99	<p>The center 1/4 sec. cor. of sec. 15.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°29' W., beginning new measurement.</p>												
20.61	<p>Point for the center W 1/16 sec. cor. of sec. 15, located within a private subdivision under construction. Impractical to monument.</p>												
41.22	<p>The 1/4 sec. cor. of secs. 15 and 16.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 14 and 15, identical with Corner 4, Lot 1.</p> <p>N. 89°51' W., on the E and W center line of the NE 1/4 of sec. 15.</p>												
7.725	<p>Point for Corner 3, Lot 1, identical with Corner 5, Lot 3.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 2½ ft. base to top, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr> <td style="padding: 0 5px;">Lot 3</td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">Lot 1</td> </tr> <tr> <td style="text-align: center;">5</td> <td style="border-left: 1px solid black; text-align: center;">3</td> <td></td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; text-align: center;">S15</td> <td></td> </tr> <tr> <td colspan="2" style="text-align: center;">1981</td> <td></td> </tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">The marks X B0 on top of a boulder, 4 x 3 x 1 ft., bears N. 45° E., 45.7 lks. dist.</p> <p style="margin-left: 40px;">A nail in the W side of a ponderosa pine, 10 ins. diam., bears N. 66° W., 2.6 lks. dist.</p>	Lot 3		Lot 1	5	3		S15			1981		
Lot 3		Lot 1											
5	3												
S15													
1981													
34.76	<p>Point for Corner 4, Lot 3, identical with Corner 11, Lot 4, at intersection with the center line of Turquoise Dr.</p> <p>Set a railroad spike, flush with asphalt surfaced road, mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr> <td style="padding: 0 5px;">Lot 4</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">Lot 3</td> </tr> <tr> <td style="text-align: center;">11</td> <td style="border-left: 1px solid black; text-align: center;">4</td> <td></td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; text-align: center;">S15</td> <td></td> </tr> <tr> <td colspan="2" style="text-align: center;">1981</td> <td></td> </tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">An aluminum post, 30 ins. long, ¾ ins. diam., set 21 ins. in the ground, for a reference monument, bears N. 34°21' E., 57.82 ft. dist., with aluminum cap mkd. Lot 3 57.82 FT.RM 1981 and an arrow pointing to the cor.</p> <p style="margin-left: 40px;">An aluminum post, 30 ins. long, ¾ in. diam., set 21 ins. in the ground, for a reference monument, bears N. 55°39' W., 66.25 ft. dist., with aluminum cap mkd. Lot 4 66.25 FT RM 1981 and an arrow pointing to the cor.</p>	Lot 4		Lot 3	11	4		S15			1981		
Lot 4		Lot 3											
11	4												
S15													
1981													

B O O K 5 1 7 2

Survey of the Subdivision of Section 15,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS	
40.055	<p>From this point, a brass tablet, 2½ ins. diam., set flush with surface in concrete base in center of Turquoise Dr., bears S. 12°36'04" E., 5.514 chs. dist. This monument represents a point of curvature as shown on plat No. 6152, by John D. Prewit, Reg. Civil Engineer No. 2649 AZ, on file with the City of Flagstaff, AZ.</p> <p>The center N 1/16 sec. cor of sec. 15.</p>
20.24	<p>From the center W 1/16 sec. cor. of sec. 15.</p> <p>N. 0°55' W., on the N and S center line of the NW 1/4 of sec. 15.</p> <p>Point for the NW 1/16 sec. cor. of sec. 15, identical with Corner 7, Lot 5, at intersection with the E and W centerline of the NW 1/4.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with aluminum cap mkd.</p> <p style="text-align: center;">NW 1/16 S15 1981</p> <p>from which</p> <p style="padding-left: 40px;">An open end iron pipe of unknown origin, 5/8" diam., projecting 7 ins. from ground in mound of stone, 1½ ft. base, 3 ins. high, bears N. 53°17' W., 40.3 lks. dist.</p>
22.77	<p>Point for the center S-S-N-NW 1/1024 sec. cor. of sec. 15, identical with Corner 6, Lot 5.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with aluminum cap mkd.</p> <p style="text-align: center;">S15 1/1024 1981</p> <p>from which</p> <p style="padding-left: 40px;">The marks X B0 on the SW face of a volcanic boulder, 4 x 4 x 3 ft., bears N. 39° E., 72.9 lks. dist.</p> <p style="padding-left: 40px;">A galvanized nail, in E side of ponderosa pine, 12 ins. diam., bears S. 30° W., 43.7 lks. dist.</p> <p style="padding-left: 40px;">A rebar, 5/8 in. diam., projecting 2 ins. above ground with an aluminum cap, 1 1/4 diam., mkd. + 2007, bears S. 88°43' W., 22.4 lks. dist. The monument was set by James B. Holmquist prior to 1972 in an unrecorded survey, is not accepted as a careful and faithful determination of the position of the corner, and is not utilized in the course of this survey.</p> <p style="padding-left: 40px;">An open end iron pipe of unknown origin, 5/8 in. diam., projecting 6 ins. above ground, in a mound of stone, 2 ft. base, 6 ins. high, bears N. 15°44' W., 22.3 lks. dist. This monument is not accepted as a careful and faithful determination of the position of the corner, and is not utilized in the course of this survey.</p>


Survey of the Subdivision of Section 15,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS																	
30.36	<p>Point for the center N-NW 1/64 sec. cor. of sec. 15, identical with Corner 3, Lot 5.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 16 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with an aluminum cap mkd.</p> <p style="text-align: center;">S15 C-N-NW 1/64 1981</p> <p>from which</p> <p style="padding-left: 40px;">The top of a fire hydrant bears N. 86°54' E., 39.8 lks. dist.</p> <p style="padding-left: 40px;">The NW corner of a stucco building, 32 x 50 ft., bears S. 10°54' E., 77.7 lks. dist., long side bears south.</p> <p style="padding-left: 40px;">An open end iron pipe of unknown origin, 1 in. diam., projecting 2 ins. from a concrete base, 6 ins. diam., set flush with ground, bears N. 54°24' W., 19.7 lks. dist. The monument is not accepted as a careful and faithful determination of the corner position, and is not utilized in the course of this survey.</p>																
40.48	<p>The W 1/16 sec. cor. of secs. 10 and 15.</p>																
16.00	<p>From the center N 1/16 sec. cor. of sec. 15.</p> <p>N. 89°49' W., on the E and W center line of the NW 1/4 of sec. 15.</p>																
16.82	<p>Center line of San Francisco St., asphalt surfaced, bears N. 21°07' E., and S. 21°07' W.</p>																
16.82	<p>Point for Corner 9, Lot 4, identical with Corner 8, Lot 5, at intersection with the W right-of-way of San Francisco St.</p> <p>Set an aluminum post, 20 ins. long, 1 in. diam., 2 ins. into drill hole, in bedrock 7 ins. below ground, secured in a concrete base and in a mound of stone, 3 ft base, to top, with an aluminum cap mkd.</p> <p style="text-align: center;"> <table style="margin: auto;"> <tr> <td style="padding: 0 10px;">Lot 5</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">/</td> <td style="padding: 0 10px;">Lot 4</td> </tr> <tr> <td style="text-align: center;">8</td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;">/</td> <td style="text-align: center;">9</td> </tr> <tr> <td colspan="3" style="text-align: center;">-----</td> </tr> <tr> <td colspan="3" style="text-align: center;">S15</td> </tr> <tr> <td colspan="3" style="text-align: center;">1981</td> </tr> </table> </p> <p>from which</p> <p style="padding-left: 40px;">The NE corner of a block duplex, located at 1005 and 1007 San Francisco St., bears S. 23° W., 30.9 lks. dist.</p> <p style="padding-left: 40px;">The NW corner of same duplex bears S. 77° W., 52.5 lks. dist.</p>	Lot 5	/	Lot 4	8	/	9	-----			S15			1981			
Lot 5	/	Lot 4															
8	/	9															

S15																	
1981																	
20.35	<p>The NW 1/16 sec. cor. of sec. 15.</p>																
40.71	<p>The N 1/16 sec. cor. of secs. 15 and 16.</p>																

Survey of Certain Small lots in Section 15,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS	
	<u>Lot 1</u>
	Beginning at Corner 1, Lot 1, identical with the cor. of
	secs. 10, 11, 14 and 15, heretofore described.
	S. 89°47' W., on line 1-2, Lot 1, identical with the line
	bet. secs. 10 and 15.
15.15	Corner 2, Lot 1, identical with Corner 1, Lot 2, heretofore described.

	S. 21°09' E., on line 2-3, Lot 1, identical with line
	1-7, Lot 2.
12.78	Point for Corner 7, Lot 2, identical with Corner 1, Lot
	3.
	Set an aluminum post, 28 ins. long, 1 in. diam., 19 ins.
	in the ground, in a mound of stone, 2½ ft. base, to top,
	with aluminum cap mkd.
	
	1981
	from which
	A nail in the S side of a ponderosa pine, 12 ins.
	diam., bears N. 35° E., 36.5 lks. dist.
	A nail in the N side of a ponderosa pine, 12 ins.
	diam., bears S. 69° E., 36.4 lks. dist.
	Continue along line 2-3, Lot 1, identical with line 1-5,
	Lot 3.
22.03	Corner 3, Lot 1, identical with Corner 5, Lot 3, at
	intersection with the E and W center line of the NE 1/4,
	sec. 15, heretofore described.

	S. 89°51' E., on line 3-4, Lot 1, identical with the E
	and W center line of the NE 1/4 of sec. 15.
7.725	Corner 4, Lot 1, identical with the N 1/16 sec. cor. of
	secs. 14 and 15, heretofore described.

	N. 1°26' W., on line 4-1, Lot 1, identical with the line
	bet. secs. 14 and 15.
20.61	Corner 1, Lot 1, identical with the cor. of secs. 10, 11,
	14, and 15, and point of beginning.

	<u>Lot 2</u>
	Beginning at Corner 1, Lot 2, identical with Corner 2,
	Lot 1, heretofore described.
	S. 89°47' W., on line 1-2, Lot 2, identical with the line
	bet. secs. 10 and 15.


Survey of Certain Small Lots in Section 15,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS										
24.36	<p>Corner 2, Lot 2, identical with Corner 1, Lot 4, on the center line of Turquoise Dr., heretofore described.</p> <p>S. 0°24' E., on line 2-3, Lot 2, identical with line 1-16, Lot 4, on the center line of Turquoise Dr.</p>									
.252	<p>Corner 3, Lot 2, identical with Corner 16, Lot 4, monumented with a brass tablet, 2½ ins. diam., set flush with pavement, mkd.</p> <p style="text-align: center;">63 .</p> <p>This monument represents a point of curvature as shown on plat No. 6152 by John D. Prewit, Reg. Civil Engineer No. 2649 AZ, on file with the City of Flagstaff, AZ.</p> <p>Remarked the tablet to read</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 10px;">Lot 4</td> <td style="border-left: 1px solid black; padding-left: 5px; padding-right: 5px;"> </td> <td style="padding-left: 10px;">Lot 2</td> </tr> <tr> <td style="padding-right: 10px;">16</td> <td style="border-left: 1px solid black; padding-left: 5px; padding-right: 5px;"> </td> <td style="padding-left: 10px;">3</td> </tr> <tr> <td colspan="3" style="text-align: center; padding-top: 5px;">1981</td> </tr> </table> <hr style="width: 20%; margin: 10px auto;"/> </div> <p>Thence, on line 3-4, Lot 2, identical with line 16-15, Lot 4, along the arc of a circular curve to the left, identical with the center line of Turquoise Dr., having a radius of 695.55 ft. the chord of said curve bears S. 14°32'39" E., 5.15 chs. dist.</p>	Lot 4		Lot 2	16		3	1981		
Lot 4		Lot 2								
16		3								
1981										
5.203	<p>Corner 4, Lot 2, identical with Corner 15, Lot 4, monumented with an unmkd. brass tablet, 2½ ins. diam., set flush with road in a concrete base, 8 ins. diam.</p> <p>This monument represents a point of curvature as shown on plat No. 6152 by John D. Prewit, Reg. Civil Engineer No. 2649 AZ, on file with the City of Flagstaff, AZ.</p> <p>Mkd. the tablet to read</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 10px;">Lot 4</td> <td style="border-left: 1px solid black; padding-left: 5px; padding-right: 5px;"> </td> <td style="padding-left: 10px;">Lot 2</td> </tr> <tr> <td style="padding-right: 10px;">15</td> <td style="border-left: 1px solid black; padding-left: 5px; padding-right: 5px;"> </td> <td style="padding-left: 10px;">4</td> </tr> <tr> <td colspan="3" style="text-align: center; padding-top: 5px;">1981</td> </tr> </table> <hr style="width: 20%; margin: 10px auto;"/> </div> <p>Thence, on line 4-5, Lot 2, identical with line 15-14, Lot 4, along the arc of a circular curve to the right, identical with the center line of Turquoise Dr., having a radius of 849.68 ft., the chord of said arc bears S. 14°44'03" E., 6.212 chs. dist.</p>	Lot 4		Lot 2	15		4	1981		
Lot 4		Lot 2								
15		4								
1981										
6.274	<p>Corner 5, Lot 2, identical with Corner 14, Lot 4, monumented with an unmkd. brass tablet, 2½ ins. diam., set flush with road in a concrete base, 8 ins. diam.</p> <p>This monument represents a point of curvature as shown on plat No. 6152 by John D. Prewit, Reg. Civil Engineer No. 2649 AZ., on file with the City of Flagstaff, Az.</p> <p>Mkd. the tablet to read</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 10px;">Lot 4</td> <td style="border-left: 1px solid black; padding-left: 5px; padding-right: 5px;"> </td> <td style="padding-left: 10px;">Lot 2</td> </tr> <tr> <td style="padding-right: 10px;">14</td> <td style="border-left: 1px solid black; padding-left: 5px; padding-right: 5px;"> </td> <td style="padding-left: 10px;">5</td> </tr> <tr> <td colspan="3" style="text-align: center; padding-top: 5px;">1981</td> </tr> </table> <hr style="width: 20%; margin: 10px auto;"/> </div>	Lot 4		Lot 2	14		5	1981		
Lot 4		Lot 2								
14		5								
1981										

Survey of Certain Small Lots in Section 15,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona


CHAINS	
<p>6.405</p>	<p>Thence on line 5-6, Lot 2, identical with line 14-13, Lot 4, along the arc of a circular curve to the left, identical with the center line of Turquoise Dr., having a radius of 1,198.25 ft., the chord of said arc bears S. 10°52'48" E., 6.372 chs. dist.</p> <p>Point for Corner 6, Lot 2, identical with Corner 2, Lot 3, and Corner 13, Lot 4.</p> <p>Set a railroad spike flush with surface of road, mkd.</p> <div data-bbox="617 693 925 927" style="text-align: center;"> <p>1981</p> </div> <p>Corner is located 7 lks. W of painted center line stripe of road.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 77°08' E., on line 6-7, Lot 2, identical with line 2-1, Lot 3.</p>
<p>25.52</p>	<p>Corner 7, Lot 2, identical with Corner 1, Lot 3, heretofore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 21°09' W., on line 7-1, Lot 2, identical with line 3-2, Lot 1.</p>
<p>12.78</p>	<p>Corner 1, Lot 2, identical with Corner 2, Lot 1, and point of beginning, heretofore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p style="text-align: center;"><u>Lot 3</u></p> <p>Beginning at Corner 1, Lot 3, identical with Corner 7, Lot 2, heretofore described.</p> <p>S. 77°08' W., on line 1-2, Lot 3, identical with line 7-6, Lot 2.</p>
<p>25.52</p>	<p>Corner 2, Lot 3, identical with Corner 6, Lot 2, and Corner 13, Lot 4, heretofore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence on line 2-3, Lot 3, identical with line 13-12, Lot 4, along the arc of a circular curve to the left, identical with the center line of Turquoise Dr., having a radius of 1,198.25 ft., the chord of said arc bears S. 22°43' E., 1.097 chs. dist.</p>
<p>1.097</p>	<p>Corner 3, Lot 3, identical with Corner 12, Lot 4, monumented with an unmkd. brass tablet, 2½ ins. diam., set flush with road in a concrete base, 8 ins. diam.</p> <p>This monument represents a point of curvature as shown on plat No. 6152 by John D. Prewit, Reg. Civil Engineer No. 2649 Az, on file with the City of Flagstaff, AZ.</p> <p>Mkd. the tablet to read</p>

Survey of Certain Small Lots in Section 15,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS		
	 <p>Lot 4 Lot 3 12 3 1981</p>	
	<p>Thence on line 3-4, Lot 3, identical with line 12-11, Lot 4, along the arc of a circular curve to the right, identical with the center line of Turquoise Dr., having a radius of 1,523.25 ft., the chord of said arc bears S. 21°57'21" E., 2.008 chs. dist.</p>	
2.009	<p>Corner 4, Lot 3, identical with Corner 11, Lot 4, at intersection with the E and W center line of the NE 1/4 of sec. 15, heretofore described.</p>	
	<p>S. 89°51' E., on line 4-5, Lot 3, identical with the E and W center line of the NE 1/4 of sec. 15.</p>	
27.035	<p>Corner 5, Lot 3, identical with Corner 3, Lot 1, heretofore described.</p>	
	<p>N. 21°09' W., on line 5-1, Lot 3, identical with line 3-2, Lot 1.</p>	
9.24	<p>Corner 1, Lot 3, identical with Corner 7, Lot 2, and point of beginning, heretofore described.</p>	
	<p><u>Lot 4</u></p>	
	<p>Beginning at Corner 1, Lot 4, identical with Corner 2, Lot 2, heretofore described.</p>	
	<p>S. 89°47' W., on line 1-2, Lot 4, identical with the line bet. secs. 10 and 15.</p>	
0.61	<p>Corner 2, Lot 4, identical with the 1/4 sec. cor. of secs. 10 and 15, heretofore described.</p>	
	<p>S. 89°50' W., on line 2-3, Lot 4, identical with the line bet. secs. 10 and 15.</p>	
10.86	<p>Center line of San Francisco St., asphalt surfaced, bears N. 20° E., curving N, and S. 20° W., curving S.</p>	
11.67	<p>Corner 3, Lot 4, identical with Corner 1, Lot 5, at intersection with the W right-of-way of San Francisco St., heretofore described.</p>	
	<p>Thence, on line 3-4, Lot 4, identical with line 1-13, Lot 5, along the arc of a circular curve to the left, identical with the W right-of-way of San Francisco St., having a radius of 796.21 ft., the chord of said arc bears S. 9°57'16" W., 4.382 chs. dist.</p>	
4.407	<p>Point for Corner 4, Lot 4, identical with Corner 13, Lot 5, and end of curve.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.</p>	

Survey of Certain Small Lots in Section 15,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS



from which

A railroad rail, serving as the corner of a chain link fence, 8 ft. high, bears N. 86° E., 19.7 lks. dist. Fence extends W and S.


A nail, in the W side of a ponderosa pine, 14 ins. diam., bears S. 8° W., 30.0 lks. dist.

A nail, in the N side of a ponderosa pine, 14 ins. diam., bears N. 86° W., 29.0 lks. dist.

S. 0°31' E., on line 4-5, Lot 4, identical with line 13-12, Lot 5, on the W right-of-way of San Francisco St.

9.30 Point for Corner 5, Lot 4, identical with Corner 12, Lot 5, and beginning of curve.

Set an aluminum post, 20 ins. long, 1 in. diam., 2 ins. into a drill hole in bedrock, 8 ins. below ground, secured with a concrete base and in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.



from which

A railroad rail serving as the corner of a chain link fence, 8 ft. high, bears S. 14° E., 69.5 lks. dist. Fence extends N and W.


A nail in S side of a ponderosa pine, 30 ins. diam., bears S. 86° W., 14.1 lks. dist.

Corner is located 20.5 lks. W of 8 ft. chain link fence, bears N and S.

Thence, on line 5-6, Lot 4, identical with line 12-11, Lot 5, along the arc of a circular curve to right, identical with the W right-of-way of San Francisco St., having a radius of 282.07 ft., the chord of said arc bears S. 23°03'35" W., 3.418 chs. dist.

3.516 Point for Corner 6, Lot 4, identical with Corner 11, Lot 5, and end of curve.

Set an aluminum post, 18 ins. long, 1 in. diam., 8 ins. in the ground, secured with a concrete base, and in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.



from which

Survey of Certain Small Lots in Section 15,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS


A nail in the W side of a ponderosa pine, 8 ins. diam., bears N. 67° E., 49.4 lks. dist.

A nail in the E side of a ponderosa pine, 6 ins. diam., bears N. 41° W., 44.7 lks. dist.

S. 46°38' W., on line 6-7, Lot 4, identical with line 11-10, Lot 5, on the W right-of-way of San Francisco St.

1.06 Point for Corner 7, Lot 4, identical with Corner 10, Lot 5, and beginning of curve.

Set an aluminum post, 22 ins. long, 1 in. diam., 2 ins. into a drill hole, in bedrock, 8 ins. below ground, secured in a concrete base and in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.



from which


A nail in the W side of a ponderosa pine, 8 ins. diam., bears S. 35° W., 53.9 lks. dist.

A nail in the S side of a ponderosa pine, 6 ins. diam., bears N. 52° W., 22.3 lks. dist.

Thence, on line 7-8, Lot 4, identical with line 10-9, Lot 5, along the arc of a circular curve to the left, identical with the W right-of-way of San Francisco St., having a radius of 451.23 ft., the chord of said arc bears S. 33°52'18" W., 3.019 chs. dist.

3.044 Point for Corner 8, Lot 4, identical with Corner 9, Lot 5, and end of curve.

Set an aluminum post, 20 ins. long, 1 in. diam., 8 ins. in the ground, secured with a concrete base and in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.



from which

A nail in the N side of a ponderosa pine, 10 ins. diam., bears N. 64° W., 8.4 lks. dist.

S. 21°07' W., on line 8-9, Lot 4, identical with line 9-8, Lot 5, on the W right-of-way of San Francisco St.

0.30 Corner 9, Lot 4, identical with Corner 8, Lot 5, at intersection with the E and W center line of the NW 1/4 of sec. 15, heretofore described.

S. 89°49' E., on line 9-10, Lot 4, identical with the E and W center line of the NW 1/4 of sec. 15.

Survey of Certain Small Lots in Section 15,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS 16.82	<p>Corner 10, Lot 4, identical with the center N 1/16 sec. cor. of sec. 15, heretofore described.</p> <hr/> <p>S. 89°51' E., on line 10-11, Lot 4, identical with the E and W center line of the NE 1/4 of sec. 15.</p>
5.295	<p>Corner 11, Lot 4, identical with Corner 4, Lot 3, on the center line of Turquoise Dr., heretofore described.</p> <hr/> <p>Thence, on line 11-12, Lot 4, identical with line 4-3, Lot 3, along the arc of a circular curve to the left, identical with the center line of Turquoise Dr., having a radius of 1,523.25 ft., the chord of said arc bears N. 21°57'21" W., 2.008 chs. dist.</p>
2.009	<p>Corner 12, Lot 4, identical with Corner 3, Lot 3, on the center line of Turquoise Dr., heretofore described.</p> <hr/> <p>Thence, on line 12-13, Lot 4, identical with line 3-2, Lot 3, along the arc of a circular curve to the right, identical with the center line of Turquoise Dr., having a radius of 1,198.25 ft., the chord of said arc bears N. 22°43' W., 1.097 chs. dist.</p> <p>Corner 13, Lot 4, identical with Corner 2, Lot 3, and Corner 6, Lot 2, on the center line of Turquoise Dr., heretofore described.</p> <hr/> <p>Thence, on line 13-14, Lot 4, identical with line 6-5, Lot 2, along the arc of a circular curve to the right, identical with the center line of Turquoise Dr., the chord of said arc bears N. 10°52'48" W., 6.372 chs. dist.</p>
6.405	<p>Corner 14, Lot 4, identical with Corner 5, Lot 2, on the center line of Turquoise Dr., heretofore described.</p> <hr/> <p>Thence, on line 14-15, Lot 4, identical with line 5-4, Lot 2, along the arc of a circular curve to the left, identical with the center line of Turquoise Dr., having a radius of 849.68 ft., the chord of said arc bears N. 14°44'03" W., 6.212 chs. dist.</p>
6.274	<p>Corner 15, Lot 4, identical with Corner 4, Lot 2, on the center line of Turquoise Dr., heretofore described.</p> <hr/> <p>Thence, on line 15-16, Lot 4, identical with line 4-3, Lot 2, along the arc of a circular curve to the right, identical with the center line of Turquoise Dr., having a radius of 695.55 ft., the chord of said arc bears N. 14°32'39" W., 5.15 chs. dist.</p>
5.203	<p>Corner 16, Lot 4, identical with Corner 3, Lot 2, on the center line of Turquoise Dr., heretofore described.</p> <hr/> <p>N. 0°24' W., on line 16-1, Lot 4, identical with line 3-2, Lot 2, on the center line of Turquoise Dr.</p>
0.252	<p>Corner 1, Lot 4, identical with Corner 2, Lot 2, on the center line of Turquoise Dr., heretofore described, and being the point of beginning.</p>

B00 K5 172

Survey of Certain Small Lots in Section 15,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS		
	<u>Lot 5</u>	
	From Corner 1, Lot 5, identical with Corner 3, Lot 4, on the section line bet. secs. 10 and 15, heretofore described.	
	S. 89°50' W., on line 1-2, Lot 5, identical with the line bet. secs. 10 and 15.	
8.43	Corner 2, Lot 5, identical with the W 1/16 sec. cor. of secs. 10 and 15, heretofore described.	

	S. 0°55' E., on line 2-3, Lot 5, identical with the N and S center line of the NW 1/4 of sec. 15.	
10.12	Corner 3, Lot 5, identical with the center N-NW 1/64 sec. cor. of sec. 15, heretofore described.	

	N. 89°58' W., on line 3-4, Lot 5, identical with the E and W center line of the NW 1/4 NW 1/4 of sec. 15.	
5.06	Point for Corner 4, Lot 5, identical with the center E-NW-NW 1/256 sec. cor. of sec. 15. Falls in center of asphalt surfaced driveway of the Flagstaff Hospital, bears N. 20° E. and S. 20° W.	
	Set a railroad spike, flush with surface of driveway, with top mkd.	
	C-E-NW-NW 1/256 1981	
	from which	
	A nail, set in NE corner of a native stone wall around main hospital entrance, bears S. 71° W., 35.4 lks. dist.	
	The marks B XO, at bottom of fire standard pipe outlet in E wall of main hospital building, bears N. 77° W., 57.2 lks. dist.	
	An aluminum cap, 1½ ins. diam., of unknown origin, set 2 ins. below asphalt surface, bears N. 88°56' W., 10.7 lks. dist. This position was not accepted as a careful and faithful determination of the position of the cor. and is not utilized in the course of this survey.	

	S. 0°44' E., on line 4-5, Lot 5, identical with the N and S center line of the SE 1/4 NW 1/4 NW 1/4 of sec. 15.	
7.58	Point for Corner 5, Lot 5, identical with the center S SE NW NW 1/1024 sec. cor. of sec. 15.	
	Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with aluminum cap mkd.	
	S15 1/1024 1981	
	from which	

Survey of Certain Small Lots in Section 15,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>A galvanized nail, in the E side of a pine, 24 ins. diam., bears N. 3° E., 69.2 lks. dist.</p> <p>The marks XBO on the SW face of a boulder, 7 x 5 x 2 ft. above ground, bears N. 84° E., 39.4 lks. dist.</p>	
	<p>S. 89°51' E., on line 5-6, Lot 5, identical with the E and W center line of the SE 1/4 SE 1/4 NW 1/4 NW 1/4 of sec. 15.</p>	
5.08	<p>Corner 6, Lot 5, identical with the center S-S-N-NW 1/1024 sec. cor. of sec. 15, heretofore described.</p>	
	<p>S. 0°55' E., on line 6-7, Lot 5, identical with the N and S center line of the NW 1/4 of sec. 15.</p>	
2.53	<p>Corner 7, Lot 5, identical with the NW 1/16 sec. cor. of sec. 15, heretofore described.</p>	
	<p>S. 89°49' E., on line 7-8, Lot 5, identical with the E and W center line of the NW 1/4 of sec. 15.</p>	
3.53	<p>Corner 8, Lot 5, identical with Corner 9, Lot 4, at intersection with the W right-of-way of San Francisco St., heretofore described.</p>	
	<p>N. 21°07' E., on line 8-9, Lot 5, identical with line 9-8, Lot 4, on the W right-of-way of San Francisco St., heretofore described.</p>	
0.30	<p>Corner 9, Lot 5, identical with Corner 8, Lot 4, on the W right-of-way of San Francisco St., heretofore described.</p>	
	<p>Thence, on line 9-10, Lot 5, identical with line 8-7, Lot 4, along the arc of a circular curve to the right, identical with the W right-of-way of San Francisco St., having a radius of 451.23 ft., the chord of said arc bears N. 33°52'18" E., 3.019 chs. dist.</p>	
3.044	<p>Corner 10, Lot 5, identical with Corner 7, Lot 4, heretofore described.</p>	
	<p>N. 46°38' E., on line 10-11, Lot 5, identical with line 7-6, Lot 4, on the W right-of-way of San Francisco St.</p>	
	<p>Corner 11, Lot 5, identical with Corner 6, Lot 4, heretofore described.</p>	
1.06	<p>Thence, on line 11-12, Lot 5, identical with line 6-5, Lot 4, along the arc of a circular curve to the left, identical with the W right-of-way of San Francisco St., having a radius of 282.07 ft., the chord of said arc bears N. 23°03'35" E., 3.418 chs. dist.</p>	

Survey of Certain Small Lots in Section 15,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS		
3.516	<p>Corner 12, Lot 5, identical with Corner 5, Lot 4, on the W right-of-way of San Francisco St., heretofore described.</p> <hr/> <p>N. 0°31' W., on line 12-13, Lot 5, identical with line 5-4, Lot 4, on the W right-of-way of San Francisco St.</p>	
9.30	<p>Corner 13, Lot 5, identical with Corner 4, Lot 4, heretofore described.</p> <hr/> <p>Thence, on line 13-1, Lot 5, identical with line 4-3, Lot 4, along the arc of a circular curve to the right, identical with the W right-of-way of San Francisco St., having a radius of 796.21 ft. the chord of said arc bears N. 9°57'16" E., 4.382 chs. dist.</p>	
4.407	<p>Corner 1, Lot 5, identical with Corner 3, Lot 4, at intersection with the section line between secs. 10 and 15, heretofore described, and being the place of beginning.</p> <hr/> <p style="text-align: center;">Subdivision of Section 16, T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 16 and 21.</p> <p>N. 1°40' W., on the N and S center line of sec. 16.</p>	
41.59	<p>The center 1/4 sec. cor. of sec. 16, identical with Corner 8, Lot 2, monumented with an open end pipe, 1 in. diam., of unknown origin, set flush with asphalt surface of Cherry St. This position is accepted as a careful and faithful determination of the position of the corner.</p> <p>from which</p> <p style="padding-left: 40px;">The SW corner of the house at 824 Cherry bears N. 5°29' E., 69.7 lks. dist. House is 40 x 28 ft., long side bears N. 21° E.</p> <p style="padding-left: 40px;">The SW corner of the garage of the house at 824 Cherry bears N. 2°28' E., 109.0 lks. dist. Garage is 22 x 11 ft., long side bears N. 2° E.</p> <p style="padding-left: 40px;">The top of a hydrant bears N. 36°03' W., 47.3 lks. dist.</p> <p>Cor. is located 14 lks. North of the center line of Cherry St., bears S. 65° E. and N. 65° W.</p> <p>Cor. not remonumented.</p> <hr/> <p>N. 1°40' W., beginning new measurement.</p>	
19.89	<p>Point for the center N 1/16 sec. cor. of sec. 16. Falls at a point occupied by a mobile home, 64 ft. x 12 ft., long side bears N. 60° W. Impractical to monument.</p>	
25.93	<p>Point for Corner 4, Lot 1, identical with Corner 1, Lot 2.</p>	

Subdivision of Section 16,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>Lot 1 4 1 Lot 2 1981</p> <p>S16</p> </div> <p>from which</p> <p>The mark X on the top of a concrete retaining wall bears N. 83° E., 29.2 lks. dist.</p> <p>A fence post bears N. 35° W., 1 lk. dist. Fence extends S. 69° W. only.</p> <p>Corner is located 30 ft. N. of the center of Thorpe Road, asphalt surfaced, bears N. 69° E. and S. 69° W.</p> <p>34.81 Point for the center N N N 1/256 sec. cor. of sec. 16, identical with Corner 1, Lot 1.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>S16 CNNN 1/256 1981</p> </div> <p>from which</p> <p>A ponderosa pine, 16 ins. diam., bears S. 58° E., 12.0 lks. dist., mkd. CNNN 1/256 S16 BT.</p> <p>A galvanized nail, in the E side of a ponderosa pine, 6 ins. diam., bears S. 56° W., 12.2 lks. dist.</p> <p>The cor. of fences, extending N and W, bears N. 78° E., 10.3 lks. dist.</p> <p>From this corner two local monuments, an open end pipe of unknown origin, 1 in. diam., projecting 2 ins. from ground, bears S. 20°33' E., 3.5 lks. dist., and a 5/8 in. diam. rebar, set by the City of Flagstaff as part of an administrative survey, bears S. 2°26' E., 3.5 lks. dist. Neither monument has been used for any survey of record, were not accepted as a careful and faithful determination of the position of the corner, and were not utilized in the course of this survey.</p> <p>39.78 The 1/4 sec. cor. of sec. 9 and 16.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 15 and 16.</p> <p>N. 89°53' W., on the E and W center line of sec. 16.</p> <p>38.97 The center 1/4 sec. cor. of sec. 16, identical with Corner 8, Lot 2.</p> <hr/> <p>N. 89°52' W., beginning new measurement.</p>
---------------	--

Subdivision of Section 16,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS

- 3.45 Center line of Thorpe Road, asphalt surfaced, bears S. 6° E. and N. 6° W.
- 3.91 Point for Corner 7, Lot 2, identical with Corner 9, Lot 3.
- Set an aluminum post, 28 ins. long, 1 in. diam., 25 ins. in the ground, in a mound of stone, 1½ ft. base, to top, with aluminum cap mkd.

$$\begin{array}{r} \text{Lot 3} \quad | \quad \text{Lot 2} \\ \hline 9 \quad | \quad 7 \\ \hline \text{S16} \\ 1981 \end{array}$$

from which

An X, chiseled on the top of a curb return, bears N. 75° E., 14.5 lks. dist.

The center of a galvanized steel lamp post bears S. 0°35' W., 95.9 lks. dist.

- 13.02 Point for Corner 8, Lot 3, identical with Corner 7, Lot 4.
- Set an aluminum post, 28 ins. long, 1 in. diam., flush with the surface of an abandoned cinder road, with aluminum cap mkd.

$$\begin{array}{r} \text{Lot 4} \quad | \quad \text{Lot 3} \\ \hline 7 \quad | \quad 8 \\ \hline \text{S16} \\ 1981 \end{array}$$

from which

A ponderosa pine, 8 ins. diam., bears S. 19°27' W., 98.2 lks. dist., mkd. X BT at the base.

A ponderosa pine, 12 ins. diam., bears N. 87°30' W., 68.5 lks. dist., mkd. LOT 4 COR 7 BT.

Corner is located in the center of an abandoned cinder road, bears S. 33° E. and N. 33° W.

- 20.68 The center W 1/16 sec. cor. of sec. 16, identical with Corner 6, Lot 4, monumented with a 5/8 in. diam. rebar, projecting 1 in. above a concrete base. This monument is shown on a 1972 plat by Lysons, Gomez and Associates of Flagstaff, Az., for Lowell Observatory, on file with Arizona Engineering Company, Flagstaff, Az. The monument is accepted as a careful and faithful determination of the position of the corner.

At the corner point

Set an aluminum cap, 1 1/4 ins. diam., on existing 5/8" rebar, mkd.

$$\begin{array}{r} \text{BLM} \\ \text{W 1/16} \\ \hline \text{C} \quad \text{C} \\ \hline \text{S16} \\ 1981 \end{array}$$

from which

Subdivision of Section 16,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS		
5.16	<p>A pine, 7 ins. diam., bears N. 38° E., 14.9 lks. dist., mkd. X BT at base.</p> <p>A pine, 10 ins. diam., bears S. 71° E., 12.2 lks. dist., mkd. CW 1/16 S16 BT.</p> <p>Corner is located at cor. of fences extending N and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°53' W., beginning new measurement.</p> <p>Ascending through scattering to dense oak and ponderosa pine.</p> <p>Point for the center EWW 1/256 sec. cor. of sec. 16.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, in a mound of stone, 2 ft. base, to top, with aluminum cap mkd.</p> <p style="text-align: center;">S16 C-E-W-W 1/256 1981</p> <p>from which</p> <p>A pine, 6 ins. diam., bears N. 64 1/4° E., 51.3 lks. dist., mkd. X BT at base.</p> <p>A pine, 14 ins. diam., bears S. 51° E., 75.4 lks. dist., mkd. C-E-W-W 1/256 S16 BT.</p> <p>Corner is located 73 lks. S of track road, bears S. 74° E., and N. 74° W.</p>	
20.65	<p>The 1/4 sec. cor. of secs. 16 and 17.</p> <hr/> <p>From the center W 1/16 sec. cor. of sec. 16, identical with Corner 6, Lot 4.</p> <p>N. 1°33' W., on the N and S center line of the NW 1/4 of sec. 16.</p> <p>On slight descent along fence, through oak and dense ponderosa pine.</p> <p>5.00 Fence turns to West.</p> <p>19.97 Point for the NW 1/16 sec. cor. of sec. 16, identical with Corner 5, Lot 4, at intersection with the E and W center line of the NW 1/4.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.</p> <p style="text-align: center;">NW 1/16 S16 1981</p> <p>from which</p> <p>A ponderosa pine, 14 ins. diam., bears N. 68° E., 24.0 lks. dist., mkd. NW 1/16 S16 BT.</p>	

Subdivision of Section 16,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>A ponderosa pine, 10 ins. diam., bears S. 35° E., 33.7 lks. dist., mkd. X BT at base.</p>
39.94	<p>The W 1/16 sec. cor. of secs. 9 and 16, identical with Corner 4, Lot 4.</p>
	<p>From the center N 1/16 sec. cor. of sec. 16. N. 89°41' W., on the E and W center line of the NW 1/4 of sec. 16.</p>
4.99	<p>Intersect line 2-3, Lot 2, identical with line 13-1, Lot 3, at point from which Corner 3, Lot 2, identical with Corner 13, Lot 3, bears S. 12°52' W., 1.92 chs. dist., hereinafter described.</p>
12.10	<p>Intersect line 5-6, Lot 3, identical with line 9-10, Lot 4, at a point from which Corner 5, Lot 3, identical with Corner 10, Lot 4, bears N. 15°51' E., 2.09 chs. dist., hereinafter described.</p>
20.64	<p>The NW 1/16 sec. cor. of sec. 16.</p>
41.26	<p>The N 1/16 sec. cor. of sec. 16 and 17.</p>
	<p>From the center N-N-N 1/256 sec. cor. of sec. 16, identical with Corner 1, Lot 1, heretofore described. N. 89°32' W., on the E and W center line of the NE 1/4 NE 1/4 NW 1/4 of sec. 16.</p>
0.69	<p>Center of B.I.A Dormitory access rd., cinder surfaced, bears N. 13° E., curving N, and S. 13° W.</p>
1.15	<p>Point for Corner 2, Lot 1, identical with Corner 1, Lot 3. Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.</p>
	$\begin{array}{r} \text{S16} \\ \hline 1/2 \\ \text{Lot 3} \quad / \quad \text{Lot 1} \\ 1981 \end{array}$ <p>Corner is located 6 lks. N. of a wire mesh fence extend- ing E and W.</p>
1.53	<p>Point for Corner 2, Lot 3, identical with Corner 1, Lot 4. Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.</p>
	$\begin{array}{r} \text{S16} \\ \hline 1/2 \\ \text{Lot 4} \quad / \quad \text{Lot 3} \\ 1981 \end{array}$ <p>from which</p>

Subdivision of Section 16,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS		
10.30	<p>A galvanized nail, in the S side of a ponderosa pine, 8 ins. diam., bears S. 80° E., 6.7 lks. dist.</p> <p>A galvanized nail, in the W side of a ponderosa pine, 16 ins. diam., bears S. 2° W., 28.2 lks. dist.</p> <p>Corner is located 6 lks. N. of a wire mesh fence extending E and W.</p> <p>Point for the center N-NE-NW 1/256 sec. cor. of sec. 16, identical with Corner 2, Lot 4.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, 3 ft. base, to top, with an aluminum cap mkd.</p> <p style="text-align: center;">S16 C-N-NE-NW 1/256 1981</p> <p>from which</p> <p>A ponderosa pine, 12 ins. diam., bears S. 40° E., 22.4 lks. dist., mkd. C-N-NE-NW 1/256 S16 BT.</p> <p>A galvanized nail in the W side of a ponderosa pine, 4 ins. diam., bears S. 4° W., 15.9 lks. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1°37' W., on the N and S center line of NE 1/4 NW 1/4 of sec. 16.</p>	
4.98	<p>The E-W 1/64 sec. cor. of secs. 9 and 16, identical with Corner 3, Lot 4, heretofore described.</p> <hr/> <p>From the center E-W-W 1/256 sec. cor. of sec. 16, heretofore described.</p> <p>N. 1°31' W., on the N and S center line of the E½ SW 1/4 NW 1/4 of sec. 16.</p>	
14.99	<p>Point for the NE-SW-NW 1/156 sec. cor. of sec. 16.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, 3 ft. base, to top, with an aluminum cap mkd.</p> <p style="text-align: center;">S16 NE-SW-NW 1/256 1981</p> <p>from which</p> <p>A ponderosa pine, 6 ins. diam., bears N. 46½° E., 15.0 lks. dist., mkd X BT.</p> <p>A ponderosa pine, 8 ins. diam., bears N. 7 1/4° W., 33.7 lks. dist., mkd. NE-SW-NW 1/256 S16 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°44' W., on the E and W center line of the N½ SW 1/4 NW 1/4 of sec. 16.</p>	

Subdivision of Section 16,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS	
15.47	The N-S-N 1/256 sec. cor. of secs. 16 and 17, heretofore described.
<hr/> Survey of Certain Small Lots in Section 16, T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona <hr/>	
<p><u>MEMORANDUM</u></p>	
<p>The bdys. of the lots in Sec. 16 were constructed at the direction of the U.S.F.S. The W bdy. of Lot 1 and Lot 2, identical with the E bdy. of Lot 3, is a line roughly conforming to an offset, 30 ft. westerly, and parallel with Thorpe Rd. and the B.I.A. Dormitory access rd. The S bdy. of Lot 1, identical with the N bdy. of Lot 2, is a line roughly conforming to an offset, 30 ft. northerly, and parallel with Thorpe Rd. The westerly bdy. of Lot 3, identical with a portion of the easterly bdy. of Lot 4, is a line roughly conforming to the City Park Loop Road path of travel (abandoned), so that the bdy. line remains within the constructed portion of the road.</p>	
<p><u>Lot 1</u></p>	
<p>Beginning at Corner 1, Lot 1, identical with the center N-N-N 1/256 sec. cor. of sec. 16, heretofore described.</p>	
<p>N. 89°32' W., on line 1-2, Lot 1, identical with the E and W center line of the NE 1/4 NE 1/4 NW 1/4 of sec. 16.</p>	
0.69	Center of B.I.A. Dormitory access rd., cinder surface, bears N. 13° E., curving N, and S. 13° W.
1.15	Corner 2, Lot 1, identical with Corner 1, Lot 3, heretofore described.
<hr/> <p>S. 12°52' W., on line 2-3, Lot 1, identical with a portion of line 1-13, Lot 3.</p>	
10.63	Point for Corner 3, Lot 1, identical with Corner 2, Lot 2.
<p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, 3 ft. base, to top, with an aluminum cap mkd.</p>	
<p>from which</p>	
<p style="padding-left: 40px;">A nail in the W side of a ponderosa pine, 18 ins. diam., bears S. 3° E., 5.9 lks. dist.</p>	
<p style="padding-left: 40px;">A nail in the S side of a ponderosa pine, 12 ins. diam., bears S. 62° W., 15.9 lks. dist.</p>	
<hr/> <p>N. 68°43' E., on line 3-4, Lot 1, identical with line 2-1, Lot 2.</p>	

Survey of Certain Small Lots in Section 16,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS	
0.40	Center of B.I.A. Dormitory access road, cinder surface, bears N. 13° E. and S. 13° W.
4.05	Corner 4, Lot 1, identical with Corner 1, Lot 2, at intersection with the N and S center line of sec. 16, heretofore described.
	<hr/> N. 1°40' W., on line 4-1, Lot 1, identical with the N and S center line of sec. 16.
8.88	Corner 1, Lot 1, identical with the center N-N-N 1/256 sec. cor. of sec. 16, heretofore described, and the point of beginning.
	<hr/> <p style="text-align: center;"><u>Lot 2</u></p> Beginning at Corner 1, Lot 2, identical with Corner 4, Lot 1, heretofore described. S. 68°43' W., on line 1-2, Lot 2, identical with line 4-3, Lot 1.
4.05	Corner 2, Lot 2, identical with Corner 3, Lot 1, and on line 13-1, Lot 3, heretofore described.
	<hr/> S. 12°52' W., on line 2-3, Lot 2, identical with a portion of line 1-13, Lot 3.
4.66	Intersect the E and W center line of the NW 1/4 of sec. 16. Point of intersection not monumented. Point for Corner 3, Lot 2, identical with Corner 13, Lot 3. Set an aluminum post, 28 ins. long, 1 in diam., flush with the surface of an asphalt sidewalk, with aluminum cap mkd. <div style="text-align: center; margin: 10px 0;"> $\begin{array}{r} 13 \\ \text{lot 3} \end{array} / \begin{array}{r} 3 \\ \text{Lot 2} \end{array}$ <p>1981</p> </div> from which <p style="margin-left: 40px;">A nail, in the NW side of a double trunk ponderosa pine, 28 ins. diam., bears S. 34°56' W., 38.4 lks. dist.</p> <p style="margin-left: 40px;">A nail, in the SW side of a ponderosa pine, 22 ins. diam., bears N. 40°05' W., 28.4 lks. dist.</p> Corner is located 10 lks. S of the center of a park access road, dirt surfaced, bears northwesterly.
	<hr/> Thence, on line 3-4, Lot 2, identical with line 13-12, Lot 3, along the arc of a circular curve to the left, having a radius of 800.00 ft., the chord of said arc bears S. 0°28' W., 5.21 lks dist.
5.251	Point for Corner 4, Lot 2, identical with Corner 12, Lot 3.

Survey of Certain Small Lots in Section 16,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

	CHAINS		
		<p>Set an aluminum post, 28 ins. long, 1 in. diam., flush with the surface of an asphalt sidewalk, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>Lot 3 Lot 2 12 4 1981</p> </div> <p>from which</p> <p>A nail, in the NW side of a ponderosa pine, 14 ins. diam., bears S. 28°36' W., 91.8 lks. dist.</p> <p>The center of a manhole cover, 2.35 ft. diam., bears N. 24°38' W., 152.8 lks. dist.</p> <hr/> <p>S. 11°56' E., on line 4-5, Lot 2, identical with line 12-11, Lot 3.</p>	
5.28		<p>Point for Corner 5, Lot 2, identical with Corner 11, Lot 3.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., flush with the surface of the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>Lot 3 Lot 2 11 5 1981</p> </div> <p>from which</p> <p>The top of a hydrant bears N. 53°21' E., 112.0 lks dist.</p> <p>A nail, in the N side of a ponderosa pine, 12 ins. diam., bears N. 79°48' W., 23.3 lks. dist.</p> <hr/> <p>Thence, on line 5-6, Lot 2, identical with line 11-10, Lot 3, along the arc of a circular curve to the right, having a radius of 2700.00 ft., the chord of said arc bears S. 9°02' E., 4.14 chs. dist.</p>	
4.143		<p>Point for Corner 6, Lot 2, identical with Corner 10, Lot 3.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., flush with the surface of the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>Lot 3 Lot 2 10 6 1981</p> </div> <p>from which</p> <p>A nail, in the N side of a ponderosa pine, 18 ins. diam., bears N. 81°47' W., 25.3 lks. dist.</p> <p>A nail, in the W side of a power pole, mkd. 290, bears N. 5°38' W., 95.3 lks. dist.</p> <hr/>	

Survey of Certain Small Lots in Section 16,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona


CHAINS	
	S. 6°08' E., on line 6-7, Lot 2, identical with line 10-9, Lot 3.
3.60	Corner 7, Lot 2, identical with Corner 9, Lot 3, heretofore described.
	S. 89°52' E., on line 7-8, Lot 2, identical with the E and W center line of sec. 16.
3.91	Corner 8, Lot 2, identical with the center 1/4 sec. cor. of sec. 16, heretofore described.
	N. 1°40' W., on line 8-1, Lot 2, identical with the N and S center line of sec. 16.
19.89	The center N 1/16 sec. cor. of sec. 16, heretofore described.
25.93	Corner 1, Lot 2, identical with Corner 4, Lot 1, heretofore described, and the point of beginning.
	<u>Lot 3</u>
	Beginning at Corner 1, Lot 3, identical with Corner 2, Lot 1, heretofore described.
	N. 89°32' W., on line 1-2, Lot 3, identical with the E and W center line of the NE 1/4 NE 1/4 NW 1/4 of sec. 16.
0.38	Corner 2, Lot 3, identical with Corner 1, Lot 4, heretofore described.
	S. 53°50' W., on line 2-3, Lot 3, identical with line 1-12, Lot 4.
5.00	Thence, along abandoned cinder surfaced road.
10.65	Point for Corner 3, Lot 3, identical with Corner 12, Lot 4.
	Set an aluminum post, 11 ins. long, 1 in. diam., flush with cinder road surface, with aluminum cap mkd.
	<p>Lot 4 Lot 3 12 3 1981</p>
	from which
	A ponderosa pine, 10 ins. diam., bears S. 32 1/4° E., 24.5 lks. dist., mkd. LOT 3 COR 3 BT.
	A ponderosa pine, 18 ins. diam., bears N. 77 1/4° W., 42.5 lks. dist., mkd. X BT at the base.
	Corner is located 5 lks. W of the center of the cinder surfaced road.
	S. 29°58' W., on line 3-4, Lot 3, identical with line 12-11, Lot 4.

Survey of Certain Small Lots in Section 16,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>Along abandoned cinder road.</p> <p>2.65 Point for Corner 4, Lot 3, identical with Corner 11, Lot 4.</p> <p>Set an aluminum post, 12 ins. long, 1 in. diam., flush with cinder road surface, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>Lot 4 / Lot 3</p> <p>11 / 4</p> <p>1981</p> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears S. 77° E., 45.2 lks. dist., mkd. LOT 3 COR 4 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears S 82° W., 67.3 lks. dist., mkd. X BT at the base.</p> <p>Corner is located 9 lks. W of the center of the cinder surfaced road.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 4°47' E., on line 4-5, Lot 3, identical with line 11-10, Lot 4.</p>	
	<p>Along abandoned cinder road.</p> <p>4.28 Point for Corner 5, Lot 3, identical with Corner 10, Lot 4.</p> <p>Set an aluminum post, 12 ins. long, 1 in. diam., flush with cinder road surface, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>Lot 4 / Lot 3</p> <p>10 / 5</p> <p>1981</p> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears S. 86° E., 52.3 lks. dist., mkd. LOT 3 COR 5 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N. 43° W., 81.8 lks. dist., mkd. X BT at the base.</p> <p>Corner is located in the center of the cinder road.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 15°51' W., on line 5-6, Lot 3, identical with line 10-9, Lot 4.</p>	
	<p>Along abandoned cinder road.</p> <p>2.09 Intersect the E and W center line of the NW 1/4 of sec. 16. Point of intersection not monumented.</p> <p>13.90 Point for Corner 6, Lot 3, identical with Corner 9, Lot 4.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., flush with cinder road surface, with aluminum cap mkd.</p>	

Survey of Certain Small Lots in Section 16,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS



from which

A ponderosa pine, 18 ins. diam., bears S. 86° E.,
44.0 lks. dist., mkd. LOT 3 COR 6 BT.

A ponderosa pine, 12 ins. diam., bears S. 74° W.,
45.0 lks. dist., mkd. X BT at the base.


Corner is located 7.5 lks. W of center of cinder road.

S. 4°57' E., on line 6-7, Lot 3, identical with line 9-8,
Lot 4.

Along abandoned cinder road.

4.78 Point for Corner 7, Lot 3, identical with Corner 8, Lot
4.

Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins.
in the ground, in a mound of stone, 4 ft. base to top,
with aluminum cap mkd.



from which

A pine, 18 ins. diam., bears S. 81½° E., 69.0 lks.
dist., mkd. LOT 3 COR 7 BT.

A pine, 10 ins. diam., bears S. 29¾° W., 71.5 lks.
dist., mkd. X BT at base.

Corner is located 16 lks. W of the center of an abandoned
cinder road.

S. 33°02' E., on line 7-8, Lot 3, identical with line
8-7, Lot 4.

Along abandoned cinder road.

4.55 Corner 8, Lot 3, identical with Corner 7, Lot 4, at
intersection with the E and W center line of sec. 16,
heretofore described.

S. 89°52' E., on line 8-9, Lot 3, identical with the E
and W center line of sec. 16.

9.11 Corner 9, Lot 3, identical with Corner 7, Lot 2, hereto-
fore described.

N. 6°08' W., on line 9-10, Lot 3, identical with line
7-6, Lot 2.

Survey of Certain Small Lots in Section 16,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS	
3.60	Corner 10, Lot 3, identical with Corner 6, Lot 2, heretofore described.
	<hr/> Thence, on line 10-11, Lot 3, identical with line 6-5, Lot 2, along the arc of a circular curve to the left, having a radius of 2700.00 ft., the chord of said arc bears N. 9°02' W., 4.14 chs. dist.
4.143	Corner 11, Lot 3, identical with Corner 5, Lot 2, heretofore described.
	<hr/> N. 11°56' W., on line 11-12, Lot 3, identical with line 5-4, Lot 2.
5.28	Corner 12, Lot 3, identical with corner 4, Lot 2, heretofore described.
	<hr/> Thence, on line 12-13, Lot 3, identical with line 4-3, Lot 2, along the arc of a circular curve to the right, having a radius of 800.00 ft., the chord of said arc bears N. 0°28' E., 5.21 chs. dist.
5.251	Corner 13, Lot 3, identical with Corner 3, Lot 2, heretofore described.
	<hr/> N. 12°52' E., on line 13-1, Lot 3, identical with line 3-2, Lot 2.
1.92	Intersect the E and W center line of the NW 1/4 of sec. 16, heretofore described.
6.58	Corner 2, Lot 2, identical with Corner 3, Lot 1, heretofore described.
	Thence, continue along line 13-1, Lot 3, identical with line 3-2, Lot 1.
17.21	Corner 1, Lot 3, identical with Corner 2, Lot 1, heretofore described, and being the point of beginning.
	<hr/> <p style="text-align: center;"><u>Lot 4</u></p>
	Beginning at Corner 1, Lot 4, identical with Corner 2, Lot 3, heretofore described.
	N. 89°32' W., on line 1-2, Lot 4, identical with the E and W center line of the NE 1/4 NE 1/4 NW 1/4 of sec. 16.
8.77	Corner 2, Lot 4, identical with the center N-NE-NW 1/256 sec. cor. of sec. 16, heretofore described.
	<hr/> N. 1°37' W., on line 2-3, Lot 4, identical with the N and S center line of the NE 1/4 NW 1/4 of sec. 16.
4.98	Corner 3, Lot 4, identical with the E-W 1/64 sec. cor. of secs. 9 and 16, heretofore described.
	<hr/> N. 89°29' W., on line 3-4, Lot 4, identical with the section line between secs. 9 and 16.

Survey of Certain Small Lots in Section 16,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

CHAINS	
10.295	Corner 4, Lot 4, identical with the W 1/16 sec. cor. of secs 9 and 16, heretofore described. <hr/>
	S. 1°33' E., on line 4-5, Lot 4, identical with the N and S center line of the NW 1/4 of sec. 16.
19.97	Corner 5, Lot 4, identical with the NW 1/16 sec. cor. of sec. 16, heretofore described. <hr/>
	S. 1°33' E., on line 5-6, Lot 4, identical with the N and S center line of the NW 1/4 of sec. 16.
19.97	Corner 6, Lot 4, identical with the center W 1/16 sec. cor. of sec. 16, heretofore described. <hr/>
	S. 89°52' E., on line 6-7, Lot 4, identical with the E and W center line of sec. 16.
7.66	Corner 7, Lot 4, identical with Corner 8, Lot 3, heretofore described. <hr/>
	N. 33°02' W., on line 7-8, Lot 4, identical with line 8-7, Lot 3.
	Along abandoned cinder road.
4.55	Corner 8, Lot 4, identical with Corner 7, Lot 3, heretofore described. <hr/>
	N. 4°57' W., on line 8-9, Lot 4, identical with line 7-6, Lot 3.
	Along abandoned cinder road.
4.78	Corner 9, Lot 4, identical with Corner 6, Lot 3, heretofore described. <hr/>
	N. 15°51' E., on line 9-10, Lot 4, identical with line 6-5, Lot 3.
	Along abandoned cinder road.
11.81	Intersect the E and W center line of the NW 1/4 of sec. 16, heretofore described.
13.90	Corner 10, Lot 4, identical with Corner 5, Lot 3, heretofore described. <hr/>
	N. 4°47' W., on line 10-11, Lot 4, identical with line 5-4, Lot 3.
	Along abandoned cinder road.
4.28	Corner 11, Lot 4, identical with Corner 4, Lot 3, heretofore described. <hr/>

Survey of Certain Small Lots in Section 16,
T. 21 N., R. 7 E., Gila and Salt River Mer., Arizona

	CHAINS		
		<p>N. 29°58' E., on line 11-12, Lot 4, identical with line 4-3, Lot 3.</p> <p>Along abandoned cinder road.</p>	
	2.56	<p>Corner 12, Lot 4, identical with Corner 3, Lot 3, heretofore described.</p> <hr/> <p>N. 53°50' E., on line 12-1, Lot 4, identical with line 3-2, Lot 3.</p> <p>Along abandoned cinder road.</p>	
	10.65	<p>Corner 1, Lot 4, identical with Corner 2, Lot 3, heretofore described, and being the point of beginning.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The land encompassed in this survey is located within the city limits of Flagstaff and is almost entirely developed for commercial, residential and recreational use. The elevation ranges between 6900 to 7200 ft. above sea level.</p> <p>The soil in the undeveloped areas is not suitable for cultivation. The woodlands contain varying densities of ponderosa pine, juniper and oak.</p>	

CHAINS

CERTIFICATE OF SURVEY

(I) ~~(ME)~~, John P. Bennett, Supervisory Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 4th day of September, 1981, (I) ~~(ME)~~ have dependently resurveyed a portion of the subdivisional lines and surveyed the subdivision and a metes-and-bounds survey of certain small lots in sections 15 and 16, Township 21 North, Range 7 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(US)~~ and under (my) ~~(MY)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

August 2, 1982 (Date) [Signature] Supervisory (Cadastral Surveyor) (Date) (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT ~~Denver, Colorado~~ Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines, the survey of the subdivision and a metes-and-bounds survey of certain small lots in sections 15 and 16, Township 21 North, Range 7 East, Gila and Salt River Meridian, Arizona

executed by John P. Bennett, Supervisory Cadastral Surveyor having been critically examined and found correct, are hereby approved.

August 2, 1982 (Date) [Signature] Chief Cadastral Surveyor of Arizona

~~CERTIFICATE OF TRANSCRIPT I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes. (Date) (Chief, Cadastral Survey Examination and Approval Staff)~~