

Form 9600-9
(December 1979)
(formerly 9180-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

_____ OF THE _____
DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
_____ A PORTION OF THE SUBDIVISIONAL LINES _____
AND _____
A METES-AND-BOUNDS SURVEY _____
IN SECTIONS 21, 22, 27, 28, 33 AND 34 _____
TOWNSHIP 3 NORTH, RANGE 22 WEST _____

Of the GILA AND SALT RIVER _____ Meridian,
In the State of ARIZONA _____

EXECUTED BY

PAUL L. REEVES, CADASTRAL SURVEYOR

Under special instructions dated NOVEMBER 12, 19 80, approved NOVEMBER 14, 1980,
AND SUPPLEMENTAL SPECIAL INSTRUCTIONS DATED DECEMBER 12, 1981, APPROVED
DECEMBER 12, 1980, which provided for the surveys included under U.S. Survey/Group
Number 621, and assignment instructions dated DECEMBER 12, 1980.

Survey commenced DECEMBER 16, 19 80

Survey completed JANUARY 22, 19 81

INDEX DIAGRAM

Township 3 NORTH, Range 22 WEST

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
		11			
19	20	21	11 22 6	23	24
		10	10		
30	29	28	9 27 5	26	25
		7	7 6		
31	32	33	8 5	35	36
			34 4		
			4 3		

Metes-and-Bounds Survey

- Sec. 22 pp. 12-17
- Sec. 34 pp. 17-18
- Sec. 21 pp. 18-20
- Sec. 28 pp. 20-23
- Sec. 33 pp. 23

Informative Traverse of Road--- pp. 23-24

T. 3 N., R. 22 W., Gila and Salt River Mer., Arizona

CHAINS

The boundaries, subdivisional lines and meander lines were surveyed by William B. Kimmell in 1916 and 1917. A portion of the south boundary and subdivisional lines were resurveyed and accretion lands were surveyed by William W. Glenn, Floyd H. Brooks and Leonard W. Murphy, in 1961. Certain corners were remonumented by Paul G. Bauer in 1965. The boundaries and subdivision of section 15 were concurrently surveyed under this same group by Harry K. Smith and Paul L. Reeves.

The following field notes are those of a dependent re-survey of a portion of the south boundary, a portion of the subdivisional lines and a metes-and-bounds survey in sections 21, 22, 27, 28, 33 and 34, of Township 3 North, Range 22 West, Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 621, Arizona, dated November 12, 1980, and Supplemental Special Instructions dated December 12, 1980.

The directions of lines were determined from U.S.G.S. triangulation station "EHRENBERG", and refer to the true meridian. Distances were measured with a Hewlett-Packard 3820A Total Station.

Preliminary to the resurvey the lines of the previous surveys were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southeast corner of section 34, as determined from a tie to U.S.G.S. triangulation station "EHRENBERG", located in sec. 13, T 3 N, R 21 W, is as follows:

Latitude: 33°33'04.908" N Longitude: 114°30'36.284" W

The mean magnetic declination is 14°30' E.

Dependent Resurvey of a Portion of the South Boundary,
T. 3 N., R. 22 W., Gila and Salt River Mer., Arizona

(Restoring the 1961 dependent resurvey and accretion survey by Floyd A. Brooks, William W. Glenn and Leonard W. Murphy)

Beginning at the cor. of secs. 2, 3, 34 and 35, monumented with an iron post, 3 ins. diam., projecting 10 ins. above ground, with brass cap mkd.

T3N R22W	
S34	S35
S 3	S 2
T2N	
1916	

Mound of stone, 2½ ft. base, 1 ft. high, is W of cor.

Dependent Resurvey of a Portion of the South Boundary,
T. 3 N., R. 22 W., Gila and Salt River Mer., Arizona

CHAINS		
	<p>From this point, U.S.G.S. triangulation station "EHRENBERG," bears N 18°02'05" E, 301.24 chs. dist., monumented with a brass tablet 3 ins. diam., seated in a rock 20 x 16 x 3 ins. above ground, mkd. EHRENBURG BM. The geographic position as established by U.S.G.S. is:</p> <p>Latitude: 33°36'11.94195" N Longitude: 114°29'23.53516" W</p> <p>N. 89°57' W., bet. secs. 3 and 34.</p> <p>Over rolling land, through scattered creosote and cacti.</p>	
39.99	<p>The 1/4 sec. cor. of secs. 3 and 34, monumented with an iron post, 1 in. diam., projecting 6 ins. above ground, with brass cap mkd.</p> $\frac{1}{4} \frac{S34}{S3}$ <p>1916</p> <p>Mound of stone, 2½ ft. base, 1½ ft. high, N of cor.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89°57' W., beginning new measurement.</p>	
20.27	<p>Point for the 1916 witness point of secs. 3 and 34, at record dist.; there is no remaining evidence of the original cor., not remonumented.</p>	
23.17	<p>Point for the 1961 meander cor. of secs. 3 and 34, on the left bank of the Colorado River, at record dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> $\begin{array}{c} T3N R22W \\ MC \frac{S34}{S3} \\ T2N \\ 1981 \end{array}$ <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <hr/> <p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 3 N., R. 22 W., Gila & Salt River Mer., Ariz.</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S bdy. of the Tp.</p> <p>North, bet. secs. 34 and 35.</p> <p>Over rolling land, through scattered creosote, palo verde and iron wood.</p>	
39.97	<p>The 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 1 in. diam., projecting 8 ins. above ground, with brass cap mkd.</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 3 N., R. 22 W., Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">1/4 S34 S35 1916</p> <p>from which the original bearing tree</p> <p style="text-align: center;">An ironwood, 16 ins. diam., bears N. 13½° W., 189 lks. dist., illegible scribe marks.</p> <p>Mound of stone, 2½ ft. base, 1½ ft. high, W of cor.</p> <hr style="width: 20%; margin: auto;"/> <p>North, beginning new measurement.</p>	
39.98	<p>The cor. of secs. 26, 27, 34 and 35, monumented with an iron post, 2 ins. diam., projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T3N R22W S27 S26 S34 S35 1916</p> <p>Mound of stone, 2½ ft. base, 1 ft. high, W of cor.</p> <hr/>	
	<p>N. 0°01' E., bet. secs. 26 and 27.</p> <p>Over rolling land, through medium creosote.</p>	
39.97	<p>The 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 2½ ins. diam., projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T3N R22W 1/4 S27 S26 1961</p> <p>from which the original bearing tree</p> <p style="text-align: center;">An ironwood, 10 ins. diam., bears N. 17° E., 208 lks. dist., mkd. 1/4 S26 BT.</p> <p>Mound of stone, 2½ ft. base, 1½ ft. high, W of cor.</p> <hr style="width: 20%; margin: auto;"/> <p>North, beginning new measurement.</p>	
39.98	<p>The cor. of secs. 22, 23, 26 and 27, determined from the original bearing tree</p> <p style="text-align: center;">An ironwood, 16 ins. diam., bears N. 2° W., 61 lks. dist., with scribe marks visible through a partly healed blaze.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T3N R22W S22 S23 S27 S26 1980</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 3 N., R. 22 W., Gila and Salt River Mer., Arizona

CHAINS	
39.97	<p>Cor. is located in a wash, 140 lks. wide, 3 ft. deep, drains northerly.</p> <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 53° W., 88.8 lks. dist., with brass cap mkd. T3N R22W S27 RM 58.6 FT. 1980 and an arrow pointing to the cor.</p> <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the RM.</p> <hr/> <p>North, bet. secs. 22 and 23.</p> <p>Over broken land, through medium creosote.</p> <p>The 1/4 sec. cor. of secs. 22 and 23, monumented with an iron post, 1 in. diam., projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 S22 S23 1916</p> <p>Mound of stone, 2½ ft. base, 1 ft. high, is W of cor.</p> <hr/> <p>N. 0°01' E., beginning new measurement.</p> <p>The cor. of secs. 14, 15, 22 and 23, monumented with an iron post, 2 ins. diam., projecting 9 ins. above ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T3N R22W S15 S14 S22 S23 1916</p>
29.11	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>West, bet. secs. 27 and 34.</p> <p>Point for Angle Point No. 6, sec. 27, identical with Angle Point No. 1, sec. 34.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T3N R22W S27 AP6 → AP1 S34 1981</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 3 N., R. 22 W., Gila & Salt River Mer., Arizona

CHAINS						
	<p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <p>40.02 The 1/4 sec. cor. of secs. 27 and 34, monumented with an iron post, 2½ ins. diam., projecting 4 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> $\frac{1}{4} \begin{array}{l} S27 \\ S34 \end{array}$ <p>T3N R22W 1961</p> </div> <p>A 4 x 4 in. wooden post, projecting 4 ft. above ground, is alongside the cor.</p> <p>Cor. is located 12 lks. E of a fence cor., fences extend N and W.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89°59' W., beginning new measurement.</p>					
	<p>40.02 The cor. of secs. 27, 28, 33 and 34, monumented with an iron post, 2½ ins. diam., 16 ins. below surface of the center of a N and S graded gravel road, 42 lks. wide, with brass cap mkd.</p> <div style="text-align: center;"> <p>T3N R22W</p> <table border="1" style="margin: auto;"> <tr> <td style="padding: 2px;">S28</td> <td style="padding: 2px;">S27</td> </tr> <tr> <td style="padding: 2px;">S33</td> <td style="padding: 2px;">S34</td> </tr> </table> <p>1961</p> </div> <p>from which</p> <p style="padding-left: 40px;">An iron post, 2½ ins. diam., flush with surface of ground, bears S. 45° W., 58 lks. dist., with brass cap mkd. T3N R22W S33 RM 38 FT. 1961 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the RM which is located in an abandoned N and S fence line.</p> <p style="padding-left: 40px;">An iron post, 2½ ins. diam., projecting 3 ins. above ground, bears N. 45° W., 58 lks. dist., with brass cap mkd. T3N R22W S28 RM 38 FT. 1961 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the RM which is located in an abandoned N and S fence line.</p>	S28	S27	S33	S34	
S28	S27					
S33	S34					
	<p>S. 89°59' W., bet. secs. 28 and 33.</p> <p>Through dense salt cedar.</p> <p>2.605 Point for Angle Point No. 11, sec. 28, identical with Angle Point No. 1, sec. 33.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>					

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 3 N., R. 22 W., Gila & Salt River Mer., Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T3N R22W S28 AP11 AP1 S33 1981</p> </div> <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <p>3.43 The meander cor. of secs. 28 and 33, monumented with an iron post, 2½ ins. diam., projecting 6 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T3N R22W MC S28 S33 1961</p> </div> <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p>
	<p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>South, bet. secs. 33 and 34.</p> <p>Along center of graded gravel road.</p> <p>3.49 Point for Angle Point No. 2, sec. 33, identical with Angle Point No. 5, sec. 34.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. below surface of a N and S graded gravel road, with brass cap mkd.</p> <div style="text-align: center;"> <p>T3N R22W AP2 S34 S33 AP5 1981</p> </div> <p>Cor. is located in the center of a N and S graded road, 24 lks. wide, extending S from the main graded gravel road. The cor. is 18 lks. W of a curve in the main road, 35 lks. wide, extending N and S. 25° E.</p> <p>4.40 Point for the meander cor. of secs. 33 and 34, at record dist., there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T3N R22W S33 S34 MC 1981</p> </div>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 3 N., R. 22 W., Gila & Salt River Mer., Arizona

CHAINS		
	<p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <p>Cor. is located 13 lks. E of a N and S graded road, 24 lks. wide.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 0°01' W., bet. secs. 27 and 28.</p> <p>Along a graded gravel road.</p> <p>40.01 The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 2½ ins. diam., 26 ins. below surface of a road, with brass cap mkd.</p> <p style="text-align: center;">1/4 S28 S27 T3N R22W 1961</p> <p>Cor. is located 12 lks. E of center of a N and S graded gravel road, 35 lks. wide.</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 2½ ins. diam., projecting 2 ins. above ground, bears N. 45° W., 50 lks. dist., with brass cap mkd. T3N R22W S28 RM 33 FT. 1961 and an arrow pointing to the cor. (Record: N. 50° W.)</p> <p style="padding-left: 40px;">RM is located 3 lks. E of a N and S fence line.</p> <p style="padding-left: 40px;">Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the RM.</p> <p>The point for the SW RM is in the center of a road extending W from main N and S road. The monument has been removed.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°05' E., beginning new measurement.</p>	
39.96	<p>Point for the cor. of secs. 21, 22, 27 and 28, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T3N R22W S21 S22 S28 S27 1981</p> <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <p>Cor. is located 2 lks. off the E edge of a N and S graded gravel road, 22 lks. E of the center. The road is 40 lks. wide.</p> <hr/>	

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 3 N., R. 22 W., Gila & Salt River Mer., Arizona

CHAINS		
40.01	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 89°58' W. bet. secs. 22 and 27.</p> <p>Over nearly level land, through medium creosote.</p> <p>The 1/4 sec. cor. of secs. 22 and 27, monumented with an iron post, 2½ ins. diam., 34 ins. below surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T3N R22W $\frac{1}{4}$ $\frac{S22}{S27}$ 1961</p> <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <p>This cor. now functions as Angle Point No. 12, sec. 22, identical with Angle Point No. 1, sec. 27.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°58' W., beginning new measurement.</p> <p>Through dense salt cedar.</p>	
40.01	<p>The cor. of secs. 21, 22, 27 and 28.</p> <hr style="width: 100%;"/> <p>S. 89°59' W., bet. secs. 21 and 28.</p> <p>Over level land, through dense salt cedar and weeds.</p> <p>25.85 An abandoned dirt canal, 10 lks. wide, 3 ft. deep, bears N and S.</p> <p>29.17 Point for Angle Point No. 9, sec. 21, identical with Angle Point No. 1, sec. 28.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T3N R22W S21 $\frac{AP9}{API}$ S28 1981</p> <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p>	
30.07	<p>The witness 1/4 sec. cor. of secs. 21 and 28, monumented with an iron post, 2½ ins. diam., projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T3N R22W WC 1/4 $\leftarrow \frac{S21}{S28}$ 1961</p>	




Dependent Resurvey of a Portion of the Subdivisional Lines, T. 3 N., R. 22 W., Gila & Salt River Mer., Arizona

CHAINS		
	<p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N. 0°01' W., bet. secs. 21 and 22.</p> <p>Along E edge of a graded gravel road.</p>	
17.85	Center of same graded gravel road, 43 lks. wide, in a curve, bears northeasterly and S.	
19.50	Fence line, bears E and W, thence over cultivated land, along a track road.	
39.95	<p>The 1/4 sec. cor. of secs. 21 and 22, monumented with an iron post, 2½ ins. diam., 3 ins. below surface of ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 S21 S22 T3N R22W 1961</p> <p>The remains of a 4 x 4 in. wooden post, alongside the cor., under the ground.</p> <p>Cor. is located 15 lks. N of the center of track road intersections, extending N, E, S and W.</p> <hr/> <p>N. 0°01' E., beginning new measurement.</p>	
39.94	<p>The cor. of secs. 15, 16, 21 and 22, monumented with an iron post, 2 ins. diam., 15 ins. below surface of a road, with brass cap mkd.</p> <p style="text-align: center;">T3N R22W S16 S15 S21 S22 1917</p> <p>This cor. was not found in the 1961 dependent resurvey. At that time a new monument was set which has since been removed by road work.</p> <p>The remains of a 4 x 4 in. wooden post was below the ground alongside the cor.</p> <p>From the cor., a local cor., a 1 in. iron pipe with a nail in top, flush with surface of road, bears N. 69°25' W., 4 lks. dist. (1961 Record S. 85°22' W., 3.7 lks. dist.)</p> <p>Cor. is located 15 lks. N of center of an E and W graded gravel road, 32 lks. wide, and 14 lks. S of an E and W fence line.</p> <hr/> <p>West, on record bearing bet. secs. 16 and 21.</p> <p>Along the N edge of a graded gravel road, 32 lks. wide.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 3 N., R. 22 W., Gila & Salt River Mer., Arizona

<p>CHAINS 14.80</p>	<p>Point for the 1961 meander cor. of secs. 16 and 21, at record dist.; there is no remaining evidence of the cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. below N edge of road, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T3N R22W MC \ S16 S21 1981</p> </div> <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, N of cor.</p> <p>Cor. is located 18 lks. N of the center of an E and W graded gravel road, 32 lks. wide, and 6 lks. S of an E and W fence line.</p>
<p>32.71</p>	<p>Point for Angle Point No. 1, sec. 21.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T3N R22W S16 — AP1 S21 1981</p> </div> <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <p>Cor. is located on the W bank of a canal, 18 lks. W of the center, and 28 lks. N of the center of a graded gravel road, 22 lks. wide, bears E and S. 80° W.</p>
<p>34.50</p>	<p>Point for the witness 1/4 sec. cor. of secs. 16 and 21, at record dist., there is no remaining evidence of the 1961 witness cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>W C T3N R22W 1/4 ← S16 S21 1981</p> </div> <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <p>Cor. is located 36 lks. N of the center of a graded gravel road, bears S. 80° E., curving E and N. 80° W.</p> <p>The lines surveyed in 1961 bet. secs. 16 and 21 and 17 and 20 were fully retraced, and no evidence of the cors. was found.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p style="text-align: center;">Metes-and-Bounds Survey in Section 22, T. 3 N., R. 22 W., Gila and Salt River Mer., Arizona</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/>

Metes-and-Bounds Survey, Section 22,
T. 3 N., R. 22 W., Gila and Salt River Mer., Arizona

CHAINS		
	<p>From Angle Point No. 1, sec. 22, identical with Angle Point No. 4, sec. 15, as described in the field notes of the concurrent survey of sec. 15, T. 3 N., R. 22 W., which is located N. 89°58' E., 8.275 chs. from the cor. of secs. 15, 16, 21 and 22, heretofore described.</p> <p>Thence in sec. 22.</p> <p>S. 4°27' E., on line 1-2, sec. 22.</p>	
4.24	<p>Point for Angle Point No. 2, sec. 22.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T3N R22W</p>  <p>AP2 S22</p> <p>1981</p> </div> <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <p>Cor. is located in a fence line, 23 lks. W of center of a graded gravel road, 37 lks. wide.</p> <div style="text-align: center;"> <hr style="width: 20%; margin: 0 auto;"/> </div> <p>S. 16°53'30" E., on line 2-3, sec. 22.</p>	
6.74	<p>Point for Angle Point No. 3, sec. 22.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T3N R22W</p>  <p>AP3 S22</p> <p>1981</p> </div> <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <p>Cor. is located in a fence line, 21 lks. W of center of a graded gravel road, 33 lks. wide.</p> <div style="text-align: center;"> <hr style="width: 20%; margin: 0 auto;"/> </div> <p>S. 24°34' E., on line 3-4, sec. 22.</p>	
6.54	<p>Point for Angle Point No. 4, sec. 22.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T3N R22W</p>  <p>AP4 S22</p> <p>1981</p> </div> <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p>	

Metes-and-Bounds Survey in Section 22,
T. 3 N., R. 22 W., Gila and Salt River Mer., Arizona

CHAINS		
	<p>Cor. is located in a fence line, 20 lks. W of center of a graded gravel road, 36 lks. wide.</p>	
	<p>S. 32°36' E., on line 4-5, sec. 22.</p>	
7.98	<p>Point for Angle Point No. 5, sec. 22.</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T3N R22W AP5 \ S22 1981</p>	
	<p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p>	
	<p>Cor. is located in a fence line, 24 lks. W of center of a graded gravel road, 33 lks. wide.</p>	
	<p>S. 45°27' E., on line 5-6, sec. 22.</p>	
12.09	<p>Point for Angle Point No. 6, sec. 22.</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T3N R22W AP6 \ S22 1981</p>	
	<p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p>	
	<p>Cor. is located 3 lks. W of a fence line and 28 lks. W of center of a graded gravel road, 38 lks. wide.</p>	
	<p>S. 39°09' E., on line 6-7, sec. 22.</p>	
4.225	<p>Point for Angle Point No. 7, sec. 22.</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T3N R22W AP7 \ S22 1981</p>	
	<p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p>	
	<p>Cor. is located 1 lk. W of a fence line and 24 lks. W of the center of a graded gravel road, 37 lks. wide.</p>	

Metes-and-Bounds Survey in Section 22,
T. 3 N., R. 22 W., Gila and Salt River Mer., Arizona

CHAINS		
	<p>S. 23°41' E., on line 7-8, sec. 22.</p> <p>5.08 Point for Angle Point No. 8, sec. 22.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T3N R22W AP8 \ S22 1981</p> <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <p>Cor. is located in a fence line, 33 lks. W of the center of a graded gravel road, 37 lks. wide.</p>	
	<p>S. 16°49' E., on line 8-9, sec. 22.</p> <p>5.29 Point for Angle Point No. 9, sec. 22.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T3N R22W AP9 \ S22 1981</p> <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <p>Cor. is located 1 lk. W of a fence line, and 24 lks. W of center of a graded gravel road, 39 lks. wide.</p>	
	<p>S. 7°40' E., on line 9-10, sec. 22.</p> <p>8.37 Point for Angle Point No. 10, sec. 22.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T3N R22W AP10 \ S22 1981</p> <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <p>Cor. is located 1 lk. W of a fence line, and 26 lks. W of center of a graded gravel road, 40 lks. wide.</p>	
	<p>S. 23°23' E., on line 10-11, sec. 22.</p> <p>.75 Center of graded gravel road, 40 lks. wide.</p>	

Metes-and-Bounds Survey in Section 22,
T. 3 N., R. 22 W., Gila and Salt River Mer., Arizona

CHAINS		
19.655	<p>Point for Angle Point No. 11, sec. 22.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T3N R22W AP11 } S22 1981</p> </div> <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 8°51' W., on line 11-12, sec. 22.</p>	
8.85	<p>The 1/4 sec. cor. of secs. 22 and 27. This point now also functions as Angle Point No. 12, sec. 22, identical with Angle Point No. 1, sec. 27, heretofore described.</p> <hr/> <p style="text-align: center;">Metes-and-Bounds Survey in Section 27, T. 3 N., R. 22 W., Gila and Salt River Mer., Arizona</p> <hr/> <p>S. 26°43' E., on line 1-2, sec. 27.</p>	
11.43	<p>Point for Angle Point No. 2, sec. 27.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T3N R22W AP2 } S27 1981</p> </div> <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 11°06' W., on line 2-3, sec. 27.</p>	
9.52	<p>Point for Angle Point No. 3, sec. 27.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T3N R22W AP3 } S27 1981</p> </div> <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 2°40' E., on line 3-4, sec. 27.</p>	

Metes-and-Bounds Survey in Section 27,
T. 3 N., R. 22 W., Gila and Salt River Mer., Arizona

CHAINS		
23.73	<p>Point for Angle Point No. 4, sec. 27.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T3N R22W AP4 } S27 1981</p> <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 2°50' W., on line 4-5, sec. 27.</p>	
22.04	<p>Point for Angle Point No. 5, sec. 27.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T3N R22W AP5 } S27 1981</p> <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 27°10' E., on line 5-6, sec. 27.</p>	
16.53	<p>Angle Point No. 6, sec. 27, identical with Angle Point No. 1, sec. 34, heretofore described.</p> <hr/> <p>Metes-and-Bounds Survey in Section 34, T. 3 N., R. 22 W., Gila and Salt River Mer., Arizona</p> <hr/>	
17.50	<p>S. 17°49' W., on line 1-2, sec. 34.</p> <p>Point for Angle Point No. 2, sec. 34.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T3N R22W AP2 } S34 1981</p> <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 84°16' W., on line 2-3, sec. 34.</p>	
31.37	<p>Point for Angle Point No. 3, sec. 34.</p>	

Metes-and-Bounds Survey in Section 34,
T. 3 N., R. 22 W., Gila and Salt River Mer., Arizona

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T3N R22W

AP3

S34

1981

Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.

Cor. is located 24 lks. W of intersection of track roads, extending N. 80° E., S. 60° E. and N. 80° W.

N. $66^\circ 25'$ W., on line 3-4, sec. 34.

8.40 Point for Angle Point No. 4, sec. 34.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T3N R22W

AP4

S34

1981

Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.

Cor. is located 55 lks. E of intersection of roads extending S. 35° E., N. 45° W. and N. 20° W., and 24 lks. W of a track road, bears S. 60° E. and N. 60° W.

N. $27^\circ 10'$ W., on line 4-5, sec. 34.

14.59 Angle Point No. 5, sec. 34, identical with Angle Point No. 2, sec. 33, heretofore described.

Metes-and-Bounds Survey in Section 21,
T. 3 N., R. 22 W., Gila and Salt River Mer., Arizona

From Angle Point No. 1, sec. 21, on the line bet. secs. 16 and 21, heretofore described.

S. $1^\circ 52'$ W., on line 1-2, sec. 21.

Along the W side of a canal.

20.46 Point for Angle Point No. 2, sec. 21.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T3N R22W

S21/AP2

1981

Metes-and-Bounds Survey in Section 21,
T. 3 N., R. 22 W., Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <p>Cor. is located on W bank of a canal.</p> <hr/> <p>S. 43°11' W., on line 2-3, sec. 21.</p>	
3.825	<p>Point for Angle Point No. 3, sec. 21.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T3N R22W S21/AP3 1981</p> <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <p>Cor. is located on W bank of a canal.</p> <hr/> <p>S. 4°19' W., on line 3-4, sec. 21.</p>	
17.46	<p>Point for Angle Point No. 4, sec. 21.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T3N R22W S21/AP4 1981</p> <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <p>Cor. is located on W bank of a canal.</p> <hr/> <p>S. 12°35' W., on line 4-5, sec. 21.</p>	
2.99	<p>Point for Angle Point No. 5, sec. 21.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T3N R22W S21/AP5 1981</p> <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <p>Cor. is located on W bank of canal.</p> <hr/>	

Metes-and-Bounds Survey in Section 21,
T. 3 N., R. 22 W., Gila and Salt River Mer., Arizona

CHAINS

S. 0°09' E., on line 5-6, sec. 21.

6.27 Point for Angle Point No. 6, sec. 21.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T3N R22W

S21 | AP6

1981

Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.

Cor. is located 44 lks. S. 45° W. of cor. of canal, extending N and E.

S. 11°19' E., on line 6-7, sec. 21.

5.28 Point for Angle Point No. 7, sec. 21.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T3N R22W

S21 | AP7

1981

Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.

S. 18°40' E., on line 7-8, sec. 21.

6.815 Point for Angle Point No. 8, sec. 21.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T3N R22W

S21 | AP8

1981

Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.

S. 16°47' E., on line 8-9, sec. 21.

19.24 Angle Point No. 9, sec. 21, identical with Angle Point No. 1, sec. 28, heretofore described.

Metes-and-Bounds Survey in Section 28,
T. 3 N., R. 22 W., Gila and Salt River Mer., Arizona

Metes-and-Bounds Survey in Section 28,
T. 3 N., R. 22 W., Gila and Salt River Mer., Arizona

CHAINS		
	<p>S. 6°59' E., on line 1-2, sec. 28.</p> <p>8.48 Point for Angle Point No. 2, sec. 28.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T3N R22W S28 \ AP2 1981</p> <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <hr style="width: 20%; margin: auto;"/>	
	<p>S. 3°10' E., on line 2-3, sec. 28.</p> <p>8.525 Point for Angle Point No. 3, sec. 28.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T3N R22W S28 \ AP3 1981</p> <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <hr style="width: 20%; margin: auto;"/>	
	<p>S. 5°27'30" W., on line 3-4, sec. 28.</p> <p>5.93 Point for Angle Point No. 4, sec. 28.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T3N R22W S28 \ AP4 1981</p> <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <hr style="width: 20%; margin: auto;"/>	
	<p>S. 48°40' E., on line 4-5, sec. 28.</p> <p>3.49 Point for Angle Point No. 5, sec. 28.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T3N R22W S28 \ AP5 1981</p>	

Metes-and-Bounds Survey in Section 28,
T. 3 N., R. 22 W., Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <p>Cor. is located on W bank of an abandoned canal which bears N and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 21°54' E., on line 5-6, sec. 28.</p>	
5.73	<p>Point for Angle Point No. 6, sec. 28.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T3N R22W</p> <p>S28 \ AP6</p> <p>1981</p> </div>	
	<p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <p>Cor. is located on W bank of an abandoned canal which bears S. 25° E. and N. 25° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 10°42' E., on line 6-7, sec. 28.</p>	
9.66	<p>Point for Angle Point No. 7, sec. 28.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T3N R22W</p> <p>S28 \ AP7</p> <p>1981</p> </div>	
	<p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 17°07' E., on line 7-8, sec. 28.</p>	
.36	<p>Center of a graded gravel road, 28 lks. wide, bears E and W curving SW.</p>	
9.51	<p>Point for Angle Point No. 8, sec. 28.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T3N R22W</p> <p>S28 \ AP8</p> <p>1981</p> </div> <p>Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/>	

Metes-and-Bounds Survey in Section 28,
T. 3 N., R. 22 W., Gila and Salt River Mer., Arizona

CHAINS

S. 7°49' E., on line 8-9, sec. 28.

10.405 Point for Angle Point No. 9, sec. 28.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T3N R22W

S28 \ AP9

1981

Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.

S. 32°49' E., on line 9-10, sec. 28.

16.755 Point for Angle Point No. 10, sec. 28.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T3N R22W

S28 \ AP10

1981

Set a fiberglass post, 6 ft. long, 2 ft. in the ground, alongside the cor.

S. 41°20' E., on line 10-11, sec. 28.

8.70 Angle Point No. 11, sec. 28, identical with Angle Point No. 1, sec. 33, heretofore described.

Metes-and-Bounds Survey in Section 33,
T. 3 N., R. 22 W., Gila and Salt River Mer., Arizona

S. 36°42'30" E., on line 1-2, sec. 33.

4.355 Angle Point No. 2, sec. 33, identical with Angle Point No. 5, sec. 34, heretofore described.

Informative Traverse of a Gravel Road Through Sections
22 and 28, T. 3 N., R. 22 W., Gila & Salt River Mer., Az.

The following notes are those of a traverse of the center of a graded gravel road in sec. 22, for informational purposes only.

From a point in the center of a graded gravel road, from which Angle Point No. 10, sec. 22, bears N. 23°23' W., 75 lks. dist., heretofore described.

Thence, along the center of graded gravel road, 32 lks. wide.

Informative Traverse of a Gravel Road Through Sections 22 and 28,
T. 3 N., R. 22 W., Gila and Salt River Mer., Arizona

CHAINS	<p>S. 5°26' W., 2.40 chs.</p> <p>S. 12°55' W., 1.80 chs.</p> <p>S. 27°23' W., 1.55 chs.</p> <p>S. 52°27' W., 1.56 chs.</p> <p>S. 80°55' W., 2.20 chs.</p> <p>S. 89°53' W., 27.83 chs.</p> <p>S. 64°12' W., .795 chs.</p> <p>S. 31°09' W., 1.15 chs.</p> <p style="text-align: right;">At end of course intersect the line, bet. secs. 21 and 22, at a point from which the cor. of secs. 21, 22, 27 and 28, bears S. 0°01' E., 17.87 chs. dist., heretofore described.</p> <hr/> <p>Thence in sec. 28, with a traverse of the center of a graded gravel road, for informational purposes only.</p> <p>From a point at the intersection of graded gravel roads extending N, S and W, from which the 1/4 of secs. 27 and 28, bears N. 15°59' E., 36 lks. dist., heretofore described.</p> <p>Thence along the center of graded gravel road, 22 lks. wide.</p> <p>N. 89°48' W., 18.65 chs.</p> <p>S. 88°42' W., 2.77 chs.</p> <p style="text-align: right;">At end of course intersect the metes-and-bounds survey line in sec. 28, bet. Angle Points 7 and 8, at a point from which Angle Point No. 7, bears N. 17°07' W., 36 lks. dist., heretofore described.</p> <p style="text-align: right;">From this point the road extends W curving SW.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The town of Ehrenberg is located in sec. 15 of this township. The elevation ranges from about 265 to 450 ft. above sea level.</p> <p>The soil consists of sand and silt deposits. A portion of the bottom lands are under cultivation.</p> <p>Vegetation consists of salt cedar, arrowweed, mesquite and cottonwood in the uncleared areas of the bottom land, with ironwood, palo verde and cactus on the desert.</p>
--------	---

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Paul L. Reeves, Cadastral Surveyor, HEREBY
 supplemental 12th
 CERTIFY upon honor that, in pursuance of special instructions bearing date of the 12th day
 of December 80
 of November, 1980, (I) ~~(We)~~ have dependently resurveyed a portion of
 the south boundary, a portion of the subdivisional lines and surveyed a
 metes-and-bounds survey in sections 21, 22, 27, 28, 33 and 34 of
 Township 3 North, Range 22 West,

of the Gila and Salt River Meridian, in the State of Arizona, which
 are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my)
~~(our)~~ direction; and that said survey has been made in strict conformity with said special instruc-
 tions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in
 specific manner described in the foregoing field notes.

MAR 24 1983

 (Date) Paul L. Reeves

 (Cadastral Surveyor)

 (Date) _____
 (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
 Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the south
 boundary, a portion of the subdivisional lines and the metes-and-bounds
 survey in sections 21, 22, 27, 28, 33 and 34 of T. 3 N., R. 22 W.,
 Gila and Salt River Meridian, Arizona

executed by Paul L. Reeves, Cadastral Surveyor
 having been critically examined and found correct, are hereby approved.

MAR 29 1983

 (Date) *Jerald E. Knight*

~~(Chief Cadastral Survey Examination and Approval Staff)~~
 Acting (Chief Cadastral Surveyor of Arizona)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
 T. 3 N., R. 22 W., G&SPM, Arizona, is a true copy of the original field notes.

 (Date) _____

~~(Chief Cadastral Survey Examination and Approval Staff)~~
 (Chief Cadastral Surveyor of Arizona)