

Form 9600-9
(December 1979)
(formerly 9180-6)

ORIGINAL
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF A PORTION OF THE EAST BOUNDARY

(BLACK MESA FOREST RESERVE)

AND

SUBDIVISIONAL LINES

AND

THE SURVEY OF

SUBDIVISIONS IN SECTIONS 29 AND 32

TOWNSHIP 11½ NORTH, RANGE 11½ EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Paul L. Reeves, Supervisory Cadastral Surveyor

Under special instructions dated October 2, 1981, approved October 2, 1981,

_____, which provided for the surveys included under ~~US Survey~~/Group

Number 625, and assignment instructions dated October 2, 1981.

Survey commenced October 5, 1981

Survey completed March 30, 1983

INDEX DIAGRAM

Township 11½ North, Range 11½ East,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20 18	Sec. 6 3 21	22	23	24
30	16 29 12	5 28 Sec. 7	27	26	25
31	10 32 8	6 33 Sec. 18	34	35	36

Subdivision of Sec. 29 ----- p. 19

Subdivision of Sec. 32 ----- p. 22

T. 11½ N., R. 11½ E., Gila and Salt River Mer., Arizona

CHAINS

The following field notes are those of the dependent resurvey of a portion of the east boundary (Black Mesa Forest Reserve) and subdivisional lines, and a survey of subdivisions in sections 29 and 32, Township 11½ North, Range 11½ East, Gila and Salt River Meridian, Arizona.

The north and east boundaries (Black Mesa Forest Reserve) were surveyed in 1902-03 by W.H. Thorn. The south boundary and the subdivisional lines were surveyed in 1904 by Ivan E. Oakes. The west boundary was surveyed by Charles L. Campbell in 1904 and was concurrently, dependently resurveyed under T. 11½ N., R. 11 E., of this same Group. In 1907, Charles L. Campbell executed a corrective survey of portions of the south boundary and subdivisional lines. The north boundary was dependently resurveyed in 1933 by Theodore Vander Meer. The north half mile between sections 31 and 32 was retraced in 1927 by C. A. Long, U.S. Forest Service, while executing Homestead Entry Survey No. 646.

Patterson and Associates, Inc., Mesa, Arizona, surveyed the boundaries and subdivided sections 29 and 32, under U.S. Forest Service contract. The Forest Service requested this dependent resurvey and subdivision of sections 29 and 32, in order to verify and to delineate the National Forest boundary lines and to resolve conflicts of ownership and prevent future trespass.

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instruction for Group No. 625, Arizona, dated October 2, 1981.

The direction of the lines of this survey was determined by altitude observations on the sun and refer to the true meridian. Distances were measured with a Hewlett Packard 3820A total station.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished in a proportionate position based on original records. All evidence of private surveys was evaluated and considered and was accepted if the evidence indicated that the survey was properly executed. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the closing cor. of secs. 5 and 32, Tps. 11 and 11½ N., R. 11½ E., on the W bdy. of T. 11 N., R. 12 E., as computed from a tie to U.S.F.S. triangulation station "MYRTLE POINT", located in sec. 36, T. 12 N., R. 11 E., is as follows:

Latitude: 34°19'58.59" N Longitude: 111°08'03.67" W

The mean magnetic declination is 13½° E.

Dependent Resurvey of a Portion of the E Bdy.
(W Bdy., T. 11 N., R. 12 E.)
T. 11½ N., R. 11½ E., Gila and Salt River Mer., Arizona

Dependent Resurvey of a Portion of the E Bdy.,
 (W Bdy., T. 11 N., R. 12 E.)
 T. 11½ N., R. 11½ E., Gila and Salt River Mer., Arizona

CHAINS

(Restoring the 1902-03 Survey by W.H. Thorn)

Beginning at the cor. of T. 11 N., R. 12 E., T. 11½ N., R. 11½ E., and Tps. 12 N., Rs. 11 and 12 E., secs. 6, 20, 31 and 36, monumented with an iron post, 4 ins. diam., projecting 12 ins. above ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the 1902-03 official record.

from which the remaining original bearing trees

A ponderosa pine, 20 ins. diam., bears S. 17°50' E., 43 lks. dist., mkd. T11N R12E S6 BT.

A ponderosa pine stump, 34 ins. diam., bears S. 64°45' W., 104 lks. dist., mkd. T11N R11E S1 BT.

A fallen ponderosa pine, 32 ins. diam., bears N. 70° W., 112 lks. dist., mkd. T12N R11E S36 BT.

from which the 1933 bearing tree

A ponderosa pine, 10 ins. diam., bears N. 75° W., 17 lks. dist., mkd. T12N R11E S36 BT. (Record: N. 80° W.)

From this point U.S.F.S. triangulation station "MYRTLE POINT", bears N. 89°44' W., 55.91 chs. dist., monumented with a brass tablet 3 ins. diam., set in a rock surface. The geodetic position as published by U.S.F.S. is:

Latitude: 34°22'31.153" N Longitude: 111°08'46.787" W

S. 0°25' W., on the W bdy. of sec. 6.

Over mountainous land, through dense ponderosa pine, scattered juniper, spruce and oak.

39.98 The 1/4 sec. cor. of sec. 6 only, monumented with a sandstone, 18 X 15 X 7 ins., loosely set in a scattered mound of stone, mkd. 1/4.

from which the remains of the original bearing trees

A ponderosa pine stump, 14 ins. diam., bears S. 45½° E., 13 lks. dist., mkd. BT. (Record: S. 53° E.)

A ponderosa pine stump, 15 ins. diam., bears S. 77°30' W., 23 lks. dist., mkd. S BT.

At the cor. point

Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, with cap mkd.

T11N | T11N
 R11½E | R12E
 | 1/4 S6
 1981

Dependent Resurvey of a Portion of the E Bdy.,
 (W Bdy., T. 11 N., R. 12 E.)
 T. 11½ N., R. 11½ E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>from which a new bearing tree</p> <p>A ponderosa pine, 15 ins. diam., bears S. 53° E., 22 lks. dist., mkd. 1/4 S6 BT.</p> <p>Raise a mound of stone, 4 ft. base, 1½ ft. high, E of cor.</p> <p>Bury the original stone in the mound of stone.</p> <hr/> <p>S. 0°22' W., beginning new measurement.</p>	
33.15	Point for the closing cor. of secs. 20 and 29, T. 11½ N., R. 11½ E., hereinafter described.	
39.90	<p>The cor. of secs. 6 and 7 only, monumented with an iron post, 4 ins. diam., projecting 24 ins. above ground, with brass cap mkd. as described in the 1902-03 official record, with a mound of stone, 2 ft. base, 1 ft. high, E of cor.</p> <p>from which the remaining original bearing trees</p> <p>A dead oak snag, 18 ins. diam., bears N. 55° E., 27 lks. dist., mkd. T11N R12E S6 BT. (Record: N. 50°10' E.)</p> <p>A dead oak snag, 10 ins. diam., bears S. 22° E., 82 lks. dist., healed blaze. (Record: 75 lks. dist.)</p> <p>from which new bearing trees</p> <p>A ponderosa pine, 10 ins. diam., bears N. 86° E., 42 lks. dist., mkd. T11N R12E S6 BT.</p> <p>A ponderosa pine, 15 ins. diam., bears S. 29° E., 47.5 lks. dist., mkd. T11N R12E S7 BT.</p> <p>Add the marks 1981 to the cap.</p> <hr/> <p>(Restoring the 1902-03 Survey by W.H. Thorn) and the 1904 Retracement by Ivan E. Oaks)</p> <hr/> <p>S. 0°15' W., on the W bdy. of sec. 7.</p> <p>Over mountainous land, through dense ponderosa pine, manzanita, scattered oak and juniper.</p>	
33.23	The 1/4 sec. cor. of sec. 29 only, T. 11½ N., R. 11½ E., hereinafter described.	
39.65	<p>The 1/4 sec. cor. of sec. 7 only, monumented with a sandstone, 15 X 15 X 8 ins. above ground, in a mound of stone, 4 ft. base, 1 ft. high, mkd. 1/4 on W face.</p> <p>from which the original bearing trees</p> <p>A yellow pine, 21 ins. diam., bears N. 28° E., 15 lks. dist., healed blaze.</p> <p>A white oak, 16 ins. diam., bears S. 12°30' E., 40 lks. dist., healed blaze.</p>	

Dependent Resurvey of a Portion of the E Bdy.,
 (W Bdy., T. 11 N., R. 12 E.)
 T. 11½ N., R. 11½ E., Gila and Salt River Mer., Arizona

CHAINS														
	<p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T11½N</td> <td> </td> <td>T11N</td> </tr> <tr> <td>R11½E</td> <td> </td> <td>R12E</td> </tr> <tr> <td></td> <td></td> <td>1/4 S7</td> </tr> <tr> <td></td> <td></td> <td>1981</td> </tr> </table> </div> <p>Bury the original stone alongside the cor.</p> <p>Raise a mound of stone 3 ft. base, 1 ft. high, E of cor.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 0°14' W., beginning new measurement.</p>	T11½N		T11N	R11½E		R12E			1/4 S7			1981	
T11½N		T11N												
R11½E		R12E												
		1/4 S7												
		1981												
33.56	Point for the closing cor. of secs. 29 and 32, T. 11½ N., R. 11½ E., hereinafter described.													
38.34	Graded dirt road, bears N. 70° E. and S. 70° W., curving NW.													
40.01	<p>The cor. of secs. 7 and 18 only, monumented with an iron post, 4 ins. diam., projecting 24 ins. above ground, with brass cap mkd. as described in the 1902-03 official record.</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A burnt out alligator juniper stump, 36 ins. diam., bears N. 25° E., 60 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A standing dead ponderosa pine, 22 ins. diam., bears S. 40° E., 153 lks. dist., mkd. T11N R12E S18 BT.</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears N. 21° E., 103 lks. dist., mkd. T11N R12E S7 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears S. 83½° E., 158 lks. dist., mkd. T11N R12E S18 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, around the cor.</p> <p>Add the marks 1981 to the cap.</p> <hr style="width: 50%; margin-left: 0;"/> <p>S. 0°19' W., on the W bdy. of sec. 18.</p> <p>Over rolling mountainous land, through dense ponderosa pine, scattered juniper, oak and manzanita.</p>													
13.63	The N 1/16 sec. cor. of sec. 32 only, T. 11½ N., R. 11½ E., hereinafter described.													
33.71	The 1/4 sec. cor. of sec. 32 only, T. 11½ N., R. 11½ E., hereinafter described.													
40.03	The 1/4 sec. cor. of sec. 18 only, monumented with a limestone, 22 X 12 X 12 ins., projecting 15 ins. above ground, mkd. only with a cross on top.													

Dependent Resurvey of a Portion of the E Bdy.,
(W Bdy., T. 11 N., R. 12 E.)
T. 11½ N., R. 11½ E., Gila and Salt River Mer., Arizona

CHAINS

from which the original bearing trees

A dead standing yellow pine, 24 ins. diam., bears
N. 6°50' E., 149 lks. dist., mkd. 1/4 S BT.

A white oak, 8 ins. diam., bears S. 42° W., 13
lks. dist., healed blaze.

At the cor. point

Set an aluminum post, 30 ins. long, ¾ in. diam., 6 ins.
in the ground, in a mound of stone, 2½ ft. base, to top,
with cap mkd.

T11½N	T11N
R11½E	R12E
	1/4 S18
	1981

from which new bearing trees

A ponderosa pine, 10 ins. diam., bears N. 25° E.,
19 lks. dist., mkd. 1/4 S12 BT.

A ponderosa pine, 8 ins. diam., bears S. 45½° E.,
42 lks. dist., mkd. X at breast height and BT
at base.

Bury the original stone in the mound of stone.

S. 0°07' W., beginning new measurement.

33.84 The closing cor. of Tps. 11 and 11½ N., Rs. 11½ E., secs.
5 and 32, hereinafter described.

40.06 The cor. of secs. 18 and 19 only, monumented with an iron
post, 4 ins. diam., projecting 16 ins. above ground, in a
mound of stone, 6 ft. base, to top, with brass cap mkd.
as described in the 1902-03 official record.

from which the remaining original bearing trees

A black oak, 14 ins. diam., bears N. 11° E., 40
lks. dist., healed blaze.

A white oak snag, 20 ins. diam., bears S. 33° E.,
23 lks. dist., mkd. T11N R12E S19 BT.

from which the remains of the 1933 bearing tree

A stump hole bears N. 35° E., 53 lks dist.,
with the remains of a fallen pine alongside,
mkd. T11N R12E S18 BT (Record: N. 45½° E.)

from which new bearing trees

An alligator juniper, 5 ins. diam., bears
N. 77° E., 66 lks. dist., mkd. T11N R12E S18 BT.

A ponderosa pine, 17 ins. diam., bears S. 69° E.,
75 lks. dist., mkd. T11N R12E S19 BT.

Add the marks 1981 to the cap.

Dependent Resurvey of a Portion of the S Bdy.,
 (N Bdy., T. 11 N., R. 11½ E.)
 T. 11½ N., R. 11½ E., Gila and Salt River Mer., Arizona

CHAINS

(Restoring the 1904 Survey by Ivan E. Oaks and the
 Correctional Survey by Charles L. Campbell in 1907)

From the cor. of secs. 31 and 32 only, monumented with a
 slate stone, 24 X 8 X 6 ins., projecting 18 ins. above
 ground, in a mound of stone, 3 ft. base, 1 ft. high, mkd.
 with 1 groove on the E face, and 1 groove on the W face.

from which the original bearing trees

A white oak, 28 ins. diam., bears N. 68° E., 60
 lks. dist., healed blaze. (Record: pine,
 N. 44° E.)

A dead standing oak snag, 14 ins. diam., bears
 S. 19° E., 19.5 lks. dist., marks visible 11N
 11½ E BT. (Record: S. 31° E., 18 lks. dist.)

A black oak, 16 ins. diam., bears S. 27° W.,
 28 lks. dist., marks visible 11N. (Record:
 juniper, 25 lks. dist.)

A white oak, 14 ins. diam., bears North,
 28.5 lks. dist., healed blaze. (Record:
 N. 5° W., 30 lks. dist.)

At the cor. point

Set an aluminum post, 28 ins. long, 1 in. diam., 2 ins.
 in the ground, in a mound of stone, 4 ft. base, to top,
 with cap mkd.

T11½N R11½E
S31 | S32
 T11N R11½E
 1981

from which new bearing trees

An alligator juniper, 18 ins. diam., bears
 N. 44½° E., 60 lks. dist., mkd. T11½N R11½E
 S32 BT.

A ponderosa pine, 8 ins. diam., bears N. 30½° W.,
 51 lks. dist., mkd. T11½N R11½E S31 BT.

Bury the original stone in the mound of stone.

S. 89°28' E., on the S bdy. of sec. 32.

Over rolling mountainous land, through dense ponderosa
 pine, scattered juniper, oak and manzanita.

40.08

The 1/4 sec. cor. of sec. 32 only, monumented with a
 slate stone, 15 X 9 X 7 ins., projecting 8 ins. above
 ground, in a small mound of stone, mkd. 1/4 on N face.

At the cor. point

Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins.
 in the ground, in a mound of stone, 2½ ft. base, to top,
 with cap mkd.

Dependent Resurvey of a Portion of the S Bdy.,
 (N Bdy. T. 11 N., R. 11½ E.)
 T. 11½N R. 11½ E., Gila and Salt River Mer., Arizona

CHAINS

T11½N R11½E
 1/4 S32
 T11N R11½E
 1981

from which

An alligator juniper, 21 ins. diam., bears
 N. 39° W., 23.5 lks. dist., mkd. 1/4 S32 BT.

Bury the original stone alongside the cor.

From this point a Forest Service aluminum post, 2½ ins.
 diam., projecting 7 ins. above ground, in a mound of
 stone, 2½ ft. base, to top, bears N. 77°48' W., 55 lks.
 dist., with cap mkd.

T11½N R11½E
 1/4 S32
 RLS 13056 1981

This cor. was established by Patterson and Associates
 under Forest Service contract, using improper procedures
 and is not utilized in the course of this survey.

S. 89°38' E., beginning new measurement.

35.43

The closing cor. of sec. 32 only, on the W bdy. of
 T. 11 N., R. 12 E., monumented with a limestone, 15 X 10
 X 8 ins., projecting 6 ins. above ground, in a mound of
 stone, 2½ ft. base, 6 ins. high, stone mkd. CC with 2
 grooves on the W face, and 3 grooves on the N face.

from which the original bearing trees

An oak, 17 ins. diam., bears S. 58° W., 63 lks.
 dist., healed blaze. (Record: S. 40½° W.)

A dead standing oak snag, 24 ins. diam., bears
 N. 49° W., 40 lks. dist., marks visible 11½.
 (Record: N. 35½ W.)

At the cor. point

Set an aluminum post, 30 ins. long, ¼ in. diam., 22 ins.
 in the ground, with cap mkd.

	T11½N	
	R11½E	T11N
	S32	S18
CC	-----	
	T11N	R12E
	R11½E	
	1981	

from which new bearing trees

An alligator juniper, 6 ins. diam., bears
 S. 57° E., 57 lks. dist., mkd. X BT at the base.

An alligator juniper, 9 ins. diam., bears
 N. 30° W., 27 lks. dist., mkd. T11½N R11½E
 S32 CC BT.

Dependent Resurvey of a Portion of the S Bdy.,
 (N Bdy., T. 11 N., R. 11½ E.)
 T. 11½ N., R. 11½ E., Gila and Salt River Mer., Arizona

CHAINS

Raise a mound of stone, 2 ft. base, 1½ ft. high, W of cor.

Bury the original stone in the mound.

From this point the cor. of secs. 18 and 19 only, on the W bdy. of T. 11 N., R. 12 E., bears S. 0°07' W., 6.22 chs. dist., heretofore described.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 11½ N., R. 11½ E., Gila & Salt Riv. Mer., Ariz.

(Restoring the 1904 Survey by Ivan E. Oakes and the Correctional Survey by Charles L. Campbell in 1907)

From the cor. of secs. 31 and 32 only, on the S bdy., heretofore described.

N. 0°02' W., bet. secs. 31 and 32.

Over mountainous land, through dense ponderosa pine, oak and juniper.

39.95 The 1/4 sec. cor. of secs. 31 and 32, monumented with a slate stone, 12 X 9 X 7 ins., projecting 9 ins. above ground, mkd. 1/4 on E face, with a mound of stone, 2 ft. base, 1 ft. high, W of cor.

from which the original bearing trees

A dead standing oak, 18 ins. diam., bears
 N. 63° E., 24 lks. dist., mkd. 1/4 S32 BT.
 (Record: N. 50° E.)

An oak, 12 ins. diam., bears S. 40½° W., 40 lks.
 dist., marks visible 1/4 S T.

At the cor. point

Set an aluminum post, 28 ins. long, 1 in. diam., 16 ins. in the ground, with cap mkd.

T11½N R11½E
 1/4
 S31 | S32
 1981

from which

A ponderosa pine, 21 ins. diam., bears N. 80° E.,
 69 lks. dist., mkd. 1/4 S32 BT.

A ponderosa pine, 5 ins. diam., bears S. 86° W.,
 13 lks. dist., mkd. 1/4 S31 BT.

Bury original stone alongside the cor.

(Restoring the 1927 Retracement by C.A. Long)

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11½ N., R. 11½ E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>N. 0°11' W., beginning new measurement.</p> <p>20.105 Point for the N 1/16 sec. cor. of secs. 31 and 32.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 16 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T11½N R11½E N 1/16 S31 S32 1981</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears S. 38° E., 52 lks. dist., mkd. N 1/16 S32 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears S. 11° W., 44 lks. dist., mkd. N 1/16 S31 BT.</p> <p>From this point a Forest Service aluminum post, 2½ ins. diam., projecting 12 ins. above ground, in a mound of stone, 2½ ft. base, to top, bears N. 80°32' W., 1.2 lks. dist., with cap mkd.</p> <p style="text-align: center;">T11½N R11½E N 1/16 S31— —S32 RLS 13056 1980</p> <p>This monument was established by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>	
	<p>40.21 The cor. of secs. 29, 30, 31 and 32, monumented with a Forest Service aluminum post, 2½ ins. diam., projecting 6 ins. above ground, in a mound of stone, 2½ ft. base, to top, with the original sandstone, 16 X 8 X 9 ins., alongside, mkd. with 1 notch on two sides, with cap mkd.</p> <p style="text-align: center;">T11½N R11½E S30 S29 S31 S32 RLS 13056 1980</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">An oak, 21 ins. diam., bears N. 40° E., 70 lks. dist., healed blaze. (Record: N. 27° E.)</p> <p style="padding-left: 40px;">An alligator juniper, 32 ins. diam., bears S. 32° W., 60 lks. dist., healed blaze. (Record: S. 30° W.)</p> <p style="padding-left: 40px;">A dead standing alligator juniper snag, 38 ins. diam., bears N. 60½° W., 160 lks. dist., marks visible T11 S3 BT. (Record: N. 50° W., 15 lks. dist.)</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11½ N., R. 11½ E., Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">T11½N R11½E $\frac{S30}{S31} \mid \frac{S29}{S32}$ 1981</p> <p>Deposited the original stone alongside the cor. and removed the Forest Service aluminum post.</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears S. 43° W., 46.5 lks. dist., mkd. T11½N R11½E S31 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N. 50° W., 30.5 lks. dist., mkd. T11½N R11½E S30 BT.</p>	
	<p style="text-align: center;">(Restoring the 1904 Survey by Ivan E. Oakes and the Correctional Survey by Charles L. Campbell in 1907)</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89°27' E., bet. secs. 29 and 32.</p> <p>Over rolling grass land.</p>	
<p>20.07</p>	<p>Point for the W 1/16 sec. cor. of secs. 29 and 32.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11½N R11½E $\frac{W\ 1/16\ S29}{S32}$ 1983</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears N. 32° E., 14.5 lks. dist., mkd. W 1/16 S29 BT.</p> <p>From this point a Forest Service aluminum post, 2½ ins. diam., projecting 6 ins. above ground, bears S. 81°52' W., .7 lk. dist., with cap mkd.</p>	
<p>40.14</p>	<p style="text-align: center;">T11½N R11½E $\frac{W\ 1/16\ S29}{W\ 1/16\ S32}$ 1980</p> <p>Removed the Forest Service aluminum post.</p> <p>Continue measurement over rolling land, through dense ponderosa pine and juniper.</p> <p>The 1/4 sec. cor. of secs. 29 and 32, monumented with a sandstone, 15 X 12 X 7 ins., projecting 6 ins. above ground, mkd. 1/4 on the N face.</p> <p>from which the remaining original bearing tree</p> <p style="padding-left: 40px;">An alligator juniper, 31 ins. diam., bears S. 61° E., 71 lks. dist., mkd. 1/4 S32 BT. (Record: S. 18° E.)</p> <p>At the cor. point</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11½ N., R. 11½ E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T11½N R11½E 1/4 $\frac{S29}{S32}$ 1981</p> <p>from which a new bearing tree</p> <p style="text-align: center;">A ponderosa pine, 14 ins. diam., bears N. 36° W., 65 lks. dist., mkd. 1/4 S29 BT.</p> <p>Bury the original stone alongside the cor.</p> <p>Cor is located 3 lks. N of a fence cor., fence extends E and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°55' E., beginning new measurement.</p>	
19.70	<p>Point for the E 1/16 sec. cor. of secs. 29 and 32.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11½N R11½E E 1/16 $\frac{S29}{S32}$ 1983</p> <p>from which</p> <p style="text-align: center;">An alligator juniper, 5 ins. diam., bears S. 49° E., 14 lks. dist., mkd. E 1/16 S32 BT.</p> <p style="text-align: center;">A ponderosa pine, 10 ins. diam., bears N. 13½° W., 11 lks. dist., mkd. E 1/16 S29 BT.</p> <p>From this point, the NE cor. of a block support for the NE cor. of a building under construction, bears S. 3°19' E., 1.203 chs. dist.</p> <p>From this same point a Forest Service aluminum post, 2½ ins. diam., projecting 28 ins. above ground, in a mound of stone, 4 ft. base, to top, bears S. 12°06' E., 17.2 lks. dist., with cap mkd.</p> <p style="text-align: center;">T11½N R11½E E 1/16 $\frac{S29}{S32}$ 1980</p> <p>This monument was established by Patterson and Associates under Forest Service contract using improper procedures and is not utilized in the course of this survey.</p>	
23.70	<p>Graded dirt road, bears S. 20° E. and N. 20° W.</p>	
35.81	<p>Point for the closing cor. of secs. 29 and 32, on the W bdy. of sec. 7, T. 11 N., R. 12 E., determined from the remaining original bearing tree.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11½ N., R. 11½ E., Gila and Salt River Mer., Arizona

CHAINS

An oak, 10 ins. diam., bears N. 34½° W., 91
lks. dist., mkd. T11½N R11½ E S29 BT.
(Record: S. 34½° W.)

The bearing quadrant of the original bearing trees was transformed in the 1904 record. The determined point for this cor. matches the record tie to the cor. of secs. 7 and 18 only, T. 11 N., R. 12 E.

At the cor. point

Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.

T11½N T11N	
CC $\frac{S29}{S32}$	S7
R11½E	R12E
1981	

from which new bearing trees

A ponderosa pine, 7 ins. diam., bears S. 75½° W.,
57.5 lks. dist., mkd. T11½N R11½E S32 CC BT.

A ponderosa pine, 8 ins. diam., bears N. 51° W.,
37 lks. dist., mkd. T11½N R11½E S29 CC BT.

Raise a mound of stone, 2½ ft. base, 1 ft. high, W of cor.

From this point the cor. of secs. 7 and 18 only,
T. 11 N., R. 12 E., bears S. 0°14' W., 6.45 chs. dist.,
heretofore described.

From this same point a Forest Service aluminum post, 2½
ins. diam., projecting 6 ins. above ground, bears
S. 0°22' E., 31 lks. dist., with cap mkd.

T11½N T11N	
CC $\frac{S29}{S32}$	R12E
R11½E	S7
RLS 13056 1980	

This monument was established by Patterson and Associates under Forest Service contract using improper procedures and is not utilized in the course of this survey.

The point for the 1/4 sec. cor. of sec. 32 only,
T. 11½ N., R. 11½ E., is at midpoint on the E bdy. of
sec. 32.

Set an aluminum post, 30 ins. long, ¾ in. diam., 23 ins. in the ground, with cap mkd.

T11½N		T11N
1/4		
S32		
R11½E		R12E
1981		

from which

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11½ N., R. 11½ E., Gila and Salt River Mer., Arizona

CHAINS

A ponderosa pine, 8 ins. diam., bears S. 62° W.,
79 lks. dist., mkd. X at breast height and BT
at base.

A ponderosa pine, 12 ins. diam., bears N. 21° W.,
30 lks. dist., mkd. 1/4 S32 BT.

Raise a mound of stone, 2 ft. base, 1½ ft. high, W of
cor.

From this point the 1/4 sec. cor. of sec. 18 only,
T. 11 N., R. 12 E., bears S. 0°19' W., 6.32 chs. dist.,
heretofore described.

From this same point, a Forest Service aluminum post, 2½
ins. diam., projecting 12 ins. above ground, in a mound
of stone, bears S. 0°21' E., 16.2 lks. dist., with cap
mkd.

C C	
T11½N	T11N
R11½E	R12E
1/4 S32	S18
RSL 13056 1980	

This monument was established by Patterson and Associates
under Forest Service contract using improper procedures
and is not utilized in the course of this survey.

The point for the N 1/16 sec. cor. of sec. 32 only,
T. 11½ N., R. 11½ E., is at midpoint bet. the closing
cor. of secs. 29 and 32, and the 1/4 sec. cor. on the E
bdy. of sec. 32.

Set an aluminum post, 30 ins. long, ¾ in. diam., 22 ins.
in the ground, with cap mkd.

T11½N	T11N
N 1/16	
S32	R12E
R11½E	
1981	

from which

A ponderosa pine, 4 ins. diam., bears S. 72° W.,
55 lks. dist., mkd. X at breast height and BT
at base.

Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.

From this point the cor. of secs. 7 and 18 only,
T. 11 N., R. 12 E., bears N. 0°19' E., 13.63 chs. dist.,
heretofore described.

From this same point, a ½ in. diam. rebar, projecting 1
in. above ground, bears S. 0°46' E., 22.4 lks. dist. This
monument was established by Patterson and Associates
under Forest Service contract using improper procedures
and is not utilized in the course of this survey.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11½ N., R. 11½ E., Gila and Salt River Meridian, Arizona

CHAINS		
	<p>From the cor. of secs. 29, 30, 31 and 32, heretofore described.</p> <p>N. 0°03' E., bet. secs. 29 and 30.</p> <p>Over rolling land, through dense ponderosa pine, juniper and manzanita.</p> <p>19.94 Point for the S 1/16 sec. cor. of secs. 29 and 30.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 5 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T11½N R11½E S 1/16 S30 S29 1981</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears N. 60½° E., 38 lks. dist., mkd. S 1/16 S29 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N. 12° W., 22 lks. dist., mkd. S 1/16 S30 BT.</p> <p>From this point a Forest Service aluminum post, 2½ ins. diam., projecting 24 ins. above ground, in a mound of stone, 3½ ft. base, to top, bears N. 63°26' W., .7 lk. dist., with cap mkd.</p> <p style="text-align: center;">T11½N R11½E S 1/16 S30 S29 RLS 13056 1980</p> <p>This monument was established by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey and was removed.</p>	
30.90	Graded gravel road, bears N. 65° E. and S. 65° W.	
39.88	<p>The 1/4 sec. cor. of secs. 29 and 30, monumented with a sandstone, 14 X 9 X 9 ins., projecting 8 ins. above ground, mkd. 1/4 on the W face, in a mound of stone, 2½ ft. base, 6 ins. high.</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A dead standing black oak, 5 ins. diam., bears S. 17° E., 45 lks. dist., illegible scribe marks visible. (Record: S. 20° E.)</p> <p style="padding-left: 40px;">A fallen oak, 15 ins. diam., bears N. 64½° W., 39 lks. dist., mkd. 1/4 S30 BT. (Record: N. 70° W.)</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T11½N R11½E 1/4 S30 S29 1981</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11½ N., R. 11½ E., Gila and Salt River Mer., Arizona

CHAINS										
	<p>from which new bearing trees</p> <p>A ponderosa pine, 15 ins. diam., bears N. 74½° E., 44.5 lks. dist., mkd. 1/4 S29 BT.</p> <p>A ponderosa pine, 14 ins. diam., bears N. 81° W., 20.5 lks. dist., mkd. 1/4 S30 BT.</p> <p>Rebuilt the mound of stone, 2½ ft. base, 1 ft. high, W of cor.</p> <p>Bury the original stone in the mound of stone.</p> <hr/> <p>N. 0°19' E., beginning new measurement.</p> <p>40.08 The cor. of secs. 19, 20, 29 and 30, monumented with a sandstone, 18 X 12 X 8 ins., projecting 8 ins. above ground, in a scattered mound of stone, mkd. with 2 grooves on the S only.</p> <p>from which the original bearing trees</p> <p>A fallen oak, 12 ins. diam., bears N. 54° E., 40 lks. dist., illegible scribe marks. (Record: N. 80° E.)</p> <p>A dead pine snag, 18 ins. diam., bears N. 80° E., 26 lks. dist., marks visible ½N R11½E S29 BT. (Record: S. 84° E.)</p> <p>An oak, 13 ins. diam., bears S. 4° W., 15 lks. dist., with rotted out blaze. (Record: S. 30° W.)</p> <p>A dead standing juniper, 16 ins. diam., bears N. 33½° W., 6 lks. dist., marks visible 11½N R11½E BT. (Record: N. 51° W.)</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td colspan="2">T11½N R11½E</td> </tr> <tr> <td>S19</td> <td>S20</td> </tr> <tr> <td>S30</td> <td>S29</td> </tr> <tr> <td colspan="2">1981</td> </tr> </table> </div> <p>from which</p> <p>A ponderosa pine, 6 ins. diam., bears S. 20½° E., 52.5 lks. dist., mkd. T11½N R11½E S29 BT.</p> <p>A ponderosa pine, 4 ins. diam., bears S. 20° W., 70 lks. dist., mkd. X at breast height and BT at base.</p> <p>A black oak, 6 ins. diam., bears N. 77° W., 34 lks. dist., mkd. T11½N R11½E S19 BT.</p> <p>Bury original stone alongside the cor.</p> <p>Rebuilt the mound of stone, 3 ft. base, 2 ft. high, W of cor.</p>	T11½N R11½E		S19	S20	S30	S29	1981		
T11½N R11½E										
S19	S20									
S30	S29									
1981										

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11½ N., R. 11½ E., Gila and Salt River Mer., Arizona

CHAINS	<p>N. 89°58' E., bet. secs. 20 and 29.</p> <p>Over rolling mountainous land, through dense ponderosa pine, juniper, oak and manzanita.</p>
40.90	<p>The 1/4 sec. cor. of secs. 20 and 29, determined from the original bearing trees</p> <p style="padding-left: 40px;">A pine stump, 18 ins. diam., bears N. 23° E., 54 lks dist., mark visible B only.</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears S. 70° W., 27 lks. dist., mkd. 1/4 S29 BT. (Record: S. 65° W.)</p> <p>Cor. point falls on a sandstone outcropping, 8 X 6 X 1 ft. above ground.</p> <p>At the cor. point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3½ in. stem, in a drill hole, with top mkd.</p> <div style="text-align: center; padding: 10px 0;"> $\begin{array}{r} T11\frac{1}{2}N \ R11\frac{1}{2}E \\ 1/4 \ \frac{S20}{S29} \\ 1981 \end{array}$ </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears S. 3° E., 69 lks. dist., mkd. 1/4 S29 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears N. 26° W., 16 lks. dist., mkd. 1/4 S20 BT.</p> <p>From this point a Forest Service aluminum post, 2½ ins. diam., projecting 22 ins. above ground, in a mound of stone, 3½ ft. base, 1½ ft. high, bears S. 67°12' W., 1.138 chs. dist., with cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> $\begin{array}{r} T11\frac{1}{2}N \ R11\frac{1}{2}E \\ \hline S \ \ 20 \\ S \ \ 29 \\ \hline RLS \ 13056 \ 1980 \end{array}$ </div> <p>This monument was established by Patterson and Associates under Forest Service contract using improper procedures and is not utilized in the course of this survey.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°11' E., beginning new measurement.</p>
35.14	<p>The original closing cor. of secs. 20 and 29, monumented with a sandstone, 18 X 12 X 8 ins. above ground, mkd. CC on W face, 1 groove on the N face and 2 on the S face, with a mound of stone, 1½ ft. base, 1 ft. high, W of cor.</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A juniper, 30 ins. diam., bears S. 37½° W., 52.5 lks. dist., mkd. T11½N R11½E S29 BT. (Record: 50 lks. dist.)</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11½ N., R. 11½ E., Gila and Salt River Mer., Arizona


CHAINS

A fallen oak, 10 ins. diam., bears N. 53° W.,
38 lks. dist., mks. visible T11½N. (Record:
40 lks. dist.)

Add the marks AM to the cor.

35.19 Point for the closing cor. of secs. 20 and 29, at inter-
section with the W bdy. of sec. 6, T. 11 N., R. 12 E.

Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins.
in the ground, with cap mkd.




from which

A ponderosa pine, 18 ins. diam., bears N. 27½° W.,
35 lks. dist., mkd. T11½N R11½E S20 CC BT.

From this point the cor. of secs. 6 and 7 only, T. 11 N.,
R. 12 E., bears S. 0°22' W., 6.75 chs. dist., heretofore
described.

Point for the ¼ sec. cor. of sec. 29 only, T. 11½ N.,
R. 11½ E., is at midpoint on the E bdy. of sec. 29.


Set an aluminum post, 23 ins. long, 1 in. diam., 22 ins.
in the ground, with cap mkd.



Raise a mound of stone, 2 ft. base, 1½ ft. high, W of
cor.

From this point the ¼ sec. cor. of sec. 7 only,
T. 11 N., R. 12 E., bears S. 0°15' W., 6.42 chs. dist.,
heretofore described.

From this same point a Forest Service aluminum post, 2½
ins. diam., projecting 12 ins. above ground, in a mound
of stone, 2½ ft. base, to top, bears S. 5°21' W., 30 lks.
dist., with cap mkd.



This monument was established by Patterson and Associates
under Forest Service contract using improper procedures
and is not utilized in the course of this survey.

Subdivision of Section 29,
T. 11½ N., R. 11½ E., Gila and Salt River Mer., Arizona

Subdivision of Section 29,
T. 11½ N., R. 11½ E., Gila and Salt River Mer., Arizona

CHAINS	<p>From the 1/4 sec. cor. of secs. 29 and 32.</p> <p>N. 0°44' E., on the N and S center line of sec. 29.</p> <p>Over rolling mountainous land, through dense ponderosa pine, juniper and oak.</p>
20.04	<p>Point for the center S 1/16 sec. cor. of sec. 29.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T11½N R11½E C S 1/16 S29 C 1981</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N. 37½° E., 23 lks. dist., mkd. C-S 1/16 S29 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S. 15° W., 7.5 lks. dist., mkd. C-S 1/16 S29 BT.</p> <p>Raise a mound of stone, 3½ ft. base, 2 ft. high, W of cor.</p> <p>From this point a ½ in. diam. rebar, projecting 2 ins. above ground, bears S. 68°18' W., 31.6 lks. dist. This monument was established by Patterson and Associates under Forest Service contract using improper procedures and is not utilized in the course of this survey.</p>
21.90	<p>Graded gravel road, bears N. 80° E. and S. 80° W.</p>
40.08	<p>Point for the center 1/4 sec. cor., at intersection with the E and W center line of sec. 29.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T11½N R11½E C 1/4 S29 1981</p> <p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 10 ins. diam., bears N. 34½° W., 33 lks. dist., mkd. C 1/4 S29 BT.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.</p> <p>From this point a Forest Service aluminum post, 2½ ins. diam., projecting 8 ins. above ground, bears S. 69°51' W., 60 lks. dist., with cap mkd.</p> <p style="text-align: center;">T11½N R11½E C 1/4 S29 RLS 13056 1980</p> <p>This monument was established by Patterson and Associates under Forest Service contract using improper procedures and is not utilized in the course of this survey.</p>

Subdivision of Section 29,
T. 11½ N., R. 11½ E., Gila and Salt River Mer., Arizona

CHAINS		
80.38	The 1/4 sec. cor. of secs. 20 and 29.	
	From the 1/4 sec. cor. of sec. 29 only, on the E bdy. of the Tp.	
	N. 89°46' W., on the E and W center line of sec. 29.	
	Over rolling mountainous land, through dense ponderosa pine, juniper and oak.	
35.49	The center 1/4 sec. cor. of sec. 29.	
55.80	Point for the center W 1/16 sec. cor. of sec. 29.	
	Set an aluminum post, 28 ins. long, 1 in. diam., 4 ins. in the ground, in a mound of stone, 4 ft. base, 1½ ft. high, with cap mkd.	
	<p style="text-align: center;">T11½N R11½E W 1/16 C——C S29 1981</p>	
	from which	
	A ponderosa pine, 11 ins. diam., bears N. 71° E., 13 lks. dist., mkd. C-W 1/16 S29 BT.	
	A ponderosa pine, 10 ins. diam., bears S. 10½° E., 17 lks. dist., mkd. C-W 1/16 S29 BT.	
	Cor. is located 70 lks. E of a graded gravel road, bears S. 10° E. and N. 10° W., curving westerly.	
	From this point a ½ in. diam. rebar, projecting 2 ins. above ground, bears S. 67°10' W., 28.9 lks. dist. This monument was established by Patterson and Associates under Forest Service contract using improper procedures and is not utilized in the course of this survey	
76.11	The 1/4 sec. cor. of secs. 29 and 30.	
	SW 1/4, Section 29	
	From the W 1/16 sec. cor. of secs. 29 and 32.	
	N. 0°25' E., on the N and S center line of the SW 1/4, sec. 29.	
	Over rolling land, through dense ponderosa pine and juniper.	
19.99	Point for the SW 1/16 sec. cor., at intersection with the E and W center line of the SW 1/4, sec. 29.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.	
	T11½N R11½E SW 1/16 S29 1983	

Subdivision of Section 29,
T. 11½ N., R. 11½ E., Gila and Salt River Mer., Arizona

CHAINS	<p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N. 22° E., 30 lks. dist., mkd. SW 1/16 S29 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N. 59° W., 26.5 lks. dist., mkd. SW 1/16 S29 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>Cor. falls in bottom of a small draw, drains W.</p> <p>From this point a Forest Service aluminum post, 2½ ins. diam., projecting 8 ins. above ground, bears N. 71°12' W., 14.9 lks. dist., with cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>W.C.</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">SW</td> <td style="padding: 0 5px;">1/16</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S</td> <td style="padding: 0 5px;">29</td> </tr> </table> <p>1980</p> </div> <p>This monument was established by Patterson and Associates under Forest Service contract using improper procedures and is not utilized in the course of this survey.</p> <p>39.98 The center W 1/16 sec. cor of sec. 29.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the center S 1/16 sec. cor. of sec. 29.</p> <p>N. 89°36' W., on the E and W center line of the SW 1/4, sec. 29.</p> <p>Over rolling land, through dense ponderosa pine and juniper.</p> <p>20.18 The SW 1/16 sec. cor. of sec. 29.</p> <p>40.37 The S 1/16 sec. cor. of secs. 29 and 30.</p> <hr/> <div style="text-align: center; margin: 10px 0;"> <p>Subdivision of Section 32, T. 11½ N., R. 11½ E., Gila and Salt River Mer., Arizona</p> </div> <hr/> <p>From the 1/4 sec. cor. of sec. 32 only, on the S bdy. of the Tp., heretofore described.</p> <p>N. 0°04' W., on the N and S center line of sec. 32.</p> <p>Over rolling land, through dense ponderosa pine, juniper and oak.</p> <p>40.12 Point for the center 1/4 sec. cor., at intersection with the E and W center line of sec. 32.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T11½N R11½E C 1/4 S32 1981</p> </div> <p>from which</p>	SW	1/16	S	29
SW	1/16				
S	29				

Subdivision of Section 32,
T. 11½ N., R. 11½ E., Gila and Salt River Mer., Arizona

CHAINS


A ponderosa pine, 10 ins. diam., bears S. 53½° E.,
40 lks. dist., mkd. C 1/4 S32 BT.

A ponderosa pine, 5 ins. diam., bears S. 80° W.,
7 lks. dist., mkd. C 1/4 S32 BT.

Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.

Cor. is located 35 lks. E of a N and S power line.


From this point a Forest Service aluminum post, 2½ ins.
diam., projecting 20 ins. above ground, in a mound of
stone, 2½ ft. base, 1 ft. high, bears S. 74°54' W., 27.2
lks. dist., with cap mkd.



This monument was established by Patterson and Associates
under Forest Service contract using improper procedures
and is not utilized in the course of this survey.

60.135 Point for the center N 1/16 sec. cor. of sec. 32.

Set an iron post, 28 ins. long, 2½ ins. diam., 5 ins. in
the ground, over a cross chiseled in bedrock, in a mound
of stone, 4 ft. base, to top, with brass cap mkd.




from which

A ponderosa pine, 10 ins. diam., bears S. 21½° E.,
82 lks. dist., mkd. C-N 1/16 S32 BT.

A ponderosa pine, 12 ins. diam., bears S. 51½° W.,
61.5 lks. dist., mkd. C-N 1/16 S32 BT.

A fence cor. bears S. 18° W., 18 lks. dist.,
fence extends N and E.

From this point a Forest Service aluminum post, 2½ ins.
diam., 24 ins. in the ground, in a mound of stone, 1½
ft. base, to top, bears S. 74°31' W., 13.5 lks. dist.,
with cap mkd.



This monument was established by Patterson and Associates
under Forest Service contract using improper procedures
and is not utilized in the course of this survey.

80.15 The 1/4 sec. cor. of secs. 29 and 32.

Subdivision of Section 32,
T. 11½ N., R. 11½ E., Gila and Salt River Mer., Arizona

CHAINS	<p>From the 1/4 sec. cor. of sec. 32 only, on the E bdy. of the Tp., heretofore described.</p> <p>N. 89°43' W., on the E and W center line of sec. 32.</p> <p>Over rolling land, through dense ponderosa pine, juniper and oak.</p> <p>15.87 Point for the center E 1/16 sec. cor. of sec. 32.</p> <p>Set an aluminum post, 30 ins. long, ½ in. diam., 25 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T11½N R11½E C—E 1/16—C S32 1982</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears S. 51° W., 48 lks. dist., mkd. C-E 1/16 S32 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 4 ins. diam., bears N. 56° W., 18 lks. dist., mkd. X at breast height and BT at base.</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.</p> <p>From this point a ½ in. diam. rebar, projecting 2 ins. above ground, bears S. 38°46' W., 15.6 lks. dist. This monument was established by Patterson and Associates under Forest Service contract using improper procedures and is not utilized in the course of this survey.</p> <p>35.57 The center 1/4 sec. cor. of sec. 32.</p> <p>55.595 Point for the center W 1/16 sec. cor. of sec. 32.</p> <p>Set an aluminum post, 30 ins. long, ½ in. diam., 23 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T11½N R11½E W 1/16 C—C S32 1981</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears N. 65½° E., 9 lks. dist., mkd. C-W 1/16 S32 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears N. 21½° W., 9 lks. dist., mkd. C-W 1/16 S32 BT.</p> <p>Raise a mound of stone, 2½ ft. base, 1 ft. high, W of cor.</p> <p>75.62 The 1/4 sec. cor. of secs. 31 and 32.</p> <hr style="width: 50%; margin: 20px auto;"/> <p style="text-align: center;">NE 1/4, Section 32</p>
--------	--

Subdivision of Section 32,
T. 11½ N., R. 11½ E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>From the center E 1/16 sec. cor. of sec. 32.</p> <p>N. 0°04' W., on the N and S center line of the NE 1/4, sec. 32.</p> <p>Over rolling land, through dense ponderosa pine, scattered oak and juniper.</p> <p>20.05 Point for the NE 1/16 sec. cor., at intersection with the E and W center line of the NE 1/4, sec. 32.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T11½N R11½E NE 1/16 S32 1981</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S. 79½° E., 75 lks. dist., mkd. NE 1/16 S32 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S. 40° W., 28 lks. dist., mkd. NE 1/16 S32 BT.</p> <p style="padding-left: 40px;">A fence cor., bears S. 70° E., 49.5 lks. dist., fence extends N and W.</p> <p>From this point an iron pipe, ¾ in. diam., projecting 2 ins. above ground, bears S. 42°26' E., 37.8 lks. dist., origin unknown.</p> <p>From this same point a Forest Service brass tablet, 3 ins. diam., set in concrete, flush with ground, bears S. 21°31' W., 14.7 lks. dist., with top mkd.</p> <p style="text-align: center;">T11½N R11½E NE 1/16 S 32 RLS 13056 1980</p> <p>This monument was established by Patterson and Associates under Forest Service contract using improper procedures and is not utilized in the course of this survey.</p>
25.51	Intersect the S side of Mead's cabin at a point 7.37 ft. West of the SE cor. Cabin bears from the SE cor., North 26.5 ft., thence West 26.8 ft., thence South 8 ft., thence West 13 ft., thence South 38.4 ft., thence East 22 ft., thence North 19.9 ft., thence East 18.5 ft., to the SE cor.
25.91	Intersect the N side of Mead's cabin at a point 7.40 ft. West of the NE cor.
40.10	<p>The E 1/16 sec. cor. of secs. 29 and 32.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the N 1/16 sec. cor. of sec. 32 only, on the E bdy. of the Tp., heretofore described.</p> <p>N. 89°49' W., on the E and W center line of the NE 1/4, sec. 32.</p>

Subdivision of Section 32,
T. 11½ N., R. 11½ E., Gila and Salt River Mer., Arizona

CHAINS	
	Over rolling land, through medium ponderosa pine, juniper and oak.
15.99	The NE 1/16 sec. cor. of sec. 32.
16.48	Intersect the E side of a cabin at a point 0.4 ft. North of the SE cor. Cabin bears from the SE cor., North 32.8 ft., thence West 2.4 ft., thence South 16.8 ft., thence East 7.8 ft., thence South 16 ft., thence East 16.3 ft., to the SE cor.
16.73	Intersect the W side of same cabin at a point 0.45 ft. North of the SE cor.
34.07	Intersect the E side of a garage at a point 12.5 ft. North of the SE cor. Garage bears from the SE cor., North 17 ft., thence West 9 ft., thence South 17 ft., thence East 17 ft., to the SE cor.
34.21	Intersect the W side of same garage at a point 12.53 ft. North of the SW cor.
35.69	The center N 1/16 sec. cor. of sec. 32.
	<hr/> NW 1/4, Section 32 <hr/>
	From center W 1/16 sec. cor. of sec. 32. N. 0°07' W., on the N and S center line of the NW 1/4, sec. 32.
	Over rolling land, through dense ponderosa pine, scattered juniper and oak.
20.06	Point for the NW 1/16 sec. cor., at intersection with the E and W center line of the NW 1/4, sec. 32. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T11½N R11½E NW 1/16 S32 1981
	from which A ponderosa pine, 8 ins. diam., bears S. 20½° E., 25.5 lks. dist., mkd. NE 1/16 S32 BT. A ponderosa pine, 10 ins. diam., bears S. 43° W., 21 lks. dist., mkd. NW 1/16 S32 BT.
40.12	The W 1/16 sec. cor. of secs. 29 and 32.
	<hr/> From the center N 1/16 sec. cor. of sec. 32.
	N. 89°35' W., on the E and W center line of the NW 1/4, sec. 32.
	Over rolling land, through dense ponderosa pine, scattered juniper and oak.

Subdivision of Section 32,
T. 11½ N., R. 11½ E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p> <p>20.04</p> <p>40.09</p>	<p>The NW 1/16 sec. cor. of sec. 32.</p> <p>The N 1/16 sec. cor. of secs. 31 and 32.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The land encompassed in this survey is located about 16 miles NE of Payson, Arizona. The elevation ranges from about 6,000 ft. to 6,600 ft. above sea level.</p> <p>The land varies from gently rolling to mountainous, covered with medium to dense ponderosa pine, scattered oak and juniper with areas of dense manzanita.</p> <p>Access is by way of a graded dirt road and numerous track roads.</p> <hr/>
---	--

