

ORIGINAL
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF

A PORTION OF THE WEST BOUNDARY (SECOND GUIDE MERIDIAN EAST)

A PORTION OF THE NORTH BOUNDARY

AND

A PORTION OF THE SUBDIVISIONAL LINES,

AND THE SURVEY OF

SUBDIVISIONS AND A METES-AND-BOUNDS SURVEY

IN SECTION 6,

TOWNSHIP 27 NORTH, RANGE 9 EAST

Of the GILA AND SALT RIVER Meridian,

In the State of ARIZONA

EXECUTED BY

DENNIS K. MC KAY, CADASTRAL SURVEYOR

Under special instructions dated FEBRUARY 25, 19 82, approved FEBRUARY 25, 1982,

_____ , which provided for the surveys included under ~~DCS~~ Survey/Group

Number 632 , and assignment instructions dated FEBRUARY 26 , 19 82 .

Survey commenced MARCH 4 , 19 82

Survey completed MARCH 25 , 19 82

INDEX DIAGRAM

Township 27 North, Range 9 East,

7 4 6 10	5	4	3	2	1
3 8 12 10	8	9	10	11	12
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 6 ----- pp. 12-16

Metes-and-bounds survey of lot 11, sec. 6 ----- pp. 16-17

T 27 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS

The following field notes are those of the dependent re-survey of a portion of the west boundary (Second Guide Meridian East), the north boundary and subdivisional lines, and the survey of subdivisions and the metes-and-bounds survey of lot 11 in section 6, T 27 N, R 9 E, Gila and Salt River Meridian, Arizona.

The west boundary (Second Guide Meridian East) was surveyed in 1905 by Philip Contzen and was retraced by Theodore O. Johnson and Philip L. Inch in 1916. The north boundary and the subdivisional lines were surveyed in 1916 by Theodore O. Johnston and Philip L. Inch. The subdivision of the SW 1/4 SE 1/4 of section 6, was performed by Charles W. Dryden, Sr., L.S. 4321, in 1961 in a private survey. The right-of-way monuments of U.S. Highway No. 89 were set in 1938 and 1976 by the Arizona Department of Transportation.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 632, Arizona, dated February 25, 1982.

The directions of lines were determined from a U.S.G.S. triangulation line and checked by altitude observations on the sun. Angles and distances were measured with a Hewlett-Packard 3820A Total Station instrument.

In initiating the resurvey, retracements of the previous surveys were performed and a diligent search made to identify evidence of all previously established corner monuments. Identified corners were remonumented in their original positions. Where available, collateral evidence was used to reestablish obliterated corners.

The geographic position of the southeast corner of section 6, as determined from a tie to U.S.G.S. triangulation station "PLAINS", is as follows:

Latitude: 35°44'34.02" N Longitude: 111°27'55.71" W

The mean magnetic declination is 14°30' E.

Dependent Resurvey of a Portion of the W Bdy. (Second Guide Meridian East) of T 27 N, R 9 E, Gila and Salt River Mer., Arizona

(Reestablishment of the Survey Executed by Philip Contzen, Deputy Surveyor, in 1905)

Beginning at the cor. of secs. 1, 6, 7 and 12, Tps. 27 N, Rs. 8 and 9 E, monumented with a limestone, 12 x 10 x 8 ins., firmly set, projecting 6 ins. above ground, mkd. R8E on E face, T27N R9E on the W face, 5 grooves on the N face, and X on top.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.

Dependent Resurvey of a Portion of the W Bdy. (Second Guide Meridian East) of T 27 N, R 9 E, Gila and Salt River Mer., Ariz.

CHAINS		
	<p style="text-align: center;">T27N R8E R9E S1 S6 S12 S7</p>	
	<p style="text-align: center;">1982</p>	
	<p>Deposit original stone alongside iron post.</p>	
	<p>Cor. is located in open, flat land and 2.3 lks. N of a barbed wire fence extending E and W.</p>	
	<p>N 0°05' E, bet. secs. 1 and 6.</p>	
	<p>Very slight asc., open land.</p>	
40.01	<p>The 1/4 sec. cor. of secs. 1 and 6, monumented with a limestone, 16 x 10 x 3 ins. firmly set, projecting 8 ins. above ground, in a scattered mound of stone, mkd. 1/4 1 on W face, 6 on E face, and X on top.</p>	
	<p>At the cor. point</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, in a mound of stone, 3½ ft. base, to top, with brass cap mkd.</p>	
	<p style="text-align: center;">T27N 1/4 R8E R9E S1 S6 1982</p>	
	<p>Deposit original stone alongside iron post.</p>	
	<p>Drive steel fence post alongside the cor.</p>	
	<p>Cor. is located in open, level land.</p>	
	<hr style="width: 20%; margin: auto;"/> <p>N 0°17' E, bet. secs. 1 and 6.</p>	
	<p>Across open slightly rolling land.</p>	
21.40	<p>Center of paved road, 25 ft. wide, bears S 45° E and N 48° W.</p>	
40.07	<p>The cor. of Tps. 27 and 28 N, Rs. 8 and 9 E, monumented with a 5/8 in. diam. rebar, of unknown origin, firmly set and projecting 2 ins. above ground. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. position.</p>	
	<p>At the cor. point</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, and in a mound of stone, 2½ ft. base, to top, with brass cap mkd.</p>	

Dependent Resurvey of a Portion of the W Bdy. (Second Guide Meridian East) of T 27 N, R 9 E, Gila and Salt River Mer., Ariz.

CHAINS

T28N	
R8E	R9E
S36	S31
S 1	S 6
T27N	
1982	

Deposit the local rebar alongside the iron post.

Cor. is located in an abandoned portion of a fence line extending E and W along the Tp. line and located in open, flat land.

From this point the 1/4 sec. cor. of secs. 31 and 36, Tps. 28 N, Rs. 8 and 9 E, bears N 0°12' W, 40.02 chs. dist., monumented with a limestone, 18 x 12 x 8 ins., firmly set and projecting 1 in. above ground, in a scattered mound of stone, mkd. 31 on E face, 1/4 36 on W face, and X on top.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T28N	
1/4	
R8E	R9E
S36	S31

1982

Deposit original stone alongside iron post.

Drive steel fence post alongside the cor.

Cor. is located in the open, on slight N slope.

From this same point, the cor. of secs. 1, 2, 35 and 36, Tps. 27 and 28 N, Rs. 8 E, bears N 89°34' W, 80.01 chs. dist., monumented with an iron post, 3 ins. diam., projecting 13 ins. above ground, in a scattered mound of stone, with brass cap mkd.

R8E	
T28N	
S35	S36
S 2	S 1
T27N	

1916

Rebuild a mound of stone to W.

Cor. is located 30 ft. S of the center of a gravel road bearing E and W.

The intervening 1/4 sec. cor. was searched for but not found.

Dependent Resurvey of a Portion of the N Bdy.,
T 27 N, R 9 E, Gila and Salt River Mer., Arizona

Dependent Resurvey of a Portion of the N Bdy.,
T 27 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS

(Reestablishment of the Survey Executed by
Theodore O. Johnston, U.S. Surveyor, and Philip L. Inch,
U.S. Transitman, in 1916)

From the cor. of secs. 5, 6, 31 and 32, Tps. 27 and 28 N,
Rs. 9 E, monumented with an iron post, 36 ins. long, 3
ins. diam., loosely set in a scattered mound of stone,
with brass cap mkd.

T28N R9E	
S31	S32
S6	S5
T27N	
1916	

At the cor. point

Reset the same iron post 8 ins. in the ground, in a mound
of stone, 3½ ft. base, to top.

Add the marks 1982 to the brass cap.

Cor. is located in a barbed wire fence extending E and W,
along the Tp. line.

From this point the cor. of sec. 4, 5, 32 and 33,
Tps. 27 and 28 N, Rs. 9 E, bears S 89°42' E, 80.04 chs.
dist., monumented with an iron post, 3 ins. diam., firmly
set and projecting 24 ins. above ground, in a mound of
stone, 2½ ft. base, 6 ins. high, with brass cap mkd.

T28N R9E	
S32	S33
S5	S4
T27N	
1916	

Cor. is located in a barbed wire fence extending E and W
along the Tp. line, near the top of the W bank of a large
ravine.

The intervening 1/4 sec. cor. was searched for but not
found.

N 89°41' W, bet. secs. 6 and 31.

Along a barbed wire fence line in slightly rolling, open
land.

8.02 Intersect the line offset 100 ft. easterly from the
center line of U.S. Highway No. 89, as established in
1938. This point was used to control alignment of the
western edge of lot 11, sec. 6.

8.12 Intersection of the right-of-way line offset 100 ft.
easterly from the center line of U.S. Highway No. 89, N
of the Tp. line, monumented with an aluminum tablet, 3
ins. diam., set flush in a concrete base, 6 ins. diam.,
projecting 5 ins. above ground, mkd.

ADOT HIGHWAY DIV.
1976

Dependent Resurvey of a Portion of the N Bdy.,
T 27 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>Monument is located S 20° W, 2 lks. dist. from barbed wire fence cor. Fence line extends E and W along the Tp. line and N 20° E, along the line offset 100 ft. easterly from the center line of U.S. Highway No. 89, north of the Tp. line.</p> <p>The alignment of the highway center line N of the Tp. line was shifted an offset distance of 6 ft. to the West in 1976 as shown on Drawing No. D-3-T-601, sheet 7 of 37, on file with Arizona Department of Transportation, Plans, Phoenix, Arizona. This 1976 alignment does not apply to the highway south of the Tp. line.</p>	
8.44	Cor. of fence extending S 20° W only, along the line offset 75 ft. easterly from the center line of U.S. Highway No. 89, S of the Tp. line.	
9.74	Center of asphalt pavement of U.S. Highway No. 89, 58 lks. wide, bears N 20° E and S 20° W.	
10.84	Cor. of fence extends S 20° W only, along the line offset 75 ft. westerly from the center line of U.S. Highway No. 89, S of the Tp. line.	
11.33	Intersect line offset 100 ft. westerly from the center line of U.S. Highway No. 89, N of the Tp. line. A right-of-way point, bears S 20° W, 1 lk. dist., monumented with an aluminum tablet, 3 ins. diam., set flush in a concrete base, 6 ins. diam., projecting 4 ins. above ground, mkd.	
	<p>ADOT HIGHWAY DIV.</p> <p>•</p> <p>1976</p>	
	<p>Monument is located S 20° W, 2½ lks. dist. from a fence cor. Barbed wire fence line extends E and W along Tp. line and N 20° E, along the line offset 100 ft. westerly from the center line of U.S. Highway No. 89, N of the Tp. line.</p>	
19.71	<p>Point for the E 1/16 sec. cor. of secs. 6 and 31.</p> <p>Set an aluminum post, 20 ins. long, 1 in. diam., 2 ins. into a drillhole, a total of 5 ins. below ground surface, secured with a concrete base, and in a mound of stone, 3½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T28N R9E E 1/16 $\frac{S31}{S 6}$ T27N 1982</p> <p>Cor. is located in a barbed wire fence extending E and W along the Tp. bdy., and located in open land on a slight NW slope.</p>	

Dependent Resurvey of a Portion of the N Bdy.,
T 27 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS		
39.42	<p>The 1/4 sec. cor. of secs. 6 and 31, monumented with a limestone, 13 x 6 x 5 ins. lying loose near the center of a slightly scattered mound of stone, 4 ft. base, 1 ft. high, mkd. 1/4. The stone was not mentioned in the original notes but was found by Charles Dryden with the original iron post as shown on page 10 of the survey of the SW 1/4 SE 1/4 of sec. 6, dated 7/31/61, on file in the private records of Arizona Engineering Company, Flagstaff, Arizona. The iron post has been subsequently removed without destruction to the mound.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T28N R9E 1/4 $\frac{S31}{S6}$ T27N 1982</p> <p>Deposit original stone alongside iron post.</p> <p>Cor. is located in a barbed wire fence extending E and W along the Tp. bdy., and located in open land on a slight N slope.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 89°50' W, beginning new measurement.</p> <p>Along barbed wire fence, in open, slightly rolling land.</p>	
7.00	Center of wash, drains N.	
38.23	The cor. of Tps. 27 and 28 N, Rs. 8 and 9 E.	
<p>Dependent Resurvey of a Portion of the Subdivisional Lines, T 27 N, R 9 E, Gila and Salt River Mer., Arizona</p>		
<p>(Reestablishment of the Survey Executed by Theodore O. Johnston, U.S. Surveyor, and Philip L. Inch, U.S. Transitman, in 1916)</p>		
<p>From the cor. of secs. 5, 6, 7 and 8, monumented with an iron post, 2 ins. diam., firmly set and projecting 15 ins. above ground, in a scattered mound of stone, with brass cap mkd.</p>		
<p>T27N R9E $\frac{S6}{S7} \mid \frac{S5}{S8}$ 1916</p>		
<p>Rebuilt mound, 3 ft. base, to top, around cor.</p>		
<p>From this point U.S.G.S. triangulation station "PLAINS", bears S 60°56'23" E, 210.988 chs. dist., monumented with a brass tablet set in a concrete stand, ½ ft. high, mkd. PLAINS 1936. A 10 ft. landmark post is set alongside to aid in recovery.</p>		

Dependent Resurvey of a Portion of the Subdivisional Lines
T 27 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>N 0°08' E, bet. secs. 5 and 6.</p> <p>Over flat, open land.</p> <p>20.02 The S 1/16 sec. cor. of secs. 5 and 6, monumented with a 5/8 in. diam. rebar, firmly set and projecting 8 ins. above ground, in a scattered mound of stone. This monument was set by Charles W. Dryden, Sr., L.S. No. 4321, in 1961, as shown in the field notebook of the property survey of the SW 1/4 SE 1/4 of sec. 6, on file at Arizona Engineering Company, Flagstaff, Arizona, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Attach an aluminum cap, 1 1/4 ins. diam., to the top of the rebar, mkd.</p> <p style="text-align: center;">B L M S 1/16 S6 S5 1982</p> <p>from which</p> <p style="padding-left: 40px;">A 1/8 in. diam. rebar, projecting 3 ins. above ground, bears N 14° E, 2.3 lks. dist.</p> <p style="padding-left: 40px;">An aluminum tablet, 3 ins. diam., set flush in concrete base, 8 ins. diam., 5 ins. high. mkd. GRAY . 1976, bears S 79° E, 279.3 lks. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°08' E, beginning new measurement.</p>	
5.10	Power lines, bear N 27° E and S 27° W; begin slight desc.	
20.03	<p>The 1/4 sec. cor. of secs. 5 and 6, monumented with an iron post, 1 in. diam., firmly set and projecting 18 ins. above ground, with a scattered mound of stone to west, and with a brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S 6 S 5 1916</p> <p>from which</p> <p style="padding-left: 40px;">A steel fence cor. post, 8 ft. high, bears NW, 0.8 lks. dist. Chain link fences extend N and W only.</p> <p>This cor. is now designated to also stand for cor. 4, lot 11, sec. 6.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°08' E, beginning new measurement.</p> <p>Along chain link fence, slight desc., open land.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines
T 27 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS		
19.99	<p>The N 1/16 sec. cor. of secs. 5 and 6, monumented with an open end galvanized iron pipe, 1 1/4 ins. diam., firmly set and projecting 11 ins. above ground, in a scattered mound of stone. This monument, of unknown origin, is harmoniously related to existing original cors., and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Cut off the top 5 ins. of the iron pipe and set over it an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stone, 1 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 6 S 5 1982</p> <p>from which</p> <p style="padding-left: 40px;">A nail in the base of a power pole, bears N 71° E, 13.9 lks. dist.</p> <p style="padding-left: 40px;">A steel fence cor. post, bears S 5° W, 46.4 lks. dist. Chain link fences extend S and W only.</p> <p>This cor. is now designated to also stand for cor. 1, lot 11, sec. 6.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°08' E, beginning new measurement.</p>	
19.63	<p>The cor. of secs. 1, 6, 31 and 36.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>S 89°53' W, bet. secs. 6 and 7.</p> <p>Across open, flat land.</p>	
19.99	<p>The E 1/16 sec. cor. of secs. 6 and 7, monumented with a 5/8 in. diam. rebar, projecting 4 ins. from a concrete base, 8 ins. diam., projecting 3 ins. above ground. This monument was set by Charles W. Dryden, Sr., L.S. 4321, in 1961, as shown in the field notebook of the property survey of the SW 1/4 SE 1/4 of sec. 6, on file at Arizona Engineering Company, Flagstaff, Arizona, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Attach an aluminum cap, 1 1/4 ins. diam., to the top of the rebar, mkd.</p> <p style="text-align: center;">B L M E 1/16 $\frac{S 6}{S 7}$ 1982</p> <p>from which</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines
T 27 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A steel fence cor. post, bears N 6° E, 2.3 lks. dist. Chain link fences extend N and W only.</p> <hr/> <p>S 89°53' W, beginning new measurement.</p> <p>Across open, flat land.</p>
17.63	Intersect line offset 100 ft. easterly from the center line of U.S. Highway No. 89. This position was used for the alignment of the western side of lot 11.
19.25	Center line stripe of U.S. Highway No. 89.
19.99	<p>The 1/4 sec. cor. of secs. 6 and 7, monumented with the stump of the original iron post, 1 in. diam., projecting 1 in. from a concrete collar, 5 x 5 ins., inserted and top flush with a concrete base, 2 ft. diam., resting 4 ins. below ground surface.</p> <p>At the cor. point</p> <p>Removed concrete insert with post stump and set into hole an iron post, 18 ins. long, 2½ ins. diam., 22 ins. in the ground, top flush with concrete base, with brass cap mkd.</p> <p style="text-align: center;">T27N R9E 1/4 $\frac{S6}{S7}$ 1982</p> <p>Deposit concrete insert with post stump alongside iron post.</p> <p>from which</p> <p>An aluminum post, 28 ins. long, 1 in. diam., set 6 ins. in the ground, in a mound of stone, 2½ ft. base, 1½ ft. high, for a reference monument, bears S 59° W, 72.6 lks. dist., with cap mkd. T27N R9E 1/4 S7 RM 47.9 FT., with an arrow pointing to the true cor. Monument is located in old right-of-way fence line bearing N 20½° E and S 20½° W.</p> <p>An aluminum post, 28 ins. long, 1 in. diam., set 6 ins. in the ground, in a mound of stone, 2½ ft. base, 1½ ft. high, for a reference monument, bears N 14° W, 75.8 lks. dist., with cap mkd. T27N R9E 1/4 S6 RM 50 FT., with an arrow pointing to the true cor. Monument is located in old right-of-way fence line bearing N 20½° E and S 20½° W.</p> <hr/> <p>West, beginning new measurement.</p> <p>Across open, flat land.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
T 27 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS		
0.47	<p>The intersection with the line offset 75 ft. westerly from the center line of U.S. Highway No. 89, monumented with a wooden post, 5 x 5 ins., the stump of which lies 6 ins. below ground surface. The top portion, mkd. STA. 1921+72 on NE face, and HWY. R. OF W. on SE face, lies nearby. The monument was set in 1938 as shown on right-of-way maps on file with the Arizona Department of Transportation, Flagstaff, Az.</p>	
0.48	<p>Cor. of fences bears S, 3½ lks. dist. Barbed wire fences bear N 20½° E and S 20½° W, along the line offset 75 ft. westerly from the center line of U.S. Highway No. 89, and W along the line bet. secs. 6 and 7.</p>	
37.75	<p>The cor. of secs. 1, 6, 7 and 12, on the west boundary of the Tp.</p>	
<p>Subdivision of Section 6 T 27 N, R 9 E, Gila and Salt River Mer., Arizona</p>		
<p>From the 1/4 sec. cor. of secs. 6 and 7.</p>		
<p>N 0°34' E, on the N and S center line of sec. 6.</p>		
<p>Across open, flat land.</p>		
1.34	<p>Barbed wire fence extending N 20½° E and S 20½° W, along the line offset 75 ft. westerly from the center line of U.S. Highway No. 89.</p>	
12.61	<p>Intersect the S side of a mobile home, 12 x 50 ft., the SW cor. bears N 70° W, 56 lks. dist., the long side bears S 70° E.</p>	
20.03	<p>The center S 1/16 sec. cor. of sec. 6, monumented with a 5/8 in. diam. rebar, projecting 6 ins. above ground, in a concrete base, 8 ins. diam. This monument was set by Charles W. Dryden, Sr., L.S. 4321, in 1961, as shown in the field notebook of the property survey of the SW 1/4 SE 1/4 of sec. 6, on file at Arizona Engineering Company, Flagstaff, Arizona, and is accepted as a careful and faithful determination of the position of the cor.</p>	
<p>At the cor. point</p>		
<p>Attach an aluminum cap, 1 1/4 ins. diam., to the top of the rebar, mkd.</p>		
<p>B L M C S 1/16 S 6 C 1982</p>		
<p>from which</p>		
<p>A steel fence cor. post bears, S 51½° E, 1.7 lks. dist. Chain link fence extends E and S only.</p>		
<p>N 0°35' E, beginning new measurement.</p>		
<p>Across open, flat land.</p>		

Subdivision of Section 6
T 27 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS		
20.03	<p>The center 1/4 sec. cor. of sec. 6, monumented with a 5/8 in. diam. rebar, firmly set and projecting 2 ins. above ground, in a mound of stone, 1 ft. base, 4 ins. high. This monument was set by Charles W. Dryden, Sr., L.S. No. 4321, in 1961, as shown in the field notebook of the property survey of the SW 1/4 SE 1/4 of sec. 6, on file at Arizona Engineering Company, Flagstaff, Arizona, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Attach an aluminum cap, 1 1/4 ins. diam., to the top of the rebar, mkd.</p> <p style="text-align: center;">B L M T27N R9E C 1/4 . S 6 1982</p> <p>Drove steel fence post alongside the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>N 0°29' E, beginning new measurement.</p> <p>Across open, slightly rolling land.</p>	
20.03	<p>Point for the center N 1/16 sec. cor. of sec. 6.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">C N 1/16 S 6 C 1982</p>	
39.91	<p>The 1/4 sec. cor. of secs. 6 and 31 on the north bdy. of the Tp.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 5 and 6.</p> <p>S 89°55' W, on the E and W center line of sec. 6.</p> <p>Along a chain link fence, 6 ft. high, over open land.</p>	
19.84	<p>Point for the center E 1/16 sec. cor. of sec. 6.</p> <p>Set an aluminum post, 20 ins. long, 1 in. diam., 18 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">E 1/16 C-----C S 6 1982</p> <p>from which</p> <p style="text-align: center;">A steel fence post, bears S 45° W, 1.5 lks. dist., chain link fence extends E and W.</p> <p>Cor. is located in a landscaped area, 0.5 lks. N of same chain link fence.</p>	

Subdivision of Section 6
T 27 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS		
20.86	Steel fence cor. Barbed wire fence extends W, chain link fence extends E and N 20° E.	
22.76	Intersect the line offset 100 ft. easterly from the center line of the U.S. Highway No. 89, identical with cor. 3, lot 11, sec. 6.	
	Set an aluminum post, 12 ins. long, 1 in. diam., 1 in. into a crack in bedrock, a total of 3 ins. in the ground, secured with a concrete base, 12 ins. diam., 2 ins. deep, and in a mound of stone, 2½ ft. base, to top, with cap mkd.	
	<p>T27N R9E S6 / COR 3 / LOT 11</p> <hr style="width: 50px; margin: auto;"/> <p>1982</p>	
	Cor. is located in a barbed wire fence line extending E and W.	
23.12	A 5/8 in. diam. rebar, of unknown origin, firmly set and projecting 12 ins. above ground, in a mound of stone, 1 ft. base, 5 ins. high.	
23.17	Fence cor., barbed wire fences extend E, N 20½° E and S 20½° W.	
39.68	The center 1/4 sec. cor. of sec. 6. _____	
	S 89°55' W, beginning new measurement. Across open, slightly rolling land.	
38.09	The 1/4 sec. cor. of secs. 1 and 6 on the west bdy. of the Tp.	
	<p>NE 1/4 of Section 6</p> <hr style="width: 50px; margin: auto;"/>	
	From the center E 1/16 sec. cor. of sec. 6. N 0°18' E, on the N and S center line of the NE 1/4 of sec. 6. Across open, flat land, through a highway maintenance yard.	
20.00	Point for the NE 1/16 sec. cor., at intersection with the E and W center line of the NE 1/4, sec. 6. Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.	
	<p>NE 1/16 S6 1982</p>	
	Drove steel post alongside cor.	
39.76	The E 1/16 sec. cor. of secs. 6 and 31, on the north bdy. of the Tp. _____	

Subdivision of Section 6
T 27 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>From the N 1/16 sec. cor of secs. 5 and 6.</p> <p>S 89°57' W, on the E and W center line of the NE 1/4 of sec. 6.</p>
15.33	<p>Intersect the line offset 100 ft. easterly from the center line of U.S. Highway No. 89, point for cor. 2, lot 11, sec. 6.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 16 ins. in the ground, in a mound of stone, 4 ft. base, to top, with cap mkd.</p> <div style="text-align: center;"> <p>T27N R9E</p> <p>S 6</p> <hr style="width: 50px; margin: 0 auto;"/> <p>COR 2</p> <p>LOT 11</p> <p>1982</p> </div> <p>Cor. is located 40.5 lks. E of the old right-of-way fence extending N 20½° E and S 20½° W.</p>
19.78	The NE 1/16 sec. cor. of sec. 6.
39.55	The center N 1/16 sec. cor. of sec. 6.
<hr/> <p>SE 1/4 of Section 6</p> <hr/>	
	<p>From the E 1/16 sec. cor. of secs. 6 and 7.</p> <p>N 0°21' E, on the N and S center line of the SE 1/4 of sec. 6.</p> <p>Across open, flat land, along a chain link fence.</p>
20.03	<p>The SE 1/16 sec. cor. of sec. 6, monumented with a 5/8 in. diam. rebar, projecting 8 ins. above the ground, in a concrete base, 8 ins. diam., This monument was set by Charles W. Dryden, Sr., L.S. 4321, in 1961, as shown in the field notebook of the property survey of the SW 1/4 SE 1/4 of sec. 6, on file with Arizona Engineering Company, Flagstaff, Arizona, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Attach an aluminum cap, 1 1/4 ins. diam., to the top of the rebar, mkd.</p> <div style="text-align: center;"> <p>B L M</p> <p>SE 1/16 S 6</p> <p>1982</p> </div> <p>Drove fence post, projecting 4 ft. above ground, alongside cor.</p> <p>from which</p> <p style="padding-left: 40px;">A fence cor., bears S 19° W, 21.5 lks. dist. Barbed wire fence extends W and S only.</p> <hr style="width: 20%; margin: 0 auto;"/>

Subdivision of Section 6
T 27 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS		
	N 0°21' E, beginning new measurement. Across open, flat land.	
20.03	The center E 1/16 sec. cor. of sec. 6. <hr/>	
	From the S 1/16 sec. cor. of secs. 5 and 6. S 89°55' W, on the E and W center line of the SE 1/4 of sec. 6. Across open, slightly rolling land.	
2.60	Power lines, bear N 27° E and S 27° W.	
7.70	Land changes from rolling to flat.	
19.92	The SE 1/16 sec. cor. of sec. 6. <hr/>	
	S 89°55' W, beginning new measurement.	
11.89	Center line of U.S. Highway No. 89, bears N 20½° E and S 20½° W.	
19.92	The center S 1/16 sec. cor. of sec. 6 <hr/>	
Metes-and-Bounds Survey of Lot 11, Section 6 T 27 N, R 9 E, Gila and Salt River Mer., Arizona		
	From cor. 1, lot 11, sec. 6, identical with the N 1/16 sec. cor. of secs. 5 and 6. S 89°57' W, on line 1-2, lot 11, sec. 6, identical with the E and W center line of the NE 1/4 of sec. 6.	
15.33	Cor. 2, lot 11, sec. 6, at intersection with the line offset 100 ft. easterly from the center line of U.S. Highway No. 89, heretofore described. <hr/>	
	S 20°27' W, on line 2-3, lot 11, sec. 6, identical with the line offset 100 ft. easterly from the center line of U.S. Highway No. 89.	
21.36	Cor. 3, lot 11, sec. 6, at intersection of the E and W center line of sec. 6, with the line offset 100 ft. easterly from the center line of U.S. Highway No. 89, heretofore described. <hr/>	
	N 89°55' E, on line 3-4, lot 11, sec. 6, identical with the E and W center line of sec. 6.	
2.92	The center E 1/16 sec. cor. of sec. 6.	
22.76	Cor. 4, lot 11, sec. 6, identical with the 1/4 sec. cor. of secs. 5 and 6, heretofore described. <hr/>	

Metes-and-Bounds Survey of Lot 11, Section 6
T 27 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS		
19.99	<p>N 0°08' E, on line 4-1, lot 11, sec. 6, indential with the sec. line bet. secs. 5 and 6.</p> <p>Cor. 1, lot 11, sec. 6.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>Sec. 6 of T 27 N, R 9 E, surrounds the settlement of Gray Mountain, Arizona. The elevation varies from 4,920 to 5,040 feet above sea level. The soil varies from sandy loam to eroded rock outcroppings. The vegetation is native grasses and cacti. There is no timber or undergrowth. Dainage is northerly through small washes.</p> <p>U.S. Highway No. 89 crosses the E $\frac{1}{2}$ of the section in a northeasterly direction. A paved road bears northwesterly from the highway at Gray Mountain. A power line crosses the SE portion of the section. A landing strip is in the SW $\frac{1}{4}$ of the section.</p> <p>The mean magnetic bearing in the section is $14\frac{1}{2}^{\circ}$ E as determined from a U.S.G.S. quadrangle map.</p> <hr/>	

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Dennis K. Mc Kay, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 25th day of February, 1982, (I) ~~(We)~~ have dependently resurveyed a portion of the West boundary (Second Guide Meridian East) and a portion of the North boundary and subdivisional lines and surveyed subdivisions and metes-and-bounds survey in section 6, Township 27 North, Range 9 East.

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 5, 1983 (Date) Dennis K. Mc Kay (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Dennis C. Cook
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the West boundary (Second Guide Meridian East), the North boundary and the subdivisional lines and the survey of the subdivisions and metes-and-bounds survey in section 6, Township 27 North, Range 9 East, Gila and Salt River Meridian, Arizona.

executed by Dennis K. Mc Kay, Cadastral Surveyor
having been critically examined and found correct, are hereby approved.

APR 05 1983 (Date) James P. Kelley (Chief Cadastral Surveyor of Arizona)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in T. 27 N., R. 9 E., G&SRM, Arizona, is a true copy of the original field notes.

(Date) (Chief Cadastral Surveyor of Arizona)