

BOOK 5 211

1

ORIGINAL

UNITED STATES

DEPARTMENT OF THE INTERIOR

BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION

OF THE

SOUTH BOUNDARY (FIRST STANDARD PARALLEL SOUTH)

AND A

PORTION OF THE SUBDIVISIONAL LINES

OF

TOWNSHIP 5 SOUTH, RANGE 22 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Will C. Gabonay, Cadastral Surveyor

Under special instructions dated January 4, 1983, approved January 4, 1983

which provided for the surveys included under Group Number 636 and assignment  
instructions dated January 4, 1983

Survey commenced January 5, 1983

Survey completed January 14, 1985

INDEX DIAGRAM

TOWNSHIP 5 SOUTH , RANGE 22 EAST

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
				11	
30	29	28	27	10 26	7 25
				9	
31	32	33	34	8 35	6 36
				6 3	

T 5 S, R 22 E, Gila and Salt River Mer., Arizona

## CHAINS

The following field notes are those of the dependent re-survey of a portion of the south boundary (First Standard Parallel South) and a portion of the subdivisional lines of Township 5 South, Range 22 East, Gila and Salt River Meridian, Arizona.

Philip Contzen surveyed the south boundary (First Standard Parallel South) and surveyed the boundaries of sections 26 and 35, in 1900. The San Carlos Indian Reservation was surveyed through sections 26 and 35 by Paul Riecker, in 1883, resurveyed by Charles E. Walker, in 1887, and again by Ray Harpin and Douglas A. Cody, in 1973-74.

The survey was executed in accordance with specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 636, Arizona, dated January 4, 1983.

The directions of lines were determined by direct solar observations and refer to the true meridian. Angles and distances were measured electronically using a Hewlett Packard 3820 Total Station instrument.

Prior to restoration of any corners, all necessary lines of the original survey were retraced and diligent search was made for any evidence of the original monuments and other calls of the official record. Identified corners were remonumented in their original positions. Lost corners were reestablished at proportionate positions, but not until exhausting every reasonable possibility of finding direct evidence of the control of each corner.

The geographic position of the witness standard corner of sections 35 and 36, as determined from a tie to the U.S.C.&G.S. triangulation station "STEER", located in section 11, T 6 S, R 22 E, is as follows:

Latitude: 32°56'50.55" N Longitude: 110°03'03.90" W

The mean magnetic declination is 13½° E.

---

Dependent Resurvey of a Portion of the S Bdy.  
(First Standard Parallel South) of  
T 5 S, R 22 E, Gila and Salt River Mer., Arizona

---

Reestablishment of the survey executed by  
Philip Contzen, in 1900

---

Beginning at the witness stan. cor. of secs. 35 and 36, T 5 S, R 22 E, monumented with a sandstone, 14 x 12 x 3 ins., set 6 ins. in the ground, mkd. WCSC on N face, 5 grooves on the W face and 1 groove on the E face, from which the original bearing trees

A tesota, 6 ins. diam., bears N 11¾° E, 150 lks. dist., with barely visible marks of WC SC T5S R22E S36 BT.


A tesota, 6 ins. diam., bears N 50°30' W, 157 lks. dist., with no visible marks.

At the cor. point

Dependent Resurvey of a Portion of the S Bdy.  
 (First Standard Parallel South) of  
 T 5 S, R 22 E, Gila and Salt River Mer., Arizona

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



1983

Deposit the original mkd. stone alongside the iron post.

Raise a mound of stone, 2½ ft. base, 18 ins. high, N of cor.

From the witness cor., National Geodetic Survey triangulation station, "STEER 1945", bears S 39°50'57" W, 129.242 chs. dist., monumented with a stan. brass cap, 3½ ins. diam., set in an iron pipe, 10 ins. above ground, and in a mound of stone, 3 ft. base, mkd. USC&GS STEER 1945 and a triangle.

Witness cor. is located 4.5 chs. W of a ridge running northerly and southerly.

West, along the S bdy. of sec. 36.

Over moderately hilly terrain, with scattered mesquite, creosote and sagebrush.

0.50

True point for the stan. cor. of secs. 35 and 36, falls in a wash, 35 lks. wide, draining N 15° E. Point unsuitable for monumentation.

West, along the S bdy. of sec. 35.


Over moderately hilly terrain, with scattered mesquite, creosote and sagebrush.

18.90

Intersect the E bdy. of the San Carlos Indian Reservation.

Point for the closing cor. of secs. 1 and 35.

Set a stainless steel post, 30 ins. long, 2½ ins. diam., 27 ins. in the ground, with a magnetic cap deposited at base and brass cap mkd.



Cor. is located 1 lk. E of a N-S fence.

From this point, the 10 Mi. Cor. bears N 0°14' W, 4.02 chs. dist., monumented with an iron post, 2½ ins. diam., projecting 7 ins. above ground, with brass cap mkd. as described in the 1974 resurvey of a portion of the E bdy. of the San Carlos Indian Reservation. A mound of stone, 3 ft. base, 6 ins. high, is W of cor. Cor. is located in a fence line, bears N and S.

Dependent Resurvey of a Portion of the S Bdy.  
 (First Standard Parallel South) of  
 T 5 S, R 22 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>From this same point, the 10½ Mi. Cor. bears S 0°14' E, 36.04 chs. dist., monumented with an iron post, 2½ ins. diam., projecting 3 ins. above ground, with brass cap mkd. as described in the 1974 resurvey of a portion of the E bdy. of the San Carlos Indian Reservation. A mound of stone, 3 ft. base, 6 ins. high, is W of cor. Cor. is located in a fence line, bears N and S.</p>	
25.85	<p>The closing cor. of secs. 1 and 2, T 6 S, R 22 E, bears North 2 lks. dist., monumented with an iron post, 2 ins. diam., 8 ins. above ground, with a mound of stone, 3½ ft. base, 2 ft. high, S of cor., with brass cap mkd.</p>	
	<p style="text-align: center;">T5S R22E                  S35  <hr style="width: 50px; margin: auto;"/>                 S 2   S 1                  T6S R22E                  C C                  1924</p>	
	<p>Add the marks 1983 on the brass cap.</p> <p>Cor. falls on N side of a draw, drains NE.</p>	
39.96	<p>The stan. ¼ sec. cor. of sec. 35, monumented with a sandstone, 18 x 10 x 8 ins., set 10 ins. in the ground, with no marks visible, from which the original bearing tree</p>	
	<p style="padding-left: 40px;">A scrub mesquite, 10 ins. diam., bears N 74¼° E, 146.5 lks. dist., with visible blaze only.                  (Record: 145 lks. dist.)</p>	
	<p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 25 ins. in the ground, with cap mkd.</p>	
	<p style="text-align: center;">S C                  T5S R22E                  ¼ S35  <hr style="width: 50px; margin: auto;"/>                 1983</p>	
	<p>Bury the original mkd. stone alongside the aluminum post.</p> <p>Raise a mound of stone, 3 ft. base, 18 ins. high, N of cor.</p>	
	<p style="text-align: center;">_____</p> <p>S 89°59' W, beginning new measurement.</p>	
39.85	<p>The stan. cor. of secs. 34 and 35, monumented with a quartzite stone, 18 x 8 x 8 ins. high, mkd. SC on the N, 2 grooves on the E and 4 grooves on the W face.</p>	
	<p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 13 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.</p>	
	<p style="text-align: center;">T5S R22E                  S C                  S34   S35  <hr style="width: 50px; margin: auto;"/>                 1983</p>	

Dependent Resurvey of a Portion of the S Bdy.  
 (First Standard Parallel South) of  
 T 5 S, R 22 E, Gila and Salt River Mer., Arizona

CHAINS

Bury the original mkd. stone alongside the aluminum post.

Cor. falls on S slope of ridge.

A wash, 20 lks. wide, draining NE, bears North, 120 lks. dist.

---

Dependent Resurvey, a Portion of the Subdivisional Lines  
 T 5 S, R 22 E, Gila and Salt River Mer., Arizona

---

Reestablishment of the survey executed by  
 Philip Contzen, in 1900

---

From the true point for the stan. cor. of secs. 35 and 36, on the S bdy. of the Tp., hereinbefore described.

N 0°01' W, bet. secs. 35 and 36.

Over gently rolling terrain, through creosote.

40.13

The ¼ sec. cor. of secs. 35 and 36, is determined at record bearing and dist. from the original bearing trees

A mesquite, 10 ins. diam., bears S 86¾° E,  
 230 lks. dist., marks visible are /4.

A mesquite, 8 ins. diam., bears N 4¼° W, 83  
 lks. dist., mkd. ¼ S35 BT.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.

T5S R22E  
 ¼  
 S35 | S36  
 1983

from which a new bearing tree

A forked mesquite, 8 ins. diam., bears S 8° E,  
 51 lks. dist., mkd. ¼ S36 BT.

---

N 0°05' W, beginning new measurement.

20.06

Point for the N 1/16 sec. cor. of secs. 35 and 36.

At the cor. point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.

T5S R22E  
 N 1/16  
 S35 | S36  
 1985

Raise a mound of stone, 2½ ft. base, 1 ft. high, W of cor.

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 5 S, R 22 E, Gila and Salt River Mer., Arizona

CHAINS

40.12

The cor. of secs. 25, 26, 35 and 36, monumented with a granite stone, 14 x 12 x 10 ins., set 12 ins. in the ground, mkd. with 1 notch on the E and S edges, from which original bearing trees

A mesquite stump, 4 ins. diam., bears S 25° E, 64 lks. dist., no marks visible.

A mesquite, 6 ins. diam., bears S 62¼° W, 113.5 lks. dist., no marks visible.

A mesquite, 6 ins. diam., bears N 46½° W, 82 lks. dist., no marks visible.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T5S R22E	
S26   S25	
S35   S36	
1983	

from which new bearing trees

A mesquite, 8 ins. diam., bears S 81° E, 188 lks. dist., mkd. T5S R22E S36 BT.

A mesquite, 6 ins. diam., bears S 19° W, 35 lks. dist., mkd. T5S R22E S35 BT.

Bury the original mkd. stone alongside the iron post.

A wash, 33 lks. wide, draining northerly, bears North, 36 lks. dist.

---

N 0°06' W, bet. secs. 25 and 26.

Over hilly terrain, through creosote.

40.14

Point for the ¼ sec. cor. of secs. 25 and 26, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 72 ins. long, ¾ in. diam., 68 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with cap mkd.

T5S R22E	
¼	
S26   S25	
1983	

from which

An aluminum post, 24 ins. long, ¾ in. diam., set 20 ins. in the ground, for a reference monument, bears N 20°05' E, 76.19 ft. dist., with cap mkd. RM T5S R22E ¼ S25 76.19 FT 1983, and an arrow pointing to the cor.

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 5 S, R 22 E, Gila and Salt River Mer., Arizona

	CHAINS								
	80.28	<p>An aluminum post, 24 ins. long, <math>\frac{3}{4}</math> in. diam., set 20 ins. in the ground, for a reference monument, bears N <math>49^{\circ}03'</math> W, 76.09 ft. dist., with cap mkd. RM T5S R22E <math>\frac{1}{4}</math> S26 76.09 FT 1983, and an arrow pointing to the cor.</p> <p>Cor. falls in the center of Black Rock Wash, 80 lks. wide, drains N <math>80^{\circ}</math> E.</p> <p>The cor. of secs. 23, 24, 25 and 26, monumented with a granite stone, 18 x 10 x 10 ins., set 6 ins. in the ground, mkd. with 2 notches on the S, and 1 notch on the E edge, with a scattered mound of stone, <math>2\frac{1}{2}</math> ft. base, 6 ins. high, to the W, from which original bearing trees</p> <p>A mesquite stump, 5 ins. diam., bears N <math>17\frac{1}{2}^{\circ}</math> E, 235 lks. dist., no marks visible. (Record: 232 lks. dist.)</p> <p>A mesquite, 4 ins. diam., bears S <math>71^{\circ}</math> E, 192 lks. dist., no marks visible. (Record: 194 lks. dist.)</p> <p>A mesquite, 6 ins. diam., bears S <math>51^{\circ}</math> W, 217 lks. dist., no marks visible. (Record: 219 lks. dist.)</p> <p>At the cor. point</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 32 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <p>T5S R22E</p> <table border="1" style="margin: auto;"> <tr> <td>S23</td> <td> </td> <td>S24</td> </tr> <tr> <td>S26</td> <td> </td> <td>S25</td> </tr> </table> <p>1983</p> </div> <p>Bury the original mkd. stone alongside the aluminum post.</p> <p>Raise a mound of stone, <math>2\frac{1}{2}</math> ft. base, 18 ins. high.</p> <p>A wash, 60 lks. wide, draining easterly, bears South, 225 lks. dist.</p>	S23		S24	S26		S25	
S23		S24							
S26		S25							
	39.90	<p>From the stan. cor. of secs. 34 and 35, on the S bdy. of the Tp., hereinbefore described.</p> <p>N <math>0^{\circ}12'</math> W, bet. secs. 34 and 35.</p> <p>Over hilly, broken terrain of washes, gulches and ridges, through creosote and sagebrush.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 34 and 35, monumented with a granite stone, 18 x 8 x 9 ins., set 6 ins. in the ground, mkd. <math>\frac{1}{4}</math> S34 on W face, 35 on E face, from which original bearing trees</p> <p>A mesquite stump, 6 ins. diam., bears N <math>62\frac{1}{2}^{\circ}</math> E, 55.5 lks. dist., marked with a blaze, but no visible marks.</p> <p>A mesquite, 10 ins. diam., bears S <math>16\frac{1}{4}^{\circ}</math> W, 148 lks. dist., mkd. <math>\frac{1}{4}</math> S34 BT.</p> <p>At the cor. point</p>							

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 5 S, R 22 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 25 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T5S R22E <math>\frac{1}{4}</math> S34   S35 1983</p> <p>Bury the original mkd. stone alongside the aluminum post.</p> <p>Raise a mound of stone, 2½ ft. base, 1 ft. high, N of cor.</p> <p>A wash, 20 lks. wide, draining N 70° E, bears South, 135 lks. dist.</p> <hr/> <p>N 0°12' W, beginning new measurement.</p>	
40.08	<p>The cor. of secs. 26, 27, 34 and 35, monumented with a granite stone, 18 x 7 x 7 ins., set 6 ins. in the ground, mkd. with 1 notch on the S and 2 notches on the E edges, from which an original bearing tree</p> <p style="text-align: center;">A mesquite 12 ins. diam., bears S 37° W, 51 lks. dist., mkd. T5S R22E S34 BT. (Record: 50 lks. dist.)</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R22E S27   S26 S34   S35 1983</p> <p>Bury the original mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 1½ ft. base, 1 ft. high, W of cor.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S 89°32' W, bet. secs. 26 and 35.</p> <p>Over relatively level terrain, with gullies and washes, through creosote.</p>	
19.16	<p>Intersect the E bdy. of the San Carlos Indian Reservation.</p> <p>Point for the closing cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with magnetic cap deposited at base, and cap mkd.</p> <p style="text-align: center;">T5S R22E SCIR CC S26   S26 CC S35   S35 1985</p> <p>Cor. is located in a N-S fence line.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 5 S, R 22 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>From this point, the 9 Mi. Cor. bears N 0°13' W, 4.16 chs. dist., monumented with an iron post, 2½ ins. diam., projecting 3 ins. above ground, with brass cap mkd. as described in the 1974 resurvey of a portion of the E bdy. of the San Carlos Indian Reservation. A mound of stone, 2½ ft. base, 6 ins. high, is W of cor. Cor. is located in a fence line, bears N and S.</p> <p>From this same point, the 9½ Mi. Cor. bears S 0°13' E, 35.93 chs. dist., monumented with an iron post, 2½ ins. diam., projecting 3 ins. above ground, with brass cap mkd. as described in the 1974 resurvey of a portion of the E bdy. of the San Carlos Indian Reservation. A mound of stone, 2½ ft. base, 6 ins. high, is W of cor. Cor. is located in a fence line, bears N and S.</p>	
40.08	<p>The ¼ sec. cor. of secs. 26 and 35, monumented with a granite stone, 18 x 12 x 6 ins., set 8 ins. in the ground, mkd. ¼ S26 on N face and 35 on S face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R22E ¼ S26 S35 1983</p> <p>from which</p> <p style="text-align: center;">A mesquite, 5 ins. diam., bears S 54° E, 40 lks. dist., mkd. ¼ S35 BT.</p> <p>Bury the original mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 89°57' W, beginning new measurement.</p>	
39.96	<p>The cor. of secs. 26, 27, 34 and 35, hereinbefore described.</p> <hr style="width: 50%; margin: 10px auto;"/>	
40.16	<p>N 0°19' W, bet. secs. 26 and 27.</p> <p>Over relatively flat, broken terrain, through creosote.</p> <p>Point for the ¼ sec. cor. of secs. 26 and 27, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T5S R22E ¼ S27   S26 1983</p> <p>Cor. falls on S edge of Black Rock Wash, 140 lks. wide, drains S 85° E.</p>	
47.00	<p>Top of bluff, edge bears E and W.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 5 S, R 22 E, Gila and Salt River Mer., Arizona

CHAINS												
80.32	<p>The cor. of secs. 22, 23, 26 and 27, monumented with a granite stone, 16 x 12 x 8 ins., set 8 ins. in the ground, mkd. with 2 notches on the S and E edges, from which an original bearing tree</p> <p style="padding-left: 40px;">A tesota, 8 ins. diam., bears N 31° W, 188 lks. dist., mkd. T5S R22E BT.</p> <p>At the cor. point</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <p>T5S R22E</p> <table style="margin: auto;"> <tr> <td>S22</td> <td> </td> <td>S23</td> </tr> <tr> <td>S27</td> <td> </td> <td>S26</td> </tr> </table> <p>1983</p> </div> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 6 ins. diam., bears N 33° E, 143 lks. dist., mkd. T5S R22E S23 BT.</p> <p style="padding-left: 40px;">A mesquite, 6 ins. diam., bears S 74° E, 81.5 lks. dist., mkd. T5S R22E S26 BT.</p> <p>Bury original mkd. stone alongside the aluminum post.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S 89°47' W, bet. secs. 23 and 26.</p> <p>Over relatively level terrain.</p>	S22		S23	S27		S26					
S22		S23										
S27		S26										
19.34	<p>Intersect the E bdy. of the San Carlos Indian Reservation.</p> <p>Point for the closing cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with a magnetic cap deposited at base and cap mkd.</p> <div style="text-align: center;"> <p>T5S R22E</p> <p>SCIR</p> <table style="margin: auto;"> <tr> <td>CC</td> <td>S23</td> <td> </td> <td>S23</td> <td>CC</td> </tr> <tr> <td></td> <td>S26</td> <td> </td> <td>S26</td> <td></td> </tr> </table> <p>1985</p> </div> <p>Cor. is located in a N-S fence line.</p> <p>From this point, the 8 Mi. Cor. bears N 0°14' W, 3.83 chs. dist., monumented with an iron post, 2 1/2 ins. diam., projecting 3 ins. above ground, with brass cap mkd. as described in the 1974 resurvey of a portion of the E bdy. of the San Carlos Indian Reservation. A mound of stone, 2 1/2 ft. base, 6 ins. high, is W of cor. Cor. is located in a fence line, bears N and S.</p> <p>From this same point, the witness 8 1/2 Mi. Cor. bears S 0°14' E, 35.29 chs. dist., monumented with an iron post, 2 1/2 ins. diam., projecting 4 ins. above ground, with brass cap mkd. as described in the 1974 resurvey of a portion of the E bdy. of the San Carlos Indian Reservation. A mound of stone, 1 1/2 ft. base, 1 ft. high, is W of cor. Cor. is located in a fence line, bears N and S.</p>	CC	S23		S23	CC		S26		S26		
CC	S23		S23	CC								
	S26		S26									

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 5 S, R 22 E, Gila and Salt River Mer., Arizona

CHAINS		
40.17	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 23 and 26, monumented with a granite stone, 18 x 16 x 14 ins., set 8 ins. in the ground, mkd. with <math>\frac{1}{4}</math> S23 on N face and 26 on S face, from which an original bearing tree</p> <p style="padding-left: 40px;">A mesquite, 8 ins. diam., bears S 13° E, 296 lks. dist., mkd. <math>\frac{1}{4}</math> S6 BT.</p> <p>At the cor. point</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T5S R22E <math>\frac{1}{4}</math> <math>\frac{S23}{S26}</math> 1983</p> <p>Bury the original mkd. stone alongside the aluminum post.</p> <p>Raise a mound of stone, 2<math>\frac{1}{2}</math> ft. base, 1 ft. high, W of cor.</p> <p>A wash, draining E, bears South, 79 lks. dist.</p> <p>A wash, 5 lks. wide, draining S 45° E, bears East, 34 lks. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S 89°51' W, beginning new measurement.</p>	
40.16	<p>The cor. of secs. 22, 23, 26 and 27, hereinbefore described.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The land encompassed in this survey is located about 8 miles southwest of the town of Fort Thomas, Arizona. Black Rock Wash is the predominant wash in the area and runs through a part of this survey. The average elevation is about 3,100 feet above sea level, with the terrain ranging from level and brushy with scattered mesquite and creosote, to broken and open, with hills, gullies and dry washes formed by erosion. The soil is clay-like.</p> <p>The area is principally used for livestock grazing.</p> <p>No mining activity was noticed.</p> <p>The mean magnetic declination for the area is 13<math>\frac{1}{2}</math>° E, with negligible local attraction.</p> <hr/>	



CERTIFICATE OF SURVEY

I, Will C. Gabonay, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 4th day of January, 1983, I have dependently resurveyed a portion of the south boundary (First Standard Parallel South) and a portion of the subdivisional lines of Township 5 South, Range 22 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

July 15, 1985  
(Date)

Will C. Gabonay  
(Cadastral Surveyor)

\_\_\_\_\_  
(Date)

\_\_\_\_\_  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

Arizona State Office  
Bureau of Land Management  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the south boundary (First Standard Parallel South) and a portion of the subdivisional lines of Township 5 South, Range 22 East, of the Gila and Salt River Meridian, Arizona, executed by Will C. Gabonay, having been critically examined and found correct, are hereby approved.

JUL 24 1985  
(Date)

James P. Kelley  
(Chief Cadastral Surveyor of Arizona)