

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF

A PORTION OF THE FIRST STANDARD PARALLEL NORTH,

ON THE SOUTH BOUNDARY OF TOWNSHIP 5 NORTH, RANGE 4 WEST;

A PORTION OF THE FIRST GUIDE MERIDIAN WEST BETWEEN RANGES 4 AND 5 WEST;

AND A PORTION OF THE EAST BOUNDARY AND SUBDIVISIONAL LINES

AND THE SURVEY OF SUBDIVISION

IN SECTIONS 13, 21 AND 29

AND THE METES-AND-BOUNDS SURVEY

OF TRACTS 37, 38 AND 39

TOWNSHIP 4 NORTH, RANGE 4 WEST

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY

Paul L. Reeves, Cadastral SurveyorStephen J. Malloy, Cadastral Surveyor

Under special instructions dated November 8, 1985, approved November 8, 1985

, which provided for the surveys included under Group Number
674, and assignment instructions dated November 12, 1985.

Survey commenced November 12, 1985

Survey completed January 16, 1986

BOOK 5223

INDEX DIAGRAM

TOWNSHIP 4 NORTH, RANGE 4 WEST,

4		4									
6		5		4		3		2		1	
7		8		9		10		11		12	
18		19 17		16		15		14		13	
		19		14		11		9		9 7	
6 19		18 20		13 21		10 22		9 23		7 24	
17		17 16		12							
6 30		15 29		28		27		26		25	
14		14									
5											
31		32		33		34		35		36	
4											

- Subdivision of Section 13 -----pp. 19-20
- Subdivision of Section 21 -----pp. 20-23
- Subdivision of Section 29 -----pp. 23-24
- Survey of Tract 37 -----pp. 24-26
- Survey of Tract 38 -----pp. 26-27
- Survey of Tract 39 -----pp. 27-46
- General Description -----pg. 47

T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS

The following field notes are those of the dependent resurvey of a portion of the First Standard Parallel North, on the south boundary of Township 5 North, Range 4 West; a portion of the First Guide Meridian West between Ranges 4 and 5 West; and a portion of the east boundary and subdivisional lines and the survey of subdivisions in sections 13, 21 and 29 and the metes-and-bounds survey of Tracts 37, 38 and 39, Township 4 North, Range 4 West, Gila and Salt River Meridian, Arizona.

Hans D. Voigt, U.S. Transitman, resurveyed the north boundary (First Standard Parallel North), surveyed the west boundary (First Guide Meridian West), and surveyed the south boundary in 1915-1916. The east boundary was surveyed by Roy J. Gill, U.S. Transitman, in 1915. The subdivisional lines were surveyed by H. D. Voigt and R. J. Gill in 1915-1916. The Bureau of Reclamation surveyed and monumented certain points for the right-of-way of the Central Arizona Project Canal.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated November 8, 1985, for Group No. 674, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were recovered in good condition and required no remonumentation. Lost corners were restored and monumented at proportionate positions based on the official record. Lost corners pertaining to the right-of-way of the Central Arizona Project Canal were restored and monumented at proportionate positions based on the Bureau of Reclamation's survey, as shown on diagram No. 344-330-2218. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of all lines were determined by observations on a U.S.G.S. triangulation network, confirmed by altitude observations on the sun, and refer to the true meridian. Distances and angles were measured with ZEISS Elta 46 Total Station.

The geographic position of the southeast corner of section 13, as determined from a tie made to U.S.C. & G.S. triangulation station "WAGNER," located in the SE quarter of section 36, T 4 N, R 4 W, is as follows:

Latitude: 33°40'56.2" N Longitude: 112°36'27.7" W

The mean magnetic declination, as shown on U.S.G.S. quadrangle map "WHITE TANK MTS., ARIZ.", published in 1957, is 14° E.

Dependent Resurvey
A Portion of the First Stan. Par. North
on the South Boundary of T 5 N, R 4 W,
Gila and Salt River Mer., Arizona

Restoring the resurvey executed by
Hans D. Voigt, in 1916

Dependent Resurvey
A Portion of the First Stan. Par. North
on the South Boundary of T 5 N, R 4 W,
Gila and Salt River Mer., Arizona

CHAINS		
	<p>Beginning at the stan. $\frac{1}{4}$ sec. cor. of sec. 33, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S33 <u>SC</u> 1916</p> <p>Cor. is located in a fence, bears N and S. S 89°59' W, on the S. bdy. of sec. 33.</p> <p>Over gently rolling land.</p>	
40.04	<p>Point for the stan. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum finned post, 36 ins. long, $\frac{3}{4}$ in. diam., 33 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">SC T5N R4W <u>S32 S33</u> 1985</p> <p>Set a steel fence post near the cor.</p> <p>Cor. is located within the Hassayampa River bottom.</p>	
	<p>S 89°59' W, on the S. bdy. of sec. 32.</p> <p>Over river bottom land.</p>	
23.69	<p>The closing cor. of sec. 5 and 6, T 4 N, R 4 W, at proportionate dist.; there is no remaining evidence of the original cor., hereinafter described.</p>	
40.04	<p>The stan. $\frac{1}{4}$ sec. cor. of sec. 32, monumented with an iron post, 1 in. diam., projecting 16 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S32 <u>SC</u> 1916</p>	
<p>Dependent Resurvey A Portion of the First Guide Meridian West, between Ranges 4 and 5 West, Gila and Salt River Mer., Arizona</p>		
<p>Restoring the survey executed by Hans D. Voigt, in 1916</p>		
	<p>From the cor. of Tps. 3 and 4 N, Rs. 4 and 5 W, monumented with an iron post, 3 ins. diam., projecting 12 ins. above ground, with brass cap mkd.</p>	

Dependent Resurvey, a portion of the First Guide Meridian West, between Ranges 4 and 5 West, Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">T4N R5W R4W S36 S31 <u>S1 S6</u> T3N 1915</p>	
	<p>N 0°01' E, bet. secs. 31 and 36.</p> <p>Over gently rolling land.</p>	
15.71	<p>AP 29, Tract 39, on the southerly right-of-way line of the C.A.P. Canal, hereinafter described.</p> <p>Continue on the line bet. secs. 31 and 36, on line 29-28, Tract 39.</p>	
26.45	<p>AP 28, Tract 39, on the northerly right-of-way line of the C.A.P. Canal, hereinafter described.</p> <p>Continue on the line bet. secs. 31 and 36.</p>	
40.05	<p>Point for the ¼ sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T4N R5W R4W ¼ S36 S31 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>	
80.10	<p>Point for the stan. cor. of secs. 25, 30, 31 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T4N R5W R4W S25 S30 <u>S36 S31</u> 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Cor. is located within the Hassayampa River bottom.</p>	

Dependent resurvey, a portion of the First Guide Meridian West, between Ranges 4 and 5 West, Gila and Salt River Mer., Arizona

CHAINS	
40.05	<p>N 0°01' E, bet. secs. 25 and 30.</p> <p>Over river bottom land.</p> <p>The ¼ sec. cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., projecting 14 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \frac{1}{4} \\ S S \\ 25 30 \\ 1916 \end{array}$ </div>
40.04	<p>N 0°02' E, beginning new measurement.</p> <p>Over level land.</p> <p>The cor. of secs. 19, 24, 25 and 30, monumented with an iron post, 3 ins. diam., projecting 10 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} T4N \\ R5W R4W \\ S S \\ \hline 24 19 \\ \hline S S \\ 25 30 \\ 1916 \end{array}$ </div>
40.07	<p>N 0°03' E, bet. secs. 19 and 24.</p> <p>Over gently rolling land, through medium to dense creosote and scattered palo verde and mesquite.</p> <p>The ¼ sec. cor. of secs. 19 and 24, monumented with an iron post, 1 in. diam., projecting 15 ins. above ground, in a mound of stone, 2 ft. base, 1 ft. high, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \frac{1}{4} \\ S S \\ 24 19 \\ 1916 \end{array}$ </div>
40.14	<p>N 0°01' E, beginning new measurement.</p> <p>The cor. of secs. 13, 18, 19 and 24, monumented with and iron post, 3 ins. diam., projecting 14 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} T4N \\ R5W R4W \\ S S \\ \hline 13 18 \\ \hline S S \\ 24 19 \\ 1916 \end{array}$ </div> <p>A mound of stone, 3 ft. base, 2 ft. high, is W of cor.</p>

Dependent Resurvey, a Portion of the East Boundary
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS

Reestablishment of the Survey Executed by
Roy J. Gill in 1915

From the cor. of secs. 13, 18, 19 and 24, on the E bdy. of the Tp., monumented with an iron post, 3 ins. diam., projecting 7 ins. above ground, with brass cap mkd.

T4N
R4W|R3W
S13|S18
S24|S19
1915

Cor. is located in a fence, bears N and S.

From this cor., U.S.C.&G.S. triangulation station "WAGNER," bears S 18°01'22" W (forward bearing), 228.43 chs. dist., monumented with a brass tablet, 3¼ ins. diam., set flush, with top mkd. WAGNER 1947.

N 0°01' E, bet. secs. 13 and 18.

Over nearly level land, along fence.

24.735 AP 4, Tract 37, falls in fence bearing N 69° E and S 69° W, on the southerly right-of-way line of the C.A.P. Canal, hereinafter described.

Continue on the line bet. secs. 13 and 18, on line 4-1, Tract 37.

37.72 AP 1, Tract 37, falls at fence cor., fences extend N 69° E, S 69° W and N, on the northerly right-of-way line of the C.A.P. Canal, hereinafter described.

Continue on the line bet. secs. 13 and 18.

Along fence.

40.035 The ¼ sec. cor. of secs. 13 and 18, monumented with an iron post, 1 in. diam., projecting 18 ins. above ground, with brass cap mkd.

¼
S13|S18
1915

Cor. is located at fence cor., from which fence extends S and W.

Dependent Resurvey,
a portion of the Subdivisional Lines,
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

Reestablishment of the Survey executed by
Hans D. Voigt and Roy J. Gill, in 1915-16.

From the ¼ sec. cor. of secs. 23 and 24, monumented with an iron post, 1 in. diam., projecting 18 ins. above ground, with brass cap mkd.

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS		
	$\frac{1}{4}$ S23 S24 1915	
	From this cor. an unmarked rebar, 3/8 ins. diam., firmly set, flush with ground, bears N 0°01' E, 1.13 chs. dist.	
	N 0°07' E, bet. secs. 23 and 24.	
	Over nearly level land.	
34.18	AP 3, Tract 38, on the southerly right-of-way line of the C.A.P. Canal, hereinafter described. Continue on the line bet. secs. 23 and 24, on line 3-2, Tract 38.	
40.025	True point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist., falls in the C.A.P. Canal where it is impracticable to establish a permanent monument; there is no remaining evidence of the original cor. This point now also functions as AP 2, Tract 38. From this point, the point selected for the witness cor. to the cor. of secs. 13, 14, 23 and 24, identical with AP 2, Tract 38, bears N 8°33' W, 3.113 chs. dist. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	WC T4N R4W S14 S13 S23 S24 1985	
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post. Set a steel fence post near the cor.	
	From the cor. of secs. 13, 18, 19 and 24, on the E bdy. of the Tp. N 89°59' W, bet. secs. 13 and 24. Over nearly level land.	
40.02	The ¼ sec. cor. of secs. 13 and 24, monumented with an iron post, 1 in. diam., projecting 16 ins. above ground, with brass cap mkd.	
	$\frac{1}{4}$ S13 S24 1915	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS		
	<p>S 89°59' W, beginning new measurement.</p> <p>Over nearly level land.</p>	
24.635	<p>AP 1, Tract 38, on the southerly right-of-way line of the C.A.P. Canal, hereinafter described.</p> <p>Continue on the line bet. secs. 13 and 24, on line 1-2, Tract 38.</p>	
24.825	<p>Fence bears N 69° E and S 69° W.</p>	
39.915	<p>True point for the cor. of secs. 13, 14, 23 and 24, identical with AP 2, Tract 38.</p>	
40.025	<p>N 0°07' W, bet. secs. 13 and 14.</p> <p>Over nearly level land.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 13 and 14, monumented with an iron post, 1 in. diam., projecting 19 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S14 S13 1915</p> <p>Cor. is located at a gate in a fence, bears E and W.</p>	
39.99	<p>From the true point for the cor. of secs. 13, 14, 23 and 24, identical with AP 2, Tract 38.</p> <p>N 89°52' W, bet. secs. 14 and 23.</p> <p>Over gently rolling land.</p>	
39.99	<p>The $\frac{1}{4}$ sec. cor. of secs. 14 and 23, monumented with an iron post, 1 in. diam., projecting 18 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S14}{S23}$ 1916</p>	
4.00	<p>From the $\frac{1}{4}$ sec. cor. of secs. 22 and 23, monumented with an iron post, 1 in. diam., projecting 16 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S22 S23 1916</p> <p>N 0°01' W, bet secs. 22 and 23.</p> <p>Over nearly level land, along a fence and track road.</p>	
4.00	<p>Fence, bears E and W, thence along an improved road over C.A.P. Canal.</p>	
7.08	<p>AP 47, Tract 39, on the southerly right-of-way line of the C.A.P. Canal, hereinafter described.</p> <p>Continue on the line bet. secs. 22 and 23, on line 47-1, Tract 39.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS	
19.60	Leave improved road; cross canal fence and continue along fence and track road.
37.32	AP 1, Tract 39, on the northerly right-of-way line of the C.A.P. Canal, hereinafter described. Continue on the line bet. secs. 22 and 23. Along fence and E side of trail road.
39.99	The cor. of secs. 14, 15, 22 and 23, monumented with an iron post, 2 ins. diam., projecting 16 ins. above ground, with brass cap mkd. <div style="text-align: center;"> <p>T4N R4W S15 S14 S22 S23 1916</p> </div> <p>Cor is located in a fence extending N and S.</p> <p>From this cor. U.S.G.S. bench mark "HYR-75 1970," bears S 87°04' W, 0.275 chs. dist., monumented with a brass tablet, 3½ ins. diam., seated in a concrete monument, 6 ins. diam., projecting 6 ins. above ground.</p>
	From the cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 ins. diam., projecting 20 ins. above ground, with brass cap mkd. <div style="text-align: center;"> <p>T4N R4W S21 S22 S28 S27 1916</p> </div> <p>N 0°01' W, bet. secs. 21 and 22.</p> <p>Over nearly level land.</p>
20.02	Point for the S 1/16 sec. cor. of secs. 21 and 22. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>S1/16 S21 S22 1985</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
40.04	The ¼ sec. cor. of secs. 21 and 22, monumented with an iron post, 1 in. diam., projecting 15 ins. above ground, with brass cap mkd. <div style="text-align: center;"> <p>¼ S21 S22 1916</p> </div> <p>N 0°02' W, beginning new measurement.</p> <p>Over nearly level land.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS		
7.73	Point for a witness point on line bet. secs. 21 and 22, on the southerly right-of-way line of the C.A.P. Canal.	
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. the ground with brass cap mkd.	
	WP T4N R4W TR 39 S21 S22 1985	
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.	
7.76	Fence, bears S 89½° E and N 89½° W.	
40.01	The cor. of secs. 15, 16, 21 and 22, monumented with an iron post, 2 ins. diam., projecting 16 ins. above ground, with brass cap mkd.	
	T4N R4W S16 S15 S21 S22 1916	
	This cor. now also functions as AP 8, Tract 39.	
	From the cor. of secs. 14, 15, 22 and 23.	
	West, bet. secs. 15 and 22.	
	Over gently rolling land.	
39.97	Point for the ¼ sec. cor of secs. 15 and 22, at proportionate dist.; there is no remaining evidence of the original cor. position. The original monument, 36 ins. long, 1 in. diam., was found nearby lying loose on the surface of the ground, with brass cap mkd. as described in the official record of the 1915-16 survey of the subdivisional lines of T 4 N, R 4 W.	
	Set the 1916 monument at proportionate position, 24 ins. in the ground, add mks. T4N R4W 1985; the cap is now mkd.	
	T4N R4W ¼ S15 S22 1985 1916	
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the 1916 monument.	
	Set a steel fence post near the cor.	
41.915	AP 4, Tract 39, on the northerly right-of-way line of the C.A.P. Canal, hereinafter described.	
	Continue on the line bet. secs. 15 and 22, on line 4-5, Tract 39.	

Dependent Resurvey, a Portion of the Subdivisional Lines
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS		
52.57	AP 5, Tract 39, on the northerly right-of-way line of the C.A.P. Canal, hereinafter described.	
	Continue on the line bet. secs. 15 and 22.	
68.09	AP 7, Tract 39, on the northerly right-of-way line of the C.A.P. Canal, hereinafter described.	
	Continue on the line bet. secs. 15 and 22, on line 7-8, Tract 39.	
79.94	The cor. of secs. 15, 16, 21 and 22, identical with AP 8, Tract 39.	
	From the cor. of secs. 28, 29, 32 and 33, monumented with an iron post, 2 ins. diam., projecting 16 ins. above ground, with brass cap mkd.	
	<p style="text-align: center;">T4N R4W S29 S28 S32 S33 1916</p>	
	N 0°02' E., bet. secs. 28 and 29.	
	Over nearly level land.	
40.03	The $\frac{1}{4}$ sec. cor. of secs. 28 and 29, monumented with an iron post, 1 in. diam., projecting 15 ins. above ground, with brass cap mkd.	
	<p style="text-align: center;">$\frac{1}{4}$ S29 S28 1916</p>	
	From the cor. of secs. 21, 22, 27 and 28.	
	N 89°59' W, bet. secs. 21 and 28.	
	Over gently rolling land.	
19.95	Point for the E 1/16 sec. cor. of secs. 21 and 28.	
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">E 1/16 $\frac{S21}{S28}$ 1985</p>	
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.	
	Cor. is located on E side of fence cor., from which fences extend N and W along fence.	
29.925	Point for the W-E 1/64 sec. cor. of secs. 21 and 28.	
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">S21 W-E 1/64 S28 1985</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS		
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.	
39.90	<p>The 1/4 sec. cor. of secs. 21 and 28, monumented with an iron post, 1 in. diam., projecting 24 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4} \frac{S21}{S28}$ 1916 </p>	
	<p>From the cor. of secs. 20, 21, 28 and 29, monumented with an iron post, 2 ins. diam., projecting 16 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;"> T4N R4W $\frac{S20 S21}{S29 S28}$ 1916 </p>	
	<p>N 0°03' W, bet. secs. 20 and 21.</p> <p>Over gently rolling land.</p>	
37.27	<p>Point for a witness point on line bet. secs. 20 and 21, on the southerly right-of-way line of the C.A.P. Canal.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> WP T4N R4W TR 39 $\frac{S20 S21}{1985}$ </p>	
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.	
37.31	Fence, bears N 56 1/2° E, and S 56 1/2° W.	
40.03	Point for the 1/4 sec. cor of secs. 20 and 21, at proportionate dist., falls in canal where it is impracticable to establish a permanent monument; there is no remaining evidence of the original cor., not monumented.	
46.13	Fence, bears N 44° E and S 44° W.	
46.33	<p>AP 15, Tract 39, on the northerly right-of-way line of the C.A.P. Canal, hereinafter described.</p> <p>Continue on the line bet. secs. 20 and 21, on line 15-14, Tract 39.</p>	
73.27	<p>AP 14, Tract 39, on the northerly right-of-way line of the C.A.P. Canal, hereinafter described.</p> <p>Continue on the line bet. secs. 20 and 21.</p>	
80.06	The cor. of secs. 16, 17, 20 and 21, monumented with an iron post, 2 ins. diam., projecting 16 ins. above ground, with brass cap mkd.	

Dependent Resurvey, a Portion of the Subdivisional Lines
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS		
	<p>T4N R4W S17 S16 S20 S21 1916</p>	
	<p>From the cor. of secs. 15, 16, 21 and 22, identical with AP 8, Tract 39.</p> <p>West, bet. secs. 16 and 21.</p> <p>Over gently rolling land.</p>	
16.41	<p>AP 10, Tract 39, on the northerly right-of-way line of the C.A.P. Canal, hereinafter described.</p> <p>Continue on the line bet. secs. 16 and 21, on line 10-11, Tract 39.</p>	
29.36	<p>AP 11, Tract 39, on the northerly right-of-way line of the C.A.P. Canal, hereinafter described.</p> <p>Continue on the line bet. secs. 16 and 21.</p>	
39.96	<p>The $\frac{1}{4}$ sec. cor. of secs. 16 and 21, monumented with an iron post, 1 in. diam., projecting 16 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ $\frac{S16}{S21}$ 1916 </p>	
	<p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>S 89°53' W, bet. secs. 29 and 32.</p> <p>Over nearly level land.</p>	
40.05	<p>The $\frac{1}{4}$ sec. cor. of secs. 29 and 32, monumented with an iron post, 1 in. diam., projecting 16 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ $\frac{S29}{S32}$ 1916 </p> <p>Cor. is located in a N-S fence line.</p>	
	<p>From the cor. of secs. 29, 30, 31 and 32 monumented with an iron post, 2 ins. diam., projecting 16 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;"> T4N R4W S30 S29 S31 S32 1916 </p>	
36.04	<p>N 89°55' W, bet. secs. 30 and 31.</p> <p>Over gently rolling land.</p> <p>Point for a witness point on line bet. secs. 30 and 31, on the southerly right-of-way line of the C.A.P. Canal.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS

Set an aluminum finned post, 36 ins. long, $\frac{3}{4}$ in. diam.,
30 ins. in the ground, with cap mkd.

WP
T4N R4W
TR39 / S30
S31
1985

Set a steel fence post near the witness point.

40.02

Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31, at
proportionate dist.; there is no remaining evidence of
the original cor.

Set an aluminum finned post, 36 ins. long, $\frac{3}{4}$ in diam.,
24 ins. in the ground, in a mound of stone $2\frac{1}{2}$ ft. base,
to top, with cap mkd.

T4N R4W
 $\frac{1}{4}$ S30
S31
1985

Fence cor. of an 8 ft. high fence, bears N 64° W.,
3.00 chs. dist., fences extend N 53° E and S 27° W.

Set a steel fence post near the cor.

50.08

Fence, bears N 7° E and S 7° W.

50.54

Point for a witness point on line bet. secs. 30 and 31,
on the northerly right-of-way line of the C.A.P. Canal.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins.
diam., 24 ins. in the ground, with brass cap mkd.

WP
T4N R4W
S30 / TR39
S31
1985

Deposit a magnet in a 1 x 1 x $2\frac{5}{8}$ in. white colored
plastic case beneath the stainless steel post.

Set a steel fence post near the cor.

79.71

The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of
the Tp. (First Guide Meridian West).

From the cor. of secs. 29, 30, 31 and 32.

N $0^\circ 05'$ E, bet. secs. 29 and 30.

Over gently rolling land.


32.39

Point for a witness point on line bet. secs. 29 and 30,
on the southerly right-of-way line of the C.A.P. Canal.

Set an aluminum finned post, 36 ins. long, $\frac{3}{4}$ in. diam.,
30 ins. in the ground, with cap mkd.

Dependent Resurvey, a Portion of the Subdivisional Lines
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS




Set a steel fence post near the cor.

32.68 Fence, bears N 35° E and S 35° W.

40.04 Point for the ¼ sec. cor. of secs. 29 and 30, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.




Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

68.935 Fence extends N 35° E and S 35° W.

69.535 Point for a witness point on line bet. secs. 29 and 30, on the northerly right-of-way line of the C.A.P. Canal.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.




Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Set a steel fence post near the cor. witness point.

80.08 Point for the cor of secs. 19, 20, 29 and 30, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Set a steel fence post near the cor.

From the cor. of secs. 20, 21, 28 and 29.

Dependent Resurvey, a Portion of the Subdivisional Lines
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS		
	S 89°57' W, bet. secs. 20 and 29.	
	Over gently rolling land.	
37.62	Point for a witness point on line bet. secs. 20 and 29, on the southerly right-of-way line of the C.A.P. Canal.	
	Set an aluminum finned post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, with cap mkd.	
	WP T4N R4W TR39 / S20 S29 1985	
37.67	Fence, bears N 44° E and S 44° W.	
39.975	Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	T4N R4W $\frac{1}{4}$ S20 S29 1985	
	Deposit a magnet in a 1 x 1 x 2 $\frac{5}{8}$ in. white colored plastic case beneath the stainless steel post.	
	Cor. is located on S side of canal road, 25 lks. wide.	
73.43	Point for a witness point on line bet. secs. 20 and 29, on the northerly right-of-way line of the C.A.P. Canal.	
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	WP T4N R4W S20 / TR39 S29 1985	
	Deposit a magnet in a 1 x 1 x 2 $\frac{5}{8}$ in. white colored plastic case beneath the stainless steel post.	
	Cor. of an 8 ft. high fence, bears S $3\frac{1}{2}$ ° E, 1.10 chs. dist., fences extend N 80° E and S 45° W, 60 lks. dist., thence S 26° W.	
	Set a steel fence post near the cor.	
79.95	The cor. of secs. 19, 20, 29 and 30.	
	N 89°48' W, bet. secs. 19 and 30.	
	Over river bottom land.	
40.015	The $\frac{1}{4}$ sec. cor. of secs. 19 and 30, monumented with an iron post, 1 in. diam., projecting 14 ins. above ground, with brass cap mkd.	

Dependent Resurvey, a Portion of the Subdivisional Lines
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS		
	$\frac{1}{4} \frac{S19}{S30}$ <p style="text-align: center;">1916</p> <hr/> <p>S 89°59' W, beginning new measurement.</p> <p>Over level land.</p>	
39.78	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp. (First Guide Meridian West).</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N 0°01' W, bet. secs. 19 and 20.</p> <p>Over river bottom land.</p>	
40.04	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> $\begin{array}{c} T4N R4W \\ \frac{1}{4} \\ S19 S20 \\ 1986 \end{array}$	
80.08	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> $\begin{array}{c} T4N R4W \\ S18 S17 \\ S19 S20 \\ 1986 \end{array}$ <p>From this cor., the point for the closing cor. of secs. 5 and 6, on the N. bdy. of the Tp. (First Standard Parallel North), bears N 0°01' W, 230.94 chs. dist.</p> <p>Set an aluminum finned post, 72 ins. long, $\frac{3}{4}$ in. diam., 68 ins. in the ground, with cap mkd.</p> $\begin{array}{c} T5N R4W \\ S32 \\ S6 S5 \\ C C \\ T4N R4W \\ 1985 \end{array}$ <p>Set a steel fence post near the cor.</p> <p>Cor. is located within the Hassayampa River bottom.</p> <p>The control line was fully retraced, and no evidence of the intervening cors. was found.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS		
	<p>From the closing cor. of secs. 5 and 6, the standard $\frac{1}{4}$ sec. cor. of sec. 32, T 5 N, R 4 W, bears S $89^{\circ}59'$ W, 16.35 chs. dist., hereinbefore described.</p>	
	<p>From the cor. of secs. 16, 17, 20 and 21. S $89^{\circ}58'$ W, bet. secs. 17 and 20.</p>	
	<p>Over gently rolling land.</p>	
39.935	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20, at proportionate dist.; there is no remaining evidence of the original cor.</p>	
	<p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T4N R4W $\frac{1}{4}$ <u>S17</u> S20 1986</p>	
	<p>Deposit a magnet in a 1 x 1 x $2\frac{5}{8}$ in. white colored plastic case beneath the stainless steel post.</p>	
	<p>Set a steel fence post near the cor.</p>	
	<p>Over river bottom land.</p>	
79.87	<p>The cor. of secs. 17, 18, 19 and 20.</p>	
	<p>N $89^{\circ}48'$ W, bet. secs. 18 and 19.</p>	
	<p>Over river bottom land.</p>	
40.005	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19, at proportionate dist.; there is no remaining evidence of the original cor.</p>	
	<p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T4N R4W $\frac{1}{4}$ <u>S18</u> S19 1986</p>	
	<p>Deposit a magnet in a 1 x 1 x $2\frac{5}{8}$ in. white colored plastic case beneath the stainless steel post.</p>	
	<p>Set a steel fence post near the cor.</p>	
79.71	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp. (First Guide Meridian West)</p>	
	<p style="text-align: center;">Subdivision of Section 13, T 4 N, R 4 W, Gila and Salt River Mer., Arizona</p>	
	<p>From the $\frac{1}{4}$ sec. cor of secs. 13 and 24.</p>	

Subdivision of Section 13, T 4 N, R 4 W,
Gila and Salt River Mer., Arizona

CHAINS		
	N 0°01' W, on the N and S center line of sec. 13.	
9.375	Fence, bears N 69° E and S 69° W.	
9.415	AP 3, Tract 37, on the southerly right-of-way line of the C.A.P. Canal, hereinafter described.	
	Continue on the N and S center line of sec. 13, on line 3-2, Tract 37.	
22.38	Fence, bears N 69° E and S 69° W.	
22.39	AP 2, Tract 37, on the northerly right-of-way line of the C.A.P. Canal, hereinafter described.	
	Continue on the N and S center line of sec. 13.	
40.02	Point for the center $\frac{1}{4}$ sec. cor. of sec. 13, at the intersection with the E and W center line of sec. 13.	
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	T4N R4W C $\frac{1}{4}$ S13 1985	
	Deposit a magnet in a 1 x 1 x $2\frac{5}{8}$ in. white plastic case beneath the stainless steel post.	
	From this corner a bench mark established by the Bureau of Reclamation, bears N 77°17' E, 4.51 chs. dist., monument with a brass tablet, $3\frac{1}{2}$ ins. diam., firmly set in a cement column, 8x8 ins., projecting 3 ins. above ground, with cap mkd. Wagner Well 1580.2 above sea Datum feet.	
40.055	Fence, bears E and W.	
80.03	The $\frac{1}{4}$ sec. cor. of secs. 12 and 13, monumented with an iron post, 1 in. diam., projecting 18 ins. above ground, with brass cap mkd.	
	$\frac{1}{4}$ S12 S13 1915	
	From the $\frac{1}{4}$ sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp.	
	West, on the E and W center line of sec. 13.	
40.03	The center $\frac{1}{4}$ sec. cor. of sec. 13.	
	Continue along fence.	
80.03	The $\frac{1}{4}$ sec. cor. of secs. 13 and 14.	
Subdivision of Section 21, T 4 N, R 4 W, Gila and Salt River Mer., Arizona		
	From the $\frac{1}{4}$ sec. cor. of secs. 21 and 28.	

Subdivision of Section 21, T 4 N, R 4 W,
Gila and Salt River Mer., Arizona

CHAINS		
	N 0°04' W, on the N and S center line of sec. 21.	
10.005	Point for the center S-S 1/64 sec. cor. of sec. 21.	
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	S21	
	C-S-S	
	1/64	
	1985	
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.	
	Set a steel fence post near the cor.	
20.01	Point for the center S 1/16 sec. cor. of sec. 21.	
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	C	
	S 1/16 S21	
	C	
	1985	
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.	
40.02	Point for the center ¼ sec. cor. of sec. 21, at intersection with the E and W center line of sec 21.	
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	T4N R4W	
	C¼ S21	
	1985	
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.	
45.46	Intersect line 40-41, Tract 39, point not monumented; from this point AP 41 bears N 80°02' E, 10.65 chs. dist., hereinafter described.	
65.27	Intersect line 12-13, Tract 39, point not monumented; from this point AP 12 bears S 74°21' E, 6.315 chs. dist., hereinafter described.	
80.04	The ¼ sec. cor. of secs. 16 and 21.	
	From the ¼ sec. cor. of secs. 21 and 22.	
	S 89°59' W, on the E and W center line of sec. 21.	
19.97	Point for the center E 1/16 sec. cor. of sec. 21.	
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	

Subdivision of Section 21, T 4 N, R 4 W,
Gila and Salt River Mer., Arizona

CHAINS		
	$\begin{array}{c} C \ E \ 1/16 \ C \\ S21 \\ 1985 \end{array}$	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>	
39.94	The center 1/4 sec. cor. of sec. 21.	
70.94	Intersect line 40 - 41, Tract 39, point not monumented; from this point AP 40, bears S 80°02' W, 6.64 chs. dist., hereinafter described.	
79.93	True point for the 1/4 sec. cor. of secs. 20 and 21.	
	<hr/> <p>SE 1/4, Section 21</p> <hr/>	
	<p>From the E 1/16 sec. cor. of secs. 21 and 28.</p> <p>N 0°03' W, on the N and S center line of the SE 1/4 of sec. 21.</p> <p>Along fence.</p>	
10.005	<p>Point for the center S-SE 1/64 sec. cor. of sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
	$\begin{array}{c} S21 \\ C-S-SE \\ 1/64 \\ 1985 \end{array}$	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Cor. is located N 45° E, 3 lks. dist. from a steel pipe fence post, 3 ins. diam., 4.5 ft. tall.</p>	
20.01	<p>Point for the SE 1/16 sec. cor. of sec. 21, at intersection with the E and W center line of the SE 1/4 of sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>	
	$\begin{array}{c} SE \ 1/16 \ S21 \\ 1985 \end{array}$	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>	
40.02	The center E 1/16 sec. cor. of sec. 21.	
	<hr/>	
	West, on the E and W center line of the SE 1/4 of sec. 21.	
19.96	The SE 1/16 sec. cor. of sec. 21.	

Subdivision of Section 21, T 4 N, R 4 W,
Gila and Salt River Mer., Arizona

CHAINS		
29.94	<p>Point for the center W-SE 1/64 sec. cor. of sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S21 C-W-SE 1/64 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>	
39.92	<p>The center S 1/16 sec. cor. of sec. 21.</p>	
<hr/> <p>SW ¼ of SE ¼, Section 21</p> <hr/>		
10.005	<p>From the W-E 1/64 sec. cor. of secs. 21 and 28.</p> <p>N 0°03.5' W, on the N and S center line of the SW ¼ of the SE ¼ of sec. 21.</p> <p>Point for the SW-SE 1/64 sec. cor. of sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S21 SW-SE 1/64 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>	
9.977	<p>From the center S-SE 1/64 sec. cor. of sec. 21.</p> <p>N 89°59.5' W, on the E and W center line of the SW ¼, of the SE ¼ of sec. 21.</p> <p>The SW-SE 1/64 sec. cor. of sec. 21.</p>	
<hr/> <p>Subdivision of Section 29, T 4 N, R 4 W, Gila and Salt River Mer., Arizona</p> <hr/>		
40.06	<p>From the ¼ sec. cor. of secs. 29 and 32.</p> <p>N 0°03' E, on the N and S center line of sec. 29.</p> <p>Along fence.</p> <p>Point for the center ¼ sec. cor. of sec. 29, at the intersection with the E and W center line of sec. 29.</p>	

Subdivision of Section 29, T 4 N, R 4 W,
Gila and Salt River Mer., Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T4N R4W
C¼ S29
1985

Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

Cor is located near the W side of a fence, bears N and S.

61.56 Intersect line 36-37, Tract 39, point not monumented; from this point AP 37, bears N 82°17' E, 4 lks. dist., hereinafter described.

80.09 The ¼ sec. cor. of secs. 20 and 29.

From the ¼ sec. cor. of secs. 28 and 29.

S 89°56' W, on the E and W center line of sec. 29.

40.02 The center ¼ sec. cor. of sec. 29.

74.685 Intersect line 35-36, Tract 39, point not monumented; from this point a witness point on line bet. secs. 29 and 30, on the southerly right-of-way line of the C.A.P. Canal, bears S 34°55' W, 9.335 chs. dist., hereinbefore described.

From this same point, AP 35, bears S 34°55' W, 19.235 chs. dist., hereinafter described.


80.02 The ¼ sec. cor of secs. 29 and 30.

Survey of Tract 37

T 4 N, R 4 W, Gila and Salt River Mer., Arizona

Beginning at the point for AP 1, Tract 37, on the northerly right-of-way line of the C.A.P. Canal, on line bet. secs. 13 and 18, Tps. 4 N, Rs. 3 and 4 W, determined at proportionate dist., bet. AP 4 and the ¼ sec. cor. of secs. 13 and 18.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

Set a steel fence post near the cor.

Cor. is located at fence cor., from which fences extend N, N 70° E and S 70° W.

Survey of Tract 37
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS

From this point the $\frac{1}{4}$ sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., bears N $0^{\circ}01'$ E, 2.315 chs. dist., hereinbefore described.


S $69^{\circ}03.5'$ W, on line 1-2, Tract 37, on the northerly right-of-way line of the C.A.P. Canal.

Along fence.

42.87

Point for AP 2, Tract 37, determined at intersection with the N and S center line of sec. 13.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 28 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x $2\frac{5}{8}$ in. white plastic case beneath the stainless steel post.

Set a steel fence post near the cor.

Cor. is located on N side of a fence, bears N 69° E and S 69° W.

S $0^{\circ}01'$ E, on line 2-3, Tract 37, on a portion of the N and S center line of sec. 13.


0.01

Fence, bears N 69° E and S 69° W.

12.975

Point for AP 3, Tract 37, determined at intersection with the southerly right-of-way line of the C.A.P. Canal.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 28 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x $2\frac{5}{8}$ in. white plastic case beneath the stainless steel post.

Set a steel fence post near the cor.

From this point a Bureau of Reclamation right-of-way marker, bears S $69^{\circ}03.5'$ W, 38.195 chs. dist., hereinafter described.

From this same point another Bureau of Reclamation right-of-way marker, bears N $69^{\circ}03.5'$ E, 52.71 chs. dist., hereinafter described.

N $69^{\circ}03.5'$ E, on line 3-4, Tract 37, on the southerly right-of-way line of the C.A.P. Canal.

Along fence.


Survey of Tract 37
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS

42.86

Point for AP 4, Tract 37, determined at intersection with the line bet. secs. 13 and 18, Tps. 4 N, Rs. 3 and 4 W.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

Set a steel fence post near the cor.

Cor. is located in a fence bearing N 69° E, and S 69° W.

From this point a Bureau of Reclamation right-of-way marker bears N 69°03.5' E, 9.85 chs. dist., monumented with a brass tablet, 3½ ins. diam., firmly set, in concrete, flush with ground, with top mkd. 360+00.12 ROW 400 FTRT R-8.

N 0°01' E, on line 4-1, Tract 37, on a portion of the line bet. secs. 13 and 18, Tps. 4 N, Rs. 3 and 4 W.


12.985

AP 1, Tract 37, and place of beginning.

Survey of Tract 38
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

Beginning at the point for AP 1, Tract 38, determined at intersection of the line bet. secs. 13 and 24, with the southerly right-of-way line of the C.A.P. Canal, falls in trail road, 15 lks. wide, bears N 69° E and S 69° W.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 36 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

Set a steel fence post near the cor.

Survey of Tract 38
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS

From this point a Bureau of Reclamation right-of-way marker, bears S 69°03.5' W, 11.825 chs. dist., hereinafter described.

From this same point another Bureau of Reclamation right-of-way marker, bears N 69°03.5' E, 79.08 chs. dist., hereinbefore described.

From this same point the ¼ sec. cor. of secs. 13 and 24, bears N 89°59' E, 24.635 chs. dist., hereinbefore described.

S 89°59' W, on line 1-2, Tract 38, on a portion of the line bet. secs. 13 and 24.

15.28


AP 2, Tract 38, identical with the true point for the cor. of secs. 13, 14, 23 and 24, hereinbefore described.

S 0°07' W, on line 2-3, Tract 38, on a portion of the line bet. secs. 23 and 24.

5.845

Point for AP 3, Tract 38, determined at intersection with the southerly right-of-way line of the C.A.P. Canal.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

Set a steel fence post near the cor.

N 69°03.5' E, on line 3-1, Tract 38, on the southerly right-of-way line of the C.A.P. Canal.

4.545

A Bureau of Reclamation right-of-way marker, monumented with a brass tablet, 3½ ins. diam., firmly set, flush in concrete, with top mkd. 300+00.39 ROW 400 FTRT R-8.

16.37

AP 1, Tract 38, and place of beginning.

Survey of Tract 39
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

Beginning at the point for AP 1, Tract 39, on the northerly right-of-way line of the C.A.P. Canal on line bet. secs. 22 and 23, determined at proportionate dist., bet. the cor. of secs. 14, 15, 22 and 23 and the ¼ sec. cor. of secs. 22 and 23.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.

Survey of Tract 39
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS

T4N R4W
S22|S23
/|
AP1|
TR39|
1985

Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

Cor. is located at a gate in a fence, bears N and S.

From this point the cor. secs. 14, 15, 22 and 23, bears N 0°01' W, 2.67 chs. dist., hereinbefore described.

S 56°47' W, on line 1-2, Tract 39, on the northerly right-of-way line of the C.A.P. Canal.

0.20 Trail road, bears N and S.

16.05 AP 2, Tract 39, established by the Bureau of Reclamation, monumented with a wooden hub, 1 x 2 ins.

At the cor. point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T4N R4W
S22
/|
AP2
TR39
1985

Deposit the wooden hub alongside the cor. monument.

Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

Set a steel fence post near the cor.

N 80°02' W, on line 2-3, Tract 39, on the northerly right-of-way line of the C.A.P. Canal.

24.42 AP 3, Tract 39, established by the Bureau of Reclamation, monumented with a wooden hub, 2 x 2 ins.

At the cor. point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T4N R4W
S22
/|
AP3
TR39
1985

Deposit the wooden hub alongside the cor. monument.

Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

Survey of Tract 39
T 4 N, R 4 W, Gila and Salt River Mer., Arizona


CHAINS

Set a steel fence post near the cor.

N 31°32' W, on line 3-4, Tract 39, on the northerly right-of-way line of the C.A.P. Canal.

8.48 Point for AP 4, Tract 39, at intersection with the line bet. secs. 15 and 22.


Set an aluminum finned post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, with cap mkd.



West, on line 4-5, Tract 39, on the northerly right-of-way line of the C.A.P. Canal, on a portion of the line bet. secs. 15 and 22.

10.655 Point for AP 5, Tract 39.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 $\frac{5}{8}$ in. white plastic case beneath the stainless steel post.


Set a steel fence post near the cor.

S 32°03' W, on line 5-6, Tract 39, continue on the northerly right-of-way line of the C.A.P. Canal.

12.35 AP 6, Tract 39, established by the Bureau of Reclamation, monumented with a wooden hub, 2 x 2 ins.

At the cor. point

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit the wooden hub alongside the cor. monument.

Deposit a magnet in a 1 x 1 x 2 $\frac{5}{8}$ in. white plastic case beneath the stainless steel post.

Set a steel fence post near the cor.


Survey of Tract 39
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS

N 40°37' W, on line 6-7, Tract 39, on the northerly right-of-way line of the C.A.P. Canal.

13.78 Point for AP 7, Tract 39, at intersection with the line bet. secs. 15 and 22.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

Set a steel fence post near the cor.

West, on line 7-8, Tract 39, on the northerly right-of-way line of the C.A.P. Canal, on a portion of the line bet. secs. 15 and 22.

11.85 AP 8, Tract 39, identical with the cor. of secs. 15, 16, 21 and 22, hereinbefore described.

S 25°49' W, on line 8-9, Tract 39, on the northerly right-of-way line of the C.A.P. Canal.

11.53 AP 9, Tract 39, established by the Bureau of Reclamation, monumented with a wooden hub, 2 x 2 ins.

At the cor. point

Set a stainless steel post, 20 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit the wooden hub alongside the cor. monument.

Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

Set a steel fence post near the cor.

N 47°39' W, on line 9-10, Tract 39, on the northerly right-of-way line of the C.A.P. Canal.

15.41 Point for AP 10, Tract 39, at intersection with the line bet. secs. 16 and 21.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of Tract 39
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS

T4N R4W
S16
AP10 \ S21
TR39 /
1985

Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

Set a steel fence post near the cor.

West, on line 10-11, Tract 39, on the northerly right-of-way line of the C.A.P. Canal, on a portion of the line bet. secs. 16 and 21.

12.95 Point for AP 11, Tract 39.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T4N R4W
S16
S21 / AP11
TR39 \
1985

Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

Set a steel fence post near the cor.

S 15°17' W, on line 11-12, Tract 39, continue on the northerly right-of-way line of the C.A.P. Canal.

17.08 AP 12, Tract 39, established by the Bureau of Reclamation, monumented with a wooden hub, 2 x 2 ins.

At the cor. point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T4N R4W
S21 /
AP12
TR39 \
1985


Deposit the wooden hub alongside the cor. monument.

Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

Set a steel fence post near the cor.

N 74°21' W, on line 12-13, Tract 39, on the northerly right-of-way line of the C.A.P. Canal.

Survey of Tract 39
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS	
6.315	Intersect the N and S center line of sec. 21, point not monumented; from this point the $\frac{1}{4}$ sec. cor. of secs. 16 and 21, bears N 0°04' W, 14.77 chs. dist.
24.49	<p>Point for AP 13, Tract 39.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T4N R4W S21</p>  <p>AP13 TR39 1985</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>N 82°14' W, on line 13-14, Tract 39, on the northerly right-of-way line of the C.A.P. Canal.</p>
22.69	<p>Point for AP 14, Tract 39, at intersection with the line bet. secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T4N R4W S21 S20 AP14 TR39 1985</p>  </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>S 0°03' E, on line 14-15, Tract 39, on the northerly right-of-way line of the C.A.P. Canal, on a portion of the line bet. secs. 20 and 21.</p>
26.94	<p>Point for AP 15, Tract 39.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T4N R4W S20 AP15 TR39 1985</p>  </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/>

Survey of Tract 39
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS

S 44°06' W, on line 15-16, Tract 39, continue on the northerly right-of-way line of the C.A.P. Canal.

39.34

AP 16, Tract 39, established by the Bureau of Reclamation, monumented with a bronze disk, 3¾ ins. diam., flush with the ground, set in concrete, 15 in. diam., with top mkd. 115+43.56 R.O.W. 175 FT LT R-8.

Add the marks AP 16, TR 39 on the bronze disk.


Cor. is located 20 lks. N of a fence cor., from which fences extend N 44° E and N 60° W.

N 59°51' W, on line 16-17, Tract 39, on the northerly right-of-way line of the C.A.P. Canal.

30.68

Point for AP 17, Tract 39.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.


Set a steel fence post near the cor.

S 32°29' W, on line 17-18, Tract 39, on the northerly right-of-way line of the C.A.P. Canal.

30.31

Point for AP 18, Tract 39.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

Set a steel fence post near the cor.

S 21°43' W, on line 18-19, Tract 39, on the northerly right-of-way line of the C.A.P. Canal.

Survey of Tract 39
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS	
0.77	A Bureau of Reclamation right-of-way marker, monumented with a rebar, ½ in. diam, projecting 5 ins. above ground, with attached aluminum cap mkd. W.P.R.S. B.O.L. H.R.R.2-1 1980.
8.60	A witness point on the line bet. secs. 20 and 29, hereinbefore described; from this point the cor. of secs. 19, 20, 29 and 30, bears S 89°57' W, 6.52 chs. dist.
11.575	Point for AP 19, Tract 39. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T4N R4W S29 / AP19 TR39 1985</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
	<hr/> <p>S 34°55' W, on line 19-20, Tract 39, on the northerly right-of-way line of the C.A.P. Canal.</p>
3.17	A Bureau of Reclamation right-of-way marker, monumented with a bronze disk, 3¾ ins. diam., flush with the ground, set in concrete, 15 ins. diam., with top mkd. STA P.C. 729+84.56 R.O.W. 200.00 LT.
7.27	A Bureau of Reclamation right-of-way marker, monumented with a bronze disk, 3¾ ins. diam., flush with the ground, set in concrete, 15 ins. diam., with top mkd. STA 727+14.41 R.O.W. 200.00 LT. B.O.L. H.R.R.L.-2 1980.
9.495	A witness point on the line bet. secs. 29 and 30, hereinbefore described; from this point the cor. of secs. 19, 20, 29 and 30, bears N 0°05' E, 10.545 chs. dist.
13.465	A Bureau of Reclamation right-of-way marker, monumented with a bronze disk, 3¾ ins. diam., flush with the ground, set in concrete, 15 ins. diam., with top mkd. STA 723+05.45 R.O.W. 200.00 LT.
21.47	A Bureau of Reclamation right-of-way marker, monumented with a bronze disk, 3¾ ins. diam., flush with the ground, set in concrete, 15 ins. diam., with top mkd. STA 717+77.06 R.O.W. 200.00 LT B.O.L. H.R.R.L.-3 1980.
31.265	A Bureau of Reclamation right-of-way marker, monumented with a bronze disk, 3¾ ins. diam., flush with the ground, set in concrete, 15 ins. diam., with top mkd. STA 711+30.56 R.O.W. 200.00 LT. B.O.L. H.R.R.L.-4 1980
46.52	Point for AP 20, Tract 39. Set an aluminum finned post, 72 ins. long, ¾ in. diam., 72 ins. in the ground, with cap mkd.

Survey of Tract 39
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS




Set a steel fence post near the cor.

Cor. is located 12 lks. W of a fence, bears N 35° E, and S 35° W.

N 50°40' W, on line 20-21, Tract 39, on the northerly right-of-way line of the C.A.P. Canal.

3.03 Point for AP 21, Tract 39.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a steel fence post, with brass cap mkd.




Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

Set a steel fence post near the cor.

S 53°39' W, on line 21-22, Tract 39, on the northerly right-of-way line of the C.A.P. Canal.

6.075 Point for AP 22, Tract 39.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a steel fence post, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

Set a steel fence post near the cor.


S 43°46' W, on line 22-23, Tract 39, on the northerly right-of-way line of the C.A.P. Canal.

31.87 Point for AP 23, Tract 39.

Survey of Tract 39
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a steel fence post, with brass cap mkd.



1985


Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

Set a steel fence post near the cor.

S 16°12' W, on line 23-24, Tract 39, on the northerly right-of-way line of the C.A.P. Canal.

7.975 Point for AP 24, Tract 39.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a steel fence post, with brass cap mkd.



1985

Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

Set a steel fence post near the cor.

S 64°32' E, on line 24-25, Tract 39, on the northerly right-of-way line of the C.A.P. Canal.

3.03 AP 25, Tract 39, established by the Bureau of Reclamation, monumented with a bronze disk, 3¾ ins. diam., flush with the ground, set in concrete, 15 ins. diam., with top mkd. STA P.C. 672+71.99 R.O.W. 200.00 LT.

Add the marks AP 25 TR 39 on the bronze disk.

S 7°11' W, on line 25-26, Tract 39, on the northerly right-of-way line of the C.A.P. Canal.

5.18 A Bureau of Reclamation right-of-way marker, monumented with a bronze disk, 3¾ ins. diam., flush with the ground, set in concrete, 15 ins. diam., with top mkd. STA 669+30.43 R.O.W. 200.00 LT.

5.48 A witness point on the line bet. secs. 30 and 31, hereinbefore described; from this point the ¼ sec. cor. of secs. 30 and 31, bears S 89°55' E, 10.52 chs. dist.

Survey of Tract 39
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS	
7.65	<p>AP 26, Tract 39, established by the Bureau of Reclamation, monumented with a bronze disk, $3\frac{3}{4}$ ins. diam., flush with the ground, set in concrete, 15 ins. diam., with top mkd. STA P.T. 667+67.30 R.O.W. 200.00 LT.</p> <p>Add the marks AP 26 TR 39 on the bronze disk.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S $18^{\circ}33'$ W, on line 26-27, Tract 39, on the northerly right-of-way line of the C.A.P. Canal.</p>
3.08	<p>AP 27, Tract 39, established by the Bureau of Reclamation, monumented with a bronze disk, $3\frac{3}{4}$ ins. diam., set 8 ins. below the surface of the ground, in concrete, 15 ins. diam., with top mkd. STA 664+82.83 R.O.W. 200.00 LT.</p> <p>Add the marks AP 27 TR 39 on the bronze disk.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S $29^{\circ}56'$ W, on line 27-28, Tract 39, on the northerly right-of-way line of the C.A.P. Canal.</p>
0.945	<p>A Bureau of Reclamation right-of-way marker, monumented with a bronze disk, $3\frac{3}{4}$ ins. diam., flush with the ground, set in concrete, 15 ins. diam., with top mkd. STA 664+20.74 R.O.W. 200.00 LT.</p>
6.785	<p>A Bureau of Reclamation right-of-way marker, monumented with a bronze disk, $3\frac{3}{4}$ ins. diam., flush with the ground, set in concrete, 15 ins. diam., with top mkd. STA 660+35.51 R.O.W. 200.00 LT.</p>
19.98	<p>A Bureau of Reclamation right-of-way marker, monumented with a bronze disk, $3\frac{3}{4}$ ins. diam., flush with the ground, set in concrete, 15 ins. diam., with top mkd. STA 651+64.70 R.O.W. 200.00 LT.</p>
33.42	<p>A Bureau of Reclamation right-of-way marker, monumented with a bronze disk, $3\frac{3}{4}$ ins. diam., flush with the ground, set in concrete, 15 ins. diam., with top mkd. STA 642+77.81 R.O.W. 200.00 LT.</p>
46.185	<p>A Bureau of Reclamation right-of-way marker, monumented with a bronze disk, $3\frac{3}{4}$ ins. diam., flush with the ground, set in concrete, 15 ins. diam., with top mkd. STA 634+35.40 R.O.W. 200.00 LT.</p>
56.01	<p>Point for AP 28, Tract 39, at intersection with the line bet. secs. 31 and 36, on the W. bdy. of the Tp. (First Guide Meridian West).</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of Tract 39
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS

T4N
R5W|R4W
|S31
S36|
|AP28
|TR39
1985

Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

Set a steel fence post near the cor.

Cor. is located 9 lks. W of a fence bears N 30° E and S 30° W.

S 0°01' W, on line 28-29, Tract 39, on a portion of the line bet. secs. 31 and 36, Tps. 4 N, Rs. 4 and 5 W.

10.74 Point for AP 29, Tract 39.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T4N
R5W|R4W
|AP29
S36|TR39
|S31
1985

Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic container beneath the stainless steel post.

Set a steel fence post near the cor.

S 80°54' E, on line 29-30, Tract 39, on the southerly right-of-way line of the C.A.P. Canal.

0.75 Point for AP 30, Tract 39.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T4N R4W
AP30
TR39
S31
1985

Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

Set a steel fence post near the cor.

N 29°59' E, on line 30-31, on the southerly right-of-way line of the C.A.P. Canal.

Survey of Tract 39
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS


Along fence.

5.585 A Bureau of Reclamation right-of-way marker, monumented with a bronze disk, $3\frac{3}{4}$ ins. diam., flush with the ground, set in concrete, 15 ins. diam., with top mkd. R-7 R.O.W. STA 624+88.26 PI 200.00 FT RT 90 FR AH TAN.

7.84 A Bureau of Reclamation right-of-way marker, monumented with a bronze disk, $3\frac{3}{4}$ ins. diam., flush with the ground, set in concrete, 15 ins. diam., with top mkd. R-7 R.O.W. E.Q. STA 626+30.60 BK 627+07.66 AH 200.00 FT RT.

12.28 Point for AP 31, Tract 39.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.


S 60°01' E, on line 31-32, Tract 39, on the southerly right-of-way line of the C.A.P. Canal.

Along fence.

8.33 AP 32, Tract 39, established by the Bureau of Reclamation, monumented with a rebar, $\frac{1}{2}$ in. diam., projecting 4 ins. above ground, with attached aluminum cap mkd. R.O.W.

At the cor. point

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over the rebar, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 in. in a white plastic case beneath the stainless steel post.

Cor. is located S 45° E, 2 lks. dist. from a fence cor., from which fences extend N 30° E, and N 60° W.

N 29°56' E, on line 32-33, Tract 39, on the southerly right-of-way line of the C.A.P. Canal.


Survey of Tract 39
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Along fence.</p>
<p>28.57</p>	<p>Point for a witness point on line 32-33, Tract 39.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WP T4N R4W TR39 / S31 1985</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
<p>54.90</p>	<p>Leave fence, extending S 30° W.</p>
<p>57.24</p>	<p>Point for AP 33, Tract 39.</p> <p>Set an aluminum finned post, 36 ins. long, ¾ in. diam., 30 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <p>T4N R4W AP33 / TR39 S31 1985</p> </div> <p>Set a steel fence post near the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>N 7°11' E, on line 33-34, Tract 39, on the southerly right-of-way line of the C.A.P. Canal.</p>
<p>8.435</p>	<p>A witness point on the line bet. secs. 30 and 31, hereinbefore described; from this point the ¼ sec. cor. of secs. 30 and 31, bears N 89°55' W, 3.98 chs. dist.</p>
<p>12.12</p>	<p>Point for AP 34, Tract 39.</p> <p>Set an aluminum finned post, 36 ins. long, ¾ in. diam., 30 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <p>T4N R4W AP34 / TR39 S30 1985</p> </div> <p>Set a steel fence post near the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>N 55°33' E, on line 34-35, Tract 39, on the southerly right-of-way line of the C.A.P. Canal.</p>
<p>36.34</p>	<p>Point for AP 35, Tract 39.</p>

Survey of Tract 39
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS

Set an aluminum finned post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, with cap mkd.



Set a steel fence post near the cor.

Cor. is located 48 lks. E of a fence bearing NE and SW.

N $34^{\circ}55'$ E, on line 35-36, Tract 39, on the southerly right-of-way line of the C.A.P. Canal.


9.90 A witness point on the line bet. secs. 29 and 30, hereinbefore described; from this point the $\frac{1}{4}$ sec. cor. of secs. 29 and 30, bears N $0^{\circ}05'$ E, 7.65 chs. dist.

19.235 Intersect the E and W center line of sec. 29, point not monumented; from this point the $\frac{1}{4}$ sec. cor. of secs. 29 and 30, bears S $89^{\circ}56'$ W, 5.335 chs. dist.

41.91 AP 36, Tract 39, established by the Bureau of Reclamation, monumented with a rebar, $\frac{1}{2}$ in. diam., set 18 ins. below the surface of the ground, with an unmarked attached aluminum cap.

At the cor. point

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over the rebar, with brass cap mkd.



Deposit a magnet in a 1 x 1 x $2\frac{5}{8}$ in. white plastic case beneath the stainless steel post.

Cor. is located N 65° E, $2\frac{1}{2}$ lks. dist. of a fence cor., from which fences extend N $82\frac{1}{4}^{\circ}$ E and S 35° W.

N $82^{\circ}17'$ E, on line 36-37, Tract 39, on the southerly right-of-way line of the C.A.P. Canal.

Along fence.

21.90 Intersect the N and S center line of sec. 29, point not monumented; from this point the $\frac{1}{4}$ sec. cor. of secs. 20 and 29, bears N $0^{\circ}03'$ E, 18.53 chs. dist.

Survey of Tract 39
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS	
21.94	<p>AP 37, Tract 39, established by the Bureau of Reclamation, monumented with a bronze disk, $3\frac{3}{4}$ ins. diam., set flush with the ground, in concrete, 15 ins. diam., with top mkd. R.O.W. 1200 FT RT 751+44.10 R-7.</p> <p>Add the marks AP 37 TR 39 on the bronze disk.</p> <p>Cor. is located S 45° E, $1\frac{1}{2}$ lks. dist. of a fence cor., from which fences extend N $4\frac{1}{2}^\circ$ E, S and S $82\frac{1}{4}^\circ$ W.</p> <hr/> <p>N $0^\circ 03'$ W, on line 37-38, Tract 39, on the southerly right-of-way line of the C.A.P. Canal.</p>
16.10	<p>Point for AP 38, Tract 39.</p> <p>Set an aluminum finned post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, with cap mkd.</p> <div data-bbox="836 981 1047 1142" style="text-align: center;"> <p>T4N R4W AP38 TR39 S29 1985</p> </div> <p>A fence cor., bears N. 44° E., 1.925 chs. dist., fences extend N. 44° E. and S. $4\frac{1}{2}^\circ$ W.</p> <p>Set a steel fence post near the cor.</p> <hr/> <p>N $44^\circ 08'$ E, on line 38-39, Tract 39, on the southerly right-of-way line of the C.A.P. Canal.</p>
1.96	<p>A Bureau of Reclamation right-of-way marker, monumented with a bronze disk, $3\frac{3}{4}$ ins. diam., flush with the ground, set in concrete, 15 ins. diam., with top mkd. R.O.W. 175 FT RT 752 + R-7 R-8.</p>
3.38	<p>A witness point on the line bet. secs. 20 and 29, hereinbefore described; from this point the $\frac{1}{4}$ sec. cor. of secs. 20 and 29, bears S $89^\circ 57'$ W, 2.355 ch. dist.</p>
12.87	<p>A Bureau of Reclamation right-of-way marker, monumented with a bronze disk, $3\frac{3}{4}$ ins. diam., flush with the ground, set in concrete, 15 ins. diam., with top mkd. 107+99.87 R.O.W. 175 FT RT R-8.</p>
24.795	<p>A Bureau of Reclamation right-of-way marker, monumented with a bronze disk, $3\frac{3}{4}$ ins. diam., flush with the ground, set in concrete, 15 ins. diam., with top mkd. 115+87.04 R.O.W. 175 FT RT R-8.</p>
51.81	<p>AP 39, Tract, 39, established by the Bureau of Reclamation, monumented with a bronze disk, $3\frac{3}{4}$ ins. diam., flush with the ground, set in concrete, 15 ins. diam., with top mkd. P.C. 133+70.02 R.O.W. 175 FT RT R-8.</p> <p>Add the marks AP 39 TR 39 on the bronze disk.</p>

Survey of Tract 39
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS		
	<p>Cor. is located 4 lks. S of a fence bearing N 56½° E, and S 44° W.</p> <hr/> <p>N 56°37' E, on line 39-40, Tract 39, on the southerly right-of-way line of the C.A.P. Canal.</p> <p>Along fence.</p>	
4.62	<p>A witness point on the line bet. secs. 20 and 21, hereinbefore described; from this point the true point for the ¼ sec. cor. of secs. 20 and 21, bears N 0°03' W, 2.76 chs. dist.</p>	
7.55	<p>AP 40, Tract 39, established by the Bureau of Reclamation, monumented with a bronze disk, 3¾ ins. diam., flush with the ground, set in concrete, 15 ins. diam., with top mkd. P.T. 139+68.18 R.O.W. 125 FT RT R-8.</p> <p>Add the marks AP 40 TR 39 on the bronze disk.</p> <p>Cor is located 4 lks. S of a fence bearing N 80° E, and S 56½° W.</p> <hr/> <p>N 80°02' E, on line 40-41, Tract 39, on the southerly right-of-way line of the C.A.P. Canal.</p> <p>Along fence.</p>	
6.64	<p>Intersect the E and W center line of sec. 21, point not monumented; from this point the true point for the ¼ sec. cor. of secs. 20 and 21, bears S 89°59' W, 8.99 chs. dist.</p>	
22.32	<p>Point for a witness point on line 40-41, Tract 39.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> WP T4N R4W TR39 <hr style="width: 10%; margin: 0 auto;"/> S21 1985 </p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Witness point is located 3 lks. S of a fence, bearing N 80° E and S 80° W.</p>	
38.11	<p>Intersect the N and S center line of sec. 21, point not monumented; from this point the center ¼ sec. cor. of sec. 21, bears S 0°04' E, 5.44 chs. dist.</p>	
48.76	<p>AP 41, Tract 39, established by the Bureau of Reclamation, monumented with a bronze disk, 3¾ ins. diam., flush with the ground, set in concrete, 15 ins. diam., with top mkd. P.C. 171+86.39 R.O.W. 125 FT RT R-8.</p>	

Survey of Tract 39
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS

Add the marks AP 41 TR 39 on the bronze disk.

Cor. is located 4 lks. S of a fence bearing
N $85\frac{1}{4}^{\circ}$ E, and S 80° W.

N $85^{\circ}13'$ E, on line 41-42, Tract 39, on the southerly
right-of-way line of the C.A.P. Canal.

Along fence.

7.525 AP 42, Tract 39, established by the Bureau of
Reclamation, monumented with a bronze disk, $3\frac{3}{4}$ ins.
diam., flush with the ground, set in concrete, 15 ins.
diam., with top mkd. P.T. 177+06.37 R.O.W. 125 FT RT
R-8.

Add the marks AP 42 TR 39 on the bronze disk.

Cor. is located 4 lks. S of a fence bearing
S $89\frac{1}{2}^{\circ}$ E and S $85\frac{1}{4}^{\circ}$ W.

S $89^{\circ}33'$ E, on line 42-43, Tract 39, on the southerly
right-of-way line of the C.A.P. Canal.

Along fence.

3.75 Barbed wire fence, bears S 20° E and N 20° W, 4 lks.
dist., to cor. of fences extending N 40° E and N $89\frac{1}{2}^{\circ}$ W.

4.45 Point for AP 43, Tract 39, falls in graded road.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins.
diam., 29 ins. in the ground, with brass cap mkd.

T4N R4W

S21 | AP43
| TR39
1985

Deposit a magnet in a 1 x 1 x $2\frac{5}{8}$ in. white plastic
case beneath the stainless steel post.

Cor. is located S $10\frac{1}{2}^{\circ}$ E, $73\frac{1}{2}$ lks. dist. of a fence
cor., from which fences extend S 60° E and S 40° W.

S $0^{\circ}27'$ W, on line 43-44, Tract 39, on the southerly
right-of-way line of the C.A.P. Canal.

1.137 AP 44, Tract 39, established by the Bureau of
Reclamation, monumented with a rebar, $\frac{1}{2}$ in. diam.,
projecting 2 ins. above ground, set in concrete, 12
ins. diam., with an unmarked attached aluminum cap.

Stamp marks for AP 44, Tract 39; the cap is now mkd.

T4N R4W

| AP44
| TR39
S21
1985

Survey of Tract 39
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS		
	<p>Cor. is located S 45° W, 2 lks. dist. of fence cor., from which fences extend S 89½° E and N 20° W.</p> <hr/> <p>S 89°33' E, on line 44-45, Tract 39, on the southerly right-of-way line of the C.A.P. Canal.</p> <p>Along fence.</p> <p>4.545 AP 45, Tract 39, established by the Bureau of Reclamation, monumented with a rebar, ½ in. diam., projecting 2 ins. above ground, set in concrete, 12 ins. diam., with an unmarked aluminum cap mkd.</p> <p>Stamp marks for AP 45, Tract 39; the cap is now mkd.</p> <p style="text-align: center;">T4N R4W AP45 TR39 ----- S21 1985</p> <p>Cor. is located S 45° E, 4 lks. dist. of a fence cor., from which fences extend N 89½° W and northwesterly.</p> <hr/> <p>N 0°27' E, on line 45-46, Tract 39, on the southerly right-of-way line of the C.A.P. Canal.</p>	
	<p>1.137 AP 46, Tract 39, established by the Bureau of Reclamation, monumented with an open end pipe, 1 in. diam., projecting 2 ins., set in concrete, 8 ins. diam., cap apparently has been removed.</p> <p>At the cor. point</p> <p>Remove the remains of the Bureau of Reclamation monument and set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4N R4W AP46 TR39 ----- S21 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Bury the remains of the Bureau of Reclamation monument alongside the stainless steel post.</p> <p>Cor. is located 5 lks. S of a fence, bearing S 89½° E. and N 89½° W.</p> <hr/> <p>S 89°33' E, on line 46-47, Tract 39, on the southerly right-of-way line of the C.A.P. Canal.</p> <p>Along fence.</p>	
12.96	<p>A witness point on the line bet. secs. 21 and 22, hereinbefore described; from this point the ¼ sec. cor. of secs. 21 and 22, bears S 0°02' E, 7.73 chs. dist.</p>	

Survey of Tract 39
T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS	
13.63	<p>A Bureau of Reclamation right-of-way marker, monumented with a bronze disk, 3$\frac{3}{4}$ ins. diam., flush with the ground, set in concrete, 15 ins. diam., with top mkd. 191+99.49 R.O.W. 125 FT RT R-8.</p>
44.02	<p>Point for a witness point on line 46-47, Tract 39.</p> <p>Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground with cap mkd.</p> <p style="text-align: center;">WP T4N R4W TR 39 S22 1985</p> <p>Cor. is located 4 lks. S of a fence, bearing S 89$\frac{1}{2}$° E and N 89$\frac{1}{2}$° W.</p>
56.035	<p>A Bureau of Reclamation right-of-way marker, monumented with a bronze disk, 3$\frac{3}{4}$ ins. diam., flush with the ground, set in concrete, 15 ins. diam., with top mkd. 220 + 00.10 R.O.W. 125 FT RT R-8.</p> <p>Cor. is located 4 lks. S of a fence, bears S 89$\frac{1}{2}$° E and N 89$\frac{1}{2}$° W.</p>
92.90	<p>Point for AP 47, Tract 39, at intersection with the line bet. secs. 22 and 23.</p> <p>Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 12 ins. below surface of a N and S road, with cap mkd.</p> <p style="text-align: center;">T4N R4W AP47 TR39 S23 S22 1985</p> <hr/> <p>from which</p> <p>An aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., set 30 ins. in the ground for a reference monument, bears S 63°51' E., 32.58 ft. dist., with cap mkd. RM T4N R4W AP 47 32.58 FT S 23 1985 and an arrow pointing to the cor.</p> <p>An aluminum post, 36 ins. long, $\frac{3}{4}$ in diam., set 30 ins. in the ground for a reference monument, bears S 70°29' W., 36.38 ft. dist., with cap mkd. RM T4N R4W AP 47 36.38 FT S 22 1985 and an arrow pointing to the cor.</p> <p>Both reference monuments are located in N and S fences.</p> <hr/> <p>N 0°01' W, on line 47-1, Tract 39, on a portion of the line bet. secs. 22 and 23.</p>
30.24	<p>AP 1, Tract 39, and place of beginning.</p> <hr/>

T 4 N, R 4 W, Gila and Salt River Mer., Arizona

CHAINS

GENERAL DESCRIPTION

The land encompassed in this survey is located about 50 miles NW of Phoenix, Arizona. The elevation ranges from about 1,400 ft. to 1,560 ft. above sea level.

The land varies from gently rolling to broken near the Hassayampa River. The land is covered with medium to dense creosote and scattered paloverde, mesquite and cacti. The Central Arizona Project Canal crosses the township flowing in a northeasterly direction.

Access is by way numerous improved and unimproved roads.

CERTIFICATE OF SURVEY

We, Paul L. Reeves and Stephen J. Malloy, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 8th day of November, 1985, we have dependently resurveyed a portion of the First Standard Parallel North on the south boundary of Township 5 North, Range 4 West; a portion of the First Guide Meridian West between Ranges 4 and 5 West, and a portion of the east boundary and subdivisional lines and the survey of subdivisions in sections 13, 21 and 29, and the metes-and-bounds survey of Tracts 37, 38 and 39, Township 4 North, Range 4 West, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

MAR 03 1986

 (Date)

Paul L. Reeves

 (Cadastral Surveyor)

MAR 03 1986

 (Date)

Stephen J. Malloy

 (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

Arizona State Office
 Bureau of Land Management
 Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the First Standard Parallel North on the south boundary of Township 5 North, Range 4 West; a portion of the First Guide Meridian West between Ranges 4 and 5 West, and a portion of the east boundary and subdivisional lines and the survey of subdivisions in sections 13, 21 and 29, and the metes-and-bounds survey of Tracts 37, 38 and 39, Township 4 North, Range 4 West, Gila and Salt River Meridian, Arizona, executed by Paul L. Reeves and Stephen J. Malloy, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

MAR 03 1986

 (Date)

James P. Kelley

 (Chief Cadastral Surveyor of Arizona)