



INDEX DIAGRAM

TOWNSHIP 12 NORTH, RANGE 20 EAST,

Third Standard Parallel North

9	9	8	7	6	5	3
16 6	35 5	32 4	29 3	26 2	23 1	13
35	34	31	28	25	22	
15 7	34 8	30 9	27 10	24 11	21 12	12
34	33	29	27	23	19	
14 18	17	16	15	14	18 13	11
					17	
19	20	21	22	23	24	11
30	29	28	27	26	25	10
31	32	33	34	35	36	

T 12 N, R 20 E, Gila and Salt River Mer., Arizona

## CHAINS

The following field notes are those of the dependent resurvey of the Third Standard Parallel North (north boundary) through Range 20 East, a portion of the Fifth Auxiliary Guide Meridian East (east boundary) through Township 12 North, a portion of the west boundary and a portion of the subdivisional lines of Township 12 North, Range 20 East, Gila and Salt River Meridian, Arizona.

The Third Standard Parallel North, (north boundary) was surveyed by C.B. Foster, in 1874. The Fifth Auxiliary Guide Meridian East (east boundary) was surveyed by J.L. Harris, in 1879. The west boundary was surveyed by H.A. Cox, in 1883. M.N. Grant retraced the Third Standard Parallel North (north boundary), the Fifth Auxiliary Guide Meridian East (east boundary), and surveyed the subdivisional lines, in 1883.

The resurvey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 620, Arizona, dated May 28, 1980.

The direction of lines of this survey were determined by observations on the sun and refer to the true meridian. Angles and distances were measured with a Zeiss Elta 46 Total Station instrument.

Prior to restoration of any corners, retracements of the previous surveys were performed and a diligent search was made to identify evidence of all previously established corner monuments. Identified corners were monumented in their original position; where available, collateral evidence was used to reestablish obliterated corners; and lost corners were reestablished at proportionate measurement based on official records. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the corner of sections 19 and 24, on the W bdy. of T 12 N, R 21 E, as determined from a tie made to U.S.C. & G.S. triangulation station "DAY 1958", is as follows:

Latitude: 34°24'40.87" N Longitude: 110°10'31.23" W

The mean magnetic declination is 12½° E.

---

Dependent Resurvey of the Third Standard Parallel North  
(North Bdy.) through R 20 E,  
Gila and Salt River Mer., Arizona

---

Reestablishment of the Dependent Resurvey  
by M.N. Grant, in 1883

---

Beginning at the point for the stan. cor. of Tps. 13 N, Rs. 20 and 21 E, at proportionate dist; there is no remaining evidence of the original cor.

At the cor. point

Set an aluminum post, 36 ins. long, ¾ in. diam., 37 ins. in the ground, with cap mkd.

Dependent Resurvey of the Third Standard Parallel North  
(North Bdy.) through R 20 E,  
Gila and Salt River Mer., Arizona

CHAINS

S C  
T13N  
R20E | R21E  
S36 | S31

1983

Set a steel fence post alongside the cor.

From this point a steel fence post, projecting 24 ins. above ground, bears N 44°16' W, 39.0 lks. dist., mkd. SE COR 36 R20E on the W side and SW COR 31 on the E side. This monument was set by Don Ellison, Arizona Department of Transportation using improper procedures and is not utilized in the course of this resurvey.

From this same point, the stan.  $\frac{1}{4}$  sec. cor. of sec. 31, T 13 N, R 21 E, bears S 89°57' E, 40.12 chs. dist., monumented with the base of a steel fence post, projecting 4 ins. above ground. This monument was set by Don Ellison, Arizona Department of Transportation, is at record bearing and dist. from an original bearing tree, is accepted as a careful and faithful perpetuation of the position of the original cor., and is used to proportion the Third Stan. Par. North, through R 20 E, from which the original bearing tree

A juniper, 22 ins. diam., bears N 65° W, 190 lks. dist., mkd.  $\frac{1}{4}$  S BT.

At the cor. point

Set a monument, 30 ins. long, composed of an iron post, 25 ins. long, 2 $\frac{1}{2}$  ins. diam., bonded to a magnetic poly breakaway base, 38 ins. in the ground, with brass cap mkd.

S C  
T13N R21E  
 $\frac{1}{4}$  S31

1983

Bury the fence post base alongside the iron post.

Cor. is located in a bladed portion of a road right-of-way, 6 lks. S of a barbed wire fence, bears E and W, and 46 lks. N of the center of pavement of the road bet. Taylor and Heber, 45 lks. wide, bears E and W.

N 89°57' W, on the S bdy. of sec. 36.

Over rolling land, with clusters of juniper.

40.07

Point for the stan.  $\frac{1}{4}$  sec. cor. of sec. 36, at proportionate dist; there is no remaining evidence of the original cor.

Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.

Dependent Resurvey of the Third Standard Parallel North  
(North Bdy.) through R 20 E,  
Gila and Salt River Mer., Arizona

CHAINS

S C  
T13N R20E  
¼ S36

1983

Cor. is located 127 lks. N of a fence, bears E and W.

From this point, a local monument, a steel fence post in a mound of stone, 2 ft. base, 8 ins. high, bears N 43°45' W, 81 lks. dist. This monument was set by Don Ellison, Arizona Department of Transportation, in the late 1960's using improper procedures and is not utilized in the course of this resurvey.

S 89°27' W, beginning new measurement.

Over rough, rolling land, through medium juniper.

2.01 The closing cor. of Tps. 12 N, Rs. 20 and 21 E, hereinafter described.

40.76 Point for the stan. cor. of secs. 35 and 36, at proportionate dist; there is no remaining evidence of the original cor.

Set an aluminum post, 60 ins. long, ¾ in. diam., 48 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.

S C  
T13N | R20E  
S35 | S36  
1983

Set a steel fence post alongside the cor.

Cor. is located 98 lks. N of a barbed wire fence, bears S 82° E and N 82° W.

S 89°19' W, on the S bdy. of sec. 35.

Over rolling land, through medium creosote.

39.44 The closing cor. of secs. 1 and 2, T 12 N, R 20 E, hereinafter described.

40.01 Point for the stan. ¼ sec. cor. of sec. 35, at proportionate dist; there is no remaining evidence of the original cor.

Set an aluminum post, 36 ins. long, ¾ in. diam., 30 ins. in the ground, with cap mkd.

S C  
T13N R20E  
¼ S35

1983

Set a steel fence post alongside the cor.

Cor. is located in a fence line, bears N and S.

Dependent Resurvey of the Third Standard Parallel North  
(North Bdy.) through R 20 E,  
Gila and Salt River Mer., Arizona

CHAINS		
	<p>From this point, a local monument, a rebar, 5/8 in. diam., projecting 2 ins. above ground, in a mound of stone, 3 ft. base, 1½ ft. high, bears N 52°41' W, 2.23 chs. dist. This monument was set by Don Ellison, Arizona Department of Transportation in the late 1960's using improper procedures and is not utilized in the course of this resurvey.</p> <hr/> <p>N 89°57' W, beginning new measurement.</p> <p>Over rolling land, through medium mesquite.</p> <p>40.87 Point for the stan. cor. of secs. 34 and 35, at proportionate dist. there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 30 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <p>S C T13N   R20E S34   S35 ----- 1983</p> </div> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 2.27 chs. S of a fence, bears N 88° E and S 88° W.</p> <p>From this point, a local monument, an iron bar, 5/8 in. diam., projecting 6 ins. above ground, bears North, 47 lks. dist; this monument was set by Don Ellison, Arizona Department of Transportation in the late 1960's using improper procedures and is not utilized in the course of this resurvey.</p>	
	<p>S 89°27' W, on the S bdy. of sec. 34.</p> <p>Over nearly level, open land.</p> <p>39.22 The closing cor. of secs. 2 and 3, T 12 N, R 20 E, hereinafter described.</p> <p>40.57 Point for the stan. ¼ sec. cor. of sec. 34, at proportionate dist; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 26 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <div style="text-align: center;"> <p>S C T13N R20E ¼ S34 ----- 1983</p> </div> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 56 lks. N of a track road, bears N 70° E and S 70° W.</p> <hr/> <p>S 89°03' W, beginning new measurement.</p>	

Dependent Resurvey of the Third Standard Parallel North  
(North Bdy.) through R 20 E,  
Gila and Salt River Mer., Arizona

CHAINS												
	Over level, open land.											
40.46	Point for the stan. cor. of secs. 33 and 34, at proportionate dist; there is no remaining evidence of the original cor.											
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, with cap mkd.											
	<table border="0"> <tr><td colspan="2">S C</td></tr> <tr><td>T13N</td><td>R20E</td></tr> <tr><td>S33</td><td>S34</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td colspan="2">1983</td></tr> </table>	S C		T13N	R20E	S33	S34	<hr/>		1983		
S C												
T13N	R20E											
S33	S34											
<hr/>												
1983												
	Set a steel fence post alongside the cor.											
	Cor. is located 190 lks. N of a track road, bears E and W.											
	<hr/>											
	S 89°29' W, on the S bdy. of sec. 33.											
	Over level, open land.											
38.07	The closing cor. of secs. 3 and 4, T 12 N, R 20 E, hereinafter described.											
40.41	Point for the stan. $\frac{1}{4}$ sec. cor. of sec. 33, at proportionate dist; there is no remaining evidence of the original cor.											
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 28 ins. in the ground, with cap mkd.											
	<table border="0"> <tr><td colspan="2">S C</td></tr> <tr><td>T13N</td><td>R20E</td></tr> <tr><td><math>\frac{1}{4}</math> S33</td><td></td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td colspan="2">1983</td></tr> </table>	S C		T13N	R20E	$\frac{1}{4}$ S33		<hr/>		1983		
S C												
T13N	R20E											
$\frac{1}{4}$ S33												
<hr/>												
1983												
	Set a steel fence post alongside the cor.											
	Cor. is located 90 lks. N of a track road, bears E and W.											
	<hr/>											
	S 89°03' W, beginning new measurement.											
	Slight asc. over mostly level, open land.											
40.58	Point for the stan. cor. of secs. 32 and 33, at proportionate dist; there is no remaining evidence of the original cor.											
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.											
	<table border="0"> <tr><td colspan="2">S C</td></tr> <tr><td>T13N</td><td>R20E</td></tr> <tr><td>S32</td><td>S33</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td colspan="2">1983</td></tr> </table>	S C		T13N	R20E	S32	S33	<hr/>		1983		
S C												
T13N	R20E											
S32	S33											
<hr/>												
1983												
	Set a steel fence post alongside the cor.											

Dependent Resurvey of the Third Standard Parallel North  
(North Bdy.) through R 20 E,  
Gila and Salt River Mer., Arizona

CHAINS	
	<p>Cor. is located 80 lks. S of a track road, bears E and W.</p>
	<p>N 89°09' W, on the S bdy. of sec. 32.</p>
	<p>Over rolling land, through railed juniper.</p>
0.80	<p>Ridge, bears N 25° E and S 25° W.</p>
33.00	<p>Fence, bears N and S.</p>
36.31	<p>The closing cor. of secs. 4 and 5, T 12 N, R 20 E hereinafter described.</p>
40.12	<p>Point for the stan. <math>\frac{1}{4}</math> sec. cor. of sec. 32, at proportionate dist; there is no remaining evidence of the original cor.</p>
	<p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 30 ins. in the ground, with cap mkd.</p>
	<p style="text-align: center;">S C</p>
	<p style="text-align: center;">T13N R20E</p>
	<p style="text-align: center;"><math>\frac{1}{4}</math> S32</p>
	<p style="text-align: center;">1983</p>
	<p>Set a steel fence post alongside the cor.</p>
	<p>Cor. is located 38 lks. S of a track road, bears E and W, and 53 lks. S of a fence, bears E and W.</p>
	<p>S 89°13' W, beginning new measurement.</p>
	<p>Over rolling land, through railed juniper.</p>
27.27	<p>A local monument, a rebar, <math>\frac{5}{8}</math> in. diam., projecting 4 ins. above ground, with a washer mkd. PE 8418, bears North, 40 lks. dist., this monument was set in 1973 by Richard O. Burton, P E No. 8418, AZ, to mark the cor. of private lots Lots H and I, sec. 5, using improper procedures, as shown on the plat of the Matkin-Burton Engineers survey for Jacob Weinberg, on file with Ron Matkin, Show Low, AZ, and is not utilized in the course of this resurvey.</p>
40.30	<p>Fence, bears N and S.</p>
40.37	<p>Point for the stan. cor. of secs. 31 and 32, at proportionate dist; there is no remaining evidence of the original cor.</p>
	<p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 28 ins. in the ground, with cap mkd.</p>
	<p style="text-align: center;">S C</p>
	<p style="text-align: center;">T13N R20E</p>
	<p style="text-align: center;">S31   S32</p>
	<p style="text-align: center;">1983</p>
	<p>Raise a mound of stone, 3 ft. base, 10 ins. high, N of cor.</p>

Dependent Resurvey of the Third Standard Parallel North  
(North Bdy.) through R 20 E,  
Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 25 lks. S of a track road, bears E and W, and 45 lks. S of a fence, bears E and W.</p> <hr/> <p>S 89°34' W, on the S bdy. of sec. 31.</p> <p>Over level land, through railed juniper.</p>	
35.84	The closing cor. of secs. 5 and 6, T 12 N, R 20 E, hereinafter described.	
36.16	A local monument, a rebar, 5/8 in. diam., projecting 3 ins. above ground, with a washer mkd. PE 5047, bears North, 12 lks. dist., this monument was set in 1973 by George Matkin, PE No. 5047, AZ, to mark the SW cor. of private lot D, sec. 31, using improper procedures, as shown on the plat of the Matkin-Burton Engineers survey for Jacob Weinberg, on file with Ron Matkin, Show Low, AZ, and is not utilized in the course of this resurvey.	
40.27	<p>Point for the stan. ¼ sec. cor. of sec. 31, at proportionate dist; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 30 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S C T13N R20E ¼ S31</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1983</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 80 lks. S of a track road, bears E and W.</p> <hr/> <p>S 89°16' W, beginning new measurement.</p> <p>Over rolling hills, through juniper.</p>	
24.26	The closing cor. of Tps. 12 N, Rs. 19 and 20 E, hereinafter described.	
40.31	<p>The stan. cor. of Tps. 13 N, Rs. 19 and 20 E, monumented with a sandstone, 34 x 12 x 4 ins., firmly set 10 ins. in the ground, and in a mound of stone, 2½ ft. base, 6 ins. high, mkd. CC 36-31 on the S face. This monument set by Harold Williams, U.S. Forest Service, at record bearing and dist. from the only remaining bearing tree and is accepted as a careful and faithful perpetuation of the position of the original cor., from which the bearing tree described in the 1883 survey bet. Rs. 19 and 20 E,</p> <p style="text-align: center;">A juniper, 14 ins. diam., bears N 15° E, 45 lks. dist., mkd. TXIIIN RXXE SXXXI BT.</p> <p>At the cor. point</p>	

Dependent Resurvey of the Third Standard Parallel North  
(North Bdy.) through R 20 E,  
Gila and Salt River Mer., Arizona

CHAINS

Set a monument, 30 ins. long, composed of an iron post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 25 ins. in the ground, with brass cap mkd.

S C  
T13N  
R19E | R20E  
S36 | S31  
|  
T12N R19E S 1  
1983

Bury the mkd. stone alongside the iron post.

Raise a mound of stone, 2½ ft. base, 1 ft. high, N of cor.

Set a steel fence post alongside the cor.

Cor. is located 15 lks. S of a fence, bears E and W.

Dependent Resurvey of a Portion of the Fifth Auxiliary Guide Mer. East ( East Bdy.) through T 12 N,  
Gila and Salt River Mer., Arizona

Reestablishment of the Dependent Resurvey by  
M.N. Grant, in 1883

From the cor. of secs. 19 and 30 only, T 12 N, R 21 E, monumented with the base of an old hewn post, 6 ins. long, 4 ins. diam., firmly set 8 ins. in the ground, in a mound of stone, 3 ft. base, 6 ins. high, from which the remains of the original bearing tree

A hole, 10 ins. diam., filled with the decomposed root of a tree, bears S 12° E, 50 lks. dist., the scorched remains of a pine tree is lying alongside.

At the cor. point

Set a monument, 30 ins. long, composed of an iron post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 25 ins. in the ground, with brass cap mkd.

T12N  
R20E | R21E  
| S19  
S25 | \_\_\_\_\_  
| S30  
1983

from which

A pinyon, 8 ins. diam., bears N 53° E, 110 lks. dist., mkd. T12N R21E S19 BT.

A juniper, 10 ins. diam., bears S 40° E, 85½ lks. dist., mkd. T12N R21E S30 BT.

Dependent Resurvey of a Portion of the Fifth Auxiliary  
Guide Mer. East ( East Bdy.) through T 12 N,  
Gila and Salt River Mer., Arizona

CHAINS														
	<p>Deposit the original wood post alongside the iron post.</p> <p>Raise a mound of stone, 2½ ft. base, 8 ins. high, E of cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>N 0°15' E, on the W bdy. of sec. 19, T 12 N, R 21 E.</p> <p>Over rolling land, through thick juniper and sparse pinyon pine.</p>													
27.67	<p>The original closing cor. of secs. 24 and 25, T 12 N, R 20 E, bears East, 11 lks. dist., monumented with a sandstone, 16 x 12 x 6 ins., set in a mound of stone, 3 ft. base, 2 ft. high and mkd. with 4 grooves on the N face, 2 grooves on the S face and CC on the W face.</p>													
40.73	<p>Point for the ¼ sec. cor. of sec. 19 only, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p>													
81.46	<p>Point for the cor. of secs. 18 and 19 only, at proportionate dist; there in no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 30 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p>													
	<div style="text-align: center;"> <p>T12N</p> <table border="0"> <tr> <td>R20E</td> <td> </td> <td>R21E</td> </tr> <tr> <td></td> <td> </td> <td>S18</td> </tr> <tr> <td>S24</td> <td> </td> <td>_____</td> </tr> <tr> <td></td> <td> </td> <td>S19</td> </tr> </table> <p>1983</p> </div> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 170 lks. W of a fence, bears N and S.</p>	R20E		R21E			S18	S24		_____			S19	
R20E		R21E												
		S18												
S24		_____												
		S19												
	<p>N 0°06' E, on the W bdy. of sec. 18, T 12 N, R 21 E.</p> <p>Over rolling hills, along a fence line, through destroyed juniper.</p>													
26.87	<p>The closing cor. of secs. 13 and 24, T 12 N, R 20 E, hereinafter described.</p>													
40.33	<p>Point for the ¼ sec. cor. of sec. 18, at proportionate dist; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 30 ins. in the ground, with cap mkd.</p>													

Dependent Resurvey of a Portion of the Fifth Auxiliary  
Guide Mer. East ( East Bdy.) through T 12 N,  
Gila and Salt River Mer., Arizona

CHAINS

T12N  
R20E | R21E  
      | ¼ S18  
      |  
      1983

Set a steel fence post alongside the cor.

Cor. is located in a cleared area, ½ lk. E of a N and S fence, and 146 lks. N of a fence, bears N 84° W and N.

80.66

Point for the cor. of secs. 7 and 18 only, at proportionate dist; there is no remaining evidence of the original cor.

Set an aluminum post, 36 ins. long, ¾ in. diam., 32 ins. in the ground, with cap mkd.

T12N  
R20E | R21E  
      | S 7  
S13 | \_\_\_\_\_  
      | S18  
      1983

Set a steel fence post alongside the cor.

Cor. is located on the E slope of a cleared area, 7 lks. E of a fence, bears N 10° E and S 10° W.

---

N 0°10' E, on the W bdy. of sec. 7, T 12 N, R 21 E.

Over rolling land, along a fence line, through railed juniper.

26.16

The closing cor. of secs. 12 and 13, T 12 N, R 20 E, hereinafter described.

40.33

The ¼ sec. cor. of sec. 7 only, monumented with the base of an old hewn wood post, 6 ins. long, 5 ins. diam., firmly set 14 ins. in the ground, in an old mound of stone, 2½ ft. base, flush with ground, covered with a newer mound of stone, 3 ft. base, 6 ins. high, and impaled by a steel fence post, projecting 3 ft. above ground. The steel fence post and newer mound of stone were set by Don Ellison, Arizona Department of Transportation, in late 1960's, using the old mound of stone as evidence of the original cor. position.

At the cor. point

Set an aluminum post, 36 ins. long, ¾ in. diam., 30 ins. in the ground, with cap mkd.

T12N  
R20E | R21E  
      | ¼ S 7  
      |  
      1983

Deposit the wood post and the steel fence post alongside the aluminum post.

Dependent Resurvey of a Portion of the Fifth Auxiliary  
Guide Mer. East ( East Bdy.) through T 12 N,  
Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set a steel fence post alongside the cor.</p>	
	<p>Cor. is located 1½ lks. E of a fence, bears N and S.</p>	
	<p>_____</p> <p>N 0°15' W, beginning new measurement.</p>	
	<p>Over open, rolling land, along a fence line.</p>	
26.03	<p>The ¼ sec. cor. of sec. 12 only, T 12 N, R 20 E, not monumented.</p>	
40.08	<p>The cor. of secs. 6 and 7, monumented with an old scattered mound of stone, with a steel fence post projecting 3 ft. above ground, in its center. This mound of stone is accepted as the best available evidence of the original cor. position.</p>	
	<p>At the cor. point</p>	
	<p>Set an aluminum post, 72 ins. long, ¾ in. diam., 62 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p>	
	<p style="text-align: center;">             T12N              R20E   R21E                S 6              S12   _____                S 7              1983           </p>	
	<p>Deposit the steel fence post alongside the iron post.</p>	
	<p>Set a steel fence post alongside the cor.</p>	
	<p>Cor. is located 24½ lks. E of a fence, bears N and S.</p>	
	<p>_____</p> <p>N 0°33' W, on the W bdy. of sec. 6, T 12 N, R 21 E.</p>	
	<p>Over rolling land, along a fence line, through sparse juniper.</p>	
27.34	<p>The closing cor. of secs. 1 and 12, T 12 N, R 20 E, hereinafter described.</p>	
40.48	<p>The ¼ sec. cor. of sec. 6 only, monumented with an old scattered mound of stone underneath a newer mound of stone, 3 ft. base, 1 ft. high, with the following monuments in the center; a sandstone, 27 x 15 x 4 ins., mkd. ¼ on one face, a steel fence post projecting 18 ins. above ground, and a rebar, 2 ft. long, 5/8 in. diam., projecting 1 in. The sandstone was set by Harold Williams, U.S. Forest Service, in the mid 1960's. The steel fence post was set by Don Ellison, Arizona Department of Transportation, in the late 1960's. The rebar is of unknown origin.</p>	
	<p>At the cor. point</p>	
	<p>Set an aluminum post, 36 ins. long, ¾ in. diam., 31 ins. in the ground, with cap mkd.</p>	

Dependent Resurvey of a Portion of the Fifth Auxiliary  
Guide Mer. East ( East Bdy.) through T 12 N,  
Gila and Salt River Mer., Arizona

CHAINS

T12N  
R20E | R21E  
          | ¼ S 6  
          |  
          1983

Deposit the mkd. stone, steel fence post and rebar  
alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 1 ft. high, E of  
cor.

Set a steel fence post alongside the cor.

Cor. is located 83 lks. W of fence bearing N and S.

---

N 0°18' E, beginning new measurement.

Over mostly level land, along a fence line, through  
sparse juniper.

36.56

Point for the closing cor. of Tps. 12 N, Rs. 20 and 21  
E, at proportionate dist on the Third Stan. Par. North;  
there is no remaining evidence of the original closing  
cor.

Set an aluminum post, 36 ins. long, ¾ in. diam., 28 ins.  
in the ground, in a mound of stone, 2½ ft. base, to top,  
with cap mkd.

T13N R20E  
S36  

---

S 1 | S 6  
R20E | R21E  
T12N  
C C  
1983

Set a steel fence post alongside the cor.

Cor. is located N 21½° E, 123 lks. dist. from a fence  
cor., barbed wire fences extend E, S and W.

From this point, the stan. ¼ sec. cor. of sec. 36,  
T 13 N, R 20 E, bears S 89°57' E, 2.01 chs. dist.,  
hereinbefore described.

From this point, a local monument, a steel fence post  
in a mound of stone, 2 ft. base, 3 ins. high, bears  
N 40°34' W, 80 lks. dist., this monument was set by Don  
Ellison, Arizona Department of Transportation, in the  
late 1960's using improper procedures and is not  
utilized in the course of this resurvey.

---

Dependent Resurvey of a Portion of the West Bdy.,  
T 12 N, R 20 E, Gila and Salt River Mer., Arizona

---

Reestablishment of the Survey executed  
by H.A. Cox, in 1883

---

Dependent Resurvey of a Portion of the West Bdy.,  
T 12 N, R 20 E, Gila and Salt River Mer., Arizona

CHAINS

From the  $\frac{1}{4}$  sec. cor. of secs. 13 and 18, monumented with a limestone, 18 x 12 x 4 ins., set in a mound of stone, 3 ft. base, 1 ft. high, mkd.  $\frac{1}{4}$  on the W face, from which the original bearing trees

A sec. of a pine trunk, 3 ft. long, containing a blaze, bears S 45° E, 68 lks. dist. The blaze, found lying loose on the ground, is mkd.  $\frac{1}{4}$  S BT.

A cluster of juniper limbs, growing from a decomposed trunk, bears N 35° W, 130 lks. dist., no blaze was found.

At the cor. point

Set a monument, 30 ins. long, composed of an iron post, 25 ins. long, 2 $\frac{1}{2}$  ins. diam., bonded to a magnetic poly breakaway base, 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T12N  
 $\frac{1}{4}$   
R19E | R20E  
S13 | S18  
1983

Deposit the mkd. stone in the mound of stone.

Cor. is located in a cleared area, 9 lks. E of a fence, bears N and S.

N 0°06' E, bet. secs. 13 and 18.

Over open rolling land, along a fence line.

40.10

The cor. of secs. 7, 12, 13 and 18, monumented with a mound of stone, 3 ft. base, 6 ins. high, in a fence line, bears N and S. This monument is accepted as the best available evidence of the original cor. position.

At the cor. point

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 24 ins. in the ground, in a mound of stone, 3 $\frac{1}{2}$  ft. base, to top, with cap mkd.

T12N  
R19E | R20E  
S12 | S 7  
S13 | S18  
1983

Cor. is located in a fence line, bears N and S.

N 0°03' E, bet. secs. 7 and 12.

Over rolling land, along a fence line, through medium juniper.

40.18

The  $\frac{1}{4}$  sec. cor. of secs. 7 and 12, monumented with a granite stone, 13 x 12 x 7 ins. (record size: 16 x 8 x 3 ins.) mkd.  $\frac{1}{4}$  on top, lying loose in a mound of stone, 3 $\frac{1}{2}$  ft. base, 6 ins. high, and in a fence line, bears N and S.

Dependent Resurvey of a Portion of the West Bdy.,  
T 12 N, R 20 E, Gila and Salt River Mer., Arizona

## CHAINS

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T12N		
¼		
R19E		R20E
S12		S 7
1983		

Deposit the mkd. stone in the mound of stone.

Cor. is located 2 lks. E of a fence, bears N and S.

---

N 0°38' E, beginning new measurement.

Over rolling land, along a fence line, through medium juniper.

40.34 Point for the cor. of secs. 1, 6, 7 and 12, at proportionate dist; there is no remaining evidence of the original cor.

Set an aluminum post, 28 ins. long, 1 in. diam., 14 ins. in the ground, in a mound of stone, 3½ ft. base, to top, with cap mkd.

T12N		
R19E		R20E
S 1		S 6
S12		S 7
1983		

from which

A juniper, 10 ins. diam., bears S 48° E,  
46 lks. dist., mkd. T12N R20E S7 BT.

Set a steel fence post alongside the cor.

Cor. is located 50 lks. N of a cor. of fences bearing S, E and W for 15 lks. to the cor. of fences bearing N and E; and 60 lks. N of the center of a track road, 20 lks. wide, bears E and W.

---

N 0°38' E, bet. secs. 1 and 6.

Over rolling land, along a fence line, through medium juniper.

40.34 Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate dist; there is no remaining evidence of the original cor.

Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.

Dependent Resurvey of a Portion of the West Bdy.,  
T 12 N, R 20 E, Gila and Salt River Mer., Arizona

CHAINS

T12N  
 $\frac{1}{4}$   
R19E | R20E  
S 1 | S 6  
1983

from which

A juniper limb, 6 ins. diam., bears N 34° W,  
36½ lks. dist., mkd.  $\frac{1}{4}$  S1 BT.

Set a steel fence post alongside the cor.

Cor. is located in medium juniper, 79 lks. E of a  
fence, bears N and S.

46.64

Point for the closing cor. of Tps. 12 N, Rs. 19 and  
20 E, at proportionate dist. on the Third Stan. Par.  
North; there is no remaining evidence of the original  
cor.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 28 ins.  
in the ground, with cap mkd.

T13N R20E  
S31

S 1 | S 6  
R19E | R20E  
T12N  
C C  
1983

Raise a mound of stone, 3 ft. base, 10 ins. high, S of  
cor.

Set a steel fence post alongside the cor.

From this point the stan. cor. of Tps. 13 N, Rs. 19 and  
20 E, bears S 89° 16' W, 16.05 chs. dist., hereinbefore  
described.

---

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 12 N, R 20 E, Gila and Salt River Mer., Arizona

---

Reestablishment of the survey executed  
by M.N. Grant, in 1883

---

From the cor. of secs. 13, 14, 23 and 24, monumented  
with a sandstone, 13 x 6 x 5 ins., projecting 13 ins.  
above ground, in an old mound of stone, 3 ft. diam., 2  
ins. high, mkd. with 1 groove on the E and 3 grooves on  
the S, a newer mound of stone, 3 ft. base, 10 ins. high,  
was placed around the stone by Harold Williams, U.S.  
Forest Service, in 1967.

At the cor. point

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 26 ins.  
in the ground, in a mound of stone, 3 ft. base, to top,  
with cap mkd.

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 12 N, R 20 E, Gila and Salt River Mer., Arizona

CHAINS	
38.49	<p style="text-align: center;">T12N R20E S14   S13 S23   S24 1983</p> <p>Deposit the mkd. stone in the mound of stone.</p> <p>N 89°33' E, bet. secs. 13 and 24.</p> <p>Over rolling hills, through medium juniper.</p> <p>Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate dist; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 30 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p>
77.36	<p style="text-align: center;">T12N R20E ¼ S13 S24 1983</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located on a flat ridge, bears N 50° E only, in new growth of juniper.</p> <p>Point for the closing cor. of secs. 13 and 24, at proportionate dist. on the Fifth Auxiliary Guide Mer. East; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 30 ins. in the ground, with cap mkd.</p>
41.18	<p style="text-align: center;">T12N R20E   R21E S13   CC ———   S18 S24   1983</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 55 lks. W of a fence, bears N and S.</p> <p>From this point, the ¼ sec. cor. of sec. 18 only, T 12 N, R 21 E, bears N 0°06' E, 13.46 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N 4°03' W, bet. secs. 13 and 14.</p> <p>Over rolling land, through medium juniper.</p> <p>The ¼ sec. cor. of secs. 13 and 14, monumented with a limestone, 14 x 12 x 9 ins., set in a mound of stone, 3 ft. base, 1 ft. high, mkd. ¼ on the N face. The stone was set by Harold Williams, U.S. Forest Service, in 1967, in the old mound and is accepted as the best available evidence of the original cor.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 12 N, R 20 E, Gila and Salt River Mer., Arizona

CHAINS

At the cor. point

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 26 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.

T12N R20E  
 $\frac{1}{4}$   
S14 | S13  
1983

Deposit the mkd. stone in the mound of stone.

N 0°17' W, beginning new measurement.

Over rolling land, through medium juniper.

39.91

The cor. of secs. 11, 12, 13 and 14, monumented with a sandstone, 18 x 11 x 5 ins., with no discernable marks, set in a mound of stone, 2½ ft. base, 1½ ft. high. A sandstone, 24 x 10 x 4 ins., was lying loose alongside the mound of stone, mkd. with 4 grooves on one side and 1 groove on another side. This stone was set by Harold Williams, U.S. Forest Service, in 1967.

from which an original bearing tree

A juniper, 16 ins. diam., bears S 54½° W, 116 lks. dist., mkd. T12N R20E S14 BT. (Record: S 61° W)

At the cor. point

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 32 ins. in the ground, in a collar stone, with cap mkd.

T12N R20E  
S11 | S12  
S14 | S13  
1983

Bury the mkd. stone and the original stone alongside the cor.

From this cor. the U.S.C. & G.S. triangulation station "DAY 1958" bears N 48°52'34" W, (forward bearing) 354.09 chs. dist., monumented with a brass tablet set flush in a concrete square 10 x 10 ins., projecting 3 ins. above the ground with reference marks as described.

S 89°42' E, bet. secs. 12 and 13.

Asc. over rolling land, through medium juniper.

5.80

Fence, bears N, E and S, continue over rolling land, along a fence line, through railed and some live juniper.

40.31

Point for the  $\frac{1}{4}$  sec. cor. of secs. 12 and 13, at proportionate dist; there is no remaining evidence of the original cor.

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 12 N, R 20 E, Gila and Salt River Mer., Arizona

CHAINS

Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.

T12N R20E  
 $\frac{1}{4}$   $\frac{S12}{S13}$   
 1983

Set a steel fence post alongside the cor.

Cor. is located 20 lks. S of a fence, bears E and W.

41.70 Small wash, drains N 50° E.

48.90 Ridge, bears N 15° E and S 15° W, desc. into flat land, along a fence line.

80.48 Point for the closing cor. of secs. 12 and 13, at intersection with the Fifth Auxiliary Guide Mer. East.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 32 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.

T12N  
 R20E | R21E  
 S12 |  
 CC ——— | S 7  
 S13 |  
 1983

Set a steel fence post alongside the cor.

Cor. is located S 45° E, 5½ lks. from a fence cor. post, fence extends N, S and W, and 45 lks. N of a track road bearing E and W.

From this point, a steel fence post, projecting 2 ft. above ground, in a mound of stone, 3 ft. base, 6 ins. high, bears S 89°42' E, 7 lks. dist., mkd. N E C. This monument was set as the closing cor. by Don Ellison, Arizona Department of Transportation, in the late 1960's and is accepted as the best available evidence of the original closing cor. position. This now stands for an amended monument at the amended cor. point.

Set an aluminum post, 28 ins. long, 1 in. diam., 32 ins. in the ground, with cap mkd.

A M  
 T12N  
 R20E | R21E  
 S12 |  
 CC ——— | S 7  
 S13 |  
 1983

Bury the steel post alongside the aluminum post.

Cor. is located 45 lks. N of a track road, bears E and W.

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 12 N, R 20 E, Gila and Salt River Mer., Arizona

CHAINS

From this same point, the  $\frac{1}{4}$  sec. cor. of sec. 7 only, T 12 N, R 21 E, bears N  $0^{\circ}10'$  E, 14.17 chs. dist., hereinbefore described.

From the cor. of secs. 11, 12, 13 and 14.

N  $0^{\circ}10'$  W, bet. secs. 11 and 12.

Over rolling hills, through medium juniper.

40.20

The  $\frac{1}{4}$  sec. cor. of secs. 11 and 12, monumented with a limestone, 18 x 10 x 3 ins., lying in a mound of stone, 3 ft. base, 1 ft. high, mkd.  $\frac{1}{4}$  on the W face. The stone was set by Harold Williams, U.S. Forest Service, in 1967, using a small mound of stone as evidence and from which the original bearing trees

A juniper limb, 8 ins. diam., bears N  $87^{\circ}$  E, 11 lks. dist., with a partially healed blaze, mkd.  $\frac{1}{4}$  S BT. (Record: N  $78^{\circ}$  E, 12 lks. dist.)

A burned juniper stump, 8 ins. diam., bears N  $70^{\circ}$  W, 58 lks. dist., with a blaze and illegible scribing. (Record: N  $66^{\circ}$  W, 57 lks. dist.)

At the cor. point

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 24 ins. in the ground, in a mound of stone,  $3\frac{1}{2}$  ft. base, to top, with cap mkd.

T12N R20E

$\frac{1}{4}$

S11 | S12

1983

Deposit the mkd. stone alongside the aluminum post.

Set a steel fence post alongside the cor.

Cor. is located  $14\frac{1}{2}$  lks. W of a fence, bears N and S.

N  $0^{\circ}11'$  W, beginning new measurement.

Over rolling land, through medium juniper.

40.44

The cor. of secs. 1, 2, 11 and 12, monumented with a sandstone, 15 x 8 x 4 ins., set in mound of stone, 3 ft. base, 2 ft. high, mkd. with 1 groove on the E face and 5 grooves on the S face. A sandstone, 23 x 11 x 7 ins., was lying loose alongside, mkd. with 1 groove on one side and 5 grooves on another side, and was set by Harold Williams, U.S. Forest Service, in 1967.

At the cor. point

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 26 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 12 N, R 20 E, Gila and Salt River Mer., Arizona

CHAINS

T12N R20E  
S 2 | S 1  
S11 | S12  
1983

Deposit both mkd. stones in the mound of stone.

Cor. is located 15 lks. N of a fence cor., barbed wire extend N, E, S and W.

40.51

N 89°38' E, bet. secs. 1 and 12.

Over open, level land, through grasses.

Point for the ¼ sec. cor. of secs. 1 and 12, at proportionate dist; there is no remaining evidence of the original cor.

Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.

T12N R20E  
¼ S 1  
S12  
1983

Set a steel fence post alongside the cor.

Cor. is located 88 lks. N of a fence, bears E and W.

79.85

Fence, bears N and S.

80.32

The closing cor. of secs. 1 and 12, monumented with a granite stone, 12 x 6 x 4 ins., alongside a steel fence post, projecting 2 ft. above ground, in a mound of stone, 2½ ft. base, 6 ins. high, at intersection with the Fifth Auxiliary Guide Mer. East. The steel fence post and mound was set by Don Ellison, Arizona Department of Transportation, in the late 1960's and is accepted as the best available evidence of the original cor. position.

At the cor. point

Set an aluminum post, 36 ins. long, ¾ in. diam., 24 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.

T12N  
R20E | R21E  
S 1 |  
CC ——— | S 6  
S12 |  
1983

Bury the mkd. stone and fence post alongside the cor.

Set a steel fence post alongside the cor.

Cor. is located 117 lks. N of the projection of a fence, bears W from a fence which bears N and S.

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 12 N, R 20 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>From this cor., the <math>\frac{1}{4}</math> sec. cor. of sec. 6 only, T 12 N, R 21 E, bears N <math>0^{\circ}33'</math> W, 13.14 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12. N <math>2^{\circ}35'</math> E, bet. secs. 1 and 2. Over rolling hills, through medium juniper.</p>
39.41	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 2, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p>
49.40	<p>Point for the closing cor. of secs. 1 and 2, at proportionate dist. on the Third Stan. Par. North, there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 30 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T13N R20E S35</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S 2   S 1 T12N   R20E C C 1983</p> <p>Set a steel fence post alongside the cor.</p> <p>From this point the stan. <math>\frac{1}{4}</math> sec. cor. of sec. 35, T 13 N, R 20 E, bears S <math>89^{\circ}19'</math> W, 57 lks. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14. N <math>88^{\circ}40'</math> W, bet. secs. 11 and 14. Over rolling land, through medium juniper.</p>
39.94	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 11 and 14, monumented with the decomposed base of a wood post, 6 ins. long, <math>3\frac{1}{2}</math> ins. diam., firmly set 8 ins. in the ground, with a burned top. A sandstone, 18 x 15 x 8 ins., projecting 15 ins. above ground, mkd. <math>\frac{1}{4}</math>, was alongside. The sandstone was set by Harold Williams, U.S. Forest Service, in 1967, using a wood post as evidence. The stump to this wood post is accepted as the best evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set a monument, 30 ins. long, composed of an iron post, 25 ins. long, <math>2\frac{1}{2}</math> ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 12 N, R 20 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T12N R20E  <math>\frac{1}{4}</math> <u>S11</u>            S14            1983</p> <p>Deposit the post stump and the mkd. stone alongside the iron post.</p> <hr/> <p>N 89°40' W, beginning new measurement.</p> <p>Over rolling hills, through medium juniper.</p>
39.36	<p>The cor. of secs. 10, 11, 14 and 15, monumented with a sandstone, 20 x 14 x 4 ins., set in a mound of stone, 3 ft. base, 12 ins. high, mkd. with 4 grooves on a narrow face. A sandstone, 14 x 12 x 4 ins., was found in the same mound of stone, mkd. with 2 grooves on the E face and 4 grooves on the S face. The latter stone was set by Harold Williams, U.S. Forest Service, in 1967.</p> <p>from which the original bearing tree</p> <p style="padding-left: 40px;">The base of a fallen pinyon, 8 ins. diam., bears N 22° E, 26 lks. dist., blaze area decomposed. ( Record: N 30° E, 28 lks. dist.)</p> <p>At the cor. point</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 22 ins. in the ground, in a mound of stone, 3½ ft. base, to top, with cap mkd.</p>
	<p style="text-align: center;">T12N R20E  <u>S10   S11</u>  <u>S15   S14</u>            1983</p> <p>from which</p> <p style="padding-left: 40px;">A pinyon, 8 ins. diam., bears N 56° E, 80.4 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears N 24° W, 76.1 lks. dist., mkd. X BT.</p> <p>Deposit both mkd. stones alongside the aluminum post.</p> <hr/> <p>N 0°34' W, bet. secs. 10 and 11.</p> <p>Over rolling land, through medium pinyon pine and juniper.</p>
23.00	Cottonwood Wash, 15 lks. wide, drains S 75° E. (scaled)
34.30	Canyon rim, bears E and N 10° W.
39.70	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11, at proportionate dist; there is no remaining evidence of the original cor.

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 12 N, R 20 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 3½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R20E           ½ S10   S11           1983</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in torn land.</p> <p>Over rolling land, cleared of juniper.</p>	
79.15	Fence, bears E and W.	
79.40	<p>Point for the cor. of secs. 2, 3, 10 and 11, at proportionate dist; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 28 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R20E S 3   S 2 S10   S11           1983</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 126 lks. W of a fence, bears N and S and 25 lks. N of a fence bearing E and W.</p> <p>From this point, a sandstone, 27 x 12 x 4 ins., in a mound of stone, 2½ ft. base, 1½ ft. high, bears S 51°42' E, 1.607 chs. dist., mkd. with 2 grooves on the E face and 5 grooves on the S face. This stone was set by Harold Williams, U.S. Forest Service, in 1967, was perpetuated using erroneous evidence and is not utilized in the course of this resurvey.</p>	
39.90	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S 89°56' W, bet. secs. 2 and 11.</p> <p>Over level, open terrain, along a fence line.</p> <p>Point for the ¼ sec. cor. of secs. 2 and 11, at proportionate dist; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R20E           ¼ S 2           S11           1983</p> <p>from which</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 12 N, R 20 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>A juniper, 10 ins. diam., bears N 85° W, 29½ lks. dist., mkd. ¼ S2 BT.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located on a N slope, 18½ lks. N of a fence, bears E and W.</p> <p>Over hilly terrain, through scattered juniper.</p>	
79.80	<p>The cor. of secs. 2, 3, 10 and 11.</p> <hr/> <p>N 1°34' E, bet. secs. 2 and 3.</p> <p>Over rolling land, through groves of medium juniper.</p>	
39.71	<p>Point for the ¼ sec. cor. of secs. 2 and 3, at propor- tionate dist; there is no remaining evidence of the original cor.</p> <p>Set a monument, 30 ins. long, composed of an iron post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.</p>	
49.14	<p style="text-align: center;">T12N R20E ¼ S 3   S 2 1983</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located N 76½° E, 72½ lks. dist. from a fence cor., fence lines extend N 65° E, S and S 65° W.</p> <p>Point for the closing cor. of secs. 2 and 3, at propor- tionate dist. on the Third Stan. Par. North; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 40 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T13N R20E S34 ----- S 3   S 2 T12N   R20E C C 1983</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 7 lks. N of the center of a track road, bears N 70° E and S 60° W.</p> <p>From this point the stan. ¼ sec. cor. of sec. 34, T 13 N, R 20 E, bears S 89°27' W, 1.35 chs. dist., here- inbefore described.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 12 N, R 20 E, Gila and Salt River Mer., Arizona

CHAINS

From this point, a local monument, an iron rod, 5/8 in. diam., projecting 10 ins. above ground, bears N 51°22' W, 1.37 chs. dist. This monument is of unknown origin, is not accepted as a careful and faithful reestablishment of the position of the cor. and is not utilized in the course of this resurvey.

From the cor. of secs. 10, 11, 14 and 15.

N 89°39' W, bet. secs. 10 and 15.

Over rolling land, through medium juniper.

39.83

The 1/4 sec. cor. of secs. 10 and 15, monumented with a limestone of record size, 17 x 8 x 5 ins., in a mound of stone, 2 ft. base, 10 ins. high, with no discernable marks. A limestone, 20 x 17 x 5 ins., was in the same mound of stone, mkd. 1/4 on the N face. This latter stone was set by Harold Williams, U.S. Forest Service, in 1967. The former stone is used as the original cor. stone.

At the cor. point

Set an aluminum post, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, in a mound of stone, 3 1/2 ft. base, to top, with cap mkd.

T12N R20E  
1/4 S10  
S15  
1983

Deposit the mkd. stone and the unmarked stone in the mound of stone.

S 87°05' W, beginning new measurement.

Over rolling hills, through areas of medium juniper.

38.91

The cor. of secs. 9, 10, 15 and 16, monumented with a sandstone, 15 x 10 x 3 ins., in a mound of stone, 2 1/2 ft. base, 10 ins. high, mkd. with 4 grooves on the S face only. A limestone, 18 x 12 x 5 ins., was alongside the cor. stone, mkd. with 3 grooves on the E face and 4 grooves on the S face. This latter stone was set by Harold Williams, U.S. Forest Service, in 1967.

At the cor. point

Set an aluminum post, 36 ins. long, 3/4 in. diam., 20 ins. in the ground, in a mound of stone, 3 1/2 ft. base, to top, with cap mkd.

T12N R20E  
S 9 | S10  
S16 | S15  
1983

Deposit both mkd. stones in the mound of stone.

N 0°54' W, bet. secs. 9 and 10.

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 12 N, R 20 E, Gila and Salt River Mer., Arizona

CHAINS		
	Over rolling land, through sparse juniper and sage.	
36.00	Cottonwood Wash, 90 lks. wide, drains N 65° E.	
40.31	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10, at proportionate dist; there is no remaining evidence of the original cor.	
	Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.	
	<p style="text-align: center;">T12N R20E  <math>\frac{1}{4}</math>  S 9   S10  1983</p>	
	Set a steel fence post alongside the cor.	
	Over rolling land, through medium juniper and sparse pinyon.	
80.33	Fence, bears E and W.	
80.62	Point for the cor. of secs. 3, 4, 9 and 10, at proportionate dist; there is no remaining evidence of the original cor.	
	Set an aluminum post, 28 ins. long, 1 in. diam., 14 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.	
	<p style="text-align: center;">T12N R20E  S 4   S 3  S 9   S10  1983</p>	
	Set a steel fence post alongside the cor.	
	Cor. is located in cleared area.	
	From the cor. of secs. 2, 3, 10 and 11.	
	S 89°37' W, bet. secs. 3 and 10.	
	Over hilly terrain, through juniper.	
39.60	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10, at proportionate dist; there is no remaining evidence of the original cor.	
	Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.	
	<p style="text-align: center;">T12N R20E  <math>\frac{1}{4}</math> S 3  S10  1983</p>	
	Set a steel fence post alongside the cor.	

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 12 N, R 20 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>Cor. is located 25 lks. N of a fence, bears E and W. Over level terrain, along a fence line, through cleared land with grasses.</p>	
79.20	<p>The cor. of secs. 3, 4, 9 and 10.</p> <hr/> <p>N 0°42' E, bet. secs. 3 and 4. Over rolling land, through railed juniper.</p>	
40.31	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 3 and 4, at proportionate dist; there is no remaining evidence of the original cor. Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.</p>	
	<p style="text-align: center;">T12N R20E <math>\frac{1}{4}</math> S 4   S 3 1983</p>	
47.60	<p>Set a steel fence post alongside the cor. Cor. is located in level, open area, cleared of juniper. Center of a track road, bears E and W.</p>	
48.57	<p>Point for the closing cor. of secs. 3 and 4, at proportionate dist. on the Third Stan. Par. North; there is no remaining evidence of the original cor. Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 30 ins. in the ground, with cap mkd.</p>	
	<p style="text-align: center;">T13N R20E S33 <hr/>S 4   S 3 T12N   R20E C C 1983</p>	
	<p>Set a steel fence post alongside the cor. From this point the stan. <math>\frac{1}{4}</math> sec. cor. of sec. 33, T 13 N, R 20 E, bears S 89°29' W, 2.34 chs. dist., hereinbefore described.</p> <hr/>	
	<p>From the cor. of secs. 9, 10, 15 and 16. N 89°30' W, bet. secs. 9 and 16. Over rolling land, with sandy soil, through medium juniper and scattered pinyon.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 12 N, R 20 E, Gila and Salt River Mer., Arizona

CHAINS

40.05

The  $\frac{1}{4}$  sec. cor. of secs. 9 and 16, monumented with a limestone, 16 x 8 x 5 ins., in a mound of stone,  $2\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, mkd.  $\frac{1}{4}$  on N face. A sandstone, 14 x 12 x 5 ins., mkd.  $\frac{1}{4}$ , was alongside the cor. stone. This latter stone was set by Harold Williams, U.S. Forest Service, in 1967.

At the cor. point

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 22 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.

T12N R20E  
 $\frac{1}{4}$  S 9  
S16  
1983

from which

A pinyon, 10 ins. diam., bears N  $21^\circ$  W,  
106 $\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S9 BT.

A pinyon, 8 ins. diam., bears S  $16^\circ$  W,  
79 $\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S16 BT.

Deposit the two mkd. stones in the mound of stone.

---

N  $89^\circ 15'$  W, beginning new measurement.

Over open, rolling land, through groves of medium juniper.

35.40

The cor. of secs. 8, 9, 16 and 17, monumented with a sandstone, 26 x 11 x 5 ins., in small mound of stone, mkd. with faint grooves on the S and E faces. A sandstone, 20 x 20 x 5 ins., was alongside the cor. stone, mkd. with 4 grooves on the E face and 4 grooves on the S face. This latter stone was set by Harold Williams, U.S. Forest Service, in 1967.

At the cor. point

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 24 ins. in the ground, in a mound of stone,  $3\frac{1}{2}$  ft. base, to top, with cap mkd.

T12N R20E  
S 8 | S 9  
S17 | S16  
1983

from which

A juniper, 6 ins. diam., bears S  $81^\circ$  W,  
60 $\frac{1}{2}$  lks. dist., mkd. T12N R20E S17 BT.

Deposit the two mkd. stones in the mound of stone.

---

N  $3^\circ 29'$  W, bet. secs. 8 and 9.

Over rugged rock formations, through medium juniper.

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 12 N, R 20 E, Gila and Salt River Mer., Arizona

CHAINS		
38.80	Cottonwood Wash, 90 lks. wide, drains S 60° E.	
40.48	Point for the ¼ sec. cor. of secs. 8 and 9, at proportionate dist; there is no remaining evidence of the original cor.	
	Set a monument, 30 ins. long, composed of an iron post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 20 ins. in the ground, in a mound of stone, 4 ft. base, with brass cap mkd.	
	T12N R20E ¼ S 8   S 9 1983	
	from which	
	A pinyon, 8 ins. diam., bears N 55° W, 115½ lks. dist., mkd. ¼ S8 ET.	
	Cor. is located on a S 30° W slope.	
	Over rolling hills, through medium juniper.	
80.27	Fence, bears E and W.	
80.96	Point for the cor. of secs. 4, 5, 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.	
	At the cor. point	
	Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.	
	T12N R20E S 5   S 4 S 8   S 9 1983	
	Set a steel fence post alongside the cor.	
	From the cor. of secs. 3, 4, 9 and 10.	
	N 89°47' W, bet. secs. 4 and 9.	
	Over level, open terrain, along a fence line.	
39.55	Point for the ¼ sec. cor. of secs. 4 and 9, at proportionate dist; there is no remaining evidence of the original cor.	
	Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.	
	T12N R20E ¼ S 4 S 9 1983	
	from which	

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 12 N, R 20 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Center pipe of a windmill, bears N 20° E, 6.67 chs. dist.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in a cleared area, 76 lks. N of a fence, bears E and W and 152 lks. N of a track road, bears N 65° E and S 65° W.</p>
74.48	<p>A rebar, 5/8 in. diam., projecting 4 ins. above ground, tagged PE 5047, bears North, 90 lks. dist. This monument was set by George Matkin, PE 5047, AZ, in 1973, as shown on the plat of his survey for Jacob Weinberg, on file in the records of Ron Matkin, Show Low, AZ, using improper methods and is not utilized in the course of this survey. A fence bears N and S.</p>
79.10	<p>The cor. of secs. 4, 5, 8 and 9.</p> <hr/> <p>N 0°30' E, bet. secs. 4 and 5.</p> <p>Over rolling land, cleared of juniper.</p>
40.40	<p>Point for the 1/4 sec. cor. of secs. 4 and 5, at propor- tionate dist; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R20E 1/4 S 5   S 4 1983</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in a flat area, cleared of juniper.</p> <p>Over level, cleared land with new growth of juniper.</p>
47.94	<p>Point for the closing cor. of secs. 4 and 5, at propor- tionate dist. on the Third Stan. Par. North; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T13N R20E S32 ----- S 5   S 4 T12N   R20E C C 1983</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 65 lks. S of a fence, bears E and W.</p> <p>From this point the stan. 1/4 sec. cor. of sec. 32, T 13 N, R 20 E, bears N 89°09' W, 3.81 chs. dist., here- inbefore described.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 12 N, R 20 E, Gila and Salt River Mer., Arizona

CHAINS

From this point, a rebar, 5/8 in. diam., projecting 2 ins. above ground, mkd. PE 8418, bears N 80°53' E, 3.34 chs. dist., reestablished by Richard O. Burton, PE 8418, in 1973, using improper procedures and is not utilized in the course of this resurvey.

From the cor. of secs. 8, 9, 16 and 17.

N 89°43' W, bet. secs. 8 and 17.

Over slightly rolling land, through scattered juniper.

40.10

The ¼ sec. cor. of secs. 8 and 9, monumented with a sandstone, 24 x 24 x 5 ins., projecting 18 ins. above ground, in a mound of stone, 2½ ft. base, 6 ins. high, mkd. ¼ on the N face.

At the cor. point

Set an aluminum post, 36 ins. long, ¾ in. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.

T12N R20E  
¼ S 8  
S17  
1983

Deposit the mkd. stone in the mound of stone.

N 89°38' W, beginning new measurement.

Over rolling, open land.

42.46

Point for the cor. of secs. 7, 8, 17 and 18, at proportionate dist; there is no remaining evidence of the original cor.

Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.

T12N R20E  
S 7 | S 8  
S18 | S17  
1985

Set a steel fence post alongside the cor.

From this point, the cor. of secs. 29, 30, 31 and 32 bears S 0°05' W, 241.16 chs. dist., monumented with a sandstone, 18 x 10 x 7 ins., set in a mound of stone, 2½ ft. base, 10 ins. high, mkd. with 5 grooves on the S side, no other marks were found, from which an original bearing tree

A juniper, 16 ins. diam., bears S 53° W,  
92 lks. dist., mkd. T12N R20E S31 BT.

At the cor. point

Set a monument, 30 ins. long, composed of an iron post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 20 ins. in the ground, in a mound of stone, 3½ ft. base, to top, with brass cap mkd.

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 12 N, R 20 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">T12N R20E S30   S29 S31   S32 1983</p> <p>from which</p> <p style="text-align: center;">A pinyon, 10 ins. diam., bears S 20° E, 54 lks. dist., mkd. T12N R20E S32 BT.</p> <p>Deposit the mkd. stone in the mound of stone.</p> <p>Cor. is located 45 lks. S of a wash, 15 lks. wide, drains N 65° E.</p> <hr/> <p>N 89°44' W, bet. secs. 7 and 18.</p> <p>Over slightly rolling, open land, with native grasses.</p>	
31.71	<p>The cor. of secs. 7, 12, 13 and 18, on the W bdy. of the Tp.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N 1°25' W, bet. secs. 7 and 8.</p> <p>Over rolling land, through sparse juniper.</p>	
40.21	<p>Point for the ¼ sec. cor. of secs. 7 and 8, at propor- tionate dist; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R20E ¼ S 7   S 8 1985</p> <p>Set a steel fence post alongside the cor.</p> <p>Over rolling land, through medium juniper.</p>	
80.42	<p>Point for the cor. of secs. 5, 6, 7 and 8, at propor- tionate dist; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R20E S 6   S 5 S 7   S 8 1983</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in a fence, bears E and W.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 12 N, R 20 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>N 89°59' W, bet. secs. 5 and 8.</p>	
	<p>Over level, open terrain, along a fence line.</p>	
39.80	<p>Point for the ¼ sec. cor. of secs. 5 and 8, at proportionate dist; there is no remaining evidence of the original cor.</p>	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p>	
	<p style="text-align: center;">T12N R20E ¼ S 5 S 8 1983</p>	
	<p>Set a steel fence post alongside the cor.</p>	
	<p>Cor. is located in an area of railed juniper, 115 lks. N of a fence, bears E and W and 34 lks. S of the projection of the fence, bears E and W, through the cor. of secs. 5, 6, 7 and 8.</p>	
	<p>Over level land, through groves of medium juniper.</p>	
79.60	<p>The cor. of secs. 5, 6, 7 and 8.</p>	
	<p>N 89°28' W, bet. secs. 6 and 7.</p>	
	<p>Over rolling hills, along a fence line, through scattered juniper.</p>	
29.24	<p>The cor. of secs. 1, 6, 7 and 12, on the W bdy. of the Tp.</p>	
	<p>From the cor. of secs. 5, 6, 7 and 8.</p>	
	<p>North, bet. secs. 5 and 6.</p>	
	<p>Over slightly rolling land, through railed and new growth of juniper.</p>	
40.19	<p>Point for the ¼ sec. cor. of secs. 5 and 6, at proportionate dist; there is no remaining evidence of the original cor.</p>	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.</p>	
	<p style="text-align: center;">T12N R20E ¼ S 6   S 5 1983</p>	
	<p>Set a steel fence post alongside the cor.</p>	
47.22	<p>Point for the closing cor. of secs. 5 and 6, at proportionate dist., on the Third Stan. Par. North; there is no remaining evidence of the original cor.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 12 N, R 20 E, Gila and Salt River Mer., Arizona

CHAINS

Set an aluminum post, 24 ins. long,  $\frac{3}{4}$  in. diam., 26 ins. in the ground, with cap mkd.

T13N R20E  
S31

S 6		S 5
T12N		R20E
C C		
1983		

Set a steel fence post about 8 ft. S of the cor.

Cor. is located in a track road, bears E and W, and located 12 lks. S of a fence, bears E and W.

From this point, the stan.  $\frac{1}{4}$  sec. cor. of sec. 31, T 13 N, R 20 E, bears S  $89^{\circ}34'$  W, 4.43 chs. dist., hereinbefore described.

From this point, a rebar,  $\frac{5}{8}$  in. diam., projecting 3 ins. above ground, mkd. PE 8419, bears N  $87^{\circ}12'$  E, 3.52 chs. dist., reestablished by Richard O. Burton, PE 8418 in 1973 using improperly reestablished local control and is not utilized in the course of this resurvey.

GENERAL DESCRIPTION

The area resurveyed within T 12 N, R 20 E, is situated about 8 miles west of Taylor, Arizona. The elevation varies from 5750 to 6000 ft. above sea level. The soil varies from sandy to hard clay.

Cottonwood Wash, formerly Snowflake Wash, drains East-erly across the area. The vegetation is juniper and grasses, with sparse pinyon pine and sage. Much of the land surface was disturbed during the process of clearing juniper.

There are several track roads which cross the area. Several windmills are scattered throughout the area, serving cattle actively.

A number of readings throughout the area resurveyed gives a mean magnetic declination of  $12\frac{1}{2}^{\circ}$  E, with a range of  $\frac{1}{2}^{\circ}$  in local attraction.



CERTIFICATE OF SURVEY

I, Dennis K. McKay, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 28th day of May 1980, I have dependently resurveyed the Third Standard Parallel North (north boundary) through Range 20 East, a portion of the Fifth Auxiliary Guide Meridian East (east boundary) through Township 12 North, a portion of the West Boundary and a portion of the subdivisional lines of Township 12 North, Range 20 East, of the Gila and Salt River Meridian, in the State of Arizona which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

AUG 21 1986

(Date)

*Dennis K. McKay*  
 (Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

Arizona State Office  
 Bureau of Land Management  
 Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the Third Standard Parallel North (north boundary) through Range 20 East, a portion of the Fifth Auxiliary Guide Meridian East (east boundary) through Township 12 North, a portion of the west boundary and a portion of the subdivisional lines of Township 12 North, Range 20 East, Gila and Salt River Meridian, Arizona executed by Dennis K. McKay, Cadastral Surveyor having been critically examined and found correct, are hereby approved.

AUG 22 1986

(Date)

*James P. Kelley*  
 (Chief Cadastral Surveyor of Arizona)