

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF THE NORTH BOUNDARY, AND OF A PORTION OF THE

SOUTH, EAST, AND WEST BOUNDARIES AND THE SUBDIVISIONAL LINES

AND THE SURVEY OF SUBDIVISIONS OF SECTIONS 2 AND 5,

TOWNSHIP 19 NORTH, RANGE 25 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Kenneth W. Bays and Stephen J. Malloy, Cadastral Surveyors

Under special instructions dated January 12, 1987, approved February 17, 1987,

which provided for the surveys included under Group Number

686 and assignment instructions dated February 17, 1987.

Survey commenced February 18, 1987

Survey completed May 27, 1987

BOOK 5245

2

INDEX DIAGRAM

TOWNSHIP 19 NORTH, RANGE 25 EAST,

31	27	26	25	23	21
19 6	57 5	50 4	44 3	39 2	35 1 13
56	55	49	43	38	34
17 7	54 8	48 9	42 10	37 11	33 12 12
53	53	46	40	33	31
16 18	52 17	16	15	14	13 11
51					
15 19	20	21	22	23	24 10
15 30	29	28	27	26	25 9
31	32	45 33	34	35	36 7
		6	5	4	

Subdivision of Section 2 ----- pp 60-66.

Subdivision of Section 5 ----- pp 66-69.

T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS

The following field notes are those of the dependent resurvey of the north boundary and a portion of the south, east, and west boundaries, and a portion of the subdivisional lines, and the survey of subdivisions of sections 2 and 5 in Township 19 North, Range 25 East, Gila and Salt River Meridian, Arizona.

The boundaries and subdivisional lines were surveyed by Henry Meyrick Jr., in 1882. Portions of the north, south, and west boundaries and subdivisional lines were retraced by F. Wayne Forrest and Claude F. Warner in 1944.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated January 12, 1987, for Group No. 686, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of all lines were determined by observations on a U.S.C. and G.S. triangulation network, confirmed by hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured with Geodimeter, Zeiss, and Hewlett Packard total stations.

The geographic position of the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, Tps. 19 N, Rs. 25 and 26 E, as determined from a tie made to U.S.C. and G.S. triangulation station "AAL 1959," located in the southeast quarter of T 20 N, R 25 E, is as follows:

Latitude: 35°00'11.58" N Longitude: 109°37'43.71" W

T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS

The mean magnetic declination is $13\frac{1}{2}^{\circ}$ E.

Dependent Resurvey, a Portion of the South Boundary,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

(Reestablishment of the survey executed by
Henry Meyrick Jr., U.S. Deputy Surveyor, in 1882.)

Beginning at the $\frac{1}{4}$ sec. cor. of secs. 2 and 35,
Tps. 18 and 19 N, R 25 E, monumented with the remains
of a rotted wood post, alongside of which is a
juniper post, 60 ins. long, 4 ins. diam., lying loose
on ground, mkd. 1/IV S.

At the cor. point

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins.
diam., 24 ins. in the ground, with brass cap mkd.

T19N R25E
 $\frac{1}{4}$ S35
S 2
T18N
1987

Deposit a magnet in a 1 x 1 x $2\frac{5}{8}$ in. white colored
plastic case beneath the stainless steel post.

Raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, W of
cor.

Set a steel fence post near the cor. and reset the
wood post alongside the cor.

From this point, the $\frac{1}{4}$ sec. cor. of secs. 6 and 31,
Tps. 18 and 19 N, R 26 E, bears S $89^{\circ}31'$ E, 170.48
chs. dist., monumented with a sandstone, 24 x 9 x 6
ins., firmly set, projecting 12 ins. above ground,
mkd. $\frac{1}{4}$ on N face, and with a mound of stone N of cor.

At the cor. point

Dependent Resurvey, a Portion of the South Boundary,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R26E ¼ <u>S31</u> S 6 T18N 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3½ ft. base, 2 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p> <p>N 89°41' W, bet. secs. 2 and 35.</p>
17.60	Dirt road, 15 lks. wide, bears N 12° E and S 12° W.
39.72	Point for the cor. of secs. 2, 3, 34, and 35, at proportionate dist.; there is no evidence of the original cor.
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E S34 S35 <u>S 3 S 2</u> T18N 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p> <hr/> <p>N 89°41' W, bet. secs. 3 and 34.</p>
36.40	Spur, slopes S.

Dependent Resurvey, a Portion of the South Boundary,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS		
39.72	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 34, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E $\frac{1}{4}$ S34 S 3 T18N 1987</p> <p>from which</p> <p style="text-align: center;">A boulder, 6 x 3 x 6 ft. above ground, bears N 85° E, 19 lks. dist., mkd. XBO on S face.</p> <p>Deposit a magnet in a 1 x 1 x $2\frac{5}{8}$ in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>	
79.44	<p>Point for the cor. of secs. 3, 4, 33, and 34, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E S33 S34 S 4 S 3 T18N 1987</p> <p>Deposit a magnet in a 1 x 1 x $2\frac{5}{8}$ in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>	
	<p>N $89^\circ 41'$ W, bet. secs. 4 and 33.</p>	
39.72	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 33, at proportionate dist.; there is no evidence of the original cor.</p>	

Dependent Resurvey, a Portion of the South Boundary,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p> <p>79.44</p>	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E ¼ S33 S 4 T18N 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. of secs. 4, 5, 32, and 33, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E S32 S33 S 5 S 4 T18N 1944</p> <hr/> <p>Dependent Resurvey, a Portion of the East Boundary, T 19 N, R 25 E, Gila and Salt River Mer., Arizona</p> <hr/> <p>(Reestablishment of the survey executed by Henry Meyrick Jr., U.S. Deputy Surveyor, in 1882.)</p> <hr/> <p>From the ¼ sec. cor. of secs. 31 and 36, on the E Bdy. of the Tp., monumented with a sandstone, 16 x 8 x 6 ins., mkd. ¼ on the W face, in a mound of stone, 3 ft. base, 1 ft. high.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N ¼ R25E R26E S36 S31 1987</p>
----------------------------	--

Dependent Resurvey, a Portion of the East Boundary,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS													
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, N of cor.</p> <p>Bury original stone alongside the cor.</p> <p>Set a steel fence post near the cor.</p> <p>From this point, the U.S.C. and G.S. triangulation station "AAL 1959," bears N 20°38'53" W (forward bearing), 542.20 chs., monumented with a standard brass disk seated in a concrete block, 1 x 1 ft., flush with ground.</p> <p>N 0°16' E, bet. secs. 31 and 36.</p> <p>Over rolling land.</p>												
4.00	Wash, 100 lks. wide, drains N 70° W.												
10.00	Same wash, 60 lks. wide, drains S 70° E.												
16.40	Same wash, 150 lks. wide, drains W.												
39.79	<p>Point for the cor. of secs. 25, 30, 31, and 36, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N</p> <table border="0"> <tr> <td>R25E</td> <td> </td> <td>R26E</td> </tr> <tr> <td>S25</td> <td> </td> <td>S30</td> </tr> <tr> <td>S36</td> <td> </td> <td>S31</td> </tr> <tr> <td colspan="3" style="text-align: center;">1987</td> </tr> </table> </div> <p>from which</p> <p>An iron pipe for an abandoned gas well, 5 ins. diam., firmly set, projecting 4 ft. above the ground, bears N 72¾° W, 4.31 chs. dist., with metal tag mkd. DUVAL No. 6 NE 36-19/25.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>	R25E		R26E	S25		S30	S36		S31	1987		
R25E		R26E											
S25		S30											
S36		S31											
1987													

Dependent Resurvey, a Portion of the East Boundary,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.</p> <p>Set a steel fence post near the cor.</p> <hr/> <p>N 0°16' E, bet. secs. 25 and 30.</p> <p>Over rolling land.</p>
39.79	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 30, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T19N $\frac{1}{4}$ R25E R26E S25 S30 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
42.60	Ridge, bears S 18° E and N 18° W.
58.40	Ridge, bears N 70° E and S 40° W.
79.58	<p>Point for the cor. of secs. 19, 24, 25, and 30, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E R26E S24 S19 <hr/>S25 S30 1987</p>

Dependent Resurvey, a Portion of the East Boundary,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.</p> <p>Set a steel fence post near the cor.</p>
	<p>N 0°16' E, bet. secs. 19 and 24.</p> <p>Over rolling land.</p>
39.79	<p>Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N 1/4 R25E R26E S24 S19 1987</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.</p> <p>Set a steel fence post near the cor.</p>
45.90	<p>Wash, 8 lks. wide, drains S 42° W.</p>
79.58	<p>Point for the cor. of secs. 13, 18, 19, and 24, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E R26E S13 S18 S24 S19 1987</p>

Dependent Resurvey, a Portion of the East Boundary,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, N of cor.</p> <p>Set a steel fence post near the cor.</p> <hr/> <p>N 0°16' E, bet. secs. 13 and 18.</p> <p>Over rolling land.</p>
39.79	<p>Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N 1/4 R25E R26E S13 S18 1987</p>
50.70	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.</p> <p>Set a steel fence post near the cor.</p>
79.58	<p>Wash, 68 lks. wide, drains S 56° W, from N.</p> <p>Point for the cor. of secs. 7, 12, 13, and 18, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E R26E S12 S 7 S13 S18 1987</p>

Dependent Resurvey, a Portion of the East Boundary,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.</p> <p>Set a steel fence post near the cor.</p> <hr/> <p>N 0°16' E, bet. secs. 7 and 12.</p> <p>Over rolling land.</p>
14.70	Spur, slopes S 70° W.
33.50	Wash, 20 lks. wide, drains W.
37.70	S edge of top of mesa, bears E and W.
39.79	Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate dist.; there is no evidence of the original cor.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N 1/4 R25E R26E S12 S 7 1987</p> </div>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
47.20	N edge of top of mesa, bears N 45° E and S 10° W.
74.20	S edge of top of mesa, bears E and W.
79.58	Point for the cor. of secs. 1, 6, 7, and 12, at proportionate dist.; there is no evidence of the original cor.

Dependent Resurvey, a Portion of the East Boundary,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E R26E S 1 S 6 S12 S 7 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.</p> <p>Set a steel fence post near the cor.</p> <hr/> <p>N 0°16' E, bet. secs. 1 and 6.</p> <p>Over rolling land.</p> <p>14.10 Track road, 12 lks. wide, bears S 48° E and N 48° W.</p> <p>19.60 N edge of top of mesa, bears N 46° E and S 66° W.</p> <p>39.79 Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N ¼ R25E R26E S 1 S 6 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 4 ft. base, 4 ft. high, N of cor.</p> <p>Set a steel fence post near the cor.</p>

Dependent Resurvey, a Portion of the East Boundary,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p> <p>77.90</p> <p>79.58</p>	<p>Puerco River, 2 chs. wide, course S 50° W.</p> <p>The cor. of Tps. 19 and 20 N, Rs. 25 and 26 E, monumented with a rebar, 5/8 in. diam., firmly set, projecting 13 ins. above the ground. This position is harmoniously related to existing orig. cors. to the N, to the record topography call to the spur to the E, and fits closely with the record position of the railroad to the N and W, even though there are now three tracks in this position instead of just one. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, over a steel fence post, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T20N</td></tr> <tr><td>R25E R26E</td></tr> <tr><td>S36 S31</td></tr> <tr><td><u>S 1 S 6</u></td></tr> <tr><td>T19N</td></tr> <tr><td>1987</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>from which</p> <p style="padding-left: 40px;">A sandstone boulder, 4 ft. x 7 ft. x 8 ins. above ground, bears S 63½° W, 16 lks. dist., mkd. XBO on top.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, S of cor.</p> <p>Bury the rebar inside the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Cor. is located at bottom of fill for railroad tracks.</p> <hr style="width: 50%; margin-left: 0;"/>	T20N		R25E R26E	S36 S31	<u>S 1 S 6</u>	T19N	1987
T20N								
R25E R26E								
S36 S31								
<u>S 1 S 6</u>								
T19N								
1987								

Dependent Resurvey, a Portion of the West Boundary,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS	<p>(Reestablishment of the survey executed by Henry Meyrick Jr., U.S. Deputy Surveyor, in 1882.)</p> <hr/> <p>Beginning at the $\frac{1}{4}$ sec. cor. of secs. 25 and 30, Tps. 19 N, Rs. 24 and 25 E, monumented with an iron post, 1 in. diam., projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S25 S30 1944</p> <p>N 0°01' E, bet. secs. 25 and 30. Asc. over desert.</p> <p>36.10 Fence, extends E and W.</p> <p>39.67 Point for the cor. of secs. 19, 24, 25, and 30, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R24E R25E S24 S19 S25 S30 1987</p> <p>Deposit a magnet in a 1 x 1 x $2\frac{5}{8}$ in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <hr/> <p>N 0°01' E, bet. secs. 19 and 24.</p> <p>39.67 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 24, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
--------	--

BOOK 5245

Dependent Resurvey, a Portion of the West Boundary,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T19N $\frac{1}{4}$ R24E R25E S24 S19 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
79.34	<p>Point for the cor. of secs. 13, 18, 19, and 24, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R24E R25E S13 S18 S24 S19 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
1.50	<p>N 0°01' E, bet. secs. 13 and 18.</p>
39.67	<p>Descend over mesa, edge bears N 38° E and S 72° W.</p> <p>Point for the ¼ sec. cor. of secs. 13 and 18, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey, a Portion of the West Boundary,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T19N $\frac{1}{4}$ R24E R25E S13 S18 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, N of cor.</p>
56.20	Dead Wash, 2 chs. wide, course S 77° W.
79.34	<p>Point for the cor. of secs. 7, 12, 13, and 18, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R24E R25E S12 S 7 S13 S18 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
20.31	<p>N 0°01' E, bet. secs. 7 and 12.</p> <p>Asc. over nearly level ground.</p> <p>From this point, an open end pipe, ¾ in. diam., projecting 12 ins. above ground, bears East, 0.71 chs. dist., established by Robert Shaw, Land Surveyor, No. 5570. This monument is not utilized in the course of this survey.</p>
39.67	Point for the ¼ sec. cor. of secs. 7 and 12, at proportionate dist.; there is no evidence of the original cor.

Dependent Resurvey, a Portion of the West Boundary,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N ¼ R24E R25E S12 S 7 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>60.00 West edge of hill, edge bears E and W.</p> <p>Continue over nearly level ground.</p> <p>79.00 Top of mesa, edge bears E and W.</p> <p>79.34 The cor. of secs. 1, 6, 7, and 12, monumented with a juniper post, 48 ins. long, 4 ins. diam., lying loose in a mound of stone, 3 ft. base, ½ ft. high, no marks visible on weathered post. Record calls for a sandstone, 15 x 10 x 6 ins., with a mound of stone alongside. No mkd. stone was found. This position is accepted as the best available evidence of the orig. cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T19N R24E R25E S 1 S 6 S12 S 7 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
--------	---

Dependent Resurvey, a Portion of the West Boundary,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Reset the wood post alongside the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <hr/> <p>N 1°53' E, bet. secs. 1 and 6.</p> <p>37.44 Point for a witness point bet. secs. 1 and 6, at intersection with the southerly right-of-way of Interstate Highway No. 40.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP T19N R24E R25E S 1 S 6 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>From this point, an Arizona Department of Transportation right-of-way monument, bears S 70°13' W, 14.20 chs. dist., monumented with an aluminum disk, 3 ins. diam., seated in a concrete cylinder, 6 ins. diam., projecting 3 ins. above ground, with disk mkd. A.D.O.T. HIGHWAY DIV. R.P. 96 E.B. 367X31.90 1976.</p> <p>From this same point, an Arizona Department of Transportation right-of-way monument, bears N 70°13' E, 41.36 chs. dist., monumented with an aluminum disk, 3 ins. diam., seated in a concrete cylinder, 6 ins. diam., projecting 3 ins. above ground, with disk mkd. A.D.O.T. HIGHWAY DIV. R.P. 96 E.B. 404X00 1976.</p>
39.79	<p>Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set an aluminum post, 12 ins. long, ¾ in. diam., cemented 6 ins. into a drill hole in solid bedrock, with cap mkd.</p>

Dependent Resurvey, a Portion of the West Boundary,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">T19N $\frac{1}{4}$ R24E R25E S 1 S 6 1987</p> <p>Cor. is located in the center strip between the E and W bound lanes of Interstate Highway No. 40.</p> <p>42.43 Point for a witness point bet. secs. 1 and 6, at intersection with the northerly right-of-way of Interstate Highway No. 40.</p> <p>Set an aluminum post, 12 ins. long, $\frac{3}{4}$ in. diam., cemented 6 ins. into a drill hole in solid bedrock, with cap mkd.</p> <p style="text-align: center;">WP T19N R24E R25E S 1 S 6 1987</p> <p>Set a steel fence post near the cor.</p> <p>From this point, an Arizona Department of Transportation right-of-way monument, bears S 70°13' W, 16.05 chs. dist., monumented with an aluminum disk, 3 ins. diam., seated in a concrete cylinder, 6 ins. diam., projecting 3 ins. above ground, with disk mkd. A.D.O.T. HIGHWAY DIV. R.P. 102 W.B. 367X31.90 1976.</p> <p>From this same point, an Arizona Department of Transportation right-of-way monument, bears N 70°13' E, 39.52 chs. dist., monumented with an aluminum disk, 3 ins. diam., seated in a concrete cylinder, 6 ins. diam., projecting 3 ins. above ground, with disk mkd. A.D.O.T. HIGHWAY DIV. R.P. 102 W.B. 404X00 1976.</p>	
79.58	<p>The cor. of Tps. 19 and 20 N, Rs. 24 and 25 E, monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p>	

Dependent Resurvey, a Portion of the West Boundary,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS

PFNM	T20N
R24E	R25E
S36	S31
S 1	S 6
T19N	
1882	
1938	

Cor. is located at a fence cor., fences extend N, E, and W.

From this cor., a local monument of unknown origin, bears N $85\frac{1}{4}^{\circ}$ E, 8.72 chs. dist., monumented with an open end iron pipe, 2 ins. diam., firmly set, projecting 3 ins. above the ground.

Dependent Resurvey of the North Boundary,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

(Reestablishment of the survey executed by
Henry Meyrick Jr., U.S. Deputy Surveyor, in 1882.)

Preliminary Statement

During the retracement of the N bdy. of T 19 N, R 25 E, preliminary to this resurvey, five open end iron pipes, with no identifying marks, were found set at positions ranging in distance from $2\frac{1}{2}$ to $8\frac{1}{2}$ chs. from the final cor. positions of this resurvey. A diligent investigation was undertaken to determine if these iron pipes were perpetuations of original cors., or faithful reestablishments of cor. positions. All of the pipes were dug up to search for traces of original cor. evidence, but no evidence was found. Then the pipes were reset. Lines were surveyed one mile northerly from each of the open end pipes to search for evidence of original subdivision cors. in T 20 N, R 25 E, which might substantiate that the pipes were harmoniously related to positions of existing original cors.; however, no original evidence was found. Research of records at local title companies, the Arizona Department of

Dependent Resurvey of the North Boundary,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>Transportation, the Santa Fe Railroad, and the Apache County Courthouse showed no record of who set the cors. or when they were set. Private land surveyors and landowners familiar with the area were interviewed and several were aware of the existence of the pipes; however, no one knew who set the pipes, the year they were set, or the purpose of the pipes. No one interviewed considered the pipes to be property cors. or had used them as such. The open end pipes are not harmoniously related to record calls of topography. One of the pipes is located 8 chs. from the existing cor. of Tps. 19 and 20 N, Rs. 24 and 25 E, which is monumented with a GLO brass cap monument set in 1938 by Benjamin J. Kinsey, Surveyor and Cadastral Engineer, during the General Land Office resurvey of the N bdy. of T 19 N, R 24 E. Kinsey found the original 1882 township cor. where he set the brass cap. After careful consideration of all the evidence obtained, the local open end iron pipes were rejected as perpetuations or faithful reestablishments of original survey cors.; therefore, they were not utilized as cors. of this resurvey.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of Tps. 19 and 20 N, Rs. 25 and 26 E. N 89°44' W, bet. secs. 1 and 36.</p> <p>Over nearly level land.</p> <p>3.10 Railroad tracks, bear N 59° E and S 58° W.</p> <p>3.60 Railroad tracks, bear N 59° E and S 58° W.</p> <p>4.05 Railroad tracks, bear N 59° E and S 58° W.</p> <p>5.10 Power line, bears N 59° E and S 58° W.</p> <p>40.64 Point for the ¼ sec. cor. of secs. 1 and 36, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
---------------	--

Dependent Resurvey of the North Boundary,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p style="text-align: center;">T20N R25E $\frac{1}{4}$ <u>S36</u> S 1 T19N 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p> <p>Continue over rolling land.</p> <p>52.30 A graded road, 25 lks. wide, bears N 24° W and S 24° E.</p> <p>53.40 A graded road, 25 lks. wide, bears N 48° E and S 48° W.</p> <p>81.28 Point for the cor. of secs. 1, 2, 35, and 36, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R25E <u>S35 S36</u> S 2 S 1 T19N 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 3 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p> <hr/> <p>N 89°44' W, bet. secs. 2 and 35.</p> <p>Over rolling land.</p>	
---------------	---	--

Dependent Resurvey of the North Boundary,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

<p>CHAINS 20.32</p>	<p>Point for the E 1/16 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R25E E 1/16 $\frac{S35}{S2}$ T19N 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p>
<p>40.64</p>	<p>Point for the ¼ sec. cor. of secs. 2 and 35, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R25E $\frac{1}{4}$ $\frac{S35}{S2}$ T19N 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p> <p>Cor. is located 1 ch. N of a barbed wire fence, bears S 86° E and N 86° W.</p>
<p>60.80</p>	<p>E edge of ridge, bears NE and SW; continue across rolling top of ridge.</p>
<p>72.10</p>	<p>W edge of ridge, bears NE and SW; desc. over rolling NW slope.</p>

Dependent Resurvey of the North Boundary,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

<p>CHAINS 81.28</p>	<p>Point for the cor. of secs. 2, 3, 34, and 35, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R25E S34 S35 S 3 S 2 T19N 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Cor. is located 56 lks. S of a barbed wire fence, bears E and W.</p> <p>From this cor., a local monument, an open end iron pipe of unknown origin, 2 ins. diam., firmly set, projecting 4 ins. above the ground, bears N 77½° E, 2.52 chs. dist.</p> <hr/> <p>N 89°44' W, bet. secs. 3 and 34.</p> <p>Desc. over rolling NW slope.</p>	
<p>12.70</p>	<p>Draw, drains SW; asc. over rolling SE slope.</p>	
<p>40.64</p>	<p>Point for the ¼ sec. cor. of secs. 3 and 34, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R25E ¼ S34 S 3 T19N 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>	

Dependent Resurvey of the North Boundary,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p> <p>58.50</p> <p>81.28</p> <p>40.64</p>	<p>Set a steel fence post near the cor.</p> <p>Cor. is located 26 lks. S of a barbed wire fence, bears E and W.</p> <p>Top of ridge, bears NE and SW; continue over rolling land.</p> <p>Point for the cor. of secs. 3, 4, 33, and 34, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R25E S33 S34 — — S 4 S 3 T19N 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Cor. is located 85 lks. S of a barbed wire fence, bears E and W.</p> <p>From this cor., a local monument, an open end iron pipe of unknown origin, 1½ ins. diam., firmly set, projecting 6 ins. above the ground, bears N 80¼° E, 3.94 chs. dist.</p> <hr/> <p>N 89°44' W, bet. secs. 4 and 33.</p> <p>Over rolling land.</p> <p>Point for the ¼ sec. cor. of secs. 4 and 33, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
--	--	--

Dependent Resurvey of the North Boundary,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T20N R25E $\frac{1}{4}$ $\frac{S33}{S 4}$ T19N 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Cor. is located 115 lks. S of a barbed wire fence, bears E and W.</p>
53.10	<p>Top of ridge, bears N 45° E and S 45° W; desc. over NW slope.</p>
81.28	<p>Point for the cor. of secs. 4, 5, 32, and 33, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R25E S32 S33 S 5 S 4 T19N 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>From this cor., a local monument, an open end iron pipe of unknown origin, 2 ins. diam., firmly set, projecting 10 ins. above the ground, bears N 81½° E, 5.34 chs. dist.</p>
29.20	<hr/> <p>N 89°44' W, bet. secs. 5 and 32.</p> <p>Desc. over rolling NW slope.</p> <p>Dead Wash, 1.75 chs. wide, drains S 23° W; continue over rolling terrain.</p>

Dependent Resurvey of the North Boundary,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

<p>CHAINS 40.64</p>	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 32, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R25E $\frac{1}{4}$ <u>S32</u> S 5 T19N 1987</p> <p>from which</p> <p style="text-align: center;">A well casing, $3\frac{1}{2}$ ins. diam., in a windmill, 5 x 5 ft. base, bears S 18° E, 5.38 chs. dist.</p> <p>Deposit a magnet in a 1 x 1 x $2\frac{5}{8}$ in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p> <p>Cor. is located 1 lk. W of a barbed wire fence, bears N and S.</p>	
<p>41.60</p>	<p>Branch of Dead Wash, 1.30 chs. wide, drains S 45° W; asc. over rolling terrain.</p>	
<p>47.32</p>	<p>Point for a witness point bet. secs. 5 and 32, at intersection with the southerly right-of-way of Interstate Highway No. 40.</p> <p>Set an aluminum post, 12 ins. long, $\frac{3}{4}$ in. diam., 4 ins. in concrete in a drill hole in bedrock, with aluminum cap mkd.</p> <p style="text-align: center;">WP T20N R25E <u>S32</u> S 5 T19N 1987</p>	

Dependent Resurvey of the North Boundary,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>Cor. is located 1 lk., S 75° E of a barbed wire fence cor. at NE cor. of rest area. Fences extends N 70° E and S 20° W.</p> <p>From this point, an Arizona Department of Transportation right-of-way marker, bears N 70°13' E, 56.42 chs. dist., monumented with an aluminum disk, 3 ins. diam., seated in a concrete cylinder, 12 ins. diam., set flush with the ground, with disk mkd. ARIZONA HIGHWAY DEPT. 495x00 19.</p> <p>From this same point, an Arizona Department of Transportation right-of-way monument, bears S 70°13' W, 32.95 chs. dist., monumented with an aluminum disk, 3 ins. diam., seated in a concrete cylinder, 6 ins. diam., projecting 3 ins. above the ground, with disk mkd. A.D.O.T. HIGHWAY DIV. R.P. 96 E.B. 436x00 1976.</p>	
51.60	E bound lanes, Interstate Highway No. 40, 60 lks. wide, bears N 70° E and S 70° W; continue across median strip.	
56.40	W bound lanes, Interstate Highway No. 40, 60 lks. wide, bears N 70° E and S 70° W; asc. over rolling SE slope.	
60.87	<p>Point for a witness point bet. secs. 5 and 32, at intersection with the northerly right-of-way of Interstate Highway No. 40.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> WP T20N R25E <u>S32</u> S 5 T19N 1987 </p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>	

Dependent Resurvey of the North Boundary,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>From this point, an Arizona Department of Transportation right-of-way monument, bears N 70°13' E, 69.14 chs. dist., monumented with an aluminum disk, 3 ins. diam., seated in a concrete cylinder, 6 ins. diam., projecting 1 in. above the ground, with disk mkd. ARIZONA HIGHWAY DEPT. 495X00 19.</p> <p>From this same point, an Arizona Department of Transportation right-of-way monument bears S 70°13' W, 20.23 chs. dist., monumented with an aluminum disk, 3 ins. diam., seated in a concrete cylinder, 6 ins. diam., projecting 2 ins. above the ground, with disk mkd. A.D.O.T. HIGHWAY DIV. R.P. 102 W.B. 436X00 1976.</p>
75.90	SE edge of bluff bears NE and SW; continue over rolling land.
81.28	<p>Point for the cor. of secs. 5, 6, 31, and 32, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R25E S31 S32 --- --- S 6 S 5 T19N 1987</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p> <p>From this cor., a local monument, an open end iron pipe of unknown origin, 2 ins. diam., firmly set, projecting 15 ins. above the ground, bears N 84° E, 6.72 chs. dist.</p>

Dependent Resurvey of the North Boundary,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>N 89°44' W, bet. secs. 6 and 31.</p> <p>Over rolling land.</p> <p>22.90 Dry wash, 10 lks. wide, drains S 24° W.</p> <p>40.64 Point for the ¼ sec. cor. of secs. 6 and 31, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R25E ¼ <u>S31</u> S 6 T19N 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p> <p>80.21 The cor. of Tps. 19 and 20 N, Rs. 24 and 25 E.</p> <hr/> <p>Dep. Resurvey, a Portion of the Subdivisional Lines, T 19 N, R 25 E, Gila and Salt River Mer., Arizona</p> <hr/> <p style="text-align: center;">(Reestablishment of the Survey Executed by Henry Meyrick Jr., U.S. Deputy Surveyor, in 1882.)</p> <hr/> <p>From the cor. of secs 7, 12, 13, and 18, on the E Bdy. of the Tp.</p> <p>N 89°30' W, bet. secs. 12 and 13.</p> <p>Over rolling desert.</p> <p>41.00 Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no evidence of the original cor.</p>	
---------------	--	--

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E ¼ <u>S12</u> S13 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Continue over rolling desert.</p> <p>82.00 Point for the cor. of secs. 11, 12, 13, and 14, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E <u>S11 S12</u> <u>S14 S13</u> 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>From this point, the cor. of secs. 25, 26, 35, and 36, bears S 0°39' W, 237.52 chs. dist., monumented with a juniper post, 50 ins. long, 5 ins. diam., lying loose on the ground, mkd. with 1 notch and other illegible scribe marks.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E <u>S26 S25</u> <u>S35 S36</u> 1987</p>	
--------	---	--

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Deposit the original wood post alongside the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <hr/> <p>N 0°29' E, bet. secs. 11 and 12.</p> <p>Over rolling desert.</p>
16.30	Spur off mesa, extends E and W. Descend and enter ranch house area.
39.59	<p>Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E 1/4 S11 S12 1987</p> <p>from which</p> <p style="text-align: center;">The NE cor. of a ranch house bears S 78° W, 69 1/2 lks. dist., short side of house bears S 20° E.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Continue over rolling desert.</p>
79.15	Puerco River, 5 chs. wide, course SW.
79.18	True point for the cor. of secs. 1, 2, 11, and 12, at proportionate dist., falls in river; there is no evidence of the original cor.

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>From this point, a point selected for the witness cor. for the cor. of secs. 1, 2, 11, and 12, bears N 45° W, 3.00 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a rock collar, 2½ ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC T19N R25E S 2 S 1 S11 S12 1987 ↘</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the witness cor.</p> <hr/> <p>From the cor. of secs 1, 6, 7, and 12, on the E Bdy. of the Tp.</p> <p>N 89°47' W, bet. secs. 1 and 12.</p> <p>Over rolling desert.</p> <p>40.80 Puerco River, 10 chs. wide, course S 20° W.</p> <p>40.84 True point for the ¼ sec. cor. of secs. 1 and 12, at proportionate dist.; falls in the Puerco River, there is no evidence of the original cor.</p> <p>From this point, a point selected for the witness cor. for the ¼ sec. cor. of secs. 1 and 12, bears N 77°56' E, 2.835 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC T19N R25E ¼ S 1 S12 ← 1987</p> </div>	
---------------	---	--

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona


CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the witness cor.</p> <p>Continue down flood plain of Puerco River.</p>
81.68	<p>The true point for the cor. of secs. 1, 2, 11, and 12.</p> <hr/> <p>N 0°32' E, bet. secs. 1 and 2.</p> <p>Ascend out of Puerco River and across nearly level desert.</p>
20.50	<p>Railroad tracks, bear N 55°E and S 55°W.</p>
39.59	<p>Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E 1/4 S 2 S 1 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p> <p>Over rolling desert.</p>
59.385	<p>Point for the N 1/16 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E N 1/16 S 2 S 1 1987</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p> <p>79.65</p> <p>40.90</p> <p>80.80</p> <p>81.80</p>	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. of secs. 1, 2, 35, and 36, on the N Bdy. of the Tp.</p> <hr/> <p>From the cor of secs. 11, 12, 13, and 14.</p> <p>N 88°57' W, bet. secs. 11 and 14.</p> <p>Over rolling desert.</p> <p>Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set an aluminum post, 72 ins. long, 3/4 ins. diam., 66 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E 1/4 <u>S11</u> S14 1987</p> <p>Set a steel fence post near the cor.</p> <p>Continue over rolling desert.</p> <p>Puerco River, 2 chs. wide, course westerly.</p> <p>True point for the cor. of secs. 10, 11, 14, and 15, at proportionate dist., falls on the right bank of the Puerco River; there is no evidence of the original cor.</p> <p>From this point, a point selected for the witness corner for the cor. of secs. 10, 11, 14, and 15, bears N 45° W, 3.00 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
---	---	--

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS




Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

Set a steel fence post near the witness cor.

From this same point, the cor. of secs. 22, 23, 26, and 27, bears S 1°27' W, 157.40 chs. dist., monumented with a juniper post, 30 ins. long, 3 ins. square, lying loose on the ground.

At the cor. point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

Deposit the original post alongside the stainless steel post.

Set a steel fence post near the cor.

Cor is located on spur, bears E and W, also 4.18 chs. dist., W of a fence extending N and S.

N 0°32' E, bet. secs. 10 and 11.

Ascend over nearly level ground

33.30 Railroad tracks, bear N 55°E and S 55°W.

39.34 Point for the ¼ sec. cor. of secs. 10 and 11, at proportionate dist.; there is no evidence of the original cor.

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E ½ S10 S11 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Over rolling desert.</p>
78.68	<p>Point for the cor. of secs. 2, 3, 10, and 11, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E S 3 S 2 S10 S11 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
	<hr/> <p>From the true point for the cor. of secs. 1, 2, 11, and 12.</p> <p>N 89°18' W, bet. secs. 2 and 11.</p> <p>Over rolling desert.</p>
27.00	<p>Railroad tracks, bear N 55° E and S 55° W.</p>
28.70	<p>Power line, bears N 55° E and S 55° W.</p>
36.25	<p>Dirt road, bears NE and SW.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p style="text-align: center;">T19N R25E S 1/16 S 3 S 2 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>39.34 Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E 1/4 S 3 S 2 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Continue over rolling desert.</p> <p>79.01 The cor. of secs. 2, 3, 34, and 35 on the N Bdy. of the Tp.</p> <hr/> <p>From the true point for the cor. of secs. 10, 11, 14, and 15.</p> <p>S 88°10' W, bet. secs. 10 and 15.</p> <p>Over rolling desert.</p> <p>40.78 Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>
---------------	--

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T19N R25E $\frac{1}{4}$ <u>S10</u> S15 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Cor. is located 53 lks. S of a fence, extending N 50° E and S 50° W.</p> <p>Continue over rolling desert.</p>
44.30	Railroad tracks, bear N 50° E and S 50° W.
81.56	<p>Point for the cor. of secs. 9, 10, 15, and 16, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E <u>S 9 S10</u> S16 S15 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>From this point, the ¼ sec. cor. of secs. 21 and 22, bears S 1°51' E, 120.17 chs. dist., monumented with the remains of a juniper post, 21 ins. long, 6 ins. square, firmly set, 18 ins. in the ground.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E $\frac{1}{4}$ S21 S22 1987</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS	
40.03	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Deposit the original post alongside the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <hr/> <p>N 0°15' E, bet. secs. 9 and 10.</p> <p>Over rolling desert.</p> <p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E S 9 S10 1987</p>
80.06	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Continue over rolling desert.</p> <p>Point for the cor. of secs. 3, 4, 9, and 10, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E S 4 S 3 S 9 S10 1987</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <hr/> <p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>S 89°09' W, bet. secs. 3 and 10.</p> <p>Over rolling desert.</p> <p>14.63 Point selected for the witness point bet. secs. 3 and 10.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 33 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">WP T19N R25E <u>S 3</u> S10 1987</p> <p>Set a steel fence post near the cor.</p> <p>Cor. is located on small spur, slopes S.</p>
40.94	<p>Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E <u>1/4 S 3</u> S10 1987</p> <p>from which</p> <p style="text-align: center;">A juniper, 4 ins. diam., bears S 51° W, 120 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p> <p>64.51</p> <p>81.88</p> <p>40.04</p>	<p>Set a steel fence post near the cor.</p> <p>Continue over rolling desert.</p> <p>Point selected for the witness point bet. secs. 3 and 10.</p> <p>Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">WP T19N R25E S 3 S10 1987</p> <p>Set a steel fence post near the cor.</p> <p>The cor. of secs. 3, 4, 9, and 10.</p> <hr/> <p>N 1°16' E, bet. secs. 3 and 4.</p> <p>Over rolling desert.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E $\frac{1}{4}$ S 4 S 3 1987</p> <p>from which</p> <p>An aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., set 31 ins. in the ground, for a reference monument, bears N 45° E, 99 ft. dist., with cap mkd. T19N R25E $\frac{1}{4}$ S3 RM 99 ft. 1987 and an arrow pointing to the cor.</p>	
--	---	--

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS	
80.60	<p>An aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., set 31 ins. in the ground, for a reference monument, bears N 45° W, 99 ft. dist., with cap mkd. T19N R25E $\frac{1}{4}$ S4 RM 99 ft. 1987 and an arrow pointing to the cor.</p> <p>Deposit a magnet in a 1 x 1 x 2 $\frac{5}{8}$ in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Cor. is located on W edge of a wash, 50 lks. wide, draining S 60° E.</p> <p>The cor. of secs 3, 4, 33, and 34, on the N Bdy. of the Tp.</p>
40.50	<p>From the cor. of secs. 4, 5, 32, and 33, on the S Bdy. of the Tp.</p> <p>N $1^\circ 25'$ E, bet. secs. 32 and 33.</p> <p>Over rolling desert.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E $\frac{1}{4}$ S32 S33 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 $\frac{5}{8}$ in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Continue over rolling desert.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

<p>CHAINS 81.00</p>	<p>The cor. of secs. 28, 29, 32, and 33, monumented with a sandstone, 24 x 10 x 4 ins., lying loose on the ground, mkd. with 4 grooves on one edge and 1 groove on the adjacent edge. Record calls for a post, 4 ft. long, 4 ins. square, with mkd. stone, 12 ins. in the ground. This sandstone is accepted as the best available evidence of the original cor. position.</p> <p>At the cor point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E S29 S28 S32 S33 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Deposit the sandstone alongside the stainless steel post.</p> <p>Cor. is located E of a gate and in a fence, extending E and W.</p> <p>From this point the ¼ sec. cor. of secs. 20 and 21, bears N 0°03.3' E, 119.07 chs. dist., hereinafter described.</p>	
<p>40.83</p>	<p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>N 88°18' W, bet. secs. 9 and 16.</p> <p>Over rolling desert.</p> <p>Point for the ¼ sec. cor. of secs. 9 and 16, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Deposit the sandstone alongside the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <hr/> <p>N 0°02' E, bet. secs. 8 and 9.</p> <p>Over rolling desert.</p> <p>39.64 Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E 1/4 S 8 S 9 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Continue over rolling desert.</p> <p>79.28 Point for the cor. of secs. 4, 5, 8, and 9, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E S 5 S 4 S 8 S 9 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
---------------	---

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>Set a steel fence post near the cor.</p> <hr/> <p>From the cor of secs. 3, 4, 9, and 10.</p> <p>N 88°51' W, bet. secs. 4 and 9.</p> <p>Over rolling desert.</p> <p>20.82 Point selected for the witness point bet. secs. 4 and 9.</p> <p>Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">WP T19N R25E <u>S 4</u> S 9 1987</p> <p>Set a steel fence post near the cor.</p> <p>Cor. is located on spur, slopes S.</p> <p>40.97 Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E $\frac{1}{4}$ <u>S 4</u> S 9 1987</p> <p>Deposit a magnet in a 1 x 1 x $2\frac{5}{8}$ in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Continue over rolling desert.</p> <p>55.46 Point selected for the witness point, bet. secs. 4 and 9.</p>	
---------------	--	--

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 31 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">WP T19N R25E <u>S 4</u> S 9 1987</p> <p>Set a steel fence post near the cor.</p> <p>Cor. is located on spur, slopes S.</p> <p>81.94 The cor. of secs. 4, 5, 9, and 10.</p> <hr/> <p>N 4°16' W, bet. secs. 4 and 5.</p> <p>Over rolling desert.</p> <p>38.25 Wash, 1 ch. wide, course S 70° W.</p> <p>39.75 The $\frac{1}{4}$ sec. cor. of secs. 4 and 5, monumented with a juniper post, 72 ins long, 5 ins. diam., lying loose on the ground. This post has the age and character of other corner posts found in this township; it is positioned nearly due N of the $\frac{1}{4}$ sec. cor. of secs. 20 and 21, and of the cor. of secs. 28, 29, 32, and 33. The distortion in this line is caused by the proportion in an E and W direction. This post is harmoniously related to the other found corners on this meridional line and is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E $\frac{1}{4}$ S 5 S 4 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 $\frac{5}{8}$ in. white plastic case beneath the stainless steel post.</p> <p>Deposit the juniper post alongside the stainless steel post.</p>
---------------	--

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p> <hr/> <p>N 7°43' E, beginning new measurement.</p> <p>Continue over rolling desert.</p> <p>40.05 The cor. of secs. 4, 5, 32, and 33, on the N Bdy. of the Tp.</p> <hr/> <p>From the cor. of secs. 17, 18, 19, and 20, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E S18 S17 S19 S20 1944</p> <p>N 89°08' W, bet. secs. 18 and 19.</p> <p>Over rolling desert.</p> <p>41.10 Spur, slopes S.</p> <p>42.08 Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E 1/4 S18 S19 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
---------------	--

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS	Continue over rolling desert.
82.77	The cor. of secs. 13, 18, 19, and 24.
	From the cor. of secs. 17, 18, 19, and 20.
	N 1°47' W, bet. secs. 17 and 18.
	Over rolling desert.
39.84	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18, at proportionate dist.; there is no evidence of the original cor.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \text{T19N R25E} \\ \frac{1}{4} \\ \text{S18 S17} \\ 1987 \end{array}$
	Deposit a magnet in a 1 x 1 x 2 $\frac{5}{8}$ in. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
	Continue over rolling desert.
79.68	Point for the cor. of secs. 7, 8, 17, and 18, at proportionate dist.; there is no evidence of the original cor.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \text{T19N R25E} \\ \text{S 7 S 8} \\ \text{S18 S17} \\ 1987 \end{array}$
	Deposit a magnet in a 1 x 1 x 2 $\frac{5}{8}$ in. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS	
40.73	<p>Cor. is located 1 ft. east of a fence, extending N 35° E and S 35° W.</p> <hr/> <p>From the cor. of secs. 8, 9, 16, and 17.</p> <p>S 89°42' W, bet. secs. 8 and 17.</p> <p>Over rolling desert.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E $\frac{1}{4}$ $\frac{S 8}{S17}$ 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Continue over rolling desert.</p>
81.46	<p>The cor. of secs. 7, 8, 17, and 18.</p> <hr/>
40.82	<p>N 89°19' W, bet. secs. 7 and 18.</p> <p>Over rolling desert.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E $\frac{1}{4}$ $\frac{S 7}{S18}$ 1987</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Continue over rolling desert.</p> <p>80.25 The cor. of secs. 7, 12, 13, and 18, on the W. Bdy. of the Tp.</p> <hr/> <p>From the cor. of secs. 7, 8, 17, and 18.</p> <p>N 0°02' E, bet. secs. 7 and 8.</p> <p>Over rolling desert.</p> <p>39.82 Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E ^{1/4} S 7 S 8 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Continue over rolling desert.</p> <p>79.64 Point for the cor. of secs. 5, 6, 7, and 8, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E S 6 S 5 S 7 S 8 1987</p>	
---------------	--	--

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
4.10	<p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>S 89°56' W, bet. secs. 5 and 8.</p> <p>Over rolling desert.</p> <p>Small spur, slope N.</p>
15.17	<p>Point selected for the witness point bet. secs. 5 and 8.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">WP T19N R25E S 5 <u>S 8</u> 1987</p>
40.72	<p>Set a steel fence post near the cor.</p> <p>Cor. falls on the edge of a mesa, bears NE and SW.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E 1/4 <u>S 5</u> S 8 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>Continue over rolling desert.</p> <p>52.14 Point selected for the witness point bet. secs. 5 and 8.</p> <p>Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">WP T19N R25E $\frac{S}{S}$ $\frac{5}{8}$ 1987</p> <p>Set a steel fence post near the cor.</p> <p>Cor. is located on a spur, slopes N.</p> <p>61.08 Point for the W 1/16 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E W 1/16 $\frac{S}{S}$ $\frac{5}{8}$ 1987</p> <p>Deposit a magnet in a 1 x 1 x $2\frac{5}{8}$ in. white plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, N of cor.</p> <p>Set a steel fence post near the cor.</p> <p>Continue over rolling desert.</p> <p>81.44 The cor. of secs. 5, 6, 7, and 8.</p> <hr/> <p>N $89^{\circ}32'$ W, bet. secs. 6 and 7.</p> <p>Over rolling desert.</p> <p>9.40 Dead Wash, 6 chs. wide, course S 15° W.</p>	
---------------	--	--

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

<p>CHAINS 40.87</p>	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 17 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E $\frac{1}{4}$ $\frac{S}{S}$ $\frac{6}{7}$ 1987</p> <p>Deposit a magnet in a 1 x 1 x $2\frac{5}{8}$ in. white plastic case beneath the stainless steel post.</p> <p>Continue over rolling desert.</p>
<p>80.27</p>	<p>The cor. of secs. 1, 6, 7, and 12 on the W Bdy. of the Tp..</p>
<p>12.30</p>	<p>From the cor. of secs. 5, 6, 7, and 8. N $1^{\circ}50'$ E, bet. secs. 5 and 6.</p>
<p>19.92</p>	<p>Dead Wash, 3 chs. wide, course S 20° W.</p>
<p>39.84</p>	<p>Point for the S $\frac{1}{16}$ sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E S $\frac{1}{16}$ S 6 S 5 1987</p> <p>Deposit a magnet in a 1 x 1 x $2\frac{5}{8}$ in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p> <p>72.31</p>	<p>Cor. is located under right-of-way fence, extending N 70° E and S 70° W.</p> <p>From this point, Arizona Department of Transportation right-of-way monument 436x00, bears N 70°13' E, 3.56 chs. dist., hereinbefore described.</p> <p>From this same point, an Arizona Department of Transportation right-of-way monument, bears S 70°13' W, 13.12 chs. dist., monumented with a 3 in. diam. aluminum disk, seated in a concrete cylinder, 6 ins. diam., projecting 3 ins. above ground, with disk mkd. A.D.O.T. HIGHWAY DIV. R.P. 96 E.B. 425x00 1976.</p> <p>From this east bound right-of-way 425x00, a rebar, ½ in. diam., projecting 3 ins. above ground., bears N 50° W, 0.144 chs. dist.</p> <p>Point selected for the witness point bet. secs. 5 and 6, at intersection with the northerly right-of-way of Interstate Highway No. 40.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP T19N R25E S 6 S 5 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Cor. is located under right-of-way fence, extending N 70° E and S 70° W.</p> <p>From this point, an Arizona Department of Transportation right-of-way monument, bears S 70°13' W, 14.95 chs. dist., monumented with a 3 in. diam. aluminum disk, seated in a concrete cylinder, 6 ins. diam., projecting 2 ins. above ground, with disk mkd. A.D.O.T. HIGHWAY DIV. R.P. 102 W.B. 425x00 1976.</p>
----------------------------	---

Subdivision of Section 2,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E C¼ S2 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p>
59.19	<p>Point for the center N 1/16 sec. cor. of sec. 2.</p>
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E C N 1/16 S 2 C 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p>
69.10	<p>Top of ridge, bears E and W.</p>
79.325	<p>The ¼ sec. cor. of secs. 2 and 35, on the N Bdy. of the Tp.</p>
	<hr/> <p>From the ¼ sec. cor. of secs. 1 and 2.</p> <p>N 89°27' W, on the E and W center line of sec. 2.</p> <p>Over nearly level ground.</p>

Subdivision of Section 2,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS	
20.37	<p>Point for the center E 1/16 sec. cor. of sec. 2.</p> <p>Set an aluminum post, 12 ins. long, $\frac{3}{4}$ in. diam., 4 ins. in concrete, in a drill hole in a sandstone boulder, 4 x 7 x 6 ft. high, with aluminum cap mkd.</p>
	$ \begin{array}{c} \text{T19N R25E} \\ \text{C } \frac{\text{E } 1/16}{\text{S } 2} \text{ C} \\ 1987 \end{array} $
	<p>from which</p> <p>The nose of the petroglyph of a dog, 8 x 12 ins., on the NE face of a sandstone boulder, 15 x 14 x 12 ft. high, bears S $55\frac{1}{4}^\circ$ W, 201 lks. dist.</p> <p>The S face of a rock bluff, 40 ft. high, bears N $34\frac{1}{2}^\circ$ W, 30 lks. dist., mkd. XBO.</p>
	<p>Cor. is located in a rocky area among large sandstone boulders.</p> <p>Continue over rocky ground, along the base of a rock bluff, extending E and W.</p>
26.70	<p>Asc. 40 ft. over rock bluff, bears E and S 30° W; continue over rolling land on top of mesa.</p>
27.63	<p>Point for a witness point on the E and W center line of sec. 2.</p> <p>Set an aluminum post, 12 ins. long, $\frac{3}{4}$ in. diam., 8 ins. in concrete in a drill hole in bedrock, with aluminum cap mkd.</p>
	$ \begin{array}{c} \text{WP} \\ \text{T19N R25E} \\ \text{C } \frac{\text{S } 2}{1987} \text{ C} \end{array} $
	<p>Set a steel fence post near the cor.</p>
40.74	<p>The center $\frac{1}{4}$ sec. cor. of sec. 2.</p>

Subdivision of Section 2,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS	
61.11	<p>Point for the center W 1/16 sec. cor. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> $\begin{array}{c} \text{T19N R25E} \\ \text{C } \frac{\text{W } 1/16}{\text{S } 2} \text{ C} \\ 1987 \end{array}$ <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 3 ft. high, N of cor.</p> <p>Set a steel fence post near the cor.</p>
81.48	<p>The ¼ sec. cor. of secs. 2 and 3.</p>
	<p>From the center E 1/16 sec. cor. of sec. 2.</p> <p>N 0°38' E, on the N and S center line of the NE¼ of sec. 2.</p> <p>Over rocky ground.</p>
0.30	<p>Asc. 40 ft. over rock bluff, bears E and W; continue over rolling land.</p>
4.32	<p>Point for a witness point on the N and S center line of the NE¼ of sec. 2.</p> <p>Set a finned aluminum post, 36 ins. long, ¾ in. diam., 31 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{c} \text{WP} \\ \text{T19N R25E} \\ \text{E} \\ \text{S } 2 \\ \text{E} \\ 1987 \end{array}$ <p>Set a steel fence post near the cor.</p>

Subdivision of Section 2,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS	
19.76	<p>Point for the NE 1/16 sec. cor. of sec. 2, at intersection with the E and W center line of the NE$\frac{1}{4}$ of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E NE 1/16 S2 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Cor. is located in a minor drainage, drains N 45° W.</p>
24.53	<p>Point for a witness point on the N and S center line of the NE$\frac{1}{4}$ of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP T19N R25E E S 2 E 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2$\frac{1}{2}$ ft. high, N of cor.</p> <p>Set a steel fence post near the cor.</p> <p>Cor. is located on top of a ridge, bears N 72° E and S 72° W.</p>
39.96	<p>The E 1/16 sec. cor. of secs. 2 and 35, on the N Bdy. of the Tp.</p>

Subdivision of Section 2,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>From the N 1/16 sec. cor. of secs. 1 and 2.</p> <p>N 89°32' W, on the E and W center line of the NE$\frac{1}{4}$ of sec. 2.</p> <p>Over rolling terrain.</p> <p>20.35 The NE 1/16 sec. cor. of sec. 2.</p> <p>40.70 The center N 1/16 sec. cor. of sec. 2.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 2 and 11.</p> <p>N 0°47' E, on the N and S center line of the SW$\frac{1}{4}$ of sec. 2.</p> <p>Over rolling land.</p> <p>19.70 Point for the SW 1/16 sec. cor. of sec. 2, at intersection with the E and W center line of the SW$\frac{1}{4}$ of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E SW 1/16 S2 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p> <p>39.40 The center W 1/16 sec. cor. of sec. 2.</p> <hr/> <p>From the center S 1/16 sec. cor. of sec. 2.</p> <p>N 89°22' W, on the E and W center line of the SW$\frac{1}{4}$ of sec. 2.</p> <p>Over rolling land.</p>
---------------	--

Subdivision of Section 2,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

<p>CHAINS 20.40</p>	<p>The SW 1/16 sec. cor. of sec. 2.</p>
<p>40.80</p>	<p>The S 1/16 sec. cor. of secs. 2 and 3.</p>
<p>Subdivision of Section 5, T 19 N, R 25 E, Gila and Salt River Mer., Arizona</p>	
<p>19.875</p>	<p>From the 1/4 sec. cor. of secs. 5 and 8. N 1°48' E, on the N and S center line of sec. 5. Over rolling desert. Point for the center S 1/16 sec. cor. of sec. 5. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E C S 1/16 S 5 C 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post. Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor. Set a steel fence post near the cor.</p>
<p>37.40</p>	<p>Dry wash, 20 lks. wide, drains N 35° W.</p>
<p>39.75</p>	<p>Point for the center 1/4 sec. cor. of sec. 5, at the intersection with the E and W center line of sec. 5. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E C 1/4 S 5 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>

Subdivision of Section 5,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>Raise a mound of stone, 2½ ft. base, 2 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p> <p>46.50 Dead Wash, 1.50 chs. wide, drains S 55° W, from N 15° E.</p> <p>50.50 Dead Wash, 1.50 chs. wide, drains S 20° E.</p> <p>62.50 Dead Wash, 1.50 chs. wide, drains S 50° W.</p> <p>70.50 Branch of Dead Wash, 1.50 chs. wide, drains S 55° E.</p> <p>79.60 The ¼ sec. cor. of secs. 5 and 32, on the N Bdy. of the Tp.</p> <hr/> <p>From the ¼ sec. cor. of secs. 4 and 5.</p> <p>N 89°55' W, on the E and W center line of sec. 5.</p> <p>Over rolling desert.</p> <p>12.00 Dry ravine, 10 lks. wide, drains S 40° W.</p> <p>18.90 Dry wash, 50 lks. wide, drains S, from S 60° E.</p> <p>30.00 Same dry wash, 12 lks. wide, drains S 80° W in curve from S 70° E.</p> <p>36.51 The center ¼ sec. cor. of sec. 5.</p> <p>47.90 Dead Wash, 6 chs. wide, drains S 35° W, from N 65° E.</p> <p>56.85 Point for the center W 1/16 sec. cor. of sec. 5.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R25E C <u>W 1/16</u> C S 5 1987</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
---------------	---

Subdivision of Section 5,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.</p> <p>Set a steel fence post near the cor.</p> <p>77.19 The $\frac{1}{4}$ sec. cor. of secs. 5 and 6.</p> <hr/> <p>From the W $\frac{1}{16}$ sec. cor. of secs. 5 and 8.</p> <p>N $1^{\circ}49'$ E, on the N and S center line of the SW$\frac{1}{4}$ of sec. 5.</p> <p>Over rolling desert.</p> <p>16.70 Dead Wash, 2.70 chs. wide, drains S 85° W.</p> <p>19.895 Point for the SW $\frac{1}{16}$ sec. cor. of sec. 5, at the intersection with the E and W center line of the SW$\frac{1}{4}$ of sec. 5.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R25E SW $\frac{1}{16}$ S 5 1987</p> <p>Deposit a magnet in a 1 x 1 x $2\frac{5}{8}$ in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p> <p>39.79 The center W $\frac{1}{16}$ sec. cor. of sec. 5.</p> <hr/> <p>From the center S $\frac{1}{16}$ sec. cor. of sec. 5.</p> <p>N $89^{\circ}59'$ W, on the E and W center line of the SW$\frac{1}{4}$ of sec. 5.</p> <p>Over rolling desert.</p>	
--------	--	--

Subdivision of Section 5,
T 19 N, R 25 E, Gila and Salt River Mer., Arizona

CHAINS 10.60	Dead Wash, 5.50 chs. wide, drains S 60° W.
20.35	The SW 1/16 sec. cor. of sec. 5. Continue over rolling desert.
40.70	The S 1/16 sec. cor. of secs. 5 and 6.
GENERAL DESCRIPTION	
<p>The land encompassed in the survey is located five miles west of a small town called Navajo, Arizona. The northwest side of the township can be reached by Interstate Highway No. 40 to the Pinto exit. The southeast portion of the township can be reached by going south and west from Navajo on numerous dirt and gravel roads.</p> <p>The elevation of the township is about 5,500 feet above sea level with areas of +/- 100 feet. The township is drained by Puerco River which flows diagonally from the northeast corner to the southwest corner.</p> <p>There are scattered juniper throughout the township, although the area is mostly open rolling desert with sage and grass for cattle.</p> <p>The area is dotted with petroglyphs and petrified wood, many on the east and south.</p> <p>The magnetic declination, as taken from the U.S.G.S. Quadrangle map "PINTA ARIZ," is 13½° E.</p>	

CERTIFICATE OF SURVEY

We, Kenneth W. Bays and Stephen J. Malloy, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 12th day of January 1987, We have dependently resurveyed the North boundary and a portion of the South, East, and West boundaries and the subdivisional lines, and the survey of subdivisions of sections 2 and 5, Township 19 North, Range 25 East, of the Gila and Salt River Meridian, in the State of Arizona which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 17, 1987
(Date)

Kenneth W. Bays
(Cadastral Surveyor)

September 17, 1987
(Date)

Stephen J. Malloy
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

Bureau of Land Management

The foregoing field notes of the dependent resurvey of the North boundary and a portion of the South, East, and West boundaries, and the subdivisional lines, and the survey of subdivisions of sections 2 and 5, Township 19 North, Range 25 East, Gila and Salt River Meridian, Arizona, executed by Kenneth W. Bays and Stephen J. Malloy, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

SEP 21 1987
(Date)

James P. Kelley
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I Certify That the foregoing transcript of the field notes of the above-described surveys in T 19 N, R 25 E, Gila and Salt River Mer., Arizona, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor of Arizona)~~