

INDEX DIAGRAM

TOWNSHIP 3 NORTH, RANGE 7 WEST,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
				11	6
30	29	28	27	26	25
		16	12		
	18	15			
31	16	32	13	33	34
8				35	36
	3				

Metes-and-Bounds Survey in Section 32 pp. 18-19

T 3 N, R 7 W, Gila and Salt River Mer., Arizona

CHAINS

The following field notes are those of the dependent resurvey of portions of the south, east and west boundaries, and a portion of the subdivisional lines, and a metes-and-bounds survey in section 32, Township 3 North, Range 7 West, Gila and Salt River Meridian, Arizona.

The south boundary was surveyed by Jesse B. Wright in 1914. In 1916, Roy J. Gill surveyed the west boundary, Hans D. Voigt surveyed the east boundary and together they surveyed the subdivisional lines.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated March 9, 1988, for Group No. 705, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Recovered corners did not require remonumentation. Collateral evidence was used in restoration of obliterated corners. The retracement data were thoroughly verified and only the true line field notes are given herein.

Positions for angle points on the south right-of-way line of the Central Arizona Project Canal when needed to establish intersections with section lines were determined from information shown on Bureau of Reclamation survey diagrams 344-330-1819 dated June 23, 1977, and 344-330-1820, dated June 30, 1977, revised March 24, 1978.

The directions of all lines were determined by observations on a U.S. Coast & Geodetic Survey triangulation network, confirmed by solar observations, and refer to the true meridian. Distances and angles were measured with a Zeiss Elta 3 total station.

The geographic position of the southeast corner of section 24, as determined from a tie made to U.S. Coast & Geodetic Survey triangulation station "WASH 1947", located in the NW quarter of section 29, Township 3 North, Range 6 West, is as follows:

Latitude: 33°34'50.85" N Longitude: 112°55'07.85" W

The magnetic declination from U.S. Geological Survey quadrangle map "BELMONT MTS., ARIZ.", published in 1962, is 14 1/2° E.

Dependent Resurvey of a Portion of the S Bdy.,
T 3 N, R 7 W, Gila and Salt River Mer., Arizona

Reestablishment of the survey executed by
Jesse B. Wright, in 1914

Dependent Resurvey of a Portion of the S Bdy.,
T 3 N, R 7 W, Gila and Salt River Mer., Arizona

CHAINS	<p>Beginning at the cor. of secs. 5, 6, 31, and 32, on the S bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td></td><td style="text-align: center;">T3N</td><td></td></tr> <tr><td></td><td style="text-align: center;">S31 S32</td><td></td></tr> <tr><td style="text-align: center;">R7W</td><td style="text-align: center;">— —</td><td></td></tr> <tr><td></td><td style="text-align: center;">S6 S5</td><td></td></tr> <tr><td></td><td style="text-align: center;">T2N</td><td></td></tr> <tr><td></td><td style="text-align: center;">1914</td><td></td></tr> </table> </div> <p>A mound of stone, 2 ft. base, 1 1/2 ft. high, is W of cor.</p> <p>N 89°59' W, bet. secs. 6 and 31.</p> <p>Over nearly level land.</p> <p>39.85 Enter wash area, edge bears NE and SW.</p> <p>40.20 Abandoned E channel in wash area, 45 lks. wide, drains SW, curving S.</p> <p>41.40 The witness 1/4 sec. cor. of secs. 6 and 31, determined at record bearing and dist. from the center of the remaining original bearing tree</p> <div style="margin-left: 40px; margin-top: 10px;"> <p>An ironwood, 42 ins. diam., bears N 31 1/2° E, 52 lks. dist., mkd. WC 1/4 31 BT on an open blaze, located on a horizontal limb, 16 ins. diam., extending W from the center of the tree.</p> </div> <p>This position falls in the W channel within the wash area, 30 lks. wide, drains SE, curving S, where it is impracticable to establish a permanent monument. There is no remaining evidence of the original iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S 89°49' W, beginning new measurement.</p> <p>0.20 Leave wash area, edge bears SE and NW.</p> <p>0.477 Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-top: 10px;"> <p>T3N R7W</p> <p>1/4 <u>S31</u></p> <p style="margin-left: 20px;">S6</p> <p>T2N</p> <p>1988</p> </div>		T3N			S31 S32		R7W	— —			S6 S5			T2N			1914	
	T3N																		
	S31 S32																		
R7W	— —																		
	S6 S5																		
	T2N																		
	1914																		

Dependent Resurvey of a Portion of the S Bdy.,
T 3 N, R 7 W, Gila and Salt River Mer., Arizona

CHAINS

T3N	
S36	S31
R8W	R7W

S1	S6
T2N	
1914	

from which the remaining original bearing tree

A double trunk ironwood, 40 ins. diam., bears S 62 1/4° W, 1.00 ch. dist., with scribe marks T2N R8W S1 BT, visible on open blaze on SW fork. (1.015 ch. dist. to blaze).

A mound of stone, 3 ft. base, 1 1/2 ft. high, is S of cor.

Dependent Resurvey of a Portion of the E Bdy.,
T 3 N, R 7 W, Gila and Salt River Mer., Arizona

Reestablishment of the survey executed by
Roy J. Gill and Hans D. Voight, in 1916

From the cor. of secs. 19, 24, 25, and 30, monumented with an iron post, 3 ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd.

T3N	
R7W	R6W
S24	S19

S25	S30
1916	

A mound of stone, 2 ft. base, 1 ft. high, is W of cor.

From this cor. U.S.C. & G.S. triangulation station "WASH 1947," bears S 89°19.8' E, (forward bearing), 79.855 chs. dist., a brass tablet, 3 1/2 ins. diam., set flush in a concrete post, 11 ins. sq., projecting 5 ins. above ground.

North, bet. secs. 19 and 24.

Over nearly level land.

28.205

Point for a witness point on line bet. secs. 19 and 24 on the southerly right-of-way line of the Central Arizona Project Canal.

Dependent Resurvey of a Portion of the E Bdy.,
T 3 N, R 7 W, Gila and Salt River Mer., Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>W P T3N R7W R6W S24 / S19 1988</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>From this point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. 694+12.65 R.O.W. 125.00 FT. RT., bears N 64°48.3' E, 4.976 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.</p> <p>From this same point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. 687+99.43 R.O.W. 125.00 FT. RT., bears S 64°48.3' W, 4.317 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.</p>
40.03	<p>The 1/4 sec. cor. of secs. 19 and 24, monumented with an iron post, 1 in. diam., bent over, projecting 15 ins. above ground, with brass cap mkd. as described in the official record of the 1916 survey of the W bdy. of T 3 N, R 6 W, with a scattered mound of stone, W and a steel fence post nearby.</p> <p>At the cor. point</p> <p>Straighten and reset the iron post, 36 ins. long, 26 ins. in the ground. Add 1988 to the brass cap which is now mkd.</p> <div style="text-align: center;"> <p>1/4 S S 24 19 1988 1916</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the original post.</p> <p>Rebuild the mound of stone, 3 ft. base, 2 ft. high, W of cor.</p>

Dependent Resurvey of a Portion of the E Bdy.,
T 3 N, R 7 W, Gila and Salt River Mer., Arizona

CHAINS	<p>North, beginning new measurement.</p>												
39.98	<p>The cor. of secs. 13, 18, 19, and 24, monumented with an iron post 3 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T3N</td> </tr> <tr> <td style="text-align: center;">R7W</td> <td style="text-align: center;">R6W</td> </tr> <tr> <td style="text-align: center;">S13</td> <td style="text-align: center;">S18</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S24</td> <td style="text-align: center;">S19</td> </tr> <tr> <td colspan="2" style="text-align: center;">1916</td> </tr> </table> <p>A mound of stone, 3 ft. base, 1 ft. high, is W of cor.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the W Bdy., T 3 N, R 7 W, Gila and Salt River Mer., Arizona</p> <hr/> <p style="text-align: center;">Reestablishment of the survey executed by Roy J. Gill, in 1916</p> <hr/> <p>From the cor. of Tps. 2 and 3 N, Rs. 7 and 8 W., hereinbefore described.</p> <p>N 0°04' E, bet. secs. 31 and 36.</p> <p>Over nearly level land.</p>	T3N		R7W	R6W	S13	S18	-----		S24	S19	1916	
T3N													
R7W	R6W												
S13	S18												

S24	S19												
1916													
40.005	<p>The 1/4 sec. cor. of secs. 31 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">1/4</td> </tr> <tr> <td style="text-align: center;">S36</td> <td style="text-align: center;">S31</td> </tr> <tr> <td colspan="2" style="text-align: center;">1916</td> </tr> </table> <p>A mound of stone, 3 ft. base, 1 ft. high, is W of cor.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the Subdivisional Lines, T 3 N, R 7 W, Gila and Salt River Mer., Arizona</p> <hr/> <p style="text-align: center;">Reestablishment of the survey executed by Roy J. Gill and Hans D. Voigt, in 1916</p> <hr/>	1/4		S36	S31	1916							
1/4													
S36	S31												
1916													

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 3 N, R 7 W, Gila and Salt River Mer., Arizona

CHAINS	<p>From the cor. of secs. 23, 24, 25, and 26, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T3N</td> <td style="padding: 0 5px;">R7W</td> </tr> <tr> <td style="padding: 0 5px;">S23</td> <td style="padding: 0 5px;">S24</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; height: 1px;"></td> </tr> <tr> <td style="padding: 0 5px;">S26</td> <td style="padding: 0 5px;">S25</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">1916</td> </tr> </table> </div> <p>A mound of stone, 2 ft. base, 1 ft. high, is W of cor.</p> <p>N 0°05' E, bet. secs. 23 and 24.</p> <p>Over nearly level land.</p> <p>7.633 Point for a witness point on line bet. secs. 23 and 24 on the southerly right-of-way line of the Central Arizona Project Canal.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">W P</td> </tr> <tr> <td style="padding: 0 5px;">T3N R7W</td> </tr> <tr> <td style="padding: 0 5px;">S23</td> </tr> <tr> <td style="border-left: 1px solid black; border-right: 1px solid black; height: 1px;"></td> </tr> <tr> <td style="padding: 0 5px;">S24</td> </tr> <tr> <td style="padding: 0 5px;">1988</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>From this point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., projecting 6 ins. above ground, with top mkd. STA. 637+68.78 R.O.W. 125.00 FT. RT. RESET, bears N 61°25.3' E, 4.046 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.</p> <p>From this same point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. 628+59.71 R.O.W. 125.00 FT. RT., bears S 61°25.3' W, 9.728 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.</p>	T3N	R7W	S23	S24			S26	S25	1916		W P	T3N R7W	S23		S24	1988
T3N	R7W																
S23	S24																
S26	S25																
1916																	
W P																	
T3N R7W																	
S23																	
S24																	
1988																	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 3 N., R 7 W., Gila and Salt River Mer., Arizona

<p>CHAINS 40.01</p>	<p>The 1/4 sec. cor. of secs. 23 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 S23 S24 1916</p> <p>A mound of stone, 2 ft. base, 1 ft. high, is W of cor.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 S27 S26 1916</p> <p>A mound of stone, 1 1/2 ft. base, 1 ft. high, is W of cor.</p> <p>N 0°00.5' W, bet. secs. 26 and 27.</p> <p>Over nearly level land.</p>
<p>6.10</p>	<p>Point for a witness point on line bet. secs. 26 and 27 on the southerly right-of-way line of the Central Arizona Project Canal.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W P T3N R7W S27 S26 1988</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>From this point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. 582+20.00 R.O.W. 125.00 RT., bears N 70°12.9' E, 10.028 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 3 N, R 7 W, Gila and Salt River Mer., Arizona

<p>CHAINS</p> <p>39.995</p> <p>14.01</p>	<p>From this same point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., projecting 1 in. above ground, with top mkd. STA. 571+92.95 R.O.W. 125.00 FT. RT., bears S 70°12.9' W, 5.533 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.</p> <p>The cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T3N R7W</td> <td></td> </tr> <tr> <td>S22</td> <td>S23</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S27</td> <td>S26</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;">1916</td> </tr> </table> </div> <p>A mound of stone, 2 ft. base, 1 ft. high, is W of cor.</p> <hr/> <p>From the cor. of secs. 23, 24, 25, and 26.</p> <p>S 89°58' W, bet. secs. 23 and 26.</p> <p>Over nearly level land.</p> <p>Point for a witness point on line bet. secs. 23 and 26 on the southerly right-of-way line of the Central Arizona Project Canal.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>W P</td> <td></td> </tr> <tr> <td>T3N R7W</td> <td></td> </tr> <tr> <td>S23</td> <td></td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td></td> <td>S26</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;">1988</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>From this point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. 628+59.71 R.O.W. 125.00 FT. RT., bears N 61°23.5' E, 6.239 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.</p>	T3N R7W		S22	S23			S27	S26	1916		W P		T3N R7W		S23					S26	1988	
T3N R7W																							
S22	S23																						
S27	S26																						
1916																							
W P																							
T3N R7W																							
S23																							
	S26																						
1988																							

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 3 N, R 7 W, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>From this same point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. 620+08.05 R.O.W. 125.00 FT. RT., bears S 61°23.5' W, 6.665 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.</p> <p>40.04 The 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 S23 S26 1916</p> <p>A mound of stone, 2 ft. base, 1 ft. high, is N of cor.</p> <hr/> <p>S 89°58' W, beginning new measurement.</p> <p>Over nearly level land.</p> <p>40.06 The cor. of secs. 22, 23, 26, and 27.</p> <hr/> <p>From the cor. of secs. 27, 28, 33, and 34, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T3N R7W S28 S27 ----- S33 S34 1916</p> <p>A mound of stone, 2 ft. base, 1 ft. high, is W of cor.</p> <p>N 0°01' E, bet. secs. 27 and 28.</p> <p>Over nearly level land.</p> <p>15.04 Point for a witness point on line bet. secs. 27 and 28 on the southerly right-of-way line of the Central Arizona Project Canal.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>
---------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 3 N, R 7 W, Gila and Salt River Mer., Arizona

CHAINS	<div style="text-align: center; margin-bottom: 20px;"> <p>W P T3N R7W S28 / S27 1988</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>From this point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., 1 in. below the ground, with top mkd. STA. 524+23.83 R.O.W. 125.00 RT., bears N 66°28.1' E, 8.195 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.</p> <p>From this same point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. 517+81.32 R.O.W. 125.00 FT. RT., bears S 66°28.1' W, 1.540 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.</p> <p>39.99 The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., firmly set, projecting 19 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>1/4 S28 S27 1916</p> </div> <p>A mound of stone, 2 1/2 ft. base, 1 ft. high, is W of cor.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 32 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>1/4 S32 S33 1916</p> </div> <p>A mound of stone, 2 ft. base, 1 ft. high, is W of cor.</p> <p>N 0°08' W, bet. secs. 32 and 33.</p> <p>Over nearly level land.</p>
--------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey of a Portion of the Subdivisional Lines
T 3 N, R 7 W, Gila and Salt River Mer., Arizona

CHAINS	
26.597	<p>Point for a witness point on line bet. secs. 32 and 33 on the southerly right-of-way line of the Central Arizona Project Canal.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>W P T3N R7W S32 S33 1988</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>From this point the point for an angle point on the S right-of-way line of the Central Arizona Project Canal, bears S 67°58.4' W, 2.303 chs. dist., hereinafter described.</p>
28.23	<p>Point for a witness point on line bet. secs. 32 and 33 on the southerly right-of-way line of the Central Arizona Project Canal.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>W P T3N R7W S32 S33 1988</p> </div> <p>From this point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. 469+80.13 R.O.W. 125.00 FT. RT., bears N 67°58.4' E, 10.426 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.</p> <p>From this same point the point for an angle point on the S right-of-way line of the Central Arizona Project Canal, bears S 67°58.4' W, 2.912 chs. dist., hereinafter described.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 3 N, R 7 W, Gila and Salt River Mer., Arizona

CHAINS										
40.01	<p>The cor. of secs. 28, 29, 32, and 33, monumented with an iron post, 2 ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T3N R7W</td> <td style="padding: 0 5px;">S29</td> <td style="padding: 0 5px;">S28</td> </tr> <tr> <td style="border-right: 1px solid black; border-bottom: 1px solid black; padding: 0 5px;"></td> <td style="border-bottom: 1px solid black; padding: 0 5px;"></td> <td style="border-bottom: 1px solid black; padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;">S32</td> <td style="padding: 0 5px;">S33</td> <td style="padding: 0 5px;">1916</td> </tr> </table> </div> <p>A mound of stone, 2 ft. base, 1 ft. high, is W of cor.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the cor of secs. 27, 28, 33, and 34.</p> <p>S 89°52' W, bet. secs. 28 and 33.</p> <p>Over nearly level land.</p>	T3N R7W	S29	S28				S32	S33	1916
T3N R7W	S29	S28								
S32	S33	1916								
40.04	<p>The 1/4 sec. cor. of secs. 28 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">1/4</td> <td style="padding: 0 5px;">S28</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S33</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">1916</td> </tr> </table> </div> <p>A mound of stone, 2 ft. base, 1 ft. high, is N of cor.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>S 89°54' W, beginning new measurement.</p>	1/4	S28		S33		1916			
1/4	S28									
	S33									
	1916									
4.62	<p>Point for a witness point on line bet. secs. 28 and 33 on the southerly right-of-way line of the Central Arizona Project Canal.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">W P</td> </tr> <tr> <td style="padding: 0 5px;">T3N R7W</td> </tr> <tr> <td style="padding: 0 5px;">S28</td> </tr> <tr> <td style="border-top: 1px solid black; border-bottom: 1px solid black; padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;">S33</td> </tr> <tr> <td style="padding: 0 5px;">1988</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>	W P	T3N R7W	S28		S33	1988			
W P										
T3N R7W										
S28										
S33										
1988										

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 3 N, R 7 W, Gila and Salt River Mer., Arizona

CHAINS	
	<p>From this point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. 491+07.93 R.O.W. 125.00 FT. RT., bears N 76°47.4' E, 4.953 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.</p>
	<p>From this point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. 484+98.71 R.O.W. 125.00 FT. RT., bears S 76°47.4' W, 4.279 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.</p>
40.04	<p>The cor. of secs. 28, 29, 32, and 33.</p>
	<p>N 0°02.5' W, bet. secs. 28 and 29.</p>
	<p>Over nearly level land.</p>
40.015	<p>The 1/4 sec. cor. of secs. 28 and 29, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.</p>
	<p>1/4</p>
	<p>S29 S28</p>
	<p>1916</p>
	<p>A mound of stone, 2 ft. base, 1 ft. high, is W of cor.</p>
	<p>From the cor. of secs. 5, 6, 31, and 32, on the S bdy. of the Tp.</p>
	<p>N 0°03.5' W, bet. secs. 31 and 32.</p>
	<p>Over nearly level land.</p>
35.925	<p>Point for a witness point on line bet. secs. 31 and 32 on the southerly right-of-way line of the Central Arizona Project Canal.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p>W P</p>
	<p>T3N R7W</p>
	<p>S31 </p>
	<p> S32</p>
	<p>1988</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 3 N, R 7 W, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>From this point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., projecting 2 ins. above ground, with top mkd. STA. 406+49.51 R.O.W. 125.00 RT., bears N 67°57.9' E, 0.768 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.</p> <p>From this same point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., projecting 1 in. above ground, with top mkd. STA. 396+21.13 R.O.W. 125.00 FT. RT., bears S 67°57.9' W, 14.813 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.</p> <p>40.010 Point for the 1/4 sec. cor. of secs. 31 and 32, determined at a calculated position from Station 406+49.51 using Bureau of Reclamation field data, falls on top of flood control dike. There is no remaining evidence of the original monument.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T3N R7W 1/4 S31 S32 1988</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>From this cor. Station 406+49.51, bears S 10°40.0' E, 3.866 chs. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°03.5' W, beginning new measurement.</p> <p>Over nearly level land.</p> <p>40.005 The cor. of secs. 29, 30, 31, and 32, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.</p>
---------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 3 N, R 7 W, Gila and Salt River Mer., Arizona

CHAINS											
	<table border="1"> <tr> <td>T3N R7W</td> <td></td> </tr> <tr> <td>S30</td> <td>S29</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S31</td> <td>S32</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;">1916</td> </tr> </table>	T3N R7W		S30	S29			S31	S32	1916	
T3N R7W											
S30	S29										
S31	S32										
1916											
	A mound of stone, 2 1/2 ft. base, 1 ft. high, is W of cor.										
	From the cor. of secs. 28, 29, 32, and 33.										
	S 89°58' W, bet. secs. 29 and 32.										
	Over nearly level land.										
39.97	The 1/4 sec. cor. of secs. 29 and 32, monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd.										
	<table border="1"> <tr> <td>1/4</td> </tr> <tr> <td><u>S29</u></td> </tr> <tr> <td>S32</td> </tr> <tr> <td style="border-top: 1px solid black;">1916</td> </tr> </table>	1/4	<u>S29</u>	S32	1916						
1/4											
<u>S29</u>											
S32											
1916											
	A mound of stone, 2 ft. base, 1 ft. high, is N of cor.										
	S 89°58' W, beginning new measurement.										
	Over nearly level land.										
40.005	The cor. of secs. 29, 30, 31, and 32.										
	<p>Metes-and-Bounds Survey in Section 32, T 3 N, R 7 W, Gila and Salt River Mer., Arizona</p>										
	(This metes-and-bounds survey is determined from Bureau of Reclamation survey diagram 344-330-1820, dated June 30, 1977, revised March 24, 1978)										
	From the witness point of secs. 32 and 33, on the southerly right-of-way line of the Central Arizona Project Canal, located N 0°8' W, 26.597 chs. dist., from the 1/4 sec. cor. of secs. 32 and 33.										
	S 67°58.4' W, on the southerly right-of-way line of the Central Arizona Project Canal, 225 ft. right of center line.										
2.303	Point for an angle point on the S right-of-way line of the Central Arizona Project Canal, not monumented.										

Metes-and-Bounds Survey in Section 32,
T 3 N, R 7 W, Gila and Salt River Mer., Arizona

CHAINS	<p>N 22°01.6' W, on the southerly right-of-way line of the Central Arizona Project Canal.</p> <p>1.515 Point for an angle point on the S right-of-way line of the Central Arizona Project Canal, not monumented.</p> <hr/> <p>S 67°58.4' W, on the southerly right-of-way line of the Central Arizona Project Canal, 125 ft. right of center line.</p> <p>13.637 A brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. 452+00.00 R.O.W. 125.00 FT. RT. This monument was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The land encompassed in this survey is about 6 miles north of Tonopah, Arizona. The terrain is nearly level with a dense cover of creosote, and about 1,400 feet above sea level.</p> <p>The Central Arizona Project Canal enters the township on the south boundary of section 31, traverses northeasterly. Access is provided by the road along the canal and other secondary roads.</p> <hr/>
--------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Robert J. Lyle	Surveying Technician
Stephen M. Koval	Student Trainee (Land Surveyor)
Bruce J. Olson	Surveying Aid

CERTIFICATE OF SURVEY

I, Duane R. Garoutte, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 9th day of March, 1988, I have dependently resurveyed portions of the south, east and west boundaries and a portion of the subdivisional lines, and surveyed a metes-and-bounds survey in section 32 of Township 3 North, Range 7 West, of the Gila and Salt River Meridian, in the State of Arizona which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

MAY 09 1988

(Date)

Duane R. Garoutte
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of portions of the south, east and west boundaries and a portion of the subdivisional lines, and a metes-and-bounds survey in section 32 of Township 3 North, Range 7 West, Gila and Salt River Meridian, Arizona, executed by Duane R. Garoutte, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

MAY 09 1988

(Date)

James P. Kelley

(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I Certify that the foregoing transcript of the field notes of the above-described surveys in T 3 N, R 7 W, Gila and Salt River Meridian, Arizona is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~