

INDEX DIAGRAM

TOWNSHIP 3 NORTH, RANGE 6 WEST,

6	5	4	3	2	1
7	8	9	10	11	12
				12	7
18	17	16	15	10	14
				5	13
20	20	18	14		
	19	16	12	8	4
19	18	15			
	20	21	22	23	24
					4
30	29	28	27	26	25
31	32	33	34	35	36

- Metes-and-Bounds Survey in Section 13 pp. 21-22
- Metes-and-Bounds Survey in Section 14 pp. 22&23
- Metes-and-Bounds Survey in Section 15 pp. 24
- Metes-and-Bounds Survey in Section 19 pp. 26
- Metes-and-Bounds Survey in Section 20 pp. 25
- Metes-and-Bounds Survey in Section 21 pp. 24-25
- Metes-and-Bounds Survey in Section 23 pp. 23
- Metes-and-Bounds Survey in Section 24 pp. 21

T 3 N, R 6 W, Gila and Salt River Mer., Arizona

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, and metes-and-bounds surveys in certain sections, Township 3 North, Range 6 West, Gila and Salt River Meridian, Arizona.

The east boundary was surveyed by Woodbury Abbey, in 1915. The west boundary was surveyed by Hans D. Voigt, in 1916. The subdivisional lines were surveyed by Roy J. Gill and Hans D. Voigt in 1916. A portion of the east boundary was dependently resurveyed by Paul L. Reeves and a portion of the west boundary was dependently resurveyed by Duane R. Garoutte concurrently under this same group.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated March 9, 1988, for Group No. 705, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented if needed, in their original positions. Positions for lost corners were determined at proportionate positions based on the original record and Bureau of Reclamation record where appropriate. The retracement data were thoroughly verified and only the true line field notes are given herein.

Positions for angle points on the south right-of-way line of the Central Arizona Project Canal when needed to establish intersections with section lines were determined from information shown on Bureau of Reclamation survey diagrams 344-330-1914 dated April 8, 1977, revised March 6, 1978 and 344-330-1820, dated June 30, 1977, revised March 24, 1978.

The directions of all lines were determined by altitude observations on the sun, and refer to the true meridian. Distances and angles were measured using Zeiss Elta 46 and Hewlett-Packard 3820 total stations.

The geographic position of the southeast corner of section 24, as determined from a tie made to U.S. Coast & Geodetic Survey triangulation station "STREAK, 1947", located in the SW quarter of section 25, Township 3 North, Range 6 West, is as follows:

Latitude: 33°34'50.84" N Longitude: 112°48'53.92" W

The magnetic declination from U.S. Geological Survey quadrangle map "BELMONT MTS., ARIZ.", published in 1962, is 14 1/2° E.

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 3 N, R 6 W, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p style="text-align: center;">Reestablishment of the survey executed by Roy J. Gill and Hans D. Voigt in 1916</p> <hr/> <p>Beginning at the cor. of secs. 19, 24, 25, and 30, on the E bdy. of the Tp., described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T 3 N, R 5 W, surveyed concurrently under this same group.</p> <p>S 89°58' W, bet. secs. 24 and 25.</p> <p>Over nearly level land.</p> <p>39.93 The 1/4 sec. cor. of secs. 24 and 25, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 <u>S24</u> S25 1916</p> <hr/> <p>From the cor. of secs. 13, 18, 19, and 24, on the E bdy. of the Tp., described in the field notes of the dependent resurvey of a portion of the W bdy. of T 3 N, R 5 W, surveyed concurrently under this same group.</p> <p>From this cor. U.S.C. & G.S. triangulation station "STREAK 1947", bears S 29°03.2' W, (forward bearing), 156.895 chs. dist., monumented with a brass tablet, 3 1/2 ins. diam., set flush in a malpais boulder, 5 ft. sq., projecting 18 ins. above ground.</p> <p>S 89°59' W, bet. secs. 13 and 24.</p> <p>Over level land.</p> <p>39.94 The 1/4 sec. cor. of secs. 13 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 17 ins. above ground, in a mound of stone, 1 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">1/4 <u>S13</u> S24 1916</p> <p>A mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, is N of cor.</p> <hr/>
---------------	---

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 3 N, R 6 W, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>S 89°59' W, beginning new measurement.</p>
<p>24.95</p>	<p>Point for a witness point on line bet. secs. 13 and 24 on the southerly right-of-way line of the Central Arizona Project Canal.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <p>W P T3N R6W S13 S24 1988</p> </div> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, N of cor.</p> <p>Cor. is located 4 lks. S of a fence, bears S 28° E and N 28° W, and 13 lks. N of a trail road, bears S 28° E and N 28° W.</p> <p>From this point the point for an angle point on the S right-of-way line of the Central Arizona Project Canal, bears S 28°18.1' E, 11.982 chs. dist., hereinafter described.</p> <p>From this same point the point for an angle point on the S right-of-way line of the Central Arizona Project Canal, bears N 28°18.1' W, 14.411 chs. dist., hereinafter described.</p>
<p>39.95</p>	<p>The cor. of secs. 13, 14, 23, and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T3N R6W S S 14 13 S S 23 24 1916</p> </div> <p>A mound of stone, 3 ft. base, 1 ft. high, is W of cor.</p>
<p>13.51</p>	<p>N 0°00.5' E, bet. secs. 13 and 14.</p> <p>Over nearly level land.</p> <p>Point for a witness point on line bet. secs. 13 and 14 on the southerly right-of-way line of the Central Arizona Project Canal.</p>


Dependent Resurvey, a Portion of the Subdivisional Lines,
T 3 N, R 6 W, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.</p> <div data-bbox="857 373 987 556" style="text-align: center;"> </div> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.</p> <p>Cor. is located 1 1/2 lks. E of a fence, bears S 29° E and N 29° W.</p> <p>From this point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. PO 170+73.06 R.O.W. 83.01 RT., bears S 30°21.7' E, 4.595 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.</p> <p>Cor. is located 2 1/2 lks. S of a fence cor.; fences bear N 61° E and N 29° W.</p> <p>From this same point the point for an angle point on the S right-of-way line of the Central Arizona Project Canal, bears N 30°21.7' W, 5.308 chs. dist., hereinafter described.</p>
<p>24.555</p>	<p>Point for a witness point on line bet. secs. 13 and 14 on the northerly right-of-way line of the Central Arizona Project Canal.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <div data-bbox="857 1386 987 1568" style="text-align: center;"> </div> <p>Cor. is located 1 lk. S of a fence, bears N 67° E, and S 67° W.</p> <p>From this point a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with aluminum cap mkd. R.O.W., bears N 67°01.1 E, 15.361 chs. dist. This point was established by the Bureau of Reclamation on the N right-of-way line of the Central Arizona Project Canal.</p> <p>Cor. is located 2 lks. N of a fence cor.; fences bear S 67° W and S 25° E.</p>


Dependent Resurvey, a Portion of the Subdivisional Lines,
T 3 N, R 6 W, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>From this same point a rebar, 5/8 in. diam., firmly set, flush with the ground, with aluminum cap mkd. R.O.W., bears S 67°01.1' W, 5.638 chs. dist. This point was established by the Bureau of Reclamation on the N right-of-way line of the Central Arizona Project Canal.</p> <p>Cor. is located 2 lks. N of a fence cor.; fences bear N 67° E and S 60° W.</p> <p>39.99 The 1/4 sec. cor. of secs. 13 and 14, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>1/4</td><td></td></tr> <tr><td>S</td><td>S</td></tr> <tr><td>14</td><td>13</td></tr> <tr><td>1916</td><td></td></tr> </table> <hr style="width: 20%; margin: 0 auto;"/> </div> <p>N 0°01' W, beginning new measurement.</p> <p>40.14 The cor. of secs. 11, 12, 13, and 14, monumented with an iron post, 2 ins. diam., firmly set, projecting 2 ft. above ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T3N</td><td>R6W</td></tr> <tr><td>S11</td><td>S12</td></tr> <tr><td>S14</td><td>S13</td></tr> <tr><td>1916</td><td></td></tr> </table> <hr style="width: 20%; margin: 0 auto;"/> </div> <p>A mound of stone, 3 ft. base, 2 ft. high, is W of cor.</p> <p>From the cor. of secs. 7, 12, 13, and 18, on the E bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T3N</td><td></td></tr> <tr><td>R6W</td><td>R5W</td></tr> <tr><td>S12</td><td>S7</td></tr> <tr><td>S13</td><td>S18</td></tr> <tr><td>1915</td><td></td></tr> </table> </div> <p>Record monument, an iron post, 3 ins. diam.</p> <p>N 89°58' W, bet. secs. 12 and 13.</p> <p>39.99 The 1/4 sec. cor. of secs. 12 and 13, monumented with an iron post, 1 in. diam., firmly set flush with the ground, with brass cap mkd.</p>	1/4		S	S	14	13	1916		T3N	R6W	S11	S12	S14	S13	1916		T3N		R6W	R5W	S12	S7	S13	S18	1915	
1/4																											
S	S																										
14	13																										
1916																											
T3N	R6W																										
S11	S12																										
S14	S13																										
1916																											
T3N																											
R6W	R5W																										
S12	S7																										
S13	S18																										
1915																											

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 3 N, R 6 W, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">1/4 <u>S12</u> S13 1916</p> <p>An embedded mound of stone, 2 ft. base, 1 ft. high, is N of cor.</p> <p>Remark the brass cap to read:</p> <p style="text-align: center;">T3N R6W 1/4 <u>S12</u> S13 1988 1916</p> <p>Set a steel fence post near the cor.</p> <p>Cor. is located 50 lks. E of a wash, 50 lks. wide, 3 ft. deep, drains S 25° E.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N 89°56' W, beginning new measurement.</p>
39.83	<p>The cor. of secs. 11, 12, 13, and 14.</p> <hr/>
	<p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>N 89°59' W, bet. secs. 14 and 23.</p> <p>Over nearly level land.</p>
23.225	<p>Point for a witness point on line bet. secs. 14 and 23 on the southerly right-of-way line of the Central Arizona Project Canal.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>W P T3N R6W S14</p>  <p>S23 1988</p> </div> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, N of cor.</p> <p>Cor. is located 42 lks. E of a fence cor.; fences bear N 60° E and W.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 3 N, R 6 W, Gila and Salt River Mer., Arizona

CHAINS	
	<p>From this point the point for an angle point on the S right-of-way line of the Central Arizona Project Canal, bears N 59°38.2' E, 10.001 chs. dist., hereinafter described.</p> <p>Thence continue measurement on the line bet. secs. 14 and 23, identical with the southerly right-of-way line of the Central Arizona Project Canal.</p>
33.52	<p>Point for a witness point on line bet. secs. 14 and 23 on the southerly right-of-way line of the Central Arizona Project Canal.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 19 ins. in the ground, in a mound of stone, 4 ft. base, to top, with cap mkd.</p> <div style="text-align: center;"> <p>W P T3N R6W S14</p>  </div> <p>Cor. is located in a fence, 8 lks. E of a fence cor., fences bear E, S 60° W, and W.</p> <p>From this point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. P.T. 139+40.84 R.O.W. 175.00 RT., bears S 59°33.6' W, 11.715 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate dist., based on Bureau of Reclamation diagram 344-330-1914 dated April 8, 1977, revised March 6, 1978; there is no remaining evidence of the original monument. The true point falls in the Central Arizona Project Canal where it is impracticable to establish a permanent monument.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S 89°59' W, beginning new measurement.</p> <p>Over rolling land.</p>
20.805	<p>Point for a witness point on line bet. secs. 14 and 23 on the southerly right-of-way line of the Central Arizona Project Canal.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 12 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 3 N, R 6 W, Gila and Salt River Mer., Arizona

CHAINS	
	<div style="text-align: center;"> <p>W P T3N R6W S14</p> <hr style="width: 50%; margin: auto;"/> <p>S23 1988</p> </div> <p>Cor. is located 5 lks. W of a fence, bears S 39° E and N 39° W.</p> <p>From this point the point for an angle point on the S right-of-way line of the Central Arizona Project Canal, bears S 38°45.2' E, 13.966 chs. dist., hereinafter described.</p> <p>From this same point the point for an angle point on the S right-of-way line of the Central Arizona Project Canal, bears N 38°45.2' W, 5.588 chs. dist., hereinafter described.</p>
40.04	<p>The cor. of secs. 14, 15, 22, and 23, monumented with an iron post, 2 ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T3N R6W S15 S14</p> <hr style="width: 50%; margin: auto;"/> <p>S22 S23 1916</p> </div> <p>A mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, is W of cor.</p>
1.635	<p>N 0°02.5' W, bet. secs. 14 and 15.</p> <p>Point for a witness point on line bet. secs. 14 and 15 on the southerly right-of-way line of the Central Arizona Project Canal.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 29 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <p>W P T3N R6W S15 </p> <hr style="width: 50%; margin: auto;"/> <p>S14 1988</p> </div> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.</p> <p>Cor. is located 3 1/2 lks. S of a fence, bears N 70° E and S 70° W.</p>



Dependent Resurvey, a Portion of the Subdivisional Lines,
T 3 N, R 6 W, Gila and Salt River Mer., Arizona

<p>CHAINS</p> <p>8.09</p> <p>39.97</p>	<p>From this point the point for an angle point on the S right-of-way line of the Central Arizona Project Canal, bears N 70°13.8' E, 11.503 chs. dist., hereinafter described.</p> <p>From this same point the point for an angle point on the S right-of-way line of the Central Arizona Project Canal, bears S 70°13.8' W, 11.035 chs. dist., not monumented</p> <p>Point for a witness point on line bet. secs. 14 and 15 on the northerly right-of-way line of the Central Arizona Project Canal.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 10 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <div style="text-align: center;"> <p>W P</p> <p>T3N R6W</p> <p>S15 </p> <p>— —</p> <p> S14</p> <p>1988</p> </div> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 20 lks. N of a fence, bears N 70° E and S 70° W.</p> <p>From this point a rebar, 5/8 in. diam., firmly set, projecting 2 ins above ground, with aluminum cap mkd. R.O.W., bears N 70°12.7 E, 8.165 chs. dist. This point was established by the Bureau of Reclamation on the N right-of-way line of the Central Arizona Project Canal.</p> <p>Cor. is located 1 lk. W of a fence, bears N 26° E and S 26° W.</p> <p>From this same point a rebar, 5/8 ins. diam., firmly set, projecting 4 ins. above ground, with aluminum cap mkd. R.O.W., bears S 70°12.7 W, 6.891 chs. dist. This point was established by the Bureau of Reclamation on the N right-of-way line of the Central Arizona Project Canal.</p> <p>Cor. is located 2 lks. E of a fence, bears S 47° E and N 47° W.</p> <p>The 1/4 sec. cor. of secs. 14 and 15, monumented with an iron post, 1 in. diam., firmly set, projecting 20 ins. above ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>1/4</p> <p>S15 S14</p> <p>1916</p> </div>
--	---

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 3 N, R 6 W, Gila and Salt River Mer., Arizona

CHAINS									
	<p>N 0°04' W, beginning new measurement.</p> <p>Over nearly level land.</p>								
39.96	<p>The cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 2 ins. diam., firmly set, projecting 20 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T3N</td> <td>R6W</td> </tr> <tr> <td>S10</td> <td>S11</td> </tr> <tr> <td>S15</td> <td>S14</td> </tr> <tr> <td colspan="2">1916</td> </tr> </table> </div>	T3N	R6W	S10	S11	S15	S14	1916	
T3N	R6W								
S10	S11								
S15	S14								
1916									
40.01	<p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>S 89°50' W, bet. secs. 11 and 14.</p> <p>The 1/4 sec. cor. of secs. 11 and 14, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>1/4</td> <td>S11</td> </tr> <tr> <td></td> <td>S14</td> </tr> <tr> <td colspan="2">1916</td> </tr> </table> </div>	1/4	S11		S14	1916			
1/4	S11								
	S14								
1916									
40.09	<p>A mound of stone, 3 ft. base, 1 1/2 ft. high, is N of cor.</p> <hr/> <p>S 89°52.5' W, beginning new measurement.</p> <p>The cor. of secs. 10, 11, 14, and 15.</p>								
4.555	<p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>S 89°59.5' W, bet. secs. 15 and 22.</p> <p>Over gently rolling land.</p> <p>Point for a witness point on line bet. secs. 15 and 22 on the southerly right-of-way line of the Central Arizona Project Canal.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.</p>								

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 3 N, R 6 W, Gila and Salt River Mer., Arizona

CHAINS	
	<div style="text-align: center;"> <p>W P T3N R6W S15</p>  <p>S22 1988</p> </div> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, S of cor.</p> <p>Cor. is located 3 lks. S of a fence, bears N 70° E and S 70° W.</p> <p>From this point the witness point of secs. 14 and 15 on the S right-of-way line of the Central Arizona Project Canal, bears N 70°13.8' E, 4.838 chs. dist., hereinbefore described.</p> <p>From this same point the point for an angle point on the S right-of-way line of the Central Arizona Project Canal, bears S 70°13.8' W, 6.197 chs. dist., not monumented.</p>
15.275	<p>Point for a witness point on line bet. secs. 15 and 22 on the southerly right-of-way line of the Central Arizona Project Canal.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 18 ins. in the ground, in a mound of stone, 4 ft. base, to top, with cap mkd.</p>
	<div style="text-align: center;"> <p>W P T3N R6W S15</p>  <p>S22 1988</p> </div> <p>Set a steel fence post near the cor.</p> <p>Cor. is located 75 lks. S of a fence, bears S 67° E and N 67° W.</p> <p>From this point the point for an angle point on the S right-of-way line of the Central Arizona Project Canal, bears S 66°48.9' E, 5.319 chs. dist., not monumented.</p> <p>From this same point the point for an angle point on the S right-of-way line of the Central Arizona Project Canal, bears N 66°48.9' W, 3.864 chs. dist., hereinafter described.</p>
39.985	<p>The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 3 N, R 6 W, Gila and Salt River Mer., Arizona

CHAINS											
	<p style="text-align: center;">1/4 <u>S15</u> S22 1916</p> <p>A mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, is N of cor.</p> <hr style="width: 20%; margin: auto;"/> <p>N 89°59' W, beginning new measurement.</p>										
39.98	<p>The cor. of secs. 15, 16, 21, and 22, located on the southerly right-of-way line of the Central Arizona Project Canal, monumented with an iron post, 2 ins. diam., firmly set, projecting 20 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table border="1" style="border-collapse: collapse; margin: auto;"> <tr> <td colspan="2" style="padding: 2px;">T3N R6W</td> </tr> <tr> <td style="padding: 2px;">S16</td> <td style="padding: 2px;">S15</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; padding: 2px;"></td> </tr> <tr> <td style="padding: 2px;">S21</td> <td style="padding: 2px;">S22</td> </tr> <tr> <td colspan="2" style="padding: 2px;">1916</td> </tr> </table> </div> <p>Cor. is located 4 lks. S of a fence, bears N 64° E, and S 64° W.</p> <hr style="width: 20%; margin: auto;"/> <p>N 0°02' E, bet. secs. 15 and 16.</p> <p>Over gently rolling land.</p>	T3N R6W		S16	S15			S21	S22	1916	
T3N R6W											
S16	S15										
S21	S22										
1916											
13.255	<p>Point for a witness point on line bet. secs. 15 and 16 on the northerly right-of-way line of the Central Arizona Project Canal. This position falls in a wash where it is impracticable to establish a permanent monument.</p> <p>From this point a rebar, 5/8 in. diam., firmly set, projecting 2 ins above ground, with an unmkd. aluminum cap, bears N 78°28.5 E, 26.456 chs. dist. This point was established by the Bureau of Reclamation on the N right-of-way line of the Central Arizona Project Canal.</p> <p>Cor. is located 3 lks. N of a fence, bears N 78° E and S 78° W.</p> <p>From this same point a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with an unmkd. aluminum cap, bears S 78°28.5 W, 13.828 chs. dist. This point was established by the Bureau of Reclamation on the N right-of-way line of the Central Arizona Project Canal.</p>										
40.03	<p>The 1/4 sec. cor. of secs. 15 and 16, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.</p>										

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 3 N, R 6 W, Gila and Salt River Mer., Arizona

CHAINS	<p style="text-align: center;">1/4 S S 16 15 1916</p> <p>A mound of stone, 2 1/2 ft. base, 2 ft. high, is W of cor.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 20 and 21, monumented with an iron post, 1 in. diam., firmly set, projecting 30 ins. above ground, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">1/4 S20 S21 1916</p> <p>A mound of stone, 3 ft. base, 2 ft. high, is W of cor.</p> <p>Cor. is located on steep NE slope.</p> <p>N 0°01.5' W, bet. secs. 20 and 21.</p> <p>39.11 Point for a witness point on line bet. secs. 20 and 21 on the southerly right-of-way line of the Central Arizona Project Canal.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <p>W P T3N R6W S20 ----- S21 1988</p> </div> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, W of cor.</p> <p>Cor. is located 4 lks. S of a fence, bears N 72° E and S 72° W.</p> <p>From this point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. 810+99.96 R.O.W. 125.00 FT. RT., bears N 72°21.2' E, 4.906 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.</p> <p>Cor. is located 5 lks. S of a fence, bears N 72° E and S 72° W.</p> <p>From this same point the point for an angle point on the S right-of-way line of the Central Arizona Project Canal, bears S 72°21.2' W, 9.487 chs. dist., hereinafter described.</p>
--------	--

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 3 N, R 6 W, Gila and Salt River Mer., Arizona

<p>CHAINS 39.99</p>	<p>Point for the cor. of secs. 16, 17, 20, and 21, at proportionate dist., based on the original record and Bureau of Reclamation diagram 344-330-1820, dated June 30, 1977, revised March 24, 1978; there is no remaining evidence of the original monument.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T3N R6W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S17</td> <td style="padding: 2px 5px;">S16</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; border-bottom: 1px solid black;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S20</td> <td style="padding: 2px 5px;">S21</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 5px;">1988</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>Cor. is located 18 lks. S of a road, bears N 70° E and S 70° W, and 82 lks. N of a fence, bears N 72° E and S 72° W.</p> <hr style="border: 0.5px solid black;"/> <p>From the cor. of secs. 15, 16, 21, and 22.</p> <p>West, bet. secs. 16 and 21.</p> <p>Over level land.</p>	T3N R6W		S17	S16			S20	S21	1988	
T3N R6W											
S17	S16										
S20	S21										
1988											
<p>34.28</p>	<p>Point for a witness point on line bet. secs. 16 and 21 on the southerly right-of-way line of the Central Arizona Project Canal.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">W P</td> </tr> <tr> <td colspan="2">T3N R6W</td> </tr> <tr> <td colspan="2" style="border-bottom: 1px solid black; text-align: right; padding-right: 5px;">S16</td> </tr> <tr> <td style="border-bottom: 1px solid black; padding: 2px 5px;">S21</td> <td style="border-left: 1px solid black; padding: 2px 5px;"></td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 5px;">1988</td> </tr> </table> </div> <p>Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, N of cor.</p> <p>Cor. is located 5 lks. S of a fence, bears S 58° E and N 58° W.</p> <p>From this point the point for an angle point on the S right-of-way line of the Central Arizona Project Canal, bears S 57°41.2' E, 17.714 chs. dist., hereinafter described.</p>	W P		T3N R6W		S16		S21		1988	
W P											
T3N R6W											
S16											
S21											
1988											

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 3 N, R 6 W, Gila and Salt River Mer., Arizona

CHAINS	<p>From this same point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. 832+40.88 PT R.O.W. 125.00 FT. RT., bears N 57°41.2' W, 13.866 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.</p> <p>Cor. is located 4 lks. S of a fence cor.; fences bear S 58° E and N 83° W.</p>
40.045	<p>The 1/4 sec. cor. of secs. 16 and 21, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 <u>S16</u> S21 1916</p> <p>A mound of stone, 2 ft. base, 1 ft. high, is N of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>West, beginning new measurement.</p>
37.242	<p>Point for a witness point on line bet. secs. 16 and 21 on the southerly right-of-way line of the Central Arizona Project Canal.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">W P T3N R6W <u>S16</u> S21 1988</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, N of cor.</p> <p>Cor. is located 4 lks. S of a fence, bears N 72° E and S 72° W.</p> <p>From this point station 810+99.96, on the s right-of-way of the Central Arizona Project Canal, bears N 72°21.2' E, 2.002 chs. dist., hereinbefore described.</p> <p>From this same point the witness point of secs. 20 and 21, on the S right-of-way line of the Central Arizona Project Canal, bears S 72°21.2' W, 2.904 chs. dist., hereinbefore described.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 3 N, R 6 W, Gila and Salt River Mer., Arizona

CHAINS 40.01	<p>The cor. of secs. 16, 17, 20, and 21.</p> <hr/> <p>N 0°02' W, bet. secs. 16 and 17.</p> <p>Over gently rolling land.</p>
40.00	<p>The 1/4 sec. cor. of secs. 16 and 17, monumented with an iron post, 1 in. diam., bent over, projecting 14 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 S17 S16 1916</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T3N R6W 1/4 S17 S16 1988</p> <p>Bury the original iron post alongside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Rebuild the mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 20, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 S S 19 20 1916</p> <p>A mound of stone, 2 ft. base, 1 ft. high, is W of cor.</p> <p>N 0°01.5' W, bet. secs. 19 and 20.</p> <p>Over level land.</p>
33.60	<p>Point for a witness point on line bet. secs. 19 and 20 on the southerly right-of-way line of the Central Arizona Project Canal.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 3 N, R 6 W, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <p>W P T3N R6W S20 — S19 1988</p> </div> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W of cor.</p> <p>Cor. is located 4 lks. S of a fence, bears S 87° E and N 87° W.</p> <p>From this point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., projecting 1 in. above the ground, with top mkd. STA. 762+98.10 R.O.W. 125.00 FT. RT., bears S 86°57.4' E, 12.866 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.</p> <p>A steel fence post was found set near the cor.</p> <p>Cor. is located 4 lks. S of a fence, bears S 87° E and N 87° W.</p> <p>From this same point the point for an angle point on the S right-of-way line of the Central Arizona Project Canal, bears N 86°57.4' W, 16.237 chs. dist., hereinafter described.</p>
<p>40.00</p>	<p>The cor. of secs. 17, 18, 19, and 20, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T3N R6W S S 18 17 — S S 19 20 1916</p> </div> <p>A steel fence post was found set near the cor.</p> <p>A mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, is W of cor.</p> <hr/> <p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>S 89°43' W, bet. secs. 17 and 20.</p> <p>Over level land.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 3 N, R 6 W, Gila and Salt River Mer., Arizona

<p>CHAINS 40.03</p>	<p>The 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 <u>S17</u> S20 1916</p> <p>A mound of stone, 3 ft. base, 1 1/2 ft. high, is N of cor.</p> <hr style="width: 20%; margin: auto;"/> <p>N 89°45' W, beginning new measurement.</p>
<p>40.09</p>	<p>The cor. of secs. 17, 18, 19, and 20.</p> <hr/> <p>N 89°58.5' W, bet. secs. 18 and 19.</p> <p>Over level land.</p>
<p>40.01</p>	<p>The 1/4 sec. cor. of secs. 18 and 19, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 <u>S18</u> S19 1916</p> <p>A mound of stone, 3 ft. base, 1 1/2 ft. high, is N of cor.</p> <hr style="width: 20%; margin: auto;"/> <p>West, beginning new measurement.</p>
<p>39.16</p>	<p>The cor. of secs. 13, 18, 19, and 24, on the W bdy. of the Tp., previously described in the field notes of the dependent resurvey of a portion of the E bdy. of T 3 N, R 7 W, surveyed concurrently under this same group.</p> <hr/> <p>From the cor. of secs. 17, 18, 19, and 20.</p> <p>North, bet. secs. 17, and 18.</p> <p>Over gently rolling land.</p>
<p>40.05</p>	<p>The 1/4 sec. cor. of secs. 17 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 3 N, R 6 W, Gila and Salt River Mer., Arizona

CHAINS	<p style="text-align: center;">1/4 S S 18 17 1916</p> <p>A mound of stone, 2 1/2 ft. base, 2 ft. high, is W of cor.</p> <hr/> <p style="text-align: center;">MEMORANDUM</p> <p>The following metes-and-bounds surveys are determined from Bureau of Reclamation survey diagrams 344-330-1820 dated June 30, 1977, revised March 24, 1978 and 344-330-1914 dated April 8, 1977, revised March 6, 1978.</p> <hr/> <p style="text-align: center;">Metes-and-Bounds Survey, Portions of the S Bdy., Central Arizona Project Canal, T 3 N, R 6 W, Gila and Salt River Mer., Arizona</p> <hr/> <p>From station 223+77.70, located in sec. 24, monumented with a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., projecting 1 in. above the ground, with top mkd. STA. 223+77.70 PO Revised R.O.W. 125.00 FT. RT. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.</p> <p>N 65°06.8' W, on the southerly right-of-way line of the Central Arizona Project Canal, in sec. 24.</p> <p>37.722 Point for an angle point on the S right-of-way line of the Central Arizona Project Canal, not monumented.</p> <hr/> <p>N 28°18.1' W, on the southerly right-of-way line of the Central Arizona Project Canal.</p> <p>11.982 The witness point of secs. 13 and 24, on the southerly right-of-way line of the Central Arizona Project Canal, hereinbefore described, located N 89°59' E, 15.00 chs. dist. from the cor. of secs. 13, 14, 23, and 24.</p> <hr/> <p>Thence in sec. 13.</p> <p>N 28°18.1' W, on the southerly right-of-way line of the Central Arizona Project Canal.</p>
--------	---

Metes-and-Bounds Survey, Portions of the S Bdy., Central Arizona
Project Canal, T 3 N, R 6 W, Gila and Salt River Mer., Arizona

CHAINS	
14.411	Point for an angle point on the S right-of-way line of the Central Arizona Project Canal, not monumented. <hr/>
	S 61°41.8' W, on the southerly right-of-way line of the Central Arizona Project Canal.
6.640	Station 170+73.06, on the S right-of-way line of the Central Arizona Project Canal, hereinbefore described.
	N 30°21.7' W, on the southerly right-of-way line of the Central Arizona Project Canal.
4.595	The witness point of secs. 13 and 14, on the southerly right-of-way line of the Central Arizona Project Canal, hereinbefore described, located N 0°00.5' E, 13.51 chs. dist. from the cor. of secs. 13, 14, 23, and 24. <hr/>
	Thence in sec. 14.
	N 30°21.7' W, on the southerly right-of-way line of the Central Arizona Project Canal.
5.308	Point for an angle point on the S right-of-way line of the Central Arizona Project Canal, not monumented. <hr/>
	S 59°38.0' W, on the southerly right-of-way line of the Central Arizona Project Canal.
16.866	Point for an angle point on the S right-of-way line of the Central Arizona Project Canal, not monumented. <hr/>
	S 30°22.2' E, on the southerly right-of-way line of the Central Arizona Project Canal.
5.215	Point for an angle point on the S right-of-way line of the Central Arizona Project Canal, not monumented. <hr/>
	S 59°38.2' W, on the southerly right-of-way line of the Central Arizona Project Canal.
10.001	A witness point of secs. 14 and 23, on the southerly right-of-way line of the Central Arizona Project Canal, hereinbefore described, located N 89°59' W, 23.225 chs. dist. from the cor. of secs. 13, 14, 23, and 24. <hr/>

Metes-and-Bounds Survey, Portions of the S Bdy., Central Arizona
Project Canal, T 3 N, R 6 W, Gila and Salt River Mer., Arizona

CHAINS	
	N 89° 59' W, on the line bet. secs. 14 and 23, identical with a portion of the southerly right-of-way line of the Central Arizona Project Canal.
10.295	A witness point of secs. 14 and 23, on the southerly right-of-way line of the Central Arizona Project Canal, hereinbefore described, located N 89°59' W, 33.52 chs. dist. from the cor. of secs. 13, 14, 23, and 24. Thence in sec. 23.
11.715	S 59°33.6' W, on the southerly right-of-way line of the Central Arizona Project Canal. Station 139+40.84, on the S right-of-way line of the Central Arizona Project Canal, hereinbefore described.
9.794	S 59°33.6' W, beginning new measurement, on the southerly right-of-way line of the Central Arizona Project Canal. Point for an angle point on the S right-of-way line of the Central Arizona Project Canal, not monumented.
13.966	N 38°45.2' W, on the southerly right-of-way line of the Central Arizona Project Canal. A witness point of secs. 14 and 23, on the southerly right-of-way line of the Central Arizona Project Canal, hereinbefore described, located N 89°59' E, 19.235 chs. dist., from the cor. of secs. 14, 15, 22, and 23. Thence in sec. 14.
5.588	N 38°45.2' W, on the southerly right-of-way line of the Central Arizona Project Canal. Point for an angle point on the S right-of-way line of the Central Arizona Project Canal, not monumented.
5.051	N 76°41.9' W, on the southerly right-of-way line of the Central Arizona Project Canal. Point for an angle point on the S right-of-way line of the Central Arizona Project Canal, not monumented.

Metes-and-Bounds Survey, Portions of the S Bdy., Central Arizona
Project Canal, T 3 N, R 6 W, Gila and Salt River Mer., Arizona

CHAINS	
	S 70°13.8' W, on the southerly right-of-way line of the Central Arizona Project Canal.
11.503	The witness point of secs. 14 and 15, on the southerly right-of-way line of the Central Arizona Project Canal, hereinbefore described, located N 0°02.5' W, 1.635 chs. dist., from the cor. of secs. 14, 15, 22, and 23.
	<hr/> From the witness point of secs. 15 and 22, on the southerly right-of-way line of the Central Arizona Project Canal, hereinbefore described, located S 89°59.5' W, 15.275 chs. dist., from the cor. of secs. 14, 15, 22, and 23.
	N 66°48.9' W, in sec. 15, on the southerly right-of-way line of the Central Arizona Project Canal.
3.864	Point for an angle point on the S right-of-way line of the Central Arizona Project Canal, not monumented.
	<hr/> N 23°12.6' E, on the southerly right-of-way line of the Central Arizona Project Canal.
0.758	A brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. 910+93.22 E.O.L. R.O.W. 100+00.00 BOL 125.00 FT. RT. This monument was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.
	<hr/> From the cor. of secs. 15, 16, 21, and 22, hereinbefore described. S 63°52.7' W, in sec. 21, on the southerly right-of-way line of the Central Arizona Project Canal.
12.082	Point for an angle point on the S right-of-way line of the Central Arizona Project Canal, not monumented.
	<hr/> S 26°07.3' E, on the southerly right-of-way line of the Central Arizona Project Canal.
1.515	Point for an angle point on the S right-of-way line of the Central Arizona Project Canal, not monumented.

Metes-and-Bounds Survey, Portions of the S Bdy., Central Arizona
Project Canal, T 3 N, R 6 W, Gila and Salt River Mer., Arizona

CHAINS	
	S 63°52.7' W, on the southerly right-of-way line of the Central Arizona Project Canal.
2.274	Point for an angle point on the S right-of-way line of the Central Arizona Project Canal, not monumented. <hr/>
	N 26°07.3' W, on the southerly right-of-way line of the Central Arizona Project Canal.
1.515	Point for an angle point on the S right-of-way line of the Central Arizona Project Canal, not monumented. <hr/>
	S 63°52.7' W, on the southerly right-of-way line of the Central Arizona Project Canal.
7.151	Point for an angle point on the S right-of-way line of the Central Arizona Project Canal, not monumented. <hr/>
	N 57°41.2' W, on the southerly right-of-way line of the Central Arizona Project Canal.
17.714	The witness point of secs. 16 and 21, on the southerly right-of-way line of the Central Arizona Project Canal, hereinbefore described, located East, 5.765 chs. dist., from the 1/4 sec. cor. of secs. 16 and 21. <hr/>
	From the witness point of secs. 20 and 21, on the southerly right-of-way line of the Central Arizona Project Canal, hereinbefore described, located S 0°01.5' E, 0.880 chs. dist., from the cor. of secs. 16, 17, 20, and 21.
	S 72°21.2' W, in sec. 20, on the southerly right-of-way line of the Central Arizona Project Canal.
9.487	Point for an angle point on the S right-of-way line of the Central Arizona Project Canal, not monumented. <hr/>
	S 17°38.8' E, on the southerly right-of-way line of the Central Arizona Project Canal.
1.515	Point for an angle point on the S right-of-way line of the Central Arizona Project Canal, not monumented. <hr/>

Metes-and-Bounds Survey, Portions of the S Bdy., Central Arizona Project Canal, T 3 N, R 6 W, Gila and Salt River Mer., Arizona

CHAINS	<p>S 72°22.0' W, on the southerly right-of-way line of the Central Arizona Project Canal.</p>
1.515	<p>A rebar, 5/8 in. diam., projecting 6 ins. above ground, with aluminum cap mkd. R.O.W. This monument was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.</p> <p>A steel fence post is set near the cor.</p> <hr/> <p>From the witness point of secs. 19 and 20, on the southerly right-of-way line of the Central Arizona Project Canal, hereinbefore described, located S 0°01.5' E, 6.400 chs. dist., from the cor. of secs. 17, 18, 19, and 20.</p> <p>N 86°57.4' W, in sec. 19, on the southerly right-of-way line of the Central Arizona Project Canal.</p>
16.237	<p>Point for an angle point on the S right-of-way line of the Central Arizona Project Canal, not monumented.</p> <hr/> <p>S 70°31.5' W, on the southerly right-of-way line of the Central Arizona Project Canal.</p>
9.629	<p>A brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. 736+27.13 PC R.O.W. 125.00 FT. RT. This monument was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The land encompassed in this survey is about 9.5 miles northeast of Tonopah, Arizona. Elevations range from about 1,300 to 1,600 feet above sea level.</p> <p>The Central Arizona Project Canal enters the township on the north boundary of section 19 and traverses easterly. Access is provided by the road along the canal and other secondary roads.</p> <p>The terrain is gently rolling with a dense cover of creosote, scattering paloverde and ironwood and medium cacti.</p> <hr/>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Cheryl A. Baier	Surveying Technician
Donald B. McClure	Surveying Technician
Wilmer F. Beyl Jr.	Surveying Aid

CERTIFICATE OF SURVEY

I, Paul L. Reeves, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 9th day of March, 1988, I have dependently resurveyed a portion of the subdivisional lines, and surveyed a metes-and-bounds survey in certain sections of Township 3 North, Range 6 West, of the Gila and Salt River Meridian, in the State of Arizona which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

MAY 04 1988

(Date)

Paul L. Reeves

(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines, and a metes-and-bounds survey in certain sections of Township 3 North, Range 6 West, Gila and Salt River Meridian, Arizona, executed by Paul L. Reeves, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

MAY 09 1988

(Date)

James P. Kelley

(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I Certify that the foregoing transcript of the field notes of the above-described surveys in T 3 N, R 6 W, Gila and Salt River Meridian, Arizona is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~