



INDEX DIAGRAM

TOWNSHIP 22 NORTH, RANGE 8 EAST,

4									
6		5		4	17	3	7	2	1
		36				14			
7	35	8	20	9	10	10	6	11	12
		33				11			
18	31	17	18	16	9	15		14	13
		29							
19		20		21		22		23	24
		28							
30	26	29		28		27		26	25
		22							
31		32		33		34		35	36

- Subdivision Sec. 3    38 - 45
- Subdivision Sec. 8    45 - 48
- Subdivision Sec. 10   48 - 56
- Subdivision Sec. 15   56 - 66
- Subdivision Sec. 17   66 - 70
- Subdivision Sec. 29   70 - 74

T 22 N, R 8 E, Gila and Salt River Mer., Arizona

## CHAINS

The following field notes are those of the dependent resurvey of a portion of the north boundary, a portion of the subdivisional lines, and the subdivision of sections 3, 8, 10, 15, 17, and 29, in Township 22 North, Range 8 East, Gila and Salt River Meridian, Arizona.

The north boundary and the subdivisional lines were surveyed by O. D. Wheeler in 1883. In 1903, James A. Lamport resurveyed the north boundary of the township and the east boundary of sec. 30. Homestead Entry Survey No. 374 was surveyed by Charles D. Hodson and A. W. Hendrix in 1919. The north boundary and Homestead Entry Survey No. 376 were surveyed by R. P. A. Johnson and A. W. Hendrix in 1919. Certain corners were remonumented in 1966, by Wallace R. Ott and in 1972, by Harry K. Smith.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated April 30, 1986, for Group No. 678, Arizona.

Preliminary to the resurvey, the lines of prior surveys were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions ; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of all lines were determined by hour angle observations on the sun and refer to the true meridian. Distances and angles were measured with a Zeiss Elta 46 instrument.

The geographic position of the southeast corner of section 29, as determined from a tie made to U.S. Coast and Geodetic Survey triangulation station "TUFA," located in the SE quarter of section 29, Township 22 North, Range 9 East, is as follows:

NAD 27: Latitude: 35°15'17.60" N Longitude: 111°33'33.53" W

The mean magnetic declination as taken from quadrangle map "SUNSET CRATER EAST, ARIZ.", published in 1966 by U.S. Geological Survey is 14 1/2° E.

---

Dependent Resurvey of a Portion of the N Bdy.,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS

Restoring the resurvey executed by R. P. A. Johnson  
and A. W. Hendrix in 1919

Beginning at the cor. of secs. 2, 3, 34, and 35, on the N bdy. of  
the Tp., determined from the bearing trees mkd. by R. P. A.  
Johnson in 1919

A burned stump, 30 ins. diam., bears N 13 1/4° E,  
338 lks. dist., no marks visible.  
(Record: 318 lks. dist.)

A ponderosa pine, 36 ins. diam., bears N 80 1/2° W,  
238 lks. dist., mkd. with illegible scribe marks visible  
on a cut opened blaze.

A malpais stone, 16 x 14 x 12 ins., mkd. with 4 grooves on the  
W face and 2 grooves on the E face was lying loose on the  
ground. The iron post remonumented by Wallace R. Ott in 1966,  
was found lying on the ground nearby.

At the cor. point

Reset the iron post, 2 1/2 ins. diam., 28 ins. long, 27 ins. in  
the ground, with brass cap mkd.

T23N R8E
S34   S35
-----
S3   S2
T22N
1966

Add the marks 1988 to the brass cap.

and new bearing trees

A ponderosa pine, 18 ins. diam., bears N 27 3/4° E,  
39.5 lks. dist., mkd. T23N R8E S35 BT.

A ponderosa pine, 22 ins. diam., bears S 17° E,  
219.5 lks. dist., mkd. T22N R8E S2 BT.

A ponderosa pine, 7 ins. diam., bears S 72 1/2° W,  
51.5 lks. dist., mkd. T22N R8E S3 BT.

A ponderosa pine, 16 ins. diam., bears N 48 1/2° W,  
101.5 lks. dist., mkd. T23N R8E S34 BT.

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic  
case beneath the stainless steel post.

Dependent Resurvey of a Portion of the N Bdy.,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Bury the malpais stone mkd. in 1919 alongside the iron post.</p> <p>Raise a mound of stone, 3 1/2 ft. base, 2 1/2 ft. high, W of cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>N 89°44 W, bet. secs. 3 and 34.</p> <p>Over rolling land, through medium ponderosa pine.</p> <p>40.67 The 1/4 sec. cor. of secs. 3 and 34, is determined at record bearing and distance from the remains of an original bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine stump, 23 ins. diam., bears N 10° E, 30 lks. dist., mkd. 1/4 S BT.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23N R8E 1/4 <u>S34</u> S3 T22N 1988</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears N 41 3/4° E, 120 lks. dist., mkd. 1/4 S34 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears S 17 3/4° E, 84 lks. dist., mkd. 1/4 S3 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 89°51 W, beginning new measurement.</p>
40.37	<p>The cor. of secs. 3, 4, 33, and 34, monumented with an iron post, 2 1/2 ins. diam., firmly set, 3 ins. below ground surface, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the N Bdy.,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS

T23N R8E	
S33	S34

S4	S3
T22N	
1966	

Add the marks 1988 to the brass cap.

from which the original bearing trees

A ponderosa pine, 26 ins. diam., bears N 81° E, 110 lks. dist., opened blaze to read marks N R8E S34 B.

from which an original bearing tree remarked in 1919

A ponderosa pine, 29 ins. diam., bears S 52 1/2° W, 82.5 lks. dist., marks visible on partially healed blaze; marks visible on second blaze, 2. (1966 Record: S 51° W, 80 lks. dist.)

from which new bearing trees

A ponderosa pine, 21 ins. diam., bears N 83 3/4° E, 187 lks. dist., mkd. T23N R8E S34 BT.

A ponderosa pine, 27 ins. diam., bears N 58° W, 132.5 lks. dist., mkd. T23N R8E S33 BT.

A steel fence post is alongside the cor.

Cor. is located at the N edge of intersection of track roads; roads bear E, S, and W.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

---

Restoring the resurvey executed by R. P. A. Johnson  
and A. W. Hendrix in 1919

---

From the cor. of secs. 10, 11, 14, and 15, described in the field notes of the dependent resurvey of a portion of the subdivisional lines T 22 N, R 8 E, surveyed concurrently under this same group.

N 0°06' W, bet. secs. 10 and 11.

Over nearly level land, through medium ponderosa pine.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
2.50	Dump road, bears N 10° E and S 10° W.
40.56	<p>The 1/4 sec. cor. of secs. 10 and 11, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E 1/4 S10 S11 1966</p> <p>Add the marks 1988 to the brass cap.</p> <p>from which the bearing trees mkd. in 1919</p> <p style="padding-left: 40px;">A ponderosa pine stump, 33 ins. diam., bears N 73° E, 33 lks. dist., mkd. with illegible scribe marks visible on blaze. (Record: N 69° E)</p> <p style="padding-left: 40px;">A ponderosa pine, 27 ins. diam., bears S 68 3/4° W, 69 lks. dist., mkd. with a healed blaze. (Record: S 63 1/2° W)</p> <p>and the bearing tree mkd. in 1966</p> <p style="padding-left: 40px;">A ponderosa pine, 22 ins. diam., bears N 77 1/2° E, 94 lks. dist., mkd. with a healed blaze.</p> <p>and new bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 22 ins. diam., bears S 28 3/4° E, 79.5 lks. dist., mkd. X BT.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N 0°10' W, beginning new measurement.</p> <p>Over level land.</p>
40.59	<p>The cor. of secs. 2, 3, 10, and 11, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E S3   S2 ----- S10 S11 1966</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>from which the bearing tree mkd. in 1919</p> <p style="padding-left: 40px;">A ponderosa pine, 46 ins. diam., bears N 36 1/2° E, 566 lks. dist., mkd. with a healed blaze. (Record: 564 lks. dist.)</p> <p>A mound of stone, is W of cor.</p> <p>A steel fence post is alongside the cor.</p> <hr/> <p>N 0°53' W, bet. secs. 2 and 3.</p> <p>Over nearly level cinder lake.</p> <p>40.58 The 1/4 sec. cor. of secs. 2 and 3, is determined from the remains of the bearing trees mkd. in 1919.</p> <p style="padding-left: 40px;">A decayed stump, bears S 34 1/2° E, 16 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A fallen ponderosa pine stump, bears N 65° W, 20 lks. dist., mkd. 1/4 S3 BT. (Record: N 55 1/2° W)</p> <p>The original lava stone, 14 x 10 x 8 ins. was found buried alongside the cor. point and the 1966 iron post remonumented by Wallace R. Ott was found lying loose, bladed from its original position.</p> <p>At the cor. point</p> <p>Reset the iron post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E 1/4 S3 S2 1966</p> <p>Add the marks 1988 to the brass cap.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears N 72 3/4° E, 72 lks. dist., mkd. 1/4 S2 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears N 14° W, 47.5 lks. dist., mkd. 1/4 S3 BT.</p>
--------	---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Bury the original stone alongside the iron post.</p> <p>Set a steel fence post alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 2°26' E, beginning new measurement.</p>
39.30	<p>The cor. of secs. 2, 3, 34, and 35, on the N bdy. of the Tp., hereinbefore described.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">Restoring the resurvey executed by Charles D. Hodson and A. W. Hendrix in 1919</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of secs. 15, 16, 21, and 22, described in the field notes of the dependent resurvey of a portion of the subdivisional lines T 22 N, R 8 E, surveyed concurrently under this same group.</p> <p>N 1°35' W, bet. secs. 15 and 16.</p>
39.62	<p>Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate dist.; there is no remaining evidence of the original cor. True point falls in the center of N bound lanes of Arizona State Highway 89, impracticable to monument.</p> <p>from which</p> <p style="padding-left: 40px;">An aluminum post, 36 ins. long, 3/4 in. diam., set 32 ins. in the ground, for a reference monument, bears N 47°05' E, 70.8 ft. dist., with cap mkd. T22N R8E S15 RM 70.8 FT. TO COR. 1988, and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An aluminum post, 36 ins. long, 3/4 in. diam., set 31 ins. in the ground, for a reference monument, bears S 61°12' E, 119.0 ft. dist., with cap mkd. T22N R8E S15 RM 119.0. FT. TO COR. 1988, and an arrow pointing to the cor.</p> <p>Reference monuments are located in a N-S right-of-way fence.</p>
59.43	<p>Point for the N 1/16 sec. cor. of secs. 15 and 16. True point falls in the center of N bound lanes of Arizona State Highway 89, impracticable to monument.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>from which</p> <p>An aluminum post, 36 ins. long, 3/4 in. diam., set 33 ins. in the ground, for a reference monument, bears N 49°38' E, 67.9 ft. dist., with cap mkd. T22N R8E S15 RM 67.9 FT. TO COR. 1988, and an arrow pointing to the cor.</p> <p>An aluminum post, 36 ins. long, 3/4 in. diam., set 32 ins. in the ground, for a reference monument, bears S 51°30' E, 69.7 ft. dist., with cap mkd. T22N R8E S15 RM 69.7 FT. TO COR. 1988, and an arrow pointing to the cor.</p> <p>Reference monuments are located in a N-S right-of-way fence.</p>										
79.24	<p>The cor. of secs. 9, 10, 15, and 16, monumented with an aluminum cap, set flush in a concrete cylinder, 8 ins. diam., 4 ins. below the surface of Arizona State Highway 89, mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td colspan="2">ADOT</td> </tr> <tr> <td colspan="2">T22N</td> </tr> <tr> <td colspan="2">R8E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">9</td> <td style="padding: 0 5px;">10</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">16</td> <td style="padding: 0 5px;">15</td> </tr> </table> </div> <p>This is accepted as the best available evidence of the original cor. position.</p> <p>from which</p> <p>An aluminum post, 36 ins. long, 3/4 in. diam., set 33 ins. in the ground, for a reference monument, bears N 49°53' E, 67.5 ft. dist., with cap mkd. T22N R8E S10 RM 67.5 FT. TO COR. 1988, and an arrow pointing to the cor.</p> <p>An aluminum post, 36 ins. long, 3/4 in. diam., set 33 ins. in the ground, for a reference monument, bears S 47°53' E, 72.7 ft. dist., with cap mkd. T22N R8E S15 RM 72.7 FT. TO COR. 1988, and an arrow pointing to the cor.</p> <p>Reference monuments are located in a N-S right-of-way fence.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>N 89°34' W, bet. secs. 10 and 15.</p> <p>Over rolling land, through medium ponderosa pine.</p>	ADOT		T22N		R8E		9	10	16	15
ADOT											
T22N											
R8E											
9	10										
16	15										

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
40.41	<p>The 1/4 sec. cor. of secs. 10 and 15, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E 1/4 S10 S15 1966</p> <p>Add the marks 1988 to the brass cap.</p> <p>from which the original bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 37 ins. diam., bears S 33 1/2° W, 44 lks. dist., mkd. with illegible scribe marks on partially healed blaze. (Record: S 36° W)</p> <p>and the bearing tree mkd. in 1966</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N 72° E, 87 lks. dist., mkd. with illegible scribe marks on partially healed blaze.</p> <p>and new bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears S 31 1/4° E, 40 lks. dist., mkd. 1/4 S15 BT.</p> <p>A steel fence post is alongside the cor.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>S 89°53' W, beginning new measurement.</p>
15.15	<p>Point for the W-E-W 1/256 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S10 W-E-W 1/256 S15 1988</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N 54° E, 79 lks. dist., mkd. W-E-W 1/256 S10 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S 32 1/2° E, 229.5 lks. dist., mkd. X BT.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 8 lks. W of a fence cor.; fences bear S and W.</p> <p>From this cor., a local monument, established by Wilfred P. Hanson, LS 2473, in 1970, a rebar, 1/2 in. diam., firmly set, projecting 1/2 in. above ground, with tag attached and mkd. LS 2473, bears N 83°13' E, 0.085 chs. dist. This cor. is not at the position as shown on his plat and is not utilized in the course of this survey.</p>
<p>20.20</p>	<p>The W 1/16 sec. cor. of secs. 10 and 15, established by Wilfred P. Hanson, LS 2473, monumented with a rebar, 16 ins. long, 1/2 in. diam., projecting 3 ins. above ground with tag attached and mkd. LS 2473. This position is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E W 1/16 <u>S10</u>           <u>S15</u>           1988</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Insert the rebar, inside the stainless steel post.</p> <p>Cor. is located 1 lk. NW of a fence cor.; fences bear N, E, and S.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>S 89°55' W, beginning new measurement</p> <p>Over nearly level grassy field.</p>
<p>20.20</p>	<p>The cor. of secs. 9, 10, 15, and 16.</p> <hr style="width: 80%; margin-left: 0;"/> <p>N 0°17' W, bet. secs. 9 and 10.</p> <p>Over nearly level land, alongside Arizona State Highway 89.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS									
20.19	<p>The S 1/16 sec. cor. of secs. 9 and 10, established by J. B. Holmquist, Registered Civil Engineer, of unknown date, monumented with an aluminum cap 1 1/4 ins. diam., set 12 ins. below the road surface, mkd. 1/16 + 2007. This is accepted as a careful and faithful determination of the cor. position.</p> <p>from which</p> <p>A nail in a power pole, bears N 45°04' E, 49.5 lks. dist.</p> <p>An aluminum post, 36 ins. long, 3/4 in. diam., set 32 ins. in the ground, for a reference monument, bears N 51°31' E, 27.4 ft. dist., with cap mkd. T22N R8E S10 RM 27.4 FT. TO COR. 1988, and an arrow pointing to the cor.</p> <p>From this cor. an aluminum cap, 2 1/2 ins. diam., set flush in concrete abutment, bears S 24° E, 35.05 ft. dist., mkd. ADOT 6721.48.</p> <hr/> <p>N 0°17' W, beginning new measurement.</p>								
20.20	<p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor. True point falls in Arizona State Highway 89 where it is impracticable to monument.</p> <p>from which</p> <p>An aluminum post, 36 ins. long, 3/4 in. diam., set 32 ins. in the ground, for a reference monument, bears N 48°41' E, 110.8 ft. dist., with cap mkd. T22N R8E S10 RM 110.8 FT. TO COR. 1988, and an arrow pointing to the cor.</p> <p>An aluminum post, 36 ins. long, 3/4 in. diam., set 33 ins. in the ground, for a reference monument, bears S 51°10' E, 106.0 ft. dist., with cap mkd. T22N R8E S10 RM 106.0 FT. TO COR. 1988, and an arrow pointing to the cor.</p> <p>Reference monuments are located in a N-S right-of-way fence.</p>								
60.60	<p>The cor. of secs. 3, 4, 9, and 10, monumented with an Arizona Department of Transportation aluminum cap, 3 ins. diam., set in a concrete cylinder, 8 ins. diam., 5 ins. below Arizona State Highway 89, with aluminum cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T22N</td> </tr> <tr> <td colspan="2">R8E</td> </tr> <tr> <td>S4</td> <td>S3</td> </tr> <tr> <td>S9</td> <td>S10</td> </tr> </table> </div>	T22N		R8E		S4	S3	S9	S10
T22N									
R8E									
S4	S3								
S9	S10								

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>This is accepted as the best available evidence of the original cor. position.</p> <p>from which</p> <p>An aluminum cap, 2 1/2 ins. diam., set flush in concrete butment, bears S 26°18' W, 105 lks. dist., mkd. ADOT 6703.09 19.</p> <p>An aluminum cap, 2 1/2 ins. diam., set flush in concrete butment, bears N 21°40' W, 124.5 lks. dist., mkd. ADOT 6703.28 19.</p> <hr/> <p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>N 89°54' W, bet. secs. 3 and 10.</p> <p>40.73 The 1/4 sec. cor. of secs. 3 and 10, is determined at record bearing and distance from the remains of an original bearing tree</p> <p>A pine stump, 23 ins. diam., bears S 15° E, 43 lks. dist., no marks visible.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E 1/4 <u>S3</u> S10 1988</p> <p>from which the bearing trees mkd. in 1919</p> <p>A ponderosa pine, 24 ins. diam., bears N 26 3/4° E, 64 lks. dist., mkd. 1/4 S.</p> <p>A ponderosa pine, 23 ins. diam., bears S 36 1/4° E, 156 lks. dist., mkd. 1/4 S.</p> <p>and bearing trees not of record</p> <p>A ponderosa pine, 24 ins. diam., bears N 83 1/4° E, 110 lks. dist., mkd. S3 1/4 BT.</p> <p>A ponderosa pine, 23 ins. diam., bears S 44 1/4° E, 159 lks. dist., mkd. S10 1/4 BT.</p>
--------	---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>and new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears S 75 3/4° E, 26.5 lks. dist., mkd. 1/4 S3 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears N 9 1/2° W, 216 lks. dist., mkd. 1/4 S10 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>From this cor., an open end pipe, 1 in. diam., firmly set, projecting 8 ins. above ground, in a mound of stone. bears S 44°08' E, 0.424 chs. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S 89°44' W, beginning new measurement.</p>
10.07	<p>Point for the E-W 1/64 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a steel fence post, with brass cap mkd.</p> <p style="text-align: center; padding-left: 100px;">S 3 E-W 1/64 S 10 1988</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears N 86° E, 233 lks. dist., mkd. E-W 1/64 S3 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. falls in a ditch, 10 lks. wide, 2 ft. deep, drains E.</p> <p>Cor. is located 42 lks. N of an E-W fence; 59 lks. W of a N-S fence; and 1.25 chs. W of a trail road, bears N and S.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>From this cor., a local monument, a rebar, 1/2 in. diam., firmly set, projecting 3 ins. above ground, bears S 42°44' E, 0.323 chs. dist. This cor. was established using an improper control cor. and is not utilized in the course of this survey.</p>
20.14	<p>Point for the W 1/16 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E W 1/16 <u>S3</u>           S10 1988</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in a fence, bears N and S, and in a ditch, 10 lks. wide, 5 ft. deep, drains E.</p> <p>From this point, a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with aluminum cap mkd. ARENCO PE 8218 LS 13010, bears S 44°14' E, 0.211 chs. dist.</p> <p>From this same point, a rebar, 1/2 in. diam., firmly set, projecting 4 ins. above ground, bears S 41°42' E, 0.214 chs. dist., .</p> <p style="text-align: center;">These cors. were established using an improper control cor. and are not utilized in the course of this survey.</p>
40.28	<p>The cor. of secs. 3, 4, 9, and 10.</p> <hr/> <p>N 0°10' E, bet. secs. 3 and 4.</p>
20.20	<p>The S 1/16 sec. cor. of secs. 3 and 4, monumented with an aluminum cap 1 1/4 in. diam., 2 ins. below the surface of Arizona State Highway 89, mkd. with an X on top. Origin and date unknown. This position is accepted as a careful and faithful determination of the position of the cor.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>An aluminum post, 36 ins. long, 3/4 in. diam., set 30 ins. in the ground, for a reference monument, bears N 48°06' E, 72.5 ft. dist., with cap mkd. T22N R8E S3 RM 72.5 FT. TO COR. 1988, and an arrow pointing to the cor.</p> <p>An aluminum post, 36 ins. long, 3/4 in. diam., set 30 ins. in the ground, for a reference monument, bears S 47°08' E, 75.3 ft. dist., with cap mkd. T22N R8E S3 RM 75.3. FT. TO COR. 1988, and an arrow pointing to the cor.</p> <p>Reference monuments are located in a N-S right-of-way fence.</p> <p>Cor. is located 6 lks. W of center line of Arizona State Highway 89</p> <hr/> <p>N 0°12' E, beginning new measurement.</p>
20.21	<p>The 1/4 sec. cor. of secs. 3 and 4, identical with cor. 1, H.E.S. 376, monumented with a rebar, 5/8 in. diam., firmly set, 2 ins. below the surface of Arizona State Highway 89. This is accepted as the best available evidence of the original cor. position.</p> <p>from which</p> <p>An aluminum post, 36 ins. long, 3/4 in. diam., set 33 ins. in the ground, for a reference monument, bears N 48°46' E, 71.5 ft. dist., with cap mkd. T22N R8E S3 RM 71.5 FT. TO COR. 1988, and an arrow pointing to the cor.</p> <p>An aluminum post, 36 ins. long, 3/4 in. diam., set 33 ins. in the ground, for a reference monument, bears S 44°53' E, 75.3 ft. dist., with cap mkd. T22N R8E S3 RM 75.3. FT. TO COR. 1988, and an arrow pointing to the cor.</p> <p>Reference monuments are located in a N-S right-of-way fence.</p> <p>Cor. is located 5 lks. W of center line of Arizona State Highway 89.</p> <hr/> <p>N 1°15' E, beginning new measurement.</p>
39.87	<p>The cor. of secs. 3, 4, 33, and 34, on the N bdy. of the Tp., hereinbefore described.</p> <hr/>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Restoring the survey executed by O. D. Wheeler in 1883</p> <hr/> <p>From the cor. of secs. 16, 17, 20, and 21, described in the field notes of the dependent resurvey of a portion of the subdivisional lines T 22 N, R 8 E, surveyed concurrently under this same group.</p> <p>N 1°36' W, bet.secs. 16 and 17.</p>
38.80	<p>The 1/4 sec. cor. of secs. 16 and 17, monumented with a U.S. Department of Agriculture aluminum post, 2 1/2 ins. diam., projecting 5 ins. above ground, in a mound of stone, 2 ft. base, to top., with aluminum cap mkd.</p> <p style="text-align: center;">T22N R8E 1/4 S17 S16 RLS 11369 1983</p> <p>This cor. was reestablished by Arizona Engineering Company, and is accepted as the best available evidence of the original cor. position,</p> <p>Add marks 1988 to the cap.</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears S 31° E, 103 lks. dist., mkd. 1/4 S16 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 5 ins. diam., bears N 78° W, 42 lks. dist., mkd. 1/4 S17 BT.</p> <p>Set a steel fence post alongside the cor.</p> <hr/> <p>N 1°36' W, beginning new measurement.</p>
19.39	<p>The N 1/16 sec. cor. of secs. 16 and 17, monumented with a U.S. Department of Agriculture aluminum post, 2 1/2 ins. diam., projecting 7 ins. above ground, with aluminum cap mkd.</p> <p style="text-align: center;">S S N 1/16 17 16 RLS 11369 1983</p> <p>This cor. was established by Arizona Engineering Company, and is accepted as careful and faithful determination of the cor. position.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Add the marks 1988 to the aluminum cap.</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 17 ins. diam., bears S 49° E, 105.5 lks. dist., mkd. N 1/16 S16 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears S 53 3/4° W, 86.5 lks. dist., mkd. N 1/16 S17 BT.</p> <p>Cor. is located 64.5 lks. dist. N of an E-W fence, and 64.5 lks. dist. E of a N-S fence.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 1°36' W, beginning new measurement.</p> <p>14.55 The N-N-N 1/256 sec. cor. of secs. 16 and 17, established by persons unknown, monumented with a rebar, 18 ins. long, 5/8 in. diam., firmly set but bent, projecting 5 ins. above ground, with an iron rod, set alongside, 24 ins. long, 5/8 in. diam., 8 ins. below surface. Origins and dates are unknown. This is accepted as a careful and faithful determination of the cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>N-N-N 1/256 S17 S16 1988</p> </div> <p>from which new bearing objects</p> <p style="padding-left: 40px;">The SW cor. of a red barn, bears N 62 3/4° E, 68 lks. dist.</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears S 17 3/4° W, 89 lks. dist., mkd. N-N-N 1/256 S17 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Insert the local monuments inside the stainless steel post.</p> <p>Cor. is located alongside a fence cor.; fences bear N and W.</p> <hr style="width: 20%; margin: 10px auto;"/>
--------	---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>N 1°36' W, beginning new measurement.</p>								
4.85	<p>The cor. of secs. 8, 9, 16, and 17, perpetuated by Wilfred P. Hanson, LS 2473, with a rebar, 36 ins. long, 5/8 in. diam., set 18 ins. below surface of graded gravel road, with tag attached and mkd. LS 2473. This cor. was reestablished by C.W. Dryden, PE 971 and RLS 4321, in 1959, and utilized by Dwan Utley, RLS 11369 in 1983, and is accepted as a careful and faithful reestablishment of the position of the original cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 7 ins. below surface of graded road, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T22N R8E</td> </tr> <tr> <td style="text-align: center; border-right: 1px solid black;">S8</td> <td style="text-align: center;">S9</td> </tr> <tr> <td colspan="2" style="text-align: center; border-top: 1px solid black;">S17   S16</td> </tr> <tr> <td colspan="2" style="text-align: center;">1988</td> </tr> </table> <p>from which new bearing objects</p> <p style="padding-left: 40px;">A fence cor., 6 ins. diam., bears East, 151.5 lks. dist., fences bear E and S.</p> <p style="padding-left: 40px;">The NW cor. of Doney Park galvanized steel water shed, bears S 18 1/4° E, 79 lks. dist.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Insert the rebar, inside the stainless steel post.</p> <hr style="border: 0.5px solid black;"/> <p>N 0°10' E, bet. secs. 8 and 9.</p> <p>Through residential area.</p>	T22N R8E		S8	S9	S17   S16		1988	
T22N R8E									
S8	S9								
S17   S16									
1988									
20.26	<p>Point for the S 1/16 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T22N R8E</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 1/16</td> </tr> <tr> <td style="text-align: center; border-right: 1px solid black;">S8</td> <td style="text-align: center;">S9</td> </tr> <tr> <td colspan="2" style="text-align: center;">1988</td> </tr> </table>	T22N R8E		S 1/16		S8	S9	1988	
T22N R8E									
S 1/16									
S8	S9								
1988									

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which a new bearing object</p> <p style="padding-left: 40px;">A power pole, bears S 87° W, 104 lks. dist., mkd. 65 and an aluminum tag mkd. P.S. 102542.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
20.78	Center line of Campbell Ave., bears E and W.
40.52	<p>The 1/4 sec. cor. of secs. 8 and 9, prepruated by persons unknown, monumented with an open end pipe, 1 in. diam., firmly set, projecting 4 ins. above ground, in concrete. This is accepted as the best available evidence of the original cor. position. Not remonumented.</p> <p>from which new bearing objects</p> <p style="padding-left: 40px;">An aluminum post, 24 ins. long, 3/4 ins. diam., set 21 ins. in the ground, for a reference monument, bears N 82°20' W, 34.7 ft. dist., with aluminum cap mkd. T22N R8E S8 RM 34.7 FT. TO COR. 1988, and an arrow pointing to the cor. Set a steel fence post alongside. RM is located 6 lks. dist. N of a fence, bears E and W.</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears N 40° W, 185.5 lks. dist., mkd. 1/4 S8 BT.</p> <p style="padding-left: 40px;">Center of a water meter, bears N 7 3/4° W, 18.5 lks. dist.</p> <p>Cor. is located in cor. of fences; fences bear N, E, S, and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>North, beginning new measurement.</p> <p>Over gently rolling land, through medium ponderosa pine, scattered juniper, pinyon and oak.</p>
40.38	<p>The cor. of secs. 4, 5, 8, and 9, monumented with a sandstone, 22 x 8 x 4 ins., firmly set in concrete, projecting 12 ins. above ground, mkd. with 4 grooves on the E face and 5 grooves on the S face, and a cross on top, from which the remains of the original bearing trees</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS

A dead and down ponderosa pine, 11 ins. diam., bears  
N 58° E, 76 lks. dist., no marks visible.  
(Record: N 60° E, 67 lks. dist.)

A pine snag, 14 ins. diam., bears N 22° W, 85 lks. dist.,  
with illegible scribe marks. (Record: N 30° W, 82 lks.  
dist.)

and a bearing tree not of record

A ponderosa pine, 24 ins. diam., bears N 36° E,  
143 lks. dist., mkd. S4 T22N R8E.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
2 ins. in the ground, to bedrock, and in a mound of stone, 4 ft.  
base, to top, with brass cap mkd.

T22N R8E

S5	S4
----	----

S8	S9
----	----

1988

from which new bearing trees

A ponderosa pine, 12 ins. diam., bears N 22° E,  
55.5 lks. dist., mkd. T22N R8E S4 BT.

A ponderosa pine, 14 ins. diam., bears S 64 1/4° E,  
21 lks. dist., mkd. T22N R8E S9 BT.

A ponderosa pine, 17 ins. diam., bears S 78 3/4° W,  
111.5 lks. dist., mkd. T22N R8E S8 BT.

A ponderosa pine, 15 ins. diam., bears N 60 1/4° W,  
15.5 lks. dist., mkd. T22N R8E S5 BT.

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic  
case beneath the stainless steel post.

Bury the original stone alongside the stainless steel post.

Cor. is located in a cor. of fences; fences bear N, E, and S.

From the cor. of secs. 28, 29, 32, and 33, described in the field  
notes of the dependent resurvey of a portion of the subdivisional  
lines T 22 N, R 8 E, surveyed concurrently under this same group.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>From this cor., U.S. Coast and Geodetic Survey triangulation station "TUFA," bears N 88°30.6 E, (forward bearing), 442.46 chs. dist., monumented with a brass disk, 3 1/2 ins. diam., cemented in a drill hole in a rock outcropping, that projects 3 ft., top is mkd. TUFA 1936 with a triangle in the center.</p> <p>S 89°52' W, bet. secs. 29 and 32.</p> <p>Over nearly level land, through dense undergrowth.</p> <p>14.995 Point for the W-E-E 1/256 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S29 W-E-E 1/256 S32 1988</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears S 85 1/2° W, 246.5 lks. dist., mkd. W-E-E 1/256 S32 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 4 ins. diam., bears N 49° W, 65 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, N of cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 19 lks. E of a trail road, bears N 14° E and S 10° W and 5 lks. N 75° E of a fence cor.; fences bear N, E, and S.</p> <p>19.995 Point for the E 1/16 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E E 1/16 <u>S29</u> S32 1988</p>
--------	--

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A ponderosa pine, 17 ins. diam., bears S 64 1/2° W, 79.5 lks. dist., mkd. E 1/16 S32 BT.</p> <p>A ponderosa pine, 14 ins. diam., bears N 53 3/4° W, 68.5 lks. dist., mkd. E 1/16 S29 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.</p> <p>Set a steel fence post alongside the cor.</p>
39.99	<p>The 1/4 sec. cor. of secs. 29 and 32, monumented with a U. S. Department of Agriculture aluminum post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 2 ft. base, to top. with aluminum cap mkd.</p> <p style="text-align: center;">T22N R8E 1/4 S29 S32 LS 9431 1979</p> <p>This cor. was perpetuated by Wallace R. Ott, Forest Service Cadastral Surveyor; Registered Land Surveyor 9431 in 1979 and is accepted as the best available evidence of the original cor.position.</p> <p>from which the original bearing tree</p> <p>A ponderosa pine, 31 ins. diam., bears N 80° E, 73 lks. dist., mkd. 1/4 on a partially healed blaze.</p> <p>and from which the bearing tree mkd. in 1979</p> <p>A ponderosa pine, 24 ins. diam., bears N 1 1/2° W, 141 lks. dist., mkd. 1/4 S29 BT. (Record: N 1° W)</p> <p>A steel fence post is alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S 86°12' W, beginning new measurement.</p> <p>Ascend gradually over rolling land, through moderate timber and undergrowth.</p>
41.25	<p>Draw, 60 lks. wide, 20 ft. deep, drains S 20° E.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>42.01 The cor. of secs. 29, 30, 31, and 32, monumented with a granite stone, 20 x 18 x 12 ins., mkd. with 5 grooves on the E face, 1 groove on the S face, firmly set, projecting 8 ins. above the ground. with a rebar, 28 ins. long, 3/4 in. diam., projecting 4 ins. above ground, firmly set, alongside. From which the remains of an original bearing tree</p> <p style="padding-left: 40px;">An oak stump, 8 ins. diam., bears S 71° E, 17 lks. dist., no marks visible. (Record: S 72° E, 18 lks. dist.)</p> <p>and from which the remains of the bearing trees mkd. in 1903</p> <p style="padding-left: 40px;">An oak snag, 18 ins. diam., bears N 88° E, 6 lks. dist., mkd. with a healed blaze. (Record: 7 lks. dist.)</p> <p style="padding-left: 40px;">A burned pine stump, 12 ins. diam., bears S 17° W, 117 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A pine snag, 35 ins. diam., bears N 19° W, 66 lks. dist., with scribe marks T22 S30 B visible on partially healed face.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T22N R8E</td> <td style="border-left: 1px solid black; padding: 0 10px;"></td> <td style="padding: 0 10px;"></td> </tr> <tr> <td style="padding: 0 10px;">S30</td> <td style="border-left: 1px solid black; padding: 0 10px; border-bottom: 1px solid black;"></td> <td style="padding: 0 10px;">S29</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="border-left: 1px solid black; padding: 0 10px;"></td> <td style="padding: 0 10px;"></td> </tr> <tr> <td style="padding: 0 10px;">S31</td> <td style="border-left: 1px solid black; padding: 0 10px;"></td> <td style="padding: 0 10px;">S32</td> </tr> <tr> <td colspan="3" style="padding: 0 10px;">1988</td> </tr> </table> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears N 42 1/4° E, 99 lks. dist., mkd. T22N R8E S29 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears S 76° E, 160 lks. dist., mkd. T22N R8E S32 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N 49 1/4° W, 19.5 lks. dist., mkd. T22N R8E S30 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>	T22N R8E			S30		S29				S31		S32	1988		
T22N R8E																
S30		S29														
S31		S32														
1988																

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Deposit the original stone in the mound of stone.</p> <p>Bury the rebar alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>A mound of stone, 2 ft. base, 2 ft. high, is W of cor.</p> <p>Cor. is located 35 lks. E of a trail road, bears N and S.</p> <hr/> <p style="text-align: center;">Restoring the reurvey executed by James A. Lamport in 1903</p> <hr/> <p>N 1°38' E, bet. secs. 29 and 30.</p> <p>Over mountainous land, through moderate timber.</p> <p>40.70 Draw, drains NE.</p> <p>42.20 The 1/4 sec. cor. of secs. 29 and 30, monumented with a sandstone, 18 x 12 x 10 ins., mkd. 1/4 on W face, firmly set 8 ins. in the ground and with an imbedded mound of stone to the W. From which the bearing trees mkd. in 1903</p> <p style="padding-left: 40px;">A stumphole, with fallen pine snag alongside, bears N 24 1/2° E, 45 lks. dist., no marks visible on burned blaze. (Record: 47 lks. dist.)</p> <p style="padding-left: 40px;">A pine stump, 18 ins. diam., bears N 15° W, 58 lks. dist., with illegible scribe marks visible.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E 1/4 S30 S29 1988</p>
--------	---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	and new bearing trees
	A ponderosa pine, 13 ins. diam., bears N 29 1/4° E, 104 lks. dist., mkd. 1/4 S29 BT.
	A white fir, 6 ins. diam., bears S 13 3/4° E, 38 lks. dist., mkd. 1/4 S29 BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Bury the original stone alongside the stainless steel post.
	Set a steel fence post alongside the cor.
	Cor. is located on a ridge, bears E and W.
	_____
	N 1°43' E, beginning new measurement.
	Over rolling land, through burned area.
4.00	Draw, drains E.
6.00	Trail road, bears N 86° E and S 86° E.
13.00	Top of ridge, bears S 76° E and N 76° W.
40.30	Draw, drains NE.
42.78	The cor. of secs. 19, 20, 29, and 30, monumented with a granite stone, 20 x 10 x 8 ins., mkd. with 5 grooves on the N face, 2 notches on the E face, firmly set 13 ins. in the ground. Record is a sandstone with 5 notches on E edge and 2 notches on S edge. From which the remains of an original bearing tree
	An oak snag, 12 ins. diam., bears N 44 3/4° E, 5 lks. dist., with illegible scribe marks visible. (Record: N 40° E)
	and from which the remains of the bearing trees mkd. in 1903
	An alligator juniper snag, 40 ins. diam., bears S 71° E, 108.5 lks. dist., no marks visible on burned out blaze. (Record: 118 lks. dist.)
	An oak snag, 11 ins. diam., bears N 17° W, 58 lks. dist., mkd. with a healed blaze. (Record: 60 lks. dist.)

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px;">T22N R8E</td> <td style="padding: 2px;">S19</td> <td style="padding: 2px;">S20</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 2px;"></td> <td style="border-top: 1px solid black; padding: 2px;"></td> <td style="border-top: 1px solid black; padding: 2px;"></td> </tr> <tr> <td style="padding: 2px;"></td> <td style="padding: 2px;">S30</td> <td style="padding: 2px;">S29</td> </tr> <tr> <td style="padding: 2px;"></td> <td style="padding: 2px;">1988</td> <td style="padding: 2px;"></td> </tr> </table> <p>and from which a new bearing object</p> <p style="padding-left: 40px;">An X BO chiseled on a granite boulder, 20 x 12 x 8 ft. high, bears N 32 1/4° E, 179 lks. dist.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr style="width: 50%; margin: 10px auto;"/> <p style="text-align: center;">Restoring the survey executed by O. D. Wheeler in 1883</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of secs. 20, 21, 28, and 29, described in the field notes of the dependent resurvey of a portion of the subdivisional lines T 22 N, R 8 E, surveyed concurrently under this same group.</p> <p>N 89°52' W, bet. secs. 20 and 29.</p> <p>Over rolling land, through scattered timber.</p> <p>39.85 The 1/4 sec. cor. of secs. 20 and 29, monumented with a U. S. Department of Agriculture aluminum post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, in a mound of stone, 2 ft. base, to top, with aluminum cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px;">USDA FS</td> </tr> <tr> <td style="padding: 2px;">T22N R8E</td> </tr> <tr> <td style="padding: 2px;">1/4 S20</td> </tr> <tr> <td style="padding: 2px;">S29</td> </tr> <tr> <td style="padding: 2px;">LS 9431</td> </tr> <tr> <td style="padding: 2px;">1975</td> </tr> </table>	T22N R8E	S19	S20					S30	S29		1988		USDA FS	T22N R8E	1/4 S20	S29	LS 9431	1975
T22N R8E	S19	S20																	
	S30	S29																	
	1988																		
USDA FS																			
T22N R8E																			
1/4 S20																			
S29																			
LS 9431																			
1975																			

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>from which the remains of the original bearing trees</p> <p>A ponderosa pine stump, 24 ins. diam., bears S 27 3/4° E, 59 lks. dist., with BT visible on burned blaze. (Record: S 10° E)</p> <p>A ponderosa pine snag, 30 ins. diam., bears N 33° W, 33 lks. dist., with illegible scribe marks on burned blaze. (Record: N 30° W)</p> <p>This cor. was set by Wallace R. Ott, Forest Service Cadastral Surveyor; Registered Land Surveyor No. 9431 in 1975 and is accepted as the best available evidence of the original cor. position.</p> <p>and new bearing trees</p> <p>A ponderosa pine, 14 ins. diam., bears N 15 3/4° E, 154.5 lks. dist., mkd. 1/4 S20 BT.</p> <p>An alligator juniper, 13 ins. diam., bears S 80 1/2° W, 156.5 lks. dist., mkd. 1/4 S29 BT.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 38 lks. W of a fence, bears N and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 88°18' W, beginning new measurement.</p> <p>Over rolling land, through burned area.</p> <p>13.55 Power line, bears N 10° E and S 10° W.</p> <p>40.41 The cor. of secs. 19, 20, 29, and 30.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>N 89°53' W, bet. secs. 17 and 20.</p> <p>Over nearly level land, through scattered ponderosa pine and oak.</p> <p>40.02 The 1/4 sec. cor. of secs. 17 and 20, remonumented by Harry K. Smith in 1972, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E 1/4 <u>S17</u> S20 1972</p>
--------	--

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>from which the original bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 31 ins. diam., bears S 79 1/2° E, 42 lks. dist., no marks visible. (1972 Record: S 78° E)</p> <p style="padding-left: 40px;">A ponderosa pine, 26 ins. diam., bears N 65 1/2° W, 16 lks. dist., mkd. with illegible scribe marks on partially healed blaze. (1972 Record: N 69 1/2° W)</p> <p>Add the marks 1988 to the brass cap.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N 17 1/2° E, 148.5 lks. dist., mkd. 1/4 S17 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S 68 1/2° W, 60.5 lks. dist., mkd. 1/4 S20 BT.</p> <p>A mound of stone, 3 ft. base, 2 ft. high, is N of cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 80 lks. S of a small draw, drains S 70° E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 89°56 W, beginning new measurement.</p>										
40.06	<p>The cor. of secs. 17, 18, 19, and 20, remonumented by Harry K. Smith in 1972, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="padding: 0 10px;">T22N R8E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S18</td> <td style="padding: 0 5px;">S17</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; padding: 0 10px;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S19</td> <td style="padding: 0 5px;">S20</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">1972</td> </tr> </table> </div> <p>from which the 1903 bearing trees</p> <p style="padding-left: 40px;">An oak, 13 ins. diam., bears N 85 1/4° E, 133 lks. dist., no marks visible on rotted out blaze. (1972 Record: N 83° E)</p> <p style="padding-left: 40px;">A ponderosa pine stump, 20 ins. diam., bears S 11° E, 110 lks. dist., no marks visible. (1972 Record: S 12° E)</p> <p style="padding-left: 40px;">An oak, 12 ins. diam., bears S 49 3/4° W, 88.5 lks. dist., mkd. with a healed blaze. (1972 Record: S 48° W, 89 lks. dist.)</p>	T22N R8E		S18	S17			S19	S20	1972	
T22N R8E											
S18	S17										
S19	S20										
1972											

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>and 1972 bearing trees</p> <p>A ponderosa pine, 16 ins. diam., bears S 12 1/4° E, 41 lks. dist., mkd. T22N R8E S20 BT. (Record: S 14° E)</p> <p>A ponderosa pine, 11 ins. diam., bears N 56 1/4° W, 23 lks. dist., mkd. T22N R8E S18 BT. (Record: N 58° W)</p> <p>A mound of stone, 2 ft. base, 1 ft. high, is W of cor.</p> <p>Cor. is located N 20° W, 9 lks. dist. from a fence cor.; fences bear N and S 55° E.</p>
	<p>N 1°18' W, bet. secs. 17 and 18.</p>
	<p>Over rolling land, through moderate ponderosa pine and oak.</p>
39.22	<p>Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T22N R8E 1/4 S18 S17 1988</p>
	<p>from which</p>
	<p>A ponderosa pine, 11 ins. diam., bears S 59 1/2° E, 28 lks. dist., mkd. 1/4 S17 BT.</p>
	<p>A ponderosa pine, 11 ins. diam., bears S 46 1/2° W, 20.5 lks. dist., mkd. 1/4 S18 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post alongside the cor.</p>
	<p>Cor. is located 86 lks. dist. W of a fence, bears N and S.</p>
78.44	<p>The cor. of secs. 7, 8, 17, and 18, monumented with a sandstone, 12 x 4 x 4 ins., firmly set, projecting 7 ins. above a mound of stone, 2 1/2 ft. base, 1 ft. high, mkd. with 5 notches on the E edge, 4 notches on the S edge, and a cross on top, from which the 1883 bearing trees</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

## CHAINS

A fallen oak, 8 ins. diam., bears N 70 1/2° E,  
57 lks. dist., no marks visible.  
(Record: N 59° E, 60 lks. dist.)

A pine snag, 17 ins. diam., bears S 46 1/4° E,  
50 lks. dist., with scribe marks T22N R8E S17 BT visible  
on opened blaze. (Record: S 70° E)

The remains of a ponderosa pine, 22 ins. diam., bears  
N 72 3/4° W, 65.5 lks. dist., with illegible scribe marks  
on burnt out blaze. (Record: N 15° W, 59 lks. dist.)

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
23 ins. in the ground, with brass cap mkd.

T22N R8E	
S7	S8
-----	
S18	S17
1988	

from which new bearing trees

A ponderosa pine, 10 ins. diam., bears N 34° E,  
11 lks. dist., mkd. T22N R8E S8 BT.

A ponderosa pine, 12 ins. diam., bears S 50 1/4° E,  
59 lks. dist., mkd. T22N R8E S17 BT.

A ponderosa pine, 9 ins. diam., bears S 33 1/2° W,  
22.5 lks. dist., mkd. T22N R8E S18 BT.

A ponderosa pine, 11 ins. diam., bears N 67° W,  
11.5 lks. dist., mkd. T22N R8E S7 BT.

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic  
case beneath the stainless steel post.

Bury the original stone alongside the stainless steel post.

Set a steel fence post alongside the cor.

Cor. is located 3 lks. W of a fence, bears N and S.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>From the cor. of secs. 8, 9, 16, and 17.</p> <p>N 88°26' W, bet. secs. 8 and 17.</p> <p>Along Paintbrush Rd.</p> <p>1.90 Buried telephone line, bears N and S.</p> <p>19.98 The E 1/16 sec. cor. of secs. 8 and 17, established by Wilfred P. Hanson, RLS 2473, in 1967, monumented with a rebar, 30 ins. long, 5/8 in. diam., set flush with ground, with tag attached and mkd. LS 2473, This is accepted as a careful and faithful determination of the cor. position.</p> <p style="padding-left: 40px;">Alongside is set a rebar, of unknown origin, 18 ins. long, 1/2 in. diam., 6 ins. below ground.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T22N R8E E 1/16 <u>S8</u>           S17 1988</p> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears S 63° W, 267.5 lks. dist., mkd. E 1/16 S17 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 5 ins. diam., bears N 58 1/4° W, 134.5 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Insert both rebars inside the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, N of cor.</p> <p>Cor. is located at the end of Paintbrush Rd., and 1 lk. W of a fence, bears N and S.</p> <p>From this cor. a rebar, 1/2 diam., set 3 ins. below ground, bears N 15° W, 0.013 chs. dist., with a tag attached and mkd. RE 2958.</p> <hr style="width: 20%; margin: 20px auto;"/>
--------	--

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>N 88°26' W, beginning new measurement.</p> <p>Over gently rolling land, through medium ponderosa pine and scattered pinyon.</p> <p>19.97 The 1/4 sec. cor. of secs. 8 and 17, monumented with a spike nail, in a mound of stone, 2 ft. base, 1 ft. high, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine stump, 24 ins. diam., bears S 63 1/2° W, 50 lks. dist., with no marks visible. (Record: S 45° W, 48 lks. dist.)</p> <p style="padding-left: 40px;">The remains of a fallen ponderosa pine, 15 ins. diam., bears N 16 1/4° W, 54 lks. dist., mkd. 1/4 S BT. (Record: N 10° W, 56 lks. dist.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E 1/4 <u>S8</u>           <u>S17</u>           1988</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears N 4° E, 29 lks. dist., mkd. 1/4 S8 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears S 58 3/4° E, 41 lks. dist., mkd. 1/4 S17 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Insert the spike nail inside the stainless steel post.</p> <p>Rebuild a mound of stone, 2 1/2 ft. base, 2 ft. high, N of cor.</p> <p>Set a steel fence post alongside the cor.</p> <hr style="width: 30%; margin-left: auto; margin-right: auto;"/> <p>S 89°51' W, beginning new measurement.</p>
39.77	<p>The cor. of secs. 7, 8, 17, and 18.</p> <hr/>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
40.00	<p>N 0°24' W, bet. secs. 7 and 8.</p> <p>Over gently rolling land, through medium ponderosa pine.</p> <p>The 1/4 sec. cor. of secs. 7 and 8, monumented with the remains of a pine post, 24 ins. long, 4 ins. diam., lying in a mound of stone, 2 ft. base, 1 ft. high, no marks visible on post.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E 1/4 S7 S8 1988</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears N 66 3/4° E, 37 lks. dist., mkd. 1/4 S8 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 17 ins. diam., bears N 66° W, 64 lks. dist., mkd. 1/4 S7 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Bury the remains of the wooden post alongside the stainless steel post.</p> <p>Rebuild a mound of stone, 2 ft. base, 1 1/2 ft. high, W of cor.</p> <p>Cor. is located 45 lks. E of a fence, bears N and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°43' W, beginning new measurement.</p>
39.90	<p>The cor. of secs. 5, 6, 7, and 8, monumented with a sandstone, 15 x 14 x 6 ins., firmly set, projecting 6 ins. above ground, mkd. with 5 grooves on the E face, and 1 notch visible on the S, with a mound of stone, 2 ft. base, 1 ft. high, W, from which an original bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears N 49 1/4° E, 57 lks. dist., with marks N R 8E S visible through partially healed blaze. (Record: N 30° E)</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T22N R8E</td> </tr> <tr> <td style="text-align: center; border-right: 1px solid black;">S6</td> <td style="text-align: center;">S5</td> </tr> <tr> <td colspan="2" style="text-align: center; border-top: 1px solid black;">S7 S8</td> </tr> <tr> <td colspan="2" style="text-align: center;">1988</td> </tr> </table> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 19 ins. diam., bears N 74 1/2° E, 100.5 lks. dist., mkd. T22N R8E S5 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S 11° E, 105 lks. dist., mkd. T22N R8E S8 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears S 36 3/4° W, 36 lks. dist., mkd. T22N R8E S7 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N 56 1/4° W, 90 lks. dist., mkd. T22N R8E S6 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <p>Rebuild mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>Cor. is located 14 lks. E of a fence, bears N and S, and 14 lks. S of a track road, bears E and W.</p> <hr/> <p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>N 89°45' W, bet. secs. 5 and 8.</p> <p>Over gently rolling land, through moderate ponderosa pine and scattered pinyon and alligator juniper.</p> <p>40.30 Point for the 1/4 sec. cor. of secs. 5 and 8, determined at record bearing and distance from the remains of an original bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 34 ins. diam., bears N 19 1/2° W, 24 lks. dist., with marks BT visible.</p>	T22N R8E		S6	S5	S7 S8		1988	
T22N R8E									
S6	S5								
S7 S8									
1988									

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Near cor. point, found a sandstone, 14 x 9 x 6 ins. lying loose on ground, with faint marks on one face of stone.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E 1/4 S5 S8 1988</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears N 36° E, 29 lks. dist., mkd. 1/4 S5 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears S 43 3/4° E, 52 lks. dist., mkd. 1/4 S8 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Bury the stone alongside the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>From this point, a malpais stone, 9 x 3 ins., firmly set, projecting 5 ins. above ground, bears S 30°01' W, 0.542 chs. dist., mkd. 1/4 on S face and in a mound of stone, 1 1/2 ft. base, 1/2 ft. high, with a sandstone 14 x 12 x 9 ins. in the mound, mkd. 1/4 on a face, from which bearing trees of unknown origin mkd. in approximately 1945</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears S 43 3/4° E, 52 lks. dist., mkd. 1/4 S8 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears S 43 3/4° E, 52 lks. dist., mkd. 1/4 S8 BT.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>S 89°45' W, beginning new measurement.</p>
3.30	Power line, bears N and S.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
40.28	The cor. of secs. 5, 6, 7, and 8.
	<hr/> Subdivision Section 3, T 22 N, R 8 E, Gila and Salt River Meridian, Arizona <hr/>
	From the 1/4 sec. cor. of secs. 3 and 10. N 0°43' E, on the N and S center line of sec. 3.
20.16	Point for the center S 1/16 sec. cor. of sec. 3. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd. <div style="text-align: center; margin: 10px 0;">                         T22N R8E                          C                          S 1/16   S 3                          C                          1988                     </div> from which <p style="margin-left: 40px;">A ponderosa pine, 12 ins. diam., bears S 26 3/4° W, 18 lks. dist., mkd. X at breast height and BT at base.</p> <p style="margin-left: 40px;">A ponderosa pine, 16 ins. diam., bears N 30 1/2° W, 131.5 lks. dist., mkd. CS 1/16 S3 BT.</p> Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post. Set a steel fence alongside near the cor.
35.28	Point for the center N-N-S 1/256 sec. cor. of sec. 3. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd. <div style="text-align: center; margin: 10px 0;">                         C                          N-N-S   S3                          1/256                            C                          1988                     </div>

Subdivision Section 3,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears S 80 1/4° E, 80.5 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S 3 1/2° W, 15 lks. dist., mkd. C-N-N-S 1/256 S3 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 46.5 lks. dist., N 17° E, of a fence cor.; fences bear N and W; and 29 lks. W of a trail road, 15 lks. wide, bears N 20° E and S 20° W.</p> <p>From this cor., a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, bears S 45°00' E, 0.052 chs. dist. This cor. was established using an improper control cor. and is not utilized in the course of this survey.</p> <p>40.32 The center 1/4 sec. cor. of sec. 3, identical with Cor. 4, H.E.S. 376, perpetuated by Charles C Doak, LS 4476, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">HES</td> <td style="border-left: 1px solid black; padding: 0 5px;">T22N</td> </tr> <tr> <td style="padding: 0 5px;">376</td> <td style="border-left: 1px solid black; padding: 0 5px;">R8E</td> </tr> <tr> <td style="padding: 0 5px;">LS 4476</td> <td style="border-left: 1px solid black; padding: 0 5px;">4 C 1/4 S3</td> </tr> <tr> <td style="padding: 0 5px;">1968</td> <td style="border-left: 1px solid black;"></td> </tr> </table> </div> <p>This is accepted as the best available evidence of the original cor. position.</p> <p>from which the bearing tree mkd. in 1919</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N 76 3/4° W, 25 lks. dist., mkd. with a healed blaze. (Record: N 78 1/4° W)</p> <p>and from which the bearing tree mkd. in 1968</p> <p style="padding-left: 40px;">A double trunk ponderosa pine, 16 ins. diam., bears N 28 1/2° E, 67.5 lks. dist., mkd. C 1/4 4 HES 376 BT. (Record: N 32° E)</p> <p>Add the marks 1988 to the brass cap.</p> <p>and a new bearing tree</p>	HES	T22N	376	R8E	LS 4476	4 C 1/4 S3	1968	
HES	T22N								
376	R8E								
LS 4476	4 C 1/4 S3								
1968									

Subdivision Section 3,  
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>A ponderosa pine, 24 ins. diam., bears S 72 1/4° E, 165.5 lks. dist., mkd. C 1/4 S3 BT.</p> <p>Two steel fence posts are alongside the cor.</p> <p>Cor. is located in a fence, bears N and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°47' E, beginning new measurement.</p> <p>19.925 The center N 1/16 sec. cor. of sec. 3, identical with Cor. 3 H.E.S. 376, perpetuated by Charles C. Doak, LS 4476, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 10px;">HES</td> <td style="padding: 0 5px;">3</td> <td style="padding: 0 10px;">T22N R8E S3 CN 1/16 LS 4476 1968</td> </tr> <tr> <td style="padding: 0 10px;">376</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;"></td> <td></td> </tr> </table> </div> <p>from which the bearing trees mkd. in 1919</p> <p style="padding-left: 40px;">A rotted pine stump, bears S 79 1/2° E, 152 lks. dist., marks visible on remains of blaze. (Record: S 79°31' E)</p> <p style="padding-left: 40px;">A fallen and rotted ponderosa pine, bears S 22° W, 161.5 lks. dist., no marks visible. (Record: S 21°54' W, 154 lks. dist.)</p> <p>and from which the bearing trees mkd. in 1966</p> <p style="padding-left: 40px;">A ponderosa pine, 22 ins. diam., bears S 71° E, 81 lks. dist., illegible scribe marks visible on partially healed blaze. (Record: S 73° E, 80.5 lks. dist.)</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears N 48 3/4° W, 69 lks. dist., mkd. CN 1/16 HES 376 BT-3. (Record: N 47° W)</p> <p>A steel fence post is alongside the cor.</p> <p>Cor. is located 1 lk. N of a fence cor.; fences bear S and N 63° W, and 23 lks. S of curve in trail road, curves S 10° E and N 60° W.</p>	HES	3	T22N R8E S3 CN 1/16 LS 4476 1968	376		
HES	3	T22N R8E S3 CN 1/16 LS 4476 1968					
376							

Subdivision Section 3,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this point, the cor. of secs. 3, 4, 33, and 34, on the N bdy. of Tp., identical with Cor. 2, H.E.S. 376, bears N 63°40' W, 44.72 chs. dist.</p> <hr/>
	<p>N 0°52' E, beginning new measurement.</p>
19.73	<p>The 1/4 sec. cor. of secs. 3 and 34 on the N bdy. of the Tp., hereinbefore described.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 2 and 3.</p>
	<p>S 89°43.5' W, on the E and W center line of sec. 3.</p>
38.63	<p>Trail road, bears S 12° E and N 12° W.</p>
39.575	<p>The center 1/4 sec. cor. of sec. 3.</p> <hr/>
	<p>S 89°52' W, beginning new measurement.</p>
20.34	<p>The center W 1/16 sec. cor. of sec. 3, established by persons unknown, monumented with a rebar, 24 ins. long, 5/8 in. diam., firmly set, projecting 2 ins. above ground. This is accepted as a careful and faithful determination of the cor. position.</p>
	<p>At the cor. point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T22N R8E C W 1/16 C S 3 1988</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Insert the rebar, inside the stainless steel post.</p>
	<p>Set a steel fence post alongside the cor.</p>
	<p>Cor. is located S 60° W, 12 lks. dist. of a fence cor.; fences bear S and W.</p>
	<p>From this cor., a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, bears S 0°07.6' W, 0.408 chs. dist., in a fence line bears E and W.</p> <hr/>

Subdivision Section 3,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	<p>S 89°53' W, beginning new measurement.</p>
20.33	<p>The 1/4 sec. cor. of secs. 3 and 4.</p> <hr/> <p style="text-align: center;">SW 1/4 of Sec. 3</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 3 and 10.</p> <p>N 0°28' W, on the N and S center line of the SW 1/4 of sec. 3.</p>
20.175	<p>Point for the SW 1/16 sec. cor. of sec. 3 at intersection with the E and W center line of the SW 1/4 of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E SW 1/16 S3 1988</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located in a barbed wire fence, bears N and S.</p>
40.355	<p>The center W 1/16 sec. cor. of sec. 3.</p> <hr/> <p>From the center S 1/16 sec. cor. of sec. 3.</p> <p>S 89°47.5' W, on the E and W center line of the SW 1/4 of sec. 3.</p>
10.12	<p>Point for the center E-SW 1/64 sec. cor. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S3 C-E-SW 1/64 1988</p> <p>from which</p> <p style="text-align: center;">A ponderosa pine, 9 ins. diam., bears N 68° E, 121 lks. dist., mkd. C-E-SW 1/64 S3 BT.</p> <p style="text-align: center;">A ponderosa pine, 9 ins. diam., bears S 23 3/4° E, 229 lks. dist., mkd. X BT.</p>

Subdivision Section 3,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located N 9° W, 62 lks. dist., of a fence cor.; fences bear S and W and 22 lks. E of a broken fence, bears N and S.</p>
20.24	The SW 1/16 sec. cor. of sec. 3.
40.48	The S 1/16 sec. cor. of secs. 3 and 4.
10.085	<hr/> <p>From the center E-SW 1/64 sec. cor. of sec. 3.</p> <p>N 0°36' E, on the N and S center line of the S 1/2 of the NE 1/4 of the SW 1/4 of sec. 3.</p> <p>Point for the NE-SW 1/64 sec. cor. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 3 NE-SW 1/64 1988</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 7 lks. W of a fence, bears N and S.</p> <p>From this point a fence cor., 6 ins. sq., bears N 5 1/2° E, 63 lks. dist., fences bear N, S, and W.</p> <p>From this same point the SW cor. of a wood shed, bears N 73°32' E, 39 lks. dist.</p> <p>From this same point a rebar, 3/8 in. diam., firmly set, projecting 1 in. above ground bears S 54°23' E, 0.091 chs. dist., in a fence line bearing N and S. This cor. was established using an improper control cor. and is not utilized in the course of this survey.</p> <hr style="width: 20%; margin: 10px auto;"/>

Subdivision Section 3,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	
5.07	<p>N 89°50' E, on a portion of the E and W center line of the E 1/2 of the NE 1/4 of the SW 1/4 of sec. 3.</p> <p>Point for the center E-NE-SW 1/256 sec. cor. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 3 C-E-NE-SW 1/256 1988</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears N 48 1/4° E, 134.5 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 22 ins. diam., bears S 84 3/4° E, 250.5 lks. dist., mkd. C-E-NE-SW 1/256 S3 BT.</p> <p style="padding-left: 40px;">The SW cor. of a block house, bears N 66°35' W, 189.5 lks. dist.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N 0°40' E, on a portion of the N and S center line of the NE 1/4 of the NE 1/4 of the SW 1/4 of sec. 3.</p>
5.045	<p>Point for the NE-NE-SW 1/256 sec. cor. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 3 NE-NE-SW 1/256 1988</p> <p>from which</p> <p style="padding-left: 40px;">The SW cor. of a garage, bears N 42°34' E, 88.5 lks. dist.</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears S 66 1/2° E, 245.5 lks. dist., mkd. NE-NE-SW 1/256 S3 BT.</p>

Subdivision Section 3,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 42 lks. S of center line of Leisure Lane, 36 lks. wide, bears N and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 89°50' E, on a portion of the E and W center line of the NE 1/4 of the NE 1/4 of the SW 1/4 of sec. 3.</p>
5.08	<p>The center N-N-S 1/256 sec. cor. of sec. 3.</p> <hr/> <p>From the E-W 1/64 sec. cor. of secs. 3 and 10.</p> <p>N 0°36' E, on the N and S center line of the SE 1/4 of the SW 1/4 of sec. 3.</p>
20.17	<p>The center E-SW 1/64 sec. cor. of sec. 3.</p> <hr/> <p style="text-align: center;">Subdivision Section 8, T 22 N, R 8 E, Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 8 and 17.</p> <p>N 0°11' W, on the N and S center line of sec. 8.</p> <p>Over gently rolling land, through medium ponderosa pine.</p>
19.83	<p>Point for the center S 1/16 sec. cor. of sec. 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E C S 1/16   S 8 C 1988</p>

Subdivision Section 8,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>A ponderosa pine, 9 ins. diam., bears S 16° E, 33.5 lks. dist., mkd. C-S 1/16 S8 BT.</p> <p>A ponderosa pine, 9 ins. diam., bears S 86 1/2° W, 94.5 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, W of cor.</p> <p>Set a steel fence post alongside the cor.</p>
39.66	<p>Point for the center 1/4 sec. cor. of sec. 8 at intersection with the E and W center line of sec. 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E C 1/4 S8 1988</p>
	<p>from which</p> <p>A ponderosa pine, 15 ins. diam., bears S 73° W, 29 lks. dist., mkd. C 1/4 S8 BT.</p> <p>A ponderosa pine, 7 ins. diam., bears N 18 3/4° W, 58.5 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
79.97	<p>The 1/4 sec. cor. of secs. 5 and 8.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 8 and 9.</p> <p>N 89°38' W, on the E and W center line of sec. 8.</p> <p>Over gently rolling land, through medium ponderosa pine.</p>

Subdivision Section 8,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	
20.09	<p>Point for the center E 1/16 sec. cor of sec. 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E C E 1/16 C S 8 1988</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears N 32 1/4° E, 68.5 lks. dist., mkd. C-E 1/16 S8 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears S 67 3/4° W, 41.5 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, N of cor.</p> <p>Cor. is located 7 lks. NE of a fence cor.; fences bear E and S.</p> <p>From this point, a local monument, established by Wilfred P. Hanson, RLS 2473, in 1967, a rebar, 5/8 in. diam., set flush with ground, with a tag attached and mkd. LS 2473, bears S 73°57' W, 0.076 chs. dist. This point was established using improper control corners and is not utilized in the course of this survey.</p>
40.18	The center 1/4 sec. cor. of sec. 8.
80.10	The 1/4 sec. cor. of secs. 7 and 8.
<hr/> <p>SE 1/4 of Sec. 8</p> <hr/>	
20.045	<p>Point for the SE 1/16 sec. cor. of sec. 8, at intersection with the E and W center line of the SE 1/4 of sec.8.</p> <p>From the E 1/16 sec. cor. of secs. 8 and 17.</p> <p>North, on the N and S center line of the SE 1/4 of sec. 8.</p> <p>Over nearly level land, through moderate ponderosa pine.</p>

Subdivision Section 8,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E SE 1/16 S8 1988</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears S 47 1/4° W, 95.5 lks. dist., mkd. SE 1/16 S8 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N 44° W, 120.5 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 3.5 lks. E of a fence, bears N and S.</p> <p>From this point, a lot cor. bears S 1°08' W, 2.676 chs. dist., monumented with a rebar, 1/2 in. diam., firmly set, projecting 3 ins. above ground, with a tag attached and mkd. LS 2473.</p> <p>From this same point, a lot cor. bears N 0°43' W, 3.379 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with a tag attached and mkd. LS 2473.</p>
40.09	The center E 1/16 sec. cor. of sec. 8.
	<hr/> <p>From the S 1/16 sec. cor. of secs. 8 and 9.</p> <p>N 89°02' W, on the E and W center line of the SE 1/4 of sec. 8.</p>
0.30	Center line of Pinon St., bears S.
20.03	The SE 1/16 sec. cor. of sec. 8.
40.06	The center S 1/16 sec. cor. of sec.8.
	<hr/> <p style="text-align: center;">Subdivision Section 10, T 22 N, R 8 E, Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 10 and 15.</p> <p>N 0°22' W, on the N and S center line of sec. 10.</p>

Subdivision Section 10,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	
20.145	<p>Point for the center S 1/16 sec. cor. of sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E C S 1/16   S 10 C 1988</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears N 51° E, 29 lks. dist., mkd. CS 1/16 S10 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears N 37 3/4° W, 49 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
40.29	<p>Point for the center 1/4 sec. cor. of sec. 10 at intersection with the E and W center line of sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E C 1/4 S10 1988</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N 43 1/4° E, 56.5 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears S 6 1/2° E, 69 lks. dist., mkd. C 1/4 S10 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
60.60	<p>Point for the center N 1/16 sec. cor. of sec. 10.</p>

Subdivision Section 10,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E C N 1/16   S 10 C 1988</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N 27° E, 452 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 23 ins. diam., bears S 76 3/4° E, 372.5 lks. dist., mkd. CN 1/16 S10 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 60 lks. W of an abandoned fence, bears N and S.</p>
80.91	<p>The 1/4 sec. cor. of secs. 3 and 10.</p>
	<hr/> <p>From the 1/4 sec. cor. of secs. 10 and 11.</p> <p>N 89°56' W, on the E and W center line of sec. 10.</p>
40.59	<p>The center 1/4 sec. cor. of sec. 10.</p>
45.633	<p>Point for the center E-E-W 1/256 sec. cor of sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S10 C-E-E-W 1/256 1988</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located on the W edge of a track road, bears N 5° E and S 5° W.</p>

Subdivision Section 10,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	<p>60.76 Point for the center W 1/16 sec. cor. of sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E C <u>W 1/16</u> C S 10 1988</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located S 21° E, 21 lks. dist. of a fence cor.; fences bear N and W.</p> <p>From this cor., a rebar, 1/2 in. diam., firmly set, projecting 3 ins. above ground, bears S 87°05' E, 0.059 chs. dist. This cor. was established using an improper control cor. and is not utilized in the course of this survey.</p> <p>A steel fence post is alongside the rebar.</p>
80.93	<p>The 1/4 sec. cor. of secs. 9 and 10.</p> <hr style="width: 50%; margin: 10px auto;"/> <p style="text-align: center;">SW 1/4 of Sec. 10</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the W 1/16 sec. cor. of secs. 10 and 15.</p> <p>N 0°18' W, on the N and S center line of the SW 1/4 of sec. 10.</p>
20.17	<p>Point for the SW 1/16 sec. cor. of sec. 10 at intersection with the E and W center line of the SW 1/4 of sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E SW 1/16 S10 1988</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>

Subdivision Section 10,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located 20 lks. N of a ditch, 15 lks. wide, 6 ft. deep, drains E, and S 25° W, 76 lks. dist., from a fence cor.; fences bear S and W.</p>
	<p>From this cor., a rebar, 1/2 in. diam., firmly set, projecting 4 ins. above ground, with aluminum cap mkd. PE 11712 bears S 83°40' E, 0.036 chs. dist. This cor. was established using an improper control cor. and is not utilized in the course of this survey.</p>
40.34	<p>The center W 1/16 sec. cor. of sec. 10.</p> <hr/>
	<p>From the center S 1/16 sec. cor. of sec. 10. S 89°59' W, on the E and W center line of the SW 1/4 of sec. 10.</p>
15.14	<p>Point for the C-W-E-SW 1/256 sec. cor. of sec. 10.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p>from which</p>
	<p>A ponderosa pine, 22 ins. diam., bears N 74 1/2° E, 216.5 lks. dist., mkd. C-W-E-SW 1/256 S10 BT.</p>
	<p>A ponderosa pine, 8 ins. diam., bears S 46 3/4° E, 124.5 lks. dist., mkd. X BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post alongside the cor.</p>
	<p>Cor. is located on the N bank of a ditch, 15 lks. wide, 6 ft. deep, drains E.</p>
20.185	<p>The SW 1/16 sec. cor. of sec. 10.</p>
40.37	<p>The S 1/16 sec. cor. of secs. 9 and 10.</p> <hr/>
	<p>From the center W-E-SW 1/256 sec. cor of sec. 10.</p>

Subdivision Section 10,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	
	<p>N 0°19' W, on a portion of the N and S center line of the SW 1/4 of the NE 1/4 of the SW 1/4 of sec. 10.</p>
5.04	<p>Point for the SW-NE-SW 1/256 sec. cor. of sec. 10.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S10 SW-NE-SW 1/256 1988</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post alongside the cor.</p>
	<p style="text-align: center;">_____</p> <p>East, on a portion of the E and W center line of the S 1/2 of the NE 1/4 of the SW 1/4 of sec. 10, on mean bearing.</p>
0.50	<p>Track road, bears N 15° E and S 15° W.</p>
9.50	<p>Track road, bears N and S.</p>
10.095	<p>Point for the SE-NE-SW 1/256 sec. cor. of sec. 10.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S10 SE-NE-SW 1/256 1988</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears N 59° E, 249.5 lks. dist., mkd. SE NE SW 1/256 S10 BT.</p>
	<p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears S 46° E, 342.5 lks. dist., mkd. X BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post alongside the cor.</p>

Subdivision Section 10,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located 40 lks. N of a track road, bears N 70° E and S 70° W.</p> <hr/>
	<p>N 0°21' W, on a portion of the N and S center line of the E 1/2 of the NE 1/4 of the SW 1/4 of sec. 10.</p>
15.11	<p>The center E-E-W 1/256 sec. cor. of sec. 10.</p> <hr/>
	<p>From the W-E-W 1/256 sec. cor. of secs. 10 and 15.</p>
	<p>N 0°19' W, on the N and S center line of the SW 1/4 of the SE 1/4 of the SW 1/4 of sec. 10.</p>
10.08	<p>Point for the center W-SE-SW 1/256 sec. cor. of sec. 10.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S10 C-W-SE-SW 1/256 1988</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post alongside the cor.</p> <hr/>
	<p>N 89°56' E, on a portion of the E and W center line of the SE 1/4 of the SW 1/4 of sec. 10.</p>
5.05	<p>Point for the SE-SW 1/64 sec. cor. of sec. 10.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S10 SE-SW 1/64 1988</p>

Subdivision Section 10,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	<p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 31 ins. diam., bears S 52 1/4° E, 403.5 lks. dist., mkd. SE SW 1/64 S10 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N 0°20' W, on a portion of the N and S center line of the SE 1/4 of the SW 1/4 of sec. 10.</p> <p>5.04 Point for the center N-SE-SW 1/256 sec. cor. of sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S10 C-N-SE-SW 1/256 1988</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears N 17 1/2° E, 316.5 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 34 ins. diam., bears N 25 1/4° W, 255 lks. dist., mkd. C-N-SE-SW 1/256 S10 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>S 89°58' W, on a portion of the E and W center line of the NW 1/4 of the SE 1/4 of the SW 1/4 of sec. 10.</p> <p>5.05 Point for the NW-SE-SW 1/256 sec. cor. of sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S10 NW-SE-SW 1/256 1988</p>
--------	--

Subdivision Section 10,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	<p>from which</p> <p>A ponderosa pine, 16 ins. diam., bears N 20 3/4° E, 222 lks. dist., mkd. NW SE SW 1/256 S10 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr/> <p>N 0°20' W, on a portion of the N and S center line of the NW 1/4 of the SE 1/4 of the SW 1/4 of sec. 10.</p> <p>5.04 The center W-E-SW 1/256 sec. cor. of sec. 10.</p> <hr/> <p>Subdivision Section 15, T 22 N, R 8 E, Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 15 and 22, described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T 22 N, R 8 E, surveyed concurrently under this same group.</p> <p>N 1°21' W, on the N and S center line of sec. 15.</p> <p>14.84 Point for the center N-S-S 1/256 sec. cor of sec. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 3 ins. below the ground surface, with brass cap mkd.</p> <p style="text-align: center;">S15 C-N-S-S 1/256 1988</p> <p>from which</p> <p>A ponderosa pine, 11 ins. diam., bears N 18 1/2° E, 46.5 lks. dist., mkd. X BT.</p> <p>A ponderosa pine, 11 ins. diam., bears S 33° E, 197.5 lks. dist., mkd. C-N-S-S 1/256 S15 BT.</p>
--------	--

Subdivision Section 15,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	
19.79	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 43 lks. dist., N 56° W, of a dump road, bears N and W, and 4 lks. S of a fence cor.; fences bear N and W.</p> <p>From this cor., a rebar, set by Wilfred P. Hanson LS 2473, 1/2 in. diam., firmly set, projecting 3 ins. above ground, with tag attached and mkd. LS 2473, bears N 14°27' E, 0.34 chs. dist.</p> <p>The center S 1/16 sec. cor. of sec. 15, identical with Cor. 15, Tract B, H.E.S. 374, monumented with the remains of the the original charred post.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T22N R8E</p> <p>C</p> <p>S1/16   S 15</p> <p>C</p> <p>1988</p> </div> <p>from which the remains of a bearing tree mkd in 1919</p> <p style="padding-left: 40px;">A ponderosa pine stump, 26 ins. diam., bears S 18°E, 42 lks, dist no marks visible on rotted stump</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 23 ins diam., bears N 71 1/2°E, 141 lks. dist., mkd. C-S 1/16 S 15 BT.</p> <p style="padding-left: 40px;">A Ponderosa pine 13 ins. diam., bears s 11 1/4° E, 141 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1x1x2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located in a fence, bears N and S.</p>

Subdivision Section 15,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	<p>From this cor. a rebar, set by Wilfred P. Hanson LS 2473, 1/2 in. diam., firmly set, projecting 2 ins. above ground, with tag attached and mkd. LS 2473, bears N 12°E, 0.042 chs. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 1°19" W, beginning new measurement.</p>
9.51	<p>Point for Cor. 14 Tract B, H.E.S. 374, sec. 15, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T22N R8E TR D   S15 COR14 TR B HES 374 1988</p> </div> <p>Deposit a magnet in a 1 x1 x1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located in a fence, bears N and S.</p>
19.875	<p>The center 1/4 sec. cor. of sec. 15, established by Wilfred P. Hanson LS 2473, monumented with a rebar, 16 ins. long, 1/2 in. diam., firmly set, projecting 2 ins. above ground, with tag attached and mkd. LS 2473. This position is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T22N R8E C 1/4 S15 1988</p> </div>

Subdivision Lines in Section 15,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>A ponderosa pine, 8 ins. diam., bears N 42° E, 94 lks. dist., mkd. C 1/4 S15 BT.</p> <p>A ponderosa pine, 5 ins. diam., bears S 36° E, 153.5 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Bury the local cor. alongside the stainless steel post.</p> <p>Cor. is located in a fence, bears N and S.</p> <hr/> <p>N 1°20' W, beginning new measurement.</p>
4.97	<p>Point for the center S-S-N 1/256 sec. cor. of sec. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>C</p> <p>S-S-N  </p> <p>1/256   S 15</p> <p>C</p> <p>1988</p> </div>
	<p>from which</p> <p>A ponderosa pine, 23 ins. diam., bears N 31 1/4° E, 92.5 lks. dist., mkd. C-S-S-N 1/256 S15 BT.</p> <p>A ponderosa pine, 13 ins. diam., bears S 38 3/4° E, 151.5 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Cor. is located at the cor. of fences, bearing S and W.</p>
19.87	<p>Point for the center N 1/16 sec. cor. of sec. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Subdivision Section 15,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T22N R8E C N 1/16   S 15 C 1988</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears N 34 1/4° E, 23.5 lks. dist., mkd. CN 1/16 S15 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears S 74° E, 18.5 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located on top of prominent knoll.</p> <p>39.74 The 1/4 sec. cor. of secs. 10 and 15.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 14 and 15, described in the field notes of the dependent resurvey of a portion of the subdivisional lines T 22 N, R 8 E, surveyed concurrently under this same group.</p> <p>N 89°48' W, on the E and W center line of sec. 15.</p> <p>Over rolling land, through medium ponderosa pine.</p>
40.13	<p>The center 1/4 sec. cor. of sec. 15.</p> <hr/> <p>N 89°56.5' W, beginning new measurement.</p>
15.09	<p>Point for the center W-E-W 1/256 sec. cor. of sec. 15, identical with Cor. 5 Tract A, H.E.S. 374, at proportionate dist.; there is no remaining evidence of the original cor. Not monumented.</p>
20.12	<p>The center W 1/16 sec. cor. of sec. 15, identical with Cor. 4 Tract A, H.E.S. 374, established by Wilfred P. Hanson, LS 2473, monumented with a rebar, 16 ins. long, 1/2 in. diam., firmly set, flush with the ground surface, in a mound of stone, with tag attached and mkd. LS 2473. This position is accepted as a careful and faithful determination of the position of the cor.</p>

Subdivision Section 15,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E C <u>W 1/16</u> _C S 15 1988</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Insert the rebar inside the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, N of cor.</p> <p>Cor. is located in a fence, bears N and S.</p> <hr/> <p>N 89°54' W, beginning new measurement.</p> <p>20.12 The 1/4 sec. cor. of secs. 15 and 16.</p> <hr/> <p style="text-align: center;">SW 1/4 of Sec. 15</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 15 and 22, described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T 22 N, R 8 E, surveyed concurrently under this same group.</p> <p>N 1°29' W, on a portion of the N and S center line of the SW 1/4 of sec. 15.</p> <p>14.26 Cor. 21, Tract C, H.E.S. 374, monumented with a malpais stone, 24 x 15 x 10 ins., projecting 10 ins. above ground, mkd. 21 HES 374 on S face and a cross on top, and a small stone with a cross beneath the malpais stone.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
---------------	---

Subdivision Section 15,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p>TR D</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">COR 21</td> <td style="padding: 0 5px;">T22N</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">TR C</td> <td style="padding: 0 5px;">S15</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">HES 374</td> <td style="padding: 0 5px;">R8E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">1988</td> </tr> </table>	COR 21	T22N	TR C	S15	HES 374	R8E		1988
COR 21	T22N								
TR C	S15								
HES 374	R8E								
	1988								
	<p>from which the bearing trees mkd. in 1919</p> <p style="padding-left: 40px;">A ponderosa pine, 46 ins. diam., bears N 50 1/2° E, 109 lks. dist., mkd. with a healed blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 22 ins. diam., bears S 12 3/4° E, 60 lks. dist., mkd. with a healed blaze.</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears S 47 1/2° E, 280.5 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <p>Cor. is located in a fence, bears N and S.</p> <p>From this cor., Cor. 18, Tract B, H.E.S. 374, bears N 36°40' E, 76 lks. dist., hereinafter described.</p> <hr/> <p>From the center N-S-S 1/256 sec. cor. of sec. 15.</p> <p>N 89°38' W, on a portion of the E and W center line of the N 1/2 of the SE 1/4 of the SW 1/4 of sec. 15.</p>								
<p>15.015</p>	<p>Cor. 17, Tract B, H.E.S. 374, now identical with NW-SE-SW 1/256 sec. cor. of sec. 15, monumented with a malpais stone, 22 x 12 x 10 ins., projecting 7 ins. above ground, mkd. with 17 HES 374 on the N face and a cross on top.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>								

Subdivision Section 15,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p style="text-align: center;">S15 NW-SE-SW 1/256 1988</p> <p>from which a bearing tree mkd. in 1919</p> <p style="padding-left: 40px;">A ponderosa pine, 28 ins. diam., bears N 87° E, 117 lks. dist., mkd. with a healed blaze. (Record: East)</p> <p>and from which a new bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S 49° E, 151 lks. dist., mkd. NW-SE-SW 1/256 S15 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 6 lks. N of a fence, bears E and W and 49 lks. N of a dump road, bears E and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 89°55' W, beginning new measurement.</p> <p>4.55 Cor. 18, Tract B, H.E.S. 374, monumented with a small stone, 3 x 3 x 2 ins., mkd. with a cross on top.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>COR 18 TR B HES 374</p> <hr style="width: 20%; margin: 5px auto;"/> <p>T22N S15 R8E 1988</p> </div>
---------------	---

Subdivision Section 15,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which the bearing trees mkd. in 1919</p> <p>A ponderosa pine, 46 ins. diam., bears N 78 1/2° E, 39 lks. dist., mkd. with a healed blaze.</p> <p>A pine stump, 32 ins. diam., bears S 15° E, 104 lks. dist., mkd. 18 HES 374.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 8 lks. N of a fence, bears E and W.</p>
	<hr/> <p>NW 1/4 of Sec. 15</p> <hr/>
	<p>From the center W 1/16 sec. cor. of sec. 15.</p> <p>N 1°28' W, on the N and S center line of the NW 1/4 of sec. 15.</p>
19.84	<p>Point for the NW 1/16 sec. cor. of sec. 15 at intersection with the E and W center line of the NW 1/4 of sec. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E NW 1/16 S15 1988</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 1 lk. W of a fence, bears N and S.</p>
39.67	<p>The W 1/16 sec. cor. of secs. 10 and 15.</p>
15.12	<p>From the center N 1/16 sec. cor. of sec. 15.</p> <p>S 89°59' W, on the E and W center line of the NW 1/4 of sec. 15.</p> <p>Point for the center W-E-NW 1/256 sec. cor. of sec. 15.</p>

Subdivision Section 15,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S15 C-W-E-NW 1/256 1988</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 17 ins. diam., bears N 30 3/4° E, 218.5 lks. dist., mkd. C-W-E-NW 1/256 S15 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 17 ins. diam., bears S 64 3/4° E, 187.5 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 11 lks. W of a fence, bears N and S.</p>
20.16	The NW 1/16 sec. cor. of sec. 15.
40.32	The N 1/16 sec. cor. of secs. 15 and 16.
	<hr/> <p>From the center W-E-NW 1/256 sec. cor. of sec. 15.</p> <p>N 1°27' W, on the N and S center line of the W 1/2 of the NE 1/4 of the NW 1/4 of sec. 15.</p>
19.84	The W-E-W 1/256 sec. cor. of secs. 10 and 15.
	<hr/> <p>From the center-S-S-N 1/256 sec. cor. of sec. 15.</p> <p>N 89°58' W, on a portion of the E and W center line of the S 1/2 of the SE 1/4 of the NW 1/4 of sec. 15.</p>

Subdivision Section 15,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	
15.10	<p>The SW-SE-NW 1/256 sec. cor. of sec. 15, established by Wilfred P. Hanson, LS 2473, monumented with a rebar, 16 ins. long, 1/2 in. diam., firmly set, 2 ins. below the ground surface, with tag attached and mkd. LS 2473. This position is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S15 SW-SE-NW 1/256 1988</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Insert the rebar inside the stainless steel post.</p> <p>Cor. is located 2 lks. W of a fence cor.; fences bear N, E, and W.</p> <hr/> <p>N 1°27' W, on a portion of the N and S center line of the W 1/2 of the SE 1/4 of the NW 1/4 of sec. 15.</p>
14.89	<p>The center W-E-NW 1/256 sec. cor. of sec. 15.</p>
	<p style="text-align: center;">Subdivision Section 17, T 22 N, R 8 E, Gila and Salt River Meridian, Arizona</p>
	<p>From the 1/4 sec. cor. of secs. 17 and 20.</p> <p>N 1°31' W, on the N and S center line of sec. 17.</p> <p>Over gently rolling land, through moderate ponderosa pine and scattered oak.</p>
39.00	<p>Point for the center 1/4 sec. cor. of sec. 17, at intersection with the E and W center line of sec. 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Subdivision Section 17,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T22N R8E C 1/4 S17 1988</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears S 2 1/4° W, 79.5 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears S 82 1/2° W, 77 lks. dist., mkd. C 1/4 S17 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, W of cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 29 lks. N of a fence, bears E and W.</p>
58.80	<p>Point for the center N 1/16 sec. cor. of sec. 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E C N 1/16   S 17 C 1988</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears N 32° E, 44 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears S 66 1/4° W, 47 lks. dist., mkd. CN 1/16 S 17 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 1/2 ft. base, 3 ft. high, W of cor.</p> <p>Set a steel fence post alongside the cor.</p>
78.60	<p>The 1/4 sec. cor. of secs. 8 and 17.</p> <hr/>

Subdivision Section 17,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	<p>From the 1/4 sec. cor. of secs. 16 and 17.</p> <p>N 89°35' W, on the E and W center line of sec. 17.</p> <p>Over gently rolling land, through medium ponderosa pine.</p> <p>19.985 Point for the center E 1/16 sec. cor. of sec. 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E C E 1/16 C S 17 1988</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears S 87 1/2° W, 108.5 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears N 3 1/2° W, 71.5 lks. dist., mkd. CE 1/16 S17 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 30 lks. N of a fence, bears E and W.</p> <p>39.97 The center 1/4 sec. cor. of sec. 17.</p> <p>79.90 The 1/4 sec. cor. of secs. 17 and 18.</p> <hr style="width: 50%; margin: 10px auto;"/> <p style="text-align: center;">NE 1/4 of Sec. 17</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the center E 1/16 sec. cor. of sec. 17.</p> <p>N 1°33' W, on the N and S center line of the NE 1/4 of sec. 17.</p> <p>Over gently rolling land, through moderate ponderosa pine and scattered juniper and oak.</p> <p>19.595 Point for the NE 1/16 sec. cor. of sec. 17, at intersection with the E and W center line of the NE 1/4 of sec. 17.</p>
--------	--

Subdivision Section 17,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E NE 1/16 S17 1988</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 5 ins. diam., bears S 83° E, 17 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears S 32 1/2° W, 43.5 lks. dist., mkd. NE 1/16 S17 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>34.29 Point for the center N-N-NE 1/256 sec. cor. of sec. 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S17 C-N-N-NE 1/256 1988</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears S 84 1/4° E, 169 lks. dist., mkd. C-N-N-NE 1/256 S17 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N 3° W, 95 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, W of cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located near a fence cor.; fences bear N and E.</p>
--------	---

Subdivision Section 17,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	
39.19	The E 1/16 sec. cor. of secs. 8 and 17.
	From the N 1/16 sec. cor. of secs. 16 and 17.
	N 89°01' W, on the E and W center line of the NE 1/4 of sec. 17.
	Over gently rolling land, through medium ponderosa pine.
19.98	The NE 1/16 sec. cor. of sec. 17.
21.10	Track road, bears N curving NE and S 15° E.
39.955	The center N 1/16 sec. cor. of sec. 17.
	From the N-N-N 1/256 sec. cor. of secs. 16 and 17.
	N 88°34' W, on the E and W center line of the N 1/2 of the NE 1/4 of the NE 1/4 of sec. 17.
1.90	Buried telephone line, bears N and S.
3.095	A lot cor., monumented with a rebar, 1/2 in. diam., projecting 2 ins. above ground, with a tag attached and mkd. LS 2473.
5.515	A lot cor., monumented with a rebar, 1/2 in. diam., projecting 2 ins. above ground, with a tag attached and mkd. LS 2473.
10.36	A lot cor., monumented with a rebar, 1/2 in. diam., projecting 2 ins. above ground, with a tag attached and mkd. LS 2473.
19.98	The center N-N-NE 1/256 sec. cor. of sec. 17.
	Subdivision Section 29,
	T 22 N, R 8 E, Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 29 and 32.
	N 0°42' E, on the N and S center line of sec. 29.
20.08	Point for the center S 1/16 sec. cor. of sec. 29.

Subdivision Section 29,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E C S 1/16   S 29 C 1988</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears N 60 1/2° E, 15 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears S 2 1/4° W, 29 lks. dist., mkd. CS 1/16 S29 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
20.83	Wash, in a draw, 20 lks. wide, 2 ft. deep, drains N 62° E.
40.16	<p>Point for the center 1/4 sec. cor. of sec. 15 at intersection with the E and W center line of sec. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E C 1/4 S29 1988</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears S 85 3/4° W, 143.5 lks. dist., mkd. C 1/4 S29 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears N 25 1/2° W, 142.5 lks. dist., mkd. C 1/4 S29 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>

Subdivision Section 29,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	
80.98	The 1/4 sec. cor of secs. 20 and 29.
19.41	<p>From the 1/4 sec. cor. of secs. 28 and 29, described in the field notes of the dependent resurvey of a portion of the subdivisional lines T 22 N, R 8 E, surveyed concurrently under this same group.</p> <p>S 88°57' W, on the E and W center line of sec. 29.</p> <p>Point for the center E 1/16 sec. cor of sec. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E C <u>E 1/16</u> C S 29 1988</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears N 57 3/4° E, 134 lks. dist., mkd. CE 1/16 S29 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N 7 1/2° W, 143.5 lks. dist., mkd. CE 1/16 S29 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 1.5 chs. S of a wash, in a draw, 30 lks. wide, 2 ft. deep, drains N 75° E.</p>
38.82	The center 1/4 sec. cor. of sec. 29.
80.02	The 1/4 sec. cor. of secs. 29 and 30.
	<p style="text-align: center;">SE 1/4 of Sec. 29</p> <hr style="width: 20%; margin: auto;"/> <p>From the E 1/16 sec. cor. of secs. 29 and 32.</p> <p>N 0°09' W, on the N and S center line of the SE 1/4 of sec. 29.</p>

Subdivision Section 29,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	
20.24	<p>Point for the SE 1/16 sec. cor. of sec. 29 at intersection with the E and W center line of the SE 1/4 of sec. 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears N 65 1/2° E, 61.5 lks. dist., mkd. SE 1/16 S29 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears S 5 3/4° E, 37 lks. dist., mkd. SE 1/16 S29 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 20 lks. S of a dry wash, 10 lks. wide, drains S 60° W.</p>
40.48	<p>The center E 1/16 sec. cor. of sec. 29.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 28 and 29, described in the field notes of the dependent resurvey of a portion of the subdivisional lines T 22 N, R 8 E, surveyed concurrently under this same group.</p> <p>S 89°25' W, on the E and W center line of the SE 1/4 of sec. 29.</p>
19.705	<p>The SE 1/16 sec. cor. of sec. 29.</p>
39.405	<p>The center S 1/16 sec. cor. of sec. 29.</p> <hr/> <p>From the W-E-E 1/256 sec. cor. of secs. 29 and 32.</p> <p>N 0°22' W, on the N and S center line of the SW 1/4 of the SE 1/4 of the SE 1/4 of sec. 29, on mean bearing.</p>
10.145	<p>Point for the center W-SE-SE 1/256 sec. cor. of sec. 29</p>

Subdivision Section 29,  
T 22 N, R 8 E, Gila and Salt River Meridian, Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S29 C-W-SE-SE 1/256 1988</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N 33 1/4° E, 245 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears N 40 1/2° W, 209 lks. dist., mkd. C-W-SE-SE 1/256 S29 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 15 lks. N of a fence cor.; fences bear E and S; and 91 lks. E of a trail road, bears N 30° E and S 30° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 89°37.5' E, on a portion of the E and W center line of the SE 1/4 of the SE 1/4 of sec. 29, on mean bearing.</p> <p>14.885 The S-S 1/64 sec. cor. of secs. 28 and 29, described in the field notes of the dependent resurvey of a portion of the subdivisional lines T 22 N, R 8 E, surveyed concurrently under this same group.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;"><b>GENERAL DESCRIPTION</b></p> <p>The land encompassed in this survey is located at the NE edge of the corporated limits of the city of Flagstaff, Arizona. Elevations range from about 6,600 ft. to about 7,200 ft. above sea level.</p> <p>The land varies from nearly level to rolling, covered with medium to moderate ponderosa pine, scattered oak and juniper, with numerous open areas.</p> <p>Access is by way of Arizona State Highway 89 and numerous improved and unimproved roads.</p> <p>Magnetic Declination : 14 1/2° E</p> <hr style="width: 80%; margin: 10px auto;"/>
--------	--

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Cheryl A. Baier	Surveying Technician
Donald B. McClure	Surveying Technician
Robert D. Begley	Student Trainee (Land Surveyor)
Wilmer F. Beyl Jr.	Surveying Aid

CERTIFICATE OF SURVEY

I, Paul L. Reeves, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 30th day of April, 1986, and supplemental special instructions dated June 13, 1988, I have dependently resurveyed a portion of the north boundary, a portion of the subdivisional lines, and the subdivision of sections, of Township 22 North, Range 8 East, of the Gila and Salt River Meridian, in the State of Arizona which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Paul L. Reeves is no longer assigned to this office and is not available for signature.

FEB 21 1991

(Date)



(Supervisor, Field Section)


CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Arizona State Office  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the north boundary, a portion of the subdivisional lines, and the subdivision of sections, of Township 22 North, Range 8 East, Gila and Salt River Meridian, Arizona, executed by Paul L. Reeves, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

FEB 28 1991

(Date)



(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I Certify that the foregoing transcript of the field notes of the above-described surveys in T 22 N, R 8 E, Gila and Salt River Meridian, Arizona is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~