

BOOK 5316

1

ORIGINAL

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

R-5316

FIELD NOTES
OF THE

DEPENDENT RESURVEY,

PORTION OF THE SAN RAFAEL DEL VALLE LAND GRANT,

A PORTION OF THE NORTH BOUNDARY,

PORTION OF THE EAST BOUNDARY AND SUBDIVISIONAL LINES

AND

THE SUBDIVISION OF SELECTED SECTIONS,

TOWNSHIP 22 SOUTH, RANGE 21 EAST

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY

Paul L. Reeves,

Cadastral Surveyor,

Under special instructions dated January 13, 1987, approved January 13, 1987
supplemental special instructions dated and approved May 15, 1987 and Memorandum
dated November 27, 1987, which provided for the surveys included under Group Number
688 and assignment instructions dated October 28,, 1987.

Survey commenced November 16, 1987

Survey completed January 14, 1988

INDEX DIAGRAM

TOWNSHIP 22 SOUTH, RANGE 21 EAST,

					10	12
6	5	4	3	2	20	1
						19
7	8	9	10	11	18	12
					24	16
18	17	16	15	22	14	13
				25	22	15
19	20	21	22	20	23	14
						24
30	29	28	27	26		25
31	32	33	34	35		36

SRDV Land Grant, bet. mile post 21 and 23 1/2, Pages 4-9
 Subdivision of Section 12 Pages 25-28
 Subdivision of Section 13 Pages 28-31
 Subdivision of Section 14 Pages 31-34

T.22 S., R.21 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of a dependent resurvey of a portion of the San Rafael del Valle Land Grant, a portion of the north boundary, portion of the east boundary and subdivisional lines and the subdivision of selected sections, Township 22 South, Range 21 East, Gila and Salt River Meridian, Arizona.

In 1879 Salon M. Allis did a preliminary survey of the San Rafael del Valle Land Grant. Philip Contzen surveyed the West, North and South township boundaries in 1901 and the San Rafael del Valle Land Grant in 1902. Alford N. Oliver surveyed the East township boundary in 1911. John F. Hesse and Alford N. Oliver surveyed the subdivisional lines and resurveyed the south boundary of Township 21 South, Range 21 East, in 1911.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, Special Instructions dated January 13, 1987, Supplemental Special Instructions dated May 15, 1987, and Memorandum dated November 27, 1987 for Group No. 688, Arizona.

The directions of lines were determined by direct solar observations and refer to the true meridian. Distances and angles were measured using a Zeiss Elta 46 electronic instrument.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southeast corner of section 13, as determined from a tie made to U.S. Coast and Geodetic Survey triangulation station "JUNIPER 1938", is:

NAD 27: Latitude: 31°30'38.04" N Longitude: 110°09'18.60" W

The magnetic declination as taken from quadrangle map LEWIS SPRINGS, ARIZ., published in 1952 by U.S. Geological Survey, is 12° E.

Dependent Resurvey, Portion of the San Rafael del Valle Land Grant
T. 22 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Restoring the survey executed by Philip Contzen in 1902</p> <hr/> <p>Beginning at mile post 21, monumented with a granite stone, 20 x 12 x 8 ins., firmly set, projecting 1 in. from the ground, mkd. PL on W. face, 21M on N. face and SRDV on E. face.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T22S / SRDV S18 / 21M R22E 1987</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Bury the stone alongside the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, W. of cor.</p> <p>Cor. is located in a fence, bears SE and NW.</p> <p>N. 13°29' W., on mile 22.</p> <p>Over gently rolling land, through dense undergrowth.</p>
3.94	<p>Point for a witness point.</p> <p>Set an aluminum post, 24 ins. long, 3/4 in. diam., 12 ins. in the ground, in a mound of stone, 3 ft. base to top, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>W P T22S / SRDV S18 R22E 1987</p> </div> <p>Cor. is located in a fence, bears SE and NW.</p>
18.23	<p>The closing cor. of secs. 7 and 18, T 22 S, R 22 E, hereinafter described.</p>
31.98	<p>The closing cor. of secs. 7 and 12, T 22 S, Rs. 21 and 22 E, hereinafter described.</p>

Dependent Resurvey, Portion of the San Rafael del Valle Land Grant
T. 22 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.16	<p>The 21 1/2 mile post, monumented with a granite stone, 16 x 10 x 8 ins., firmly set, projecting 4 ins. from the ground, mkd. 21 1/2 M on N. face, SRDV on E. face and PL on W. face.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T22S SRDV S12 \ 21 1/2 M R21E / 1987</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Bury the stone alongside the stainless steel post.</p> <p>Cor. is located in an abandoned fence, bears SE and NW.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 13°28' W., beginning new measurement.</p>
16.065	<p>Point for a witness point.</p> <p>Set an aluminum post, 24 ins. long, 3/4 in. diam., 12 ins. in the ground, in a mound of stone, 2 ft. base to top, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>W P T22S \ SRDV S12 / R21E 1987</p> </div> <p>Set a steel fence post alongside the cor.</p>
19.245	<p>The 1/4 sec. cor. of sec. 12 only, hereinafter described.</p>
22.56	<p>Point for a witness point.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>W P T22S \ SRDV S12 / R21E 1987</p> </div>

Dependent Resurvey, Portion of the San Rafael del Valle Land Grant
T.22 S., R.21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in an abandoned fence, bears SE and NW.</p>
36.89	<p>Point for a witness point.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd.</p>
	<div style="text-align: center;"> <p>W P</p> <p>T22S \ SRDV</p> <p>S12 \</p> <p>R21E \</p> <p>1987</p> </div>
39.84	<p>Set a steel fence post alongside the cor.</p> <p>The N 1/16 sec. cor. of sec. 12 only, hereinafter described.</p>
40.195	<p>Point for mile post 22, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T22S SRDV</p> <p>S12 \ 22M</p> <p>R21E \</p> <p>1987</p> </div>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in an abandoned fence, bears SE and NW.</p>
12.735	<hr/> <p>N. 13°28' W., on mile 23.</p> <p>Over gently rolling land, through dense undergrowth.</p> <p>Point for a witness point.</p> <p>Set an aluminum post, 24 ins. long, 3/4 in. diam., 12 ins. in the ground, in a mound of stone, 3 ft. base to top, with aluminum cap mkd.</p>



Dependent Resurvey, Portion of the San Rafael del Valle Land Grant
T.22 S., R.21 E., Gila and Salt River Meridian, Arizona

CHAINS	<div style="text-align: center; margin-bottom: 20px;"> <p>W P T22S S12 \ SRDV R21E 1987</p> </div> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in an abandoned fence, bears SE and NW.</p> <p>20.235 The closing cor. of secs. 1 and 12, hereinafter described.</p> <p>28.945 Point for a witness point.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 29 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center; margin-bottom: 20px;"> <p>W P T22S S1 \ SRDV R21E 1987</p> </div> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in an abandoned fence, bears SE and NW.</p> <p>40.19 The 22 1/2 mile post, monumented with a granite stone, 21 x 14 x 10 ins., firmly set, projecting 9 ins. from the ground, marks visible, 2 on N. face, SRDV on E. face and PL on top.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-bottom: 20px;"> <p>T22S \ SRDV S1 22 1/2 M R21E 1987</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Bury the stone alongside the stainless steel post.</p>
--------	---

Dependent Resurvey, Portion of the San Rafael del Valle Land Grant
T. 22 S., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located alongside a 4 x 4 in. fence post in an abandoned fence, bears SE and NW.</p>
	<p>N. 13°28' W. beginning new measurement.</p>
18.10	<p>Arizona State Highway 90, bears SE and NW</p>
32.425	<p>Point for a witness point.</p> <p>Set an aluminum post, 24 ins. long, 3/4 in. diam., 10 ins. in the ground, in a mound of stone, 2 ft. base to top, with aluminum cap mkd.</p>
	<div style="text-align: center;"> <p>W P</p> <p>T22S \</p> <p>S1 \ SRDV</p> <p>R21E \</p> <p>1987</p> </div>
	<p>Set a steel fence post alongside the cor.</p>
	<p>Cor. is located in an abandoned fence, bears SE and NW.</p>
40.15	<p>The 23 mile post, monumented with a granite stone, 15 x 8 x 8 ins., firmly set, projecting 9 ins. from the ground, mkd. 23 on N. face, SRDV on E. face and PL on W. face.</p>
	<p>At the cor. point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T22S SRDV</p> <p>S1 \ 23M</p> <p>R21E \</p> <p>1987</p> </div>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Bury the stone alongside the stainless steel post.</p>
	<p>Set a steel fence post alongside the cor.</p>
	<p>The cor. is located in an abandoned fence, bears SE and NW.</p>
	<hr/> <p>N. 13°29' W., on mile 24.</p>

Dependent Resurvey, Portion of the San Rafael del Valle Land Grant
T.22 S., R.21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over gently rolling land, through dense undergrowth.
22.545	Point for the closing cor. of secs. 1 and 36, Tps. 21 and 22 S, R 21 E, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	 <p style="text-align: center;">T21S R21E S36 SRDV CC ———— S1 T22S 1988</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
	Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.
	Cor. is located in an abandoned fence, bears SE and NW and 24 lks. W. of a narrow arroyo 10 ft. deep, drains NW.
24.50	Wash, 75 lks. wide, 10 ft. deep, drains NE.
40.16	The 23 1/2 mile post monumented with a granite stone, 16 x 12 x 9 ins., firmly set, projecting 13 ins. from the ground, illegible marks on N. face, SRDV on E. face and P visible on W. face.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	 <p style="text-align: center;">T21S SRDV S36 23 1/2 M R21E 1988</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
	Bury the stone alongside the stainless steel post.
	Cor. is located in an abandoned fence, bears SE and NW.

Dependent Resurvey, Portion of the N. Bdy.,
T.22 S., R.21 E., Gila and Salt River Meridian, Arizona

CHAINS

Restoring the resurvey executed by John F. Hesse
and Alford N. Oliver in 1911

From the cor. of secs. 35 and 36, monumented with the remains of
a 4 x 4 in. redwood post, loosely set, projecting 12 ins. from
the ground, mkd. with illegible scribe marks.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
25 ins. in the ground, with brass cap mkd.

T21S	R21E
S35	S36

S 1
T22S
1988

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic
case beneath the stainless steel post.

Bury the post alongside the stainless steel post.

Set a steel fence post alongside the cor.

Cor. is located 8 lks. W. of a fence cor.; fences bear N. and W.

S. 89°55' E., on the S. bdy. of sec. 36 only, T.21 S., R.21 E.

Over gently rolling land, through medium to dense undergrowth.

8.30 Point for a witness point.

Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the
ground, with aluminum cap mkd.

W P
T21S R21E
S36

S1
T22S
1988

Dependent Resurvey, Portion of the N. Bdy.,
T.22 S., R.21 E., Gila and Salt River Meridian, Arizona

CHAINS	
34.71	<p>Set a steel fence post alongside the cor.</p> <p>Point for a witness point.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">W P T21S R21E <u>S36</u> S1 T22S 1988</p>
39.51	<p>Set a steel fence post alongside the cor.</p> <p>Point for the 1/4 sec. cor. of sec. 1 only, T.22 S., R. 21 E.. Not monumented.</p>
40.12	<p>Point for the 1/4 sec. cor, of sec. 36 only, T.21 S., R.21 E., determined at record bearing and dist., from an original bearing tree</p> <p style="text-align: center;">A mesquite, 11 ins. diam. bears S 42° W, 32 lks. dist., no marks visible on open blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T21S R21E 1/4 <u>S36</u> T22S 1988</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located at the base of a steep cut bank, 30 lks. W. of a wash, 1 ch. wide, 10 ft. deep, drains NE.</p> <hr style="width: 20%; margin: 10px auto;"/>

Dependent Resurvey, Portion of the N. Bdy.,
T.22 S., R.21 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>N. 88°24' E., beginning new measurement.</p>
4.315	<p>The closing cor. of secs. 1 and 36 on the W. bdy. of the San Rafael del Valle Land Grant, hereinbefore described.</p> <hr/> <p style="text-align: center;">Dependent Resurvey, Portion of the E. Bdy., T.22 S., R.21 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;">Restoring the survey executed by Alford N. Oliver in 1911</p> <hr/> <p>From the cor. of secs. 13, 18, 19, and 24, monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. from the ground, with brass cap mkd. as described in the field note record of the 1911 dependent resurvey of the E. bdy.</p> <p>Not remonumented</p> <p>From this cor. point, U.S.C. & G.S. triangulation station "JUNIPER," bears S. 81°37'40" E., (forward bearing), 951.959 chs. dist., monumented with a brass tablet, 3 ins. diam., set in a sandstone outcrop, with top mkd. JUNIPER 1938, and a triangle in the center.</p> <p>N. 0°02' E., bet. secs. 13 and 18, on the E. bdy. of the Tp.</p> <p>Over gently rolling land, through medium to dense undergrowth.</p>
40.10	<p>The 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. from ground, with brass cap mkd.</p> <p style="text-align: center;">S13 S18 1911</p> <p>Remark the cap to read</p> <p style="text-align: center;">T22S R21E R22E 1/4 S13 S18 1987 1911</p> <p>A iron pipe, 2 in. diam., is set alongside the cor.</p> <hr/> <p>N. 0°04' E., beginning new measurement.</p>

Dependent Resurvey, Portion of the E. Bdy.,
T.22 S., R.21 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>40.10 The cor. of secs. 7, 12, 13, and 18, monumented with an iron post, 3 ins. diam., firmly set, projecting 4 ins. from the ground, with brass cap mkd. as described in the field note record of the 1911 dependent resurvey of the E. bdy. .</p> <p>Not remonumented</p> <p>Cor. is located 1 lk. W. of a fence cor.; fences bear N., E. and W.</p> <p>From this cor. point, the closing cor. established in 1916, bears S. 89°43' E., 3.20 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. from the ground, with brass cap mkd. as described in the official record of the 1916 survey of the subdivisional lines, T.22 S., R.22 E..</p> <p>Add the marks A M 1988 and bury in place.</p> <p>Cor. is located alongside a fence cor.; fences bear SE, W., and NW.</p> <p>From this same cor. point, the closing cor. established for secs. 7 and 18, T.22 S., R.22 E., on the W. bdy. of the San Rafael Del Valle Land Grant, bears S. 89°43' E., 3.21 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T22S S7 SRDV CC— S18 R22E 1988</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>From this cor. point, a witness point on the W. bdy. of the San Rafael del Valle Land Grant, bears S. 13°29' E., 14.29 chs. dist., hereinbefore described.</p> <p>From the same cor. point, the 21 1/2 mile post on the San Rafael del Valle Land Grant, bears N. 13°29' W., 21.93 chs. dist., hereinbefore described.</p> <hr style="width: 60%; margin-left: 0;"/> <p>N. 0°01' E., bet. secs. 7 and 12, on the E. bdy. of the Tp.</p> <p>Over nearly level land, along a fence.</p>
--------	---

Dependent Resurvey, Portion of the E. Bdy.,
T.22 S., R.21 E., Gila and Salt River Meridian, Arizona

CHAINS	
13.36	<p>Point for a closing cor. on the W. bdy. of the San Rafael del Valle Land Grant. Point falls in a fence cor. where it is impractical to establish a permanent monument.</p> <p>from which</p> <p>An aluminum post 24 ins. long 3/4 in. diam., set 18 ins. in the ground, for a reference monument, bears N. 39°48'E., 39.4 ft. dist., with aluminum cap mkd. SRDV RM 39.4 FT. TO COR. 1988, and an arrow pointing to the cor. Set a steel fence post alongside the reference monument.</p> <p>An aluminum post, 24 ins. long 3/4 in. diam., set 17 ins. in the ground, for a reference monument, bears N. 42°28' W., 25.2 ft. dist., with aluminum cap mkd. T22S R21E S12 RM 25.2 FT. TO COR. 1988, and an arrow pointing to the cor. Set a steel fence post alongside the reference monument.</p> <p>Cor. of fences bear SE, S., and abandoned fence NW.</p> <p>From this cor. point, a closing cor. for secs. 7 and 12, established in 1911, bears N. 0°01' E., 0.02 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. from the ground, with brass cap mkd. as described in the field note record of the 1911 dependent resurvey of the E. bdy. Add the marks A M 1988 and bury in place.</p> <p>From this same cor. point, a witness point on the San Rafael del Valle Land Grant, bears S. 13°29'E., 28.04 chs. dist., hereinbefore described.</p> <p>From this same cor. point the 21 1/2 mile post on the San Rafael del Valle Land Grant, bears N. 13°29' W., 8.18 chs. dist., hereinbefore described.</p> <hr/> <p style="text-align: center;">Dependent Resurvey, Portion of the Subdivisional Lines T.22 S., R.21 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;">Restoring the survey executed by John F. Hesse and Alford N. Oliver in 1911</p> <hr/> <p>From the 1/4 sec. cor. of secs. 23 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. from the ground, with brass cap mkd. as described in the field note record of the 1911 survey of the subdivisional lines.</p> <p>Not remonumented</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T.22 S., R.21 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p> <p>40.09</p> <p>40.15</p> <p>40.16</p>	<p>A railroad tie is set alongside the cor.</p> <p>N. 0°05' E., bet. secs. 23 and 24.</p> <p>Over nearly level land, through scattered undergrowth.</p> <p>Point for the cor. of secs. 13, 14, 23, and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T22S R21E</td> </tr> <tr> <td>S14</td> <td>S13</td> </tr> <tr> <td colspan="2"><hr/></td> </tr> <tr> <td>S23</td> <td>S24</td> </tr> <tr> <td colspan="2">1988</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>From this cor. point, a local cor., bears N. 4°29' W., 0.05 chs. dist., monumented with an iron post, 1/2 in. diam., firmly set, projecting 8 ins. from the ground, with a copper cap attached and mkd. 13 14 23 24 J. A. Wilcox 1959. This cor. is not utilized in the course of this survey.</p> <hr/> <p>From the cor. of secs. 13, 18, 19, and and 24 on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°54' W., bet. secs. 13 and 24.</p> <p>Over gently rolling land, through medium to dense undergrowth.</p> <p>The 1/4 sec. cor. of secs. 13 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. from ground, with brass cap mkd. as described in the field note record of the 1911 survey of the subdivisional lines.</p> <p style="padding-left: 40px;">An iron post 2 ins. diam., projecting 4 ft. from the ground is set alongside the cor.</p> <p>Not remonumented</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>S. 89°53' W., beginning new measurement.</p> <p>The cor. of secs. 13, 14, 23, and 24.</p>	T22S R21E		S14	S13	<hr/>		S23	S24	1988	
T22S R21E											
S14	S13										
<hr/>											
S23	S24										
1988											

Dependent Resurvey, Portion of the Subdivisional Lines,
T.22 S., R.21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°04' E., bet. secs. 13 and 14.
	Over gently rolling land, through medium undergrowth.
40.09	The 1/4 sec. cor. of secs. 13 and 14, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. from ground, with brass cap mkd. as described in the field note record of the 1911 survey of the subdivisional lines.
	Not remonumented
	Cor. is located 1 lk. N. of a fence cor.; fences bear N. and W.
	N. 0°02' E., beginning new measurement.
19.90	An arroyo, drains NW.
20.06	Point for the N 1/16 sec. cor. of secs. 13 and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T22S R21E N 1/16 S14 S13 1987
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
	Cor. is located 12 lks. W. of a N. and S. fence.
40.12	The cor. of secs. 11, 12, 13, and 14, monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. from the ground, with brass cap mkd. as described in the field note record of the 1911 survey of the subdivisional lines.
	Not remonumented
	Cor. is located 1 lk. N. of a fence cor.; fences bear N. and E.
	From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described.
	Over nearly level land, through dense undergrowth
	S. 89°57' W., bet. secs. 12 and 13.
4.105	Point for a witness point bet. secs. 12 and 13.

Dependent Resurvey, Portion of the Subdivisional Lines,
T.22 S., R.21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an aluminum post, 24 ins. long, 3/4 in. diam., 12 ins. in the ground, in a mound of stone, 2 ft. base to top, with aluminum cap mkd.</p>
	<p style="text-align: center;">W P T22S R21E <u>S12</u> S13 1987</p>
	<p>Cor. is located in an E. and W. fence.</p>
20.105	<p>Point for the E 1/16 sec. cor. of secs. 12 and 13.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T22S R21E E 1/16 <u>S12</u> S13 1987</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Cor. is located in an E. and W. fence.</p>
40.21	<p>The 1/4 sec. cor. of secs. 12 and 13, monumented with an iron post, 1 in. diam., firmly set, projecting 20 ins. from the ground, in a mound of stone, 2 x 1 ft., with brass cap mkd. as described in the field note record of the 1911 survey of the subdivisional lines.</p>
	<p>Not remonumented</p>
	<p>Cor. is located 5 lks. E. of a fence cor.; fences bear E., SW, and W.</p>
	<p style="text-align: center;">_____</p> <p>S. 89°55' W., beginning new measurement.</p>
2.685	<p>Point for a witness point.</p>
	<p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">W P T22S R21E <u>S12</u> S13 1987</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T.22 S., R.21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Cor. is located in an E. and W. fence.
20.055	<p>Point for the W 1/16 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22S R21E W 1/16 <u>S12</u> S13 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 5 lks. N. of an E. and W. fenceline.</p>
40.11	<p>The cor. of secs. 11, 12, 13, and 14.</p> <hr/> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over rolling land, through dense undergrowth.</p>
14.28	<p>Point for a witness point.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 33 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">W P T22S R21E S11 S12 1987</p>
40.08	<p>Cor. is located 8 lks. E. of a N. and S. fence.</p> <p>The 1/4 sec. cor. of secs. 11 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. from the ground, with brass cap mkd. as described in the field note record of the 1911 survey of the subdivisional lines.</p> <p>Not remonumented</p> <p>Cor. is located 1 lk. E. of a N. and S. fence.</p> <hr/>
40.09	<p>N. 0°02' E., beginning new measurement.</p> <p>The cor. of secs. 1, 2, 11, and 12, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. from the ground, with brass cap mkd. as described in the field note record of the 1911 survey of the subdivisional lines.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T.22 S., R.21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A mound of stone, 2 x 1/2 ft. is set N. of the cor.</p> <p>Not remonumented</p> <p>Cor. is located at a fence cor.; fences bear N., S., and W.</p> <hr/>
40.14	<p>N. 89°58' E., bet. secs. 1 and 12.</p> <p>Over rolling land, through dense undergrowth.</p> <p>The 1/4 sec. cor. of secs. 1 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. from the ground, with brass cap mkd. as described in the field note record of the 1911 survey of the subdivisional lines.</p> <p>Not remonumented</p> <hr/>
24.19	<p>N. 89°59' E., beginning new measurement.</p> <p>Point for a closing cor. on the W. bdy. of the San Rafael del Valle Land Grant.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div data-bbox="787 1163 998 1352" style="text-align: center;"> <p>T22S S1 CC — SRDV S12 R21E 1988</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in an abandoned fence, bears SE and NW.</p> <p>From this cor. point, a closing cor. established in 1911, bears N. 89°59' E., 0.01 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. from the ground, with brass cap mkd. as described in the field note record of the 1911 survey of the subdivisional lines. Add the marks A M 1988 and bury in place.</p> <p>From this same cor. point, a witness point on the W. bdy. of the San Rafael del Valle Land Grant, bears S. 13°28' E., 7.50 chs. dist., hereinbefore described.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T.22 S., R.21 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>From this same cor. point, a witness point on the W. bdy. of the San Rafael del Valle Land Grant, bears N. 13°28' W., 8.71 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>N. 0°05' W., bet. secs. 1 and 2.</p> <p>Over gently rolling land, through dense undergrowth.</p>
40.08	<p>The 1/4 sec. cor. of secs. 1 and 2, monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. from the ground, with brass cap mkd. as described in the field note record of the 1911 survey of the subdivisional lines.</p> <p>Not remonumented</p> <p>Cor. is located in a N. and S. fence.</p> <hr/> <p>North, beginning new measurement.</p>
8.20	<p>Arizona State Highway 90, bears SE and NW.</p>
40.26	<p>A closing cor., established for secs. 1 and 2 with the N. bdy. of the Tp., monumented with a granite stone, 8 x 4 ins., firmly set, flush with ground, mkd. CC on S. face, 1 groove on E. face, 5 grooves on W. face and a cross on top.</p> <p>Not remonumented</p> <p>Cor. is located 3 lks. S. of a fence cor.; fences bear E. and S.</p> <p>From this point, the cor. of secs. 35 and 36, T 21 S, R 21 E, bears East, 0.68 chs. dist., hereinbefore described.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 22 and 23, monumented with an iron post, 1 in. diam., set 2 ins. below asphalt surfaced, with broken off brass cap mkd. as described in the field note record of the 1911 survey of the subdivisional lines..</p> <p>At the cor. point</p> <p>Set a stainless steel post, 8 ins. long, 2 1/2 ins. diam., flush with road surface, with brass cap mkd.</p>
	<p>T22S R21E 1/4 S22 S23 1988</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T.22 S., R.21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Bury the remains of the iron post alongside the stainless steel post.</p> <p>from which</p> <p>An aluminum post, 36 ins. long, 3/4 in. diam., set 32 ins. in the ground for a reference monument, bears S. 59°53' E., 30.1 ft. dist., with aluminum cap mkd. T22S R21E S23 RM 30.1 FT. TO COR. 1988, and an arrow pointing to the cor. Set a steel fence post alongside the reference monument.</p> <p>An aluminum post, 36 ins. long, 3/4 ins. diam., set 30 ins. in the ground for a reference monument, bears S. 61°07' W., 31.9 ft. dist., with aluminum cap mkd. T22S R21E S22 RM 31.9 FT. TO COR. 1988, and an arrow pointing to the cor. Set a steel fence post alongside the reference monument.</p> <p>N. 0°05' E., bet. secs. 22 and 23.</p> <p>Along Moson road.</p>
40.12	<p>The cor. of secs. 14, 15, 22, and 23, monumented with a brass cap, 2 1/2 ins. diam., set flush in concrete, 10 ins. below asphalt surfaced, with top mkd. as described in the field note record of the 1911 survey of the subdivisional lines.</p> <p>Add the marks 1988 to the brass cap.</p> <p>from which</p> <p>An aluminum post, 36 ins. long, 3/4 in. diam., set 30 ins. in the ground for a reference monument, bears N. 33°40' E., 54.2 ft. dist., with aluminum cap mkd. T22S R21E S14 RM 54.2 FT. TO COR. 1988, and an arrow pointing to the cor. Set a steel fence post alongside the reference monument.</p> <p>An aluminum post 36 ins. long, 3/4 in. diam., set 34 ins. in the ground for a reference monument, bears S. 31°02' E., 46.4 ft. dist., with aluminum cap mkd. T22S R21E S23 RM 46.4 FT. TO COR. 1988, and an arrow pointing to the cor. Set a steel fence post alongside the reference monument.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T.22 S., R.21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point a local cor., bears N. 26°47' W., 0.027 chs. dist., monumented with a spike nail, encircled with a washer, mkd. PE 1270. This cor. was established by Clarence S. Wilcox, registered Civil Engineer 1270, in 1972 and is not utilized in the course of this resurvey.</p> <hr/>
40.04	<p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>N. 89°57' W., bet. secs. 14 and 23.</p> <p>Over gently rolling land, through dense undergrowth.</p> <p>The 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. from the ground, with brass cap mkd. as described in the field note record of the 1911 survey of the subdivisional lines.</p> <p>Not remonumented</p> <p>Cor. is located at the cor. of fences extending N., S. and W.</p> <hr/> <p>N. 89°54' W., beginning new measurement.</p>
40.07	<p>The cor. of secs. 14, 15, 22, and 23.</p> <hr/> <p>N. 0°02' E., bet. secs. 14 and 15.</p> <p>Along Moson road.</p>
40.12	<p>The 1/4 sec. cor. of secs. 14 and 15, monumented with a brass cap, 2 ins. diam., set flush in concrete, 8 ins. below surface of Moson road, with top mkd. as described in the field note record of the 1911 survey of the subdivisional lines.</p> <p>Add the marks 1988 to the brass cap.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T.22 S., R.21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>An aluminum post, 36 ins. long, 3/4 in. diam., set 31 ins. in the ground, in a N. and S. fence line, for a reference monument, bears N. 36°14' E., 49.3 ft. dist., with aluminum cap mkd. T22S R21E S14 RM 49.3 FT. TO COR. 1988, and an arrow pointing to the cor.</p> <p>An aluminum post, 36 ins. long, 3/4 in. diam., set 30 ins. in the ground, in a N. and S. fence line, for a reference monument, bears S. 55°16' E., 37.2 ft. dist., with aluminum cap mkd. T22S R21E S14 RM 37.2 FT. TO COR. and an arrow pointing to the cor.</p> <p>From this cor. point, a local cor. bears N. 6°07' W., 0.014 chs. dist., monumented with a rebar, 1/2 in. diam., set flush with surface of Moson road. This cor. was established by Lloyd Eichelberger registered land surveyor, 11845, in 1981 and is not utilized in the course of this resurvey.</p> <p>From this same cor. point, another local cor., bears N. 2°03' W., 0.014 chs. dist., monumented with a P K nail, encircled with a washer, mkd. PE 1270. This cor was established by Clarence S. Wilcox, registered Civil Engineer 1270, in 1972 and is not utilized in the course of this resurvey.</p> <hr/> <p>N. 0°03' E., beginning new measurement.</p>
40.13	<p>The cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 1 in. diam., set flush with surface of Moson road, with brass cap mkd. as described in the field note record of the 1911 survey of the subdivisional lines.</p> <p>Add the marks 1988 to the brass cap.</p> <p>from which</p> <p>An aluminum post, 36 ins. long, 3/4 in. diam., set 31 ins. in the ground for a reference monument, bears N. 51°13' E., 37.4 ft. dist., with aluminum cap mkd. T22S R21E S11 RM 37.4 FT. TO COR. 1988, and an arrow pointing to the cor. Set a steel fence post alongside the reference monument.</p> <p>An aluminum post, 36 ins. long, 3/4 in. diam., set 30 ins. in the ground for a reference monument, bears S. 45°49' E., 41.9 ft. dist., with aluminum cap mkd. T22S R21E S14 RM 41.9 FT. TO COR. 1988, and an arrow pointing to the cor. Set a steel fence post alongside the reference monument.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T.22 S., R.21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>N. 89°46' W., bet. secs. 11 and 14.</p> <p>Over rolling land, through dense undergrowth.</p>
8.07	<p>Point for a witness point.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">W P T22S R21E <u>S11</u> S14 1987</p>
20.035	<p>Set a steel fence post alongside the cor.</p> <p>Point for the E 1/16 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22S R21E E 1/16 <u>S11</u> S14 1987</p>
40.07	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>The 1/4 sec. cor. of secs. 11 and 14, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. from the ground, with brass cap mkd. as described in the field note record of the 1911 survey of the of the subdivisional lines.</p> <p style="text-align: center;">A mound of stone, 2 1/2 x 2 ft. is set N. of the cor.</p> <p>Not remonumented</p> <hr style="width: 30%; margin-left: auto; margin-right: auto;"/> <p>S. 89°58' W., beginning new measurement.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T.22 S., R.21 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.03	<p>The cor. of secs. 10, 11, 14, and 15.</p> <hr/>
	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 89°55' W., bet. secs. 15 and 22.</p> <p>Over nearly level land, along a fence and road.</p>
40.31	<p>The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. from the ground, with brass cap mkd. as described in the field note record of the 1911 survey of the subdivisional lines.</p> <p>Not remonumented</p> <p>Cor. is located in an E. and W. fence line and 45 lks. S. of Lower Ranch Rd., bears E. and W.</p> <hr/>
	<p style="text-align: center;">Subdivision of Selected Sections, T.22 S., R.21 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;">Section 12</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 12 and 13.</p> <p>N. 0°02' E., on the N. and S. center line of sec. 12.</p> <p>Over rolling land, through dense undergrowth.</p>
40.045	<p>Point for the center 1/4 sec. cor. of sec. 12, at intersection with the E. and W. center line of sec. 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22S R21E C 1/4 S12 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
43.595	<p>Point for a witness point.</p>

Subdivision of Selected Sections,
T.22 S., R.21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">W P T22S R21E S12 1987</p>
60.085	<p>Set a steel fence post alongside the cor.</p> <p>Point for the center N 1/16 sec. cor. of sec. 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22S R21E C N 1/16 S12 C 1987</p>
80.125	<p>Set a steel fence post alongside the cor.</p> <p>The 1/4 sec. cor. of secs. 1 and 12.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 11 and 12.</p> <p>N. 89°57' E., on the E. and W. center line of sec. 12.</p> <p>Over nearly level land, through dense undergrowth.</p>
19.305	<p>Point for a witness point.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">W P T22S R21E S12 1988</p>
40.135	<p>Set a steel fence post alongside the cor.</p> <p>The center 1/4 sec. cor. of sec. 12.</p>
73.935	<p>Point for the 1/4 sec. cor. of sec. 12 only, on the W. bdy. of the San Rafael del Valle Land Grant.</p>

Subdivision of Selected Sections,
T.22 S., R.21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T22S 1/4 S12 \ SRDV R21E / 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in an abandoned fence, bears SE and NW.</p> <hr/> <p style="text-align: center;">NE 1/4 of Section 12</p> <hr/> <p>From the center N 1/16 sec. cor. of sec. 12.</p> <p>N. 89°58' E., on the E. and W. center line of the NE 1/4 of sec. 12.</p> <p>Over gently rolling land, through dense undergrowth.</p>
9.03	<p>Point for a witness point.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">W P T22S R21E S12 1987</p> <p>Set a steel fence post alongside the cor.</p>
16.305	<p>Point for a witness point.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">W P T22S R21E S12 1987</p> <p>Set a steel fence post alongside the cor.</p>

Subdivision of Selected Sections,
T.22 S., R.21 E., Gila and Salt River Meridian, Arizona

CHAINS	
28.995	<p>Point for the N 1/16 sec. cor. of sec. 12 on the W. bdy. of the San Rafael del Valle Land Grant.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T22S N 1/16 S12 \ SRDV R21E 1987</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr/> <p style="text-align: center;">Section 13</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 24.</p> <p>N. 0°01' E., on the N. and S. center line of sec. 13.</p> <p>Over rolling land, through dense undergrowth.</p>
40.09	<p>Point for the center 1/4 sec. cor. of sec.13, at the intersection with the E. and W. center line of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T22S R21E C 1/4 S13 1987</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 25 lks. S. of a track road, bears E. and W.</p>

Subdivision of Selected Sections,
T.22 S., R.21 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>From this cor. point, a local cor. bears S. 4°09' W., 0.124 chs. dist., monumented with an iron post, 1 in. diam., projecting 7 ins. from the ground, with a copper cap attached and mkd. INT 1/4 COR SEC 13 J A WILCOX 1959. This cor was established using improper procedures and is not utilized in the course of this survey.</p>
60.15	<p>Point for the center N 1/16 sec. cor. of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T22S R21E C N 1/16 S13 C 1987</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
80.21	<p>The 1/4 sec. cor. of secs. 12 and 13.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the 1/4 sec. cor. of secs. 13 and 18 on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°54' W., on the E. and W. center line of sec. 13.</p> <p>Over nearly level land, through dense undergrowth.</p>
40.17	<p>The center 1/4 sec. cor. of sec. 13.</p>
60.23	<p>Point for the center W 1/16 sec. cor of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T22S R21E C <u>W 1/16</u> C S13 1987</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>

Subdivision of Selected Sections,
T.22 S., R.21 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.29	<p>Set a steel fence post alongside the cor. Cor. is located 40 lks. S. of a track road, bears E. and W. The 1/4 sec. cor. of secs. 13 and 14.</p>
	<hr/> <p>NW 1/4 of Section 13</p> <hr/>
20.06	<p>From the center W 1/16 sec. cor. of sec. 13. N. 0°01' E., on the N. and S. center line of the NW 1/4 of sec. 13. Over nearly level land, through dense undergrowth. Point for the NW 1/16 sec. cor. of sec. 13, at intersection with the E. and W. center line of the NW 1/4 of sec. 13. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22S R21E NW 1/16 S13 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
40.12	<p>Set a steel fence post alongside the cor. The W 1/16 sec. cor. of secs. 12 and 13.</p>
20.055	<p>From the center N 1/16 sec. cor. of sec. 13. S. 89°54' W., on the E. and W. center line of the NW 1/4 of sec. 13. Over rolling land, through dense undergrowth.</p>
38.105	<p>The NW 1/16 sec. cor. of sec. 13. Point for a witness point.</p>

Subdivision of Selected Sections,
T.22 S., R.21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">W P T22S R21E S13 1987</p>
	<p>Set a steel fence post alongside the cor.</p>
40.115	<p>The N 1/16 sec. cor. of secs. 13 and 14.</p> <hr/> <p style="text-align: center;">Section 14</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 14 and 23.</p>
	<p>N. 0°01' E., on the N. and S. center line of sec. 14.</p>
	<p>Over rolling land, through dense undergrowth.</p>
40.12	<p>Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E. and W. center line of sec. 14, from which</p>
	<p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">T22S R21E C 1/4 S14 1988</p>
	<p>A rebar, 1/2 in. diam., projecting 1/2 in. from ground bears N. 23°12' E., 0.008 chs. dist..</p>
	<p>Cor. is located in an E. and W. fence.</p>
60.23	<p>Point for the center N 1/16 sec. cor. of sec. 14.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T22S R21E C N 1/16 S14 C 1988</p>

Subdivision of Selected Sections,
T.22 S., R.21 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.34	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>The 1/4 sec. cor. of secs. 11 and 14.</p>
20.035	<p>From the 1/4 sec. cor. of secs. 13 and 14.</p> <p>N. 89°54' W., on the E. and W. center line of sec. 14.</p> <p>Over rolling land, through dense undergrowth.</p> <p>Point for the center E 1/16 sec. cor. of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22S R21E C <u>E 1/16</u> C S14 1988</p>
40.07	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 140 lks. N. of an E. and W. fence.</p> <p>The center 1/4 sec. cor. of sec. 14.</p>
80.125	<p>The 1/4 sec. cor. of secs. 14 and 15.</p>
	<p style="text-align: center;">NE 1/4 of Section 14</p> <p>From the center E 1/16 sec. cor. of sec. 14.</p> <p>N. 0°01' E., on the N. and S. center line of the NE 1/4 of sec. 14.</p> <p>Over rolling land, through dense undergrowth.</p>

Subdivision of Selected Sections,
T.22 S., R.21 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.085	<p>Point for the NE 1/16 sec. cor. of sec. 14, at intersection with the E. and W. center line of the NE 1/4 of sec. 14.</p> <p>Set an aluminum post, 72 ins. long, 3/4 in. diam., 65 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T22S R21E NE 1/16 S14 1988</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located at the base of steep bank of a wash, 40 lks. wide, 10 ft. deep, drains easterly.</p>
22.085	<p>Point for a witness point on the N. and S.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">W P T22S R21E S14 1988</p> <p>Set a steel fence post alongside the cor.</p>
40.17	<p>The E 1/16 sec. cor. of secs. 11 and 14.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 13 and 14.</p> <p>N. 89°50' W., on the E. and W. center line of the NE 1/4 of sec. 14.</p> <p>Over rolling land, through dense undergrowth.</p>
17.105	<p>Point for a witness point.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">W P T22S R21E S14 1988</p> <p>Set a steel fence post alongside the cor.</p>

T.22 S., R.21 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.035	The NE 1/16 sec. cor. of sec. 14.
40.07	The center N 1/16 sec. cor. of sec. 14.
GENERAL DESCRIPTION	
<p>The land encompassed in this survey is located about 5 miles east of Sierra Vista, Arizona. The elevation ranges from about 4,200 ft. to 4,300 ft. from sea level.</p>	
<p>The land varies from gently rolling to rolling, with broken areas along the washes. The area is drained by these washes in a northeasterly direction into the San Pedro River. The area is covered with dense creosote, cat claw, black brush, love grass and cacti, with ash, cottonwood, willow and mesquite along the washes.</p>	
<p>Access is by way of Arizona State Highway 90, which crosses section 1 in an E and W direction.</p>	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Cheryl A. Baier	Surveying Technician
Donald B. McClure	Surveying Technician
Wilmer F. Beyl, Jr.	Surveying Aid

CERTIFICATE OF SURVEY

I, Paul L. Reeves, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 13th day of January, 1987, I have dependently resurveyed a portion of the San Rafael del Valle land grant, a portion of the north boundary, a portion of the east boundary and subdivisional lines and the subdivisions of selected sections in Township 22 South Range 21 East, of the Gila and Salt River Meridian, in the state of Arizona which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Paul L. Reeves is no longer assigned to this office and is not available for signature.

5 / 7 / 91
(Date)

James R. Werbo
(Field Supervisor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the San Rafael del Valle land grant, a portion of the north boundary, a portion of the east boundary and subdivisional lines and the subdivisions of selected sections in Township 22 South, Range 21 East, Gila and Salt River Meridian, Arizona executed by Paul L. Reeves, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

MAY 9 1991
(Date)

James P. Kelley
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I Certify that the foregoing transcript of the field notes of the above-described surveys in T.22 S., R.21 E., Gila and Salt River Meridian, Arizona is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor of Arizona)~~