

INDEX DIAGRAM

TOWNSHIP 17 NORTH, RANGE 6 EAST,

6	5	4	3	2	1
	4				
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of sec. 5

pp 6-17

T 17 N, R 6 E, Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p>The following field notes are those of the dependent resurvey, portion of the subdivisional lines and subdivision of section 5, Township 17 North, Range 6 East, Gila and Salt River Meridian, Arizona.</p> <p>R. C. Powers surveyed a portion of the subdivisional lines in 1885. W.O. Secor surveyed and resurveyed portions of the subdivisional lines in 1957. Paul L. Reeves resurveyed portions of the subdivisional lines and surveyed the subdivision lines of section 5 in 1984.</p> <p>Survey was performed at the request of the U.S. Forest Service, Coconino National Forest, because of local disturbance of corner monuments and accessories.</p> <p>The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated June 28, 1990, for Group No. 720, Arizona.</p> <p>The direction of lines were determined by hour angle solar observations and refer to the true meridian. Distances and angles were measured using a Lietz Set 4 electronic instrument.</p> <p>Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. All evidence of private surveys was evaluated and considered and was accepted if evidence indicated that the survey was properly executed. The retracement data were thoroughly verified and only the true line field notes are given herein.</p> <p>The geographic position of the southeast corner of section 5, as determined in the 1984 survey, by a tie to U.S. Geological Survey triangulation station "Munds, 1930", located in section 15, T 17 N, R 6 E, is as follows:</p> <p style="padding-left: 40px;">NAD 27: Latitude: 34°52'34.59" N Longitude: 111°44'32.51" W</p> <p>The mean magnetic declination is 14° E.</p>
---------------	--

Dependent Resurvey, Portion of the Subdivisional Lines
T. 17 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Beginning at the W-E 1/64 sec. cor. of secs. 5 and 8, monumented with the magnetic tip from the 1984 monument, firmly set, 24 ins. below the surface of the ground.</p> <p>from which bearing trees of record</p> <p>A piñon, 6 ins. diam., bears N. 50° E., 11 lks. dist., with fragmentary scribe marks visible on opened blaze, remarked W E 1/64 S5 BT.</p> <p>A piñon, 6 ins. diam., bears S. 7° E., 31 lks. dist., mkd. W E 1/64 S8 BT on unhealed blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S5 W E 1/64 S8 1990</p> <p>S. 89°50' W., bet. secs. 5 and 8.</p> <p>Over rolling land through medium juniper, piñon, yew, ash, and oak brush.</p> <p>5.35 The W-W-E 1/256 sec. cor. of secs. 5 and 8, determined from bearing objects and bearing tree</p> <p>A sycamore, 6 ins. diam., bears N. 38° E., 82 lks. dist., with fragmentary scribe marks visible on an opened blaze, remarked X BT (Record:N. 43° E.)</p> <p>A basalt stone, 5 x 4 x 4 ft., bears S. 89° W., 87 lks. dist., with illegible chisel marks. (Record: S. 88° W.)</p> <p>A basalt stone, 2 x 2 x 1/2 ft., bears N. 11° W., 23 lks. dist., with illegible chisel marks. (Record: N. 8° W.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in concrete, in a mound of stone and concrete, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S5 W W E 1/256 S8 1990</p>
--------	--

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 17 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS

from which

A basalt stone, 5 x 4 x 4 ft., same as stone mkd. in 1984,
bears S. 89° W., 82 lks. dist., remarked X BO.

A basalt stone, 2 x 2 x 1/2 ft., same as stone mkd. in 1984,
bears N. 11° W., 24 lks. dist., remarked X BO.

Deposit broken brown glass, and a magnet in a 1 x 1 x 2 5/8 in.
white plastic case beneath the stainless steel post.

Cor. is located approx. 6 lks. from the W. edge of Oak Creek,
120 lks wide, course S. 60° W.

S. 89°53' W., beginning new measurement.

5.37

The 1/4 sec. cor. of secs. 5 and 8, monumented with an iron post,
2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground,
with brass cap mkd.

T17N R6E

1/4 S5
S8

1957

from which a bearing tree mkd. in 1957

An oak, 14 ins. diam., bears S. 63° E., 38 lks. dist.,
with faint illegible scribe marks on unhealed blaze.

Not remonumented.

from which a new bearing tree

An ash, 24 ins. diam., bears S. 19° E., 122 lks. dist., mkd
1/4 S8 BT.

Dependent Resurvey, Portion of the Subdivision of Section 5,
T. 17 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	<p style="text-align: center;">Restoring the survey executed by Paul Reeves in 1984</p> <hr style="width: 20%; margin: auto;"/> <p>From the 1/4 sec. cor. of secs. 5 and 8.</p> <p>N. 2°20' E., on the N. and S. center line of sec. 5.</p> <p>Over rolling land, through medium juniper and oak brush.</p> <p>9.875 The C-S-S. 1/64 sec. cor. of sec. 5, monumented with a aluminum post, 1 in. diam., projecting 16 ins. above the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>C S S 1/64 S 5 C 1984</p> </div> <p>from which bearing trees of record</p> <p style="margin-left: 40px;">A juniper 6 ins. diam., bears N. 9° E., 31 lks. dist., mkd. C S S 1/64 S5 BT. (Record: N. 11° E., 32 lks.)</p> <p style="margin-left: 40px;">A piñon, 6 ins. diam., bears N. 51° W., 28 lks. dist., with faint illegible scribe marks on partly healed blaze.</p> <p>Add the mks. 1990 to the aluminum cap.</p> <p>Cor. is located at the N. side of a flagstone patio, at the toe of a S. slope.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 2°21' E., beginning new measurement.</p> <p>9.875 The C-S 1/16 sec. cor of sec. 5, monumented with a stainless steel post, 2 1/2 ins. diam., projecting 4 ins. above the ground, in a mound of stone, 1 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T17N R6E C S 1/16 S5 C 1984</p> </div>
--------	---

Dependent Resurvey, Portion of the Subdivision of Section 5,
T. 17 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>from which bearing trees of record</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears N. 3 1/2° E., 41 lks. dist., mkd. C S S 1/64 S5 BT.</p> <p style="padding-left: 40px;">A piñon, 4 ins. diam., bears S. 71° W., 29 lks. dist., with faint illegible scribe marks on partly healed blazes. (Record: 30 lks.)</p> <p>Add the mks. 1990 to the brass cap.</p> <p>Set a steel fence post near the cor.</p> <hr/> <p style="text-align: center;">SW 1/4 SE 1/4 Section 5</p> <hr/> <p>From the W-E 1/64 sec. cor of secs. 5 and 8.</p> <p>N. 1°34' E., on the N. and S. center line of the SW 1/4 of the SE 1/4, sec. 5.</p> <p>7.415 Point for the 1/1024 sec. cor. of sec. 5, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in concrete with rebar, with brass cap mkd.</p> <p style="text-align: center;">S5 1/1024 1990</p> <p>from which</p> <p style="padding-left: 40px;">A sycamore, 15 ins. diam., bears N. 15° E., 137 lks. dist., mkd. 1/1024 S5 BT.</p> <p style="padding-left: 40px;">An alder, 11 ins. diam., bears S. 67° E., 16 lks. dist., mkd. 1/1024 S5 BT.</p> <p style="padding-left: 40px;">An ash, 7 ins. diam., bears S. 1° W., 62 lks. dist., mkd. X BT.</p> <p>Deposit broken brown glass, and a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
--------	---

Dependent Resurvey, Portion of the Subdivision of Section 5,
 T. 17 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Cor. is located in sandy soil and blackberry bushes 80 lks. N. of Oak Creek, course SW.</p> <p>9.885 The SW-SE 1/64 sec. cor. of sec. 5, determined from remains of the magnetic poly breakaway base of the 1984 monument, firmly set, 24 ins. below the surface of the ground.</p> <p>from which bearing trees of record</p> <p style="padding-left: 40px;">An ash, 20 ins. diam., bears S. 5° E., 42 lks. dist., with fragmentary scribe marks visible on opened blaze, and remarked SW SE 1/64 S5 BT.</p> <p>At the cor point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stone and concrete, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S5 SW SE 1/64 1990</p> <p>from which new bearing objects</p> <p style="padding-left: 40px;">A basalt stone, 26 x 18 x 23 ins., bears S. 50° E., 19 lks dist., mkd. X BO.</p> <p>Bury remains of magnetic breakaway poly base beneath the stainless steel pipe.</p> <p>Deposit broken brown glass, and a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a angle iron, 2 1/2 x 2 1/2 in., projecting 4 ft. above the ground near the cor.</p> <p>Cor. is located on the crest of a S. facing slope that levels to a garden area to the N.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/>
--------	--

Dependent Resurvey, Portion of the Subdivision of Section 5,
T. 17 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
2.473	<p>N. 1°34' E., beginning new measurement.</p> <p>The 1/1024 sec. cor. of sec. 5, determined from bearing tree and bearing object.</p> <p style="padding-left: 40px;">A piñon, 6 ins. diam., bears N. 38° E., 32 lks. dist., mkd. 1/1024 S5 BT. (Record: N. 40° E)</p> <p style="padding-left: 40px;">The northerly cor. of an unfinished house, exterior trim, bears N. 89° 37' E., 161.2 lks. dist. Unable to determine where measurement was taken to partly constructed house in 1984. (Record: 161.8 lks.)</p> <p>A substantial amount of construction and other local disturbances has removed or affected positions of 1984 accessories, and their position could not be relied upon to determine the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 29 ins. in the ground, in concrete, with brass cap mkd.</p> <p style="text-align: center;">S5 1/1024 1990</p> <p>From which new bearing object</p> <p style="padding-left: 40px;">A power pole, bears N. 70° E., 26 lks. dist. There is evidence that the position of power pole has moved since 1984 to expand driveway. (Record: N. 70 1/2° E., 27.5 lks. dist.)</p> <p>Deposit broken brown glass, and a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, a 1/2 in. rebar, firmly set, projecting 4 ins. above the ground, bears N. 1°39' W., 57.8 lks. dist.</p> <p>Cor. is located in a gravel driveway at the base of a S. slope near an occupied frame house.</p> <hr style="width: 20%; margin: 20px auto;"/>

Dependent Resurvey, Portion of the Subdivision of Section 5,
T. 17 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
7.415	<p>N. 1°34' E., beginning new measurement.</p> <p>The C-W-SE 1/64 sec. cor. of sec. 5, monumented with a stainless steel post, 28 ins. long, projecting 18 ins. above the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S5 C W SE 1/64 1984</p> <p>from which bearing trees of record</p> <p style="padding-left: 40px;">A piñon, 9 ins. diam., bears N. 18° W., 70 lks. dist., with faint illegible scribe marks on partly healed blaze. (Record: N. 13° W., 69 lks.)</p> <p style="padding-left: 40px;">A juniper, 13 ins. diam., bears S. 58° W., 30 lks. dist., on unhealed blaze mkd. C W SE 1/64 BT. (Record: S 62° W.)</p> <p>Add the marks 1990 on the aluminum cap.</p> <hr/> <p>From the C-S-SE 1/64 cor. of sec 5, determined from bearing objects</p> <p style="padding-left: 40px;">A sandstone boulder, 8 x 4 x 4 fl., bears S. 66° E., 44 lks. dist., with illegible chisel marks.</p> <p style="padding-left: 40px;">A sandstone boulder, 10 x 6 x 6 fl., bears S. 60° W., 16 lks. dist., with illegible chisel marks.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S5 C S SE 1/64 1990</p>

Dependent Resurvey, a Portion of the Subdivision of Section 5,
T. 17 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
7.945	<p>from which new bearing objects</p> <p>A sandstone boulder, 8 x 8 x 4 ft., same as in 1984, bears S. 66° E., 44 lks. dist., remarked X BO next to illegible marks.</p> <p>A sandstone boulder, 10 x 6 x 6 ft., same as in 1984, bears S. 60° W., 16 lks. dist., remarked X BO next to illegible marks.</p> <p>A cedar, 15 ins. diam., bears N. 37° W., 54 lks. dist., mkd. C S SE 1/64 BT.</p> <p>Deposit broken brown glass, and a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Cor. is located in a wash, 30 lks. wide, in the bottom of a canyon, drains NW.</p> <p>S. 89°46' W., on the E. and W. center line of the SW 1/4 of the SE 1/4, sec. 5.</p> <p>True point for 1/1024 cor. of sec. 5, determined from bearing tree and remains of the 1984 reference monument.</p> <p>A ponderosa pine, 22 ins. diam., bears S. 43 1/4° E., 126 lks. dist., with healed blaze.</p> <p>The magnetic tip from the 1984 monument, firmly set, 24 ins. below the surface of the ground, in a scattered mound of stone, bears S 69°22' W., 90.7 ft. dist. The 1984 notes indicate that the aluminum cap was erroneously mkd. 90.4 FT.</p> <p>Point falls in Oak Creek, 150 lks. wide, course SW., where it is impractical to establish a permanent monument.</p> <p>from which new accessories</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 69°22' E., 90.7 ft. dist., with brass cap mkd. 1/1024 RM 90.7 FT. 1990, and an arrow pointing to the cor.</p> <p>A sandstone boulder, 36 x 28 x 16 ins., bears S. 67° E, 97.5 lks. dist., mkd. X BO on top face.</p>

Dependent Resurvey, Portion of the Subdivision of Section 5,
T. 17 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit the magnetic tip from the 1984 monument, broken clear glass, and a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <hr/>
2.65	<p>S. 89°46' W., beginning new measurement</p> <p>The SW-SE 1/64 sec. cor. of sec. 5.</p> <hr/>
5.295	<p>S. 89°46' W., beginning a new measurement.</p> <p>Point for the C-W-SW-SE 1/256 sec. cor. of secs. 5, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a mound of stone and concrete, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S5 C W SW SE 1/256 1990</p> <p>Deposit broken brown glass, and a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, a rebar, 5/8 in. diam., projecting 4 ins. above the ground, bears S. 85°51' W., 38.3 lks. dist.</p> <p>From this same cor. point, an open end pipe, 1 in. diam., projecting 3 ins. above the ground, bears N. 56°42' W., 45.8 lks. dist.</p> <p>Cor. is located 5 lks. S. of an old 2 strand barbed wire fence, bears NE and SW.</p> <p>Cor. is located SE. 158 lks. dist. from a power pole, lines extend NE. and SW.</p>
10.59	<p>The C-S-S 1/64 cor. of sec. 5.</p> <hr/>

Dependent Resurvey, Portion of the Subdivision of Section 5,
T. 17 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the true point for the 1/1024 sec. cor of sec. 5, on the E. and W. center line of the SW 1/4 of the SE 1/4 of sec. 5.</p> <p>N. 1°21' E., on the N. and S. center line of the SW 1/4 of the NE 1/4 of the SW 1/4 of the SE 1/4 of sec. 5.</p>
2.47	<p>Point for the 1/1024 cor. of sec. 5, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a mound of stone and concrete, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S5 1/1024 1990</p> <p>from which</p> <p style="padding-left: 40px;">An oak, 5 in. diam., bears N. 28° E., 28 lks. dist., mkd. X BT</p> <p style="padding-left: 40px;">The NE corner, exterior trim, of an unfinished house, bears S. 89° W., 102 lks. dist.</p> <p style="padding-left: 40px;">A juniper, 5 in. diam., bears N. 37° W., 49.5 lks. dist., mkd. X BT.</p> <hr style="width: 30%; margin-left: auto; margin-right: auto;"/>
2.64	<p>S. 89°45' W., on the E. and W. center line of the SW 1/4 of the NE 1/4 of the SW 1/4 of the SE 1/4 of sec. 5.</p> <p>The 1/1024 sec. cor. of sec. 5.</p> <hr/>
	<p>From the W-W-E 1/256 sec. cor. of secs. 5 and 8.</p> <p>N. 1°43' E., on the N. and S. center line of the SW 1/4 of the SW 1/4 of the SE 1/4, sec. 5.</p>
2.47	<p>The 1/1024 cor. of sec. 5, determined from a record tie to a local survey cor.</p> <p style="padding-left: 40px;">An open end pipe, 1 in. diam., firmly set, projecting 6 ins. above ground, bears S. 72°19' W., 14.5 lks. dist.</p>

Dependent Resurvey, Portion of the Subdivision of Section 5,
T. 17 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>This is accepted as the best available evidence of the cor. position.</p> <p>At the cor. point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in concrete, with brass cap mkd.</p> <p style="text-align: center;">S5 1/1024 1990</p> <p>From which</p> <p style="padding-left: 40px;">A sycamore, 12 ins. diam., bears S. 18° E., 127 lks. dist., mkd. 1/1024 S5 BT.</p> <p style="padding-left: 40px;">A sycamore, 18 ins. diam., bears S. 73° E., 129 lks. dist., mkd. 1/1024 S5 BT.</p> <p>Deposit the 1984 monument alongside the stainless steel pipe. Deposit broken brown glass, and a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set angle iron, 2 1/2 x 2 1/2 ins., projecting 4 ft above the ground, near the cor.</p> <p>Cor. is located 1 1/2 lks. S. of the end of a post and mortar fence.</p> <p>From this cor. point, a monument, loosely set, mkd. as described in 1984, bears S. 72° W., 11 lks. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°49' E., on the E. and W. center line of the SE 1/4 of the SW 1/4 of the SW 1/4 of the SE 1/4, sec. 5.</p>
2.67	<p>The 1/1024 sec. cor. of sec. 5, determined from accessories of record</p> <p style="padding-left: 40px;">An elm, 17 ins. diam., bears N. 53° E., 21 lks. dist., with fragmentary scribe marks on an opened blaze. (Record: N.51 1/2° E.)</p> <p style="padding-left: 40px;">A basalt stone, 2 1/2 x 3 1/2 x 1 1/2 ft., bears N. 7 1/2° W., 67 lks. dist., with illegible chisel marks. (Record: N 6° W.)</p>

Dependent Resurvey, Portion of the Subdivision of Section 5,
 T. 17 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A 1 in. diam. open end pipe, a local survey cor., firmly set, projecting 2 ins. above ground, bears S 55°27'W, 19.2lks. (Record: S 56°23' W.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a mound of stone and concrete, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S5 1/1024 1990</p> <p>from which new accessories</p> <p>An elm, 17 ins. diam., same as in 1984, bears N. 53° E., 21 lks. dist., and remarked 1/1024 S5 BT alongside the 1984 blaze.</p> <p>A basalt stone, 2 1/2 x 3 1/2 x 1 1/2 ft., same as in 1984, bears N. 8° W., 68 lks. dist., remarked X BO.</p> <p>Deposit broken brown glass, and a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a 2 1/2 x 2 1/2 in. x 3/32 in. angle iron, projecting 4 ft., near the cor.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 1°44'E., on a portion of the N. and S. centerline of the E 1/2 of the E 1/2 of the SE 1/4 of the SW 1/4 of the SW 1/4 of the SE 1/4 of sec. 5.</p>
4.94	<p>The 1/1024 cor. of sec. 5, determined from bearing tree</p> <p>A ponderosa pine, 27 ins. diam., bears S. 37° E., 132 lks. dist., with healed blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in concrete, with brass cap mkd.</p> <p style="text-align: center;">S5 1/1024 1990</p>

Dependent Resurvey, Portion of the Subdivision of Section 5,
 T. 17 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which a new accessory</p> <p>A red sandstone boulder, 40 x 30 x 28 ins., bears S. 18° E., 31.5 lks., mkd. X BO.</p> <p>Deposit broken brown glass, and a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set creosote treated beam, 6 x 6 ins., projecting 4 1/2 ft. above the ground near the cor.</p> <hr/> <p>N. 89°48' E., on the E. and W. center line of the NE 1/4 of the SW 1/4 of the SE 1/4 of the SE 1/4 of sec. 5.</p>
2.66	<p>The 1/1024 cor. of sec. 5, on the N. and S. center line of the SW 1/4 of the SE 1/4 of sec. 5.</p> <hr/> <p>From the C-W-SW-SE 1/256 sec. cor. of sec. 5.</p> <p>N. 1°53' E., on the N. and S. center line of the NW 1/4 of the SW 1/4 of the SE 1/4 of sec. 5.</p>
2.00	<p>Center of Highway 89A, bears NE. and SW.</p>
2.47	<p>The 1/1024 sec. cor of sec. 5, monumented with an aluminum post, 1 in. diam., firmly set, projecting 4 ins. above the ground, and mkd.</p> <p style="text-align: center;">S5 1/1024 1984</p> <p>from which</p> <p>A point on a concrete abutment, bears S. 50° W., 26 lks. dist., remarked X BO below illegible chisel marks.</p> <p>A piñon, 5 ins. diam., bears N. 11 1/2° W., 21 lks. dist., mkd. X BT on partly healed blazes.</p> <hr/>

Dependent Resurvey, Portion of the Subdivision of Section 5,
T. 17 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>N. 89°45' E., on the E. and W. center line of the SE 1/4 of the NW 1/4 of the SW 1/4 of the SE 1/4 of sec. 5.</p> <p>5.28 The 1/1024 sec. cor. of sec. 5, on the N. and S. center line of the SW 1/4 of the SE 1/4 of sec. 5.</p> <hr/> <p style="text-align: center;">General Description</p> <p>Section 5, of this survey, is located at the NE edge of Sedona, Arizona. The elevation ranges from about 4,200 to 5,300 feet above sea level.</p> <p>The land varies from gently rolling high rolling ridges, sandstone and limestone buttes, cliffs and pinnacles. The U.S. Forest Service land is covered with medium to dense timber and undergrowth. Oak Creek flows through the southeastern portion of section 5 in a southwesterly direction.</p> <p>Access is by way of Highways 89A and 179. There are numerous other paved and gravel roads in the area.</p> <p>The mean magnetic declination is 14° E.</p>
--------	--

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Wally R. Ott, Sr.	Land Surveyor, U.S. Forest Service
Ben G. Garcia, Jr.	Survey Technician, U.S. Forest Service
Luke B. Granger	Survey Technician, B.L.M.

CERTIFICATE OF SURVEY

I, Stephen K. Hansen, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions dated the 28th day of June, 1990, I have dependently resurveyed portions of the subdivisional lines and subdivision of section 5, of Township 17 North, Range 6 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

7-25-91

(Date)

Stephen K. Hansen

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of portions of the subdivisional lines and subdivision of section 5, of Township 17 North, Range 6 East, Gila and Salt River Meridian, Arizona, executed by Stephen K. Hansen, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

NOV 18 1991

(Date)

Joe A. Stutz

(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I certify that the foregoing transcript of the field notes of the above-described surveys in T. 17 N., R. 6 E., Gila and Salt River Meridian, Arizona is a true copy of the original field notes.~~

~~(Date)~~~~(Chief Cadastral Surveyor of Arizona)~~