

ORIGINAL

1 BOOK 5348

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE

REMONUMENTATION

OF

CERTAIN CORNERS

IN

TOWNSHIP 21 NORTH, RANGE 14 WEST

AND

TOWNSHIP 24 NORTH, RANGE 15 WEST

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY

William P Carpender, Cadastral Surveyor

Under Special Instructions dated May 23, 1986, approved May 23, 1986,
which provided for the surveys included under Group Number 680 and assignment
instructions dated February 18, 1987.

Survey commenced March 9, 1987

Survey completed May 6, 1987

INDEX DIAGRAM

TOWNSHIP 21 NORTH, RANGE 14 WEST,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
		5			
30	29	28	27	26	25
		5			
31	32	33	34	35	36

INDEX DIAGRAM

TOWNSHIP 24 NORTH , RANGE 15 WEST ,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

T. 21 N., R. 14 W., and T. 24 N., R. 15 W.,
Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the remonumentation of certain cors. in T. 21 N., R. 14 W., and T. 24 N., R. 15 W., in the Gila and Salt River Meridian, Arizona.

T. 21 N., R. 14 W., was subdivided in 1912 by Jesse B. Wright and William H. Elliot. T. 24 N., R. 15 W., was subdivided in 1911 by W.O.Secor.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, the Special Instructions dated May 23, 1986, and Assignment Instructions dated February 18, 1987, for Group No. 680, Arizona.

Identified corners were remonumented in their original positions.

The mean magnetic declination as shown on HUALAPI PEAK NE, ARIZ. quadrangle map, published by U.S. Geological Survey in 1968 is 15° E.

Remonumentation of Certain Monuments
T. 21 N., R. 14 W., Gila and Salt River Meridian, Arizona

CHAINS

Restoring the survey executed by
Jesse B. Wright, U.S. Surveyor, in 1912.

The cor. of secs. 27, 28, 33, and 34, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. from the ground, with brass cap incorrectly mkd. T21N R12W S27 S28 S33 S34 1912.

Remark the brass cap to read

T21N R14W	
S28	S27
S33	S34
1987	
1912	

Raise a mound of stone, 3 ft. base, to top, around the iron post.

Cor. is East, 20 lks. dist., from a track road, 24 lks. wide, bears N. and S.

Cor. falls West, 10 lks. dist., from a fence, bears N. and S.

Cor. is located West, 40 lks. dist., from a track road, 24 lks. wide, bears N. and S.

The cor. of secs. 21, 22, 27, and 28, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 27 ins. from the ground, with brass cap incorrectly mkd., T21N R12W S21 S22 S27 S28 1912.

Remark the brass cap to read:

T21N R14W	
S21	S22
S28	S27
1987	
1912	

Raise a mound of stone, 3 ft. base, to top, around the iron post

Set a steel fence post alongside the cor.

Cor. is located North, 17 lks. dist., from a power line, bears E. and W.

Remonumentation of Certain Monuments
T. 24 N., R. 15 W., Gila and Salt River Meridian, Arizona

CHAINS

Restoring the survey executed by
W.O.Secor, U.S. Transitman, in 1911.

The cor. of secs. 28, 29, 32, and 33, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. from the ground, with brass cap incorrectly mkd., T24N R16W S28 S29 S32 S33 1911.

Remark the brass cap to read:

T24N R15W	
S29	S28
S32	S33
1987	
1911	

From this cor. point, U.S.Geological Survey Bench Mark 30 DOR bears East, 4 lks. dist., monumented with a standard brass disk, 4 ins. diam., firmly set in cement, projecting 2 ins. from the ground, mkd. ELEV. 3019 30 DOR 1967.

Cor. is located South, 1.5 lks. dist., from a fence cor., fences extend N., E., and W.

Cor falls West, 20 lks. dist. from a track road, 18 lks. wide, bears N. and S.

GENERAL DESCRIPTION

T. 21 N., R. 14 W. is about 15 air miles East of Kingman, Arizona.

T. 24 N., R. 15 W. is about 20 air miles east of Kingman, Arizona. The terrain consists of a series of low, broken ridges, with washes draining predominately Northeast, covered with a moderate growth of scruboak, and catclaw brush, with scattered juniper and pinyon pine trees. The soil is largely decomposed granite, sand and gravel.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Robert D. Begley	Land Surveyor in Training
Luke B. Granger	Survey Technician
Cheryl A. Baier	Survey Technician

CERTIFICATE OF SURVEY

I, William P. Carpender, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 23th day of May, 1986, I have remonumented certain corners in T. 21 N., R. 14 W., and T. 24 N., R. 15 W., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

FEB. 27, 1992

(Date)

William P. Carpender

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the remonumentation of certain corners in T. 21 N., R. 14 W., and T. 24 N., R. 15 W., Gila and Salt River Meridian, Arizona, executed by William P. Carpender, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

MAR 3 1992

(Date)

James A. Talbot

(Chief Cadastral Surveyor of Arizona)

Acting

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 21 N., R. 14 W. and T. 24 N., R. 15 W., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.

(Date)

(Chief Cadastral Surveyor of Arizona)