

ORIGINAL
BOOK 1 5355

R-5355

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE

SURVEY OF

THE WEST BOUNDARY, IDENTICAL WITH THE SIXTH GUIDE MERIDIAN EAST,

THE SOUTH AND EAST BOUNDARIES,

AND

THE SUBDIVISIONAL LINES

OF

TOWNSHIP 28 NORTH, RANGE 25 EAST

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY

William F. Olver and John A. Pex, Cadastral Surveyors

Under special instructions dated November 22, 1989, approved November 22, 1989,
which provided for the surveys included under Group Number 715 and assignment
instructions dated December 18, 1989 and January 25, 1990.

Survey commenced January 2, 1990

Survey completed April 5, 1990

ORIGINAL

2

BOOK 5355

INDEX DIAGRAM

TOWNSHIP 28 NORTH, RANGE 25 EAST,

36	31	32	33	34	35
8 74 6	74 73 5	60 59 4	51 49 3	41 40 2	32 31 1 21
7 72 7	71 70 8	58 57 9	49 48 10	39 39 11	30 29 12 20
7 70 18	69 68 17	57 56 16	47 46 15	38 37 14	29 28 13 19
6 67 19	67 66 20	55 54 21	46 45 22	36 36 23	27 26 24 18
5 65 30	65 64 29	54 53 28	44 44 27	35 34 26	25 24 25 17
4 63 31 15	62 61 32 14	52 51 33 13	43 42 34 12	33 33 35 11	23 22 36 16 10

T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS

The following field notes described the survey of the west boundary, identical with the Sixth Guide Meridian East, the south and east boundaries, and the subdivisional lines of Township 28 North, Range 25 East, Gila and Salt River Meridian, Arizona.

The west boundary of the Navajo Indian Reservation and the boundaries and subdivision of Townships 1 and 2 North, Range 11 West, Navajo Special Meridian were surveyed by E.N. Darling in 1869. The west boundary of the Navajo Indian Reservation was dependently resurveyed by L.E. Sechrist in 1919-20. The survey of the Seventh Standard Parallel North, through Ranges 24 and 25 East, was executed concurrently under this group. The southeast and southwest corners of the township were established in the survey of Township 27 North, Range 25 East, executed concurrently under this group.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973 and the Special Instructions dated November 22, 1989, for Group No. 715, Arizona.

The directions of all lines were determined by direct hour angle solar observations and refer to the true meridian. Distances and angles were measured using a Zeiss Elta 3 electronic instrument.

The geographic position of the southeast corner of the Tp., as determined from a tie made to U.S. Coast and Geodetic Survey first order triangulation station "GANADO SE BASE 1951", located in the NW quarter of section 34, is as follows:

Latitude: 35°46'43.19" N. Longitude: 109°36'45.73" W.

The geographic position of the southwest corner of the Tp., as determined from a tie made to a control station whose geographic coordinates were determined by the technique of relative positioning using the Magnavox Golden Eagle Satellite Surveyor, as reported in the survey of T. 27 N., R. 25 E., executed concurrently under this group, is as follows:

Latitude: 35°46'43.65" N. Longitude: 109°43'09.48" W.

The mean magnetic declination is 12 1/2° E., as taken from the magnetic declination map published in 1985 by U.S. Geological Survey.

Survey of the West Boundary,
 Identical with Sixth Guide Meridian East,
 T. 28 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Beginning at the cor. of Tps. 27 and 28 N., Rs. 24 and 25 E., set, mkd. and witnessed as described in the field note record of the survey of the Sixth Guide Meridian East, through T. 27 N., executed concurrently under this group.
	North, bet. secs. 31 and 36.
	Over gently rolling land.
2.80	Trail road, bears ENE and WSW.
8.40	Power line, bears ENE and WSW.
15.30	Power line, bears SE and NW.
17.71	South right-of-way fence of Arizona State Highway No. 264, barbed wire, 5 strands, parallels highway.
19.33	Center line, Arizona State Highway No. 264, asphalt pavement, 38 lks. wide, bears ENE and WSW, in curve to the right.
20.93	North right-of-way fence of Arizona State Highway No. 264, barbed wire, 5 strands, parallels highway.
33.50	Power line, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T28N R24E 1/4 R25E S36 S31 1990
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
80.00	Point for the cor. of secs. 25, 30, 31 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the West Boundary,
 Identical with Sixth Guide Meridian East,
 T. 28 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<table border="1"> <tr><td colspan="2">T28N</td></tr> <tr><td>R24E</td><td>R25E</td></tr> <tr><td>S25</td><td>S30</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S36</td><td>S31</td></tr> <tr><td colspan="2">1990</td></tr> </table>	T28N		R24E	R25E	S25	S30	-----		S36	S31	1990	
T28N													
R24E	R25E												
S25	S30												

S36	S31												
1990													
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses, scattered brush and cacti.</p> <hr/> <p>North, bet. secs. 25 and 30.</p> <p>Over gently rolling land.</p>												
32.85	Trail road, bears SE and NW.												
40.00	Point for the 1/4 sec. cor. of secs. 25 and 30.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.												
	<table border="1"> <tr><td colspan="2">T28N</td></tr> <tr><td>R24E 1/4</td><td>R25E</td></tr> <tr><td>S25</td><td>S30</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td colspan="2">1990</td></tr> </table>	T28N		R24E 1/4	R25E	S25	S30	-----		1990			
T28N													
R24E 1/4	R25E												
S25	S30												

1990													
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>												
45.00	Graded road, 38 lks. wide, bears SE and NW.												
50.30	Power line, bears ESE and WNW.												
80.00	Point for the cor. of secs. 19, 24, 25 and 30.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.												
	<table border="1"> <tr><td colspan="2">T28N</td></tr> <tr><td>R24E</td><td>R25E</td></tr> <tr><td>S24</td><td>S19</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S25</td><td>S30</td></tr> <tr><td colspan="2">1990</td></tr> </table>	T28N		R24E	R25E	S24	S19	-----		S25	S30	1990	
T28N													
R24E	R25E												
S24	S19												

S25	S30												
1990													

Survey of the West Boundary,
Identical with Sixth Guide Meridian East,
T. 28 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p>
	<p>North, between secs. 19 and 24.</p> <p>Over gently rolling land.</p>
8.95	Trail road, bears SSE and NNW.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 24.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R24E 1/4 R25E S24 S19 1990</p>
	from which
	<p style="text-align: center;">The NW cor. of a log cabin with concrete foundation, 30 x 15 ft., bears S. 82 1/2° W., 3.06 chs. dist., long side extends S. 25° W.</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
80.00	Point for the cor. of secs. 13, 18, 19 and 24.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R24E R25E S13 S18 ----- S24 S19 1990</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>

Survey of the West Boundary,
Identical with Sixth Guide Meridian East,
T. 28 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/>
	<p>North, bet. secs. 13 and 18.</p>
	<p>Over gently rolling land.</p>
<p>40.00</p>	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T28N R24E 1/4 R25E S13 S18 1990</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
<p>68.70</p>	<p>Graded road, 30 lks. wide, bears NNE and SSW.</p>
<p>80.00</p>	<p>Point for the cor. of secs. 7, 12, 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T28N R24E R25E S12 S 7 ----- S13 S18 1990</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
	<p>Land, gently rolling. Soil, sandy loam and clay. No timber; native grasses and scattered brush.</p> <hr/>
	<p>North, bet. secs. 7 and 12.</p>
	<p>Over rolling land.</p>
<p>26.65</p>	<p>Trail road, bears E. and W.</p>

Survey of the West Boundary,
Identical with Sixth Guide Meridian East,
T. 28 N., R. 25 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p> <p>40.00</p> <p>80.00</p> <p>40.00</p>	<p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R24E 1/4 R25E S12 S 7 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 1, 6, 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R24E R25E S 1 S 6 ----- S12 S 7 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam and clay. No timber; native grasses and scattered brush.</p> <hr/> <p>North, bet. secs. 1 and 6.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R24E 1/4 R25E S 1 S 6 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
--	---

ORIGINAL

BOOK 9
5355

Survey of the West Boundary,
Identical with Sixth Guide Meridian East,
T. 28 N., R. 25 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p> <p>42.90</p> <p>80.00</p> <p>89.35</p>	<p>Graded road, 30 lks. wide, bears SE and NW.</p> <p>Point for the 80 1/16 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R24E 80 R25E 1/16 S 1 S 6 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Point for the closing cor. of T. 28 N., Rs. 24 and 25 E., at intersection with the N. Bdy. of the Tp., identical with the Seventh Standard Parallel North.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R24E S36 ----- S 1 S 6 R24E R25E T28N CC 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 29 N., R. 24 E., bears East, 13.54 chs. dist., set, mkd. and witnessed as described in the field note record of the survey of the Seventh Standard Parallel North, through R. 24 E., executed concurrently under this group.</p> <p>Land, rolling. Soil, sandy loam and clay. No timber; native grasses and scattered brush.</p> <hr/>
--	---

Survey of the South Boundary,
T. 28 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of Tps. 27 and 28 N., Rs. 25 and 26 E., set, mkd. and witnessed as described in the field note record of the survey of the east boundary of T. 27 N., R. 25 E., executed concurrently under this group.</p>
	<p>N. 89°55' W., bet. secs. 1 and 36.</p>
	<p>Over level land.</p>
28.33	<p>East right-of-way fence of U.S. Highway No. 191, barbed wire, 5 strands, parallels highway.</p>
29.90	<p>Center line, U.S. Highway No. 191, asphalt pavement, 38 lks. wide, bears NNE and SSW.</p>
31.45	<p>West right-of-way fence of U.S. Highway No. 191, barbed wire, 5 strands, parallels highway.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R25E S36 1/4 — S 1 T27N 1990</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
	<p>From this cor. point, the 2 Mile Cor. on the 1868 west boundary of the Navajo Indian Reservation, bears N. 76°04' W., 15.39 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd. NIR 2M 1920. As it is impracticable to bury the iron post, remove brass cap and mark AM on north side of iron post.</p>
54.85	<p>Power line, bears NNE and SSW.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 35 and 36.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the South Boundary,
T. 28 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td>T28N</td> <td>R25E</td> </tr> <tr> <td>S35</td> <td>S36</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S 2</td> <td>S 1</td> </tr> <tr> <td colspan="2" style="text-align: center;">T27N</td> </tr> <tr> <td colspan="2" style="text-align: center;">1990</td> </tr> </table> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, level. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/>	T28N	R25E	S35	S36			S 2	S 1	T27N		1990	
T28N	R25E												
S35	S36												
S 2	S 1												
T27N													
1990													
	<p>N. 89°55' W., bet. secs. 2 and 35.</p> <p>Over level land.</p>												
<p>40.00</p>	<p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>												
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td>T28N</td> <td>R25E</td> </tr> <tr> <td></td> <td>S35</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 2</td> </tr> <tr> <td colspan="2" style="text-align: center;">T27N</td> </tr> <tr> <td colspan="2" style="text-align: center;">1990</td> </tr> </table> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>	T28N	R25E		S35	1/4	—		S 2	T27N		1990	
T28N	R25E												
	S35												
1/4	—												
	S 2												
T27N													
1990													
<p>80.00</p>	<p>Point for the cor. of secs. 2, 3, 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>												
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td>T28N</td> <td>R25E</td> </tr> <tr> <td>S34</td> <td>S35</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S 3</td> <td>S 2</td> </tr> <tr> <td colspan="2" style="text-align: center;">T27N</td> </tr> <tr> <td colspan="2" style="text-align: center;">1990</td> </tr> </table> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>	T28N	R25E	S34	S35			S 3	S 2	T27N		1990	
T28N	R25E												
S34	S35												
S 3	S 2												
T27N													
1990													

Survey of the South Boundary,
T. 28 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, level. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/> <p>N. 89°55' W., bet. secs. 3 and 34.</p> <p>Over level land.</p>
20.96	The SE cor. of a house, 17 x 14 ft., long side extends NNE, bears North, 0.90 chs. dist.
35.65	Graded road, 30 lks. wide, bears SSE and NNW.
37.30	Northeast right-of-way fence of Arizona State Highway No. 264, barbed wire, 5 strands, parallels highway.
39.54	Center line, Arizona State Highway No. 264, asphalt pavement, 38 lks. wide, bears SE and NW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T28N R25E S34 1/4 — S 3 T27N 1990</p> </div> <p>from which</p> <p style="padding-left: 40px;">A right-of-way monument, an angle iron, firmly set, projecting 20 ins. above the ground, bears N. 39 1/4° E., 195 1/2 lks. dist., mkd. PC 1894+92.4.</p> <p style="padding-left: 40px;">A right-of-way monument, an angle iron, firmly set, projecting 20 ins. above the ground, bears S. 51 3/4° W., 109 1/2 lks. dist., mkd. PC 1894+92.4.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
41.61	Southwest right-of-way fence of Arizona State Highway No. 264, barbed wire, 5 strands, parallels highway.
47.50	Power line, bears SE and NW.

Survey of the South Boundary,
T. 28 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
63.36	The NE cor. of a house, 30 x 20 ft., long side extends South, bears South, 0.75 chs. dist.												
71.50	Base of ascent.												
76.60	Top of ridge, bears N. and S.												
77.60	Wash at base of descent, 20 ft. deep, drains NNW.												
80.00	Point for the cor. of secs. 3, 4, 33 and 34.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.												
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T28N</td> <td>R25E</td> </tr> <tr> <td>S33</td> <td>S34</td> </tr> <tr> <td colspan="2" style="text-align: center;"> </td> </tr> <tr> <td>S 4</td> <td>S 3</td> </tr> <tr> <td colspan="2" style="text-align: center;">T27N</td> </tr> <tr> <td colspan="2" style="text-align: center;">1990</td> </tr> </table>	T28N	R25E	S33	S34			S 4	S 3	T27N		1990	
T28N	R25E												
S33	S34												
S 4	S 3												
T27N													
1990													
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.												
	<p>Land, level to rolling. Soil, sandy loam and clay. Timber, scattered juniper and piñon; native grasses and scattered brush.</p>												
	N. 89°55' W., bet. secs. 4 and 33.												
	Over rolling land.												
4.60	Top of ridge, bears NNE and SSW.												
6.10	Wash at base of descent, 20 ft. deep, drains SSW.												
7.40	Top of ridge, bears NNE and SSW.												
12.10	Base of descent.												
20.10	Wash, 120 lks. wide, 20 ft. deep, drains NNW.												
28.40	Base of ascent.												

ORIGINAL

.. 14
BOOK 5355

Survey of the South Boundary,
T. 28 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
29.60	Top of ridge, bears N. and S.
30.60	Base of descent, start gradual ascent.
36.40	Top ridge, bears N. and S.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 33.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, cemented in place, in sandstone bedrock, with top mkd.
	<p style="text-align: center;">T28N R25E S33 1/4 — S 4 T27N 1990</p>
	Deposit a magnet, 1 in. long, 7/8 in. diam., beneath the brass tablet.
41.70	Base of descent.
80.00	Point for the cor. of secs. 4, 5, 32 and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T28N R25E S32 S33 — — S 5 S 4 T27N 1990</p>
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
	<p>Land, rolling. Soil, sandy loam, clay and exposed sandstone bedrock. Timber, scattered juniper and piñon; native grasses and scattered brush.</p>
	<hr/> <p>N. 89°55' W., bet. secs. 5 and 32.</p>
	Over rolling land.

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R25E S32 1/4 — S 5 T27N 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
47.20	<p>Graded road, 30 lks. wide, bears SSE and NNW.</p>
54.05	<p>The SE cor. of a house, 25 x 12 ft., long side extends N. 25° E., bears North, 1.70 chs. dist.</p>
56.25	<p>Trail road, bears NE and SW.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R25E S31 S32 — — S 6 S 5 T27N 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam and clay. Timber, scattered juniper and piñon; native grasses and scattered brush.</p> <hr/> <p>N. 89°55' W., bet. secs. 6 and 31.</p> <p>Over rolling land.</p>

Survey of the South Boundary,
T. 28 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
24.65	Trail road, bears SSE and NNW.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T28N R25E S31 1/4 — S 6 T27N 1990
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
58.31	The SE cor. of a house, 40 x 20 ft., long side extends North, bears North, 12.08 chs. dist.
79.23	The cor. of Tps. 27 and 28 N., Rs. 24 and 25 E., hereinbefore described.
	Land, rolling. Soil, sandy loam. No timber; native grasses and scattered brush.
<hr/> Survey of the East Boundary, T. 28 N., R. 25 E., Gila and Salt River Meridian, Arizona <hr/>	
	From the cor. of Tps. 27 and 28 N., Rs. 25 and 26 E., set, mkd. and witnessed as described in the field note record of the survey of the east boundary of T. 27 N., R. 25 E., executed concurrently under this group.
	North, bet. secs. 31 and 36.
	Over level land.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

CHAINS	
	<p style="text-align: center;">T28N R25E 1/4 R26E S36 S31 1990</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
43.80	<p>Wash, 45 lks. wide, 4 ft. deep, drains WNW.</p>
71.85	<p>Trail road, bears E. and W.</p>
72.85	<p>Trail road, bears E. and W.</p>
75.70	<p>Trail road, bears ENE and WSW.</p>
80.00	<p>Point for the cor. of secs. 25, 30, 31 and 36.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R25E R26E S25 S30 ----- S36 S31 1990</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
	<p>Cor. is located 20 lks. S. of a trail road, bears NE and SW.</p>
	<p>Land, level. Soil, sandy loam. No timber; native grasses and scattered brush.</p>
	<p>North, bet. secs. 25 and 30.</p>
	<p>Over level land.</p>
37.87	<p>East right-of-way fence of U.S. Highway No. 191, barbed wire, 5 strands, parallels highway.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p>

ORIGINAL

18

BOOK 5355

Survey of the East Boundary,

T. 28 N., R. 25 E.,

Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T28N R25E 1/4 R26E S25 S30 1990</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
44.47	<p>Center line, U.S. Highway No. 191, asphalt pavement, 38 lks. wide, bears NNE and SSW.</p>
50.76	<p>West right-of-way fence of U.S. Highway No. 191, barbed wire, 5 strands, parallels highway.</p>
71.70	<p>Power line, bears ESE and WNW.</p>
74.40	<p>Trail road, bears ESE and WNW.</p>
80.00	<p>Point for the cor. of secs. 19, 24, 25 and 30.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R25E R26E S24 S19 ----- S25 S30 1990</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
	<p>Land, level. Soil, sandy loam. No timber; native grasses and scattered brush.</p>
	<p>North, bet. secs. 19 and 24.</p>
	<p>Over gently rolling land.</p>
27.50	<p>Trail road, bears ENE and WSW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

ORIGINAL

19

BOOK 5355

Survey of the East Boundary,

T. 28 N., R. 25 E.,

Gila and Salt River Meridian, Arizona

CHAINS	<p style="text-align: center;">T28N R25E 1/4 R26E S24 S19 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>41.05 Trail road, bears ESE and WNW.</p> <p>52.89 Center shaft of a windmill, bears West, 22.74 chs. dist.</p> <p>77.10 Trail road, bears ESE and WNW.</p> <p>80.00 Point for the cor. of secs. 13, 18, 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R25E R26E S13 S18 ----- S24 S19 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/> <p>North, bet. secs. 13 and 18.</p> <p>Over gently rolling land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R25E 1/4 R26E S13 S18 1990</p>
--------	--

ORIGINAL

20
BOOK 5355

Survey of the East Boundary,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

<p>CHAINS</p> <p>48.15</p> <p>58.60</p> <p>80.00</p> <p>12.90</p> <p>40.00</p> <p>80.00</p>	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Trail road, bears E. and W.</p> <p>Wash, 76 lks. wide, 20 ft. deep, drains WNW.</p> <p>Point for the cor. of secs. 7, 12, 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T28N</p> <table border="1"> <tr> <td>R25E</td> <td>R26E</td> </tr> <tr> <td>S12</td> <td>S 7</td> </tr> <tr> <td>S13</td> <td>S18</td> </tr> <tr> <td colspan="2">1990</td> </tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/> <p>North, bet. secs. 7 and 12.</p> <p>Over rolling land.</p> <p>Power line, bears NNE and SSW.</p> <p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T28N</p> <table border="1"> <tr> <td>R25E 1/4</td> <td>R26E</td> </tr> <tr> <td>S12</td> <td>S 7</td> </tr> <tr> <td colspan="2">1990</td> </tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 1, 6, 7 and 12.</p>	R25E	R26E	S12	S 7	S13	S18	1990		R25E 1/4	R26E	S12	S 7	1990	
R25E	R26E														
S12	S 7														
S13	S18														
1990															
R25E 1/4	R26E														
S12	S 7														
1990															

CHAINS													
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="836 388 1023 577"> <tr><td colspan="2" style="text-align:center">T28N</td></tr> <tr><td style="text-align:center">R25E</td><td style="text-align:center">R26E</td></tr> <tr><td style="text-align:center">S 1</td><td style="text-align:center">S 6</td></tr> <tr><td colspan="2" style="text-align:center">-----</td></tr> <tr><td style="text-align:center">S12</td><td style="text-align:center">S 7</td></tr> <tr><td colspan="2" style="text-align:center">1990</td></tr> </table> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p>	T28N		R25E	R26E	S 1	S 6	-----		S12	S 7	1990	
T28N													
R25E	R26E												
S 1	S 6												

S12	S 7												
1990													
40.00	<p>North, bet. secs. 1 and 6.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="820 1144 1039 1281"> <tr><td colspan="2" style="text-align:center">T28N</td></tr> <tr><td style="text-align:center">R25E 1/4</td><td style="text-align:center">R26E</td></tr> <tr><td style="text-align:center">S 1</td><td style="text-align:center">S 6</td></tr> <tr><td colspan="2" style="text-align:center">1990</td></tr> </table> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>	T28N		R25E 1/4	R26E	S 1	S 6	1990					
T28N													
R25E 1/4	R26E												
S 1	S 6												
1990													
80.00	<p>Point for the 80 1/16 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="820 1564 1023 1732"> <tr><td colspan="2" style="text-align:center">T28N</td></tr> <tr><td style="text-align:center">R25E 80</td><td style="text-align:center">R26E</td></tr> <tr><td colspan="2" style="text-align:center">1/16</td></tr> <tr><td style="text-align:center">S 1</td><td style="text-align:center">S 6</td></tr> <tr><td colspan="2" style="text-align:center">1990</td></tr> </table> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>	T28N		R25E 80	R26E	1/16		S 1	S 6	1990			
T28N													
R25E 80	R26E												
1/16													
S 1	S 6												
1990													

Survey of the East Boundary,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS					
84.30	Graded road, 30 lks. wide, bears SSE and NNW.				
90.04	Point for the closing cor. of T. 28 N., Rs. 25 and 26 E., at intersection with the N. Bdy. of the Tp., identical with the Seventh Standard Parallel North.				
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.				
	<div style="text-align: center;"> <p>T29N R25E S36</p> <hr style="width: 10%; margin: auto;"/> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 2px;">S 1</td> <td style="padding: 2px;">S 6</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">R25E</td> <td style="padding: 2px;">R26E</td> </tr> </table> <p>T28N CC 1990</p> </div>	S 1	S 6	R25E	R26E
S 1	S 6				
R25E	R26E				
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.				
	From this cor. point, the stan. 1/4 cor. of sec. 36, T. 29 N., R. 25 E., bears East, 14.86 chs. dist., set, mkd. and witnessed as described in the field note record of the survey of the Seventh Standard Parallel North, through R. 25 E., executed concurrently under this group.				
	Land, rolling. Soil, sandy loam. No timber; native grasses and scattered brush.				
	<hr/> <p>Survey of the Subdivisional Lines, T. 28 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <hr/>				
	From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.				
	N. 0°01' W., bet. secs. 35 and 36.				
	Over gently rolling land.				
20.05	Trail road, bears ENE and WSW.				
40.00	Point for the 1/4 sec. cor. of secs. 35 and 36.				

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T28N R25E S25 1/4 — S36 1990</p>
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
41.70	Trail road, bears NNE and SSW.
71.30	Trail road, bears NNE and SSW.
80.00	The cor. of secs. 25, 26, 35 and 36.
	<p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p>
	N. 0°01' W., bet. secs. 25 and 26.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T28N R25E 1/4 S26 S25 1990</p>
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
55.30	Trail road, bears SE and NW.
59.50	Trail road, bears ESE and WNW.
80.00	Point for the cor. of secs. 23, 24, 25 and 26.

ORIGINAL

25
BOOK 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
25 ins. in the ground, with brass cap mkd.

T28N R25E
S23 | S24

S26 | S25
1990

Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic
case beneath the stainless steel post.

Land, gently rolling.
Soil, sandy loam.
No timber; native grasses and scattered brush.

From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the
Tp., hereinbefore described.

N. 89°55' W., bet. secs. 24 and 25.

Over gently rolling land.

6.00 Trail road, bears NNE and SSW.

7.34 The SW cor. of a house, 34 x 20 ft., long side extends S. 70° E.,
bears South, 3.78 chs. dist.

22.50 Power line, bears ESE and WNW.

28.50 Power line, bears N. 10° E. and S. 10° W.

40.00 Point for the 1/4 sec. cor. of secs. 24 and 25.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T28N R25E
S24
1/4 —
S25
1990

Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic
case beneath the stainless steel post.

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point , the 4 Mile Cor. on the 1868 west boundary of the Navajo Indian Reservation, bears N. 67°58' W., 16.45 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd. NIR 4M 1920. As it is impracticable to bury the iron post, remove brass cap and mark AM on north side of iron post.</p>
41.89	<p>The NE cor. of a house, 44 x 24 ft., long side extends S. 20° W., bears North, 15.64 chs. dist.</p>
56.10	<p>Trail road, bears NE and SW.</p>
80.00	<p>The cor. of secs. 23, 24, 25 and 26.</p>
	<p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p>
	<p>N. 0°01' W., bet. secs. 23 and 24.</p>
	<p>Over rolling land.</p>
4.70	<p>Trail road, bears NE and SW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R25E 1/4 S23 S24 1990</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 13, 14, 23 and 24.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R25E S14 S13 ----- S23 S24 1990</p>

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°56' W., bet. secs. 13 and 24.</p> <p>Over rolling land.</p>
5.20	Graded road, 23 lks. wide, bears ESE and WNW.
15.50	Power line, bears NNE and SSW.
35.25	Trail road, bears SSE and NNW.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 24.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R25E S13 1/4 — S24 1990</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the 5 Mile Cor. on the 1868 west boundary of the Navajo Indian Reservation, bears N. 64°40' W., 17.03 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd. NIR 5M 1920. As it is impracticable to bury the iron post, remove brass cap and mark AM on north side of iron post.</p>
43.10	Wash, 23 lks. wide, 5 ft. deep, drains NNE.
80.00	The cor. of secs. 13, 14, 23 and 24.

ORIGINAL

28

BOOK 5355

Survey of the Subdivisional Lines,

T. 28 N., R. 25 E.,

Gila and Salt River Meridian, Arizona

CHAINS	<p>Land, rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/> <p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over rolling land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R25E 1/4 S14 S13 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>42.23 The center of an hexagonal hogan, 15 ft. diam., bears East, 80 lks. dist.</p> <p>49.20 Graded road, 23 lks. wide, bears SE and NW.</p> <p>80.00 Point for the cor. of secs. 11, 12, 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R25E S11 S12 ----- S14 S13 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/>
--------	--

ORIGINAL

BOOK²⁹ 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.
	N. 89°56' W., bet. secs. 12 and 13.
	Over rolling land.
2.20	Power line, bears NNE and SSW.
39.995	Point for the 1/4 sec. cor. of secs. 12 and 13.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T28N R25E S12 1/4 — S13 1990
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
79.99	The cor. of secs. 11, 12, 13 and 14.
	Land, rolling. Soil, sandy loam. No timber; native grasses and scattered brush.
	N. 0°01' W., bet. secs. 11 and 12.
	Over level land.
22.00	Trail road, bears NNE and SSW.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T28N R25E 1/4 S11 S12 1990
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

ORIGINAL

BOOK 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	<p>80.00 Point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td>T28N</td><td>R25E</td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S11</td><td>S12</td></tr> <tr><td colspan="2">1990</td></tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, level. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°56' W., bet. secs. 1 and 12.</p> <p>Over level land.</p>	T28N	R25E	S 2	S 1			S11	S12	1990	
T28N	R25E										
S 2	S 1										
S11	S12										
1990											
39.99	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td>T28N</td><td>R25E</td></tr> <tr><td colspan="2">S 1</td></tr> <tr><td colspan="2">1/4 —</td></tr> <tr><td colspan="2">S12</td></tr> <tr><td colspan="2">1990</td></tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>From this cor. point , the 7 Mile Cor. on the 1868 west boundary of the Navajo Indian Reservation, bears N. 59°04' W., 18.33 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd. NIR 7M 1920. As it is impracticable to bury the iron post, remove brass cap and mark AM on north side of iron post.</p>	T28N	R25E	S 1		1/4 —		S12		1990	
T28N	R25E										
S 1											
1/4 —											
S12											
1990											

ORIGINAL

31
BOOK 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
69.25	Trail road, bears NNE and SSW.
79.98	<p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, level. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/>
	N. 0°01' W., bet. secs. 1 and 2.
	Over rolling land.
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R25E 1/4 S 2 S 1 1990</p>
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
80.00	<p>Point for the 80 1/16 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R25E 80 1/16 S 2 S 1 1990</p>
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
89.93	<p>Point for the closing cor. of secs. 1 and 2, at intersection with the N. Bdy. of the Tp., identical with the Seventh Standard Parallel North.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

ORIGINAL

BOOK³² 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS

T29N R25E
S35

S 2 | S 1
T28N R25E
CC
1990

Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 35, T. 29 N., R. 25 E., bears East, 14.81 chs. dist., set, mkd. and witnessed as described in the field note record of the survey of the Seventh Standard Parallel North, through R. 25 E., executed concurrently under this group.

Land, rolling.
Soil, sandy loam.
No timber; native grasses and scattered brush.

The point for the 1/4 sec. cor. of sec. 1 only, T. 28 N., R. 25 E., is at midpoint on the N. bdy. of sec. 1.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T29N R25E

1/4 S 1
T28N R25E
1990

Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

From this cor. point, the stan. cor. of secs. 35 and 36, T. 29 N., R. 25 E., bears East, 14.835 chs. dist., set, mkd. and witnessed as described in the field note record of the survey of the Seventh Standard Parallel North, through R. 25 E., executed concurrently under this group.

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	<p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T28N R25E 1/4 S34 S35 1990</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
63.10	<p>Top of low ridge, bears NE and SW.</p>
80.00	<p>Point for the cor. of secs. 26, 27, 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T28N R25E S27 S26 ----- S34 S35 1990</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 89°55' W., bet. secs. 26 and 35.</p> <p>Over gently rolling land.</p>

ORIGINAL

BOOK ³⁴ 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R25E S26 1/4 — S35 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 26, 27, 34 and 35.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p>
<hr/> <p>N. 0°01' W., bet. secs. 26 and 27.</p>	
<p>Over gently rolling land.</p>	
5.65	<p>Trail road, bears NE and SW.</p>
9.45	<p>Trail road, bears NNE and SSW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R25E 1/4 S27 S26 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
69.45	<p>Trail road, bears ESE and WNW.</p>
80.00	<p>Point for the cor. of secs. 22, 23, 26 and 27.</p>

ORIGINAL

BOOK³⁵ 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS											
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T28N</td><td>R25E</td></tr> <tr><td>S22</td><td>S23</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S27</td><td>S26</td></tr> <tr><td colspan="2" style="text-align: center;">1990</td></tr> </table>	T28N	R25E	S22	S23			S27	S26	1990	
T28N	R25E										
S22	S23										
S27	S26										
1990											
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.										
	Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.										
	From the cor. of secs. 23, 24, 25 and 26.										
	N. 89°55' W., bet. secs. 23 and 26.										
	Over gently rolling land.										
5.50	Trail road, bears NE and SW.										
40.00	Point for the 1/4 sec. cor. of secs. 23 and 26.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T28N</td><td>R25E</td></tr> <tr><td></td><td>S23</td></tr> <tr><td></td><td>1/4 —</td></tr> <tr><td></td><td>S26</td></tr> <tr><td colspan="2" style="text-align: center;">1990</td></tr> </table>	T28N	R25E		S23		1/4 —		S26	1990	
T28N	R25E										
	S23										
	1/4 —										
	S26										
1990											
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.										
60.50	Trail road, bears NNE and SSW.										
80.00	The cor. of secs. 22, 23, 26 and 27.										
	Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.										

ORIGINAL

BOOK³⁶ 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R25E 1/4 S22 S23 1990</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
60.90	<p>Trail road, bears ENE and WSW.</p>
64.60	<p>Trail road, bears NNE and SSW.</p>
80.00	<p>Point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R25E S15 S14 ----- S22 S23 1990</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/>
33.95	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 89°56' W., bet. secs. 14 and 23.</p> <p>Over gently rolling land.</p> <p>Trail road, bears NNE and SSW.</p>

ORIGINAL

BOOK³⁷ 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
40.005	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R25E S14 1/4 — S23 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
55.25	<p>Trail road, bears NNE and SSW.</p>
80.01	<p>The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 14 and 15.</p>
	<p>Over gently rolling land.</p>
23.30	<p>Trail road, bears S. 80° E. and N. 80° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R25E 1/4 S15 S14 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
70.15	<p>Trail road, bears ESE and WNW.</p>
80.00	<p>Point for the cor. of secs. 10, 11, 14 and 15.</p>

ORIGINAL

38
BOOK 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS											
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.										
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td>T28N</td><td>R25E</td></tr> <tr><td>S10</td><td>S11</td></tr> <tr><td colspan="2" style="text-align: center;"> </td></tr> <tr><td>S15</td><td>S14</td></tr> <tr><td colspan="2" style="text-align: center;">1990</td></tr> </table>	T28N	R25E	S10	S11			S15	S14	1990	
T28N	R25E										
S10	S11										
S15	S14										
1990											
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.										
	Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.										
	From the cor. of secs. 11, 12, 13 and 14.										
	N. 89°55' W., bet. secs. 11 and 14.										
	Over gently rolling land.										
4.70	Trail road, bears NNE and SSW.										
26.15	Graded road, 15 lks. wide, bears SE and NW.										
40.01	Point for the 1/4 sec. cor. of secs. 11 and 14.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td>T28N</td><td>R25E</td></tr> <tr><td></td><td>S11</td></tr> <tr><td></td><td>1/4 —</td></tr> <tr><td></td><td>S14</td></tr> <tr><td colspan="2" style="text-align: center;">1990</td></tr> </table>	T28N	R25E		S11		1/4 —		S14	1990	
T28N	R25E										
	S11										
	1/4 —										
	S14										
1990											
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.										
80.02	The cor. of secs. 10, 11, 14 and 15.										
	Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.										

ORIGINAL

.. 39
BOOK 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	<p>N. 0°01' W., bet. secs. 10 and 11.</p> <p>Over gently rolling land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R25E 1/4 S10 S11 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>61.25 Graded road, 15 lks. wide, bears SE and NW.</p> <p>80.00 Point for the cor. of secs. 2, 3, 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R25E S 3 S 2 ----- S10 S11 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°55' W., bet. secs. 2 and 11.</p> <p>Over gently rolling land.</p> <p>38.80 Trail road, bears SSE and NNW.</p> <p>40.025 Point for the 1/4 sec. cor. of secs. 2 and 11.</p>
--------	---

ORIGINAL

BOOK⁴⁰ 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R25E S 2 1/4 — S11 1989</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
80.05	<p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p>
	<p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R25E 1/4 S 3 S 2 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
64.75	<p>Trail road, bears ENE and WSW.</p>
65.00	<p>Trail road, bears E. and W.</p>
80.00	<p>Point for the 80 1/16 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. cor. of secs. 34 and 35, T. 29 N., R. 25 E., bears East, 14.845 chs. dist., set, mkd. and witnessed as described in the field note record of the survey of the Seventh Standard Parallel North, through R. 25 E., executed concurrently under this group.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over gently rolling land.</p>
25.70	Power line, bears ESE and WNW.
28.23	South right-of-way fence of Arizona State Highway No. 264, barbed wire, 5 strands, parallels highway.
30.02	Center line, Arizona State Highway No. 264, asphalt pavement, 38 lks. wide, bears SE and NW.
31.84	North right-of-way fence of Arizona State Highway No. 264, barbed wire, 5 strands, parallels highway.
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R25E 1/4 S33 S34 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
63.65	Trail road, bears ESE and WNW.
80.00	<p>Point for the cor. of secs. 27, 28, 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

ORIGINAL

BOOK⁴³ 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS																			
	<div style="text-align: center;"> <table border="1"> <tr> <td>T28N</td> <td>R25E</td> </tr> <tr> <td>S28</td> <td>S27</td> </tr> <tr> <td>S33</td> <td>S34</td> </tr> <tr> <td colspan="2">1990</td> </tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 50 lks. S. and 35 lks. W. of a graded road, 38 lks. wide, bears S. 33° E. and N. 33° W.</p> <p>From this cor. point, U.S. Coast and Geodetic Survey first order triangulation station, "GANADO SE BASE", bears S. 35°18' E., 20.09 chs. dist., monumented with a standard brass tablet, 3 1/2 ins. diam., set in a concrete cylinder, 10 ins. diam., 18 ins. below the surface of the ground, mkd. GANADO SE BASE 1972 1951 and a triangle.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°55' W., bet. secs. 27 and 34.</p> <p>Over gently rolling land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T28N</td> <td>R25E</td> </tr> <tr> <td></td> <td>S27</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S34</td> </tr> <tr> <td colspan="2">1990</td> </tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>80.00 The cor. of secs. 27, 28, 33 and 34.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/>	T28N	R25E	S28	S27	S33	S34	1990		T28N	R25E		S27	1/4	—		S34	1990	
T28N	R25E																		
S28	S27																		
S33	S34																		
1990																			
T28N	R25E																		
	S27																		
1/4	—																		
	S34																		
1990																			

ORIGINAL

BOOK⁴⁴ 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	<p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over gently rolling land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>T28N</td><td>R25E</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S28</td><td> S27</td></tr> <tr><td>1990</td><td></td></tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>80.00 Point for the cor. of secs. 21, 22, 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>T28N</td><td>R25E</td></tr> <tr><td>S21</td><td> S22</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S28</td><td> S27</td></tr> <tr><td>1990</td><td></td></tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr style="border: 0.5px solid black;"/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 89°55' W., bet. secs. 22 and 27.</p> <p>Over gently rolling land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>	T28N	R25E	1/4		S28	S27	1990		T28N	R25E	S21	S22			S28	S27	1990	
T28N	R25E																		
1/4																			
S28	S27																		
1990																			
T28N	R25E																		
S21	S22																		
S28	S27																		
1990																			

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T28N R25E S22 1/4 — S27 1990</p>
80.00	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 21, 22, 27 and 28.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/>
40.00	<p>N. 0°02' W., bet. secs. 21 and 22.</p> <p>Over gently rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
80.00	<p style="text-align: center;">T28N R25E 1/4 S21 S22 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 15, 16, 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R25E S16 S15 — — S21 S22 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>

ORIGINAL

46

BOOK 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/>
	<p>From the cor. of secs. 14, 15, 22 and 23.</p>
	<p>N. 89°55' W., bet. secs. 15 and 22.</p>
	<p>Over gently rolling land.</p>
39.995	<p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R25E</p>
	<p style="text-align: center;">S15</p>
	<p style="text-align: center;">1/4 —</p>
	<p style="text-align: center;">S22</p>
	<p style="text-align: center;">1990</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
79.99	<p>The cor. of secs. 15, 16, 21 and 22.</p>
	<p>Land, gently rolling.</p>
	<p>Soil, sandy loam.</p>
	<p>No timber; native grasses and scattered brush.</p> <hr/>
	<p>N. 0°02' W., bet. secs. 15 and 16.</p>
	<p>Over gently rolling land.</p>
5.60	<p>Trail road, bears ENE and WSW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R25E</p>
	<p style="text-align: center;">1/4</p>
	<p style="text-align: center;">S16 S15</p>
	<p style="text-align: center;">1990</p>

ORIGINAL

47
BOOK 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS											
80.00	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 9, 10, 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T28N</td><td>R25E</td></tr> <tr><td>S 9</td><td>S10</td></tr> <tr><td>S16</td><td>S15</td></tr> <tr><td colspan="2">1990</td></tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 80 lks. S. of a trail road, bears ESE and WNW.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p>	T28N	R25E	S 9	S10	S16	S15	1990			
T28N	R25E										
S 9	S10										
S16	S15										
1990											
39.995	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 89°55' W., bet. secs. 10 and 15.</p> <p>Over gently rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T28N</td><td>R25E</td></tr> <tr><td colspan="2">S10</td></tr> <tr><td colspan="2">1/4 —</td></tr> <tr><td colspan="2">S15</td></tr> <tr><td colspan="2">1990</td></tr> </table> </div>	T28N	R25E	S10		1/4 —		S15		1990	
T28N	R25E										
S10											
1/4 —											
S15											
1990											
79.99	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 9, 10, 15 and 16.</p>										

ORIGINAL

.. 48

BOOK 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	<p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over gently rolling land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R25E 1/4 S 9 S10 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>48.45 Trail road, bears NE and SW.</p> <p>55.90 Graded road, 18 lks. wide, bears SSE and NNW.</p> <p>56.40 The SE cor. of a cemetery enclosure, 125 x 100 ft., barbed wire, 4 strands, long side extends N. 84° W., bears West, 1.06 chs. dist.</p> <p>80.00 Point for the cor. of secs. 3, 4, 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R25E S 4 S 3 ----- S 9 S10 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/>
--------	---

ORIGINAL

BOOK⁴⁹ 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	From the cor. of secs. 2, 3, 10 and 11.
	N. 89°55' W., bet. secs. 3 and 10.
	Over gently rolling land.
16.80	Graded road, 18 lks. wide, bears SE and NW.
39.99	Point for the 1/4 sec. cor. of secs. 3 and 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	26 ins. in the ground, with brass cap mkd.
	T28N R25E
	S 3
	1/4 —
	S10
	1990
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic
	case beneath the stainless steel post.
56.30	Graded road, 18 lks. wide, bears NNE and SSW.
79.98	The cor. of secs. 3, 4, 9 and 10.
	Land, gently rolling.
	Soil, sandy loam.
	No timber; native grasses and scattered brush.
	N. 0°02' W., bet. secs. 3 and 4.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	26 ins. in the ground, with brass cap mkd.
	T28N R25E
	1/4
	S 4 S 3
	1990
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic
	case beneath the stainless steel post.

ORIGINAL

.. 50

BOOK 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
71.30	Graded road, 18 lks. wide, bears SE and NW.
76.67	Intersect the S. side of a shed, 21 x 17 ft., the SE cor. bears ESE., 5 lks. dist., long side extends NNE.
76.01	The SE cor. of a house, 24 x 16 ft., long side extends NNE, bears West, 8 lks. dist.
80.00	Point for the 80 1/16 sec. cor. of secs. 3 and 4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. below the surface of the ground, with brass cap mkd.
	<p>T28N R25E 80 1/16 S 4 S 3 1990</p>
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
	Cor. is located 23 lks. W. of W. edge of a trash pit.
89.69	Point for the closing cor. of secs. 3 and 4, at intersection with the N. Bdy. of the Tp., identical with the Seventh Standard Parallel North.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p>T29N R25E S35 ----- S 4 S 3 T28N R25E CC 1990</p>
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
	From this cor. point, the stan. 1/4 sec. cor. of sec. 33, T. 29 N., R. 25 E., bears East, 14.85 chs. dist., set, mkd. and witnessed as described in the field note record of the survey of the Seventh Standard Parallel North, through R. 25 E., executed concurrently under this group.

ORIGINAL

.. 51

BOOK 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	<p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/> <p>The point for the 1/4 sec. cor. of sec. 3 only, T. 28 N., R. 25 E., is at midpoint on the N. bdy. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R25E ----- 1/4 S 3 T28N R25E 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. cor. of secs. 33 and 34, T. 29 N., R. 25 E., bears East, 14.865 chs. dist., set, mkd. and witnessed as described in the field note record of the survey of the Seventh Standard Parallel North, through R. 25 E., executed concurrently under this group.</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 32 and 33.</p> <p>Over rolling land.</p> <p>28.05 Trail road, bears ENE and WSW.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R25E 1/4 S32 S33 1990</p> <p>Cor. is located 30 lks. S. of a power line, bears ENE and WSW.</p>
--------	--

ORIGINAL

52

BOOK 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS									
48.40	South right-of-way fence of Arizona State Highway No. 264, barbed wire, 5 strands, parallels highway.								
49.88	Center line, Arizona State Highway No. 264, asphalt pavement, 38 lks. wide, bears ENE and WSW.								
51.48	North right-of-way fence of Arizona State Highway No. 264, barbed wire, 5 strands, parallels highway.								
79.75	Trail road, bears ESE and WNW.								
80.00	<p>Point for the cor. of secs. 28, 29, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 5px;">T28N</td> <td style="padding: 2px 5px;">R25E</td> </tr> <tr> <td style="padding: 2px 5px;">S29</td> <td style="padding: 2px 5px;">S28</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 2px 5px;">S32</td> <td style="border-top: 1px solid black; padding: 2px 5px;">S33</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 5px;">1990</td> </tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 89°55' W., bet. secs. 28 and 33.</p> <p>Over gently rolling land.</p>	T28N	R25E	S29	S28	S32	S33	1990	
T28N	R25E								
S29	S28								
S32	S33								
1990									
8.10	Trail road, bears NE and SW.								
19.15	Center shaft of a windmill, bears South, 8.96 chs. dist.								
19.30	Trail road, bears NNE and SSW.								
40.005	<p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								

ORIGINAL

53

BOOK 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T28N R25E S28 1/4 — S33 1990</p>
80.01	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 28, 29, 32 and 33.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/>
13.20	<p>N. 0°03' W., bet. secs. 28 and 29.</p> <p>Over rolling land.</p> <p>Trail road, bears NNE and SSW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R25E 1/4 S29 S28 1990</p>
80.00	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 20, 21, 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R25E S20 S21 — — S29 S28 1990</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>

ORIGINAL

54

BOOK 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/>
	<p>From the cor. of secs. 21, 22, 27 and 28.</p>
	<p>N. 89°55' W., bet. secs. 21 and 28.</p>
	<p>Over gently rolling land.</p>
20.70	<p>Graded road, 27 ft. wide, bears NNE and SSW.</p>
27.45	<p>Trail road, bears SSE and NNW.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R25E S21 1/4 — S28 1990</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
52.50	<p>Graded road, 38 lks. wide, bears SE and NW.</p>
80.02	<p>The cor. of secs. 20, 21, 28 and 29.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/>
	<p>N. 0°03' W., bet. secs. 20 and 21.</p>
	<p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

CHAINS	
	<p style="text-align: center;">T28N R25E 1/4 S20 S21 1990</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
42.15	<p>Graded road, 38 lks. wide, bears SE and NW.</p>
80.00	<p>Point for the cor. of secs. 16, 17, 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R25E S17 S16 ----- S20 S21 1990</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/>
	<p>From the cor. of secs. 15, 16, 21 and 22.</p>
	<p>N. 89°55' W., bet. secs. 16 and 21.</p>
	<p>Over gently rolling land.</p>
18.25	<p>Trail road, bears NE and SW.</p>
21.00	<p>Trail road, bears NNE and SSW.</p>
25.04	<p>The NW cor. of a house, 38 x 25 ft., long side extends SSW., bears South, 7.41 chs. dist.</p>
25.75	<p>The NW cor. of a house, 22 x 12 ft., long side extends S. 11° W., bears South, 14.05 chs. dist.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

ORIGINAL

56

BOOK 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T28N R25E S16 1/4 — S21 1990</p>
80.04	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/>
40.00	<p>N. 0°03' W., bet. secs. 16 and 17.</p> <p>Over gently rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>
64.40	<p style="text-align: center;">T28N R25E 1/4 S17 S16 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Trail road, bears ENE and WSW.</p>
75.20	<p>Trail road, bears ENE and WSW.</p>
80.00	<p>Point for the cor. of secs. 8, 9, 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R25E S 8 S 9 ----- S17 S16 1990</p>

ORIGINAL

57

BOOK 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/>
	<p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 89°55' W., bet. secs. 9 and 16.</p> <p>Over gently rolling land.</p>
16.35	Trail road, bears NNE and SSW.
19.60	Trail road, bears SSE and NNW.
40.03	Point for the 1/4 sec. cor. of secs. 9 and 16.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R25E S 9 1/4 — S16 1990</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
80.06	<p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/>
	<p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over gently rolling land.</p>
9.45	Trail road, bears SE and NW.
11.85	Trail road, bears ESE and WNW.
31.80	The southernmost cor. of a house, 15 x 15 ft., one side extends NE, bears West, 10.33 chs. dist.

ORIGINAL

BOOK⁵⁸ 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T28N R25E 1/4 S 8 S 9 1990</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
55.30	Trail road, bears SE and NW.
80.00	<p>Point for the cor. of secs. 4, 5, 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T28N R25E S 5 S 4 ----- S 8 S 9 1990</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 89°55' W., bet. secs. 4 and 9.</p> <p>Over gently rolling land.</p>
40.035	<p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

ORIGINAL

59
BOOK 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T28N R25E S 4 1/4 — S 9 1990</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
58.65	<p>Trail road, bears SSE and NNW.</p>
80.07	<p>The cor. of secs. 4, 5, 8 and 9.</p>
	<p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/>
	<p>N. 0°03' W., bet. secs. 4 and 5.</p>
	<p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R25E 1/4 S 5 S 4 1990</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
58.95	<p>Trail road, bears ENE and WSW.</p>
75.00	<p>Trail road, bears NE. and SW.</p>
80.00	<p>Point for the 80 1/16 sec. cor. of secs. 4 and 5.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

ORIGINAL

BOOK⁶⁰ 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	<p style="text-align: center;">T28N R25E 80 1/16 S 5 S 4 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>84.75 Trail road, bears SSE and NNW.</p> <p>89.58 Point for the closing cor. of secs. 4 and 5, at intersection with the N. Bdy. of the Tp., identical with the Seventh Standard Parallel North.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R25E S32 ----- S 5 S 4 T28N R25E CC 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 32, T. 29 N., R. 25 E., bears East, 14.94 chs. dist., set, mkd. and witnessed as described in the field note record of the survey of the Seventh Standard Parallel North, through R. 25 E., executed concurrently under this group.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/> <p>The point for the 1/4 sec. cor. of sec. 4 only, T. 28 N., R. 25 E., is at midpoint on the N. bdy. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
--------	--

ORIGINAL

BOOK⁶¹ 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS

T29N R25E

1/4 S 4
T28N R25E
1990

Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

From this cor. point, the stan. cor. of secs. 32 and 33, T. 29 N., R. 25 E., bears East, 14.895 chs. dist., set, mkd. and witnessed as described in the field note record of the survey of the Seventh Standard Parallel North, through R. 25 E., executed concurrently under this group.

From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described.

N. 0°03' W., bet. secs. 31 and 32.

Over rolling land.

- 22.75 Trail road, bears ENE and WSW.
- 30.50 Power line, bears E. and W.
- 34.42 South right-of-way fence of Arizona State Highway No. 264, barbed wire, 5 strands, parallels highway.
- 35.97 Center line, Arizona State Highway No. 264, asphalt pavement, 38 lks. wide, bears ENE and WSW.
- 37.50 North right-of-way fence of Arizona State Highway No. 264, barbed wire, 5 strands, parallels highway.
- 40.00 Point for the 1/4 sec. cor. of secs. 31 and 32.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T28N R25E
1/4
S31 | S32
1990

Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

ORIGINAL

BOOK 5355⁶²

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS															
46.10	The NE cor. of a house, 32 x 24 ft., long side extends SSW., bears West, 20.98 chs. dist.														
50.50	The NE cor. of a house, 35 x 28 ft., long side extends SSW., bears West, 27.73 chs. dist.														
60.84	The NE cor. of a house, 27 x 15 ft., long side extends NW, bears West, 11.24 chs. dist.														
62.77	The NE cor. of a house, 28 x 20 ft., long side extends WNW, bears West, 12.10 chs. dist.														
64.30	Trail road, bears NE and SW.														
80.00	Point for the cor. of secs. 29, 30, 31 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table border="0"> <tr><td>T28N</td><td>R25E</td></tr> <tr><td>S30</td><td> </td><td>S29</td></tr> <tr><td colspan="3" style="text-align: center;">— —</td></tr> <tr><td>S31</td><td> </td><td>S32</td></tr> <tr><td colspan="3" style="text-align: center;">1990</td></tr> </table> </div> Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post. Land, rolling. Soil, sandy loam. No timber; native grasses and scattered brush.	T28N	R25E	S30		S29	— —			S31		S32	1990		
T28N	R25E														
S30		S29													
— —															
S31		S32													
1990															
	<hr/>														
	From the cor. of secs. 28, 29, 32 and 33. N. 89°55' W., bet. secs. 29 and 32. Over gently rolling land.														
40.00	Point for the 1/4 sec. cor. of secs. 29 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.														

ORIGINAL

63
BOOK 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	T28N R25E S29 1/4 — S32 1990
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
67.32	The SE cor. of a house, 28 x 15 ft., long side extends NNE., bears North, 14.74 chs. dist.
68.22	The SE cor. of a house, 32 x 16 ft., long side extends NNW, bears North, 10.14 chs. dist.
80.00	The cor. of secs. 29, 30, 31 and 32. Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.
	N. 89°55' W., bet. secs. 30 and 31. Over gently rolling land.
25.77	The NE cor. of a house, 30 x 16 ft., long side extends SSW, bears South, 4.88 chs. dist.
32.80	Trail road, bears SE and NW.
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T28N R25E S30 1/4 — S31 1990
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
54.60	Graded road, 38 lks. wide, bears SE and NW.
62.05	Trail road, bears NNE and SSW.

ORIGINAL

64

BOOK 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
79.12	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p>
40.00	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over gently rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T28N R25E 1/4 S30 S29 1990</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
44.60	Trail road, bears ESE and WNW.
80.00	<p>Point for the cor. of secs. 19, 20, 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T28N R25E S19 S20 ----- S30 S29 1990</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p>

ORIGINAL

65

BOOK 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>N. 89°55' W., bet. secs. 20 and 29.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R25E S20 1/4 — S29 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/> <p>N. 89°55' W., bet. secs. 19 and 30.</p> <p>Over gently rolling land.</p>
39.45	<p>Trail road, bears NE and SW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R25E S19 1/4 — S30 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
64.95	<p>Trail road, bears ESE and WNW.</p>

ORIGINAL

66

BOOK 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
74.50	Trail road, bears SSE and NNW.
79.00	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p> <p>Over gently rolling land.</p>
25.71	Center of a round metal water storage unit, 15 ft. diam., bears East, 22.08 chs. dist.
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <p>T28N R25E 1/4 S19 S20 1990</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
42.75	Trail road, bears NE and SW.
52.15	The SE cor. of a house, 24 x 14 ft., long side extends NNE, bears East, 14.35 chs. dist.
80.00	<p>Point for the cor. of secs. 17, 18, 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T28N R25E S18 S17 ----- S19 S20 1990</p> </div>

ORIGINAL

BOOK⁶⁷ 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/>
	<p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89°55' W., bet. secs. 17 and 20.</p> <p>Over gently rolling land.</p>
25.05	Graded road, 38 lks. wide, bears SE and NW.
39.995	<p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R25E S17 1/4 — S20 1990</p>
53.35	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Trail road, bears NE and SW.</p>
79.99	<p>The cor. of secs. 17, 18, 19 and 20.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/>
40.00	<p>N. 89°55' W., bet. secs. 18 and 19.</p> <p>Over gently rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>

ORIGINAL

68

BOOK 5355

Survey of the Subdivisional Lines,

T. 28 N., R. 25 E.,

Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p style="text-align: center;">T28N R25E S18 1/4 — S19 1990</p> <p>from which</p> <p style="padding-left: 40px;">The NE cor. of a cemetery enclosure, 35 x 30 ft., barbed wire, 5 strands, bears S. 4° E., 4.045 chs. dist., long side extends WNW.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>78.90 The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°03' W., bet. secs. 17 and 18.</p> <p>Over gently rolling land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T28N R25E 1/4 S18 S17 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
---------------	---

ORIGINAL

.. 69 -
BOOK 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS											
80.00	<p>Point for the cor. of secs. 7, 8, 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T28N</td> <td>R25E</td> </tr> <tr> <td>S 7</td> <td>S 8</td> </tr> <tr> <td>S18</td> <td>S17</td> </tr> <tr> <td colspan="2">1990</td> </tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/>	T28N	R25E	S 7	S 8	S18	S17	1990			
T28N	R25E										
S 7	S 8										
S18	S17										
1990											
	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 89°56' W., bet. secs. 8 and 17.</p> <p>Over gently rolling land.</p>										
39.99	<p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T28N</td> <td>R25E</td> </tr> <tr> <td>S 8</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S17</td> <td></td> </tr> <tr> <td colspan="2">1990</td> </tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>	T28N	R25E	S 8		1/4	—	S17		1990	
T28N	R25E										
S 8											
1/4	—										
S17											
1990											
77.65	<p>Graded road, 38 lks. wide, bears SE and NW.</p>										
79.98	<p>The cor. of secs. 7, 8, 17 and 18, hereinbefore described.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/>										

ORIGINAL

70
BOOK 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	N. 89°55' W., bet. secs. 7 and 18.
	Over gently rolling land.
6.30	Trail road, bears NNE and SSW.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T28N R25E
	S 7
	1/4 —
	S18
	1990
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
76.30	Graded road, 30 lks. wide, bears NNE and SSW.
78.80	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.
	Land, gently rolling.
	Soil, sandy loam.
	No timber; native grasses and scattered brush.
	From the cor. of secs. 7, 8, 17 and 18.
	N. 0°03' W., bet. secs. 7 and 8.
	Over gently rolling land.
3.50	Graded road, 38 lks. wide, bears SE and NW.
19.60	Trail road, bears ESE and WNW.
31.20	Trail road, bears NNE and SSW.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

ORIGINAL

.. -71 -
BOOK 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T28N R25E 1/4 S 7 S 8 1990</p>
80.00	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 5, 6, 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R25E S 6 S 5 ----- S 7 S 8 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>N. 89°56' W., bet. secs. 5 and 8.</p> <p>Over gently rolling land.</p>
31.05	Trail road, bears SE and NW.
37.60	Trail road, bears SSE and NNW.
39.98	<p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	T28N R25E S 5 1/4 — S 8 1990
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
62.40	Trail road, bears NNE and SSW.
79.96	The cor. of secs. 5, 6, 7 and 8. Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.
	N. 89°55' W., bet. secs. 6 and 7. Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 7. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T28N R25E S 6 1/4 — S 7 1990
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
50.40	Graded road, 38 lks. wide, bears SE and NW.
78.72	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described. Land, gently rolling. Soil, sandy loam. No timber; native grasses and scattered brush.
	From the cor. of secs. 5, 6, 7 and 8.

ORIGINAL

73
BOOK 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>N. 0°03' W., bet. secs. 5 and 6.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R25E 1/4 S 6 S 5 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the 80 1/16 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R25E 80 1/16 S 6 S 5 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
89.47	<p>Point for the closing cor. of secs. 5 and 6, at intersection with the N. Bdy. of the Tp., identical with the Seventh Standard Parallel North.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R25E S31 ----- S 6 S 5 T28N R25E CC 1990</p>

ORIGINAL

74
BOOK 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS

Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 29 N., R. 25 E., bears East, 14.89 chs. dist., set, mkd. and witnessed as described in the field note record of the survey of the Seventh Standard Parallel North, through R. 25 E., executed concurrently under this group.

Land, gently rolling.

Soil, sandy loam.

No timber; native grasses and scattered brush.

The point for the 1/4 sec. cor. of sec. 5 only, T. 28 N., R. 25 E., is at midpoint on the N. bdy. of sec. 5.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T29N R25E

1/4 S 5
T28N R25E
1990

Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

From this cor. point, the stan. cor. of secs. 31 and 32, T. 29 N., R. 25 E., bears East, 14.915 chs. dist., set, mkd. and witnessed as described in the field note record of the survey of the Seventh Standard Parallel North, through R. 25 E., executed concurrently under this group.

The point for the 1/4 sec. cor. of sec. 6 only, T. 28 N., R. 25 E., is at 40.00 chs. westing from the closing cor. of secs. 5 and 6, on the N. bdy. of sec. 6.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T29N R24E

1/4 S 6
T28N R25E
1990

ORIGINAL

.. 75

BOOK 5355

Survey of the Subdivisional Lines,
T. 28 N., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS

Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case and a yellow-green golf ball, mkd. PINNACLE 4, beneath the stainless steel post.

From this cor. point, the stan. cor. of T. 29 N., Rs. 24 and 25 E., bears East, 14.89 chs. dist., set, mkd. and witnessed as described in the field note record of the survey of the Seventh Standard Parallel North, through R. 24 E., executed concurrently under this group.

GENERAL DESCRIPTION

The area surveyed is within the Navajo Indian Reservation, approximately 7 miles west of Ganado, Arizona. The terrain is generally gently rolling land, with low hills in the southern portion of the township. There are a few washes, with the drainage being northerly.

Elevation varies from 6,100 to 6,600 feet above sea level. The soil is mostly sandy loam, with a few areas of exposed sandstone bedrock in the hills. The vegetation consists of native grasses, greasewood and rabbit brush, with scattered juniper and piñon in the southern portion. There is no marketable timber.

Access to the township is provided by U.S. Highway No. 191 in the east, Arizona State Highway No. 264 in the south, and numerous graded and trail roads.

A few permanent residences are scattered throughout the township. Much of the township is used for the grazing of sheep, goats, cattle and horses.

The mean magnetic declination is 12 1/2° E.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Jones Curtiss	Surveying Technician
Daniel Bryan	Navajo Engineering Technician
Nelson Kinsel	Navajo Engineering Technician
Reuben Mason	Navajo Engineering Technician
Barney Woodie	Navajo Engineering Technician

ORIGINAL

BOOK 5355

77

CERTIFICATE OF SURVEY

We, William F. Olver and John A. Pex, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 22nd day of November, 1989, we have surveyed the west boundary, identical with the Sixth Guide Meridian East, the south and east boundaries, and the subdivisional lines of Township 28 North, Range 25 East, of the Gila and Salt River Meridian, in the state of Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973 and in specific manner described in the foregoing field notes.

April 13, 1992
(Date)

William F. Olver
(Project Manager)

APRIL 2, 1992
(Date)

John A. Pex
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
New Mexico State Office
Santa Fe, New Mexico

The foregoing field notes of the survey of the West Boundary, identical with the Sixth Guide Meridian East, the south and east boundaries, and the subdivisional lines of Township 28 North, Range 25 East, Gila and Salt River Meridian, executed by William F. Olver and John A. Pex, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

APR 28 1992
(Date)

Jessie L. Talbot
Acting (Chief Cadastral Surveyor of Arizona)

CERTIFICATE OF TRANSCRIPT

I Certify that the foregoing transcript of the field notes of the above-described surveys in T. 28 N., R. 25 E., Gila and Salt River Meridian, Arizona is a true copy of the original field notes.

(Date)

(Chief Cadastral Surveyor of Arizona)