

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES  
OF THE

---

SURVEY OF

---

THE SEVENTH STANDARD PARALLEL NORTH (SOUTH BOUNDARY),

---

THE EAST AND NORTH BOUNDARIES,

---

AND

---

THE SUBDIVISIONAL LINES

---

OF

---

TOWNSHIP 29 NORTH, RANGE 26 EAST

---

Of the Gila and Salt River Meridian,

In the State of Arizona

---

EXECUTED BY

Steve D. Cully and William F. Olver, Cadastral Surveyors

---

Under Special Instructions dated and approved November 22, 1989, which provided for the surveys included under Group Number 715 and assignment instructions dated January 28, 1991 and December 18, 1989.

Survey commenced January 4, 1990

Survey completed May 21, 1991

INDEX DIAGRAM

TOWNSHIP 29 NORTH, RANGE 26 EAST,

21	21	19	18	17	16
6	72 5	57 4	48 3	38 2	30 1 15
71	70	57	47	38	30
7	69 8	56 9	46 10	37 11	29 12 14
68	67	55	45	36	28
18	66 17	54 16	44 15	35 14	27 13 13
65	64	53	44	35	26
19	63 20	52 21	43 22	34 23	25 24 12
63	62	51	42	33	25
30	61 29	50 28	41 27	32 26	24 25 11
60	59	49	40	32	23
31	58 32	48 33	39 34	31 35	22 36 10
4	5	6	7	8	9

T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes describe the survey of the Seventh Standard Parallel North (south boundary), the east and north boundaries and the subdivisional lines of Township 29 North, Range 26 East, Gila and Salt River Meridian, Arizona.

This survey supersedes portions of Township 2 and 3 North, Range 10 West of the Navajo Special Meridian. The survey history of that portion of the superseded Navajo Special Meridian is included in these notes for informational purposes only.

The boundaries and subdivisional lines of Townships 2 and 3 North, Range 10 West, Navajo Special Meridian, were surveyed by Ehud N. Darling in 1870.

The west boundary of the township was surveyed by Daniel N. Patterson and Leonard R. Sandoval in 1989 - 91.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated November 22, 1989, for Group No. 715, Arizona.

The directions of all lines were determined by direct hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured with a Lietz Set 4 total station instrument.

The geographic position of the southeast corner of the township, as determined from a tie made to Electronic Control Point 6, hereinafter described, is as follows:

Latitude: 35°52'02.96" N., Longitude: 109°29'36.96" W. NAD27

The geographic position of Electronic Control Point 6, hereinafter described, was determined by the technique of relative positioning utilizing the Motorola Golden Eagle Global Positioning System Satellite Surveyor. "GANADO" and "LOHALI", first order triangulation stations established by the U.S. Coast and Geodetic Survey, were used as the control stations. The geographic position is as follows:

Latitude: 35°52'05.75" N., Longitude: 109°29'58.36" W. NAD27

The mean magnetic declination, as taken from the 1985 magnetic declination map published by U.S. Geological Survey, is 12 1/2° E.

Survey of  
The Seventh Standard Parallel North (South Boundary),  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Beginning at the stan. cor. of T. 29 N., Rs. 25 and 26 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. SC T29N R25E R26E S36 S31 1990.</p>
	<p>East, on the the S. bdy. of sec. 31.</p>
	<p>Over rolling land.</p>
17.81	<p>W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.</p>
19.43	<p>Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears SSE and NNW.</p>
21.05	<p>E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.</p>
40.00	<p>Point for the stan. 1/4 sec. cor. of sec. 31.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">SC T29N R26E 1/4 S31 ----- 1990</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Cor. is located on W. edge of a canyon, 300 lks. wide, 50 ft. deep, drains NW.</p>
	<p>Enter rugged land.</p>
80.00	<p>Point for the stan. cor. of secs. 31 and 32.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

Survey of  
The Seventh Standard Parallel North (South Boundary),  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">SC T29N R26E S31   S32 ----- 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on N. edge of a wash, 18 lks. wide, 1 ft. deep, drains WNW.</p> <p>Land, rolling to rugged. Soil, rocky and sandy clay. Timber, juniper; undergrowth, scattered native grasses.</p> <hr/> <p>East, on the S. bdy. of sec. 32.</p> <p>Over rugged land.</p>
40.00	<p>True point for the stan. 1/4 sec. cor. of sec. 32, falls on the edge of a wash, 8 lks. wide, 5 ft. deep, drains NNE; impracticable to monument.</p>
41.00	<p>Point selected for the witness cor. to the stan. 1/4 sec. cor. of sec. 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WC SC T29N R26E 1/4 S32 ←----- 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

Survey of  
The Seventh Standard Parallel North (South Boundary),  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>Point for the stan. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>SC T29N R26E S32   S33 ----- 1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rugged. Soil, sandy clay and clay. No timber; scattered native grasses.</p> <hr/> <p>East, on the S. bdy. of sec. 33.</p> <p>Over nearly level land.</p>
40.00	<p>Point for the stan. 1/4 sec. cor. of sec. 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>SC T29N R26E 1/4 S33 ----- 1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
76.00	<p>Graded road, 15 lks. wide, bears SSE and NNW.</p>
80.00	<p>Point for the stan. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of  
The Seventh Standard Parallel North (South Boundary),  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	SC T29N R26E S33   S34 <hr style="width: 50%; margin: auto;"/> 1990
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.  Cor. is located 27 lks. W. of a trail road, bears N. and S.  Land, nearly level. Soil, sandy clay No timber; scattered native grasses.
	<hr/> East, on the S. bdy. of sec. 34.  Over nearly level land.
18.20	Bis-ii-ah Wash, 136 lks. wide, 6 ft. deep, drains NNW.
30.45	Trail road, bears SE and NW.
40.00	Point for the stan. 1/4 sec. cor. of sec. 34.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	SC T29N R26E 1/4 S34 <hr style="width: 50%; margin: auto;"/> 1990
44.00	Wash, 15 lks. wide, 3 ft. deep, drains NNW.
80.00	Point for the stan. cor. of secs. 34 and 35.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

Survey of  
The Seventh Standard Parallel North (South Boundary),  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	SC T29N R26E S34   S35 <hr style="width: 50%; margin: auto;"/> 1990
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.  Land, nearly level. Soil, sandy clay. No timber; scattered native grasses.
	<hr/> East, on the S. bdy. of sec. 35.  Over nearly level land.
34.00	Wash, 45 lks. wide, 10 ft. deep, drains WNW.
40.00	Point for the stan. 1/4 sec. cor. of sec. 35.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	SC T29N R26E 1/4 S35 <hr style="width: 50%; margin: auto;"/> 1990
62.95	Trail road, bears ENE and WSW.
64.00	Wash, 20 lks. wide, 3 ft. deep, drains WNW.
80.00	Point for the stan. cor. of secs. 35 and 36.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of  
The Seventh Standard Parallel North (South Boundary),  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<div style="text-align: center;"> <p>SC T29N R26E S35   S36 ----- 1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay and clay. No timber; scattered native grasses.</p> <hr/>
	<p>East, on the S. bdy. of sec. 36.</p> <p>Over rolling and rugged land.</p>
<p>40.00</p>	<p>Point for the stan. 1/4 sec. cor. of sec. 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>SC T29N R26E 1/4 S36 ----- 1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
<p>80.00</p>	<p>Point for the stan. cor. of T. 29 N., Rs. 26 and 27 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>SC T29N R26E   R27E S36   S31 ----- 1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

Survey of  
The Seventh Standard Parallel North (South Boundary),  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point, Electronic Control Point 6, monumented with an aluminum post, 36 ins. long, 5/8 in. diam., set flush with the surface of the ground, with magnetized aluminum cap mkd. EC-6 1989, bears N. 80°53.5' W., 27.035 chs. dist.</p> <p>Land, rolling to rugged. Soil, rocky clay. No timber; scattered native grasses.</p> <hr/> <p style="text-align: center;">Survey of the East Boundary, T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the stan. cor. of T. 29 N., Rs. 26 and 27 E., hereinbefore described.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R26E R27E 1/4 S36   S31 1991</p>
48.70	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Wash, 113 lks. wide, 20 ft. deep, drains NNW.</p>
51.10	<p>Power line, bears ENE and WSW.</p>
61.90	<p>Trail road, bears NE and SW.</p>
80.00	<p>Point for the cor. of secs. 25, 30, 31, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the East Boundary,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<table border="1"> <tr> <td colspan="2">T29N</td> </tr> <tr> <td>R26E</td> <td>R27E</td> </tr> <tr> <td>S25</td> <td>S30</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td>S36</td> <td>S31</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T29N		R26E	R27E	S25	S30	-----		S36	S31	1991	
T29N													
R26E	R27E												
S25	S30												
-----													
S36	S31												
1991													
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, rocky clay. No timber; scattered native grasses.</p> <hr/> <p>North, bet. secs. 25 and 30.</p> <p>Over rolling land.</p>												
25.90	Wash, 300 lks. wide, 50 ft. deep, drains W.												
40.00	Point for the 1/4 sec. cor. of secs. 25 and 30.												
	<p>Set a magnet in a 1 x 1 x 2 5/8 ins. white plastic case, 12 ins. below the surface of the ground.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45° E., 100 ft. dist., with brass cap mkd. T29N R27E 1/4 S30 RM 100 FT TO COR 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45° W., 100 ft. dist., with brass cap mkd. T29N R26E 1/4 S25 RM 100 FT TO COR 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>												
58.20	Trail road, bears E. and W.												
61.50	Power line, bears E. and W.												

Survey of the East Boundary,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS													
64.05	NE cor. of stucco house, 19 x 16 ft., bears West, 4.70 chs. dist., long side bears SSW.												
73.15	Trail road, bears NNE and SSW.												
75.40	Trail road, bears ENE and WSW.												
80.00	Point for the cor. of secs. 19, 24, 25, and 30.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T29N</td></tr> <tr><td style="text-align: center;">R26E</td><td style="text-align: center;">R27E</td></tr> <tr><td style="text-align: center;">S24</td><td style="text-align: center;">S19</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S25</td><td style="text-align: center;">S30</td></tr> <tr><td colspan="2" style="text-align: center;">1991</td></tr> </table> Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.  Land, rolling. Soil, rocky clay. Timber, sparse juniper; undergrowth, scattered native grasses. <hr/>	T29N		R26E	R27E	S24	S19	-----		S25	S30	1991	
T29N													
R26E	R27E												
S24	S19												
-----													
S25	S30												
1991													
	North, bet. secs. 19 and 24.  Over rolling land.												
40.00	Point for the 1/4 sec. cor. of secs. 19 and 24.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T29N</td></tr> <tr><td style="text-align: center;">R26E</td><td style="text-align: center;">R27E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S24</td><td style="text-align: center;">S19</td></tr> <tr><td colspan="2" style="text-align: center;">1991</td></tr> </table> Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.	T29N		R26E	R27E	1/4		S24	S19	1991			
T29N													
R26E	R27E												
1/4													
S24	S19												
1991													
54.30	Tah-aith-cheed wash, 114 lks. wide, 3 ft. deep, drains W.												

Survey of the East Boundary,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS													
80.00	<p>Point for the cor. of secs. 13, 18, 19, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T29N</td></tr> <tr><td>R26E</td><td>R27E</td></tr> <tr><td>S13</td><td>S18</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S24</td><td>S19</td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, rocky clay. Timber, scattered juniper and piñon; undergrowth, scattered native grasses.</p> <hr/> <p>North, bet. secs. 13 and 18.</p> <p>Over rolling land.</p>	T29N		R26E	R27E	S13	S18	<hr/>		S24	S19	1991	
T29N													
R26E	R27E												
S13	S18												
<hr/>													
S24	S19												
1991													
5.00	Wash, 114 lks. wide, 3 ft. deep, drains NW.												
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T29N</td></tr> <tr><td>R26E</td><td>R27E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S13</td><td>S18</td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T29N		R26E	R27E	1/4		S13	S18	1991			
T29N													
R26E	R27E												
1/4													
S13	S18												
1991													
80.00	Point for the cor. of secs. 7, 12, 13, and 18.												

Survey of the East Boundary,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>												
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T29N</td> </tr> <tr> <td style="text-align: center;">R26E</td> <td style="text-align: center;">R27E</td> </tr> <tr> <td style="text-align: center;">S12</td> <td style="text-align: center;">S 7</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S13</td> <td style="text-align: center;">S18</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T29N		R26E	R27E	S12	S 7	-----		S13	S18	1991	
T29N													
R26E	R27E												
S12	S 7												
-----													
S13	S18												
1991													
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>												
	<p>Land, rolling. Soil, rocky clay. No timber; scattered native grasses.</p>												
	<hr/> <p>North, bet. secs. 7 and 12.</p>												
	<p>Over rugged land.</p>												
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p>												
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>												
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T29N</td> </tr> <tr> <td style="text-align: center;">R26E</td> <td style="text-align: center;">R27E</td> </tr> <tr> <td colspan="2" style="text-align: center;">1/4</td> </tr> <tr> <td style="text-align: center;">S12</td> <td style="text-align: center;">S 7</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T29N		R26E	R27E	1/4		S12	S 7	1991			
T29N													
R26E	R27E												
1/4													
S12	S 7												
1991													
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>												
46.65	<p>Graded road, 42 lks. wide, bears E. and W.</p>												
80.00	<p>Point for the cor. of secs. 1, 6, 7, and 12.</p>												
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>												

Survey of the East Boundary,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona.

CHAINS													
	<div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T29N</td></tr> <tr><td>R26E</td><td>R27E</td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S12</td><td>S 7</td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A piñon, 8 ins. diam., bears N. 57 3/4° W., 54 lks. dist., mkd. T29N R26E S1 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rugged. Soil, rocky clay. No timber; scattered native grasses.</p>	T29N		R26E	R27E	S 1	S 6	-----		S12	S 7	1991	
T29N													
R26E	R27E												
S 1	S 6												
-----													
S12	S 7												
1991													
<p>40.00</p>	<p>North, bet. secs. 1 and 6.</p> <p>Over rugged land.</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>												
<p>77.00</p>	<div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T29N</td></tr> <tr><td>R26E</td><td>R27E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on the S. side of a small ridge, bears E. and W.</p> <p>Point selected for the witness cor. to the cor. of Tps. 29 and 30 N., Rs. 26 and 27 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>	T29N		R26E	R27E	1/4		S 1	S 6	1991			
T29N													
R26E	R27E												
1/4													
S 1	S 6												
1991													

Survey of the East Boundary,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	WC T30N R26E   R27E S36   S31 <hr style="width: 50%; margin: 0 auto;"/> S 1   S 6 T29N 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
77.30	S. rim of Nazlini Creek Canyon, bears ENE and WSW.
80.00	True point for the cor. of Tps. 29 and 30 N., Rs. 26 and 27 E., falls on N. wall of Nazlini Creek Canyon, bears ENE and WSW; impracticable to monument.  Land, rugged. Soil, rocky clay. Timber, scattered piñon and juniper; undergrowth, scattered native grasses.
<hr/> Survey of the North Boundary, T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona	
	From the true point for the cor. of Tps. 29 and 30 N., Rs. 26 and 27 E., hereinbefore described.  S. 89°59' W., bet. secs. 1 and 36.  Over broken land.
3.90	E. rim of Nazlini Creek Canyon, bears SSE and NNW.
10.10	S. rim of Nazlini Creek Canyon, bears SSE and NNW.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 36.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the North Boundary,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T30N R26E S36 1/4 — S 1 T29N 1991</p>
	<p>from which</p> <p style="text-align: center;">A piñon, 15 ins. diam., bears S. 89 1/4° E., 143 1/2 lks. dist., mkd. 1/4 S1 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
55.55	Tah-aith-cheed Wash, 152 lks. wide, 10 ft. deep, drains NE.
80.00	<p>Point for the cor. of secs. 1, 2, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R26E S35   S36 —   — S 2   S 1 T29N 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, broken. Soil, rocky clay. Timber, scattered piñon and juniper; undergrowth, scattered native grasses.</p> <hr/> <p>S. 89°59' W., bet. secs. 2 and 35.</p> <p>Over rugged land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the North Boundary,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T30N R26E S35 1/4 — S 2 T29N 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
53.00	<p>Graded road, 30 lks. wide, bears SSE and NNW.</p>
60.00	<p>Power line, bears SSE and NNW.</p>
80.00	<p>Point for the cor. of secs. 2, 3, 34, and 35.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T30N R26E S34   S35 —   — S 3   S 2 T29N 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Land, rugged. Soil, rocky clay. Timber, scattered piñon and juniper; undergrowth, scattered native grasses.</p>
	<p>S. 89°59' W., bet. secs. 3 and 34.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the North Boundary,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T30N R26E S34 1/4 — S 3 T29N 1991</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 3, 4, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T30N R26E S33   S34 —   — S 4   S 3 T29N 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered native grasses.</p>
	<hr/> <p>S. 89°59' W., bet. secs. 4 and 33.</p>
	<p>Over nearly level land.</p>
32.80	<p>Wash, 455 lks. wide, 4 ft. deep, drains ENE.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 33.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the North Boundary,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T30N R26E S33 1/4 — S 4 T29N 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
53.80	Bis-ii-ah Wash, 380 lks. wide, 6 ft. deep, drains ENE.
72.70	Power line, bears NNE and SSW.
74.75	Center of hexagonal hogan, 25 feet diam., bears South, 1.40 chs. dist.
75.30	Power line, bears NNE and SSW.
75.95	NW cor. of stucco house, 30 x 20 ft., bears South, 2.30 chs. dist., long side bears S.
76.70	Trail road, bears NNE and SSW.
77.30	Trail road, bears ENE and WSW.
80.00	Point for the cor. of secs. 4, 5, 32, and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T30N R26E S32   S33 ———— S 5   S 4 T29N 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Land, nearly level. Soil, sandy clay. No timber; scattered native grasses.

Survey of the North Boundary,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>S. 89°59' W., bet. secs. 5 and 32.</p> <p>Over nearly level land.</p>									
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T30N R26E S32 1/4 — S 5 T29N 1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>									
80.00	<p>Point for the cor. of secs. 5, 6, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table border="1" style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 2px;">T30N R26E</td> <td style="padding: 2px;">S31</td> <td style="padding: 2px;">S32</td> </tr> <tr> <td style="padding: 2px;">S 6</td> <td style="padding: 2px;">S 5</td> <td style="padding: 2px;">T29N</td> </tr> <tr> <td colspan="3" style="padding: 2px;">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on a small clay outcrop.</p> <p>Land, nearly level with clay outcrops. Soil, sandy clay and clay. No timber; scattered native grasses.</p>	T30N R26E	S31	S32	S 6	S 5	T29N	1991		
T30N R26E	S31	S32								
S 6	S 5	T29N								
1991										
35.90	<hr style="border: 0.5px solid black;"/> <p>S. 89°59' W., bet. secs. 6 and 31.</p> <p>Over rugged land, on ascent from Beautiful Valley.</p> <p>W. rim of Beautiful Valley, bears SSW and NNW.</p>									

Survey of the North Boundary,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R26E S31 1/4 — S 6 T29N 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Enter gently rolling land.</p>
41.02	<p>E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.</p>
42.49	<p>Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears SSE and NNW.</p>
44.06	<p>W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.</p>
49.70	<p>Power line, bears SSE and NNW.</p>
79.50	<p>The cor. of Tps. 29 and 30 N., Rs. 25 and 26 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T30N R25E R26E S36 S31 S1 S6 T29N 1990.</p> <p>Land, rugged to gently rolling. Soil, sandy clay and clay. No timber; scattered native grasses.</p> <hr/> <p style="text-align: center;">Survey of the Subdivisional Lines, T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the stan. cor. of secs. 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p>

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Over rolling land.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place, in bedrock, with top mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td colspan="2">T29N R26E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S35</td><td>  S36</td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>Deposit a magnet, 7/8 in. diam., 1 in. long, beneath the brass tablet.</p>	T29N R26E		1/4		S35	S36	1991			
T29N R26E											
1/4											
S35	S36										
1991											
80.00	<p>Point for the cor. of secs. 25, 26, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td colspan="2">T29N R26E</td></tr> <tr><td>S26</td><td>  S25</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S35</td><td>  S36</td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay and clay, with scattered sandstone outcrops. No timber; scattered native grasses.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 25 and 36.</p> <p>Over rolling land.</p>	T29N R26E		S26	S25	-----		S35	S36	1991	
T29N R26E											
S26	S25										
-----											
S35	S36										
1991											
39.99	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>										

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	<p style="text-align: center;">T29N R26E S25 1/4 — S36 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>79.98 The cor. of secs. 25, 26, 35, and 36.</p> <p>Land, rolling. Soil, sandy clay and clay. No timber; scattered native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over rolling land.</p> <p>37.60 Wash, 75 lks. wide, 3 ft. deep, drains SW.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R26E 1/4 S26   S25 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>80.00 Point for the cor. of secs. 23, 24, 25, and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R26E S23   S24 —   — S26   S25 1991</p>
--------	--

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay and clay. No timber; scattered native grasses.</p> <hr/>
	<p>From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°59' W., bet. secs. 24 and 25.</p> <p>Over rolling land.</p>
32.30	Trail road, bears ENE and WSW.
39.975	Point for the 1/4 sec. cor. of secs. 24 and 25.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R26E S24 1/4 — S25 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
47.50	Trail road, bears SE and NW.
79.95	The cor. of secs. 23, 24, 25, and 26.
	<p>Land, rolling. Soil, sandy clay and clay. No timber; scattered native grasses.</p> <hr/>
	N. 0°01' W., bet. secs. 23 and 24.
	Over gently rolling land.
28.70	SW cor. of stucco house, 30 x 20 ft., bears East, 9.30 chs. dist., long side bears NNE.

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place, in bedrock, with top mkd.</p> <p style="text-align: center;">T29N R26E 1/4 S23   S24 1991</p> <p>Deposit a magnet, 7/8 in. diam., 1 in. long, beneath the brass tablet.</p>
80.00	<p>Point for the cor. of secs. 13, 14, 23, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R26E S14   S13 ----- S23   S24 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay and clay. No timber; scattered native grasses.</p>
	<p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.</p>
	<p>West, bet. secs. 13 and 24.</p>
	<p>Over rolling land.</p>
5.60	<p>Tah-aith-cheed wash, 300 lks. wide, 30 ft. deep, drains NW.</p>
39.975	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T29N R26E S13 1/4 — S24 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
79.95	The cor. of secs. 13, 14, 23, and 24.  Land, rolling. Soil, sandy clay and clay. No timber; scattered native grasses.
	<hr/> N. 0°01' W., bet. secs. 13 and 14.  Over rolling land.
7.60	Trail road, bears NNE and SSW.
29.70	Wash, 300 lks. wide, 20 ft. deep, drains ENE.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T29N R26E 1/4 S14   S13 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.00	Point for the cor. of secs. 11, 12, 13, and 14.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<table border="0"> <tr> <td>T29N</td> <td>R26E</td> </tr> <tr> <td>S11</td> <td>S12</td> </tr> <tr> <td colspan="2" style="text-align: center;">— —</td> </tr> <tr> <td>S14</td> <td>S13</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T29N	R26E	S11	S12	— —		S14	S13	1991	
T29N	R26E										
S11	S12										
— —											
S14	S13										
1991											
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay and clay. No timber; scattered native grasses.</p> <hr/> <p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 12 and 13.</p> <p>Over rolling land.</p>										
38.60	Tah-aith-cheed wash, 300 lks. wide, 5 ft. deep, drains NNE.										
39.98	Point for the 1/4 sec. cor. of secs. 12 and 13.										
	<table border="0"> <tr> <td>T29N</td> <td>R26E</td> </tr> <tr> <td></td> <td>S12</td> </tr> <tr> <td></td> <td>1/4 —</td> </tr> <tr> <td></td> <td>S13</td> </tr> <tr> <td></td> <td>1991</td> </tr> </table>	T29N	R26E		S12		1/4 —		S13		1991
T29N	R26E										
	S12										
	1/4 —										
	S13										
	1991										
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>										
43.20	Trail road, bears N. and S.										
53.80	Trail road, bears N. and S.										
79.96	The cor. of secs. 11, 12, 13, and 14.										

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay and clay. No timber; scattered native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over gently rolling land.</p>
18.60	Trail road, bears ENE and WSW.
38.95	Trail road, bears NE and SW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29N R26E 1/4 S11   S12 1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
64.00	Graded road, 30 lks. wide, bears NE and SW.
71.10	Graded road, 30 lks. wide, bears SE and NW.
80.00	<p>Point for the cor. of secs. 1, 2, 11, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29N R26E S 2   S 1 ----- S11   S12 1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, gently rolling. Soil, sandy clay and clay. No timber; scattered native grasses.</p> <hr/>
	<p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., hereinbefore described.</p>
	<p>N. 89°59' W., bet. secs. 1 and 12.</p>
	<p>Over rugged and rolling land.</p>
39.985	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T29N R26E S 1 1/4 — S12 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
55.50	<p>Tah-aith-cheed Wash, 75 lks. wide, 10 ft. deep, drains NNW.</p>
60.90	<p>Power line, bears SE and NW.</p>
79.97	<p>The cor. of secs. 1, 2, 11, and 12.</p>
	<p>Land, rugged and rolling. Soil, sandy clay and clay. No timber; scattered native grasses.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 1 and 2.</p>
	<p>Over rolling land.</p>
22.10	<p>Power line, bears SE and NW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T29N R26E 1/4 S 2   S 1 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
79.97	<p>The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, scattered native grasses.</p> <hr/>
	<p>From the stan. cor. of secs. 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p>
	<p>N. 0°01' W., bet. secs. 34 and 35.</p>
	<p>Over nearly level land.</p>
16.90	<p>Wash, 115 lks. wide, 5 ft. deep, drains NW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T29N R26E 1/4 S34   S35 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 26, 27, 34, and 35.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<table border="1"> <tr> <td>T29N</td> <td>R26E</td> </tr> <tr> <td>S27</td> <td>S26</td> </tr> <tr> <td>S34</td> <td>S35</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T29N	R26E	S27	S26	S34	S35	1991			
T29N	R26E										
S27	S26										
S34	S35										
1991											
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay and rocky. No timber; scattered native grasses.</p> <hr/> <p>From the cor. of secs. 25, 26, 35, and 36. S. 89°59' W., bet. secs. 26 and 35. Over rolling land.</p>										
39.99	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>										
	<table border="1"> <tr> <td>T29N</td> <td>R26E</td> </tr> <tr> <td></td> <td>S26</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S35</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T29N	R26E		S26	1/4	—		S35	1991	
T29N	R26E										
	S26										
1/4	—										
	S35										
1991											
79.98	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 26, 27, 34, and 35.</p> <p>Land, rolling. Soil, sandy clay and clay, with sandstone outcrops. No timber; scattered native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 26 and 27. Over rolling land.</p>										
15.55	<p>Trail road, bears E. and W.</p>										

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
31.80	Wash, 76 lks. wide, 4 ft. deep, drains WSW.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 27.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <p>T29N R26E 1/4 S27   S26 1991</p> </div> Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.00	Point for the cor. of secs. 22, 23, 26, and 27.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <p>T29N R26E S22   S23 ----- S27   S26 1991</p> </div> Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.  Land, rolling. Soil, sandy clay and sand. No timber; scattered native grasses.
	<hr/> From the cor. of secs. 23, 24, 25, and 26.  West, bet. secs. 23 and 26.  Over rolling land.
39.995	Point for the 1/4 sec. cor. of secs. 23 and 26.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T29N R26E S23 1/4 — S26 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Enter nearly level land.</p>
79.99	<p>The cor. of secs. 22, 23, 26, and 27.</p> <p>Land, rolling to nearly level. Soil, sandy clay and sand. No timber; scattered native grasses.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T29N R26E 1/4 S22   S23 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 14, 15, 22, and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T29N R26E S15   S14 ----- S22   S23 1991</p>

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay and sand. No timber; scattered native grasses.</p> <hr/> <p>From the cor. of secs. 13, 14, 23, and 24. S. 89°59' W., bet. secs. 14 and 23. Over nearly level land.</p>
39.995	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R26E S14 1/4 — S23 1991</p>
79.99	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Enter rugged land.</p> <p>The cor. of secs. 14, 15, 22, and 23.</p> <p>Land, nearly level to rugged. Soil, sandy clay and clay. No timber; scattered native grasses.</p> <hr/>
40.00	<p>N. 0°01' W., bet. secs. 14 and 15. Over rugged land.</p> <p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p style="text-align: center;">T29N R26E 1/4 S15   S14 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 10, 11, 14, and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R26E S10   S11 ----- S15   S14 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rugged. Soil, sandy clay and clay. No timber; scattered native grasses.</p>
36.995	<hr/> <p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>S. 89°59' W., bet. secs. 11 and 14.</p> <p>Over nearly level land.</p> <p>Point selected for the witness cor. to the 1/4 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WC T29N R26E S11 1/4&lt;— S14 1991</p>

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Enter rugged land.</p>
39.995	<p>True point for the 1/4 sec. cor. of secs. 11 and 14, falls in a ravine, 60 lks. wide, 60 ft. deep, drains NW; impracticable to monument.</p>
79.99	<p>The cor. of secs. 10, 11, 14, and 15.</p> <p>Land, nearly level to rugged. Soil, rocky clay. No timber; scattered native grasses.</p>
	<hr/> <p>N. 0°01' W., bet. secs. 10 and 11.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R26E 1/4 S10   S11 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Enter nearly level land.</p>
50.70	<p>Graded road, 30 lks. wide, bears ENE and WSW.</p>
80.00	<p>Point for the cor. of secs. 2, 3, 10, and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<div style="text-align: center;"> <table border="1"> <tr><td>T29N</td><td>R26E</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td>S10</td><td>S11</td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling to nearly Level. Soil, sandy clay and sand. No timber; scattered native grasses.</p>	T29N	R26E	S 3	S 2	S10	S11	1991			
T29N	R26E										
S 3	S 2										
S10	S11										
1991											
6.20	<hr/> <p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>S. 89°59' W., bet. secs. 2 and 11.</p> <p>Over rolling and rugged land.</p>										
39.995	<p>Graded road, 30 lks. wide, bears SSE and NNW.</p> <p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>										
79.99	<div style="text-align: center;"> <table border="1"> <tr><td>T29N</td><td>R26E</td></tr> <tr><td>S 2</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S11</td><td></td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T29N	R26E	S 2		1/4	—	S11		1991	
T29N	R26E										
S 2											
1/4	—										
S11											
1991											
	<p>The cor. of secs. 2, 3, 10, and 11.</p> <p>Land, rolling and rugged. Soil, sandy clay and clay. No timber; scattered native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 2 and 3.</p>										

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling land.
38.00	Point selected for the witness cor. to the 1/4 sec. cor. of secs. 2 and 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	WC
	T29N R26E
	1/4
	S 3 ↑ S 2
	1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
39.60	Wash, 90 lks. wide, 40 ft. deep, drains WSW.
40.00	True point for the 1/4 sec. cor. of secs. 2 and 3, falls on an extremely steep S. slope of clay outcrop; impracticable to monument.
80.00	The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., hereinbefore described.
	Land, rolling.
	Soil, sandy clay and clay.
	No timber; scattered native grasses.
	From the stan. cor. of secs. 33 and 34, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°02' W., bet. secs. 33 and 34.
	Over nearly level land.
34.00	Trail road, bears SSE and NNW.
40.00	Point for the 1/4 sec. cor. of secs. 33 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T29N R26E 1/4 S33   S34 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 100 lks. E. of a trail road, bears N. and S., and 140 lks. W. of a trail road, bears N. on a curve to the left.</p>
41.95	Trail road, bears NNE and SSW.
80.00	<p>Point for the cor. of secs. 27, 28, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R26E S28   S27 ----- S33   S34 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay and sand. No timber; scattered native grasses.</p> <hr/> <p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>West, bet. secs. 27 and 34.</p> <p>Over nearly level land.</p>
13.45	Trail road, bears SSE and NNW.
40.005	<p>Point for the 1/4 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T29N R26E S27 1/4 — S34 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
47.00	Wash, 114 lks. wide, 3 ft. deep, drains N.
59.10	Wash, 38 lks. wide, 5 ft. deep, drains NNW.
76.40	Wash, 161 lks. wide, 6 ft. deep, drains NNE.
80.01	The cor. of secs. 27, 28, 33, and 34.
	Land, nearly level. Soil, sandy clay and clay. No timber; scattered native grasses.
	<hr/> N. 0°02' W., bet. secs. 27 and 28.  Over nearly level land.
24.30	Bis-ii-ah Wash, 242 lks. wide, 4 ft. deep, drains NW.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 28.
	Set a magnet in a 1 x 1 x 2 5/8 ins. white plastic case, 15 ins. below the surface of the ground.  from which  A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 45° E., 150 ft. dist., with brass cap mkd. T29N R26E 1/4 S27 RM 150 FT TO COR 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45° W., 150 ft. dist., with brass cap mkd. T29N R26E 1/4 S28 RM 150 FT TO COR 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>										
	<p>Cor. is located in Bis-ii-ah Wash, 150 lks. wide, 7 ft. deep, drains NNE, at foot of E. bank.</p>										
41.80	<p>W. bank of Bis-ii-ah Wash 150 lks. wide, 7 ft. deep, drains NNE.</p>										
63.50	<p>Bis-ii-ah Wash, 288 lks. wide, 2 ft. deep, drains NNW.</p>										
70.55	<p>Trail road, bears SE and NW.</p>										
80.00	<p>Point for the cor. of secs. 21, 22, 27, and 28.</p>										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>										
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>T29N</td> <td>R26E</td> </tr> <tr> <td>S21</td> <td>S22</td> </tr> <tr> <td colspan="2" style="text-align: center;"> </td> </tr> <tr> <td>S28</td> <td>S27</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T29N	R26E	S21	S22			S28	S27	1991	
T29N	R26E										
S21	S22										
S28	S27										
1991											
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>										
	<p>Land, nearly level. Soil, sandy clay and sand. No timber; scattered native grasses.</p>										
	<p>From the cor. of secs. 22, 23, 26, and 27.</p>										
	<p>S. 89°59' W., bet. secs. 22 and 27.</p>										
	<p>Over nearly level land.</p>										
40.005	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p>										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>										

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T29N R26E S22 1/4 — S27 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
70.60	Wash, 227 lks. wide, 2 ft. deep, drains NNW.
80.01	The cor. of secs. 21, 22, 27, and 28.
	Land, nearly level. Soil, sandy clay and sand. No timber; scattered native grasses.
	N. 0°02' W., bet. secs. 21 and 22.
	Over nearly level land.
18.25	Center shaft of windmill, bears West, 6.85 chs. dist.
19.80	Bis-ii-ah Wash, 273 lks. wide, 2 ft. deep, drains NE.
35.30	Bis-ii-ah Wash, 530 lks. wide, 6 ft. deep, drains WNW.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T29N R26E 1/4 S21   S22 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.00	Point for the cor. of secs. 15, 16, 21, and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<div style="text-align: center;"> <table border="1"> <tr> <td>T29N</td> <td>R26E</td> </tr> <tr> <td>S16</td> <td>S15</td> </tr> <tr> <td>S21</td> <td>S22</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay and sand. No timber; scattered native grasses.</p>	T29N	R26E	S16	S15	S21	S22	1991			
T29N	R26E										
S16	S15										
S21	S22										
1991											
	<hr/> <p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>S. 89°59' W., bet. secs. 15 and 22.</p> <p>Over nearly level land.</p>										
40.005	<p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>										
	<div style="text-align: center;"> <table border="1"> <tr> <td>T29N</td> <td>R26E</td> </tr> <tr> <td></td> <td>S15</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S22</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T29N	R26E		S15	1/4	—		S22	1991	
T29N	R26E										
	S15										
1/4	—										
	S22										
1991											
80.01	<p>The cor. of secs. 15, 16, 21, and 22.</p> <p>Land, nearly level. Soil, sandy clay and clay. No timber; scattered native grasses.</p>										
	<hr/> <p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over nearly level land.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p>										

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R26E 1/4 S16   S15 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 9, 10, 15, and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R26E S 9   S10 ----- S16   S15 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay and sand. No timber; scattered native grasses.</p>
	<p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>S. 89°59' W., bet. secs. 10 and 15.</p> <p>Over nearly level land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS		
	T29N R26E S10 1/4 — S15 1991	
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.	
80.00	The cor. of secs. 9, 10, 15, and 16.	
	Land, nearly level. Soil, sandy clay and clay, with scattered sandstone outcrops. No timber; scattered native grasses.	
	<hr/>	
	N. 0°02' W., bet. secs. 9 and 10.	
	Over nearly level land.	
17.30	Graded road, 33 lks. wide, bears NE and SW.	
26.50	Center of hexagonal hogan, 25 ft. diam., bears West, 20.55 chs. dist.	
29.70	Center of hexagonal hogan, 25 ft. diam., bears West, 19.40 chs. dist.	
40.00	Point for the 1/4 sec. cor. of secs. 9 and 10.	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.	
	T29N R26E 1/4 S 9   S10 1991	
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.	
74.20	Wash, 68 lks. wide, 3 ft. deep, drains WSW.	
80.00	Point for the cor. of secs. 3, 4, 9, and 10.	

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T29N</td> <td>R26E</td> </tr> <tr> <td>S 4</td> <td>S 3</td> </tr> <tr> <td>S 9</td> <td>S10</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay and sand. No timber; scattered native grasses.</p>	T29N	R26E	S 4	S 3	S 9	S10	1991			
T29N	R26E										
S 4	S 3										
S 9	S10										
1991											
	<hr/> <p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>S. 89°59' W., bet. secs. 3 and 10.</p> <p>Over nearly level land.</p>										
<p>40.00</p>	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T29N</td> <td>R26E</td> </tr> <tr> <td>S 3</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S10</td> <td></td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T29N	R26E	S 3		1/4	—	S10		1991	
T29N	R26E										
S 3											
1/4	—										
S10											
1991											
<p>80.00</p>	<p>The cor. of secs. 3, 4, 9, and 10.</p> <p>Land, nearly level. Soil, sandy clay and clay. No timber; scattered native grasses.</p> <hr/>										

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°02' W., bet. secs. 3 and 4.
	Over nearly level land.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T29N R26E
	1/4
	S 4   S 3
	1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
49.90	Trail road, bears NE and SW.
80.01	The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., hereinbefore described.
	Land, nearly level.
	Soil, sandy clay and clay.
	No timber; scattered native grasses.
	From the stan. cor. of secs. 32 and 33, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°03' W., bet. secs. 32 and 33.
	Over nearly level land.
40.00	Point for the 1/4 sec. cor. of secs. 32 and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T29N R26E
	1/4
	S32   S33
	1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
80.00	<p>Point for the cor. of secs. 28, 29, 32, and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T29N</td> <td>R26E</td> </tr> <tr> <td>S29</td> <td>S28</td> </tr> <tr> <td>S32</td> <td>S33</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay and sand. No timber; scattered native grasses.</p>	T29N	R26E	S29	S28	S32	S33	1991			
T29N	R26E										
S29	S28										
S32	S33										
1991											
<hr/>											
	<p>From the cor. of secs. 27, 28, 33, and 34.</p>										
	<p>West, bet. secs. 28 and 33.</p>										
	<p>Over nearly level land.</p>										
5.70	<p>Wash, 46 lks. wide, 2 ft. deep, drains NE.</p>										
14.30	<p>Trail road, bears SSE and NNW.</p>										
16.25	<p>Trail road, bears N. and S.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T29N</td> <td>R26E</td> </tr> <tr> <td>S28</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S33</td> <td></td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T29N	R26E	S28		1/4	—	S33		1991	
T29N	R26E										
S28											
1/4	—										
S33											
1991											
80.00	<p>The cor. of secs. 28, 29, 32, and 33.</p>										

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, nearly level. Soil, sandy clay and clay. No timber; scattered native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 28 and 29.</p> <p>Over nearly level land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29N R26E 1/4 S29   S28 1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 20, 21, 28, and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29N R26E S20   S21 ----- S29   S28 1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 450 lks. N. and 120 lks. W. of a wash, 46 lks. wide, drains NNE, and 500 lks. S. of same wash, drains WNW.</p> <p>Land, nearly level. Soil, sandy clay and sand. No timber; scattered native grasses.</p> <hr/>

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the cor. of secs. 21, 22, 27, and 28.
	West, bet. secs. 21 and 28.
	Over nearly level land.
5.20	Bis-ii-ah Wash, 212 lks. wide, 2 ft. deep, drains NNE.
13.00	Trail road, bears ESE and WNW.
23.60	Power line, bears NW.
26.10	Trail road, bears NE and SW.
26.20	NE cor. of log cabin, 18 ft. square, bears South, 2.60 chs. dist., sides bear SSW and WNW.
34.30	SE cor. of stucco house, 25 x 15 ft., bears North, 17.10 chs. dist., long side bears NNE.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 28.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T29N R26E S21 1/4 — S28 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
41.90	Trail road, bears N. and S.
46.25	Trail road, bears N. and S.
80.00	The cor. of secs. 20, 21, 28, and 29.
	Land, nearly level.
	Soil, sandy clay and clay.
	No timber; scattered native grasses.

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°03' W., bet. secs. 20 and 21.
	Over nearly level land.
32.20	Wash, 99 lks. wide, 2 ft. deep, drains NE.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 21.
	Set a magnet in a 1 x 1 x 2 5/8 ins. white plastic case, 12 ins. below the surface of the ground.
	from which
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45° E., 80 ft. dist., with brass cap mkd. T29N R26E 1/4 S21 RM 80 FT TO COR 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45° W., 80 ft. dist., with brass cap mkd. T29N R26E 1/4 S20 RM 80 FT TO COR 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	Cor. is located in a wash, 76 lks. wide, 2 ft. deep, drains NNW.
46.60	Wash, 76 lks. wide, 2 ft. deep, drains E.
49.50	SE cor. of stucco house, 25 x 16 ft., bears West, 34.40 chs. dist., long side bears N.
51.50	Power line, bears SE and NW.
59.30	Same wash, 76 lks. wide, 2 ft. deep, drains WNW.
60.75	Center of hexagonal hogan, 18 ft. diam., bears West, 27.30 chs. dist.
61.70	NE cor. of stucco house, 15 x 10 ft., bears West, 28.00 chs. dist., long side bears S.
63.10	Center of hexagonal hogan, 22 ft. diam., bears West, 26.95 chs. dist.

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
66.00	Same wash, 61 lks. wide, 4 ft. deep, drains NE.										
66.90	Same wash, 30 lks. wide, 4 ft. deep, drains WNW.										
80.00	Point for the cor. of secs. 16, 17, 20, and 21.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.										
	<table border="0"> <tr> <td>T29N</td> <td>R26E</td> </tr> <tr> <td>S17</td> <td>S16</td> </tr> <tr> <td colspan="2" style="text-align: center;"> </td> </tr> <tr> <td>S20</td> <td>S21</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T29N	R26E	S17	S16			S20	S21	1991	
T29N	R26E										
S17	S16										
S20	S21										
1991											
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.										
	Cor. is located 340 lks. W. of a trail road, bears SSE and NNW.										
	Land, nearly level. Soil, sandy clay and sand. No timber; scattered native grasses.										
	From the cor. of secs. 15, 16, 21, and 22.										
	N. 89°59' W., bet. secs. 16 and 21.										
	Over nearly level land.										
40.005	Point for the 1/4 sec. cor. of secs. 16 and 21.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.										
	<table border="0"> <tr> <td>T29N</td> <td>R26E</td> </tr> <tr> <td></td> <td>S16</td> </tr> <tr> <td></td> <td>1/4 —</td> </tr> <tr> <td></td> <td>S21</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T29N	R26E		S16		1/4 —		S21	1991	
T29N	R26E										
	S16										
	1/4 —										
	S21										
1991											
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.										
47.30	Bis-ii-ah Wash, 151 lks. wide, 5 ft. deep, drains WNW.										

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.01	<p>The cor. of secs. 16, 17, 20, and 21.</p> <p>Land, nearly level. Soil, sandy clay and clay. No timber; scattered native grasses.</p> <hr/>
	<p>N. 0°03' W., bet. secs. 16 and 17.</p>
	<p>Over nearly level land.</p>
17.15	<p>Trail road, bears NNE and SSW.</p>
19.05	<p>Trail road, bears SSE and NNW.</p>
22.70	<p>Power line, bears NNE and SSW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T29N R26E 1/4 S17   S16 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
40.85	<p>Trail road, bears ENE and WSW.</p>
54.30	<p>Graded road, 30 lks. wide, bears NNE and SSW.</p>
80.00	<p>Point for the cor. of secs. 8, 9, 16, and 17.</p> <p>Set a magnet in a 1 x 1 x 2 5/8 ins. white plastic case, 12 ins. below the surface of the ground.</p> <p>from which</p>

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 60° E., 200 ft. dist., with brass cap mkd. T29N R26E S9 RM 200 FT TO COR 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 60° W., 200 ft. dist., with brass cap mkd. T29N R26E S17 RM 200 FT TO COR 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Cor. is located on the W. edge of Bis-ii-ah Wash, 190 lks. wide, 10 ft. deep, drains NNW.</p>
	<p>Land, nearly level. Soil, sandy clay and sand. No timber; scattered native grasses.</p>
	<p>From the cor. of secs. 9, 10, 15, and 16.</p>
	<p>N. 89°59' W., bet. secs. 9 and 16.</p>
	<p>Over nearly level land.</p>
38.30	<p>Graded road, 30 lks. wide, bears ENE and WSW.</p>
39.20	<p>Power line, bears NE and SW.</p>
40.015	<p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T29N R26E S 9 1/4 — S16 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
71.90	Trail road, bears SSE and NNW.
80.03	<p>The cor. of secs. 8, 9, 16, and 17.</p> <p>Land, nearly level. Soil, sandy clay and clay. No timber; scattered native grasses.</p> <hr/>
40.00	<p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over nearly level land.</p> <p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29N R26E 1/4 S 8   S 9 1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
59.60	Center shaft of windmill, bears East, 8.50 chs. dist.
80.00	<p>Point for the cor. of secs. 4, 5, 8, and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29N R26E S 5   S 4 ----- S 8   S 9 1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay and sand. No timber; scattered native grasses.</p> <hr/>

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>N. 89°59' W., bet. secs. 4 and 9.</p> <p>Over nearly level land.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R26E S 4 1/4 — S 9 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
46.10	Wash, 91 lks. wide, 4 ft. deep, drains NW.
52.30	Power line, bears SSE and NNW.
64.50	Trail road, bears NNE and SSW.
80.04	<p>The cor. of secs. 4, 5, 8, and 9.</p> <p>Land, nearly level. Soil, sandy clay and clay. No timber; scattered native grasses.</p> <hr/>
40.00	<p>N. 0°01' W., bet. secs. 4 and 5.</p> <p>Over nearly level land.</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T29N R26E 1/4 S 5   S 4 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
53.80	<p>Bis-ii-ah Wash, 455 lks. wide, 3 ft. deep, drains NNE.</p>
80.00	<p>The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., hereinbefore described.</p>
	<p>Land, nearly level. Soil, sandy clay and clay. No timber; scattered native grasses.</p>
	<p>From the stan. cor. of secs. 31 and 32, on the S. bdy. of the Tp., hereinbefore described.</p>
	<p>N. 0°03' W., bet. secs. 31 and 32.</p>
	<p>Over nearly level land.</p>
17.20	<p>W. rim of Beautiful Valley, bears ESE and WNW, thence enter rugged land on descent.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T29N R26E 1/4 S31   S32 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 29, 30, 31, and 32.</p>
	<p>Set a magnet in a 1 x 1 x 2 5/8 ins. white plastic case, 12 ins. below the surface of the ground.</p>

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, for a reference monument, bears S. 60° E., 90 ft. dist., with brass cap mkd. T29N R26E S32 RM 90 FT TO COR 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 60° W., 66 ft. dist., with brass cap mkd. T29N R26E S30 RM 66 FT TO COR 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on the crumbling edge of a subsidence pit.</p> <p>Land, nearly level to rugged. Soil, sandy clay and clay. No timber; scattered native grasses.</p>
	<p>From the cor. of secs. 28, 29, 32, and 33.</p>
	<p>N. 89°59' W., bet. secs. 29 and 32.</p>
	<p>Over nearly level land.</p>
14.20	<p>Wash, 15 lks. wide, 1 ft. deep, drains N.</p>
35.00	<p>Wash, 15 lks. wide, 3 ft. deep, drains N.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p>T29N R26E</p>
	<p>S29</p>
	<p>1/4 —</p>
	<p>S32</p>
	<p>1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Enter rolling land.</p> <p>73.30 Wash, 15 lks. wide, 2 ft. deep, drains NNE.</p> <p>75.10 Wash, 12 lks. wide, 2 ft. deep, drains NNE.</p> <p>80.00 The cor. of secs. 29, 30, 31, and 32.</p> <p>Land, nearly level to rolling. Soil, sandy clay and clay. No timber; scattered native grasses.</p> <hr/> <p>West, bet. secs. 30 and 31.</p> <p>Over rugged land.</p> <p>39.00 Wash, 8 lks. wide, 3 ft. deep, drains N.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R26E S30 1/4 — S31 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>71.20 W. rim of Beautiful Valley, bears NNE and SSW.</p> <p>Thence over nearly level land.</p> <p>72.10 Wash, 23 lks. wide, 3 ft. deep, drains NNE.</p> <p>79.89 The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T29N R25E R26E S25 S30 S36 S31 1990.</p>
--------	---

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rugged to nearly level. Soil, sandy clay and clay. No timber; scattered native grasses.</p> <hr/> <p>From the cor. of secs. 29, 30, 31, and 32. N. 0°03' W., bet. secs. 29 and 30. Over rolling land.</p>
34.50	<p>Wash, 12 lks. wide, 1 ft. deep, drains E. Enter nearly level land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R26E 1/4 S30   S29 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
51.30	<p>Wash, 15 lks. wide, 1 ft. deep, drains NNE.</p>
59.20	<p>Wash, 23 lks. wide, 1 ft. deep, drains NNE.</p>
62.10	<p>Wash, 23 lks. wide, 1 ft. deep, drains ENE.</p>
68.60	<p>Wash, 23 lks. wide, 2 ft. deep, drains NNE.</p>
80.00	<p>Point for the cor. of secs. 19, 20, 29, and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R26E S19   S20 ----- S30   S29 1991</p>

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Cor. is located 440 lks. W. of a wash, 9 lks. wide, 1 ft. deep, drains N., and 470 lks. S. of a wash, 23 lks. wide, 1 ft. deep, drains NNE.</p>
	<p>Land, rolling to nearly level. Soil, sandy clay and sand. No timber; scattered native grasses.</p>
	<hr/> <p>From the cor. of secs. 20, 21, 28, and 29.</p>
	<p>N. 89°59' W., bet. secs. 20 and 29.</p>
	<p>Over nearly level land.</p>
9.60	<p>Wash, 38 lks. wide, 3 ft. deep, drains NE.</p>
40.005	<p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T29N R26E S20 1/4 — S29 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
42.00	<p>Wash, 23 lks. wide, 2 ft. deep, drains N.</p>
66.80	<p>Wash, 15 lks. wide, 3 ft. deep, drains ENE.</p>
80.01	<p>The cor. of secs. 19, 20, 29, and 30.</p>
	<p>Land, nearly level. Soil, sandy clay and sand. No timber; scattered native grasses.</p>

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	West, bet. secs. 19 and 30.
	Over nearly level land.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T29N R26E
	S19
	1/4 —
	S30
	1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
42.20	Wash, 30 lks. wide, 1 ft. deep, drains N.
52.30	Wash, 20 lks. wide, 1 ft. deep, drains NE.
69.00	Wash, 20 lks. wide, 1 ft. deep, drains N.
79.78	The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T29N R25E R26E S24 S19 S25 S30 1990.
	Land, nearly level.
	Soil, sandy clay and clay.
	No timber; scattered native grasses.
	From the cor. of secs. 19, 20, 29, and 30.
	N. 0°03' W., bet. secs. 19 and 20.
	Over nearly level land.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 20.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T29N R26E 1/4 S19   S20 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Cor. is located 90 lks. S. of an earthen dike, bears SE and NW.</p>
70.30	<p>Wash, 38 lks. wide, 1 ft. deep, drains NE.</p>
73.90	<p>Wash, 61 lks. wide, 1 ft. deep, drains NE.</p>
76.50	<p>Wash, 46 lks. wide, 2 ft. deep, drains E.</p>
80.00	<p>Point for the cor. of secs. 17, 18, 19, and 20.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T29N R26E S18   S17 ----- S19   S20 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Land, nearly level. Soil, sandy clay and sand. No timber; scattered native grasses.</p>
	<p>From the cor. of secs. 16, 17, 20, and 21.</p>
	<p>N. 89°59' W., bet. secs. 17 and 20.</p>
	<p>Over nearly level land.</p>
10.80	<p>Wash, 129 lks. wide, 4 ft. deep, drains NNW.</p>
14.35	<p>Trail road, bears NNE and SSW.</p>
16.20	<p>Power line, bears NE and SW.</p>

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
31.00	Power line, bears SE and NW.
40.01	Point for the 1/4 sec. cor. of secs. 17 and 20.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T29N R26E S17 1/4 — S20 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
47.10	SE cor. of stucco house, 25 x 18 ft., bears North, 16.95 chs. dist., long side bears N.
47.75	SE cor. of stucco house, 30 x 15 ft., bears North, 19.85 chs. dist., long side bears N.
48.10	Center of hexagonal hogan, 18 ft. diam., bears North, 18.30 chs. dist.
49.55	Trail road, bears N. and S.
56.65	Trail road, bears SE and NW.
61.60	Wash, 15 lks. wide, 2 ft. deep, drains NNE.
69.20	Wash, 18 lks. wide, 2 ft. deep, drains ENE.
72.90	Wash, 46 lks. wide, 2 ft. deep, drains ENE.
80.02	The cor. of secs. 17, 18, 19, and 20.
	Land, nearly level. Soil, sandy clay and sand. No timber; scattered native grasses.
	<hr/> West, bet. secs. 18 and 19.
	Over nearly level land.

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R26E S18 1/4 — S19 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
41.65	Trail road, bears ENE and WSW.
43.80	Trail road, bears SE and NW.
50.20	Wash, 38 lks. wide, 2 ft. deep, drains NE.
64.00	Wash, 15 lks. wide, 1 ft. deep, drains ENE.
66.50	Wash, 38 lks. wide, 1 ft. deep, drains ESE.
79.67	<p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T29N R25E R26E S13 S18 S24 S19 1990.</p> <p>Land, nearly level. Soil, sandy clay and clay. No timber; scattered native grasses.</p> <hr/> <p>From the cor. of secs. 17, 18, 19, and 20.</p> <p>N. 0°03' W., bet. secs. 17 and 18.</p> <p>Over nearly level land.</p>
11.65	Trail road, bears ENE and WSW.
17.45	Trail road, bears ESE and WNW.
31.60	Wash, 23 lks. wide, 2 ft. deep, drains ENE.

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
34.10	Graded road, 46 lks. wide, bears ENE and WSW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;">             T29N R26E              1/4              S18   S17              1991           </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
49.80	Wash, 38 lks. wide, 2 ft. deep, drains NE.
61.60	Wash, 8 lks. wide, 1 ft. deep, drains ESE.
67.90	Wash, 8 lks. wide, 1 ft. deep, drains ENE.
79.60	Wash, 38 lks. wide, 1 ft. deep, drains E.
80.00	<p>Point for the cor. of secs. 7, 8, 17, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;">             T29N R26E              S 7   S 8  <hr style="width: 50%; margin: 0 auto;"/>             S18   S17              1991           </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay and sand. No timber; scattered native grasses.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 8, 9, 16, and 17.</p> <p>N. 89°59' W., bet. secs. 8 and 17.</p>

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over nearly level land.
21.10	Wash, 136 lks. wide, 5 ft. deep, drains N.
40.02	Point for the 1/4 sec. cor. of secs. 8 and 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	26 ins. in the ground, with brass cap mkd.
	T29N R26E
	S 8
	1/4 —
	S17
	1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case
	beneath the stainless steel post.
45.65	Trail road, bears NNE and SSW.
53.30	Wash, 23 lks. wide, 2 ft. deep, drains N.
80.04	The cor. of secs. 7, 8, 17, and 18.
	Land, nearly level.
	Soil, sandy clay and sand.
	No timber; scattered native grasses.
	West, bet. secs. 7 and 18.
	Over nearly level land.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	24 ins. in the ground, with brass cap mkd.
	T29N R26E
	S 7
	1/4 —
	S18
	1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case
	beneath the stainless steel post.

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Enter rugged land on ascent.
60.30	W. rim of Beautiful Valley, bears SSE and NNW.
	Enter nearly level land.
72.45	Trail road, bears NE and SW.
79.56	The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T29N R25E R26E S12 S7 S13 S18 1990.
	Land, nearly level and rugged. Soil, sandy clay and clay. No timber; scattered native grasses.
	From the cor. of secs. 7, 8, 17, and 18.
	N. 0°03' W., bet. secs. 7 and 8.
	Over gently rolling land.
15.30	Wash, 23 lks. wide, 2 ft. deep, drains ENE.
26.00	Wash, 31 lks. wide, 1 ft. deep, drains ENE.
38.60	Wash, 31 lks. wide, 2 ft. deep, drains ENE.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T29N R26E 1/4 S 7   S 8 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.00	Point for the cor. of secs. 5, 6, 7, and 8.

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T29N</td> <td>R26E</td> </tr> <tr> <td>S 6</td> <td>S 5</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S 7</td> <td>S 8</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay and sand. No timber; scattered native grasses.</p> <hr/> <p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>West, bet. secs. 5 and 8.</p> <p>Over nearly level land.</p>	T29N	R26E	S 6	S 5			S 7	S 8	1991	
T29N	R26E										
S 6	S 5										
S 7	S 8										
1991											
22.80	Bis-ii-ah Wash, 288 lks. wide, 4 ft. deep, drains NNE.										
39.50	Trail road, bears N. and S.										
40.025	Point for the 1/4 sec. cor. of secs. 5 and 8.										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T29N</td> <td>R26E</td> </tr> <tr> <td></td> <td>S 5</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 8</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T29N	R26E		S 5	1/4	—		S 8	1991	
T29N	R26E										
	S 5										
1/4	—										
	S 8										
1991											
47.30	Wash, 15 lks. wide, 2 ft. deep, drains NNE.										
80.05	The cor. of secs. 5, 6, 7, and 8.										

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, nearly level. Soil, sandy clay and sand. No timber; scattered native grasses.</p> <hr/>
	<p>S. 89°59' W., bet. secs. 6 and 7.</p>
	<p>Over rolling to rugged land on ascent.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T29N R26E S 6 1/4 — S 7 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
41.50	<p>W. rim of Beautiful Valley, bears NNE and SSW.</p>
	<p>Thence over rolling land.</p>
52.20	<p>E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.</p>
53.76	<p>Center of U.S. Highway 191, asphalt pavement, 46 lks. wide, bears NNE and SSW.</p>
55.34	<p>W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.</p>
58.50	<p>Power line, bears NNE and SSW.</p>
79.46	<p>The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., monumented with a brass tablet, 3 1/4 ins. diam., cemented in place in sandstone bedrock, with top mkd. T29N R25E R26E S1 S6 S12 S7 1990.</p>
	<p>Land, rolling and rugged. Soil, sandy clay and clay. No timber; scattered native grasses.</p> <hr/>

Survey of the Subdivisional Lines,  
T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the cor. of secs. 5, 6, 7, and 8.
	N. 0°01' E., bet. secs. 5 and 6.
	Over rolling land.
22.10	Wash, 30 lks. wide, 4 ft. deep, drains E.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 6.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	27 ins. in the ground, with brass cap mkd.
	T29N R26E
	1/4
	S 6   S 5
	1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case
	beneath the stainless steel post.
50.20	Wash, 15 lks. wide, 2 ft. deep, drains ESE.
52.30	Wash, 15 lks. wide, 3 ft. deep, drains SE.
79.99	The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp.,
	hereinbefore described.
	Land, rolling.
	Soil, sandy clay and clay.
	No timber; scattered native grasses.

T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

---

The area surveyed is within the Navajo Indian Reservation, approximately 4 miles west of Nazlini, Arizona, and about 18 miles south of Chinle, Arizona. The elevation varies from 5,700 to 6,200 feet above sea level.

The soil is predominantly sandy clay and sand, with some clay outcrops and rocky clay in the eastern and western portions of the township.

U.S. Highway 191 passes through the northwest and southwest portions of the township. Further access is provided by two graded roads and numerous trail roads. The majority of the township is located within Beautiful Valley. The principal drainages are Bis-ii-ah Wash and Tah-aith-cheed Wash, which drain northerly.

The terrain is mostly nearly level to rolling, with some rugged land in the extreme eastern and western portions. The timber is confined to the northeastern portion and consists of scattered juniper and piñon. The predominant vegetation is scattered native grasses.

The mean magnetic declination is 12 1/2° E.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## FIELD ASSISTANTS

NAMES	CAPACITY
Kenneth D. Roy	Land Surveyor in Training
Daniel Bryan	Engineering Technician
Wilfred Chee	Engineering Technician
Edward Clarke	Engineering Technician
Nelson Kinsel	Engineering Technician
Reuben Mason	Engineering Technician
Barney Woodie	Engineering Technician

CERTIFICATE OF SURVEY

We, Steve D. Cully and William F. Olver, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 22nd day of November, 1989, we have surveyed the Seventh Standard Parallel North (south boundary), the east and north boundaries, and the subdivisional lines of Township 29 North, Range 26 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 3, 1992  
(Date)

Steve D Cully  
(Cadastral Surveyor)

OCTOBER 28, 1992  
(Date)

William F. Olver  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Arizona State Office  
Phoenix, Arizona

The foregoing field notes of the survey of the Seventh Standard Parallel North (south boundary), the east and north boundaries, and the subdivisional lines of Township 29 North, Range 26 East, Gila and Salt River Meridian, Arizona, executed by Steve D. Cully, and William F. Olver, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

DEC 8 1992  
(Date)

James P. Kelly  
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 29 N., R. 26 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~\_\_\_\_\_  
(Date)~~

~~\_\_\_\_\_  
(Chief Cadastral Surveyor of Arizona)~~