

ORIGINAL

BOOK 5382

1

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES  
OF THE

---

SURVEY OF THE SIXTH GUIDE MERIDIAN EAST,

---

(WEST BOUNDARY),

---

THE EAST AND NORTH BOUNDARIES,

---

AND

---

THE SUBDIVISIONAL LINES

---

OF

---

TOWNSHIP 31 NORTH, RANGE 25 EAST

---

Of the Gila and Salt River Meridian,  
In the State of Arizona

EXECUTED BY

Leonard R. Sandoval, Cadastral Surveyor

---

Under Special Instructions dated November 22, 1989, approved November 22, 1989, which provided for the surveys included under Group Number 715 and assignment instructions dated November 22, 1989.

Survey commenced January 23, 1990  
Survey completed September 10, 1991

INDEX DIAGRAM

TOWNSHIP 31 NORTH , RANGE 25 EAST ,

9	21 6	20 70 5	19 58 4	18 49 3	16 40 2	16 30 1 15
8	69 7	68 67 8	57 56 9	48 48 10	39 38 11	30 29 12 14
7	67 18	66 65 17	56 55 16	47 46 15	37 36 14	28 27 13 13
6	65 19	64 63 20	54 53 21	45 44 22	35 34 23	26 25 24 12
5	63 30	62 61 29	53 52 28	43 43 27	34 33 26	24 23 25 11
4	60 31	60 59 32	51 50 33	42 41 34	32 31 35	22 21 36 10

## T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes are those of the survey of the Sixth Guide Meridian East, (west boundary), the east and north boundaries, and the subdivisional lines of Township 31 North, Range 25 East, Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated November 22, 1989, for Group No. 715, Arizona.

This survey supersedes portions of Townships 4 and 5 North, Range 11 West of the Navajo Special Meridian. The west boundary of the 1868 Navajo Reservation is identified, where possible, for historical purposes only, and has no legal significance in this survey. The survey history of that portion of the superseded Navajo Special Meridian is included in these notes for informational purposes only.

The west boundary of the Navajo Indian Reservation and the boundaries and subdivision of Townships 4 and 5 North, Range 11 West, Navajo Special Meridian, were surveyed by E.N. Darling in 1869. The west boundary of the Navajo Indian Reservation was dependently resurveyed by L.E. Sechrist in 1919-20.

The south boundary of the township was surveyed by William F. Olver and Patrick S. Twohy in 1990-91, with plat and notes approved June 11, 1992.

The directions of all lines were determined by direct hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured with a Topcon GTS3B electronic total station instrument.

The geographic position of the southeast corner of the township, as determined from a tie made to U.S. Coast and Geological Survey triangulation station "BEAUTIFUL 1951", hereinafter described, is as follows:

Latitude: 36°02'29.32" N. Longitude: 109°36'01.71" W. NAD27

The mean magnetic declination as taken from the 1985 magnetic declination map published by U.S. Geological Survey, is 12 1/2° E.

Survey of the Sixth Guide Meridian East,  
 (West Boundary),  
 T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Beginning at the cor. of Tps. 30 and 31 N., Rs. 24 and 25 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T31N R24E R25E S36 S31 S1 S6 1990.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 36 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T31N              R24E   R25E              1/4              S36   S31              1990</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 25, 30, 31, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T31N              R24E   R25E              S25   S30              -----              S36   S31              1990</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling.              Soil, sandy clay.              No timber; brush and native grasses.</p>

Survey of the Sixth Guide Meridian East,  
 (West Boundary),  
 T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>North, bet. secs. 25 and 30.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,                  24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N                  R24E   R25E                  1/4                  S25   S30                  1990</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic                  case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 19, 24, 25, and 30.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,                  24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N                  R24E   R25E                  S24   S19  <hr style="width: 50%; margin: 0 auto;"/>                 S25   S30                  1990</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic                  case beneath the stainless steel post.</p>
	<p>Land, rolling.</p>
	<p>Soil, sandy clay.</p>
	<p>No timber; brush and native grasses.</p>

Survey of the Sixth Guide Meridian East,  
 (West Boundary),  
 T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	North, bet. secs. 19 and 24.
	Over rolling land.
8.20	Trail road, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T31N R24E   R25E 1/4 S24   S19 1990
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
66.10	Center of Navajo Route 4, asphalt pavement, 36 lks. wide, bears E. and W.
69.30	Power line, bears E. and W.
80.00	Point for the cor. of secs. 13, 18, 19, and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T31N R24E   R25E S13   S18 <hr style="width: 50%; margin: auto;"/> S24   S19 1990
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Land, rolling. Soil, sandy clay. No timber; brush and native grasses.

Survey of the Sixth Guide Meridian East,  
 (West Boundary),  
 T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
40.00	<p>North, bet. secs. 13 and 18.</p> <p>Over gently rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>												
65.20	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T31N</td></tr> <tr><td style="text-align: center;">R24E</td><td style="text-align: center;">R25E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S13</td><td style="text-align: center;">S18</td></tr> <tr><td colspan="2" style="text-align: center;">1990</td></tr> </table> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T31N		R24E	R25E	1/4		S13	S18	1990			
T31N													
R24E	R25E												
1/4													
S13	S18												
1990													
80.00	<p>Trail road, bears E. and W.</p>												
	<p>Point for the cor. of secs. 7, 12, 13, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T31N</td></tr> <tr><td style="text-align: center;">R24E</td><td style="text-align: center;">R25E</td></tr> <tr><td style="text-align: center;">S12</td><td style="text-align: center;">S 7</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S13</td><td style="text-align: center;">S18</td></tr> <tr><td colspan="2" style="text-align: center;">1990</td></tr> </table> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 20°55' E., 106.2 ft. dist., with brass cap mkd. T31N R25E S7 RM 106.2 FT TO COR 1990, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 14°01' W., 34.7 ft. dist., with brass cap mkd. T31N R24E S12 RM 34.7 FT TO COR 1990, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T31N		R24E	R25E	S12	S 7	-----		S13	S18	1990	
T31N													
R24E	R25E												
S12	S 7												
-----													
S13	S18												
1990													

Survey of the Sixth Guide Meridian East,  
 (West Boundary),  
 T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in Cottonwood Wash, 136 lks. wide, 10 ft. deep, drains NE.</p> <p>Land, gently rolling.            Soil, sandy clay.            No timber; brush and native grasses.</p>
40.00	<p>North, bet. secs. 7 and 12.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T31N            R24E R25E            1/4            S12   S 7            1990</p> </div>
80.00	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 1, 6, 7, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T31N            R24E   R25E            S 1   S 6            -----            S12   S 7            1990</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

Survey of the Sixth Guide Meridian East,  
 (West Boundary),  
 T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS															
	<p>Land, rolling.            Soil, sandy clay.            No timber; brush and native grasses.</p>														
40.00	<p>North, bet. secs. 1 and 6.            Over rolling land.            Point for the 1/4 sec. cor. of secs. 1 and 6.            Set a brass tablet, 3 1/4 ins diam., 2 1/2 ins. stem, in a drill hole, cemented in place, in sandstone bedrock, with top mkd.</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T31N</td></tr> <tr><td style="text-align: center;">R24E</td><td style="text-align: center;">R25E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr><td colspan="2" style="text-align: center;">1990</td></tr> </table> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the rock tablet.</p>	T31N		R24E	R25E	1/4		S 1	S 6	1990					
T31N															
R24E	R25E														
1/4															
S 1	S 6														
1990															
80.00	<p>Point for the cor. of Tps. 31 and 32 N., Rs. 24 and 25 E.            Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T32N</td></tr> <tr><td style="text-align: center;">R24E</td><td style="text-align: center;">R25E</td></tr> <tr><td style="text-align: center;">S36</td><td style="text-align: center;">S31</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr><td colspan="2" style="text-align: center;">T31N</td></tr> <tr><td colspan="2" style="text-align: center;">1990</td></tr> </table> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T32N		R24E	R25E	S36	S31	-----		S 1	S 6	T31N		1990	
T32N															
R24E	R25E														
S36	S31														
-----															
S 1	S 6														
T31N															
1990															

Survey of the Sixth Guide Meridian East,  
 (West Boundary),  
 T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling.                      Soil, sandy clay with sandstone outcrops.                      No timber; brush and native grasses.</p>
	<p style="text-align: center;">Survey of the East Boundary,                      T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona</p>
	<p>From the cor. of Tps. 30 and 31 N., Rs. 25 and 26 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 16 ins. above ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd. T31N R25E R26E S36 S31 S1 S6 T30N 1991.</p> <p>From this cor. point, U.S. Coast and Geodetic Survey triangulation station "BEAUTIFUL 1951", with published latitude of 36°04'12.342" N. and longitude of 109°36'31.975" W., NAD27, bears N. 13°25' W., 162.31 chs. dist., monumented with a standard brass disk, 3 1/2 ins. diam., cemented flush with the surface of bedrock, with top mkd. BEAUTIFUL 1951 and a triangle.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over rugged land on W. edge of Beautiful Valley.</p>
<p>40.00</p>	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N                      R25E R26E                      1/4                      S36   S31                      1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
<p>80.00</p>	<p>Point for the cor. of secs. 25, 30, 31, and 36.</p>

Survey of the East Boundary,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T31N</p> <table border="1" style="margin: auto;"> <tr> <td>R25E</td> <td>R26E</td> </tr> <tr> <td>S25</td> <td>S30</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S36</td> <td>S31</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rugged. Soil, clay. No timber; sparse native grasses.</p>	R25E	R26E	S25	S30			S36	S31	1991	
R25E	R26E										
S25	S30										
S36	S31										
1991											
	<p>North, bet. secs. 25 and 30.</p>										
	<p>Over rugged land descending into Beautiful Valley.</p>										
<p>19.00</p>	<p>Radio tower, bears West, 11.95 chs. dist.</p>										
<p>40.00</p>	<p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p>										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>										
	<div style="text-align: center;"> <p>T31N</p> <table border="1" style="margin: auto;"> <tr> <td>R25E</td> <td>R26E</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td colspan="2">1/4</td> </tr> <tr> <td>S25</td> <td>S30</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	R25E	R26E			1/4		S25	S30	1991	
R25E	R26E										
1/4											
S25	S30										
1991											
<p>80.00</p>	<p>Point for the cor. of secs. 19, 24, 25, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>										

Survey of the East Boundary,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<div style="text-align: center;"> <p>T31N</p> <table border="1"> <tr> <td>R25E</td> <td>R26E</td> </tr> <tr> <td>S24</td> <td>S19</td> </tr> <tr> <td colspan="2"><hr/></td> </tr> <tr> <td>S25</td> <td>S30</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rugged. Soil, clay. No timber; brush and native grasses.</p>	R25E	R26E	S24	S19	<hr/>		S25	S30	1991	
R25E	R26E										
S24	S19										
<hr/>											
S25	S30										
1991											
	<p>North, bet. secs. 19 and 24.</p> <p>Over rugged land.</p>										
<p>40.00</p>	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>										
	<div style="text-align: center;"> <p>T31N</p> <table border="1"> <tr> <td>R25E</td> <td>R26E</td> </tr> <tr> <td colspan="2">1/4</td> </tr> <tr> <td>S24</td> <td>S19</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	R25E	R26E	1/4		S24	S19	1991			
R25E	R26E										
1/4											
S24	S19										
1991											
<p>80.00</p>	<p>Point for the cor. of secs. 13, 18, 19, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>										
	<div style="text-align: center;"> <p>T31N</p> <table border="1"> <tr> <td>R25E</td> <td>R26E</td> </tr> <tr> <td>S13</td> <td>S18</td> </tr> <tr> <td colspan="2"><hr/></td> </tr> <tr> <td>S24</td> <td>S19</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div>	R25E	R26E	S13	S18	<hr/>		S24	S19	1991	
R25E	R26E										
S13	S18										
<hr/>											
S24	S19										
1991											

Survey of the East Boundary,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Land, rugged. Soil, clay. No timber; brush and native grasses.</p>
	<p>North, bet. secs. 13 and 18.</p>
	<p>Over rolling and broken land.</p>
11.38	<p>Intersect the S. side of a log cabin, 24 x 17 ft., the SE cor. bears ESE, 13 lks. dist., long side bears NNE.</p>
13.75	<p>SW cor. of a wood frame house, 26 x 20 ft., bears East, 44 lks. dist., long side bears NNW.</p>
22.20	<p>Graded road, 30 lks. wide, bears ESE and WNW.</p>
31.30	<p>Trail road, bears NE and SW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R25E R26E 1/4 S13   S18 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
49.20	<p>Trail road, bears NNE and SSW.</p>
80.00	<p>Point for the cor. of secs. 7, 12, 13, and 18.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the East Boundary,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T31N</td></tr> <tr><td>R25E</td><td>R26E</td></tr> <tr><td>S12</td><td>S 7</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S13</td><td>S18</td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, clay. No timber; brush and native grasses.</p>	T31N		R25E	R26E	S12	S 7	-----		S13	S18	1991	
T31N													
R25E	R26E												
S12	S 7												
-----													
S13	S18												
1991													
40.00	<p>North, bet. secs. 7 and 12.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>												
80.00	<div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T31N</td></tr> <tr><td>R25E</td><td>R26E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S12</td><td>S 7</td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 1, 6, 7, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>	T31N		R25E	R26E	1/4		S12	S 7	1991			
T31N													
R25E	R26E												
1/4													
S12	S 7												
1991													
	<div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T31N</td></tr> <tr><td>R25E</td><td>R26E</td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S12</td><td>S 7</td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T31N		R25E	R26E	S 1	S 6	-----		S12	S 7	1991	
T31N													
R25E	R26E												
S 1	S 6												
-----													
S12	S 7												
1991													

Survey of the East Boundary,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, clay. No timber; brush and native grasses.</p> <hr/>
	<p>North, bet. secs. 1 and 6.</p>
	<p>Over rolling land.</p>
22.30	<p>Trail road, bears E. and W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">             T31N              R25E R26E              1/4              S 1   S 6              1991         </p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
60.00	<p>Cottonwood Wash, drains East.</p>
80.00	<p>Point for the cor. of Tps. 31 and 32 N., Rs. 25 and 26 E.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">             T32N              R25E   R26E              S36   S31              -----              S 1   S 6              T31N              1991         </p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Land, rolling. Soil, clay. No timber; brush and native grasses.</p> <hr/>

Survey of the North Boundary,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of Tps. 31 and 32 N., Rs. 25 and 26 E., hereinbefore described.</p> <p>N. 89°59' W., bet. secs. 1 and 36.</p> <p>Over nearly level land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T32N R25E S36 1/4 — S 1 T31N 1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
64.40	<p>Power line, bears NE and SW.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T32N R25E S35   S36 —   — S 2   S 1 T31N 1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, clay. No timber; brush and native grasses.</p> <hr/> <p>N. 89°59' W., bet. secs. 2 and 35.</p> <p>Over nearly level land.</p>

Survey of the North Boundary,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
6.34	E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.
8.57	Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears NE and SW.
10.80	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.
17.25	Power line, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<pre> T32N R25E       S35       1/4 —           S 2           T31N           1991                     </pre>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
70.60	Trail road, bears N. and S.; thence ascend from Beautiful Valley.
78.50	W. rim of Beautiful Valley, bears N. and S.; enter rolling land.
80.00	Point for the cor. of secs. 2, 3, 34, and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<pre> T32N R25E S34   S35 ----- ----- S 3   S 2       T31N       1991                     </pre>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Survey of the North Boundary,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, nearly level to rolling. Soil, clay. No timber; brush and native grasses.</p> <hr/>
	<p>N. 89°59' W., bet. secs. 3 and 34.</p>
	<p>Over rolling land.</p>
7.75	<p>Trail road, bears NNE and SSW.</p>
38.50	<p>Trail road, bears ENE and WSW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T32N R25E S34 1/4 — S 3 T31N 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
74.65	<p>Trail road, bears N. and S.</p>
80.00	<p>Point for the cor. of secs. 3, 4, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T32N R25E S33   S34 —   — S 4   S 3 T31N 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

Survey of the North Boundary,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS															
	<p>Land, rolling. Soil, clay. No timber; brush and native grasses.</p> <hr/>														
	<p>N. 89°59' W., bet. secs. 4 and 33.</p>														
	<p>Over rolling land.</p>														
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 33.</p>														
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>														
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T32N</td><td>R25E</td></tr> <tr><td>S33</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S</td><td>4</td></tr> <tr><td>T31N</td><td></td></tr> <tr><td>1991</td><td></td></tr> </table>	T32N	R25E	S33		1/4	—	S	4	T31N		1991			
T32N	R25E														
S33															
1/4	—														
S	4														
T31N															
1991															
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>														
53.00	<p>Trail road, bears NE and SW.</p>														
80.00	<p>Point for the cor. of secs. 4, 5, 32, and 33.</p>														
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>														
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T32N</td><td>R25E</td></tr> <tr><td>S32</td><td>S33</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S</td><td>5</td></tr> <tr><td>S</td><td>4</td></tr> <tr><td>T31N</td><td></td></tr> <tr><td>1991</td><td></td></tr> </table>	T32N	R25E	S32	S33	<hr/>		S	5	S	4	T31N		1991	
T32N	R25E														
S32	S33														
<hr/>															
S	5														
S	4														
T31N															
1991															
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>														
	<p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p> <hr/>														

Survey of the North Boundary,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>N. 89°59' W., bet. secs. 5 and 32.</p> <p>Over rolling land.</p>
2.45	Trail road, bears NE and SW.
29.60	Trail road, bears NNE and SSW.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 32.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T32N R25E S32 1/4 — S 5 T31N 1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
73.10	Trail road, bears ENE and WSW.
80.00	Point for the cor. of secs. 5, 6, 31, and 32.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T32N R25E S31   S32 —   — S 6   S 5 T31N 1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p> <hr/>

Survey of the North Boundary,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 89°59' W., bet. secs. 6 and 31.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T32N R25E S31 1/4 — S 6 T31N 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
78.47	The cor. of Tps. 31 and 32 N., Rs. 24 and 25 E., hereinbefore described.
	Land, rolling. Soil, sandy clay. No timber; brush and native grasses.
	<p style="text-align: center;">Survey of the Subdivisional Lines, T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona</p>
	From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. T31N R25E S35 S36 S2 S1 T30N 1991.
	N. 0°01' W., bet. secs. 35 and 36.
	Over rolling land.
27.40	Trail road, bears E. and W.
40.00	Point for the 1/4 sec. cor. of secs. 35 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T31N R25E 1/4 S35   S36 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
77.25	Trail road, bears NE and SW.
80.00	Point for the cor. of secs. 25, 26, 35, and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T31N R25E S26   S25 <hr style="width: 100%;"/> S35   S36 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Land, rolling. Soil, clay. No timber; brush and native grasses.
	From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.
	N. 89°59' W., bet. secs. 25 and 36.
	Over rolling and broken land.
32.20	E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.
33.71	Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears N. and S.
35.24	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.995	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R25E S25 1/4 — S36 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
40.70	Power line, bears SSE and NNW.
74.10	Trail road, bears ENE and WSW.
77.25	Trail road, bears NE and SW.
79.99	<p>The cor. of secs. 25, 26, 35, and 36.</p> <p>Land, rolling and broken. Soil, clay. No timber; brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over rolling land.</p>
33.40	Trail road, bears ENE and WSW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R25E 1/4 S26   S25 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
71.65	SW cor. of a stucco house, 24 x 16 ft., bears East, 1.40 chs. dist., long side bears NNW.										
72.10	Trail road, bears ESE and WNW.										
73.13	SW cor. of a wood frame house, 40 x 20 ft., bears East, 1.27 chs. dist., long side bears N.										
80.00	<p>Point for the cor. of secs. 23, 24, 25, and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T31N</td> <td>R25E</td> </tr> <tr> <td>S23</td> <td>S24</td> </tr> <tr> <td>S26</td> <td>S25</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 30 lks. W. of a trail road, bears NNE in curve to the right.</p> <p>Land, rolling. Soil, clay. No timber; brush and native grasses.</p>	T31N	R25E	S23	S24	S26	S25	1991			
T31N	R25E										
S23	S24										
S26	S25										
1991											
40.005	<p>From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°59' W., bet. secs. 24 and 25.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T31N</td> <td>R25E</td> </tr> <tr> <td></td> <td>S24</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S25</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div>	T31N	R25E		S24	1/4	—		S25	1991	
T31N	R25E										
	S24										
1/4	—										
	S25										
1991											

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 23 lks. E. of E. right-of-way fence of U.S. Highway 191, 5 strands, parallels highway.</p> <p>From this cor. point, a U.S. Coast and Geodetic Survey benchmark, bears S. 23°49' W., 84 lks. dist., monumented with a brass disk, 3 1/2 ins. diam., set in a concrete post, 10 ins. square, firmly set, flush with the surface of the ground, with top mkd. 5950.267 J33 1933.</p> <p>Cor. is located 23 lks. E. of E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.</p>
41.80	Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears SSE and NNW.
43.45	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.
46.35	Power line, bears SSE and NNW.
80.01	<p>The cor. of secs. 23, 24, 25, and 26.</p> <p>Land, rolling and broken. Soil, clay. No timber; brush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 23 and 24.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R25E 1/4 S23   S24 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
44.90	Trail road, bears SE and NW.
50.40	Wash, 38 lks. wide, 4 ft. deep, drains WNW.

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
64.15	Center shaft of windmill, bears West, 8.05 chs. dist., mkd. 10T548.										
69.45	Trail road, bears NE and SW.										
70.10	Trail road, bears ESE and WNW.										
71.02	Power line, bears SSE and NNW.										
72.70	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.										
76.07	Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears SSE and NNW.										
79.45	E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.										
80.00	Point for the cor. of secs. 13, 14, 23, and 24.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T31N R25E</td> </tr> <tr> <td style="text-align: center;">S14</td> <td style="text-align: center;">S13</td> </tr> <tr> <td style="border-left: 1px solid black; border-right: 1px solid black; border-bottom: 1px solid black;"></td> <td style="border-left: 1px solid black; border-right: 1px solid black; border-bottom: 1px solid black;"></td> </tr> <tr> <td style="text-align: center;">S23</td> <td style="text-align: center;">S24</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T31N R25E		S14	S13			S23	S24	1991	
T31N R25E											
S14	S13										
S23	S24										
1991											
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.										
	Cor. is located 28 lks. E. of E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.										
	Land, rolling. Soil, clay. No timber; brush and native grasses.										
	From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.										
	N. 89°58' W., bet. secs. 13 and 24.										
	Over rolling land.										
34.15	Graded road, 30 lks. wide, bears SSE and NNW.										
40.005	Point for the 1/4 sec. cor. of secs. 13 and 24.										

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R25E S13 1/4 — S24 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
76.85	Trail road, bears SSE and NNW.
80.01	<p>The cor. of secs. 13, 14, 23, and 24.</p> <p>Land, rolling. Soil, clay. No timber; brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over rolling land.</p>
7.00	Trail road, bears SSE and NNW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R25E 1/4 S14   S13 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	Point for the cor. of secs. 11, 12, 13, and 14.

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T31N</td> <td>R25E</td> </tr> <tr> <td>S11</td> <td>S12</td> </tr> <tr> <td>S14</td> <td>S13</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, clay. No timber; brush and native grasses.</p>	T31N	R25E	S11	S12	S14	S13	1991			
T31N	R25E										
S11	S12										
S14	S13										
1991											
	<p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°59' W., bet. secs. 12 and 13.</p> <p>Over rolling and broken land.</p>										
39.995	<p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T31N</td> <td>R25E</td> </tr> <tr> <td colspan="2">S12</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td colspan="2">S13</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T31N	R25E	S12		1/4	—	S13		1991	
T31N	R25E										
S12											
1/4	—										
S13											
1991											
79.99	<p>The cor. of secs. 11, 12, 13, and 14.</p> <p>Land, rolling and broken. Soil, clay. No timber; brush and native grasses.</p>										

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>N. 0°01' W., bet. secs. 11 and 12.</p>
	<p>Over rolling land.</p>
29.80	<p>W. rim of Beautiful Valley, bears E. and W.; thence descend over broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12; falls on a sheer cliff, where it is impractical to construct a permanent monument.</p>
	<p>From this cor. point, the selected point for the witness cor. to the 1/4 sec. cor. of secs. 11 and 12, bears S. 20°00' E., 4.00 chs. dist.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, encircled with a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">WC T31N R25E 1/4 S11   S12 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Thence enter nearly level land in Beautiful Valley.</p>
61.30	<p>Graded road, 38 lks. wide, bears ESE and WNW.</p>
73.20	<p>Trail road, bears ENE and WSW.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 11, and 12.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R25E S 2   S 1 ----- S11   S12 1991</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, broken and nearly level. Soil, clay and sandstone outcrops. No timber; brush and native grasses.</p>
	<p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°59' W., bet. secs. 1 and 12.</p> <p>Over nearly level land.</p>
31.60	Graded road, 38 lks. wide, bears NE and SW.
39.995	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R25E S 1 1/4 — S12 1991</p>
73.70	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Trail road, bears ENE and WSW.</p>
79.99	<p>The cor. of secs. 1, 2, 11, and 12.</p> <p>Land, nearly level. Soil, clay. No timber; brush and native grasses.</p>
40.00	<p>N. 0°01' W., bet. secs. 1 and 2.</p> <p>Over nearly level land.</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.99	<p style="text-align: center;">T31N R25E 1/4 S 2   S 1 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, nearly level. Soil, clay. No timber; brush and native grasses.</p>
1.20	<p>From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T31N R25E S34 S35 S3 S2 T30N 1991.</p> <p>From this cor. point, the 20 Mile Cor. of the 1869 survey of the W. bdy. of the Navajo Indian Reservation, bears N. 72°54' E., 50.37 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. NIR 20M 1920. As it is impracticable to bury the iron post, remove brass cap and mark AM on the N. side of the iron post.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over rolling land.</p>
2.45	Trail road, bears E. and W.
40.00	Trail road, bears E. and W.
	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R25E 1/4 S34   S35 1991</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>										
60.20	<p>Trail road, bears ENE and WSW.</p>										
80.00	<p>Point for the cor. of secs. 26, 27, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T31N</td> <td style="padding: 0 5px;">R25E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S27</td> <td style="padding: 0 5px;">S26</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S34</td> <td style="padding: 0 5px;">S35</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, clay. No timber; brush and native grasses.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>West, bet. secs. 26 and 35.</p> <p>Over rolling land.</p>	T31N	R25E	S27	S26	S34	S35	1991			
T31N	R25E										
S27	S26										
S34	S35										
1991											
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T31N</td> <td style="padding: 0 5px;">R25E</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S26</td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="padding: 0 5px;">—</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S35</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T31N	R25E		S26	1/4	—		S35	1991	
T31N	R25E										
	S26										
1/4	—										
	S35										
1991											

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point, the 21 Mile Cor. of the 1869 survey of the W. bdy. of the Navajo Indian Reservation, bears N. 28°44' E., 15.96 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. NIR 21M 1920. As it is impracticable to bury the iron post, remove brass cap and mark AM on the N. side of the iron post.</p>
41.15	<p>Trail road, bears NNE and SSW.</p>
80.00	<p>The cor. of secs. 26, 27, 34, and 35.</p> <p>Land, rolling. Soil, clay. No timber; brush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>Over rolling land.</p>
26.90	<p>Trail road, bears E. and W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R25E 1/4 S27   S26 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 22, 23, 26, and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R25E S22   S23 ----- S27   S26 1991</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 120 lks. S. of a trail road, bears E. and W.</p> <p>Land, rolling. Soil, clay. No timber; brush and native grasses.</p>
	<p>From the cor. of secs. 23, 24, 25, and 26.</p> <p>West, bet. secs. 23 and 26.</p> <p>Over rolling land.</p>
39.995	<p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R25E S23 1/4 — S26 1991</p>
70.10	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the 22 Mile Cor. of the 1869 survey of the W. bdy. of the Navajo Indian Reservation, bears N. 26°28' E., 16.79 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. NIR 22M 1920. As it is impracticable to bury the iron post, remove brass cap and mark AM on the N. side of the iron post.</p>
79.99	<p>Trail road, bears NE and SW.</p>
79.99	<p>The cor. of secs. 22, 23, 26, and 27.</p> <p>Land, rolling. Soil, clay. No timber; brush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over rolling land.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
7.20	Trail road, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T31N R25E 1/4 S22   S23 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.00	Point for the cor. of secs. 14, 15, 22, and 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T31N R25E S15   S14 ----- S22   S23 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	<p>Land, rolling. Soil, clay. No timber; brush and native grasses.</p>
	<hr/> <p>From the cor. of secs. 13, 14, 23, and 24.</p>
	West, bet. secs. 14 and 23.
	Over rolling land.

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
1.96	Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears SSE and NNW.
3.69	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.
4.50	Power line, bears SSE and NNW.
20.00	Trail road, bears SSE and NNW.
39.995	Point for the 1/4 sec. cor. of secs. 14 and 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T31N R25E S14 1/4 — S23 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
62.20	Trail road, bears ENE and WSW.
79.99	The cor. of secs. 14, 15, 22, and 23.
	Land, rolling. Soil, clay. No timber; brush and native grasses.
	N. 0°01' W., bet. secs. 14 and 15.
	Over rolling land.
8.05	Center of Navajo Route 4, asphalt pavement, 36 lks. wide, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 15.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p style="text-align: center;">T31N R25E 1/4 S15   S14 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 10, 11, 14, and 15.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T31N R25E S10   S11 ----- S15   S14 1991</p> <p>Deposit a magnet, 1 in. long, 7/8 in. diam., beneath the brass tablet.</p> <p>Land, rolling. Soil, clay with sandstone outcrops. No timber; brush and native grasses.</p>
39.99	<p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>West, bet. secs. 11 and 14.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R25E S11 1/4 — S14 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point, the 24 Mile Cor. of the 1869 survey of the W. bdy. of the Navajo Indian Reservation, bears N. 22°43' E., 18.58 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. NIR 24M 1920. As it is impracticable to bury the iron post, remove brass cap and mark AM on the N. side of the iron post.</p>
40.63	<p>E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.</p>
42.23	<p>Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears SSE and NNW.</p>
43.94	<p>W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.</p>
45.70	<p>Power line, bears SSE and NNW.</p>
79.98	<p>The cor. of secs. 10, 11, 14, and 15.</p>
	<p>Land, rolling. Soil, clay. No timber; brush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 10 and 11.</p>
	<p>Over rolling and broken land.</p>
13.40	<p>Graded road, 23 lks. wide, bears E. and W.</p>
38.70	<p>NE cor. of a stucco house, 30 x 25 ft., bears West, 4.75 chs. dist., long side bears W.</p>
39.85	<p>The southernmost cor. of an octagonal wood frame hogan, 8 ft. sides, bears West, 4.00 chs. dist.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set flush with the surface of the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R25E 1/4 S10   S11 1991</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS									
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.								
58.40	Trail road, bears ENE and WSW.								
71.66	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.								
74.98	Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears SSE and NNW.								
75.50	Cottonwood Wash, 23 lks. wide, 5 ft. deep, drains NE.								
78.49	E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, bears SSE on curve to the left.								
80.00	Point for the cor. of secs. 2, 3, 10, and 11.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.								
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 2px;">T31N</td> <td style="padding: 2px;">R25E</td> </tr> <tr> <td style="padding: 2px;">S 3</td> <td style="padding: 2px;">S 2</td> </tr> <tr> <td style="padding: 2px;">S10</td> <td style="padding: 2px;">S11</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px;">1991</td> </tr> </table>	T31N	R25E	S 3	S 2	S10	S11	1991	
T31N	R25E								
S 3	S 2								
S10	S11								
1991									
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 50 lks. E. of E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, bears N. on curve to the right.</p> <p>Land, rolling and broken. Soil, clay. No timber; brush and native grasses.</p>								
	<p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>West, bet. secs. 2 and 11.</p> <p>Over nearly level land.</p>								
31.50	Cottonwood Wash, 23 lks. wide, 4 ft. deep, drains ENE.								
39.985	Point for the 1/4 sec. cor. of secs. 2 and 11.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.								

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T31N R25E S 2 1/4 — S11 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the 25 Mile Cor. of the 1869 survey of the W. bdy. of the Navajo Indian Reservation, bears N. 18°46' E., 14.34 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 24 ins. above ground, with brass cap mkd. NIR 25M 1920. As it is impracticable to bury the iron post, remove brass cap and mark AM on the N. side of the iron post.</p>
59.50	Power line, bears NE and SW.
79.97	<p>The cor. of secs. 2, 3, 10, and 11.</p> <p>Land, nearly level. Soil, clay. No timber; brush and native grasses.</p>
	<p>N. 0°03' W., bet. secs. 2 and 3.</p> <p>Over nearly level land.</p>
10.00	E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.
13.39	Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears NNE on curve to the right.
15.92	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.
22.20	Power line, bears NE and SW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T31N R25E 1/4 S 3   S 2 1991</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of Tp., hereinbefore described.</p> <p>Land, nearly level to rolling. Soil, clay. No timber; brush and native grasses.</p>
40.00	<p>From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. T31N R25E S33 S34 S4 S3 T30N 1991.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over nearly level land.</p> <p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R25E 1/4 S33   S34 1991</p>
70.05	<p>Trail road, bears ENE and WSW.</p>
80.00	<p>Point for the cor. of secs. 27, 28, 33, and 34.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T31N</td> <td>R25E</td> </tr> <tr> <td>S28</td> <td>S27</td> </tr> <tr> <td>S33</td> <td>S34</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, clay. No timber; brush and native grasses.</p>	T31N	R25E	S28	S27	S33	S34	1991			
T31N	R25E										
S28	S27										
S33	S34										
1991											
	<p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>N. 89°59' W., bet. secs. 27 and 34.</p> <p>Over nearly level land.</p>										
13.10	Trail road, bears N. and S.										
40.00	Point for the 1/4 sec. cor. of secs. 27 and 34.										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T31N</td> <td>R25E</td> </tr> <tr> <td></td> <td>S27</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S34</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T31N	R25E		S27	1/4	—		S34	1991	
T31N	R25E										
	S27										
1/4	—										
	S34										
1991											
58.70	Trail road, bears ENE and WSW.										
80.00	<p>The cor. of secs. 27, 28, 33, and 34.</p> <p>Land, nearly level. Soil, clay. No timber; brush and native grasses.</p>										

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over nearly level land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T31N R25E 1/4 S28   S27 1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
59.90	<p>Trail road, bears ENE and WNW.</p>
80.00	<p>Point for the cor. of secs. 21, 22, 27, and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T31N R25E S21   S22 ----- S28   S27 1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, clay. No timber; brush and native grasses.</p>
12.70	<p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>N. 89°59' W., bet. secs. 22 and 27.</p> <p>Over nearly level land.</p> <p>Trail road, bears N. and S.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.005	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R25E S22 1/4 — S27 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
46.20	<p>Trail road, bears N. and S.</p>
80.01	<p>The cor. of secs. 21, 22, 27, and 28.</p> <p>Land, nearly level. Soil, clay. No timber; brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 21 and 22.</p> <p>Over rolling land.</p>
18.60	<p>Graded road, 30 lks. wide, bears NE and SW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R25E 1/4 S21   S22 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
54.10	<p>SE cor. of barbed wire fence enclosure, bears West, 8.30 chs. dist., fences extending WSW and NNW.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
78.67	Center of Navajo Route 4, asphalt pavement, 38 lks. wide, bears E. and W.										
80.00	<p>Point for the cor. of secs. 15, 16, 21, and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T31N</td> <td>R25E</td> </tr> <tr> <td>S16</td> <td>S15</td> </tr> <tr> <td>S21</td> <td>S22</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, clay. No timber; brush and native grasses.</p>	T31N	R25E	S16	S15	S21	S22	1991			
T31N	R25E										
S16	S15										
S21	S22										
1991											
40.01	<p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>N. 89°59' W., bet. secs. 15 and 22.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T31N</td> <td>R25E</td> </tr> <tr> <td></td> <td>S15</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S22</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div>	T31N	R25E		S15	1/4	—		S22	1991	
T31N	R25E										
	S15										
1/4	—										
	S22										
1991											

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 80 lks. S. of center of Navajo Route 4, asphalt pavement, bears E. and W.</p> <p>From this cor. point, a U.S. Geological Survey benchmark, bears S. 80°44' W., 3.51 chs. dist., monumented with a brass tablet, 3 1/2 ins. diam., set in a concrete post, 6 ins. diam., firmly set, flush with the surface of the ground, with top mkd. ELEV. 5703 FT. ABOVE SEA 28 DOR 1972 and a triangle.</p>
61.10	Center of Navajo Route 4, asphalt pavement, 38 lks. wide, bears ENE and WSW.
80.02	<p>The cor. of secs. 15, 16, 21, and 22.</p> <p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
	<p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over rolling land.</p>
34.25	Trail road, bears ESE and WNW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R25E 1/4 S16   S15 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
80.00	<p>Point for the cor. of secs. 9, 10, 15, and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table data-bbox="852 451 998 609" style="margin-left: auto; margin-right: auto;"> <tr> <td>T31N</td> <td>R25E</td> </tr> <tr> <td>S 9</td> <td>S10</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S16</td> <td>S15</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, clay. No timber; brush and native grasses.</p>	T31N	R25E	S 9	S10			S16	S15	1991	
T31N	R25E										
S 9	S10										
S16	S15										
1991											
	<p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>N. 89°59' W., bet. secs. 10 and 15.</p> <p>Over rolling land.</p>										
31.50	<p>Trail road, bears NNE and SSW.</p>										
40.02	<p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table data-bbox="852 1312 998 1470" style="margin-left: auto; margin-right: auto;"> <tr> <td>T31N</td> <td>R25E</td> </tr> <tr> <td></td> <td>S10</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S15</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T31N	R25E		S10	1/4	—		S15	1991	
T31N	R25E										
	S10										
1/4	—										
	S15										
1991											
57.70	<p>Trail road, bears NE and SW.</p>										
80.04	<p>The cor. of secs. 9, 10, 15, and 16.</p> <p>Land, rolling. Soil, clay. No timber; brush and native grasses.</p>										

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>N. 0°02' W., bet. secs. 9 and 10. Over nearly level land.</p>
30.25	Trail road, bears SE and NW.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 10.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R25E 1/4 S 9   S10 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
42.70	Power line, bears FNE and WSW.
78.50	Cottonwood Wash, 23 lks. wide, 3 ft. deep, drains ESE.
80.00	Point for the cor. of secs. 3, 4, 9, and 10.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R25E S 4   S 3 ----- S 9   S10 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Land, nearly level. Soil, sandy clay. No timber; brush and native grasses.</p>
	<p>From the cor. of secs. 2, 3, 10, and 11.</p>
	<p>N. 89°59' W., bet. secs. 3 and 10.</p>
	<p>Over nearly level land.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
2.05	Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears N. on curve to the right.
3.58	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.
24.05	Power line, bears NE and SW.
32.10	Graded road, 30 lks. wide, bears ENE and WSW.
40.02	Point for the 1/4 sec. cor. of secs. 3 and 10.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T31N R25E S 3 1/4 — S10 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
42.70	Trail road, bears NNE and SSW.
50.60	Trail road, bears NE in curve to the right.
57.20	Trail road, bears ESE and WNW.
80.04	The cor. of secs. 3, 4, 9, and 10.  Land, nearly level. Soil, sandy clay. No timber; brush and native grasses.
	N. 0°02' W., bet. secs. 3 and 4.  Over rolling land.
5.80	Trail road, bears ESE and WNW.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 4.

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R25E 1/4 S 4   S 3 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
50.50	<p>Trail road, bears NE and SW.</p>
	<p>80.00 The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., hereinbefore described.</p>
	<p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
	<p>From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., monumented with stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T31N R25E S32 S33 S5 S4 T30N 1991.</p>
	<p>N. 0°03' W., bet. secs. 32 and 33.</p>
	<p>Over nearly level land.</p>
5.30	<p>Trail road, bears SE and NW.</p>
33.30	<p>Trail road, bears ENE and WSW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R25E 1/4 S32   S33 1991</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
80.00	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 28, 29, 32, and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T31N</td> <td>R25E</td> </tr> <tr> <td>S29</td> <td>S28</td> </tr> <tr> <td colspan="2" style="text-align: center;"> </td> </tr> <tr> <td>S32</td> <td>S33</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay. No timber; brush and native grasses.</p>	T31N	R25E	S29	S28			S32	S33	1991	
T31N	R25E										
S29	S28										
S32	S33										
1991											
39.995	<p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>West, bet. secs. 28 and 33.</p> <p>Over nearly level land.</p> <p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T31N</td> <td>R25E</td> </tr> <tr> <td></td> <td>S28</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S33</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T31N	R25E		S28	1/4	—		S33	1991	
T31N	R25E										
	S28										
1/4	—										
	S33										
1991											
47.55	Trail road, bears NNE and SSW.										
79.99	The cor. of secs. 28, 29, 32, and 33.										

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, nearly level. Soil, sandy clay. No timber; brush and native grasses.</p>
	<p>N. 0°03' W., bet. secs. 28 and 29.</p>
	<p>Over rolling land.</p>
34.60	<p>Graded road, 30 lks. wide, bears NE and SW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R25E 1/4 S29   S28 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
57.45	<p>Trail road, bears ENE and WSW.</p>
80.00	<p>Point for the cor. of secs. 20, 21, 28, and 29.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R25E S20   S21 ----- S29   S28 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>N. 89°59' W., bet. secs. 21 and 28.</p> <p>Over rolling land.</p>
22.80	<p>Graded road, 30 lks. wide, bears NNE and SSW.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R25E S21 1/4 — S28 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
79.98	<p>The cor. of secs. 20, 21, 28, and 29.</p> <p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
	<p>N. 0°03' W., bet. secs. 20 and 21.</p> <p>Over rolling land.</p>
39.10	<p>Trail road, bears ENE and WSW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R25E 1/4 S20   S21 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
74.50	Center of Navajo Route 4, asphalt pavement, 38 lks. wide, bears E. and W.										
80.00	<p>Point for the cor. of secs. 16, 17, 20, and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T31N</td> <td>R25E</td> </tr> <tr> <td>S17</td> <td>S16</td> </tr> <tr> <td>S20</td> <td>S21</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 80 lks. E. and 280 lks. S. of a trail road, bears NNE and SSW.</p> <p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>	T31N	R25E	S17	S16	S20	S21	1991			
T31N	R25E										
S17	S16										
S20	S21										
1991											
	<p>From the cor. of secs. 15, 16, 21, and 22.</p> <p>N. 89°59' W., bet. secs. 16 and 21.</p> <p>Over rolling land.</p>										
39.99	<p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T31N</td> <td>R25E</td> </tr> <tr> <td></td> <td>S16</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S21</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T31N	R25E		S16	1/4	—		S21	1991	
T31N	R25E										
	S16										
1/4	—										
	S21										
1991											
79.98	The cor. of secs. 16, 17, 20, and 21.										

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p> <hr/>
	<p>N. 0°03' W., bet. secs. 16 and 17.</p>
	<p>Over rolling land.</p>
<p>40.00</p>	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R25E 1/4 S17   S16 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
<p>73.20</p>	<p>Power line, bears ENE and WSW.</p>
<p>80.00</p>	<p>Point for the cor. of secs. 8, 9, 16, and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R25E S 8   S 9 ----- S17   S16 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p> <hr/>

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>West, bet. secs. 9 and 16.</p> <p>Over nearly level land.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R25E S 9 1/4 — S16 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
54.30	Trail road, bears NNE and SSW.
69.00	Power line, bears ENE and WSW.
79.98	<p>The cor. of secs. 8, 9, 16, and 17.</p> <p>Land, nearly level. Soil, sandy clay. No timber; brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over nearly level land.</p>
30.30	Wash, 23 lks. wide, 2 ft. deep, drains NE.
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R25E 1/4 S 8   S 9 1991</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.										
62.60	Cottonwood Wash, 23 lks. wide, 2 ft. deep, drains ENE.										
63.15	Trail road, bears ESE in curve to the right.										
73.35	Trail road, bears ENE and WSW.										
80.00	Point for the cor. of secs. 4, 5, 8, and 9.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 0 10px;">T31N</td> <td style="padding: 0 10px;">R25E</td> </tr> <tr> <td style="padding: 0 10px;">S 5</td> <td style="padding: 0 10px;">S 4</td> </tr> <tr> <td colspan="2" style="text-align: center;">— —</td> </tr> <tr> <td style="padding: 0 10px;">S 8</td> <td style="padding: 0 10px;">S 9</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T31N	R25E	S 5	S 4	— —		S 8	S 9	1991	
T31N	R25E										
S 5	S 4										
— —											
S 8	S 9										
1991											
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.										
	<p>Land, nearly level. Soil, sandy clay. No timber; brush and native grasses.</p>										
	From the cor. of secs. 3, 4, 9, and 10.										
	West, bet. secs. 4 and 9.										
	Over nearly level land.										
34.65	Top of earthen dike, 30 lks. wide, bears SSE and NNW.										
39.985	Point for the 1/4 sec. cor. of secs. 4 and 9.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 0 10px;">T31N</td> <td style="padding: 0 10px;">R25E</td> </tr> <tr> <td style="padding: 0 10px;">S 4</td> <td></td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="padding: 0 10px;">—</td> </tr> <tr> <td style="padding: 0 10px;">S 9</td> <td></td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T31N	R25E	S 4		1/4	—	S 9		1991	
T31N	R25E										
S 4											
1/4	—										
S 9											
1991											

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
45.85	Trail road, bears NE and SW.
53.45	Trail road, bears ENE and WSW.
54.20	Center shaft of a windmill, bears South, 8.00 chs. dist.
63.40	Trail road, bears SSE and NNW.
79.97	The cor. of secs. 4, 5, 8, and 9.  Land, nearly level. Soil, sandy clay. No timber; brush and native grasses.
	N. 0°04' W., bet. secs. 4 and 5.  Over rolling land.
21.10	Trail road, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  T31N R25E 1/4 S 5   S 4 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.  Cor. is located 90 lks. N. of a trail road, bears ENE and WSW.
59.35	Trail road, bears ENE and WSW.
78.10	Trail road, bears SE and NW.
80.01	The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., hereinbefore described.

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p> <hr/> <p>From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. T31N R25E S31 S32 S6 S5 T30N 1991.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over nearly level land.</p>
7.85	Top of earthen dike, 18 lks. wide, bears ENE and WSW.
17.40	Graded road, 38 lks. wide, bears NE and SW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T31N R25E 1/4 S31   S32 1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 29, 30, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T31N R25E S30   S29 ----- S31   S32 1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, nearly level. Soil, sandy clay. No timber; brush and native grasses.</p>
	<p>From the cor. of secs. 28, 29, 32, and 33. N. 89°59' W., bet. secs. 29 and 32. Over nearly level land.</p>
31.95	Graded road, 38 lks. wide, bears NE and SW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R25E S29 1/4 — S32 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
65.00	Trail road, bears SE and NW.
80.00	The cor. of secs. 29, 30, 31, and 32.
	<p>Land, nearly level. Soil, sandy clay. No timber; brush and native grasses.</p>
	<p>N. 89°59' W., bet. secs. 30 and 31. Over rolling land.</p>
14.34	NE cor. of a house, 20 x 12 ft., bears South, 26 lks. dist., long side bears NNE.
19.45	SE cor. of a house, 35 x 20 ft., bears North, 9.40 chs. dist., long side bears N.
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31.

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
78.93	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R25E S30 1/4 — S31 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
4.45	<p>From the cor. of secs. 29, 30, 31, and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over rolling land.</p> <p>Trail road, bears ESE and WNW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R25E 1/4 S30   S29 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
40.95	Trail road, bears E. and W.
75.85	Trail road, bears NE and SW.
80.00	Point for the cor. of secs. 19, 20, 29, and 30.

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T31N</td> <td>R25E</td> </tr> <tr> <td>S19</td> <td>S20</td> </tr> <tr> <td>S30</td> <td>S29</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>	T31N	R25E	S19	S20	S30	S29	1991			
T31N	R25E										
S19	S20										
S30	S29										
1991											
	<p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>N. 89°59' W., bet. secs. 20 and 29.</p> <p>Over rolling land.</p>										
<p>40.005</p>	<p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T31N</td> <td>R25E</td> </tr> <tr> <td colspan="2">S20</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td colspan="2">S29</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T31N	R25E	S20		1/4	—	S29		1991	
T31N	R25E										
S20											
1/4	—										
S29											
1991											
<p>41.85</p>	<p>Trail road, bears SSE and NNW.</p>										
<p>73.70</p>	<p>Trail road, bears ENE and WSW.</p>										
<p>80.01</p>	<p>The cor. of secs. 19, 20, 29, and 30.</p> <p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>										

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	N. 89°59' W., bet. secs. 19 and 30.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T31N R25E S19 1/4 — S30 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
78.84	The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., hereinbefore described.
	Land, rolling. Soil, sandy clay. No timber; brush and native grasses.
	From the cor. of secs. 19, 20, 29, and 30.
	N. 0°03' W., bet. secs. 19 and 20.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 20.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T31N R25E 1/4 S19   S20 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
70.27	Center of Navajo Route 4, asphalt pavement, 41 lks. wide, bears E. and W.

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
80.00	<p>Point for the cor. of secs. 17, 18, 19, and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T31N</td> <td>R25E</td> </tr> <tr> <td>S18</td> <td>S17</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S19</td> <td>S20</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>	T31N	R25E	S18	S17			S19	S20	1991	
T31N	R25E										
S18	S17										
S19	S20										
1991											
	<p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>N. 89°59' W., bct. secs. 17 and 20.</p> <p>Over nearly level land.</p>										
40.005	<p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T31N</td> <td>R25E</td> </tr> <tr> <td></td> <td>S17</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S20</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T31N	R25E		S17	1/4	—		S20	1991	
T31N	R25E										
	S17										
1/4	—										
	S20										
1991											
48.30	<p>Trail road, bears SSE and NNW.</p>										
80.01	<p>The cor. of secs. 17, 18, 19, and 20.</p> <p>Land, nearly level. Soil, sandy clay. No timber; brush and native grasses.</p>										

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>N. 89°59' W., bet. secs. 18 and 19.</p>
	<p>Over rolling land.</p>
38.00	<p>Power line, bears NE and SW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 18 and 19.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R25E</p>
	<p style="text-align: center;">S18</p>
	<p style="text-align: center;">1/4 —</p>
	<p style="text-align: center;">S19</p>
	<p style="text-align: center;">1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
78.74	<p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., hereinbefore described.</p>
	<p>Land, rolling.</p>
	<p>Soil, sandy clay.</p>
	<p>No timber; brush and native grasses.</p>
	<hr/> <p>From the cor. of secs. 17, 18, 19, and 20.</p>
	<p>N. 0°03' W., bet. secs. 17 and 18.</p>
	<p>Over rolling land.</p>
23.60	<p>Power line, bears NE and SW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R25E</p>
	<p style="text-align: center;">1/4</p>
	<p style="text-align: center;">S18   S17</p>
	<p style="text-align: center;">1991</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>										
65.15	<p>Trail road, bears SE and NW.</p>										
80.00	<p>Point for the cor. of secs. 7, 8, 17, and 18.</p>										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T31N</td> <td>R25E</td> </tr> <tr> <td>S 7</td> <td>S 8</td> </tr> <tr> <td>S18</td> <td>S17</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div>	T31N	R25E	S 7	S 8	S18	S17	1991			
T31N	R25E										
S 7	S 8										
S18	S17										
1991											
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>										
	<p>From the cor. of secs. 8, 9, 16, and 17.</p> <p>West, bet. secs. 8 and 17.</p> <p>Over rolling land.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p>										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T31N</td> <td>R25E</td> </tr> <tr> <td></td> <td>S 8</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S17</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div>	T31N	R25E		S 8	1/4	—		S17	1991	
T31N	R25E										
	S 8										
1/4	—										
	S17										
1991											
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>										
73.50	<p>Trail road, bears NNE and SSW.</p>										
80.00	<p>The cor. of secs. 7, 8, 17, and 18.</p>										

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
	<p>N. 89°59' W., bet. secs. 7 and 18.</p>
	<p>Over rolling land.</p>
31.55	<p>Trail road, bears NE and SW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R25E S 7 1/4 — S18 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
78.65	<p>The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
	<p>From the cor. of secs. 7, 8, 17, and 18.</p>
	<p>N. 0°03' W., bet. secs. 7 and 8.</p>
	<p>Over nearly level land.</p>
24.75	<p>Trail road, bears NE and SW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 8.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T31N R25E 1/4 S 7   S 8 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
47.10	<p>Cottonwood Wash, 38 lks. wide, 5 ft. deep, drains NE.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 7, and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R25E S 6   S 5 ----- S 7   S 8 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay. No timber; brush and native grasses.</p>
	<p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>N. 89°59' W., bet. secs. 5 and 8.</p> <p>Over rolling land.</p>
22.70	<p>Trail road, bears ESE and WNW.</p>
40.005	<p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T31N R25E S 5 1/4 — S 8 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
42.35	Trail road, bears NNE and SSW.
80.01	<p>The cor. of secs. 5, 6, 7, and 8.</p> <p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
	<p>N. 89°59' W., bet. secs. 6 and 7.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R25E S 6 1/4 — S 7 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
78.57	<p>The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 0°04' W., bet. secs. 5 and 6.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R25E 1/4 S 6   S 5 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.01	<p>The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
<b>GENERAL DESCRIPTION</b>	
<p>The area surveyed is within the Navajo Indian Reservation, approximately 6 miles south of Chinle, Arizona. The terrain is mostly rolling land with some broken badlands on the eastern part of the township. There are numerous washes, and the drainage is northerly.</p> <p>Elevation varies from 5,600 to 6,000 feet above sea level. The soil is mostly sandy clay, with clay in the eastern portion of the township. The vegetation consists of native grasses, greasewood, rabbitbrush and scattered cacti.</p> <p>Principal access to the township is provided by U.S. Highway 191, which enters the township in section 36 and exits in section 2. Navajo Route 4 enters the township in section 19 and intersects U.S. Highway 191 in section 14. There are graded roads and trail roads throughout the township. Permanent residences are scattered throughout the township. Much of the township is used for the grazing of sheep, cattle and horses.</p> <p>There is no evidence of any kind of mining activity. The mean magnetic declination is 12 1/2° E.</p>	

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## FIELD ASSISTANTS

NAMES	CAPACITY
Jones Curtiss	Surveying Technician
Daniel Bryan	Engineering Technician
Wilfred Chee	Engineering Technician
Nelson Kinsel	Engineering Technician
Reuben Mason	Engineering Technician
Andrew Murphy	Engineering Technician
Barney Woodie	Engineering Technician
Angela Segay	Resource Apprenticeship Student

CERTIFICATE OF SURVEY

I, Leonard R. Sandoval, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 22th day of November, 1989, I have surveyed the Sixth Guide Meridian East, (west boundary), the east and north boundaries, and the subdivisional lines of Township 31 North, Range 25 East, of the Gila and Salt River Meridian, in the state of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

May 19, 1993  
(Date)

Leonard R. Sandoval  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Arizona State Office  
Phoenix, Arizona

The foregoing field notes of the survey of the Sixth Guide Meridian East, (west boundary), the east and north boundaries, and the subdivisional lines of Township 31 North, Range 25 East, Gila and Salt River Meridian, Arizona, executed by Leonard R. Sandoval, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

MAY 25 1993  
(Date)

James P. Kelley  
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 31 N., R. 25 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~