

ORIGINAL

1

BOOK 5399

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES  
OF THE  
DEPENDENT RESURVEY

---

OF

---

A PORTION OF

---

THE SOUTH BOUNDARY

---

OF

---

TOWNSHIP 19 SOUTH, RANGE 16 EAST

---

---

---

---

---

---

---

---

Of the Gila and Salt River Meridian,  
In the State of Arizona

EXECUTED BY  
Clyde J. King, Cadastral Surveyor

---

Under Special Instructions dated June 14, 1993, approved June 14, 1993, which provided for the surveys included under Group Number 758, and assignment instructions dated June 14, 1993.

Survey Commenced June 16, 1993  
Survey Completed July 1, 1993

INDEX DIAGRAM

TOWNSHIP 19 SOUTH, RANGE 16 EAST,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36
10	9	8	6	4	

## T. 19 S., R. 16 E., Gila and Salt River Mer., Arizona

## CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary, Township 19 South, Range 16 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this resurvey is as follows: The south boundary was surveyed by Theodore F. White in 1874. The SW township corner was remonumented in a resurvey of a portion of Township 19 South, Range 15 East by William B. Kimmel in 1926.

This resurvey was executed in response to a request for survey made by the Director of Lands and Minerals, United States Department of Agriculture, Forest Service, Southwest Region, Albuquerque, New Mexico.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated June 14, 1993, for Group No. 758, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of all lines were determined by direct hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured with a Topcon GTS-3B total station instrument.

The geographic position of the SW cor. of sec. 31, was determined by differential positioning using the Ashtech MXII Geodetic Positioning System. U. S. Geological Survey triangulation station "GREAT" was used as a control station. The position is as follows:

Latitude: 31°43'53.60" N. Longitude: 110°45'20.44" W. NAD 27

The mean magnetic declination as taken from quadrangle map SONOITA, ARIZ., published in 1981 by U.S. Geological Survey, is 12° E.

Dependent Resurvey of a Portion of the South Boundary  
T. 19 S., R. 16 E., Gila and Salt River Mer., Arizona

CHAINS

Restoring the survey executed by  
Theodore F. White, in 1874

Beginning at the cor. of secs. 1, 2, 35, and 36, reestablished by W.L. Settlemeyer, R.L.S. 7599, monumented with an iron post, 1 in. diam., firmly set, encased in a concrete cylinder, 6 ins. diam., projecting 2 ins. above ground, with brass cap mkd., T19/20S R16E 35 36 2 1 2688-126 LS 7599 1971. This is accepted as a careful and faithful reestablishment of the position of the original corner.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.

T19S R16E	
S35	S36
S 2	S 1
T20S R16E	
1993	

from which

A forked juniper, 16 ins. diam. at base, bears  
N. 18 1/2° E., 359 lks. dist., mkd. T19S R16E S36 BT.

A mesquite, 8 ins. diam., bears S. 11 1/2° E., 257 lks.  
dist., mkd. T20S R16E S1 BT.

A mesquite, 8 ins. diam., bears S. 54 1/2° W., 222 lks.  
dist., mkd. T20S R16E S2 BT.

A forked juniper, 14 ins. diam. at base, bears  
N. 49 3/4° W., 387.5 lks. dist., mkd. T19S R16E S35 BT.

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case  
beneath the stainless steel post.

Bury the brass cap alongside the stainless steel post.

From this cor. point, the cor. of Tps. 19 and 20 S., Rs. 16 and 17 E., remonumented by W.L. Settlemeyer, R.L.S. 7599, at a point formerly occupied by an iron pin, 3/4 ins. diam., bears S. 89°46' E., 79.61 chs. dist., with an iron post, 1 ins. diam., firmly set, encased in a concrete cylinder, 6 ins. diam., projecting 2 ins. above ground, with brass cap mkd., GAC PROPERTIES LS 7599 1971. This is accepted as the best available evidence of the original corner. Not remonumented.

Dependent Resurvey of a Portion of the South Boundary  
T. 19 S., R. 16 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>N. 89°46' W., bet. secs. 2 and 35.</p> <p>Over rolling land, through dense grass, scattered oak, mesquite, and juniper.</p> <p>39.80 The 1/4 sec. cor. of secs. 2 and 35, reestablished by W.L. Settlemeyer, R.L.S. 7599, monumented with an iron post, 1 in. diam., firmly set, encased in a concrete cylinder, 6 ins. diam., flush with the ground, with brass cap mkd., 5 2 2688-127 LS 7599 1971. This is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T19S R16E S35 1/4 — S 2 T20S R16E 1993</p> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 10 ins. diam., bears N. 52 1/2° E., 84 lks. dist., mkd. 1/4 S35 BT.</p> <p style="padding-left: 40px;">A desert willow, 8 ins. diam., bears S. 80 3/4° W., 119 lks. dist., mkd. 1/4 S2 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Bury the brass cap alongside the stainless steel post.</p> <p>Cor. is located in a fence, bears E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°46' W., beginning new measurement.</p>
39.81	<p>The cor. of secs. 2, 3, 34, and 35, reestablished by W.L. Settlemeyer, R.L.S. 7599, monumented with a rebar, 3/4 in. diam., firmly set, projecting 3 ins. above the ground, with lead cap mkd., 34 35 3 2 LS 7599. This is accepted as a careful and faithful reestablishment of the position of the original corner.</p>

Dependent Resurvey of a Portion of the South Boundary  
T. 19 S., R. 16 E., Gila and Salt River Mer., Arizona

CHAINS	<p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px;">T19S R16E</td> <td style="padding: 2px;">S34</td> <td style="padding: 2px;">S35</td> </tr> <tr> <td style="padding: 2px;">S 3</td> <td style="padding: 2px;">T20S R16E</td> <td style="padding: 2px;">S 2</td> </tr> <tr> <td colspan="3" style="text-align: center; padding: 2px;">1993</td> </tr> </table> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 10 ins. diam., bears N. 7° E., 272 lks. dist., mkd. T19S R16E S35 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Deposit the rebar inside the stainless steel post.</p> <p>From this cor. point, a rebar in concrete, bears S. 88°19' W., 2.94 chs. dist.</p> <p>From this same cor. point, a corner of fences, extending N. and E., bears N. 83°49' W., 3.48 chs. dist.</p> <p>Cor. is located 37 lks. S. of a fence line, bears E. and W. and 33 lks. N. of a ridge, bears ENE. and WSW.</p> <hr/> <p>N. 89°46' W., bet. secs. 3 and 34.</p> <p>Over rolling land, through dense grass, scattered oak, mesquite, and juniper.</p> <p>39.805 Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, in a supporting mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px;">T19S R16E</td> <td style="padding: 2px;">S34</td> </tr> <tr> <td style="padding: 2px;">1/4 —</td> <td style="padding: 2px;">S 3</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px;">T20S R16E</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px;">1993</td> </tr> </table>	T19S R16E	S34	S35	S 3	T20S R16E	S 2	1993			T19S R16E	S34	1/4 —	S 3	T20S R16E		1993	
T19S R16E	S34	S35																
S 3	T20S R16E	S 2																
1993																		
T19S R16E	S34																	
1/4 —	S 3																	
T20S R16E																		
1993																		

Dependent Resurvey of a Portion of the South Boundary  
T. 19 S., R. 16 E., Gila and Salt River Mer., Arizona

CHAINS	<p>from which</p> <p style="padding-left: 40px;">A forked mesquite, 16 ins. diam. at base, bears N. 24° E., 130 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A forked juniper, 24 ins. diam. at base, bears S. 79 1/4° E., 322.5 lks. dist., mkd. 1/4 S3 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°46' W., beginning new measurement.</p>										
39.805	<p>The cor. of secs. 3, 4, 33, and 34, determined from the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A dead and down oak, 24 ins. diam., bears S. 77° E., 92 lks. dist., with no visible blaze.</p> <p style="padding-left: 40px;">A stump hole, bears S. 43 1/4° E., 120 lks. dist., with a dead and rotted oak lying alongside, with no visible blaze.</p> <p style="padding-left: 40px;">A forked oak, 19 ins. diam. at base, bears S. 21 1/4° W., 65 lks. dist., with a healed blaze.</p> <p>Point is occupied by a rebar, 1/2 in. diam., firmly set, flush with the ground.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 5px;">T19S</td> <td style="padding: 2px 5px;">R16E</td> </tr> <tr> <td style="padding: 2px 5px;">S33</td> <td style="padding: 2px 5px;">S34</td> </tr> <tr> <td style="padding: 2px 5px;">S 4</td> <td style="padding: 2px 5px;">S 3</td> </tr> <tr> <td style="padding: 2px 5px;">T20S</td> <td style="padding: 2px 5px;">R16E</td> </tr> <tr> <td colspan="2" style="padding: 2px 5px; text-align: center;">1993</td> </tr> </table> <p>from which</p> <p style="padding-left: 40px;">A forked oak, 19 ins. diam. at base, bears S. 19° W., 65.5 lks. dist., mkd. T20S R16E S4 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Deposit the rebar inside the stainless steel post.</p>	T19S	R16E	S33	S34	S 4	S 3	T20S	R16E	1993	
T19S	R16E										
S33	S34										
S 4	S 3										
T20S	R16E										
1993											

Dependent Resurvey of a Portion of the South Boundary  
T. 19 S., R. 16 E., Gila and Salt River Mer., Arizona

CHAINS											
	<p>Cor. is located in a drainage, 150 lks. wide, drains E.</p> <hr/> <p>N. 89°56' W., bet. secs. 4 and 33.</p> <p>Over rolling land, through dense grass, scattered oak, mesquite, and juniper.</p> <p>39.435 Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19S R16E S33 1/4 — S 4 T20S R16E 1993</p> </div> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 8 ins. diam., bears N. 37 3/4° E., 313 lks. dist., mkd. 1/4 S33 BT.</p> <p style="padding-left: 40px;">An oak, 18 ins. diam., bears S. 4 3/4° E., 311.5 lks. dist., mkd. 1/4 S4 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the SE cor. of unpatented mining claim "Diamond D Mine" 1980, bears S. 44°59'W., 1.60 chs. dist., monumented with a steel fence post, projecting 32 ins. above ground, with a jar containing the claim notice attached to the post.</p>										
78.87	<p>Point for the cor. of secs. 4, 5, 32, and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T19S R16E</td> <td></td> </tr> <tr> <td>S32</td> <td>S33</td> </tr> <tr> <td>S 5</td> <td>S 4</td> </tr> <tr> <td>T20S R16E</td> <td></td> </tr> <tr> <td colspan="2">1993</td> </tr> </table> </div>	T19S R16E		S32	S33	S 5	S 4	T20S R16E		1993	
T19S R16E											
S32	S33										
S 5	S 4										
T20S R16E											
1993											

Dependent Resurvey of a Portion of the South Boundary  
T. 19 S., R. 16 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A mesquite, 8 ins. diam., bears N. 2 3/4° E., 36.5 lks. dist., mkd. X BT.</p> <p>A juniper, 9 ins. diam., bears S. 61 3/4° E., 87.5 lks. dist., mkd. T20S R16E S4 BT.</p> <p>A forked mesquite, 12 ins. diam. at base, bears S. 61 1/4° W., 120 lks. dist., mkd. T20S R16E S5 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor., a wood post, 4 ins. x 4 ins., firmly set, projecting 4 ft. above the ground, in a scattered mound of stone, bears N. 78°23'W., 84 lks. dist.</p>
39.435	<p>N. 89°56' W., bet. secs. 5 and 32.</p> <p>Over rolling land, through dense grass, scattered oak, mesquite, and juniper.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T19S R16E S32 1/4 — S 5 T20S R16E 1993</p>
78.87	<p>from which</p> <p>A juniper, 14 ins. diam., bears N. 47 3/4° E., 132.5 lks. dist., mkd. 1/4 S32 BT.</p> <p>An oak, 10 ins. diam., bears S. 74 3/4° E., 87.5 lks. dist., mkd. 1/4 S5 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 5, 6, 31, and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p>

Dependent Resurvey of a Portion of the South Boundary  
T. 19 S., R. 16 E., Gila and Salt River Mer., Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px;">T19S</td> <td style="padding: 2px;">R16E</td> </tr> <tr> <td style="padding: 2px;">S31</td> <td style="padding: 2px;">S32</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 2px;">S 6</td> <td style="border-top: 1px solid black; padding: 2px;">S 5</td> </tr> <tr> <td style="padding: 2px;">T20S</td> <td style="padding: 2px;">R16E</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px;">1993</td> </tr> </table> <p>from which</p> <p style="padding-left: 40px;">A forked juniper, 24 ins. diam. at base, bears N. 23° E., 117 lks. dist., mkd. T19S R16E S32 BT.</p> <p style="padding-left: 40px;">A forked juniper, 24 ins. diam. at base, bears S. 27 3/4° E., 325.5 lks. dist., mkd. T20S R16E S5 BT.</p> <p style="padding-left: 40px;">A forked juniper, 24 ins. diam. at base, bears S. 53 1/4° W., 453.5 lks. dist., mkd. T20S R16E S6 BT.</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears N. 43 1/2° W., 120.5 lks. dist., mkd. T19S R16E S31 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the SE cor. of unpatented mining claim "Gold Seal Placer" (AMC NO. 10699), bears N. 78°49' W., 93 lks. dist., monumented with a wood post, 6 ft. long, 3 ins. sq., with a 1 1/2 in. iron cap attached to the top of the post, in a mound of stone, 2 ft. base, 1 ft. high. A jar found alongside the wood post contained information relative to the claim. Although purported to be identical with the corner of secs. 5, 6, 31 and 32, there is no evidence that any original evidence was recovered. The position of this monument can not be reconciled with the record measurements between recovered original monuments to the E. and W., and therefore this monument is not utilized in the course of this resurvey.</p> <hr/> <p>N. 89°56' W., bet. secs. 6 and 31.</p> <p>Over rolling land, through dense grass, scattered oak, mesquite, and juniper.</p> <p>39.435 Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p>	T19S	R16E	S31	S32	S 6	S 5	T20S	R16E	1993	
T19S	R16E										
S31	S32										
S 6	S 5										
T20S	R16E										
1993											

Dependent Resurvey of a Portion of the South Boundary  
T. 19 S., R. 16 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T19S R16E S31 1/4 — S 6 T20S R16E 1993</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 14 ins. diam., bears S. 37 3/4° W., 99 lks. dist., mkd. 1/4 S6 BT.</p> <p style="padding-left: 40px;">A juniper, 10 ins. diam., bears N. 35° W., 98.5 lks. dist., mkd. 1/4 S31 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, an aluminum post, 3 ins. diam., firmly set, projecting 12 ins. above the ground, in a mound of stone, 3 ft. base, 1 ft. high, with aluminum cap mkd., 1/4 S31 S6 PE 5145 1984, bears N. 77°08' W., 46 lks. dist. This position was established with the SE cor. of unpatented mining claim "Gold Seal Placer" (AMC NO. 10699) as control, and is not utilized in this survey.</p> <p>78.43 The cor. of Tps. 19 and 20 S., Rs. 15 and 16 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd. T19S R15E R16E T20S S36 S31 S1 S6 1926, from which the remains of the original bearing tree</p> <p style="padding-left: 40px;">A rotted oak stump, 16 ins. diam., bears S. 52 1/2° W., 79 lks. dist., with T R 16 S BT on the rotted out blaze. (Record: 76 lks. dist.)</p> <p>Add the marks 1993 to the cap.</p> <p>from which the new bearing trees</p> <p style="padding-left: 40px;">A forked juniper, 8 ins. diam. at base, bears N. 6° E., 119 lks. dist., mkd. T19S R16E S31 BT.</p> <p style="padding-left: 40px;">A forked juniper, 10 ins. diam. at base, bears S. 39 1/2° E., 188 lks. dist., mkd. T20S R16E S6 BT.</p> <p style="padding-left: 40px;">A juniper, 15 ins. diam., bears S. 55 3/4° W., 163 lks. dist., mkd. T20S R15E S1 BT.</p>

Dependent Resurvey of a Portion of the South Boundary  
T. 19 S., R. 16 E., Gila and Salt River Mer., Arizona

CHAINS	<hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p>This survey is located approximately 35 miles SSE of Tucson Arizona. The elevation ranges from 4500 to 5500 feet above sea level.</p> <p>Access to the surveyed area is provided by Arizona State Highway 83 and various Forest Service roads.</p> <p>Limited mineral activity was noted.</p> <p>The soil is a sandy loam. The vegetation consists of oak, mesquite, juniper, pines, cactus, and native grasses.</p> <hr/> <p>The following information is provided for informational purposes only.</p> <p>The geographic positions of the following points were determined by differential positioning using the Ashtech MKII Geodetic Positioning System. U. S. Geological Survey triangulation Station "GREAT" was used as a control station. Coordinates refer to the top of the monument.</p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Station</th> <th style="text-align: left;">Latitude</th> <th style="text-align: left;">Longitude</th> </tr> </thead> <tbody> <tr> <td>SE cor. sec. 36</td> <td>31°43'52.778" N.</td> <td>110°39'17.550" W. NAD 27</td> </tr> </tbody> </table> <hr/>	Station	Latitude	Longitude	SE cor. sec. 36	31°43'52.778" N.	110°39'17.550" W. NAD 27
Station	Latitude	Longitude					
SE cor. sec. 36	31°43'52.778" N.	110°39'17.550" W. NAD 27					



CERTIFICATE OF SURVEY

I, Clyde J. King, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 14th day of June, 1993, I have dependently resurveyed a portion of the south boundary of Township 19 South, Range 16 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

4/20/94  
(Date)

Clyde J. King  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Arizona State Office  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the south boundary of Township 19 South, Range 16 East, Gila and Salt River Meridian, Arizona, executed by Clyde J. King, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

APR 21 1994  
(Date)

James P. Kelly  
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 19 S., R. 16 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~\_\_\_\_\_~~  
~~(Date)~~

~~\_\_\_\_\_~~  
~~(Chief Cadastral Surveyor of Arizona)~~