

ORIGINAL

1

BOOK 5417

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF

MINERAL SURVEY NUMBERS 694 AND 695

IN

TOWNSHIP 13 NORTH, RANGE 1 WEST

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY

Belle A. Craig

Cadastral Surveyor

Under Special Instructions dated July 21, 1994, approved July 21, 1994, which provided for the surveys included under Group Number 780, and assignment instructions dated July 22, 1994.

Survey Commenced July 25, 1994
Survey Completed August 23, 1994

2
BOOK 5417
INDEX DIAGRAM

TOWNSHIP 13 NORTH, RANGE 1 WEST,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Mineral Survey Number 694, pp 4-9
Mineral Survey number 695, pp 9-12

T. 13 N., R. 1 W., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of Mineral Survey Numbers 694 and 695, in Township 13 North, Range 1 West, Gila and Salt River Meridian, Arizona.

The history of the surveys pertaining to this dependent resurvey is as follows: The west one-half of the township was subdivided by O.H. Case, U.S. Deputy Surveyor, in 1871, and independently resurveyed by B. J. Kinsey, U.S. Surveyor, in 1933. Patented Mineral Survey Numbers 694 and 695 were surveyed by E. Pannenberg, Deputy Surveyor, in 1884. Unpatented Mineral Survey No. 1842 was surveyed by William S. Merritt, U.S. Deputy Mineral Surveyor, in 1903. Unpatented Mineral Survey No. 2786 was surveyed by J.J. Fisher, U.S. Deputy Mineral Surveyor, in 1910.

All original corners of patented Mineral Survey Numbers 694 and 695, Discovery Location Lone Star Lode, and Lone Star 1st North Extension, respectively, as surveyed by E. Pannenberg, were identical with the original location monuments. In the course of his survey of Mineral Survey Number 1842, William S. Merritt utilized and remonumented found corners of Mineral Survey Numbers 694 and 695, in their original positions, with the exception of Corner Number 3, Mineral Survey Number 694, and Corner Number 3, Mineral Survey Number 695. In these two instances Merritt established his own monuments and surveyed a tie to the original corner of location. No original end center monuments were recovered.

This survey reestablished Corner Number 3, Mineral Survey Number 694, from a found original Pannenberg bearing tree. A rotation correction was applied to the bearing of record, based upon the difference between Pannenberg's and Merritt's, final returns on line 2-3 of the Pannenberg survey. Corner Number 3, Mineral Survey Number 695, was established using a record tie from a found monument, Corner Number 2, Mineral Survey 1842. A rotation correction was applied to the bearing of record, based upon the difference between this survey and Merritt's, final returns on line 2-3.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated July 21, 1994 for Group No. 780, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

T. 13 N., R. 1 W., Gila and Salt River Meridian, Arizona

CHAINS

The survey was performed at the request of the Prescott National Forest, Forest Supervisor. The purpose of the survey was to identify the boundary of federal land adjacent to patented mining claims.

The directions of all lines were determined by technique of static differential positioning using Ashtech models M-XII and MS-XII geodetic units, and refer to the true meridian. Distances and angles were measured with a Ziess Elta 3, total station instrument.

The geographic position of the corner 2, Discovery Location Lode Lone Star, Mineral Survey Number 694 and corner 6, Lone Star lode 1st North Extension, M.S. 695, was determined by the technique of static differential positioning using Ashtech models M-XII and MS-XII geodetic units. U.S. Coast and Geodetic Survey triangulation station "Spruce Mountain USFS 1935" was used as the control station. The elevation and coordinates refer to the top of the monument.

Elevation	Latitude	Longitude
7,696 ft.	34°27'56.76" N.	112°23'58.76" W. NAD27

The mean magnetic declination, as taken from quadrangle map GROOM CREEK QUADRANGLE, ARIZ., published in 1974 by U.S. Geological Survey, is 13 1/2° E.

Dependent Resurvey of M.S. 694
T. 13 N., R. 1 W., Gila and Salt River Meridian, Arizona

Restoring the survey executed by
E. Pannenberg, in 1884

Discovery Location Lone Star Lode

Beginning at the point for cor. 1, Discovery Location Lone Star Lode, M.S. 694, identical with cor. 1, Lone Star Lode 1st. North Extension, M.S. 695, at proportionate distance; there is no remaining evidence of the original cor.

Not monumented.

The cor. point, is located at the center of the remnants of the mining shaft, an open pit, 25 lks. diam., 5 ft. deep.

S. 84° 45' W., on line 1-2, identical with line 1-6, M.S. 695.

Dependent Resurvey of M.S. 694
 T. 13 N., R. 1 W., Gila and Salt River Meridian, Arizona

CHAINS	<p>Desc. through timber and heavy underbrush.</p> <p>4.48 Cor. 2, Discovery Location Lone Star Lode, M.S. 694, identical with cor. 6, Lone Star Lode 1st. North Extension, M.S. 695, and cor. 1, Lone Star and cor. 4 Lone Star 1st Extension, M.S. 1842, monumented with a porphyry stone, 20 x 12 x 9 ins., firmly set, projecting 6 ins. above ground, in a collar of stone, faintly mkd. X on top, 1 LS 1842 on S face from which accessories mkd. in 1903</p> <p style="padding-left: 40px;">A rock face, 3 x 2 x 1 1/2 ft. high, bears N. 84°27' E., 45 lks. dist., faintly mkd. X BR 1 LS 4 1ST N E 1842. (Record, 29.7 ft. dist.)</p> <p style="padding-left: 40px;">A dead standing pine, 36 ins. diam., bears S. 9°47' E., 14.8 lks. dist., mkd. LS II (Record, 9.8 ft. dist.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> </div> <p>from which</p> <p style="padding-left: 40px;">A spruce, 5 ins. diam., bears S. 40 3/4° W., 49 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Bury stone, 9 x 12 x 20 ins., alongside stainless steel post.</p> <p>From this cor. point, U.S. Coast and Geodetic Survey triangulation station "Spruce Mountain USFS 1935", with published latitude of 34°27'47.13661" N. and longitude of 112°24'10.97545" W., NAD 27, bears S. 46° 25' W., 21.40 chs. dist.. monumented with a standard U.S.F.S. brass disk, 3 1/2 ins. diam. in a 2 x 2 x 2 ft. triangular rock ledge, 1/2 ft. high, mkd. SPRUCE MT 1935.</p>
--------	--

Dependent Resurvey of M.S. 694
T. 13 N., R. 1 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located on moderate NW slope.</p> <hr style="width: 20%; margin: 0 auto;"/>
	<p>S. 3° 40' E., on line 2-3.</p>
3.05	<p>A rebar, 1/2 in. diam, established by Haywood and Associates, in 1982, firmly set, projecting 2 ins. above ground bears W., 3.1 lks. dist.</p>
5.90	<p>The SE cor. of an unroofed, 10 x 10 x 4 ft. high, square structure, bears W., 70 lks. dist.</p>
10.20	<p>Center of private driveway, 20 lks. wide, bears ENE and WSW.</p>
10.38	<p>A rebar, 1/2 in. diam, firmly set, projecting 2 ins. above ground bears W., 10.8 lks. dist.</p>
11.17	<p>A rebar, 1/2 in. diam, established by William Cheek, Consulting Engineer, in 1972, firmly set, projecting 2 ins. above ground bears W., 11.6 lks. dist.</p>
23.21	<p>Cor. 3, Discovery Location Lone Star Lode, M.S. 694, determined at a rotated bearing and record dist. from an original bearing tree</p> <p style="padding-left: 40px;">A dead pine, 36 ins. diam., bears S. 60° E., 59 lks. dist., mkd. BT LS III.</p>
	<p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<div style="text-align: center;"> <p style="margin: 0;">T13N R1W</p> <div style="border-left: 1px solid black; border-bottom: 1px solid black; padding-left: 10px; margin: 0;"> <p style="margin: 0;">M S 694</p> <p style="margin: 0;">LS</p> <p style="margin: 0;">3</p> </div> <p style="margin: 0;">S31</p> <p style="margin: 0;">1994</p> </div>
	<p>from which</p> <p style="padding-left: 40px;">A Ponderosa pine, 11 ins. diam., bears S. 27 1/4° E., 40 lks. dist., mkd. LS C3 MS 694 BT.</p> <p style="padding-left: 40px;">A Douglas fir, 11 ins. diam., bears S. 79 1/2° W., 37 lks. dist., mkd. LS C3 MS 694 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

Dependent Resurvey of M.S. 694
T. 13 N., R. 1 W., Gila and Salt River Meridian, Arizona

CHAINS	<p>Cor. is located on moderate SE slope.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 79° 00' E., on line 3-5.</p> <p>4.395 Point for Cor. 4, Discovery Location Lone Star Lode, M.S. 694, at proportionate distance; there is no remaining evidence of original cor. position.</p> <p>Not Monumented.</p> <p>From this point, the S.E.C., M.S. 1842, monumented with a porphyry stone, 8 x 7 ins., loosely set on side, projecting 21 ins. above ground, in a scattered mound of stone, mkd. SEC LS 1842 on S. face, bears N. 26° 28' W., 42.6 lks. dist. Reset stone and rebuild, collar of stone.</p> <p>From this same point, Cor. 1, Pay Streak No. 2, M.S. 2786, monumented with a granite stone, 9 x 4 ins., firmly set, projecting 11 ins. above ground, in a scattered mound of stone, faintly mkd. P and 2 on E. face, with a scattered mound of stone to N., bears N. 70° 14' W., 105.2 lks. dist.</p> <p>8.79 Cor. 5, Discovery Location Lone Star Lode, M.S. 694, identical with cor. 3, Lone Star, M.S. 1842, and cor. 2, Pay Streak, M.S. 2786, monumented with a porphyry stone, 9 x 4 ins., firmly set, projecting 6 ins. above ground, in a collar of stone, faintly mkd. PS 2 2786 on E. face, from which a bearing tree mkd. in 1903</p> <p style="padding-left: 40px;">An oak tree stump, 24 ins. diam., bears N. 29° W., 61 lks. dist., with a downed tree alongside, mkd. BT LS 3 1842. (Record, N. 26° 37' W., 41.2 ft. dist.)</p> <p>and an accessory mkd. in 1910</p> <p style="padding-left: 40px;">A rock face, 3 x 5 x 6 ft. high, bears N. 15°55' E., 91 lks. dist., faintly mkd. X PS 2 2786 (Record, 59.6 ft. dist.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>T13N R1W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">M S 694</td> <td style="border-left: 1px solid black; padding: 0 5px;">LS</td> <td style="padding: 0 10px;">S31</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding: 0 5px;">5</td> <td></td> </tr> </table> <hr style="width: 20%; margin: 5px auto;"/> <p>1994</p> </div>	M S 694	LS	S31		5	
M S 694	LS	S31					
	5						

Dependent Resurvey of M.S. 694
T. 13 N., R. 1 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>A Ponderosa pine, 9 ins. diam., bears S. 56° W., 8 lks. dist., mkd. LS C5 MS 694 BT.</p> <p>A Ponderosa pine, 5 ins. diam., bears N. 23° W., 11.5 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Bury stone, 9 x 4 x 20 alongside stainless steel post.</p> <p>From this cor. the N.E.C. of Pay Streak No. 2, M.S. 2786, a granite stone, 10 x 10 ins., firmly set, projecting 20 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, mkd. NEC PS on S. face, bears S. 84° 07' W., 75 lks. dist.</p> <p>Cor. is located on moderate SE slope.</p> <hr/> <p>N. 3° 03' W., on line 5-6.</p> <p>22.33 Cor. 6, Discovery Location Lone Star Lode, M.S. 694, identical with cor. 2, Lone Star Lode 1st North Extension, M.S. 695, and cor. 2, Lone Star and cor. 3, Lone Star 1st North Extension, M.S. 1842, and cor. 2, Pay Streak and cor. 2, Pay Streak No. 3, M.S. 2786, monumented with a porphyry stone, 10 x 10 ins., firmly set, projecting 6 ins. above ground, in a collar of stone, faintly mkd. 842 on S. face, and illegible marks on W. face, from which bearing trees mkd. in 1903</p> <p>An oak, 16 ins. diam., bears S. 0° 20' E., 27 lks. dist., with healed blaze. (Record, 17.5 ft. dist.)</p> <p>An oak, 13 ins. diam., bears S. 57° 30' W., 22 lks. dist., with partially healed blaze mkd. S 1842. (Record, 14.4 ft. dist.)</p> <p>and an accessory mkd. in 1910</p> <p>A rock face, 6 x 10 x 5 ft. high, bears S. 57° W., 99 lks. dist., faintly mkd. X BR PS 786. (Record, 60.4 ft. dist.)</p> <p>At the cor. point</p>

Dependent Resurvey of M.S. 694
 T. 13 N., R. 1 W., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
 21 ins. in the ground, in a collar of stone, with brass cap mkd.

T13N R1W	
LS	
1ST NE	S31
M S 695	
2	
6	
LS	
M S 694	
1994	

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case
 beneath the stainless steel post.

Bury stone, 6 x 6 x 24 ins., alongside stainless steel post.

From this cor. point, the 1/4 sec. cor. of secs. 31 and 32,
 monumented with an iron post, 1 ins. diam., firmly set,
 projecting 7 ins. above ground, with brass cap mkd. 1/4 S31 S32
 1933, bears S. 50° 17' E., 9.38 chs. dist., from which a bearing
 tree mkd. in 1933

A spruce, 24 ins. diam., bears N. 70° E., 10 lks. dist.,
 with a healed blaze.

and a new bearing tree

A spruce, 7 ins. diam., bears N. 31° W., 24 lks. dist.,
 1/4 S31 BT.

Add the marks T13N R1W 1994 to the brass cap.

Cor. is located on moderate E. slope.

S. 84° 45' W., on line 6-1, identical with line 2-1, M.S. 695.

4.48

Cor. 1, Discovery Location Lone Star Lode, M.S. 694, identical
 with cor. 1, Lone Star Lode 1st North Extension, M.S. 695, and
 place of beginning.

Dependent Resurvey of M.S. 695
 T. 13 N., R. 1 W., Gila and Salt River Meridian, Arizona

Restoring the survey executed by
 E. Pannenberg, in 1884

Dependent Resurvey of M.S. 695
 T. 13 N., R. 1 W., Gila and Salt River Meridian, Arizona

CHAINS				
	<p>Lone Star Lode 1st North Extension</p> <p>From cor. 2, Lone Star Lode 1st North Extension, M.S. 695, identical with cor. 6, Discovery Location Lone Star Lode, M.S. 694, and cor. 2, Lone Star and cor. 3, Lone Star 1st North Extension, M.S. 1842, and cor. 2, Pay Streak and cor. 2, Pay Streak No. 3, M.S. 2786, hereinbefore described.</p> <p>N. 5° 33' W., on line 2-3.</p>			
13.72	<p>Cor. 1, Pay Streak No. 3, M.S. 2786, monumented with a porphyry stone, 4 x 10 x 24 ins., loosely set in a scattered mound of stone, mkd. PS NO. 3-1 2786 on E. face, bears W. 2.9 lks.</p>			
14.093	<p>Cor. 2, Lone Star 1st North Extension Lode, M.S. 1842, monumented with a granite stone, 4 x 8 ins., firmly set, projecting 7 ins. above ground, LS 2 1842, from which original bearing trees</p> <p style="padding-left: 40px;">A rotted stump, 24 ins. diam., bears S. 12° E., 1 lk. dist., no visible marks on rotted blaze. (Record, 0.6 ft. dist.)</p> <p style="padding-left: 40px;">A dead spruce, 29 ins. diam., bears N. 6° 50' W., 47 1/2 lks. dist., no visible marks in rotted blaze. (Record, 32.2 ft. dist.)</p> <p>Cor. is located on moderately steep NW slope.</p>			
14.32	<p>Cor. 3, Lone Star Lode 1st North Extension, determined at a rotated bearing and record dist. from cor. 2, Lone Star 1st North Extension, M.S. 1842.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in the remains of a scattered mound of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T13N R1W</p> <table border="1" style="margin: auto;"> <tr> <td style="padding: 2px;">LS 3</td> <td rowspan="2" style="border: none; padding-left: 5px;">S31</td> </tr> <tr> <td style="padding: 2px;">1ST NE</td> </tr> </table> <p style="margin: 2px 0;">M S 695</p> <p style="margin: 2px 0;">1994</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears N. 87° E., 35 lks. dist., mkd. LS 1ST N E C 3 MS 695.</p>	LS 3	S31	1ST NE
LS 3	S31			
1ST NE				

Dependent Resurvey of M.S. 695
T. 13 N., R. 1 W., Gila and Salt River Meridian, Arizona

CHAINS							
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Rebuild scattered mound of stone 3 ft. base, to top.</p> <p>Cor. is located on NW slope.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 83° 09' W., on line 3-5.</p>						
4.14	A pit 45 lks. diam, 8 ft. deep, bears S., 55 lks. dist.						
4.455	Point for Cor. 4, Lone Star Lode 1st North Extension, M.S. 695, at proportionate distance; there is no remaining evidence of original cor. position.						
	Not Monumented.						
8.91	<p>Cor. 5, Lone Star Lode 1st North Extension, M.S. 695, monumented with a porphyry stone, 11 x 9 ins., firmly set, projecting 12 ins. above ground, in a collar of stone, faintly mkd. X on top, LS 1 NE 1842 on E. face, with a 1 in. iron pipe alongside, from which bearing trees mkd. in 1903</p> <p style="padding-left: 40px;">A stump hole, with the remains of an oak, 8 ins. diam., alongside bears S. 80° 16' E., 14 lks. dist., faintly mkd. 184 on reverse scribing. (Record, 9.9 ft. dist.)</p> <p style="padding-left: 40px;">A dead oak, 10 ins. diam., bears S. 52° E., 42.7 lks. dist., faintly mkd. 1842. (Record, 28.4 ft. dist.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T13N R1W</p> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="border-right: 1px solid black; padding: 5px 10px;">S31</td> <td style="padding: 5px 10px;">5 LS</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 5px 10px;"></td> <td style="padding: 5px 10px;">1ST N E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 5px 10px;"></td> <td style="padding: 5px 10px;">M S 695</td> </tr> </table> <p>1994</p> </div> <p>from which</p> <p style="padding-left: 40px;">A spruce, 5 ins. diam., bears S. 56 1/4° W., 42 1/2 lks. dist., mkd. X BT.</p>	S31	5 LS		1ST N E		M S 695
S31	5 LS						
	1ST N E						
	M S 695						

Dependent Resurvey of M.S. 695
T. 13 N., R. 1 W., Gila and Salt River Meridian, Arizona

CHAINS	<p>An oak, 5 ins. diam., bears N. 57 3/4° W., 49 1/2 lks. dist., mkd. X BT.</p> <p>Deposit 1 in. iron pipe inside stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Bury stone, 9 x 11 x 16 ins., alongside stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 5° 20' E., on line 5-6.</p>
14.07	<p>Cor. 6, Lone Star Lode 1st North Extension, M.S. 695, identical with Cor. 2, Discovery Location Lone Star Lode, M.S. 694, and cor. 1, Lone Star and cor. 4 Lone Star 1st Extension, M.S. 1842, hereinbefore described.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <hr style="width: 20%; margin: 10px auto;"/> <p>The land encompassed in this resurvey is located approximately 6 miles SE of Prescott, AZ. Elevations range from 7100 to 7400 ft. above sea level.</p> <p>Terrain is mountainous and rocky, interspersed with steep drainages that drain predominantly ESE. Vegetation consists of grasses and shrubs, in a forest of Ponderosa Pine, Spruce, and Douglas fir, and oak.</p> <p>Access is by way the Senator Hwy. S. of Prescott to the intersection with U.S.F.S. access road to Spruce Mountain Fire Lookout. The mineral surveys are located approximately 4 miles SE of this intersection.</p> <p>Additional claims have been patented in the area. Excavation and tailings were in evidence. There is extensive housing development in the area.</p>

CERTIFICATE OF SURVEY

I, Belle A. Craig, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 21st day of July, 1994, I have dependently resurveyed Mineral Survey Nos. 694 and 695 in Township 13 North, Range 1 West, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

August 31, 1994
(Date)

Belle A. Craig
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of Mineral Survey Nos. 694 and 695 in Township 13 North, Range 1 West, Gila and Salt River Meridian, Arizona, executed by Belle A. Craig, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

SEP 19 1994
(Date)

James P. Kelly
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 13 N., R. 1 W., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____~~
~~(Date)~~

~~_____~~
~~(Chief Cadastral Surveyor of Arizona)~~