

ORIGINAL

BOOK 5421

1

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE

SURVEY OF THE

EAST AND

NORTH BOUNDARIES

AND

THE SUBDIVISIONAL LINES

OF

TOWNSHIP 31 NORTH, RANGE 26 EAST

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY

William F. Olver, Supervisory Cadastral Surveyor

Under Special Instructions dated November 22, 1989, approved November 22, 1989, and under Supplemental Special Instructions dated January 6, 1992, approved January 6, 1992, which provided for the surveys included under Group Number 715 and assignment instructions dated December 18, 1989.

Survey commenced January 8, 1992

Survey completed March 18, 1993

BOOK 5421

2

INDEX DIAGRAM

TOWNSHIP 31 NORTH, RANGE 26 EAST

10 6	11 69 5	12 56 4	14 45 3	15 35 2	26 1 9
68 7	67 66 8	55 53 9	44 42 10	34 33 11	25 23 12 8
66 18	65 64 17	53 51 16	42 41 15	33 32 14	23 22 13 7
63 19	63 61 20	50 49 21	40 39 22	31 30 23	21 20 24 5
61 30	60 59 29	49 47 28	38 37 27	30 29 26	19 18 25 5
58 31	57 56 32	47 45 33	37 36 34	28 27 35	17 16 36 4

BOOK 5421

T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>The following field notes describe the survey of the east and north boundaries and the subdivisional lines of Township 31 North, Range 26 East, Gila and Salt River Meridian, Arizona.</p> <p>This survey supersedes portions of Townships 4 and 5 North, Range 10 West, of the Navajo Special Meridian. The boundaries and subdivisional lines of Townships 4 and 5 North, Range 10 West, Navajo Special Meridian, were surveyed by E. N. Darling in 1869. A portion of the subdivisional lines of Township 5 North, Range 10 West, were dependently resurveyed by B. J. Kinsey in 1933. A portion of the First Standard Parallel North, through Ranges 9 and 10 West, and portions of the east boundary and subdivisional lines, Township 5 North, Range 10 West, were dependently resurveyed by J. L. Warboys in 1940. Portions of the north boundary (First Standard Parallel North) and subdivisional lines, Township 5 North, Range 10 West, were dependently resurveyed by Leonard R. Sandoval in 1991-92, executed concurrently under this same group.</p> <p>The south boundary of the township was surveyed by Steve D. Cully in 1991 and the west boundary of the township was surveyed by Leonard R. Sandoval in 1990-91, both executed concurrently under this same group.</p> <p>The closing cors. at intersection with appropriate section lines, T. 5 N., R. 10 W., Navajo Special Meridian, were established by tying each direction to the controlling cors. For simplicity, only ties to the nearest cor. are given in the field notes and shown on the plat.</p> <p>The survey was executed in accordance with the specifications as set forth in the <u>Manual of Surveying Instructions, 1973</u>, the <u>Special Instructions dated November 22, 1989</u>, and the <u>Supplemental Special Instructions dated January 6, 1992</u>, for Group No. 715, Arizona.</p> <p>The directions of all lines were determined by direct hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured with a Topcon GTS-3B total station instrument.</p> <p>The geographic position of the southeast corner of the township was determined by the technique of differential positioning using the Ashtech M Series Geodetic Positioning System. First order U. S. Coast and Geodetic Survey triangulation stations "BEAUTIFUL 1951" and "LOHALI 1951" were used as the control stations. The geographic coordinates are as follows:</p> <p>Latitude: 36°02'30.624" N. Longitude: 109°29'36.928" W. NAD27</p>
--------	---

BOOK 5421

T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>The mean magnetic declination, as taken from the 1985 magnetic declination map published by U.S. Geological Survey, is 12 1/2° E.</p>
	<p style="text-align: center;">Survey of the East Boundary, T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona</p>
	<p>Beginning at the cor. of Tps. 30 and 31 N., Rs. 26 and 27 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T31N R26E R27E S1 S6 S31 S36 T30N 1991.</p>
	<p>North, bet. secs. 31 and 36.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R26E R27E 1/4 S36 S31 1992</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
52.70	<p>S. rim of Three Turkey Canyon, bears ENE and WSW.</p>
67.00	<p>Tse Deeshzhaai Wash, 9 chs. wide, 5 ft. deep, drains W.</p>
71.80	<p>N. rim of Three Turkey Canyon, bears ENE and WSW.</p>
80.00	<p>Point for the cor. of secs. 25, 30, 31, and 36.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R26E R27E S25 S30 ----- S36 S31 1992</p>

BOOK 54 21

Survey of the East Boundary,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling to broken. Soil, rocky clay. Timber, scattered juniper; undergrowth, native grasses.</p>												
40.00	<p>North, bet. secs. 25 and 30.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T31N</td></tr> <tr><td style="text-align: center;">R26E</td><td style="text-align: center;">R27E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S25</td><td style="text-align: center;">S30</td></tr> <tr><td colspan="2" style="text-align: center;">1992</td></tr> </table>	T31N		R26E	R27E	1/4		S25	S30	1992			
T31N													
R26E	R27E												
1/4													
S25	S30												
1992													
80.00	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 19, 24, 25, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T31N</td></tr> <tr><td style="text-align: center;">R26E</td><td style="text-align: center;">R27E</td></tr> <tr><td style="text-align: center;">S24</td><td style="text-align: center;">S19</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S25</td><td style="text-align: center;">S30</td></tr> <tr><td colspan="2" style="text-align: center;">1992</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, rocky clay. Timber, scattered juniper; undergrowth, scattered native grasses.</p> <p>North, bet. secs. 19 and 24.</p> <p>Over rolling land.</p>	T31N		R26E	R27E	S24	S19	-----		S25	S30	1992	
T31N													
R26E	R27E												
S24	S19												

S25	S30												
1992													

6
BOOK 5421

Survey of the East Boundary,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS													
33.00	Graded road, 30 lks. wide, bears E. and W.												
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T31N</td></tr> <tr><td>R26E</td><td>R27E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S24</td><td>S19</td></tr> <tr><td colspan="2">1992</td></tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A piñon, 10 ins. diam., bears N. 35° W., 2.045 chs. dist., mkd. 1/4 S24 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T31N		R26E	R27E	1/4		S24	S19	1992			
T31N													
R26E	R27E												
1/4													
S24	S19												
1992													
80.00	<p>Point for the cor. of secs. 13, 18, 19, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T31N</td></tr> <tr><td>R26E</td><td>R27E</td></tr> <tr><td>S13</td><td>S18</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S24</td><td>S19</td></tr> <tr><td colspan="2">1992</td></tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A piñon, 7 ins. diam., bears N. 33 1/2° E., 80 1/2 lks. dist., mkd. T31N R27E S18 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, rocky clay. Timber, scattered juniper and piñon; undergrowth, scattered native grasses.</p>	T31N		R26E	R27E	S13	S18			S24	S19	1992	
T31N													
R26E	R27E												
S13	S18												
S24	S19												
1992													

BOOK 5421

Survey of the East Boundary,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS													
	North, bet. secs. 13 and 18.												
	Over rolling land.												
5.63	Barbed wire fence, bears NE and SW.												
38.50	Center of water tank, 25 ft. diam., bears West, 18.90 chs. dist.												
40.00	Point for the 1/4 sec. cor. of secs. 13 and 18.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,												
	25 ins. in the ground, with brass cap mkd.												
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T31N</td></tr> <tr><td style="text-align: center;">R26E</td><td style="text-align: center;">R27E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S13</td><td style="text-align: center;">S18</td></tr> <tr><td colspan="2" style="text-align: center;">1992</td></tr> </table>	T31N		R26E	R27E	1/4		S13	S18	1992			
T31N													
R26E	R27E												
1/4													
S13	S18												
1992													
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case												
	beneath the stainless steel post.												
51.45	Barbed wire fence, bears NNE and SSW.												
80.00	Point for the cor. of secs. 7, 12, 13, and 18.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,												
	14 ins. in the ground, to bedrock, in a mound of stone, 3 ft.												
	base, to top, with brass cap mkd.												
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T31N</td></tr> <tr><td style="text-align: center;">R26E</td><td style="text-align: center;">R27E</td></tr> <tr><td style="text-align: center;">S12</td><td style="text-align: center;">S 7</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S13</td><td style="text-align: center;">S18</td></tr> <tr><td colspan="2" style="text-align: center;">1992</td></tr> </table>	T31N		R26E	R27E	S12	S 7	-----		S13	S18	1992	
T31N													
R26E	R27E												
S12	S 7												

S13	S18												
1992													
	from which												
	A piñon, 7 ins. diam., bears N. 15 1/2° E., 51 lks. dist.,												
	mkd. T31N R27E S7 BT.												
	A juniper, 14 ins. diam., bears S. 72 3/4° E., 26 1/2 lks.												
	dist., mkd. T31N R27E S18 BT.												
	A piñon, 8 ins. diam., bears S. 38° W., 1.76 chs. dist.,												
	mkd. T31N R26E S13 BT.												

Survey of the East Boundary,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, rocky clay. Timber, scattered piñon and juniper; undergrowth, scattered native grasses.</p> <hr style="border: 0.5px solid black;"/> <p>North, bet. secs. 7 and 12.</p> <p>Over broken land.</p>
7.50	SW rim of canyon draining NNW into Little White House Canyon.
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12; falls on sheer S. wall of Little White House Canyon, where it is impractical to construct a monument.</p> <p>From this cor. point, the point selected for the witness cor. to the 1/4 sec. cor. of secs. 7 and 12, bears N. 45°00' E., 2.00 chs. dist.</p> <p>At the witness cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, to bedrock, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>WC T31N R26E R27E 1/4 S12 S 7 ↙ 1992</p> </div> <p>from which</p> <p style="margin-left: 40px;">A piñon, 6 ins. diam., bears N. 81° W., 41 lks. dist., mkd. X BT.</p>
59.70	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>NW rim of canyon draining SW into Little White House Canyon.</p>

BOOK 5421

Survey of the East Boundary,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS													
80.00	<p>Point for the cor. of secs. 1, 6, 7, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <table border="1" data-bbox="824 485 1003 674"> <tr><td colspan="2" style="text-align: center;">T31N</td></tr> <tr><td style="text-align: center;">R26E</td><td style="text-align: center;">R27E</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S12</td><td style="text-align: center;">S 7</td></tr> <tr><td colspan="2" style="text-align: center;">1992</td></tr> </table> <p>from which</p> <p style="padding-left: 40px;">A piñon, 13 ins. diam., bears S. 59° E., 83 lks. dist., mkd. T31N R27E S7 BT.</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears N. 79 1/4° W., 39 1/2 lks. dist., mkd. T31N R26E S1 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, broken. Soil, rocky clay and sandstone bedrock. Timber, scattered juniper and piñon; undergrowth, scattered native grasses.</p>	T31N		R26E	R27E	S 1	S 6	-----		S12	S 7	1992	
T31N													
R26E	R27E												
S 1	S 6												

S12	S 7												
1992													
	<p>North, bet. secs. 1 and 6.</p>												
	<p>Over rolling land.</p>												
27.50	<p>Power line, bears ESE and WNW.</p>												
32.025	<p>Point for the closing cor. of secs. 1 and 6, at intersection with the S. bdy. of sec. 25, T. 5 N., R. 10 W., Navajo Special Meridian.</p>												

BOOK 5421

Survey of the East Boundary,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
26 ins. in the ground, with brass cap mkd.

T5N R10W
S25

S 1 | S 6
R26E | R27E
T31N
CC
1992

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case
beneath the stainless steel post.

From this cor. point, the cor. of secs. 25 and 36 only, on the
E. bdy. of T. 5 N., R. 10 W., Navajo Special Meridian, bears
N. 89°31' E., 15.15 chs. dist., monumented with an iron post,
2 ins. diam., firmly set, projecting 6 ins. above ground, with
brass cap mkd. T5N R10W S25 S36 1991 1940.

Land, rolling.

Soil, rocky clay.

Timber, scattered juniper and piñon; undergrowth, scattered
native grasses.

Survey of the North Boundary,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

From the cor. of Tps. 31 and 32 N., Rs. 25 and 26 E., monumented
with a stainless steel post, 2 1/2 ins. diam., firmly set,
projecting 2 ins. above ground, with brass cap mkd. T32N R25E
R26E S1 S6 S31 S36 T31N 1991.

East, bet. secs. 6 and 31.

Over nearly level land.

36.25 Trail road, bears ENE and WSW.

38.40 Point for the 1/4 sec. cor. of secs. 6 and 31.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
26 ins. in the ground, with brass cap mkd.

BOOK 5421

Survey of the North Boundary,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T32N R26E S31 1/4 — S 6 T31N 1992</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
54.90	<p>Cottonwood Wash, 2.30 chs. wide, 5 ft. deep, drains ENE.</p>
78.40	<p>Point for the cor. of secs. 5, 6, 31, and 32.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T32N R26E S31 S32 — — S 6 S 5 T31N 1992</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, rocky and sandy clay. No timber; scattered native grasses.</p>
	<hr/>
	<p>East, bet. secs. 5 and 32.</p>
	<p>Over nearly level land.</p>
4.00	<p>Wash, 15 lks. wide, 5 ft. deep, drains N.</p>
12.00	<p>Wash, 45 lks. wide, 4 ft. deep, drains NW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

BOOK 54 21

Survey of the North Boundary,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T32N R26E S32 1/4 — S 5 T31N 1992</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
45.30	<p>Graded road, 38 lks. wide, bears N. and S.</p>
65.60	<p>Nazlini Wash, 1.80 chs. wide, 12 ft. deep, drains NE. Thence over rolling land.</p>
80.00	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T32N R26E S32 S33 — — S 5 S 4 T31N 1992</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level to rolling. Soil, rocky and sandy clay. No timber; scattered native grasses.</p>
40.00	<p>East, bet. secs. 4 and 33. Over rolling and broken land. Point for the 1/4 sec. cor. of secs. 4 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Survey of the North Boundary,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T32N R26E S33 1/4 — S 4 T31N 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
52.40	Navajo Route 27, a graded road, 38 lks. wide, bears N. and S.
73.20	Graded road, 30 lks. wide, bears NNE and SSW.
80.00	Point for the cor. of secs. 3, 4, 33, and 34.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. below the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R26E S33 S34 — — S 4 S 3 T31N 1992</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 45°00' W., 270.0 ft. dist., with brass cap mkd. T31N R26E S4 RM 270.0 FT. TO COR. 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45°00' W., 130.0 ft. dist., with brass cap mkd. T32N R26E S33 RM 130.0 FT. TO COR. 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

Survey of the North Boundary,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in a cultivated field.</p> <p>Land, rolling and broken. Soil, rocky clay. No timber; scattered native grasses.</p>
	<p>East, bet. secs. 3 and 34.</p>
	<p>Over rolling land.</p>
11.30	<p>Center of hexagonal hogan, 20 ft. diam., bears South, 4.40 chs. dist.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T32N R26E S34 1/4 — S 3 T31N 1992</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
79.00	<p>Point selected for the witness cor. to the cor. of secs. 2, 3, 34, and 35.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">WC T32N R26E S34 S35 — —> S 3 S 2 T31N 1992</p>

Survey of the North Boundary,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS																						
80.00	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>True point for the cor. of secs. 2, 3, 34, and 35; falls on the edge of a rock outcrop, where it is impractical to construct a monument.</p> <p>Land, rolling. Soil, rocky clay, sand and sandstone bedrock. No timber; scattered native grasses.</p> <hr/> <p>East, bet. secs. 2 and 35.</p> <p>Over rolling land.</p>																					
16.45	<p>Point for the closing cor. of secs. 2 and 35, at intersection with the W. bdy. of sec. 26, T. 5 N., R. 10 W., Navajo Special Meridian.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td style="padding: 2px 5px;">T32N</td><td style="border-left: 1px solid black; padding: 2px 5px;"></td><td style="padding: 2px 5px;">T5N</td></tr> <tr><td style="padding: 2px 5px;">R26E</td><td style="border-left: 1px solid black; padding: 2px 5px;"></td><td style="padding: 2px 5px;">R10W</td></tr> <tr><td style="padding: 2px 5px;">S35</td><td style="border-left: 1px solid black; padding: 2px 5px;"></td><td style="padding: 2px 5px;">S26</td></tr> <tr><td style="padding: 2px 5px;">CC</td><td style="border-left: 1px solid black; padding: 2px 5px;"></td><td style="padding: 2px 5px;"></td></tr> <tr><td style="padding: 2px 5px;">S 2</td><td style="border-left: 1px solid black; padding: 2px 5px;"></td><td style="padding: 2px 5px;"></td></tr> <tr><td style="padding: 2px 5px;">T31N</td><td style="border-left: 1px solid black; padding: 2px 5px;"></td><td style="padding: 2px 5px;"></td></tr> <tr><td style="padding: 2px 5px;"></td><td style="border-left: 1px solid black; padding: 2px 5px;"></td><td style="padding: 2px 5px;">1992</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the west 1/4 sec. cor. of sec. 26 only, T. 5 N., R. 10 W., Navajo Special Meridian, bears S. 0°02' E., 7.025 chs. dist., monumented with an iron post, 1 in. diam., firmly set, flush with the surface of the ground, with brass cap mkd. T5N R10W 1/4 S26 1992 1940.</p> <p>Land, rolling. Soil, rocky clay and sand. No timber; scattered native grasses.</p> <hr/>	T32N		T5N	R26E		R10W	S35		S26	CC			S 2			T31N					1992
T32N		T5N																				
R26E		R10W																				
S35		S26																				
CC																						
S 2																						
T31N																						
		1992																				

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, encircled with a collar of stone, with brass cap mkd. T31N R26E S1 S2 S35 S36 T30N 1991.</p>
	<p>N. 0°01' W., bet. secs. 35 and 36.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R26E 1/4 S35 S36 1992</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A piñon, 13 ins. diam., bears S. 38 1/2° W., 1.195 chs. dist., mkd. 1/4 S35 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
53.30	<p>S. rim of Three Turkey Canyon, bears E. and W.</p>
	<p>Thence enter broken land.</p>
69.40	<p>Tse Deeshzhaai Wash, 7.25 chs. wide, 20 ft. deep, drains W.</p>
74.00	<p>Base of N. wall of Three Turkey Canyon, bears E. and W.</p>
80.00	<p>Point for the cor. of secs. 25, 26, 35, and 36.</p>
	<p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place, in sandstone bedrock, with top mkd.</p>

BOOK 54 21

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS

T31N	R26E
S26	S25
S35	S36
1992	

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case in the drill hole beneath the brass tablet.

Cor. is located on steep NW edge of a canyon draining SSW into Three Turkey Canyon.

Land, rolling and broken.

Soil, rocky clay and sandstone bedrock.

Timber, scattered juniper and piñon; undergrowth, scattered native grasses.

From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.

S. 89°59' W., bet. secs. 25 and 36.

Over rolling and broken land.

39.995

Point for the 1/4 sec. cor. of secs. 25 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, to bedrock, with brass cap mkd.

T31N	R26E
	S25
1/4	—
	S36
1992	

from which

The mks. X BO chiseled on the sheer N. wall of Three Turkey Canyon, bear N. 39 3/4° W., 40 1/2 lks. dist.

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.99	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on gravelly slope below N. wall of Three Turkey Canyon.</p> <p>The cor. of secs. 25, 26, 35, and 36.</p> <p>Land, rolling and broken. Soil, rocky clay and sandstone bedrock. Timber, scattered juniper and piñon; undergrowth, scattered native grasses.</p>
40.00	<p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over broken and rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R26E 1/4 S26 S25 1992</p> <p>from which</p> <p style="text-align: center;">A forked piñon, 13 ins. diam. at base, bears N. 15 1/4° E., 61 lks. dist., mkd. 1/4 S25 BT.</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 23, 24, 25, and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R26E S23 S24 ----- S26 S25 1992</p>

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, broken and rolling. Soil, rocky clay. Timber, scattered juniper and piñon; undergrowth, scattered native grasses.</p>
39.99	<p>From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 24 and 25.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R26E S24 1/4 — S25 1992</p>
69.16	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>SW cor. of stucco house, 55 x 17 ft., bears North, 2.94 chs. dist., long side bears N.</p>
79.98	<p>The cor. of secs. 23, 24, 25, and 26.</p> <p>Land, rolling. Soil, rocky clay. Timber, scattered juniper and piñon; undergrowth, scattered native grasses.</p>

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°01' W., bet. secs. 23 and 24.
	Over rolling land.
4.50	Trail road, bears ENE and WSW.
23.10	Wash, 53 lks. wide, 10 ft. deep, drains WSW.
39.30	Trail road, bears SE and NW.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T31N R26E 1/4 S23 S24 1992 </div>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
52.20	Graded road, 30 lks. wide, bears ESE and WNW.
76.30	Trail road, bears ESE and WNW.
80.00	Point for the cor. of secs. 13, 14, 23, and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to bedrock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<div style="text-align: center;"> T31N R26E S14 S13 ----- S23 S24 1992 </div>
	from which
	A piñon, 10 ins. diam., bears S. 30 1/2° E., 2.385 chs. dist., mkd. T31N R26E S24 BT.
	A juniper, 9 ins. diam., bears S. 84° W., 1.335 chs. dist., mkd. T31N R26E S23 BT.

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, rocky clay. Timber, scattered juniper and piñon; undergrowth, scattered native grasses.</p> <hr/>
39.985	<p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 13 and 24.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R26E S13 1/4 — S24 1992</p> <p>from which</p> <p style="text-align: center;">A piñon, 8 ins. diam., bears S. 53 1/4° E., 96 lks. dist., mkd. 1/4 S24 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in a trail road, bears NE and SW.</p>
79.97	<p>The cor. of secs. 13, 14, 23, and 24.</p> <p>Land, rolling. Soil, rocky clay. Timber, scattered juniper and piñon; undergrowth, scattered native grasses.</p> <hr/>

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°01' W., bet. secs. 13 and 14.
	Over rolling land.
16.90	SW cor. of stucco house, 40 x 35 ft., bears East, 5.75 chs. dist., long side bears NNE.
36.20	Trail road, bears SE and NW.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T31N R26E 1/4 S14 S13 1992</p>
	from which
	<p style="text-align: center;">A juniper, 10 ins. diam., bears S. 64 1/4° E., 81 1/2 lks. dist., mkd. 1/4 S13 BT.</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.00	Point for the cor. of secs. 11, 12, 13, and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to bedrock, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T31N R26E S11 S12 ----- S14 S13 1992</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Land, rolling.
	Soil, rocky clay.
	Timber, scattered juniper and piñon; undergrowth, scattered native grasses.

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described.
	West, bet. secs. 12 and 13.
	Over rolling land.
39.70	Trail road, bears NNE and SSW.
39.99	Point for the 1/4 sec. cor. of secs. 12 and 13.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T31N R26E S12 1/4 — S13 1992</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
79.98	The cor. of secs. 11, 12, 13, and 14.
	<p>Land, rolling. Soil, rocky clay. Timber, scattered juniper and piñon; undergrowth, scattered native grasses.</p>
	N. 0°01' W., bet. secs. 11 and 12.
	Over rolling land.
30.80	Trail road, bears E. and W.
36.10	SW rim of canyon draining NW into Little White House Canyon.
	Thence enter broken land.

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T31N R26E 1/4 S11 S12 1992</p> <p>from which</p> <p style="text-align: center;">The mks. X BO chiseled on a sandstone outcrop, bear N. 80 3/4° E., 71 lks. dist.</p> <p style="text-align: center;">The mks. X BO chiseled on a boulder, 10 x 4 x 2 ft., bear N. 51 1/2° W., 52 lks. dist.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case in the drill hole beneath the brass tablet.</p> <p>Cor. is located on NE edge of canyon draining NW into Little White House Canyon, 3 chs. SE of intersection with S. rim of Little White House Canyon.</p>
46.10	S. rim of Little White House Canyon, bears SE and NW.
49.50	Tiis Ndiitsooi Wash, 75 lks. wide, 20 ft. deep, drains W., occupying the bottom of Little White House Canyon.
53.10	N. rim of Little White House Canyon, bears SE and NW.
	Thence enter rolling land.
80.00	<p>Point for the cor. of secs. 1, 2, 11, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R26E S 2 S 1 ----- S11 S12 1992</p>

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on S. slope of ridge, 45 lks. from top.</p> <p>Land, rolling and broken. Soil, rocky clay and sandstone bedrock. Timber, scattered juniper and piñon; undergrowth, scattered native grasses.</p>
	<p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 1 and 12.</p> <p>Over rolling land.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T31N R26E S 1 1/4 — S12 1992</p> <p>from which</p> <p style="text-align: center;">A piñon, 11 ins. diam., bears N. 82 1/2° W., 1.50 chs. dist., mkd. 1/4 S1 BT.</p>
79.98	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 1, 2, 11, and 12.</p> <p>Land, rolling. Soil, rocky clay. Timber, scattered juniper and piñon; undergrowth, scattered native grasses.</p>

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>N. 0°01' W., bet. secs. 1 and 2. Over rolling and broken land.</p>
30.60	S. rim of small canyon, bears ESE and WNW.
32.08	N. rim of same canyon, bears ESE and WNW.
32.14	<p>Point for the closing cor. of secs. 1 and 2, at intersection with the S. bdy. of sec. 26, T. 5 N., R. 10 W., Navajo Special Meridian.</p>
	<p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place, in sandstone bedrock, with top mkd.</p>
	<pre> T5N R10W S26 ----- S 2 S 1 T31N R26E CC 1992 </pre>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case in the drill hole beneath the stainless steel post.</p>
	<p>From this cor. point, the cor. of secs. 25 and 26 only, T. 5 N., R. 10 W., Navajo Special Meridian, bears S. 89°56' E., 18.215 chs. dist., monumented with a brass tablet, 3 1/4 ins. diam., cemented in sandstone bedrock, and witnessed by a mound of stone, 4 ft. base, 3 ft. high, to the N., with top mkd. T5N R10W S25 S26 1992.</p>
	<p>from which</p>
	<p>A piñon, 6 ins. diam., bears N. 47 3/4° E., 1.03 chs. dist., with scribe mks. T5N R10W S25 BT visible on open blaze.</p>
	<p>Land, rolling and broken. Soil, rocky clay and sandstone bedrock. Timber, scattered juniper and piñon; undergrowth, scattered native grasses.</p>

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 3 ft. base, 1 1/2 ft. high, with brass cap mkd. T31N R26E S2 S3 S34 S35 T30N 1991.</p> <p>from which</p> <p>A forked juniper, 5 ins. diam. at base, bears N. 45 1/4° E., 1.07 chs. dist., with scribe mks. T31N R26E S35 BT visible on open blaze.</p> <p>A forked juniper, 9 ins. diam. at base, bears S. 42 3/4° E., 2.68 chs. dist., with scribe mks. T30N R26E S2 BT visible on open blaze.</p> <p>A rock outcrop, 2 ft. high, bears N. 74 1/2° W., 55 1/2 lks. dist., with chiseled mks. X BO visible on the SE face.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R26E 1/4 S34 S35 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 26, 27, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R26E S27 S26 ----- S34 S35 1992</p>

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>A juniper, 11 ins. diam., bears S. 23° W., 1.755 chs. dist., mkd. T31N R26E S34 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, rocky clay. Timber, scattered juniper and piñon; undergrowth, scattered native grasses.</p>
40.005	<p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>S. 89°59' W., bet. secs. 26 and 35.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 26 and 35; falls on sheer W. wall of canyon draining S. into Three Turkey Canyon, where it is impractical to construct a monument.</p> <p>From this cor. point, the point selected for the witness cor. to the 1/4 sec. cor. of secs. 26 and 35, bears S. 45°00' E., 1.00 ch. dist.</p> <p>At the witness cor. point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place, in sandstone bedrock, with top mkd.</p> <div style="text-align: center;"> <p>WC</p> <p>T31N R26E</p> <p>↙ S26</p> <p>1/4 —</p> <p>S35</p> <p>1992</p> </div>
46.00	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case in the drill hole beneath the brass tablet.</p> <p>NE rim of Three Turkey Canyon, bears SE and NW.</p> <p>Note: Tse Deeshzhaai Wash is not tied into because of inaccessibility from canyon rims.</p>

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
74.50	W. rim of canyon draining NNE into Three Turkey Canyon.
80.01	<p>The cor. of secs. 26, 27, 34, and 35.</p> <p>Land, rolling and broken. Soil, rocky clay and sandstone bedrock. Timber, scattered juniper and piñon; undergrowth, scattered native grasses.</p> <hr/>
	N. 0°01' W., bet. secs. 26 and 27.
	Over rolling and broken land.
4.10	<p>SW rim of Three Turkey Canyon, bears SE and NW.</p> <p>Note: Tse Deeshzhaai Wash is not tied into because of inaccessibility from canyon rims.</p>
21.70	NE rim of Three Turkey Canyon, bears SE and NW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27; falls on sheer E. wall of Three Turkey Canyon, where it is impractical to construct a monument.</p> <p>From this cor. point, the point selected for the witness cor. to the 1/4 sec. cor. of secs. 26 and 27, bears N. 45°00' W., 1.00 ch. dist.</p> <p>At the witness cor. point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, cemented in place, in sandstone bedrock, with top mkd.</p>
	<p>WC T31N R26E 1/4 S27 S26 1992 ↘</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case in the drill hole beneath the brass tablet.
80.00	<p>Point for the cor. of secs. 22, 23, 26, and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<div style="text-align: center;"> <p>T31N R26E S22 S23 ----- S27 S26 1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, rocky clay and sandstone bedrock. No timber; scattered native grasses.</p>
40.005	<p>From the cor. of secs. 23, 24, 25, and 26.</p> <p>West, bet. secs. 23 and 26.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place, in sandstone bedrock, with top mkd.</p>
80.01	<div style="text-align: center;"> <p>T31N R26E S23 1/4 — S26 1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case in the drill hole beneath the brass tablet.</p> <p>The cor. of secs. 22, 23, 26, and 27.</p> <p>Land, rolling and broken. Soil, rocky clay and sandstone bedrock. Timber, scattered juniper and piñon; undergrowth, scattered native grasses.</p>
40.00	<p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p>

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T31N R26E 1/4 S22 S23 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 14, 15, 22, and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T31N R26E S15 S14 ----- S22 S23 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 2.80 chs. S. of a graded road, 30 lks. wide, bears ESE and WNW.</p> <p>Land, rolling and broken. Soil, rocky clay. No timber; scattered native grasses.</p>
12.95	<p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>West, bet. secs. 14 and 23.</p> <p>Over rolling and broken land.</p>
15.25	<p>Center of hexagonal hogan, 18 ft. diam., bears South, 3.30 chs. dist.</p>
	<p>Center of octagonal hogan, 45 ft. diam., bears South, 6.35 chs. dist.</p>

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.005	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T31N R26E S14 1/4 — S23 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.01	<p>The cor. of secs. 14, 15, 22, and 23.</p> <p>Land, rolling and broken. Soil, rocky clay. Timber, scattered juniper and piñon; undergrowth, scattered native grasses.</p>
40.00	<p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T31N R26E 1/4 S15 S14 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 10, 11, 14, and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p>

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS						
	<div style="text-align: center;"> <table border="1"> <tr><td>T31N R26E</td></tr> <tr><td>S10 S11</td></tr> <tr><td>S15 S14</td></tr> <tr><td>1992</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in a trail road, bears NNE and SSW.</p> <p>Land, rolling and broken. Soil, rocky clay. Timber, scattered juniper and piñon; undergrowth, scattered native grasses.</p>	T31N R26E	S10 S11	S15 S14	1992	
T31N R26E						
S10 S11						
S15 S14						
1992						
40.00	<p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>West, bet. secs. 11 and 14.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>					
80.00	<div style="text-align: center;"> <table border="1"> <tr><td>T31N R26E</td></tr> <tr><td>S11</td></tr> <tr><td>1/4 —</td></tr> <tr><td>S14</td></tr> <tr><td>1992</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 10, 11, 14, and 15.</p> <p>Land, rolling and broken. Soil, rocky clay. Timber, scattered juniper and piñon; undergrowth, scattered native grasses.</p>	T31N R26E	S11	1/4 —	S14	1992
T31N R26E						
S11						
1/4 —						
S14						
1992						
	<p>N. 0°01' W., bet. secs. 10 and 11.</p>					

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T31N R26E 1/4 S10 S11 1992</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
68.00	Wash, 1 ch. wide, 2 ft. deep, drains WSW.
80.00	Point for the cor. of secs. 2, 3, 10, and 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T31N R26E S 3 S 2 ----- S10 S11 1992</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Land, rolling and broken.
	Soil, rocky clay.
	Timber, scattered juniper and piñon; undergrowth, scattered native grasses.
	From the cor. of secs. 1, 2, 11, and 12.
	West, bet. secs. 2 and 11.
	Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 11.

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T31N R26E S 2 1/4 — S11 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case in the drill hole beneath the brass tablet.</p>
46.90	Tiis Ndiitsooi Wash, 1.50 chs. wide, 10 ft. deep, drains NNW.
80.00	The cor. of secs. 2, 3, 10, and 11.
	<p>Land, rolling and broken. Soil, rocky clay and sandstone bedrock. Timber, scattered juniper and piñon; undergrowth, scattered native grasses.</p>
	<p>N. 0°02' W., bet. secs. 2 and 3.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R26E 1/4 S 3 S 2 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
79.97	The true point for the cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., hereinbefore described.

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, rocky clay and sand. Timber, scattered juniper and piñon; undergrowth, scattered native grasses.</p> <hr/> <p>From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T31N R26E S3 S4 S33 S34 T30N 1991.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over nearly level land.</p>
12.10	Top of earthen levee, 15 lks. wide, 20 ft. high, bears E. and W.
18.00	Wash, 1.15 chs. wide, 10 ft. deep, drains WNW.
	Thence enter broken land.
40.00	Point for the 1/4 sec. cor. of secs. 33 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p>T31N R26E 1/4 S33 S34 1992</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
68.60	Top of prominent ridge, bears ENE and WSW.
80.00	Point for the cor. of secs. 27, 28, 33, and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS						
	<div style="text-align: center;"> <table border="1"> <tr><td>T31N R26E</td></tr> <tr><td>S28 S27</td></tr> <tr><td>S33 S34</td></tr> <tr><td>1992</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level to broken. Soil, rocky and sandy clay. No timber; scattered native grasses.</p>	T31N R26E	S28 S27	S33 S34	1992	
T31N R26E						
S28 S27						
S33 S34						
1992						
40.015	<p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>West, bet. secs. 27 and 34.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T31N R26E</td></tr> <tr><td>S27</td></tr> <tr><td>1/4 —</td></tr> <tr><td>S34</td></tr> <tr><td>1992</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T31N R26E	S27	1/4 —	S34	1992
T31N R26E						
S27						
1/4 —						
S34						
1992						
80.03	<p>The cor. of secs. 27, 28, 33, and 34.</p> <p>Land, rolling and broken. Soil, rocky clay. No timber; scattered native grasses.</p> <p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over rolling land.</p>					

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R26E 1/4 S28 S27 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
41.00	<p>Wash, 23 lks. wide, 2 ft. deep, drains SW.</p>
80.00	<p>Point for the cor. of secs. 21, 22, 27, and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R26E S21 S22 ----- S28 S27 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, rocky clay. No timber; scattered native grasses.</p>
19.90	<p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>West, bet. secs. 22 and 27.</p> <p>Over rolling land.</p> <p>Tse Deeshzhaai Wash, 1.80 chs. wide, 3 ft. deep, drains NNW.</p>

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.015	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R26E S22 1/4 — S27 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.03	<p>The cor. of secs. 21, 22, 27, and 28.</p> <p>Land, rolling. Soil, rocky clay. No timber; scattered native grasses.</p>
40.00	<p>N. 0°02' W., bet. secs. 21 and 22.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R26E 1/4 S21 S22 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
47.05	<p>Trail road, bears ESE and WNW.</p>
66.80	<p>Tse Deeshzhaai Wash, 6.80 chs. wide, 10 ft. deep, drains NNW.</p>
72.20	<p>Power line, bears ESE and WNW.</p>

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
77.30	Center of hexagonal hogan, 25 ft. diam., bears East, 0.91 ch. dist.										
80.00	<p>Point for the cor. of secs. 15, 16, 21, and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td colspan="2">T31N R26E</td> </tr> <tr> <td>S16</td> <td>S15</td> </tr> <tr> <td colspan="2">— —</td> </tr> <tr> <td>S21</td> <td>S22</td> </tr> <tr> <td colspan="2">1992</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 80 lks. W. of a graded road, 30 lks. wide, bears SSE on curve to left.</p> <p>Land, rolling. Soil, rocky and sandy clay. No timber; scattered native grasses.</p>	T31N R26E		S16	S15	— —		S21	S22	1992	
T31N R26E											
S16	S15										
— —											
S21	S22										
1992											
	From the cor. of secs. 14, 15, 22, and 23.										
	S. 89°59' W., bet. secs. 15 and 22.										
	Over rolling land.										
15.00	Graded road, 30 lks. wide, bears ENE and WSW.										
40.015	<p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td colspan="2">T31N R26E</td> </tr> <tr> <td colspan="2">S15</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td colspan="2">S22</td> </tr> <tr> <td colspan="2">1992</td> </tr> </table> </div>	T31N R26E		S15		1/4	—	S22		1992	
T31N R26E											
S15											
1/4	—										
S22											
1992											

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.03	<p>The cor. of secs. 15, 16, 21, and 22.</p> <p>Land, rolling. Soil, rocky and sandy clay. No timber; scattered native grasses.</p>
	<p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over nearly level land.</p>
6.80	Graded road, 30 lks. wide, bears SE and NW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R26E 1/4 S16 S15 1992</p>
73.50	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Wash, 70 lks. wide, 5 ft. deep, drains NW.</p>
80.00	<p>Point for the cor. of secs. 9, 10, 15, and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R26E S 9 S10 ----- S16 S15 1992</p>

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 2.70 chs. E. of center of wash, 3 chs. wide, 5 ft. deep, drains NW.</p> <p>Land, nearly level. Soil, rocky and sandy clay. No timber; scattered native grasses.</p>
40.01	<p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>S. 89°59' W., bet. secs. 10 and 15.</p> <p>Over gently rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R26E S10 1/4 — S15 1992</p>
80.02	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 9, 10, 15, and 16.</p> <p>Land, gently rolling. Soil, rocky and sandy clay. No timber; scattered native grasses.</p>
13.00	<p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over nearly level land.</p> <p>Power line, bears E. and W.</p>
14.67	<p>Center of hexagonal hogan, 18 ft. diam., bears West, 0.86 ch. dist.</p>

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
18.14	SW cor. of wood frame house, 26 x 18 ft., bears East, 1.42 chs. dist., long side bears NNE.
24.80	Trail road, bears SE and NW.
31.35	SE cor. of wood frame house, 36 x 26 ft., bears West, 2.51 chs. dist., long side bears N.
32.08	Barbed wire fence, bears NNE and SSW.
32.62	Barbed wire fence, bears ESE and WNW.
37.35	Trail road, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T31N R26E 1/4 S 9 S10 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
45.70	Top of earthen levee, 8 lks. wide, 6 ft. high, bears NNE and SSW.
47.60	Wash, 38 lks. wide, 4 ft. deep, drains WSW.
80.00	Point for the cor. of secs. 3, 4, 9, and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T31N R26E S 4 S 3 ----- S 9 S10 1992

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 29 lks. S. of a barbed wire fence and 60 lks. S. of a trail road, bear E. and W.</p> <p>From this cor. point, cor. of barbed wire fences, extending E. and WSW, bears N. 87 1/2° W., 1.48 chs. dist.</p> <p>Land, nearly level. Soil, rocky and sandy clay. No timber; scattered native grasses.</p>
	<p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>S. 89°59' W., bet. secs. 3 and 10.</p> <p>Over gently rolling land.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R26E S 3 1/4 — S10 1992</p>
47.20	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Top of earthen levee, 53 lks. wide, 5 ft. high, bears NNE and SSW.</p>
48.40	<p>Barbed wire fence, bears NNE and SSW.</p>
80.02	<p>The cor. of secs. 3, 4, 9, and 10.</p> <p>Land, gently rolling. Soil, rocky clay and sand. No timber; scattered native grasses.</p>

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°02' W., bet. secs. 3 and 4.
	Over nearly level land.
8.00	Tiis Ndiitsooi Wash, 1.30 chs. wide, 5 ft. deep, drains SW.
39.96	Barbed wire fence, bears E. and W.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T31N R26E 1/4 S 4 S 3 1992</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
66.26	Southernmost cor. of stucco house, 46 x 40 ft., bears West, 3.95 chs. dist., long side bears NE.
79.97	The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., hereinbefore described.
	Land, nearly level.
	Soil, rocky clay and sand.
	Timber, scattered cottonwood; undergrowth, scattered native grasses.
	From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T31N R26E S4 S5 S32 S33 T30N 1991.
	N. 0°03' W., bet. secs. 32 and 33.
	Over nearly level land.
40.00	Point for the 1/4 sec. cor. of secs. 32 and 33.

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a magnet in a 1 x 1 x 2 5/8 ins. white plastic case, 26 ins. below the surface of the ground.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 45°00' W., 120.0 ft. dist., with brass cap mkd. T31N R26E 1/4 S32 RM 120.0 FT. TO COR. 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45°00' W., 220.0 ft. dist., with brass cap mkd. T31N R26E 1/4 S32 RM 220.0 FT. TO COR. 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in Nazlini Wash, 9 chs. wide, drains N., 1.50 chs. E. of W. bank.</p>
80.00	<p>Point for the cor. of secs. 28, 29, 32, and 33.</p> <p>Set a magnet in a 1 x 1 x 2 5/8 ins. white plastic case, 26 ins. below the surface of the ground.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45°00' E., 240.0 ft. dist., with brass cap mkd. T31N R26E S28 RM 240.0 FT. TO COR. 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 45°00' W., 350.0 ft. dist., with brass cap mkd. T31N R26E S32 RM 350.0 FT. TO COR. 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in Nazlini Wash, drains NNW.</p>

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, nearly level. Soil, sandy clay and sand. No timber; sparse native grasses.</p>
	<p>From the cor. of secs. 27, 28, 33, and 34.</p>
	<p>West, bet. secs. 28 and 33.</p>
	<p>Over nearly level land.</p>
29.90	<p>Navajo Route 27, a graded road, 38 lks. wide, bears NNE and SSW.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R26E S28 1/4 — S33 1992</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
75.00	<p>E. bank of Nazlini Wash, bears SSE and NNW.</p>
79.98	<p>The cor. of secs. 28, 29, 32, and 33.</p>
	<p>Land, nearly level. Soil, sandy clay and sand. No timber; scattered native grasses.</p>
	<p>N. 0°03' W., bet. secs. 28 and 29.</p>
	<p>Over nearly level land in Nazlini Wash.</p>
25.20	<p>NE bank of Nazlini Wash, bears SE and NW; thence leave Nazlini Wash.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p>

BOOK 54 21

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R26E 1/4 S29 S28 1992</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
47.10	<p>Nazlini Wash, 13.60 chs. wide, drains NE.</p>
80.00	<p>Point for the cor. of secs. 20, 21, 28, and 29.</p>
	<p>Set a magnet in a 1 x 1 x 2 5/8 ins. white plastic case, 26 ins. below the surface of the ground.</p>
	<p>from which</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45°00' E., 420.0 ft. dist., with brass cap mkd. T31N R26E S21 RM 420.0 FT. TO COR. 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 45°00' W., 520.0 ft. dist., with brass cap mkd. T31N R26E S29 RM 520.0 FT. TO COR. 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Cor. is located in Nazlini Wash, drains NNW.</p>
	<p>Land, nearly level.</p>
	<p>Soil, sandy clay and sand.</p>
	<p>No timber; scattered native grasses.</p>

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the cor. of secs. 21, 22, 27, and 28.
	West, bet. secs. 21 and 28.
	Over rolling land.
22.30	Navajo Route 27, a graded road, 30 lks. wide, bears N. and S.
39.99	Point for the 1/4 sec. cor. of secs. 21 and 28.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, encircled with a collar of stone, with brass cap mkd.
	T31N R26E S21 1/4 — S28 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located on N. slope of hill, 30 lks. from top.
	Thence enter nearly level land.
57.50	Center of hexagonal hogan, 25 ft. diam., bears North, 4.20 chs. dist.
58.36	SW cor. of log house, 26 x 14 ft., bears North, 1.97 chs. dist., long side bears NNE.
72.80	E. bank of Nazlini Wash, bears SSE and NNW.
79.98	The cor. of secs. 20, 21, 28, and 29.
	Land, rolling to nearly level. Soil, rocky clay, sandy clay and sand. No timber; scattered native grasses.
	N. 0°03' W., bet. secs. 20 and 21.
	Over nearly level land.

50
BOOK 5421

Survey of the Subdivisional Lines,
 T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
8.80	N. bank of Nazlini Wash, 5 ft. deep, bears ESE and WNW.
25.30	Trail road, bears ESE and WNW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T31N R26E 1/4 S20 S21 1992 </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 16, 17, 20, and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T31N R26E S17 S16 ———— S20 S21 1992 </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, rocky and sandy clay. No timber; scattered native grasses.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 15, 16, 21, and 22.</p> <p>West, bet. secs. 16 and 21.</p> <p>Over nearly level land.</p>
4.90	Tse Deeshzhaai Wash, 6 chs. wide, 10 ft. deep, drains NNW.

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
18.80	Power line, bears ESE and WNW.
20.20	NE cor. of log house, 20 x 20 ft., bears South, 5.45 chs. dist., long side bears S.
21.20	NW cor. of wood frame house, 26 x 16 ft., bears South, 2.65 chs. dist., long side bears S.
23.60	Center of octagonal hogan, 25 ft. diam., bears South, 5.05 chs. dist.
24.10	Power line, bears NNE and SSW.
30.95	Trail road, bears SSE and NNW.
32.50	Navajo Route 27, a graded road, 30 lks. wide, bears NNE and SSW.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 21.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T31N R26E S16 1/4 — S21 1992</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.00	The cor. of secs. 16, 17, 20, and 21.
	<p>Land, nearly level. Soil, rocky and sandy clay. No timber; scattered native grasses.</p>
	N. 0°03' W., bet. secs. 16 and 17.
	Over nearly level land.
3.77	Barbed wire fence, 5 strands, bears SE and NW.

BOOK 54 21

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
10.05	Barbed wire fence, bears ENE and WSW.
28.80	Tse Deeshzhaai Wash, 1.50 chs. wide, 6 ft. deep, drains W.
34.63	Barbed wire fence, bears E. and W.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T31N R26E 1/4 S17 S16 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
56.04	Barbed wire fence, bears E. and W.
62.00	SW cor. of log house, 20 x 16 ft., bears East, 6.20 chs. dist., long side bears NNE.
80.00	Point for the cor. of secs. 8, 9, 16, and 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T31N R26E S 8 S 9 ----- S17 S16 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Land, nearly level. Soil, clay and sandy clay. No timber; scattered native grasses.

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the cor. of secs. 9, 10, 15, and 16.
	West, bet. secs. 9 and 16.
	Over nearly level land.
19.50	Navajo Route 27, a graded road, 30 lks. wide, bears N. and S.
23.80	Power line, bears N. and S.
40.01	Point for the 1/4 sec. cor. of secs. 9 and 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	26 ins. in the ground, with brass cap mkd.
	T31N R26E
	S 9
	1/4 —
	S16
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case
	beneath the stainless steel post.
	Cor. is located on NE edge of trail road, bears SE and NW.
80.02	The cor. of secs. 8, 9, 16, and 17.
	Land, nearly level.
	Soil, clay and sandy clay.
	No timber; scattered native grasses.
	N. 0°03' W., bet. secs. 8 and 9.
	Over nearly level land.
25.20	E. bank of Nazlini Wash, 10 ft. high, bears NNE and SSW.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 9.
	Set a magnet in a 1 x 1 x 2 5/8 ins. white plastic case, 26 ins.
	below the surface of the ground.

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45°00' E., 99.0 ft. dist., with brass cap mkd. T31N R26E 1/4 S9 RM 99.0 FT. TO COR. 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 45°00' W., 200.0 ft. dist., with brass cap mkd. T31N R26E 1/4 S8 RM 200.0 FT. TO COR. 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in Nazlini Wash, drains N.</p>										
61.60	NE bank of Nazlini Wash, 10 ft. high, bears ESE and WNW.										
62.50	Trail road, bears NE and SW.										
80.00	Point for the cor. of secs. 4, 5, 8, and 9.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T31N R26E</td> </tr> <tr> <td style="text-align: center;">S 5</td> <td style="text-align: center;">S 4</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S 8</td> <td style="text-align: center;">S 9</td> </tr> <tr> <td colspan="2" style="text-align: center;">1992</td> </tr> </table>	T31N R26E		S 5	S 4	-----		S 8	S 9	1992	
T31N R26E											
S 5	S 4										

S 8	S 9										
1992											
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, clay and sand. No timber; scattered native grasses.</p>										

CHAINS	
	From the cor. of secs. 3, 4, 9, and 10.
	West, bet. secs. 4 and 9.
	Over nearly level land.
3.75	Trail road, bears ENE and WSW.
9.70	Tiis Ndiitsooi Wash, 1 ch. wide, 5 ft. deep, drains SSW.
21.80	Navajo Route 27, a graded road, 30 lks. wide, bears N. and S.
27.40	Power line, bears N. and S.
39.80	Intersect E. side of wood frame house, 60 x 30 ft., SE cor. bears SSW, 52 lks. dist., long side bears NNE and SSW.
40.02	True point for the 1/4 sec. cor. of secs. 26 and 27; falls in a wood frame house, where it is impractical to construct a monument.
40.34	Intersect W. side of same wood frame house, SW cor. bears SSW, 24 lks. dist.
42.29	Point selected for the witness cor. to the 1/4 sec. cor. of secs. 4 and 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> <p>WC T31N R26E S 4 1/4 → S 9 1992</p> </div>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
43.35	Trail road, bears NE and SW.
67.75	Trail road, bears N. and S.
80.04	<p>The cor. of secs. 4, 5, 8, and 9.</p> <p>Land, nearly level. Soil, clay and sandy clay. No timber; scattered native grasses.</p> <hr/> <p>North, bet. secs. 4 and 5.</p> <p>Over nearly level land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R26E 1/4 S 5 S 4 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
79.97	<p>The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, nearly level. Soil, rocky clay and sand. No timber; scattered native grasses.</p> <hr/> <p>From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T31N R26E S5 S6 S31 S32 T30N 1991.</p>

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°03' W., bet. secs. 31 and 32.
	Over rolling land.
6.20	Trail road, bears NNE and SSW.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T31N R26E 1/4 S31 S32 1992 </div>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
62.40	Wash, 38 lks. wide, 3 ft. deep, drains NE.
80.00	Point for the cor. of secs. 29, 30, 31, and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T31N R26E S30 S29 ----- S31 S32 1992 </div>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Land, rolling.
	Soil, rocky clay and sand.
	No timber; scattered native grasses.
	<hr/>
	From the cor. of secs. 28, 29, 32, and 33.
	West, bet. secs. 29 and 32.
	Over bed of Nazlini Wash.

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
5.00	<p>W. bank of Nazlini Wash, bears SSE and NNW.</p> <p>Thence over gently rolling land.</p>
22.00	<p>Center of octagonal hogan, 20 ft. diam., bears North, 4.35 chs. dist.</p>
23.15	<p>Trail road, bears SSE and NNW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R26E S29 1/4 — S32 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
63.70	<p>Wash, 30 lks. wide, 2 ft. deep, drains ENE.</p>
80.00	<p>The cor. of secs. 29, 30, 31, and 32.</p> <p>Land, nearly level to gently rolling. Soil, sand and rocky clay. No timber; scattered native grasses.</p>
40.00	<p>S. 89°59' W., bet. secs. 30 and 31.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R26E S30 1/4 — S31 1992</p>

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
78.83	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, encircled with a collar of stone, with brass cap mkd. T31N R25E R26E S25 S30 S31 S36 1991.</p> <p>Land, rolling and broken. Soil, rocky clay. No timber; scattered native grasses.</p>
40.00	<p>From the cor. of secs. 29, 30, 31, and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R26E 1/4 S30 S29 1992</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 19, 20, 29, and 30.</p> <p>Set a magnet in a 1 x 1 x 2 5/8 ins. white plastic case, 48 ins. below the surface of the ground.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 45°00' E., 100.0 ft. dist., with brass cap mkd. T31N R26E S29 RM 100.0 FT. TO COR. 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45°00' W., 100.0 ft. dist., with brass cap mkd. T31N R26E S19 RM 100.0 FT. TO COR. 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in a wash, 30 lks. wide, 5 ft. deep, drains ENE.</p> <p>Land, rolling. Soil, rocky clay and sand. No timber; scattered native grasses.</p> <hr/> <p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>West, bet. secs. 20 and 29.</p> <p>Over bed of Nazlini Wash.</p>
4.70	<p>W. bank of Nazlini Wash, 2 ft. high, bears ESE and WNW.</p> <p>Thence over gently rolling land.</p>
39.995	<p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T31N R26E S20 1/4 — S29 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
45.80	<p>Trail road, bears NNE and SSW.</p>

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.99	<p>The cor. of secs. 19, 20, 29, and 30.</p> <p>Land, gently rolling. Soil, rocky clay and sand. No timber; scattered native grasses.</p> <hr/>
	<p>S. 89°59' W., bet. secs. 19 and 30.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R26E S19 1/4 — S30 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
47.80	<p>Wash, 30 lks. wide, 4 ft. deep, drains NW.</p>
78.73	<p>The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T31N R25E R26E S19 S24 S25 S30 1991.</p> <p>Land, gently rolling. Soil, rocky clay. No timber; scattered native grasses.</p> <hr/>
	<p>From the cor. of secs. 19, 20, 29, and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p> <p>Over gently rolling land.</p>

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
12.50	Center of hexagonal hogan, 25 ft. diam., bears East, 6.65 chs. dist.
18.85	SW cor. of L-shaped wood frame and stucco house, with overall dimensions of 35 x 35 ft., bears East, 5.95 chs. dist., sides bear N. and E.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 20.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T31N R26E 1/4 S19 S20 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 1.25 chs. W. of graded road, 23 lks. wide, bears N. and S.
59.60	Graded road, 23 lks. wide, bears E. and W.
60.00	Wash, 15 lks. wide, 3 ft. deep, drains ENE.
80.00	Point for the cor. of secs. 17, 18, 19, and 20.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T31N R26E S18 S17 ----- S19 S20 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Land, gently rolling. Soil, rocky clay. No timber; scattered native grasses.

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the cor. of secs. 16, 17, 20, and 21.
	West, bet. secs. 17 and 20.
	Over nearly level land.
10.40	E. bank of Nazlini Wash, 6 ft. high, bears SSE and NNW.
22.70	W. bank of Nazlini Wash, 6 ft. high, bears NNE and SSW.
39.995	Point for the 1/4 sec. cor. of secs. 17 and 20.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T31N R26E S17 1/4 — S20 1992</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
44.80	Graded road, 30 lks. wide, bears SSE and NNW.
79.99	The cor. of secs. 17, 18, 19, and 20.
	Land, nearly level.
	Soil, rocky clay and sand.
	No timber; scattered native grasses.
	S. 89°59' W., bet. secs. 18 and 19.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 18 and 19.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T31N R26E S18 1/4 — S19 1992</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

64
BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
47.60	Graded road, 23 lks. wide, bears SE and NW.
78.64	<p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T31N R25E R26E S13 S18 S19 S24 1991.</p> <p>Land, gently rolling. Soil, rocky clay. No timber; scattered native grasses.</p> <hr/> <p>From the cor. of secs. 17, 18, 19, and 20. N. 0°03' W., bet. secs. 17 and 18. Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R26E 1/4 S18 S17 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
46.32	Center of octagonal hogan, 45 ft. diam., bears East, 2.05 chs. dist.
80.00	<p>Point for the cor. of secs. 7, 8, 17, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<div style="text-align: center;"> <table border="1"> <tr><td>T31N</td><td>R26E</td></tr> <tr><td>S 7</td><td>S 8</td></tr> <tr><td>S18</td><td>S17</td></tr> <tr><td colspan="2">1992</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, rocky clay. No timber; scattered native grasses.</p>	T31N	R26E	S 7	S 8	S18	S17	1992			
T31N	R26E										
S 7	S 8										
S18	S17										
1992											
	<p>From the cor. of secs. 8, 9, 16, and 17.</p> <p>West, bet. secs. 8 and 17.</p> <p>Over nearly level land.</p>										
22.70	E. bank of Nazlini Wash, 12 ft. high, bears SSE and NNW.										
27.20	W. bank of Nazlini Wash, 5 ft. high, bears N. and S.										
39.995	Point for the 1/4 sec. cor. of secs. 8 and 17.										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, brass cap mkd.</p>										
	<div style="text-align: center;"> <table border="1"> <tr><td>T31N</td><td>R26E</td></tr> <tr><td>S 8</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S17</td><td></td></tr> <tr><td colspan="2">1992</td></tr> </table> </div>	T31N	R26E	S 8		1/4	—	S17		1992	
T31N	R26E										
S 8											
1/4	—										
S17											
1992											
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>										
47.40	Graded road, 30 lks. wide, bears N. and S.										
79.99	<p>The cor. of secs. 7, 8, 17, and 18.</p> <p>Land, nearly level. Soil, rocky and sandy clay. No timber; scattered native grasses.</p>										

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	West, bet. secs. 7 and 18. Over rolling land.
12.76	Center of octagonal hogan, 26 ft. diam., bears North, 1.31 chs. dist.
13.68	NE cor. of wood frame house, 55 x 16 ft., bears South, 0.38 ch. dist., long side bears SSW.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center; margin: 10px 0;"> T31N R26E S 7 1/4 — S18 1992 </div> Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
63.10	Trail road, bears NNE and SSW.
78.53	The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T31N R25E R26E S7 S12 S13 S18 1991. Land, rolling. Soil, rocky clay. No timber; scattered native grasses.
	From the cor. of secs. 7, 8, 17, and 18. N. 0°03' W., bet. secs. 7 and 8. Over nearly level land.

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R26E 1/4 S 7 S 8 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
63.55	Trail road, bears E. and W.
80.00	<p>Point for the cor. of secs. 5, 6, 7, and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R26E S 6 S 5 ----- S 7 S 8 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, rocky clay. No timber; scattered native grasses.</p>
6.90	<p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>S. 89°59' W., bet. secs. 5 and 8.</p> <p>Over nearly level land.</p> <p>NE bank of Nazlini Wash, 5 ft. high, bears SE and NW.</p>

68
BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
16.00	SW bank of Nazlini Wash, 5 ft. high, bears SE and NW.
33.15	Trail road, bears SE and NW.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, brass cap mkd. <div style="text-align: center;">T31N R26E S 5 1/4 — S 8 1992</div> Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
59.30	Graded road, 30 lks. wide, bears N. and S.
69.45	Trail road, bears N. and S.
80.00	The cor. of secs. 5, 6, 7, and 8. Land, nearly level. Soil, rocky clay and sand. No timber; scattered native grasses.
<p>S. 89°58' W., bet. secs. 6 and 7. Over nearly level land.</p>	
29.00	Top of earthen levee, 18 lks. wide, 6 ft. high, bears SSE and NNW.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 7. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T31N R26E S 6 1/4 — S 7 1992</div>

69
BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
78.43	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T31N R25E R26E S1 S6 S7 S12 1991.</p> <p>Land, nearly level. Soil, rocky clay. No timber; scattered native grasses.</p>
23.80	<p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 0°01' W., bet. secs. 5 and 6.</p> <p>Over nearly level land.</p> <p>Trail road, bears E. and W.</p>
25.35	<p>Center shaft of windmill, bears East, 14.90 chs. dist.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T31N R26E 1/4 S 6 S 5 1992</p> </div> <p>from which</p> <p style="margin-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 45°00' E., 30.0 ft. dist., with brass cap mkd. T31N R26E 1/4 S5 RM 30.0 FT. TO COR. 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p style="margin-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45°00' W., 30.0 ft. dist., with brass cap mkd. T31N R26E 1/4 S6 RM 30.0 FT. TO COR. 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

BOOK 5421

Survey of the Subdivisional Lines,
T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in a wash, 30 lks. wide, 4 ft. deep, drains NNE.</p> <p>60.00 Wash, 30 lks. wide, 8 ft. deep, drains E.</p> <p>79.97 The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, nearly level. Soil, rocky clay. No timber; scattered native grasses.</p>
	GENERAL DESCRIPTION
	<p>Area surveyed is within the Navajo Indian Reservation. The township is located just south of Chinle, Arizona. The terrain is rolling and broken in the eastern portion and nearly level to rolling in the western portion, with elevation ranging from 5500 feet to 6100 feet above sea level. The soil is mainly clay, varying from sandy to rocky, with some areas of exposed sandstone bedrock. The timber is predominantly scattered juniper and piñon; with other vegetation being mainly scattered native grasses. The drainage is generally to the north: Nazlini Wash being the main drainage, with Tse Deeshzhaai and Tiis Ndiitsooi Washes draining westerly into it.</p> <p>Navajo Route 27, a graded road, extends from north to south in the center of the township. There are numerous trail roads throughout the township. The township is principally utilized for grazing livestock. There is no evidence of any kind of mining activity.</p> <p>The mean magnetic declination is 12 1/2° E. throughout the township.</p>

BOOK 5421

UNITED STATES

DEPARTMENT OF THE INTERIOR

BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Robert L. Harper	Cadastral Surveyor
Edward Clarke	Surveying Technician
Nelson Kinsel	Surveying Technician
Angela Segay	Surveying Aid

CERTIFICATE OF SURVEY

I, William F. Olver, Supervisory Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 22nd day of November, 1989, and Supplemental Special Instructions bearing date of the 6th day of January, 1992, I have surveyed the east and north boundaries and the subdivisional lines of Township 31 North, Range 26 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special and supplemental special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

October 17, 1994
(Date)

William F. Olver
(Supervisory Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the east and north boundaries and the subdivisional lines of Township 31 North, Range 26 East, Gila and Salt River Meridian, Arizona, executed by William F. Olver, Supervisory Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

OCT 24 1994
(Date)

James P. Kelley
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 31 N., R. 26 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor of Arizona)~~

ORIGINAL

BOOK 5421

1

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE

SURVEY OF THE

EAST AND

NORTH BOUNDARIES

AND

THE SUBDIVISIONAL LINES

OF

TOWNSHIP 31 NORTH, RANGE 26 EAST

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY

William F. Olver, Supervisory Cadastral Surveyor

Under Special Instructions dated November 22, 1989, approved November 22, 1989, and under Supplemental Special Instructions dated January 6, 1992, approved January 6, 1992, which provided for the surveys included under Group Number 715 and assignment instructions dated December 18, 1989.

Survey commenced January 8, 1992

Survey completed March 18, 1993