

ORIGINAL

BOOK 5453

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF

THE SEVENTH AUXILIARY GUIDE MERIDIAN EAST (EAST BOUNDARY),

THE WEST BOUNDARY

AND A PORTION OF THE SUBDIVISIONAL LINES,

AND THE SUBDIVISION

OF SECTION 36

IN TOWNSHIP 19 NORTH, RANGE 28 EAST

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY

JOE R. SALAZAR

Cadastral Surveyor

STEPHEN J. MALLOY

Cadastral Surveyor

Under Special Instructions dated January 12, 1987, approved February 17, 1987,
and supplemental instructions dated February 29, 1988, approved February 29, 1988, which
provided for the surveys included under Group Number 686 and assignment
instructions dated February 17, 1987 and October 19, 1992.

Survey commenced June 6, 1988

Survey completed January 21, 1993

BOOK 5453
INDEX DIAGRAM

TOWNSHIP 19 NORTH, RANGE 28 EAST,

14	6	5	4	3	2	1	9	
14	7	8	9	10	11	12	8	
13	18	17	16	15	14	16	13	7
12	19	20	21	22	23	24	6	
11	30	29	28	27	26	25	6	
10	31	32	33	34	35	15	36	4

Subdivision of section 36

pp. 17-20

BOOK 5453

T. 19 N., R. 28 E., Gila and Salt River Meridian, Arizona.

CHAINS

The following field notes are those of the dependent resurvey of the Seventh Auxiliary Guide Meridian East (east boundary), the west boundary, and a portion of the subdivisional lines and the subdivision of section 36, in Township 19 North, Range 28 East, Gila and Salt River Meridian, Arizona.

The south boundary was surveyed by Henry A. Coe, in 1882. The east and north boundaries were surveyed by W. R. Fitzgerald, in 1882. The west boundary and the subdivisional lines were surveyed by Milton Santee, in 1882. The south boundary was dependently resurveyed by William P. Carpender and Stephen K. Hansen, in 1991-93. The north boundary was dependently resurveyed and the 1/4 sec. cor. of secs. 1 and 6 on the W. bdy. of the Tp. was remonumented by William P. Carpender, in 1988-93.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated January 12, 1987, and the Supplemental Instructions dated February 29, 1988, for Group No. 686, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of all lines were determined by direct hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured with a SOKKIA SET2B Total Station.

The geographic position of the southeast corner of the township was determined by the relative positioning using the Ashtech GPS Geodetic System. U.S. Coast & Geodetic Survey triangulation stations "Beacon 54 B ECC 1936" and "Dead 1936" was used as the control stations. Coordinates refer to the top of the monument.

Latitude: 34°59'40.47" N. Longitude: 109°18'48.10" W. NAD 27

The mean magnetic declination as taken from quadrangle map BEACON WELL, ARIZ., published in 1972 by U.S. Geological Survey, is 13 1/2° E.

4
 BOOK 5453
 Dependent Resurvey of the
 Seventh Auxiliary Guide Meridian East (East Boundary),
 T. 19 N., R. 28 E., Gila and Salt River Mer., Arizona

CHAINS											
	<p>Restoring the Survey Executed by W. R. Fitzgerald, U.S. Deputy Surveyor, in 1882</p> <hr style="width: 20%; margin: auto;"/> <p>Beginning at the cor. of Tps. 18 and 19 N., Rs. 28 and 29 E., monumented with a stainless steel post, 2 1/2 ins. diam, firmly set, projecting 4 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd., T19N R28E R29E S1 S6 S31 S36 T18N 1991.</p> <p>N. 0°05' E., bet. secs. 31 and 36.</p> <p>Over rolling land.</p>										
20.25	<p>Point for the S 1/16 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border: none; margin: auto;"> <tr><td colspan="2">T19N</td></tr> <tr><td colspan="2">S1/16</td></tr> <tr><td>R28E</td><td style="border-left: 1px solid black;">R29E</td></tr> <tr><td>S36</td><td style="border-left: 1px solid black;">S31</td></tr> <tr><td colspan="2">1992</td></tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A juniper, 9 ins. diam., bears N 7 1/2° E, 228 lks. dist., mkd. S 1/16 S31 BT.</p> <p style="margin-left: 40px;">A juniper, 10 ins. diam., bears N 29 3/4° W, 234 lks. dist., mkd. S 1/16 S36 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>	T19N		S1/16		R28E	R29E	S36	S31	1992	
T19N											
S1/16											
R28E	R29E										
S36	S31										
1992											
35.60	<p>Edge of Puerco Rim.</p> <p>Descend.</p>										
40.50	<p>Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										

BOOK 5453
Dependent Resurvey of the
Seventh Auxiliary Guide Meridian East (East Boundary),
T. 19 N., R. 28 E., Gila and Salt River Mer., Arizona

CHAINS	
	T19N 1/4 R28E R29E S36 S31 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Set a steel fence post alongside the stainless steel post.
	Cor. is located on steep NW slope, 4.7 chs. W. of Puerco Rim.
41.30	Spur, bears E and WNW.
81.00	The cor. of secs. 25, 30, 31 and 36, monumented with a weathered juniper post, 2 X 3 ins. square, 31 ins. long, firmly set, projecting 14 ins. above the ground, faintly mkd. T19NR29E on NW side.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T19N R28E R29E S25 S30 --- S36 S31 1988
	from which
	A juniper, 10 ins. diam., bears S. 21 1/4° E., 279 lks. dist., mkd. T19N R29E S31 BT.
	A juniper, 12 ins. diam., bears S. 59 1/4° W., 389 lks. dist., mkd. T19N R28E S36 BT.
	From this cor., U.S. Geological Survey triangulation station "BEACON 54 B ECC 1936" bears N. 58°50'21" E. (forward bearing), 283.11 chs. dist., monumented with a standard bronze tablet, firmly set in a concrete post, 12 ins. square, projecting 12 ins. above the ground, with top mkd. BEACON 54 B 1936, and a triangle.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Dependent Resurvey of the
Seventh Auxiliary Guide Meridian East (East Boundary),
T. 19 N., R. 28 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 1°47' E., bet. secs. 25 and 30.</p> <p>Over gently rolling, nearly level land.</p>
39.82	<p>Point for the 1/4 sec. cor. of secs. 25 and 30, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N 1/4 R28E R29E S25 S30 1989</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
79.64	<p>Point for the cor. of secs. 19, 24, 25 and 30, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R28E R29E S24 S19 <hr/>S25 S30 1989</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 1°47' E., bet. secs. 19 and 24.</p> <p>Over gently rolling land.</p>
39.82	<p>Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p>

Dependent Resurvey of the
Seventh Auxiliary Guide Meridian East (East Boundary),
T. 19 N., R. 28 E., Gila and Salt River Mer., Arizona

CHAINS																							
79.64	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T19N</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R28E</td><td style="padding: 0 5px;">R29E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S24</td><td style="padding: 0 5px;">S19</td></tr> <tr><td colspan="2">1989</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside stainless steel post.</p> <p>Point for the cor. of secs. 13, 18, 19 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T19N</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R28E</td><td style="padding: 0 5px;">R29E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S13</td><td style="padding: 0 5px;">S18</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S24</td><td style="padding: 0 5px;">S19</td></tr> <tr><td colspan="2">1989</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>N. 1°47' E., bet. secs. 13 and 18.</p> <p>Over nearly level land.</p>	T19N		1/4		R28E	R29E	S24	S19	1989		T19N		1/4		R28E	R29E	S13	S18	S24	S19	1989	
T19N																							
1/4																							
R28E	R29E																						
S24	S19																						
1989																							
T19N																							
1/4																							
R28E	R29E																						
S13	S18																						
S24	S19																						
1989																							
39.82	<p>Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T19N</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R28E</td><td style="padding: 0 5px;">R29E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S13</td><td style="padding: 0 5px;">S18</td></tr> <tr><td colspan="2">1989</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>	T19N		1/4		R28E	R29E	S13	S18	1989													
T19N																							
1/4																							
R28E	R29E																						
S13	S18																						
1989																							

Dependent Resurvey of the
Seventh Auxiliary Guide Meridian East (East Boundary),
T. 19 N., R. 28 E., Gila and Salt River Mer., Arizona

CHAINS													
	Set a steel fence post alongside the stainless steel.												
78.55	Barbed wire fence bears E. and W.												
79.64	Point for the cor. of secs. 7, 12, 13 and 18, at proportionate dist.; there is no remaining evidence of the original cor.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.												
	<table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="padding: 2px;">T19N</td></tr> <tr><td style="padding: 2px;">R28E</td><td style="padding: 2px;">R29E</td></tr> <tr><td style="padding: 2px;">S12</td><td style="padding: 2px;">S 7</td></tr> <tr><td colspan="2" style="border-top: 1px solid black; padding: 2px;"></td></tr> <tr><td style="padding: 2px;">S13</td><td style="padding: 2px;">S18</td></tr> <tr><td colspan="2" style="padding: 2px;">1989</td></tr> </table>	T19N		R28E	R29E	S12	S 7			S13	S18	1989	
T19N													
R28E	R29E												
S12	S 7												
S13	S18												
1989													
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.												
	Set a steel fence post alongside the stainless steel post.												
	Cor. is located 5 chs., N. 78° W. from a cor. of fences extending ESE, and W.												
	N. 1°47' E., bet. secs. 7 and 12.												
	Over rolling land.												
26.70	Gulch, 1 ch. wide, 10 ft. deep, course W.												
39.82	Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate dist.; there is no remaining evidence of the original cor.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.												
	<table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="padding: 2px;">T19N</td></tr> <tr><td colspan="2" style="padding: 2px;">1/4</td></tr> <tr><td style="padding: 2px;">R28E</td><td style="padding: 2px;">R29E</td></tr> <tr><td style="padding: 2px;">S12</td><td style="padding: 2px;">S 7</td></tr> <tr><td colspan="2" style="border-top: 1px solid black; padding: 2px;"></td></tr> <tr><td colspan="2" style="padding: 2px;">1989</td></tr> </table>	T19N		1/4		R28E	R29E	S12	S 7			1989	
T19N													
1/4													
R28E	R29E												
S12	S 7												
1989													
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.												
	Set a steel fence post alongside the stainless steel post.												
69.30	Spur, bears SE and NW.												

BOOK⁹ 5453

Dependent Resurvey of the
Seventh Auxiliary Guide Meridian East (East Boundary),
T. 19 N., R. 28 E., Gila and Salt River Mer., Arizona

CHAINS													
79.64	<p>Point for the cor. of secs. 1, 6, 7 and 12, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="padding: 0 10px;">T19N</td></tr> <tr><td style="padding: 0 5px;">R28E</td><td style="border-left: 1px solid black; padding: 0 5px;">R29E</td></tr> <tr><td style="padding: 0 5px;">S 1</td><td style="border-left: 1px solid black; padding: 0 5px;">S 6</td></tr> <tr><td colspan="2" style="border-top: 1px solid black; padding: 0 5px;">S12</td></tr> <tr><td colspan="2" style="padding: 0 5px;">S 7</td></tr> <tr><td colspan="2" style="padding: 0 5px;">1989</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>N. 1°47' E., bet. secs. 1 and 6.</p> <p>Over rolling land.</p>	T19N		R28E	R29E	S 1	S 6	S12		S 7		1989	
T19N													
R28E	R29E												
S 1	S 6												
S12													
S 7													
1989													
8.00	Ridge, bears E and W.												
36.20	Ridge, bears E. and W.												
39.82	<p>Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="padding: 0 10px;">T19N</td></tr> <tr><td colspan="2" style="padding: 0 10px;">1/4</td></tr> <tr><td style="padding: 0 5px;">R28E</td><td style="border-left: 1px solid black; padding: 0 5px;">R29E</td></tr> <tr><td style="padding: 0 5px;">S 1</td><td style="border-left: 1px solid black; padding: 0 5px;">S 6</td></tr> <tr><td colspan="2" style="padding: 0 5px;">1989</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>	T19N		1/4		R28E	R29E	S 1	S 6	1989			
T19N													
1/4													
R28E	R29E												
S 1	S 6												
1989													
46.20	Wash, 15 lks. wide, course W.												

Dependent Resurvey of the
Seventh Auxiliary Guide Meridian East (East Boundary),
T. 19 N., R. 28 E., Gila and Salt River Mer., Arizona

CHAINS	
79.64	<p>The cor. of Tps. 19 and 20 N, Rs. 28 and 29 E, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd., T20N R28E R29E S36 S31 S1 S6 T19N 1988.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of the West Boundary, T. 19 N., R. 28 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;">Restoring the survey executed by Milton Santee, in 1882</p> <hr/> <p>From the cor. of Tps. 18 and 19 N., Rs. 27 and 28 E., monumented with a stainless steel post, 2 1/2 ins. diam, firmly set, projecting 4 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. T19N R27E R28E S36 S31 S1 S6 T18N 1992.</p> <p>from which</p> <p style="padding-left: 40px;">A piñon pine, 8 ins diam., bears N. 58° E., 26 1/2 lks. dist., mkd., X at breast height and BT at base.</p> <p>N. 0°04' E., bet. secs. 31 and 36.</p> <p>Descend, through scattered piñon and juniper.</p>
40.47	<p>Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T19N 1/4 R27E R28E S36 S31 1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located 50 lks. W. of a wash, 8 ft. deep drains NNW.</p>
41.20	<p>Wash, 30 lks. wide, drains WNW.</p>

BOOK 5453

Dependent Resurvey of the West Boundary,
T. 19 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS													
80.94	<p>The cor. of secs. 25, 30, 31 and 36, monumented with a juniper post, 17 ins. long, 3 ins. square, lying loose on ground, mkd. with 3 grooves on one side.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T19N</td></tr> <tr><td>R27E</td><td>R28E</td></tr> <tr><td>S25</td><td>S30</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S36</td><td>S31</td></tr> <tr><td colspan="2">1992</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Bury the wooden post alongside the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/>	T19N		R27E	R28E	S25	S30	-----		S36	S31	1992	
T19N													
R27E	R28E												
S25	S30												

S36	S31												
1992													
	<p>N. 0°30' E., bet. secs. 25 and 30.</p>												
	<p>Over rolling land.</p>												
20.30	<p>Spur, bears SSW and NNE.</p>												
40.09	<p>Point for the 1/4 sec. cor. of secs. 25 and 30, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T19N</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>R27E</td><td>R28E</td></tr> <tr><td>S25</td><td>S30</td></tr> <tr><td colspan="2">1992</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>	T19N		1/4		R27E	R28E	S25	S30	1992			
T19N													
1/4													
R27E	R28E												
S25	S30												
1992													
80.18	<p>Point for the cor. of secs. 19, 24, 25 and 30, at proportionate dist.; there is no remaining evidence of the original cor.</p>												

BOOK 5453

Dependent Resurvey of the West Boundary,
T. 19 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T19N</td></tr> <tr><td style="text-align: center;">R27E</td><td style="text-align: center;">R28E</td></tr> <tr><td style="text-align: center;">S24</td><td style="text-align: center;">S19</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S25</td><td style="text-align: center;">S30</td></tr> <tr><td colspan="2" style="text-align: center;">1992</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/>	T19N		R27E	R28E	S24	S19	-----		S25	S30	1992	
T19N													
R27E	R28E												
S24	S19												

S25	S30												
1992													
	<p>N. 0°30' E., bet. secs. 19 and 24.</p>												
	<p>Over rolling land.</p>												
40.09	<p>The 1/4 sec. cor. of secs. 19 and 24, monumented with a juniper post, 43 ins. long, 3 in. square, lying loose on ground, faintly mkd. with 1/4S on one side.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T19N</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">R27E</td><td style="text-align: center;">R28E</td></tr> <tr><td style="text-align: center;">S24</td><td style="text-align: center;">S19</td></tr> <tr><td colspan="2" style="text-align: center;">1992</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Bury the wooden post alongside the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/>	T19N		1/4		R27E	R28E	S24	S19	1992			
T19N													
1/4													
R27E	R28E												
S24	S19												
1992													
	<p>N. 0°26' E., beginning new measurement.</p>												
40.11	<p>Point for the cor. of secs. 13, 18, 19 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>												

BOOK 5453

Dependent Resurvey of the West Boundary,
T. 19 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T19N</td></tr> <tr><td style="text-align: center;">R27E</td><td style="text-align: center;">R28E</td></tr> <tr><td style="text-align: center;">S13</td><td style="text-align: center;">S18</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S24</td><td style="text-align: center;">S19</td></tr> <tr><td colspan="2" style="text-align: center;">1992</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 0°26' E., bet. secs. 13 and 18.</p> <p>Over rolling land.</p>	T19N		R27E	R28E	S13	S18	-----		S24	S19	1992	
T19N													
R27E	R28E												
S13	S18												

S24	S19												
1992													
40.11	<p>Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>												
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T19N</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">R27E</td><td style="text-align: center;">R28E</td></tr> <tr><td style="text-align: center;">S13</td><td style="text-align: center;">S18</td></tr> <tr><td colspan="2" style="text-align: center;">1992</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>	T19N		1/4		R27E	R28E	S13	S18	1992			
T19N													
1/4													
R27E	R28E												
S13	S18												
1992													
80.22	<p>Point for the cor. of secs. 7, 12, 13 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>												
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T19N</td></tr> <tr><td style="text-align: center;">R27E</td><td style="text-align: center;">R28E</td></tr> <tr><td style="text-align: center;">S12</td><td style="text-align: center;">S 7</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S13</td><td style="text-align: center;">S18</td></tr> <tr><td colspan="2" style="text-align: center;">1992</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T19N		R27E	R28E	S12	S 7	-----		S13	S18	1992	
T19N													
R27E	R28E												
S12	S 7												

S13	S18												
1992													

BOOK 5453

Dependent Resurvey of the West Boundary,
T. 19 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 0°26' E., bet. secs. 7 and 12.</p> <p>Over rolling land.</p>
40.11	<p>Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N 1/4 R27E R28E S12 S 7 1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
80.22	<p>Point for the cor. of secs. 1, 6, 7 and 12, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R27E R28E S 1 S 6 <hr/>S 12 S 7 1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 0°26' E., bet. secs. 1 and 6.</p> <p>Over rolling land.</p>
40.11	<p>The 1/4 sec. cor. of secs. 1 and 6, monumented with a stainless steel post 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. T19N 1/4 R27E R28E S1 S6 1992.</p> <hr/>

BOOK 5453

Dependent Resurvey of the West Boundary,
T. 19 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 2°41' E., beginning new measurement.
40.29	The cor. of Tps. 19 and 20 N., Rs. 27 and 28 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. T20N R27E R28E S36 S31 S1 S6 T19N 1992.
	<hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the Subdivisional Lines, T. 19 N., R. 28 E., Gila and Salt River Meridian, Arizona</p> <hr/>
	<p style="text-align: center;">Restoring the survey executed by Milton Santee, in 1882</p> <hr/>
	From the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, in a mound of stone 3 ft. base, to top, with brass cap mkd. T19N R28E S35 S36 S2 S1 T18N 1991.
	N. 0°42' E., bet. secs. 35 and 36.
	Descend, through scattered piñon and juniper.
39.94	Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T19N R28E 1/4 S35 S36 1993</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Set a steel fence post alongside the stainless steel post.
79.88	Point for the cor. of secs. 25, 26, 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

16
BOOK 5453

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 10px;">T19N</td> <td style="padding: 2px 10px;">R28E</td> </tr> <tr> <td style="padding: 2px 10px; border-right: 1px solid black;">S26</td> <td style="padding: 2px 10px;">S25</td> </tr> <tr> <td style="padding: 2px 10px; border-right: 1px solid black;">S35</td> <td style="padding: 2px 10px;">S36</td> </tr> <tr> <td colspan="2" style="padding: 2px 10px; text-align: center;">1992</td> </tr> </table>	T19N	R28E	S26	S25	S35	S36	1992			
T19N	R28E										
S26	S25										
S35	S36										
1992											
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located 40 lks., E. of wash, drains NNW.</p> <p>From this cor. point, the cor. of secs. 1, 2, 35 and 36 on the N. bdy. of Tp., bears. N. 1°40' E., 399.25 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T20N R28E S35 S36 S2 S1 T19N 1992.</p> <p>From this same cor. point, the cor. of secs. 25, 30, 31 and 36 on the W. bdy. of Tp., bears. S. 89°47' W., 396.18 chs. dist., hereinbefore described.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of Tp., hereinbefore described.</p> <p>S. 89°07' W., bet. secs. 25 and 36.</p> <p>Over Gently rolling land.</p>										
39.60	<p>Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 10px;">T19N</td> <td style="padding: 2px 10px;">R28E</td> </tr> <tr> <td colspan="2" style="padding: 2px 10px;">S25</td> </tr> <tr> <td colspan="2" style="padding: 2px 10px;">1/4 —</td> </tr> <tr> <td colspan="2" style="padding: 2px 10px;">S36</td> </tr> <tr> <td colspan="2" style="padding: 2px 10px;">1993</td> </tr> </table>	T19N	R28E	S25		1/4 —		S36		1993	
T19N	R28E										
S25											
1/4 —											
S36											
1993											
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>										

BOOK 5453

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.20	The cor. of secs. 25, 26, 35, and 36.
	<hr/> <p style="text-align: center;">Subdivision of Section 36, T. 19 N., R. 28 E., Gila and Salt River Meridian, Arizona</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 1 and 36 on the S. bdy. of Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T19N R28E 1/4 S36 S1 T18N 1991.</p> <p>N. 0°24' E., on the N. and S. center line of sec. 36.</p> <p>Over gently rolling land.</p>
20.11	<p>Point for the center S. 1/16 sec. cor. of sec. 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R28E C S1/16 S36 C 1993</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
40.22	<p>Point for the center 1/4 sec. cor. of sec. 36, at intersection with the E. and W. centerline of sec. 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R28E C1/4 S36 1993</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
80.44	<p>The 1/4 sec. cor. of secs. 25 and 36.</p> <hr/>

BOOK 5453

Subdivision of Section 36,
T. 19 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS	
<p>19.91</p>	<p>From the 1/4 sec. cor. of secs. 31 and 36 on the E. bdy. of Tp., hereinbefore described.</p> <p>S. 89°32' W., on the E. and W. center line of sec. 36.</p> <p>Over gently rolling land.</p> <p>Point for the center E. 1/16 sec. cor. of sec. 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R28E E1/16 C———C S36 1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located 60 lks. S. of spur, bears NE and SW.</p>
<p>39.82</p>	<p>The center 1/4 sec. cor. of sec.36.</p>
<p>79.64</p>	<hr/> <p style="text-align: center;">SE 1/4 Section 36</p> <hr/> <p>From the E. 1/16 sec. cor. of secs. 1 and 36 on the S. bdy. of Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T19N R28E E1/16 S36 S1 T18N 1991.</p> <p>N. 0°14' E., on the N. and S. center line of the SE 1/4 sec. 36.</p> <p>Over gently rolling land.</p> <p>Point for a witness point, on the N. and S. center line of the SE 1/4 sec. 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

BOOK 5453

Subdivision of Section 36,

T. 19 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">WP T19N R28E E S 36 E 1993</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located on edge of Puerco Rim.</p> <p>Descend.</p>
20.18	<p>The point for the SE 1/16 sec. cor. of sec. 36, at intersection with the E. and W. center line of the SE 1/4 of sec.36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
36.40	<p style="text-align: center;">T19N R28E SE 1/16 1993</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located on N. slope of Rio Puerco Rim.</p> <p>End descent.</p>
40.36	<p>The center W. 1/16 sec. cor. of sec. 36.</p>
12.97	<hr/> <p>From the S. 1/16 sec. cor. of secs. 31 and 36 on the E. bdy. of Tp., hereinbefore described.</p> <p>S. 89°44' W., on the E. and W. center line of the SE 1/4 sec. 36.</p> <p>Over gently rolling land.</p> <p>Point for a witness point, on the E. and W. center line of the SE 1/4 sec. 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

BOOK 5453

Subdivision of Section 36,
T. 19 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">WP T19N R28E S S—S 36 1993</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located on edge of Puerco Rim.</p> <p>19.96 The SE 1/16 sec. cor. of sec. 36.</p> <p>39.92 The center S. 1/16 sec. cor. of sec. 36.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p>The land encompassed in this survey is located approximately 9 miles south of Sanders, Arizona. Access is by dirt roads off of U. S. Highway 666.</p> <p>Vegetation consists of juniper and piñon trees, sage brush and bunch grass.</p> <p>There has been no mining activity and no homes in the area.</p> <p>The mean magnetic declination, as taken from quadrangle map BEACON WELL, ARIZ., published in 1971 by the U. S. Geological Survey, is 13 1/2° E.</p>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
William P. Carpender	Land Surveyor
Geoffrey A. Graham	Surveying Technician
Donald L. Brewer	Surveying Technician
Gordon R. Bube1	Surveying Technician
Rebecca Rameriz	Surveying Technician
Jimmy James, Jr.	Surveying Aid
Jack E. Arend	Surveying Aid

