

ORIGINAL

BOOK 5477

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

**FIELD NOTES
OF THE
DEPENDENT RESURVEY OF**

A PORTION OF THE EAST BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES

AND MINERAL SURVEY No. 4036A,

AND

THE SUBDIVISION OF SECTIONS 12, 13, 14, AND 23,

TOWNSHIP 1 SOUTH, RANGE 13 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

William P. Carpender

Cadastral Surveyor

Clyde J. King

Cadastral Surveyor

Under Special Instructions dated April 4, 1994, approved April 4, 1994, which provided for the surveys included under Group Number 772, and assignment instructions dated May 16, 1994 and May 31, 1995.

Survey Commenced May 23, 1994

Survey Completed September 25, 1995

BOOK 5477
INDEX DIAGRAM

TOWNSHIP 1 SOUTH, RANGE 13 EAST,

6	5	4	3	2	1		
						10	
					20		
7	8	9	10	11	19	12	7
					24	18	
18	17	16	15	14	16	13	4
				24		14	
19	20	21	22	22	23	11	24
					21		
30	29	28	27	26		25	
31	32	33	34	35		36	

Dependent Resurvey of M.S. 4036A
 Subdivision of Section 12
 Subdivision of Section 13
 Subdivision of Section 14
 Subdivision of Section 23

Pp. 25-29
 Pp. 29-35
 Pp. 36-46
 Pp. 46-48
 Pp. 48-49

BOOK 54 77

T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the east boundary, a portion of the subdivisional lines and Mineral Survey No. 4036A, and the subdivision of sections 12, 13, 14, and 23, Township 1 South, Range 13 East, Gila and Salt River Meridian, Arizona.

The Gila and Salt River Base Line was surveyed by Albert T. Colton in 1899. The Gila and Salt River Base Line was resurveyed, the east boundary and a portion of the subdivisional lines were surveyed by Alexander B. Titus in 1905. A portion of the east boundary was retraced by Philip Contzen in 1906. Mineral Survey No. 4036 A&B was surveyed by Edgar C. Kinderman in 1927. New measurements for a portion of the subdivisional lines were reported, and the corner of sections 1, 2, 11, and 12 remonumented by Travis L. Gant in 1973-1975, under Mineral Survey No. 4766.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated April 4, 1994, for Group No. 772, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of all lines were determined by direct hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured with Sokkia Set2BII and Topcon GTS-3B total station instruments.

The geographic position of the corner of sections 12 and 13 only, on the east boundary of the Township, as determined from a tie made to U.S. Geological Survey triangulation station "CRAIG 1944-46", is as follows:

Latitude: 33°21'01.97" N. Longitude: 110°59'04.51" W. NAD27

The mean magnetic declination, as taken from quadrangle map "Superior, ARIZ.", published in 1948 and photorevised in 1981 by U.S. Geological Survey, is 12 1/2° E.

BOOK 54 77

Dependent Resurvey of a Portion of the East Boundary
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS

Restoring the resurvey executed by
Philip Contzen in 1906

Beginning at the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., monumented with a granite stone, 26 x 11 x 6 ins., firmly set, projecting 8 ins. above ground, mkd. with 3 grooves on the N. face, and 3 grooves on the S. face, with a tack grouted onto the top, from which the original bearing trees

A dead juniper, 26 ins. diam., bears N. $89\frac{3}{4}^{\circ}$ E.,
113 lks. dist., with no visible marks on a open blaze.
(Record: oak, N. $87^{\circ}45'$ E., 115 lks.)

A juniper 28 ins. diam., bears S. $73\frac{1}{2}^{\circ}$ W.,
83 lks. dist., with no visible marks on a open blaze.
(Record: oak, S. $71^{\circ}40'$ W., 82 lks.)

At the cor. point.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
18 ins. in the ground, supported in a mound of stone, 3 ft. base,
to top, with brass cap mkd.

T1S	
R13E	R14E
S13	S18
S24	S19
1994	

from which

A granite boulder, 30 x 20 x 8 ft., bears N. $12\frac{1}{2}^{\circ}$ E.,
19 1/2 lks. dist., mkd. X B0 on the S. face.

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case
beneath the stainless steel post.

Bury the stone alongside the stainless steel post.

The cor. is located on a NW facing, oak brush and boulder filled
slope.

N. $0^{\circ}39'$ E., on the E. bdy. of sec. 13.

Over mountainous land, through granite boulders, scattered
juniper, piñon and oak, with manzanita and oakbrush undergrowth.

19.99

Point for the S. 1/16 sec. cor. of sec. 13 only, on the E. bdy.
of the Tp.

BOOK 5477

Dependent Resurvey of a Portion of the East Boundary
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in granite bedrock, with cap mkd.</p>
	<p style="text-align: center;">T1S R13E R14E S13 S 1/16 1994</p>
	<p>from which</p> <p style="padding-left: 40px;">A granite rock outcrop, 6 x 4 x 2 1/2 ft., bears S. 4 1/2° E., 61 1/2 lks. dist., mkd. X B0 on the N. face.</p>
	<p>The cor. is located on a rock shelf, 50 lks. wide, and 60 lks. S. of a wash, drains W.</p>
39.98	<p>The 1/4 sec. cor. of sec. 13 only, on the E. bdy. of the Tp., monumented with a cross on a granite boulder, 24 x 12 x 10 ft., from which the original bearing trees</p> <p style="padding-left: 40px;">An oak, 18 ins. diam., bears S. 45° E., 46 lks. dist., with no visible marks.</p> <p style="padding-left: 40px;">An oak, 18 ins. diam., bears S. 5° W., 37 lks. dist., with no visible marks.</p>
	<p>Cor. not remonumented.</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, cemented in place, in a granite boulder, 8 x 7 x 5 ft., for a reference monument, bears N. 3°02' E., 62.6 ft. dist., with cap mkd. T1S R14E RM S18 62.6 FT TO COR 1994, and an arrow pointing to the cor.</p>
	<p style="text-align: center;">_____</p> <p>N. 0°23' W., beginning new measurement.</p>
19.96	<p>True point for the N. 1/16 sec. cor. of sec. 13 only, on the E. bdy. of the Tp., falls on a vertical face of a granite rock outcrop, where it is impracticable to establish a permanent monument.</p>
	<p>From this point, the point selected for a witness cor. bears N. 35°40' W., 0.53 chs. dist.</p>

BOOK 5477

Dependent Resurvey of a Portion of the East Boundary
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, supported in a mound of stone, 4 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">WC T1S R13E R14E S13 N 1/16 1994 ↘</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p>
34.93	<p>Point for the N-N-N 1/256 sec. cor. of sec. 13 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E R14E S13 N-N-N 1/256 1994</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. is located at the base of a rock ledge, 12 ft. high, 60 ft. long, bears E. and W.</p>
39.92	<p>The cor. of secs. 12 and 13 only, perpetuated by persons unknown, monumented with an iron pipe, 1 3/4 ins. diam., 24 ins. long, with a 1/2 in. diam. rebar inside, firmly set, flush with ground, from which the remaining original bearing trees</p> <p style="padding-left: 40px;">An oak, 19 ins. diam., bears S. 39° E., 31 lks. dist., with opened blaze, no visible marks. (Record, S. 35°40' E., 29 lks. dist.)</p> <p style="padding-left: 40px;">An oak, 30 ins. diam., bears S. 69 1/2° W., 46.5 lks. dist., with healed blaze. (Record, S. 69°05' W., 45 lks. dist.)</p> <p style="padding-left: 40px;">An oak, 18 ins. diam., bears N. 20° W., 16 lks. dist., with opened blaze, no visible marks. (Record, N. 27° W., 17 lks. dist.)</p> <p>This is accepted as a careful and faithful perpetuation of the original cor. position.</p>


BOOK 5477

Dependent Resurvey of a Portion of the East Boundary
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS

At the cor. point.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, encircled with a collar of stone, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

Deposit the iron pipe inside the stainless steel post.

From this cor. point, U.S. Geological Survey triangulation station "Craig 1944-46", with published latitude of 33°21'16.554" N. and longitude of 110°59'47.995" W., NAD27, bears N. 68°13' W., 60.20 chs. dist., monumented with a copper nail and washer. Reference monuments were found in good order, and used to verify the position of the tri-station monument.


N. 0°24' E., on the E. bdy. of sec. 12.

Over rolling land, through granite boulders, scattered juniper, pinion and oak, with manzanita and oakbrush undergrowth.

0.77

Point for the closing cor. of secs. 7 and 18, T. 1 S., R. 14 E., at proportionate distance; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, encircled with a collar of stone, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

BOOK 5477

Dependent Resurvey of a Portion of the East Boundary
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point a brass cap, 1/2 in. diam., firmly set in a granite stone, 24 ins. x 18 ins. x 6 ins., mkd. SW COR. 7 LS 8022, established by J. H. Quay, LS 8022, bears N. 12° E., 2.5 lks. dist. Upon speaking with the local land owner who was present during the execution of the survey that this corner refers to, it was determined that this cor. was established using improper procedures and not utilized in the course of this resurvey.</p>
11.50	Center of U.S. Highway 60, bears NE and SW.
14.58	<p>Point for the N-S-S 1/256 sec. cor. of sec. 12 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bed rock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T1S</p> <p>R13E R14E</p> <p>N-S-S 1/256 </p> <p> S12 </p> <p> 1994</p> </div> <p>from which</p> <p style="padding-left: 40px;">A granite boulder, 4.5 x 3 x 3 ft., bears N. 11° E., 10.5 lks. dist., mkd. X B0 on the S face.</p> <p style="padding-left: 40px;">A granite boulder, 5.5 x 4 x 4 ft., bears N. 60° W., 8.5 lks. dist., mkd. X B0 on the S face.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, bears N. 24°28' W., 6 lks. dist.</p>
19.44	<p>Point for the S. 1/16 sec. cor. of sec. 12 only, falls on granite rock face, 30 ft. high, where it is impracticable to establish a permanent monument.</p> <p>From this point, the point selected for a witness cor. bears N. 3°14' E., 0.33 chs. dist.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, cemented in place, in a granite boulder, 21 x 13 x 7 ft. high, with cap mkd.</p>

BOOK 5477

Dependent Resurvey of a Portion of the East Boundary
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS

WC
T1S
R13E R14E
S12 |
S 1/16 |
1994

Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

38.88

The 1/4 sec. cor. of sec. 12 only, monumented with a granite stone, 19 x 13 x 10 ins., firmly set, projecting 7 ins. above ground, mkd. 1/4 on the W. face, with a tack grouted on to the top, from which the remaining original bearing tree

A forked juniper, 26 ins. diam. at base, bears N. 73 1/4° E., 128 lks. dist., with a partially healed blaze, mkd. 1/4 S7 BT.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bed rock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T1S
R13E R14E
1/4 |
S12 |
1994

from which

A pine, 24 ins. diam., bears N. 89 3/4° E., 113 lks. dist., mkd. 1/4 S12 BT.

Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

Bury the stone alongside the stainless steel post.


Cor. located 3 lks. E. of a rock face, 5 ft. high.

N. 0°12' E., beginning new measurement.

Over rolling land, through granite boulders, scattered juniper, pinion and oak, with manzanita and oakbrush undergrowth.

BOOK 5477

Dependent Resurvey of a Portion of the East Boundary
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona


CHAINS	
40.51	<p>The cor. of secs. 1 and 12 only, monumented with a quartzite stone, 24 x 10 x 4 ins., firmly set, projecting 12 ins. above ground, mkd. with 5 notches on the S. face, with a mound of stone 2 ft. diam. 2 ft. high to the W., from which the remaining original bearing trees</p> <p style="padding-left: 40px;">A dead and down oak, size indeterminate, bears N. 73 1/4° E., 274 lks. dist., with no visible marks. (Record, 277 lks.)</p> <p style="padding-left: 40px;">A forked juniper, 20 ins. diam. at base, bears S. 27 1/4° W., 189 lks. dist., with no visible blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bed rock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p>from which</p> <p style="padding-left: 40px;">A forked juniper, 9 ins. diam. at base, bears S. 17 3/4° W., 50.5 lks. dist., mkd. T1SR13E S12 BT.</p> <p>Bury the stone alongside the stainless steel post and deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. located 24 ft. N. of a wash, drains W.</p>
1.10	<p>N. 0°01' E., on the E. bdy. of sec. 1.</p> <p>Over rolling land, through granite boulders, scattered juniper, pinion and oak, with manzanita and oakbrush undergrowth.</p> <p>The closing cor. of secs. 6 and 7, T. 1 S., R. 14 E., monumented with a granite stone, 16 x 10 x 8 ins., firmly set, projecting 9 ins. above ground, no apparent marks on the stone, with a tack grouted onto the top, and a mound of stone, 4 ft. base, 3 ft. high, E. of the cor.</p> <p>At the corner point</p>

BOOK 5477

Dependent Resurvey of a Portion of the East Boundary
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, supported in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.



from which

A forked juniper, 29 ins. diam. at the base, bears
S. 41 1/2° E., 268.5 lks. dist., mkd. T1SR14E S7 BT.

Bury the stone alongside and deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

From this cor. point, the closing cor. of Tps. 1 S., Rs. 13 and 14 E., monumented with a quartzite stone, 14 x 6 x 5 ins., no apparent marks with a tack grouted onto the top, and a mound of stone to the S., bears N. 0°01' E., 77.25 chs. dist. Not remonumented.

Intervening cors. were searched for and not found.

Dependent Resurvey of a Portion of the Subdivisional lines
T. 1 S., R. 13 E., Gila and Salt River Mer., Arizona

Restoring the survey executed by
Alexander B. Titus in 1905

From the cor. of secs. 23, 24, 25, and 26, monumented with a trachite stone, 33 x 13 x 7 ins., firmly set, projecting 28 ins. above the ground, in a mound of stone, 3 ft. base, 1 ft. high, mkd. with 2 notches on the S. and 1 notch on the E. sides, with a mound of stone 3 ft. base, 1 1/2 ft. high, W. of the cor.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.

BOOK 5477

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS

T1S	R13E
S23	S24
S26	S25
1995	

Deposit a magnet in a 1 x 1 x 2 in. white plastic case beneath the stainless steel post.

Bury the stone alongside the stainless steel post.

The cor. is located on the W. side of a steep gulch, with prominent large boulders on the N. and W.

N. 0°02' W., bet. secs. 23 and 24.

Over rocky, mountainous terrain.

40.23

The 1/4 sec. cor. of secs. 23 and 24, monumented with a trachite stone, 20 x 14 x 6 ins., firmly set, projecting 8 ins. above the ground, mkd. 1/4 on a face, with a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor., from which the original bearing trees

A juniper, 24 ins. diam., bears N. 88 3/4° E., 105 lks.
dist., mkd. 1/4S24BT. (Record, N. 89°40' E., 102 lks.)

A juniper, 15 ins. diam., bears S. 29 3/4° W., 137 lks.
dist., mkd. with a partly opened blaze.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T1S	R13E
S23	S24
1/4	
1995	

Deposit a magnet in a 1 x 1 x 2 in. white plastic case beneath the stainless steel post.

Bury the stone alongside the stainless steel post.

N. 0°01' W., beginning new measurement.

BOOK 5477

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.36	<p>The N. 1/16 sec. cor. of secs. 23 and 24, monumented with a rebar, 15 ins. long, 5/8 ins. diam., firmly set, projecting 3 ins. above the ground, with tag mkd. L.S. 5703, with a mound of stone, 2 ft. base, 2 ft. high, S. of the cor., set by Travis Lee Gant, LS 5703, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T1S R13E N1/16 S23 S24 1995</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 in. white plastic case beneath the stainless steel post.</p> <p>Bury the rebar inside the stainless steel post, and remove the mound of stones, N. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°04' E., beginning new measurement.</p>
20.38	<p>The cor. of secs. 13, 14, 23, and 24, determined at record bearing and dist. from the remaining original bearing tree</p> <p style="padding-left: 40px;">A forked juniper, 20 ins. diam. at base, bears N. 53° E., 135 lks. dist., with a partially healed blaze, mkd. 1SR13ES13B.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T1S R13E S14 S13 S23 S24 1994</p> </div> <p>from which</p>

BOOK 5477

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A juniper, 8 ins. diam., bears S. 47° E., 92 lks. dist., mkd. T1SR13ES24BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. is located 27 lks. S. of a barbed wire fence, 4 strand, bears E. and W., 100 lks. E. of a trail road, bears SSE and NNW, and 65 lks. E. of a wash drains S.</p> <hr/> <p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°39' W., bet. secs. 13 and 24.</p> <p>Over rolling land, through scattered juniper, piñon and oak, with manzanita and oakbrush undergrowth.</p>
20.02	<p>Point for the E. 1/16 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, supported in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E S13 E 1/16 — S24 1994</p> <p>from which</p> <p style="text-align: center;">A granite boulder, 15 x 10 x 10 ft., bears S. 30 1/2° W., 13 1/2 lks. dist., mkd. X B0 on the NE face.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. is located on a brushy N. facing slope, and 60 lks W. of a wash, drains NW.</p>
40.04	<p>The 1/4 sec. cor. of secs. 13 and 24, monumented with a granite stone, 18 x 10 x 8 ins., firmly set, projecting 10 ins. above ground, mkd. 1/4 on the N. face, from which the original bearing trees</p> <p style="text-align: center;">A dead oak, 6 ins. diam., bears S. 37 3/4° W., 140 1/2 lks. dist., with a rotted blaze. (Record, 139 lks.)</p>

BOOK 5477

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A dead juniper, 20 ins. diam., bears N. $7\ 1/2^\circ$ W., 27 lks. dist., mkd. 1/4S13BT (Record, N. $4^\circ 50'$ W., 25 lks.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, $2\ 1/2$ ins. diam., 21 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E S13 1/4 — S24 1994</p> <p>from which</p> <p>A pine, 7 ins. diam., bears N. $30\ 1/4^\circ$ E., 110 lks. dist., mkd. 1/4S13BT.</p> <p>A juniper, 10 ins. diam., bears S. $53\ 1/2^\circ$ W., $73\ 1/2$ lks. dist., mkd. 1/4S24BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>Bury the stone alongside the stainless steel post.</p> <p>The cor. is located on a brushy N. slope.</p> <p style="text-align: center;">_____</p> <p>N. $89^\circ 37'$ W., beginning new measurement.</p>
20.07	<p>The W. 1/16 sec. cor. of secs. 13 and 24, monumented with an iron pipe, 1 in. diam., firmly set, projecting 7 ins. above ground, with a tag mkd. LS 14169, with a 1/4 in. rebar alongside, determined by Evert D. Bungler, LS 14169, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, $2\ 1/2$ ins. diam., 21 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E S13 W 1/16 — S24 1994</p>

BOOK 5477

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p>
	<p>Bury the iron pipe and rebar inside the stainless steel post.</p>
	<p>The cor. is located on a NW slope and 30 lks. E. of a barbed wire fence, 4 strand, bears N. and S.</p>
	<p>N. 89°37' W., beginning new measurement.</p>
20.07	<p>The cor. of secs. 13, 14, 23 and 24.</p>
	<p>N. 0°02' E., bet. secs. 13 and 14.</p>
	<p>Over rolling land, through medium juniper and oak.</p>
19.95	<p>Point for the S. 1/16 sec. cor. of secs. 13 and 14.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T1S R13E S 1/16 S14 S13 1994</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p>
	<p>The cor. is located 30 lks. N. of the cor. of an improved gravel road, extending S. and E.</p>
34.50	<p>Center of U.S. Highway 60, bears E. and W.</p>
39.90	<p>The 1/4 sec. cor. of secs. 13 and 14, monumented with a cross on a granite stone in place, 30 x 18 ins., firmly set, projecting 4 ins. above ground, mkd. 1/4 + on the top, filled with grout, from which the original bearing tree</p>
	<p style="text-align: center;">A forked juniper, 16 ins. diam. at base, bears S. 81 1/2° W., 188 lks. dist., mkd. /4.</p>
	<p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in the orig. stone, with cap mkd.</p>

BOOK 5477

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T1S R13E 1/4 S14 S13 1994</p> <p>From this cor. point, a wood post, 4 ins. diam., 4 ft. high, in a mound of stone, bears S. 89° W., 39 1/2 lks. dist.</p> <p>The cor. is located in a barbed wire fence, 4 strand, bears N. and S. and 90 lks. N. of a stone wall, 3 ft. high, bears E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°10' E., beginning new measurement.</p>
20.01	<p>Point for the N. 1/16 sec. cor. of secs. 13 and 14.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in granite bedrock, with cap mkd.</p>
	<p style="text-align: center;">T1S R13E N 1/16 S14 S13 1994</p> <p>The cor. is located on a W. slope, 8 lks. W. of a barbed wire fence, 4 strand, bears N. and S.</p>
40.02	<p>The cor. of secs. 11, 12, 13, and 14, monumented with a granite stone, 19 x 11 x 7 ins., firmly set, projecting 9 ins. above ground, mkd. with 4 grooves on the S. side, 1 groove on the E. side, with a tack grouted onto the top, and in a mound of stone, 3 ft. high, W. of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E S11 S12 —+— S14 S13 1994</p> <p>Deposit the stone in the supporting mound of stone.</p>

BOOK 54 77

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. is located on a steep, rocky, S. slope.</p> <hr/> <p>From the cor. of secs. 12 and 13 only, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°36' W., bet. secs. 12 and 13.</p> <p>Over nearly flat land, through scattered dwellings, medium juniper and oak.</p> <p>20.05 Point for the E. 1/16 sec. cor. of secs. 12 and 13, falls in the pavement of U. S. Highway 60.</p> <p>Set an aluminum nail, 3 ins. long, 1 in. diam., flush with the pavement, mkd. SURVEY MRK.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 23 ins. in the ground, for a reference monument, bears S. 69°25' E., 76.8 ft. dist., with cap mkd. RM T1S R13E E1/16 S13 76.8 FT TO COR 1994, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, for a reference monument, bears S. 19°27' W., 87.5 ft. dist., with cap mkd. RM T1S R13E E1/16 S13 87.5 FT TO COR 1994, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. is located 25 lks. S. of the E. edge of the pavement of U.S. Highway 60.</p>
25.06	<p>Point for the E-W-E 1/256 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E S12 E-W-E 1/256 S13 1994</p>

BOOK 54 77

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, a rebar, 1/2 in. diam., firmly set, projecting 4 ins. above the ground, with cap mkd. SUTTON COR 2 63, bears East, 18 lks. dist., established for a property cor. by Oscar T. Smith, LS 2648, in 1963, as per a map filed at the office of Evert E. Bunger, LS 14169, in Miami, Arizona, using unknown procedures, and is not utilized in the course of this survey.</p> <p>The cor. is located 15 lks. W. of a cor. of fences extending N. and WNW.</p>
40.10	<p>Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 9 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E S12 1/4 — S13 1994</p> <p>from which</p> <p style="padding-left: 40px;">A granite boulder, 6 x 4 x 3 ft., bears N. 34 3/4° E., 101 lks. dist., mkd. X B0 on the SW face.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, for a reference monument, bears N. 79°25' W., 23.19 ft. dist., with cap mkd. RM T1S R13E S12 23.19 FT TO COR 1994, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. is located in a track road, 15 lks. wide, bears ENE and WSW.</p>
80.20	<p>The cor. of secs. 11, 12, 13, and 14.</p> <hr/> <p>N. 0°07' E., bet secs. 11 and 12.</p> <p>Over mountainous terrain.</p>

BOOK 5477

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.63	<p>The 1/4 sec. cor. of secs. 11 and 12, monumented with a cross on a boulder, 8 x 5 x 8 ft. high, mkd. + 1/4, with a mound of stone, 3 x 3 ft., W. of the cor., from which the original bearing tree</p> <p style="padding-left: 40px;">A dead, standing juniper, 9 ins. diam., bears S. 67 1/4° E., 87 lks. dist., mkd. S12BT. (Record: S. 64°15' E., 84 lks.)</p> <p>At the cor. point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, cemented in place, with top mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T1S R13E</p> <p>1/4</p> <p>S11 S12</p> <p>1995</p> </div> <p>The cor. is located 20 lks. N. of a fence, bears SE and NW.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 2°40' E., beginning new measurement.</p>
40.16	<p>The cor. of secs. 1, 2, 11, and 12, monumented with an iron pipe, 1 in. diam., firmly set in concrete, projecting 9 ins. above the ground, in a mound of stone, 2 ft. base, to top, with brass cap, 2 ins. diam. mkd. T.1 S. R.13 E. S.2 S.1 S.11 S.12 1974 L.S.5703., with a mound of stone and concrete, 2 ft. base, 2 ft. high, N. of the cor., from which the original bearing tree</p> <p style="padding-left: 40px;">A piñon, 14 ins. diam., bears N. 0 1/4° E., 40 lks. dist., mkd. with an open, rotted blaze. (Record, N. 5°20' E.)</p> <p>This cor. was perpetuated by Travis Lee Gant, LS 5703, in 1974, as described in the field notes of Mineral Survey No. 4766, Eder Group, and does not require remonumentation.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the cor. of secs. 1 and 12 only, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°40' W., bet. secs. 1 and 12.</p> <p>Over mountainous terrain, through dense juniper, oak, piñon, and underbrush.</p>

BOOK 5477

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.17	<p>The 1/4 sec. cor. of secs. 1 and 12, monumented with a cross on a trachite stone, 22 x 13 x 5 ins., firmly set, projecting 15 ins. above the ground, in a mound of stone, 3 ft. base, 1/2 ft. high, mkd. + 1/4 on top, with a mound of stone, 3 ft. base, 1 ft. high, N. of the cor., from which a local bearing tree</p> <p style="padding-left: 40px;">An alligator juniper, 10 ins. diam., bears S. 5 3/4° E., 9 lks. dist., mkd. with a blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> T1S R13E S 1 1/4 ——— S12 1995 </div> <p>Deposit a magnet in a 1 x 1 x 2 in. white plastic case beneath the stainless steel post.</p> <p>Bury the stone alongside the stainless steel post, and remove the mound of stone to the N.</p> <p>Set an aluminum sign post alongside the cor.</p> <p>The cor. is located on a NE slope, 38 lks. S. of a dirt road, 22 lks. wide, bears E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 88°59' W., beginning new measurement.</p>
38.51	<p>The cor. of secs. 1, 2, 11, and 12.</p> <hr/>
40.25	<p>From the cor. of secs. 23, 24, 25, and 26.</p> <p>N. 89°53' W., bet. secs. 23 and 26.</p> <p>Over mountainous, rocky terrain.</p> <p>The 1/4 sec. cor. of secs. 23 and 26, monumented with a trachite stone, 21 x 9 x 6 ins., firmly set, projecting 12 ins. above the ground, mkd. 1/4 on the N. side, with a mound of stone, 3 1/2 ft. base, 2 ft. high, N. of the cor.</p> <p>At the cor. point</p>

BOOK 54 77

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E S23 1/4 ——— S26 1995</p> <p>Deposit a magnet in a 1 x 1 x 2 in. white plastic case beneath the stainless steel post.</p> <p>Bury the stone alongside the stainless steel post.</p> <p style="text-align: center;">—————</p> <p>N. 88°44' W., beginning new measurement.</p>
40.02	<p>The cor. of secs. 22, 23, 26, and 27, monumented with a trachite stone, 26 x 16 x 6 ins., firmly set, projecting 16 ins. above the ground, in a well embedded mound of stone, mkd. with 2 notches on the E., and 2 notches on the S. sides, with a mound of stone, 2 ft. diam., 3 ft. high, W. of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E S22 S23 ——— ——— S27 S26 1995</p> <p>Deposit a magnet in a 1 x 1 x 2 in. white plastic case beneath the stainless steel post.</p> <p>Bury the stone alongside the stainless steel post.</p> <p style="text-align: center;">—————</p> <p>N. 0°37' E., bet. secs. 22 and 23.</p> <p>Over rolling, mountainous terrain.</p>
40.07	<p>The 1/4 sec. cor. of secs. 22 and 23, monumented with a cross on a trachite stone in place, 18 x 14 x 8 ins. above the ground, mkd. + 1/4, with a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of the cor.</p>

BOOK 54 77

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>At the cor. point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, cemented in place, with top mkd.</p> <p style="text-align: center;">T1S R13E 1/4 S22 S23 1995</p> <p>Deposit a magnet, 7/8 in. diam., 1 in. long, beneath the brass tablet.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°03' W., beginning new measurement.</p>
40.19	<p>The cor. of secs. 14, 15, 22, and 23, monumented with a cross mkd. on a trachite bench in place, 20 x 5 ft., projecting 8 ft. above the ground, mkd. with 2 grooves E., and 3 grooves S. of the cross, with a mound stone 2 ft. base, 2 ft. high, W. of the cor.</p> <p>At the cor. point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, cemented in place, with top mkd.</p> <p style="text-align: center;">T1S R13E S15 S14 ----- S22 S23 1995</p> <p>Deposit a magnet, 7/8 in. diam., 1 in. long, beneath the brass tablet.</p> <hr style="width: 80%; margin: 10px auto;"/>
40.22	<p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>N. 89°46' W., bet. secs. 14 and 23.</p> <p>Over rocky, mountainous terrain, through juniper, oak, piñon, and dense underbrush.</p> <p>The 1/4 sec. cor. of secs. 14 and 23, monumented with a cross on a boulder, 36 x 24 x 8 ins. high, mkd. + 1/4, with a mound of stone, 3 ft. base, 2 ft. high, N. of the cor., from which the original bearing tree</p> <p style="text-align: center;">A dead standing oak, 10 ins. diam., bears S. 23 1/2° W., 72 lks. dist., mkd. with a blaze. (Record, S. 23°50' W., 69 lks.)</p>

BOOK 54 77

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>At the cor. point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, cemented in place, with top mkd.</p> <p style="text-align: center;">T1S R13E S14 1/4— S23 1995</p> <p>Set an aluminum sign post near the cor.</p> <p style="text-align: center;">_____</p> <p>N. 89°51' W., beginning new measurement.</p>
39.62	<p>The cor. of secs. 14, 15, 22, and 23.</p> <hr/>
	<p>N. 0°05' W., bet. secs. 14 and 15.</p> <p>Over rocky, mountainous terrain, through juniper, oak, piñon, and dense underbrush.</p>
40.04	<p>The 1/4 sec. cor. of secs. 14 and 15, monumented with a trachite stone, 20 x 11 x 7 ins., firmly set, projecting 12 ins. above the ground, mkd. 1/4 on a face, filled with grout, and a tack grouted onto the top, with a mound of stone, 3 ft. base, 2 1/2 ft. high, S. of the cor.</p>
	<p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E 1/4 S15 S14 1995</p> <p>Deposit a magnet in a 1 x 1 x 2 in. white plastic case beneath the stainless steel post.</p> <p>Bury the stone alongside the stainless steel post, and remove the mound of stone, S. of the cor.</p> <hr/>
	<p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>N. 89°44' W., bet. secs. 11 and 14.</p>

BOOK 5477

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rocky, mountainous terrain.
20.07	<p>Point for the E. 1/16 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, supported in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E S11 E1/16 ——— S14 1995</p>
40.14	<p>Deposit a magnet in a 1 x 1 x 2 in. white plastic case beneath the stainless steel post.</p> <p>The 1/4 sec. cor. of secs. 11 and 14, monumented with a cross on a trachite stone, 18 x 12 x 6 ins., firmly set, projecting 13 ins. above the ground, mkd. + 1/4 on top, with a mound of stone, 3 ft. base, 3 ft. high, N. of the cor., from which the remaining original bearing tree</p> <p style="text-align: center;">An oak, 12 ins. diam., bears S. 11°20' E., 99 lks. dist., mkd. with a healed blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E S11 1/4 ——— S14 1995</p> <p>Deposit a magnet in a 1 x 1 x 2 in. white plastic case beneath the stainless steel post.</p> <p>Bury the stone alongside the stainless steel post.</p>
<hr/> <p>Dependent Resurvey of Mineral Survey No. 4036A T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
<p>Restoring the survey executed by Edgar C. Kinderman, U.S. Mineral Surveyor, in 1927</p> <hr/>	

BOOK 5477

Dependent Resurvey of Mineral Survey No. 4036A
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS

LONGVIEW LODGE


From cor. 1, Longview lode, M.S. 4036A, monumented with a granite stone, 30 x 13 x 8 ins., firmly set, projecting 15 ins. above the ground, mkd. 1-L 4036 and an X on top, with a mound of stone, 3 ft. base, 3 ft. high, NE of the cor., from which the remaining original bearing objects

A granite boulder, 5 x 7 ft., projecting 4 ft. above ground, bears N. 16° 52' E., 11.74 ft. dist., with no marks visible.

A granite boulder, 8 x 14 ft., projecting 3 ft. above ground, bears S. 70° 20' E., 7.63 ft. dist., with no marks visible.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 in. white plastic case beneath the stainless steel post.

Bury the stone alongside the stainless steel post, and remove the mound of stone, NE of the cor.

Set an aluminum sign post alongside the cor.

The cor. is located 23 lks. E. of a dirt road, 22 lks. wide, bears SSE and NNW.

From this cor. point, the 1/4 sec. cor. of sec. 12 only, on the E. bdy. of the Tp., bears N. 78°53' E., 18.84 chs. dist., hereinbefore described.

S. 26°18' W., on line 1-2, Longview lode.

3.75

Intersect the N. and S. center line of the SE 1/4 of sec. 12, not monumented.



BOOK 5477

Dependent Resurvey of Mineral Survey No. 4036A
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point, the SE 1/16 sec. cor. of sec. 12 bears S. 0°20' W., 12.21 chs. dist., hereinafter described.</p>
17.30	<p>Intersect the E. and W. center line of the SE 1/4 of sec. 12, not monumented.</p>
	<p>From this point, the SE 1/16 sec. cor. of sec. 12 bears S. 89°20' E., 5.93 chs. dist., hereinafter described.</p>
22.74	<p>Cor. 2, Longview lode, monumented with a aplite stone, 22 x 9 x 7 ins., firmly set, projecting 7 ins. above the ground, in a mound of stone, 2 ft. base, 1/2 ft. high, mkd. 2-L 4036A and an X on top, with a mound of stone, 4 ft. base, 3 ft. high, SW of the cor., from which the original bearing objects</p>
	<p>A granite boulder, 5 x 6 x 6 ft. high, bears S. 61° 33' E., 28.77 ft. dist., mkd. X BR.</p>
	<p>A granite bench, projecting 2 ft. above ground, bears S. 4° 45' E., 37.72 ft. dist., mkd. with illegible chisel marks.</p>
	<p>At the cor. point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T1S R13E MS 4036 LV COR 2 S12 1995</p>
	<p>Deposit a magnet in a 1 x 1 x 2 in. white plastic case beneath the stainless steel post.</p>
	<p>Bury the stone alongside the stainless steel post.</p>
	<p>Set an aluminum sign post near the cor.</p>
	<p style="text-align: center;">_____</p> <p>N. 63°41' W., on line 2-3, Longview lode.</p>
9.10	<p>Cor. 3, Longview lode, monumented with a granite stone, 23 x 15 x 9 ins., firmly set, projecting 16 ins. above the ground, mkd. 3-L 4036 and an X on top, with a mound of stone, 4 ft. base, 3 ft. high, NW of the cor.</p>
	<p>At the cor. point</p>

BOOK 5477

Dependent Resurvey of Mineral Survey No. 4036A
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E</p> <p style="text-align: center;">  </p> <p>Deposit a magnet in a 1 x 1 x 2 in. white plastic case beneath the stainless steel post.</p> <p>Bury the stone alongside the stainless steel post, and remove the mound of stone, NW of the cor.</p> <p>Set an aluminum sign post near the cor.</p> <p style="text-align: center;">_____</p> <p>N. 26°18' E., on line 3-4, Longview lode.</p>
1.07	<p>Intersect the E. and W. center line of the SE 1/4 of sec. 12, not monumented.</p> <p>From this point, the center S. 1/16 sec. cor. of sec. 12 bears N. 89°20' W., 4.05 chs. dist., hereinafter described.</p>
22.74	<p>Cor. 4, Longview lode, M.S. 4036A, monumented with a dacite stone, 24 x 14 x 11 ins., firmly set, projecting 12 ins. above the ground, mkd. 4-1 403 A and an X on top, with a mound of stone, 5 ft. base, 3 ft. high, NW of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E</p> <p style="text-align: center;">  </p> <p>Deposit a magnet in a 1 x 1 x 2 in. white plastic case beneath the stainless steel post.</p>

BOOK 5477

Dependent Resurvey of Mineral Survey No. 4036A
 T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Bury the stone alongside the stainless steel post.</p> <p>Set an aluminum sign post near the cor.</p> <p>The cor. is located 95 lks. S. of a fence, bears E. and W.</p> <hr/> <p>S. 63°41' E., on line 4-1, Longview lode.</p>
7.28	<p>Intersect the N. and S. center line of the SE 1/4 of sec. 12, not monumented.</p> <p>From this point, the center E. 1/16 sec. cor. of sec. 12 bears N. 0°20' E., 3.15 chs. dist., hereinafter described.</p>
9.10	<p>Cor. 1, Longview lode, M.S. 4036A.</p> <hr/> <p style="text-align: center;">Subdivision of Section 12 T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 12 and 13.</p> <p>N. 0°16' E., on the N. and S. center line of sec. 12.</p>
19.63	<p>Point for the center S. 1/16 sec. cor. of sec. 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 7 ins. in the ground to bedrock, supported in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T1S R13E</p> <p> C</p> <p>S1/16 S12</p> <p> C</p> <p>1995</p> </div>
39.26	<p>Deposit a magnet in a 1 x 1 x 2 in. white plastic case beneath the stainless steel post.</p> <p>Point for the center 1/4 sec. cor. of sec. 12, at intersection with the E. and W. center line of sec. 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>

BOOK 54 77

Subdivision of Section 12

T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T1S R13E C1/4 S12 1995</p>
	<p>Deposit a magnet in a 1 x 1 x 2 in. white plastic case beneath the stainless steel post.</p> <p>The cor. is located on a steep, NE slope, in dense brush, and 14 lks. N. of a fence, bears E. and W.</p>
79.34	<p>The 1/4 sec. cor. of secs. 1 and 12.</p> <hr/>
	<p>From the 1/4 sec. cor. of sec. 12 only, on the E. bdy. of the Tp. N. 89°04' W., on the E. and W. center line of sec. 12.</p>
20.11	<p>Point for the center E. 1/16 sec. cor. of sec. 12.</p>
	<p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole in granite, cemented in place, with top mkd.</p>
	<p style="text-align: center;">T1S R13E E 1/16 C—C S12 1995</p>
	<p>from which</p>
	<p style="text-align: center;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 1 in. in the ground to bedrock, supported in a mound of stone 4 ft. base, to top, for a reference monument, bears S. 6°21' E., 61.7 ft. dist., with cap mkd. RM T1S R13E 61.7 FT TO COR CE 1/16 S12 1995, and an arrow pointing the cor.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 in. white plastic case beneath the brass tablet.</p>
	<p>The cor. is located in a dirt road, 12 lks. wide, bears SE and NW.</p>
40.22	<p>The center 1/4 sec. cor. of sec. 12</p>
80.41	<p>The 1/4 sec. cor. of secs. 11 and 12, hereinbefore described.</p> <hr/>

BOOK 54 77

Subdivision of Section 12
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">SE 1/4 of Section 12</p> <hr style="width: 20%; margin: auto;"/> <p>From the E. 1/16 sec. cor. of secs. 12 and 13.</p> <p>N. 0°20' E., on the N. and S. center line of the SE 1/4 of sec. 12.</p> <p>4.885 Point for the center S-S-SE 1/256 sec. cor. of sec. 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E S12 C-S-S-SE 1/256 1995</p> <p>from which</p> <p style="padding-left: 40px;">A magnet, 1 in. long, 7/8 ins. diam., buried 8 ins. below ground, bears N. 1° E., 67 lks. dist.</p> <p style="padding-left: 40px;">An oak, 14 ins. diam., bears N. 24 3/4° W., 102 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 in. white plastic case beneath the stainless steel post.</p> <p>Set an aluminum sign post alongside the cor.</p> <p>The cor. is located against the N. side of a stone wall, 3 ft. high, bears E. and W.</p> <p>From this cor. point, a cor. of fences with pipe fence extending N. 6° E., and wire fences extending S. 6° W. and W., bears N. 13° E., 63 lks. dist.</p> <p>From this same cor. point, a cor. of fences with a wire fence extending N. 6° E. and stone fences extending S. 20° W. and W., bears S. 84° E., 14 lks. dist.</p> <p>9.77 Point for the center S-SE 1/64 sec. cor. of sec. 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

BOOK 54 77

Subdivision of Section 12
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T1S R13E S12 C-S-SE 1/64 1995</p> <p>Deposit a magnet in a 1 x 1 x 2 in. white plastic case beneath the stainless steel post.</p> <p>Set an aluminum sign post near the cor.</p> <p>From this cor. point, an iron pin, 3/4 in. diam., firmly set, projecting 1 in. above ground, with no tag, bears N. 42° E., 20 lks. dist., established by U.S. Forest Service personnel in the 1930's, using improper procedures, and is not utilized in the course of this survey.</p> <p>From this same cor. point, a rebar, 5/8 in. diam., with an aluminum cap, 1 1/2 ins. diam., mkd. SUTTON COR. 5 8-63, bears N. 89° E., 15 lks. dist., loosely set on top of a pipe fence cor., 4 ins. diam., 6 ft. high, with cyclone fences extending S. 84° E. and S. 6° W., established for a property cor. by Oscar T. Smith, LS 2648, in 1963, as per a map filed at the office of Evert E. Bunger, LS 14169, in Miami, Arizona, using unknown procedures, and is not utilized in the course of this survey.</p>
19.54	<p>Point for the SE 1/16 sec. cor. of sec. 12, at intersection with the E. and W. center line of the SE 1/4 of sec. 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T1S R13E SE 1/16 S12 1995</p> <p>Deposit a magnet in a 1 x 1 x 2 in. white plastic case beneath the stainless steel post.</p>
31.75	<p>Intersect line 1-2, Longview lode, M.S. 4036A, not monumented.</p> <p>From this point, cor. 1, Longview lode, M.S. 4036A, bears N. 26°18' E., 3.75 chs. dist., hereinbefore described.</p>
35.92	<p>Intersect line 4-1, Longview lode, M.S. 4036A, not monumented.</p>

BOOK 54 77

Subdivision of Section 12

T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From this point, cor. 1, Longview lode, M.S. 4036A, bears S. 63°41' E., 1.82 chs. dist., hereinbefore described.
39.07	The center E. 1/16 sec. cor. of sec. 12.
	From the true point for the S. 1/16 sec. cor. of sec. 12 only, on the E. bdy. of the Tp.
	N. 89°20' W., on the E. and W. center line of the SE 1/4 of sec. 12.
20.08	The SE 1/16 sec. cor. of sec. 12, at intersection with the N. and S. center line of the SE 1/4 of sec. 12, hereinbefore described.
26.01	Intersect line 1-2, Longview lode, M.S. 4036A, not monumented.
	From this cor. point, cor. 2, Longview lode, M.S. 4036A, bears S. 26°18' W., 5.44 chs. dist., hereinbefore described.
36.11	Intersect line 3-4, Longview lode, M.S. 4036A, not monumented.
	From this cor. point, cor. 3, Longview lode, M.S. 4036A, bears S. 26°18' W., 1.07 chs. dist., hereinbefore described.
40.16	The center S. 1/16 sec. cor. of sec. 12, hereinbefore described.
	From the N-S-S 1/256 sec. cor. of sec. 12 only, on the E. bdy. of the Tp.
	N. 89°24' W., on the E. and W. center line of the NE 1/4 of the SE 1/4 of the SE 1/4 of section 12, along a fence.
10.035	Point for the center N-SE-SE 1/256 sec. cor. of sec. 12, not monumented.
	N. 89°24' W., on a portion of the E. and W. center line of the NW 1/4 of the SE 1/4 of the SE 1/4 of section 12, along a fence.
5.015	Point for the NW-SE-SE 1/256 sec. cor. of sec. 12.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, cemented in place, in granite, with top mkd.

BOOK 5477

Subdivision of Section 12

T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T1S R13E S12 NW-SE-SE 1/256 1995</p> <p>Deposit a magnet in a 1 x 1 x 2 in. white plastic case beneath the brass tablet.</p> <p>Set an aluminum sign post near the cor.</p> <p>From this cor. point, a rebar, 5/8 in. diam., firmly set, projecting 9 ins. above ground, with an aluminum cap mkd. SUTTON COR. 7 8-63, bears N. 82° E., 12 lks. dist., located alongside a fence cor. with iron mesh fences extending E. and S., and 4 lks. S. of a power pole, 10 ins. diam., lines extend E. and S., established for a property cor. by Oscar T. Smith, LS 2648, in 1963, as per a map filed at the office of Evert E. Bunger, LS 14169, in Miami, Arizona, using unknown procedures, and is not utilized in the course of this survey.</p>
4.88	<p>S. 0°21' W., on a portion of the N. and S. center line of the NW 1/4 of the SE 1/4 of the SE 1/4 of sec. 12, along a fence.</p> <p>Point for the center W-SE-SE 1/256 sec. cor. of sec. 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E S12 C-W-SE-SE 1/256 1995</p> <p>Deposit a magnet in a 1 x 1 x 2 in. white plastic case beneath the stainless steel post.</p> <p>Set an aluminum sign post near the cor.</p> <p>From this cor. point, a rebar, 5/8 in. diam., firmly set, inside a steel cylinder, 12 ins. diam., projecting 3 ft. above the ground, with an aluminum cap, 1 1/2 ins. diam., mkd. SUTTON COR. 6 8-3, bears N. 82° E., 11.5 lks. dist, located in a fence cor. with an iron mesh fence extending N. and a cyclone fence extending W., established for a property cor. by Oscar T. Smith, LS 2648, in 1963, as per a map filed at the office of Evert E. Bunger, LS 14169, in Miami, Arizona, using unknown procedures, and is not utilized in the course of this survey.</p>

BOOK 5477

Subdivision of Section 12

T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
5.02	<p>N. 89°28' W., on a portion of the E. and W. center line of the SE 1/4 of the SE 1/4 of sec. 12, along a fence.</p> <p>The center S-SE 1/64 sec. cor. of sec. 12.</p> <hr/>
5.01	<p>From the center S-S-SE 1/256 sec. cor. of sec. 12.</p> <p>N. 89°32' W., on a portion of the E. and W. center line of the SE 1/4 of the SW 1/4 of the SE 1/4 of sec. 12.</p> <p>Through the back yard area of a trailer park; there are several travel trailers and storage sheds on line along this course.</p> <p>Point for the SE-SW-SE 1/256 sec. cor. of sec. 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E S12 SE-SW-SE 1/256 1995</p> <p>Deposit a magnet in a 1 x 1 x 2 in. white plastic case beneath the stainless steel post.</p> <p>Set an aluminum sign post near the cor.</p> <p>The cor. is located on the S. edge of a dirt road, bears ENE and NW, under a power line bears ENE and WSW, and 1 ch. S. of a corral.</p> <p>From this cor. point, an iron pin, 3/4 in. diam., firmly set, projecting 2 ins. above ground, with no tag bears N. 73° E., 17 lks. dist., located alongside a cor. of fences, with hog wire fences extending E. and S. 8° W. established by U.S. Forest Service personnel in the 1930's, using improper procedures, and is not utilized in the course of this survey.</p> <hr/>
4.89	<p>S. 0°19' W., on a portion of the N. and S. center line of the SE 1/4 of the SW 1/4 of the SE 1/4 of sec. 12, along a fence.</p> <p>The E-W-E 1/256 sec. cor. of secs. 12 and 13.</p> <hr/>

BOOK 5477

Subdivision of Section 13

T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 13 and 24.</p> <p>N. 0°05' E., on the N. and S. center line of sec. 13.</p> <p>Over rolling land, through medium juniper and oak.</p> <p>19.98 The center S. 1/16 sec. cor. of secs. 13, determined by Travis L. Gant, LS 5703, monumented with a 6 sided iron pipe, 1 in. diam., firmly set, projecting 3 ins. above ground, with a tag mkd. LS 5703. This is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E C S 1/16 S13 C 1994</p> <p>from which</p> <p style="text-align: center;">A juniper, 22 ins. diam., bears S. 69 1/4° E., 45 lks. dist., mkd. CS 1/16 S13 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. is located in a barbed wire fence, 5 strand, bears E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 05' E., beginning new measurement.</p>
19.98	<p>Point for the center 1/4 sec. cor. of sec. 13, at intersection with the E. and W. center line of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E C 1/4 S13 1994</p>

BOOK 54 77

Subdivision of Section 13

T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. is located in a dense willow grove.</p>
39.97	<p>Point for the center N. 1/16 sec. cor. of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T1S R13E C N 1/16 S13 C 1994</p> </div>
44.50	<p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. is located 9 lks. S. of the southerly right-of-way fence for U.S. Highway 60, barbed wire, 4 strand, bears NE and SW.</p>
59.96	<p>Center of U.S. Highway 60, bears NE and SW.</p> <p>The 1/4 sec. cor. of secs. 12 and 13.</p>
15.165	<hr/> <p>From the 1/4 sec. cor. of sec. 13 only, on the E. bdy. of the Tp. N. 89°40' W., on the E. and W. centerline of sec. 13.</p> <p>Over rolling land, through medium juniper and oak.</p>
	<p>Point for the center W-E-E 1/256 sec. cor. of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T1S R13E S13 C-W-E-E 1/256 1994</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. is located 32 lks. WNW of a cor. of fences extending N., S., and SW, and 55 lks. W. of a paved road, bears N. and S.</p>

BOOK 54 77

Subdivision of Section 13
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.22	<p>Point for the center E. 1/16 sec. cor. of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E E1/16 C———C S13 1994</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. is located 12 lks. E. of a barbed wire fence, 4 strand, bears N. and S., and on the W. edge of a pasture.</p>
40.44	The center 1/4 sec. cor. of sec. 13.
58.00	Center of U.S. Highway 60, bears NE and SW.
60.52	<p>Point for the center W. 1/16 sec. cor. of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 3 ins. in the ground to bedrock, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E W1/16 C———C S13 1994</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. is located 1 lk. N. of a wood post, 4 x 4 ins., in a mound of stone, and on a rocky SSW facing slope.</p>
80.60	<p>The 1/4 sec. cor. of secs. 13 and 14.</p> <hr/> <p style="text-align: center;">NE 1/4 of Section 13</p> <hr/> <p>From the center E. 1/16 sec. cor. of sec. 13.</p> <p>N. 0°09' W., on the N. and S. center line of the NE 1/4 of sec. 13.</p>

BOOK 5477

Subdivision of Section 13

T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
4.99	<p>Over rolling land, through medium juniper and oak.</p> <p>Point for the center S-S-NE 1/256 sec. cor. of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E S13 C-S-S-NE 1/256 1994</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. is located in a barbed wire fence, 4 strand, bears N. and S.</p>
19.975	<p>Point for the NE 1/16 sec. cor. of sec. 13, at intersection with the E. and W. center line of the NE 1/4 of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E NE 1/16 S13 1994</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. is located 8 lks. W. of a pig wire fence, bears N. and S.</p>
34.96	<p>Point for the center N-N-NE 1/256 sec. cor. of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E S13 C-N-N-NE 1/256 1994</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p>

BOOK 54 77

Subdivision of Section 13

T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>The cor. is located on the N. edge of a driveway, bears NE and SW.</p> <p>From this cor. point, an iron pipe, 1 in. diam., firmly set, projecting 3 ins. above the ground, bears S. 85° E., 17 lks. dist.</p> <p>From this same cor. point, a cor. of fences, extending N., E. and SW, bears S. 24° E., 24 lks. dist.</p>
39.95	<p>The E. 1/16 sec. cor. of secs. 12 and 13.</p> <hr/>
20.14	<p>From the true point for the N. 1/16 sec. cor. of sec. 13 only, on the E. bdy. of the Tp.</p> <p>N. 89°38' W., on the E. and W. centerline of the NE 1/4 of sec. 13.</p> <p>Over rolling land, through medium juniper and oak.</p>
40.28	<p>The NE 1/16 sec. cor. of sec. 13.</p> <p>The center N. 1/16 sec. cor. of sec. 13.</p> <hr/>
10.04	<p>From the N-N-N 1/256 sec. cor. of sec. 13 only, on the E. bdy. of the Tp.</p> <p>N. 89°36' W., on the E. and W. centerline of the NE 1/4 of the NE 1/4 of the NE 1/4 of sec. 13.</p> <p>Over rolling land, through medium juniper and oak.</p>
	<p>Point for the center N-NE-NE 1/256 sec. cor. of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E S13 C-N-NE-NE 1/256 1994</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <hr/> <p>N. 89°36' W., on the E. and W. centerline of the NW 1/4 of the NE 1/4 of the NE 1/4 of sec. 13.</p>

BOOK 54 77

Subdivision of Section 13

T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
10.04	<p>Over rolling land, through medium juniper and oak.</p> <p>The center N-N-NE 1/256 sec. cor. of sec. 13.</p> <hr/>
4.99	<p>From the center W-E-E 1/256 sec. cor. of sec. 13.</p> <p>N. 0°12.5' W., on a portion of the N. and S. centerline of the SW 1/4 of the SE 1/4 of the NE 1/4 of sec. 13.</p> <p>Over rolling land, through medium juniper and oak.</p> <p>Point for the SW-SE-NE 1/256 sec. cor. of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E S13 SW-SE-NE 1/256 1994</p> <p>from which</p> <p style="text-align: center;">A granite boulder, 20 ft. x 6 ft. x 4 ft., bears N 45° E., 12 lks. dist., mkd. X B0 on the SW face.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. is located on a steep W. facing slope and 46 lks. E. of a paved road bears N. and S.</p> <hr/>
5.05	<p>N. 89°40' W., on a portion of the E. and W. centerline of the SW 1/4 of the SE 1/4 of the NE 1/4 of sec. 13.</p> <p>Over rolling land, through medium juniper and oak.</p> <p>The center S-S-NE 1/256 sec. cor. of sec. 13.</p> <hr/>
	<p style="text-align: center;">SE 1/4 of Section 13</p> <hr/> <p>From the E. 1/16 sec. cor. of secs. 13 and 24.</p> <p>N. 0°22' E., on the N. and S. centerline of the SE 1/4 of sec. 13.</p> <p>Over rolling land, through medium juniper and oak.</p>

BOOK 5477

Subdivision of Section 13

T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
19.98	<p>The SE 1/16 sec. cor. of secs. 13, determined by Travis L. Gant, LS 5703, monumented with a 6 sided iron pipe, 1 in. diam., firmly set, projecting 4 ins. above ground, with a tag mkd. LS 5703. This is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E</p> <p style="text-align: center;">SE 1/16 S13</p> <p style="text-align: center;">1994</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>Deposit the iron pipe inside the stainless steel post.</p> <p>The cor. is located 1 lk. N. of a cor. of barbed wire fences, 5 strand, extending N. and W.</p> <p>From this cor. point, a iron pipe, 1 in. diam., firmly set, projecting 3 ins. above the ground, with tag mkd. PE 1682, bears N. 80°28' E., 6 lks. dist. Established using improper procedures and is not utilized in the course of this resurvey.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 22' E., beginning new measurement.</p>
4.995	<p>Point for the center S-N-SE 1/256 sec. cor. of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E</p> <p style="text-align: center;">S13</p> <p style="text-align: center;">C-S-N-SE 1/256</p> <p style="text-align: center;">1994</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, a cor. of fences extending N. and E., bears S. 6° W., 73 lks. dist.</p>

BOOK 54 77

Subdivision of Section 13

T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From this same cor., a cor. of fences extending E., W. and S., bears S. 3 1/2° E., 74 lks. dist.
19.98	The center E. 1/16 sec. cor. of sec. 13. <hr/>
	From the S. 1/16 sec. cor. of sec. 13 only, on the E. bdy. of the Tp.
	N. 89°40' W., on the E. and W. centerline of the SE 1/4 of sec. 13.
	Over rolling land, through medium juniper and oak.
20.12	The SE 1/16 sec. cor. of secs. 13. <hr/>
	N. 89° 40' W., beginning new measurement.
20.12	The center S. 1/16 sec. cor. of secs. 13. <hr/>
	From the center S-N-SE 1/256 sec. cor. of sec. 13.
	S. 89°40' E., on the E. and W. centerline of the SW 1/4 of the NE 1/4 of the SE 1/4 of sec. 13.
	Over rolling land, through medium juniper and oak.
10.07	Point for the center S-NE-SE 1/256 sec. cor. of sec. 13.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled with a collar of stone, with brass cap mkd.
	T1S R13E S13 C-S-NE-SE 1/256 1994
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	The cor. is located 14 lks. W. of a trail road, bears N. and SW. <hr/>
	N. 0°31' E., on a portion of the N. and S. centerline of the NE 1/4 of the SE 1/4 of sec. 13.
	Over rolling land, through medium juniper and oak.

BOOK 54 77

Subdivision of Section 13
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
9.99	<p>Point for the center N-NE-SE 1/256 sec. cor. of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E C-N-NE-SE 1/256 S13 1994</p> <p>from which</p> <p style="text-align: center;">A granite boulder, 30 ft. x 15 ft. x 10 ft., bears N 43° E., 31 1/2 lks. dist., mkd. X BO on the SW face.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. is located in a small wash drains WSW.</p> <hr/> <p>N. 89°40' W., on a portion of the E. and W. centerline of the NW 1/4 of the NE 1/4 of the SE 1/4 of sec. 13.</p> <p>Over rolling land, through medium juniper and oak.</p>
5.05	<p>Point for the NW-NE-SE 1/256 sec. cor. of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 36 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E S13 NW-NE-SE 1/256 1994</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. is located in a corral.</p> <hr/> <p>N. 0°26.5' E., on a portion of the N. and S. centerline of the NW 1/4 of the NE 1/4 of the SE 1/4 of sec. 13.</p> <p>Over rolling land, through medium juniper and oak.</p>
4.995	<p>The center W-E-E 1/256 sec. cor. of sec. 13.</p> <hr/>

BOOK 5477

Subdivision of Section 13

T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">SW 1/4 of Section 13</p> <hr/> <p>From the W. 1/16 sec. cor. of secs. 13 and 24.</p> <p>N. 0°03' E., on the N. and S. centerline of the SW 1/4 of sec. 13.</p> <p>Over rolling land, through medium juniper and oak.</p> <p>19.96 The SW 1/16 sec. cor. of sec. 13, determined by Travis L. Gant, LS 5703, monumented with a 6 sided iron pipe, 1 in. diam., firmly set, projecting 3 ins. above ground, with a tag mkd. LS 5703. This is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T1S R13E</p> <p style="text-align: center;">SW1/16 S13</p> <p style="text-align: center;">1994</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, an iron pipe, 1 in. diam., firmly set, projecting 3 ins. above the ground, with tag mkd. PE 1682, bears S. 39° E., 12 lks. dist.</p> <p>The cor. is located 1 lk. S. of a cor. of fences extending N., E., and S.</p> <hr/> <p>N. 0° 03' E., beginning new measurement.</p>
19.96	<p>The center W. 1/16 sec. cor. of sec. 13.</p> <hr/> <p>From the center S. 1/16 sec. cor. of sec. 13.</p> <p>N. 89°38' W., on the E. and W. centerline of the SW 1/4 of sec. 13.</p> <p>Over rolling land, through medium juniper and oak.</p>

BOOK 54 77

Subdivision of Section 13
T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.08	The SW 1/16 sec. cor. of sec. 13.
	<hr/> N. 89° 38' W., beginning new measurement.
20.08	The S. 1/16 sec. cor. of secs. 13 and 14.
	<hr/> <p style="text-align: center;">Subdivision of Section 14 T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona</p> <hr/>
	From the 1/4 sec. cor. of secs. 14 and 23.
	N. 0°10' E., on the N. and S. center line of sec. 14.
39.94	Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E. and W. center line of sec. 14.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, cemented in place, with top mkd.
	T1S R13E
	C1/4 S14
	1995
59.94	Point for the center N. 1/16 sec. cor. of sec. 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, supported in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.
	T1S R13E
	C
	N1/16 S14
	C
	1995
	Deposit a magnet in a 1 x 1 x 2 in. white plastic case beneath the stainless steel post.
	Set an aluminum sign post near the cor.
79.94	The 1/4 sec. cor. of secs. 11 and 14.
	<hr/> From the 1/4 sec. cor. of secs. 13 and 14.

BOOK 5477

Subdivision of Section 14

T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 89°43' W., on the E. and W. center line of sec. 14.
20.07	Point for the center E. 1/16 sec. cor. of sec. 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T1S R13E E 1/16 C ————— C S14 1995</p>
	Deposit a magnet in a 1 x 1 x 2 in. white plastic case beneath the stainless steel post.
40.14	The center 1/4 sec. cor. of sec. 14.
79.93	The 1/4 sec. cor. of secs. 14 and 15.
	<p style="text-align: center;">NE 1/4 of Section 14</p> <hr style="width: 20%; margin: auto;"/>
	From the center E. 1/16 sec. cor. of sec. 14.
	N. 0°10' E., on the N. and S. center line of the NE 1/4 of sec. 14.
20.01	Point for the NE 1/16 sec. cor of sec. 14, at intersection with the E. and W. center line of sec. 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T1S R13E NE 1/16 S14 1995</p>
	Deposit a magnet in a 1 x 1 x 2 in. white plastic case beneath the stainless steel post.
	Set an aluminum sign post near the cor.
	The cor. is located on the W. side of a knoll.
40.02	The E. 1/16 sec. cor. of secs. 11 and 14.

BOOK 54 77

Subdivision of Section 14

T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the N. 1/16 sec. cor. of secs. 13 and 14.
	N. 89°43' W., on the E. and W. center line of the NE 1/4 of sec. 14.
20.07	The NE 1/16 sec. cor. of sec. 14.
40.14	The center N. 1/16 sec. cor. of sec. 14.
<hr/> Subdivision of Section 23 T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona <hr/>	
	From the 1/4 sec. cor. of secs. 23 and 26.
	N. 0°01' E., on the N. and S. center line of sec. 23.
40.55	Point for the center 1/4 sec. cor. of sec. 23, at intersection with the E. and W. center line of sec. 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, supported in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.
	T1S R13E
	C1/4 S23
	1995
	Deposit a magnet in a 1 x 1 x 2 in. white plastic case beneath the stainless steel post.
60.79	Point for the center N. 1/16 sec. cor. of sec. 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T1S R13E
	C
	N1/16 S23
	C
	1995
	from which
	An alligator juniper, 9 ins. diam., bears S. 55 1/4° W., 32 lks. dist., mkd. CN1/16S23BT.

BOOK 5477

Subdivision of Section 23

T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet in a 1 x 1 x 2 in. white plastic case beneath the stainless steel post.
	Set an aluminum sign post near the cor.
81.03	The 1/4 sec. cor. of secs. 14 and 23.
	From the 1/4 sec. cor. of secs. 23 and 24.
	N. 89°25' W., on the E. and W. center line of sec. 23.
40.21	The center 1/4 sec. cor. of sec. 23.
79.80	The 1/4 sec. cor. of secs. 22 and 23.
	NE 1/4 of Section 23
	From the N. 1/16 sec. cor. of secs. 23 and 24.
	N. 89°35' W., on the E. and W. center line of the NE 1/4 of sec. 23.
40.20	The center N. 1/16 sec. cor. of sec. 23.
	GENERAL DESCRIPTION
	The area surveyed is located approximately 8 miles east of Superior, Arizona. The elevation ranges from 4500 to 5000 feet above sea level.
	Access is provided by U.S. Highway 60, various Forest Service, mining, and power line access roads.
	Moderate mineral activity was noted on the Federal interest lands of the survey area.
	The soil is a rocky loam. The vegetation consists of pine, juniper, oak, manzanita, catclaw, yucca and cacti.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Stephen K. Hansen	Land Surveyor
Daniel R. Muth	Land Surveyor (Trainee)
Cheryl A. Baier	Surveying Technician
Gordon R. Bube1	Surveying Technician
Jeffry A. Hill	Surveying Technician
Wallace R. Ott Jr.	Surveying Technician
Mark R. Searles	Surveying Technician

CERTIFICATE OF SURVEY

We, William P. Carpender and Clyde J. King, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 4th day of April, 1994, we have dependently resurveyed a portion of the east boundary, a portion of the subdivisional lines and Mineral Survey No. 4036A, and subdivided sections 12, 13, 14, and 23, Township 1 South, Range 13 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

JANUARY 15, 1997
(Date)

William P. Carpender
(Cadastral Surveyor)

1-16-97
(Date)

Clyde J. King
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the east boundary, a portion of the subdivisional lines and Mineral Survey No. 4036A, and the subdivision of sections 12, 13, 14, and 23, of Township 1 South, Range 13 East, Gila and Salt River Meridian, Arizona, executed by William P. Carpender and Clyde J. King, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

1/16/97
(Date)

Dale C. Wilson
(Acting Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 1 S., R. 13 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____~~
~~(Date)~~

~~_____~~
~~(Acting Chief Cadastral Surveyor of Arizona)~~