

BOOK 5483

1

ORIGINAL

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE

DEPENDENT RESURVEY

OF THE SOUTH, EAST AND WEST BOUNDARIES

AND A PORTION OF THE SUBDIVISIONAL LINES,

AND A METES-AND-BOUNDS SURVEY IN SECTION 30,

TOWNSHIP 20 NORTH, RANGE 30 EAST,

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY

Joe R. Salazar, Cadastral Surveyor

Gary D. Knoff, Cadastral Surveyor

Under Special Instructions dated January 12, 1987, approved February 23, 1987, and Supplemental Special Instructions dated February 29, 1988, approved February 29, 1988, which provided for the surveys included under Group Number 687 and assignment instructions dated August 1, 1989, and February 16, 1993.

Survey commenced October 30, 1991

Survey completed July 28, 1994

INDEX DIAGRAM

TOWNSHIP 20 NORTH, RANGE 30 EAST,

19	6	5	4	3	2	1	11
18	7	8	9	10	11	12	11
17	18	17	16	15	14	13	11
15	19	20	21	22	23	24	11
	24						
14	30	22	29	28	27	26	10
	22						
13	31	21	32	33	34	35	10
	9	8	7	6	5	4	

T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of the south, east and west boundaries and a portion of the subdivisional lines, and a metes and bounds survey in section 30, Township 20 North, Range 30 East, Gila and Salt River Meridian, Arizona.

W. R. Fitzgerald surveyed the 5th. Standard Parallel North, the south, east, west boundaries, and the subdivisional lines in 1882. Ty White dependently resurveyed the 5th Standard Parallel North in 1947. Stephen J. Malloy dependently resurveyed the 5th Standard Parallel North in 1987-93. The cor. of Tps. 17 and 18 N., Rs. 30 and 31 E. was remonumented during the dependent resurvey of the south boundary of T. 18 N., R. 30 E. by William P. Carpender, in 1988-93. The closing cor. of Tps. 19 and 20 N., R. 31 E. was reestablished during the dependent resurvey of the Arizona-New Mexico State Line by Joe R. Salazar and Gary D. Knoff, in 1989-93.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated January 12, 1987, and Supplemental Special Instructions dated February 29, 1988, for Group No. 687, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of all lines were determined by direct hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured with a Pentax PTS-III, total station instrument.

The geographic position of the closing cor. of Tps. 20 N., Rs. 30 and 31 E., was determined by the technique of static differential positioning using Ashtech models M-XII and MS-XII geodetic units. U.S. Coast and Geodetic Survey triangulation stations "BEACON 54 B ECC 1936" and "DEAD 1936" were used as the control stations.

Latitude: 35°10'01.64" N. Longitude: 109°06'13.89" W. NAD27

The mean magnetic declination, as taken from the quadrangle map TOLAPAI SPRING, ARIZ., published in 1971 by U.S. Geological Survey, is 13 1/2° E.

Dependent Resurvey of the South Boundary,
T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS	<p style="text-align: center;">Restoring the survey executed by W. R. Fitzgerald in 1882</p> <hr style="width: 20%; margin: auto;"/> <p>Beginning at the cor. of Tps. 19 and 20 N., Rs. 30 and 31 E., at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T20N</td></tr> <tr><td>R30E</td><td>R31E</td></tr> <tr><td>S36</td><td>S31</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td colspan="2">T19N</td></tr> <tr><td colspan="2">1993</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>From this cor. point, the cor. of Tps. 17 and 18 N., Rs. 30 and 31 E., monumented with a stainless steel post, firmly set, projecting 4 ins. above ground, with brass cap mkd., T18N R30E R31E S36 S31 S1 S6 T17N 1993, bears S. 0°25' W., 958.16 chs. dist.</p> <p>From this same cor. point, the closing cor. of Tps. 19 and 20 N., R. 31 E., at intersection with the Arizona-New Mexico state line, monumented with a stainless steel post 2 1/2 ins. diam. firmly set, projecting 4 ins. above the ground, with brass cap mkd., T20N R31E S34 S3 T19N 1993, bears S. 89°01' E., 255.54 chs. dist.</p> <p>N. 82°58' W., bet. secs. 1 and 36, on the S. bdy. of the Tp.</p> <p>Over broken terrain.</p> <p>39.55 Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td>T20N</td><td>R30E</td></tr> <tr><td></td><td>S36</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S 1</td></tr> <tr><td></td><td>T19N</td></tr> <tr><td></td><td>1994</td></tr> </table> </div>	T20N		R30E	R31E	S36	S31			S 1	S 6	T19N		1993		T20N	R30E		S36	1/4	—		S 1		T19N		1994
T20N																											
R30E	R31E																										
S36	S31																										
S 1	S 6																										
T19N																											
1993																											
T20N	R30E																										
	S36																										
1/4	—																										
	S 1																										
	T19N																										
	1994																										

Dependent Resurvey of the South Boundary,
T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS															
79.10	<p>from which</p> <p>A pine, 12 ins. diam., bears N. 4 1/4° E., 28 lks. dist., mkd. T20N R30E S36 BT.</p> <p>A cedar, 30 ins. diam., bears S. 25 3/4° E., 108 lks. dist., mkd. T19N R30E S1 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 1, 2, 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T20N</td><td>R30E</td></tr> <tr><td>S35</td><td>S36</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td colspan="2" style="text-align: center;">T19N</td></tr> <tr><td colspan="2" style="text-align: center;">1994</td></tr> </table> <p>from which</p> <p>A pine, 10 ins. diam., bears N. 1° E., 26.5 lks. dist., mkd. T20N R30E S36 BT.</p> <p>A pine, 10 ins. diam., bears S. 88° E., 54.5 lks. dist., mkd. T19N R30E S1 BT.</p> <p>A pine, 8 ins. diam., bears S. 73 1/2° W., 42 lks. dist., mkd. T19N R30E S2 BT.</p> <p>A pine, 18 ins. diam., bears N. 48 3/4° W., 60.5 lks. dist., mkd. T20N R30E S35 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>	T20N	R30E	S35	S36			S 2	S 1			T19N		1994	
T20N	R30E														
S35	S36														
S 2	S 1														
T19N															
1994															
39.55	<p>N. 82°58' W., bet. secs. 2 and 35, on the S. bdy. of the Tp.</p> <p>Over broken terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>														

Dependent Resurvey of the South Boundary,
T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T20N R30E S35 1/4 — S 2 T19N 1994</p> <p>from which</p> <p style="margin-left: 40px;">A pine, 12 ins. diam., bears S. 51° W., 93.5 lks. dist., mkd. 1/4 S2 BT.</p> <p style="margin-left: 40px;">A pine, 10 ins. diam., bears N. 68° W., 42.5 lks. dist., mkd. 1/4 S35 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
79.10	<p>The cor. of secs. 2, 3, 34 and 35, monumented with a wooden post, 3 ins. square, 31 ins. long lying loose on the ground, plainly mkd. with 2 notches on one side, IA and 4 notches on another side and IA on another. This is accepted as the best available evidence of the original cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R30E S34 S35 — — S 3 S 2 T19N 1993</p> <p>Bury the wooden post alongside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>The cor. is located 10 lks. N. of a fence, bears E. and W.</p>
39.96	<hr/> <p>N. 89°59' W., bet. secs. 3 and 34, on the S. bdy. of the Tp.</p> <p>Over broken terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p>

BOOK 54 83

Dependent Resurvey of the South Boundary,
T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R30E S34 1/4 — S 3 T19N 1994</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 18 ins. diam., bears N. 78 1/4° E., 52.5 lks. dist., mkd. 1/4 S34 BT.</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. 73 1/2° W., 80.5 lks. dist., mkd. 1/4 S4 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
79.92	<p>The cor. of secs. 3, 4, 33 and 34, monumented with a wooden post, 33 ins. long, firmly set, 20 ins. in the ground, mkd. with 3 grooves on the E., and 3 grooves and IA on the W. sides. This is accepted as the best available evidence of the position of the original cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R30E S33 S34 —+— S 4 S 3 T19N 1994</p> <p>Bury the wooden post alongside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
40.17	<p>S. 89°59' W., bet. secs. 4 and 33, on the S. bdy. of the Tp.</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p>

BOOK 5483

Dependent Resurvey of the South Boundary,
T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R30E S33 1/4 — S 4 T19N 1994</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>The cor. is located 11 lks. N. of a fence, bears E. and W.</p>
80.34	<p>Point for the cor. of secs. 4, 5, 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R30E S32 S33 — — S 5 S 4 T19N 1994</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>The cor. is located 11 lks. N. of fence, bears E. and W.</p>
40.17	<p>S. 89°59' W., bet. secs. 5 and 32, on the S. bdy. of the Tp.</p> <p>Over broken terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R30E S32 1/4 — S 5 T19N 1994</p>

BOOK 54 83

Dependent Resurvey of the South Boundary,
T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS													
80.34	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>The cor. is located 14 lks. S. of a fence, bears E. and W.</p> <p>Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T20N</td><td>R30E</td></tr> <tr><td>S31</td><td>S32</td></tr> <tr><td colspan="2">— —</td></tr> <tr><td>S 6</td><td>S 5</td></tr> <tr><td colspan="2">T19N</td></tr> <tr><td colspan="2">1994</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>The cor. is located 5 lks. S. of a fence, bears E. and W.</p>	T20N	R30E	S31	S32	— —		S 6	S 5	T19N		1994	
T20N	R30E												
S31	S32												
— —													
S 6	S 5												
T19N													
1994													
40.17	<p>S. 89°59' W., bet. secs. 6 and 31, on the S. bdy. of the Tp.</p> <p>Over broken terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T20N</td><td>R30E</td></tr> <tr><td colspan="2">S31</td></tr> <tr><td colspan="2">1/4 —</td></tr> <tr><td colspan="2">S 6</td></tr> <tr><td colspan="2">T19N</td></tr> <tr><td colspan="2">1994</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>The cor. is located 7 lks. N. of a fence, bears E. and W.</p>	T20N	R30E	S31		1/4 —		S 6		T19N		1994	
T20N	R30E												
S31													
1/4 —													
S 6													
T19N													
1994													
78.53	<p>The cor. of Tps. 19 and 20 N., Rs. 29 and 30 E., monumented with a corner of fences, extending N. and E. This is accepted as the best available evidence of the position of the original cor.</p> <p>At the cor. point</p>												

Dependent Resurvey of the South Boundary,
T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T20N</td></tr> <tr><td>R29E</td><td>R30E</td></tr> <tr><td>S36</td><td>S31</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td colspan="2">T19N</td></tr> <tr><td colspan="2">1994</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p style="text-align: center;">Dependent Resurvey of the East Boundary, T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p style="text-align: center;">Restoring the survey executed by W. R. Fitzgerald in 1882</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of Tps. 19 and 20 N., Rs. 30 and 31 E., hereinbefore described.</p> <p>N. 1°12' W., bet. secs. 31 and 36, on the E. bdy. of the Tp.</p> <p>Over broken terrain.</p> <p>36.00 Ridge, bears E. and W.</p> <p>39.93 Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the original cor., point not monumented.</p> <p>44.00 Dirt road, bears ESE. and WNW.</p> <p>77.90 Dirt road, bears NE. and SW.</p> <p>79.86 Point for the cor. of secs. 25, 30, 31 and 36, at proportionate dist.; there is no remaining evidence of the original cor., point not monumented.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>N. 1°12' W., bet. secs. 25 and 30, on the E. bdy. of the Tp.</p> <p>Over broken terrain, through dense piñon and juniper.</p>	T20N		R29E	R30E	S36	S31			S 1	S 6	T19N		1994	
T20N															
R29E	R30E														
S36	S31														
S 1	S 6														
T19N															
1994															

BOOK 5483

Dependent Resurvey of the East Boundary,
T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.93	Point for the 1/4 sec. cor. of secs. 25 and 30, at proportionate dist.; there is no remaining evidence of the original cor., point not monumented.
79.86	Point for the cor. of secs. 19, 24, 25 and 30, at proportionate dist.; there is no remaining evidence of the original cor., point not monumented.
<hr/>	
N. 1°12' W., bet. secs. 19 and 24, on the E. bdy. of the Tp.	
Over broken terrain.	
39.93	Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate dist.; there is no remaining evidence of the original cor., point not monumented.
79.86	Point for the cor. of secs. 13, 18, 19 and 24, at proportionate dist.; there is no remaining evidence of the original cor., point not monumented.
<hr/>	
N. 1°12' W., bet. secs. 13 and 18, on the E. bdy. of the Tp.	
Over broken terrain.	
39.93	Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate dist.; there is no remaining evidence of the original cor., point not monumented.
79.86	Point for the cor. of secs. 7, 12, 13 and 18, at proportionate dist.; there is no remaining evidence of the original cor., point not monumented.
<hr/>	
N. 1°12' W., bet. secs. 7 and 12, on the E. bdy. of the Tp.	
Over broken terrain.	
39.93	Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate dist.; there is no remaining evidence of the original cor., point not monumented.
79.86	Point for the cor. of secs. 1, 6, 7 and 12, at proportionate dist.; there is no remaining evidence of the original cor., point not monumented.
<hr/>	
N. 1°12' W., bet. secs. 1 and 6, on the E. bdy. of the Tp.	
Over broken terrain.	

BOOK 54 83

Dependent Resurvey of the East Boundary,
T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.93	<p>Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate dist.; there is no remaining evidence of the original cor., point not monumented.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R30E R31E 1/4 S 1 S 6 1993</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
82.66	<p>Point for the closing cor. of Tps. 20 N., Rs. 30 and 31 E., at proportionate dist. on the Fifth Stan. Parallel North; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S36 T21N R30E ----- S 1 S 6 R30E R31E T20N CC 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 5 ins. diam., bears S. 55 1/2° E., 462 lks. dist., mkd. T20N R31E S6 CC BT.</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears S. 33 3/4° W., 199 lks. dist., mkd. T20N R30E S1 CC BT.</p> <p>From this cor. point, the stan. cor. of T. 21 N., Rs. 30 and 31 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd., SC T21N R30E R31E S36 S31 1947 1993, bears S. 89°24' E., 10.31 chs. dist., from which the 1947 bearing tree</p> <p style="padding-left: 40px;">A juniper, 5 ins. diam., bears N. 55 3/4° E., 19 lks. dist., mkd. BT on a nearly healed blaze.</p>

BOOK 5483

Dependent Resurvey of the East Boundary,
T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 21 N., R. 30 E., monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. SC 1/4 S36 1947 1993, bears N. 89°24' W., 30.33 chs. dist., from which the 1947 bearing trees</p> <p>A juniper, 32 ins. diam., bears N. 75° E., 52 lks. dist., mkd. 1/4S36SCBT.</p> <p>A juniper, 22 ins. diam., bears N. 22° W., 89 lks. dist., mkd. 1/4S36SCBT.</p>
	<p>Dependent Resurvey of the West Boundary, T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona</p>
	<p>Restoring the survey executed by W. R. Fitzgerald in 1882</p>
	<p>From the cor. of Tps. 19 and 20 N., Rs. 29 and 30 E., hereinbefore described.</p> <p>N. 13°21' W., bet. secs. 31 and 36, on the W. bdy. of the Tp.</p> <p>Over broken terrain.</p>
32.78	<p>Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R29E R30E 1/4 S36 S31 1994</p>
65.56	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 25, 30, 31 and 36, monumented with a wooden post, 4 ins. sq., 43 ins. long, firmly set, 25 ins. in the ground, plainly mkd. with 1 groove on the S. and 5 grooves on the N. faces.</p> <p>At the cor. point</p>

BOOK 5483

Dependent Resurvey of the West Boundary,
T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R29E R30E S25 S30 ----- S36 S31 1994</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Bury the wooden post alongside the stainless steel post.</p> <p>From this cor. point, a wooden post, 4 ins. diam., 36 ins. long, firmly set, 12 ins. in the ground, plainly mkd. with 1 notch on the S. and 5 notches on the N. edges, located in a N-S fence, bears N. 41°47' E., 23.96 chs. dist.</p> <p>Remove the wooden post.</p>
39.88	<hr/> <p>N. 0°18' E., bet. secs. 25 and 30, on the W. bdy. of the Tp.</p> <p>Over broken terrain, through scattered piñon and juniper.</p> <p>The 1/4 sec. cor. of secs. 25 and 30, monumented with a wooden post, 2 1/2 ins. sq., 43 ins. long, firmly set, 19 ins. in the ground, with no visible marks. This is accepted as the best available evidence of the position of the original cor.</p> <p>At the cor. point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R29E R30E 1/4 S25 S30 1994</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Bury the wooden post alongside the stainless steel post.</p>

BOOK 5483

Dependent Resurvey of the West Boundary,
T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>From this cor. point, a wooden post, 2 ins. diam., 42 ins. long, firmly set, 30 ins. in the ground, plainly mkd. 1/4S on the W. side, located in a fence, bears N. and S., bears N. 42°01' E., 24.43 chs. dist.</p> <p>Remove the wooden post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°04' E., beginning new measurement.</p> <p>Over broken terrain, through scattered piñon and juniper.</p>												
39.63	<p>The cor. of secs. 19, 24, 25 and 30, monumented with a wooden post, 3 ins. sq., 66 ins. long, firmly set, 14 ins. in the ground, plainly mkd. with 2 grooves on the S. and 4 grooves on the N. faces.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr><td colspan="2">T20N</td></tr> <tr><td>R29E</td><td>R30E</td></tr> <tr><td>S24</td><td>S19</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S25</td><td>S30</td></tr> <tr><td colspan="2">1994</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Bury the wooden post alongside the stainless steel post.</p> <p>From this cor. point, a wooden post 3 ins. sq., 24 ins. long, firmly set, 14 ins. in the ground, faintly mkd. NR and other illegible marks, located in a fence, bears N. and S., bears N. 42°23' E., 24.89 chs. dist.</p> <p>Remove the wooden post.</p> <hr style="width: 80%; margin: 10px auto;"/>	T20N		R29E	R30E	S24	S19			S25	S30	1994	
T20N													
R29E	R30E												
S24	S19												
S25	S30												
1994													
38.70	<p>N. 0°24' E., bet. secs. 19 and 24, on the W. bdy. of the Tp.</p> <p>Over rolling terrain.</p> <p>The 1/4 sec. cor. of secs. 19 and 24, monumented with a wooden post, 3 ins. sq., 72 ins. long, firmly set, 21 ins. in the ground, with no visible marks. This is accepted as the best available evidence of the position of the original cor.</p>												

BOOK 5483

Dependent Resurvey of the West Boundary,
T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>At the cor. point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R29E R30E 1/4 S24 S19 1994</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Bury the wood post alongside the stainless steel post.</p> <p>The cor. is located 3 chs. E. of a power line, bears N. and S.</p> <p style="text-align: center;">_____</p> <p>N. 0°03' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
39.48	<p>The cor. of secs. 13, 18, 19 and 24, monumented with a wooden post, 4 ins. sq., 67 ins. long, firmly set, 22 ins. in the ground, plainly mkd. with 3 grooves on the S. and 3 grooves on the N. faces, with an automobile leaf spring, 16 ins. long, buried alongside.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R29E R30E S13 S18 ----- S24 S19 1994</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Bury the wooden post and auto leaf spring alongside the stainless steel post.</p> <p>From this cor. point, a wooden post, 4 ins. diam., 54 ins. long, firmly set, 18 ins. in the ground, plainly mkd. with 3 notches on the S. and 3 notches on the N. faces, located 1.20 chs. E. of a fence, bears N. and S., bears N. 40°21' E., 27.63 chs. dist.</p>

BOOK 54 83

Dependent Resurvey of the West Boundary,
T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS	
35.34	<p>Remove the wooden post.</p> <hr/> <p>N. 2°57' E., bet. secs. 13 and 18, on the W. bdy. of the Tp.</p> <p>Over rolling terrain.</p> <p>The 1/4 sec. cor. of secs. 13 and 18, monumented with a wooden post, 3 x 2 ins. sq., 37 ins. long, firmly set, 10 ins. in the ground, with no visible marks. This is accepted as the best available evidence of the position of the original cor.</p> <p>At the cor. point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R29E R30E 1/4 S13 S18 1994</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Bury the wooden post alongside the stainless steel post.</p> <p>The cor. is located 1 ch. E. of a power line, bears N. and S.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 1°20' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
40.16	<p>The cor. of secs. 7, 12, 13 and 18, monumented with a wooden post, 3 ins. sq., 48 ins. long, firmly set, 21 ins. in the ground, plainly mkd. with 4 grooves on the S. and 2 grooves on the N. faces. This is accepted as the best available evidence of the position of the original cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

BOOK 5483

Dependent Resurvey of the West Boundary,
T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<div style="text-align: center;"> <p>T20N R29E R30E S12 S 7 ----- S13 S18 1994</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Bury the wooden post alongside the stainless steel post.</p> <p>The cor. is located 1.60 chs. E. of a power line, bears N. and S.</p> <hr/> <p>N. 1°07' E., bet. secs. 7 and 12, on the W. bdy. of the Tp.</p> <p>Over rolling terrain.</p>
39.835	<p>The 1/4 sec. cor. of secs. 7 and 12, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
67.50	<div style="text-align: center;"> <p>T20N R29E R30E 1/4 S12 S 7 1994</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Ridge, bears E. and W.</p>
73.70	<p>Fence, bears E. and W.</p>
79.67	<p>The cor. of secs. 1, 6, 7 and 12, monumented with a wooden post, 4 ins. sq., 90 ins. long, firmly set, 19 ins. in the ground, plainly mkd. with 5 grooves on the S. and 1 groove on the N. faces.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the West Boundary,
T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<div style="text-align: center;"> <p>T20N R29E R30E S 1 S 6 ----- S12 S 7 1994</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Bury the wooden post alongside the stainless steel post.</p> <p>The cor. is located 1.3 ch. E. of a power line, bears N. and S.</p> <hr/>
40.06	<p>N. 1°00' E., bet. secs. 1 and 6, on the W. bdy. of the Tp.</p> <p>The 1/4 sec. cor. of secs. 1 and 6, monumented with a wooden post, 4 ins. sq., 50 ins. long, firmly set, 24 ins. in the ground, with no visible marks. This is accepted as the best available evidence of the position of the original cor.</p> <p>At the cor. point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
39.55	<div style="text-align: center;"> <p>T20N R29E R30E 1/4 S 1 S 6 1994</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Bury the wooden post alongside the stainless steel post.</p> <p>The cor. is located 50 lks. E. of a power line, bears N. and S.</p> <hr/> <p>N. 2°02' E., beginning new measurement.</p> <p>Over rolling terrain.</p> <p>The original closing cor. of Tps. 20 N., Rs. 29 and 30 E., monumented with a wooden post, 4 ins. sq. 49 ins. long, firmly set, 17 ins. in the ground, faintly mkd. with 2 grooves on the E., 3 grooves on the S. and 3 grooves on the W. faces.</p>

BOOK 5483

Dependent Resurvey of the West Boundary,
T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS											
51.37	<p>Add the marks AM to the wooden post and bury it 6 ins. below ground, in place.</p> <p>Intersect the Fifth Stan. Parallel North, point for the closing cor. of Tps. 20 N., Rs. 29 and 30 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T21N R30E S31</p> <hr style="width: 10%; margin: 0 auto;"/> <table style="margin: 0 auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">S1</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">S6</td> </tr> <tr> <td style="padding: 0 5px;">R29E</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">R30E</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">CC</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">T20N</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">1994</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 21 N., R. 30 E., monumented with an iron post 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. SC 1/4 S31 1947 1993, bears S. 89°19' E., 38.37 chs. dist., from which the 1947 bearing trees</p> <ul style="list-style-type: none"> A juniper, 7 ins. diam., bears N. 69 3/4° E., 146.5 lks. dist., mkd. 31SCBT on a mostly healed blaze. A juniper, 24 ins. diam., bears N. 42 1/2° W., 76 lks. dist., mkd. 1/4 S 31 SCBT. <p>From this same cor. point, the stan. cor. of Tps. 21 N., Rs. 29 and 30 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd., SC T21N R29E R30E S36 S31 1947 1991, bears N. 89°19' W., 2.33 chs. dist., from which the 1947 bearing trees</p> <ul style="list-style-type: none"> A juniper, 14 ins. diam., bears N. 69° E., 280 lks. dist., mkd. T21NR30ES31SCBT. A juniper, 10 ins. diam., bears N. 37 1/4° W., 245.5 lks. dist., mkd. T21NR29ES36SCBT. <p>From this same cor. point, a wooden post, 4 ins. sq., 42 ins. long, firmly set, 13 ins. in the ground, plainly mkd. with 6 notches on the NE., 6 notches on the SE. and 6 notches on the NW. edges, bears N. 6°00' W., 5.41 chs.</p>	S1	S6	R29E	R30E	CC		T20N		1994	
S1	S6										
R29E	R30E										
CC											
T20N											
1994											

BOOK 54 83

Dependent Resurvey of the West Boundary,
T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>Remove the wooden post.</p> <hr/> <p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;">Restoring the survey executed by W. R. Fitzgerald in 1882</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 7°21' W., bet. secs. 31 and 32.</p> <p>Over rolling terrain.</p>										
39.05	<p>Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Cor. not monumented.</p>										
78.10	<p>Point for the cor. of secs. 29, 30, 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T20N</td> <td>R30E</td> </tr> <tr> <td>S30</td> <td>S29</td> </tr> <tr> <td colspan="2" style="text-align: center;"> </td> </tr> <tr> <td>S31</td> <td>S32</td> </tr> <tr> <td colspan="2" style="text-align: center;">1994</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the cor. of secs. 27, 28, 33 and 34, monumented with a wooden post, 5 x 4 ins. sq., 43 ins. long, firmly set, 12 ins. in the ground, mkd. with 2 grooves on the S., 3 grooves on the W. and IA on the N. faces, bears N. 89°07' E., 170.51 chs. dist. This is accepted as the best available evidence of the position of the original cor.</p> <p>At the cor. point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	T20N	R30E	S30	S29			S31	S32	1994	
T20N	R30E										
S30	S29										
S31	S32										
1994											

BOOK 5483

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<div style="text-align: center;"> <table border="1"> <tr> <td>T20N</td> <td>R30E</td> </tr> <tr> <td>S28</td> <td>S27</td> </tr> <tr> <td>S33</td> <td>S34</td> </tr> <tr> <td colspan="2">1994</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Bury the wooden post alongside the stainless steel post.</p>	T20N	R30E	S28	S27	S33	S34	1994			
T20N	R30E										
S28	S27										
S33	S34										
1994											
43.23	<hr/> <p>S. 80°42' W., bet. secs. 30 and 31.</p> <p>Over broken terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										
84.78	<div style="text-align: center;"> <table border="1"> <tr> <td>T20N</td> <td>R30E</td> </tr> <tr> <td></td> <td>S30</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S31</td> </tr> <tr> <td colspan="2">1994</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.</p>	T20N	R30E		S30	1/4	—		S31	1994	
T20N	R30E										
	S30										
1/4	—										
	S31										
1994											
38.76	<hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 2°28' W., bet. secs. 29 and 30.</p> <p>Over broken terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										

BOOK 5483

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS	
77.52	<p style="text-align: center;">T20N R30E 1/4 S30 S29 1994</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Over broken terrain.</p> <p>Point for the cor. of secs. 19, 20, 29 and 30, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R30E S19 S20 ----- S30 S29 1994</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described, bears S. 87°57' E., 407.68 chs. dist.</p> <p>From this same cor. point, the point for the closing cor. of secs. 5 and 6, at proportionate dist. on the Fifth Stan. Parallel North, bears N. 0°56' W., 312.26 chs. dist.; there is no remaining evidence of the original cor.,</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21N R30E S31 ----- S 6 S 5 C C T20N 1994</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>

BOOK 5483

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point, the stan. cor. of secs. 31 and 32, T. 21 N., R. 30 E., monumented with an iron post, 2 ins. diam, firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T21N R30E S31 S32 1947 1993, bears S. 89°22' E., 9.33 chs. dist., from which the 1947 bearing trees</p> <p style="padding-left: 40px;">A juniper, 16 ins. diam., bears N. 12 3/4° E., 270 lks. dist., mkd. T21NR30ES32SCBT.</p> <p style="padding-left: 40px;">A juniper, 5 ins. diam., bears N. 47° W., 205 lks. dist., mkd. BT on a partially healed blaze.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 21 N., R. 30 E., hereinbefore described, bears N. 89°22' W., 31.32 chs. dist.</p> <hr/> <p>S. 81°44' W., bet. secs. 19 and 30.</p> <p>Over broken terrain.</p>
41.21	<p>Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R30E S19 1/4 — S30 1994</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
80.92	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p style="text-align: center;">Metes-and-Bounds Survey in Section 30, T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the point for AP 1, established by person(s) unknown, monumented with an iron bolt, 5/8 in. diam., 24 3/4 ins. long, firmly set, 22 ins. in the ground.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

BOOK 5483

Metes-and-Bounds Survey in Section 30,
T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<div style="text-align: center;"> <p>T20N R30E $\overline{\text{AP1}}$ S30 1994</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Deposit iron bolt inside stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of secs. 29 and 30, hereinbefore described, bears N. 64°08' E., 46.85 chs. dist. West, on line 1-2.</p> <p>Over broken terrain, through dense piñon and scrub oak.</p>
3.16	<p>Point for AP 2, established by person(s) unknown, monumented with an iron bolt, 5/8 in. diam., 24 3/4 ins. long, firmly set, 22 ins. in the ground.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R30E $\overline{\text{AP2}}$ S30 1994</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Deposit the iron bolt inside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 0°02' W., on line 2-3.</p> <p>Over broken terrain, through dense piñon and scrub oak.</p>
1.51	<p>Point for AP 3, established by person(s) unknown, monumented with an iron bolt, 5/8 in. diam., 19 3/4 ins. long, firmly set, 17 ins. in the ground.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R30E $\overline{\text{AP3}}$ S30 1994</p> </div>

BOOK 5483

Metes-and-Bounds Survey in Section 30,
T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS			
3.16	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Deposit the iron bolt inside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>South, on line 3-4.</p> <p>Over broken terrain, through dense piñon and scrub oak.</p> <p>Point for AP 4, established by person(s) unknown, monumented with an iron bolt, 5/8 in. diam., 19 3/4 ins. long, firmly set, 17 ins. in the ground.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T20N R30E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S30</td> <td style="border-bottom: 1px solid black; padding: 0 5px;">AP4</td> </tr> </table> <p>1994</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Deposit the iron bolt inside the stainless steel post.</p> <p>From this cor., the 1/4 sec. cor. of secs. 30 and 31, hereinbefore described, bears S. 11°51' E., 21.04 chs. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>East, on line 4-5.</p> <p>Over broken terrain, through dense piñon and scrub oak.</p>	S30	AP4
S30	AP4		
3.16	<p>Point for AP 5, established by person(s) unknown, monumented with an iron bolt, 5/8 in. diam., 19 3/8 ins. long, firmly set, 17 ins. in the ground.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T20N R30E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">AP5</td> <td style="border-bottom: 1px solid black; padding: 0 5px;">S30</td> </tr> </table> <p>1994</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>	AP5	S30
AP5	S30		

BOOK 5483

Metes-and-Bounds Survey in Section 30,
T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS	
3.16	<p>Deposit the iron bolt inside the stainless steel post.</p> <hr/> <p>N. 0°01' E., on line 5-6.</p> <p>Over broken terrain, through dense piñon and scrub oak.</p> <p>Point for AP 6, established by person(s) unknown, monumented with an iron bolt, 5/8 in. diam., 27 3/4 ins. long, firmly set, 20 ins. in the ground.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R30E</p> <p>AP6 S30</p> <p>1994</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Deposit the iron bolt inside the stainless steel post.</p> <hr/> <p>North, on line 6-1.</p> <p>Over broken terrain, through dense piñon and scrub oak.</p>
1.51	<p>AP 1, and point of beginning.</p> <hr/>

BOOK 5483

T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS	GENERAL DESCRIPTION
	<p>The northwest corner of the Township is located approximately 8.5 miles southeast of Sanders, Arizona. Access to the area is provided by various dirt roads.</p> <p>The terrain consists of rolling land with dense juniper and piñon forests. The average elevation is 6,500 feet above sea level.</p> <p>There is limited occupancy throughout this region which is used primarily for grazing and wood cutting.</p>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Cheryl A. Baier	Surveying Technician
Richard E. Glaze	Surveying Technician
Rebecca Ramirez	Surveying Technician
W. William Foster	Surveying Technician
Wally R. Ott Jr.	Surveying Aide
Johnny R. Ramirez	Surveying Aide
Michael Searles	Surveying Aide

30
BOOK 5483
CERTIFICATE OF SURVEY

We, Joe R. Salazar and Gary D Knoff, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 12th day of January, 1987, and Supplemental Special Instructions bearing date of the 29th day of February, 1988, We have dependently resurveyed the south, east and west boundaries and a portion of the subdivisional lines, and performed a metes-and-bounds survey in section 30, Township 20 North, Range 30 East, Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

2/18/97
(Date)

Joe R. Salazar
(Cadastral Surveyor)

2/20/97
(Date)

Gary D. Knoff
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the south, east and west boundaries and a portion of the subdivisional lines, and a metes-and-bounds survey in section 30, Township 20 North, Range 30 East, Gila and Salt River Meridian, Arizona, executed by Joe R. Salazar and Gary D. Knoff, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

MAR 13 1997
(Date)

Dale C. Wilson
(Acting Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 20 N., R. 30 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____~~
~~(Date)~~

~~_____~~
~~(Acting Chief Cadastral Surveyor of Arizona)~~