

ORIGINAL

1

BOOK 5493

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF A PORTION OF THE SUBDIVISIONAL LINES

AND PORTIONS OF CERTAIN MINERAL SURVEYS

AND

THE SUBDIVISION OF SECTIONS 21 AND 22,

TOWNSHIP 4 NORTH, RANGE 3 EAST.

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY

Joe R. Salazar, Cadastral Surveyor

Under Special Instructions dated September 25, 1996, approved September 25, 1996, which provided for the surveys included under Group Number 805 and assignment instructions dated September 30, 1996.

Survey commenced October 9, 1996

Survey completed November 7, 1996

2
BOOK 5493
 INDEX DIAGRAM

TOWNSHIP 4 NORTH, RANGE 3 EAST,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Dep. Res. of Mineral Surveys

pp. 8-26

Subdivision of sec. 21

pp. 26-27

Subdivision of sec. 22

pp. 27-32

BOOK 5493

T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and portions of certain mineral surveys, and the subdivision of sections 21 and 22, Township 4 North, Range 3 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this dependent resurvey is as follows: James H. Martineau surveyed the subdivisional lines in 1894. Charles E. Hunter dependently resurveyed the subdivisional lines bounding sec. 22 in 1932. Frank Nicholson surveyed Mineral Survey No. 1139 in 1894. William H. Elliott surveyed Mineral Survey No. 1906 in 1904. Harry E. Jones surveyed Mineral Survey No. 3740 in 1921, Mineral Survey No. 4293 in 1945 and Mineral Survey No. 4429 in 1958-60. Ralph L. Motz surveyed Mineral Survey No. 4355 in 1951.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated September 25, 1996, for Group No. 805, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of all lines were determined by direct hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured with a Pentax PTS 3 total station instrument.

The geographic position of the cor. of secs. 21, 22, 27 and 28, as determined from a tie made to U. S. Geological Survey, triangulation station "UNION 1947" is as follows:

Latitude: 33°40'09.86" N. Longitude: 112°02'52.09" W. NAD27

The mean magnetic declination as taken from quadrangle map "UNION HILLS", ARIZ., published in 1964 and photorevised in 1973 by U.S. Geological Survey, is 13 1/2° E.

BOOK 5493

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">Restoring the resurvey executed by Charles E. Hunter in 1932.</p> <hr/> <p>Beginning at the 1/4 sec. cor. of secs. 22 and 23, monumented by the City of Phoenix with a brass cap, 3 ins. diam., firmly set in concrete, 5 ins. below the road surface, with brass cap mkd. CITY OF PHOENIX 19. This is accepted as the best available evidence of the 1932 reestablished cor. position.</p> <p>Cor. is located at the intersection of Rose Garden Lane, bears E. and W., and Cave Creek Rd., bears N. and S.</p> <p>N. 0°46' W., bet. secs. 22 and 23.</p> <p>Along the center of Cave Creek Rd.</p>
20.06	<p>The N 1/16 sec. cor. of secs. 22 and 23, monumented by the City of Phoenix with a brass cap, 3 ins. diam., firmly set flush with road surface, with brass cap mkd., CITY OF PHOENIX 19. This is accepted as a careful and faithful determination of the cor. position.</p> <p>Cor. is located at the intersection of Cave Creek Rd., bears N. and S., and Lone Cactus Dr., bears W.</p> <hr/> <p>N. 0°46' W., beginning new measurement.</p>
20.06	<p>The cor. of secs. 14, 15, 22 and 23, monumented by the City of Phoenix with a brass cap, 3 ins. diam., firmly set, 6 ins. below the surface, incased in a concrete pipe, 10 ins. diam., with a cast iron lid, with brass cap mkd., CITY OF PHOENIX 19. This is accepted as the best available evidence of the original cor. position.</p> <p>Cor. is located in the center of Cave Creek Rd., bears N. and S.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 22 and 27, monumented by the County of Maricopa Highway Dept. with a brass cap, 3 ins. diam., firmly set, 3 ins. below surface, incased in a concrete pipe, 10 ins. diam., with a cast iron lid, with brass cap mkd. MARICOPA COUNTY HIGHWAY DEPT. This is accepted as the best available evidence of the original cor. position.</p> <p>Cor. is located at the intersection of Beardsley Rd., bears E. and W., and 20th. St., bears N.</p> <p>S. 89°09' W., bet. secs. 22 and 27.</p>

BOOK 5493

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Along the center of Beardsley Rd.
10.51	Intersect line 5-1, Victory # 1 lode, M.S. No. 4355, hereinafter described.
24.40	Intersect line 4-5, Victory # 1 lode, M.S. No. 4355, hereinafter described.
27.15	Intersect line 1-2, Kruger lode, M.S. No. 1906, hereinafter described.
34.58	Intersect line 4-1, Kruger lode, M.S. No. 1906, hereinafter described.
41.03	<p>The cor. of secs. 21, 22, 27 and 28, monumented by the County of Maricopa Highway Dept. with a brass cap, 3 ins. diam., firmly set, 4 ins. below surface, incased in a concrete pipe, 10 ins. diam., with a cast iron lid, with brass cap mkd. MARICOPA COUNTY HIGHWAY DEPT. This is accepted as the best available evidence of the original cor. position.</p> <p>Cor. is located at the intersection of Beardsley Rd., bears E. and W., and 16th. St., bears N. and S.</p> <p>From this cor. point, U.S. Geodetic Survey triangulation station "UNION 1947", with published latitude of 33°39'10.7607" N. and longitude of 112°03'01.1915" W., NAD27, bears S. 7°20'32' W. (forward bearing), 91.27 chs. dist., monumented with a standard brass disk, 3 ins. diam., incased in concrete 12 ins. square, 3 1/2 ft. high and rounded on top, with top of disk mkd. UNION 1947 and a triangle.</p>
	N. 0°13' W., bet. secs. 21 and 22.
	Along the center of 16th. St.
2.25	Intersect line 1-2, Scarlet Wedge lode, M.S. No. 4429, hereinafter described.
3.50	Leave 16th. Street, enter housing subdivision.
4.69	Intersect line 1-2, Scarlet lode, M.S. No.4293, identical with line 4-1, Scarlet Wedge lode, M.S. No. 4429, hereinafter described.
39.91	The 1/4 sec. cor. of secs. 21 and 22, determined at record bearing and distance from a tie established by Lawrence R. Gates, Arizona Registered Land Surveyor, No. 11116, as shown on Project Red Dog Claim, No. 94138 plat, dated Dec. 6, 1994.

BOOK 5493

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>Cor. No. 1, Red Dog lode, identical to cor. No. 1, Mary Ann lode, M.S. No.3740, hereinafter described, bears N. 3°57' W, 3.60 chs. dist.</p> <p>Not monumented.</p> <p>Cor. is located in front yard of Lot 35 of Horizons at Scarlet Canyon Subdivision.</p> <hr/> <p>N. 0°27' E., beginning new measurement.</p> <p>Through housing subdivision.</p>
3.23	Intersect line 1-2, Red Dog lode, M.S. No. 3740, hereinafter described.
3.24	Leave housing subdivision, entering rolling land.
15.20	Toe of slope, thence ascend.
25.21	Intersect line 1-2, Golden Star lode, M.S. No. 3740, hereinafter described.
26.10	Top of ridge, bears E. and W.
26.40	Descend.
27.12	Intersect line 4-1, Golden Star lode, M.S. No. 3740, hereinafter described.
31.30	Toe of slope.
42.18	<p>The cor. of secs. 15, 16, 21 and 22, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 13 ins. above the ground, with brass cap mkd. T4N R3E S16 S15 S21 S22 1932.</p> <p>Add the marks 1996 to the brass cap.</p> <p>Cor. is located in corner of 5 strand barbed wire fence, extending N. and E.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 89°27' W., bet. secs. 15 and 22.</p> <p>Over rolling land.</p>

BOOK 5493

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.01	<p>Point for the E. 1/16 sec. cor. of secs. 15 and 22.</p> <p>Not monumented.</p>
40.02	<p>The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 1 in. diam., firmly set, 37 ins. below ground, with brass cap mkd. 1/4 S15 S22 1932.</p> <p>Set a steel fence post alongside the cor.</p> <hr/> <p>N. 87°46' W., beginning new measurement.</p> <p>Over rolling land.</p>
39.75	<p>The cor. of secs. 15, 16, 21 and 22.</p> <hr/> <p style="text-align: center;">Restoring the survey executed by James H. Martineau in 1894.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. 89°22' W., bet. secs. 21 and 28.</p> <p>Along the center of Beardsley Rd.</p>
2.935	<p>Intersect line 1-2, Scarlet Wedge lode, M.S. No. 4429, hereinafter described.</p>
17.71	<p>Intersect line 2-3, Scarlet Wedge No. 2 lode, M.S. No. 4429, hereinafter described.</p>
39.91	<p>The 1/4 sec. cor. of secs. 21 and 28, monumented by the County of Maricopa Highway Dept. with a brass cap, 3 ins. diam., firmly set, 5 ins. below the surface, incased in a concrete pipe, 10 ins. diam., with a cast iron lid, with brass cap mkd., MARICOPA COUNTY HIGHWAY DEPT. This is accepted as the best available evidence of the original cor. position.</p> <p>Cor. is located at the intersection of Beardsley Rd., bears E. and W., and 12th. St., bears N. and S.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 88°02' W., bet secs. 16 and 21.</p> <p>Over rolling land.</p>

BOOK 5493

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.65	<p>The 1/4 sec. cor. of secs. 16 and 21, monumented by the City of Phoenix, with a brass cap, 3 ins. diam., firmly set, 6 ins. below the surface, incased in a concrete pipe, 10 ins. diam., with a cast iron lid, with brass cap mkd. CITY OF PHOENIX 19. This is accepted as the best available evidence of the original cor. position.</p> <p>Cor. is located S., 36 lks. dist., from Deer Valley Rd., bears E. and W.</p> <p>From this cor. point, a 5 ft. high flood control gate post, 5 ins. square, bears N. 26°08' W., 14 lks. dist.</p>
<p>Dependent Resurvey of Portions of Certain Mineral Surveys, T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona</p>	
<p>Restoring the surveys executed by Frank Nicholson in 1894, William H. Elliott in 1904, Harry E. Jones in 1921, in 1945 and in 1958-60, and Ralph L. Motz in 1951.</p>	
<p>From cor. 1, Golden Star lode, M.S. No. 3740, monumented with a mound of stone, 3 1/2 ft. base, 18 ins. high, no mkd. stone found.</p>	
<p>At the cor. point.</p>	
<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to bedrock, in a mound of stone, 6 ft. base, to top, with brass cap mkd.</p>	
<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>	
<p>Cor. is located on N. slope of steep rocky ridge, bears E. and W.</p>	
<p>From this cor. point, the cor. of secs. 15, 16, 21 and 22, hereinbefore described, bears N. 2°32' W., 15.26 chs, dist.</p>	
<p>N. 76°45' W., on line 1-4, Golden Star lode, M.S. No. 3740.</p>	

BOOK 5493

Dependent Resurvey of Portions of Certain Mineral Surveys,
T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
0.815	<p>Over mountainous land.</p> <p>Intersect the line bet. secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div data-bbox="841 548 1003 764" data-label="Diagram"> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on the N. slope of steep rocky ridge, bears E. and W.</p> <p>From this cor. point, the cor. of secs. 15, 16, 21 and 22, hereinbefore described, bears N. 0°27' E., 15.06 chs, dist.</p>
8.33	<p>Cor. 4, Golden Star lode, M.S. No. 3740, monumented with a mound of stone, 3 ft. base, 2 ft. high, no visible marks.</p> <p>At the cor. point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div data-bbox="829 1373 1040 1587" data-label="Diagram"> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on very steep, rocky E. slope of ridge.</p> <hr/> <p>S. 27°54' W., on line 4-3, Golden Star lode, M.S. No. 3740.</p> <p>Over mountainous land.</p>

Dependent Resurvey of Portions of Certain Mineral Surveys,
T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
4.50	Toe of slope, thence along nearly level land.
15.69	<p>Cor. 3, Golden Star lode, identical to cor. 3, Mary Ann lode, M.S. No. 3740, monumented with a iron post, 1 in. diam., projecting 19 ins. above ground, in a mound of stone, 2 1/2 ft. base, 1 ft. high, with brass cap mkd., US MINERAL SURVEY 3740 and MA 3 GS 3 on the side.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 22°40' E., on line 3-2, Mary Ann lode, M.S. No. 3740.</p> <p>Over nearly level land.</p>
16.31	<p>Intersect the E. and W. center line of sec. 21.</p> <p>Not monumented.</p>
18.59	<p>Cor. 2, Mary Ann lode, identical to cor. 4, Red Dog lode, M.S. No. 3740, on line 2-3, Union lode, M.S. No. 1139, monumented by person(s) unknown with an iron pipe, 1 in. diam., 18 ins. long, firmly set 15 ins. in the ground. This is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> </div> <p>Deposit the iron pipe inside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Cor. is located N., 36 lks. dist. from a block wall, bears NE. and SW., and 77 lks. from the center of 17th St., bears SE. and NW.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 37°08' W., on a portion of line 2-3, Union lode, M.S. No. 1139.</p> <p>Along the W. side of 17th. St.</p>

BOOK 5493

Dependent Resurvey of Portions of Certain Mineral Surveys,
T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
2.64	Intersect the E. and W. centerline of sec. 21.
	Not monumented.
12.30	<p>Point for cor. 3, Union lode, M.S. No. 1139, determined by the grant boundary adjustment of the record surveys as shown on the plat for Project No. 93222, Scarlet Canyon, sheet 6, and the plat for Project No. 94138, Red Dog Claim, surveyed by Lawrence R. Gates, Arizona Registered Land Surveyor No. 11116; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone 3 ft. base to top, with brass cap mkd.</p> <div data-bbox="824 772 993 991" data-label="Diagram"> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in corner of block wall, bears SSE. and SW.</p> <hr/> <p>S. 52°31' W., on line 3-5, Union lode, M.S. No. 1139.</p> <p>Over nearly level land.</p> <p>Along northeasterly edge of block fence.</p>
4.535	<p>Point for cor. 4, Union lode, M.S. No. 1139 at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Not monumented.</p>
9.07	<p>Cor. 5, Union lode, M.S. No. 1139, monumented by person(s) unknown with an iron pipe, 1 in. diam., 16 ins. long, firmly set 15 ins. in the ground. This is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of Portions of Certain Mineral Surveys,
T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<div data-bbox="803 294 1071 483" data-label="Diagram"> </div> <p data-bbox="397 514 1193 546">Deposit iron pipe inside the stainless steel post.</p> <p data-bbox="397 577 1323 640">Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p data-bbox="397 672 1356 703">Cor. is located in corner of block fence, bears SSE. and NE.</p> <p data-bbox="397 735 1437 861">From this cor. point, a rock and concrete column, 4 ft. square on bottom, 27 ins. high, 20 ins. square on top, with fence post in center, concrete mkd. TILDEN APR 2, bears N. 65°33' W., 5 lks. dist.</p> <hr data-bbox="714 892 1079 898"/> <p data-bbox="397 924 1242 955">S. 37°04' E., on line 5-6, Union lode, M.S. No. 1139.</p> <p data-bbox="397 987 763 1018">Over nearly level land.</p> <p data-bbox="397 1050 1031 1081">Along southwesterly edge of block fence.</p> <p data-bbox="251 1113 1128 1144">2.84 Intersect the E. and W. centerline of sec. 21.</p> <p data-bbox="397 1176 633 1207">Not monumented.</p> <p data-bbox="235 1239 1437 1459">22.91 Cor. 6, Union lode, M.S. No. 1139, identical to cor. 2, Scarlet lode, M.S. No. 4293 and cor. 4, Scarlet Wedge lode, M.S. No. 4429, monumented by person(s) unknown with a reinforcing bar, 1/2 in. diam., 12 ins. long, firmly set flush with ground, over another reinforcing bar, 1/2 in. diam., 18 ins. long, firmly set 16 ins. below the surface of the ground. This is accepted as the best available evidence of the original cor. position.</p> <p data-bbox="397 1491 682 1522">At the cor. point.</p> <p data-bbox="397 1554 1339 1617">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

BOOK 5493

Dependent Resurvey of Portions of Certain Mineral Surveys,
T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<div data-bbox="828 294 1071 609" data-label="Diagram"> </div> <p data-bbox="397 640 1388 682">Deposit both reinforcing bars inside the stainless steel post.</p> <p data-bbox="397 703 1323 766">Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <hr data-bbox="714 787 1088 808"/> <p data-bbox="397 829 1437 892">S. 23°22' E., on line 2-1, Scarlet lode, M.S. No. 4293, identical with line 4-1, Scarlet Wedge lode, M.S. No. 4429.</p> <p data-bbox="397 924 763 955">Over nearly level land.</p>
20.76	<p data-bbox="397 997 1031 1029">Intersect the line bet. secs. 21 and 22.</p> <p data-bbox="397 1060 1339 1123">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div data-bbox="852 1155 1063 1375" data-label="Diagram"> </div> <p data-bbox="397 1407 1323 1470">Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p data-bbox="397 1501 1388 1596">Cor. is located in the median of a subdivision access road, 7.3 lks. from back of curb of S. bound lane and 11.6 lks. from back of curb of N. bound lane.</p> <p data-bbox="235 1627 1437 1785">22.75 Cor. 1, Scarlet lode, M.S. No. 4293, identical to cor. 1, Scarlet Wedge lode, M.S. No. 4229, monumented by person(s) unknown with an iron pipe, 3/4 in. diam., firmly set, projecting 1 in. above ground. This is accepted as the best available evidence of the position of the original corner.</p> <p data-bbox="397 1816 673 1848">At the cor. point</p>

BOOK 5493

Dependent Resurvey of Portions of Certain Mineral Surveys,
T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div data-bbox="792 394 1040 642" style="text-align: center;"> </div> <p>Deposit iron pipe inside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Cor. is located E., 10 lks. dist. from side walk, bears NW. and SE.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 52°01' E., on line 1-4, Scarlet lode, M.S. No. 4293.</p> <p>Over nearly level land.</p> <p>9.10 Cor. 4, Scarlet lode, M.S. No. 4293, monumented by person(s) unknown with a 1/2 in. reinforcing rod, 18 ins. long, firmly set, 8 ins. above ground. This is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div data-bbox="792 1409 1057 1625" style="text-align: center;"> </div> <p>Deposit reinforcing rod inside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 23°54' W., on a portion of line 4-3, Scarlet lode, M.S. No. 4293.</p>

Dependent Resurvey of Portions of Certain Mineral Surveys,
T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
1.96	<p>Over nearly level land.</p> <p>Cor. 3, Red Dog Wedge lode, M.S. No. 3740, on line 3-4, Scarlet lode, M.S. No. 4293, determined from a tie to cor. 1, Kruger lode, M.S. No. 1906.</p> <p>At the cor. point</p> <p>Set an aluminum tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in bedrock, with top mkd.</p> <div data-bbox="860 630 1120 892" data-label="Diagram"> </div> <p>From this cor. point, cor. 1, Kruger lode, M.S. No. 1906, hereinafter described, bears S. 11°32' E., 6.899 chs. (455.35 ft.) dist.</p> <p>From this same cor. point, the cor. of secs. 21, 22, 27 and 28, hereinbefore described, bears S. 34°54' W., 12.497 chs. (824.78 ft.) dist. (Record: S. 34°48' W.)</p> <p>Cor. is located SE., 24 lks. dist. from corner of block fences, bears NE. and SW.</p> <hr/> <p>N. 65°33' E., on line 3-2, Red Dog Wedge lode, M.S. No. 3740.</p>
7.58	<p>Over nearly level land.</p> <p>Point for cor. 2, Red Dog Wedge lode, identical to cor. 3, Santa Rosa lode and cor. 3, South Extension lode, M.S. No. 3740, determined by the grant boundary adjustment of the record survey as shown on the plat for Project No. 93222, Scarlet Canyon, sheets 2, 3 and 4, surveyed by Lawrence R. Gates, Arizona Registered Land Surveyor No. 11116; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bed rock, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p>

BOOK 5493

Dependent Resurvey of Portions of Certain Mineral Surveys,
T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<div data-bbox="776 296 1105 575" data-label="Diagram"> </div> <p data-bbox="396 611 1321 674">Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p data-bbox="396 709 1398 741">Cor. is located W., 24 lks. dist. from a block fence, bears SE.</p> <hr data-bbox="716 764 1084 772"/> <p data-bbox="396 806 1365 869">S. 50°30' E., on a portion of line 3-2, Santa Rosa lode, M.S. No. 3740.</p> <p data-bbox="396 900 760 932">Over nearly level land.</p>
16.91	<p data-bbox="396 963 1224 995">Intersect line 5-1, Victory # 1 lode, M.S. No. 4355.</p> <p data-bbox="396 1026 1333 1089">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div data-bbox="797 1121 1036 1373" data-label="Diagram"> </div> <p data-bbox="396 1409 1321 1472">Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p data-bbox="396 1503 1430 1629">From this cor. point, the point for cor. 2, Santa Rosa lode, M.S. No. 3740, determined by a direct tie to cor. 5, Victory #1 lode, M.S. No.4355, hereinafter described, bears S. 50°30' E., 0.33 ch. dist.</p> <p data-bbox="396 1661 630 1692">Not monumented.</p> <p data-bbox="396 1724 1398 1881">From this same cor. point, cor. 1, Victory #1 lode, M.S. No. 4355, bears S. 57°30' E., 15.235 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set projecting 21 ins. above the ground. This is accepted as the best available evidence of the original cor. position.</p> <hr data-bbox="716 1904 1084 1913"/>

BOOK 5493

Dependent Resurvey of Portions of Certain Mineral Surveys,
T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>N. 57°30' W., on a portion of line 1-5, Victory #1 lode, M.S. No. 4355.</p>
7.48	<p>Cor. 5, Victory #1 lode, M.S. No. 4355, monumented with a granite stone, firmly set, projecting 17 X 13 X 6 ins. above the ground, plainly mkd. V-1 S4355 on the SW. face, with a mound of stone 3 1/2 ft. base 2 ft. high N. of cor.</p> <p>Not remonumented.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>S. 32°59' W., a portion of on line 5-4, Victory #1 lode, M.S. No. 4355.</p>
7.635	<p>Intersect the line bet. secs. 22 and 28.</p> <p>Set a PK nail in center of Beardsley Rd., bears E and W.</p> <p>from which</p> <p style="padding-left: 40px;">A stone outcrop 2 X 6 X 6 ft., bears N. 57°20' E., 134 lks. dist., mkd. XBO on top.</p> <p>From this cor. point, cor. 4, Victory #1 lode, M.S. No. 4355, on line 1-2, Kruger lode, M.S. No. 1906, bears S. 32°59' W., 1.475 chs. dist., monumented with a rhyolite stone, firmly set, projecting 9 X 8 X 6 ins. above ground, with a mound of stone, 4 ft. base, 1 ft. high, to the NW., mkd. V1 4 4355 on the E. face, with an X on top.</p> <p>from which</p> <p style="padding-left: 40px;">A granite boulder, 3 X 4 X 4 ft., bears N. 28°13' W., 51 lks. dist. (Record: N. 35°35' W., 32.5 ft.), mkd. BO X on SE. face.</p> <p>From this same cor. point, the cor. of secs. 21, 22, 27 and 28. hereinbefore described, bears S. 89°09' W., 16.63 chs. dist.</p> <hr style="width: 60%; margin: 10px auto;"/>
	<p>From a point at the intersection of line 1-2, Kruger lode, M.S. No. 1906, with the line bet. secs. 22 and 27.</p> <p>Set a PK nail in center of Beardsley Rd., bears E. and W.</p> <p>from which</p> <p style="padding-left: 40px;">A granite boulder, 2 X 4 X 6 ft., bears N. 48°20' E., 93 lks. dist., mkd. X BO on S. face.</p>

BOOK 5493

Dependent Resurvey of Portions of Certain Mineral Surveys,
T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point, cor. 4, Victory #1 lode, M.S. No. 4355, on line 1-2, Kruger lode, M.S. No. 1906, hereinbefore described, bears S. 58°22' E., 2.285 chs. dist.</p>
	<p>From this same cor. point, cor. 2, Kruger lode, identical with cor. 1 Sultan lode, M.S. No. 1906, bears S. 58°22' E., 11.36 chs. dist., monumented by person(s) unknown with a reinforcing rod, 3/8 in. diam., firmly set, projecting 3 ins. above ground in an imbedded collar of stone. This is accepted as the best available evidence of the original cor. position.</p>
	<p>From this same cor. point, the cor. of secs. 21, 22, 27 and 28, hereinbefore described, bears S. 89°09' W., 13.88 chs. dist.</p>
	<p>N. 58°22' W., on a portion of line 2-1, Kruger lode, M.S. No. 1906.</p>
6.28	<p>Cor. 1, Kruger lode, M.S. No. 1906, monumented with a granite stone, firmly set, projecting 7 X 12 X 12 ins. above ground, plainly mkd. 1906 K1 on S. face.</p>
	<p>Not remonumented.</p>
	<p>S. 31°29' W., on a portion of line 1-4, Kruger lode, M.S. No. 1906.</p>
3.98	<p>Intersect the line bet. secs. 22 and 27.</p>
	<p>Set a PK nail in center of Beardsley Rd., bears E. and W. from which</p>
	<p style="padding-left: 40px;">A granite boulder, 2 X 4 X 5 ft., bears N. 8°40' E., 161 lks. dist., mkd. X B0 on top.</p>
	<p>From this cor. point, cor. 4, Kruger lode, M.S. No. 1906, bears S. 31°29' W., 5.10 chs. dist., monumented by person(s) unknown with a reinforcing rod, 3/8 in. diam., firmly set projecting 3 ins. above the ground. This is accepted as the best available evidence of the original cor. position.</p>
	<p>From this same cor. point, the cor. of secs. 21, 22, 27 and 28. hereinbefore described, bears S. 89°09' W., 6.45 chs. dist.</p>
	<p>From a point at the intersection of line 5-1, Victory #1 lode, M.S. No. 4355, with the line bet. secs. 22 and 27.</p>
	<p>Set a PK nail in the center of Beardsley Rd., bears E. and W.</p>

Dependent Resurvey of Portions of Certain Mineral Surveys,
T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, for a reference monument, bears N. 24°35' E., 62.2 ft. dist., with brass cap mkd. RM T4N R3E S22 AP 62.2 FT TO COR 1996, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, cor. 1, Victory #1 lode, M.S. No. 4355, bears S. 57°30' E., 11.18 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the 1/4 sec. cor. of secs. 22 and 27, hereinbefore described, bears N. 89°09' E., 10.51 chs. dist.</p> <p>N. 57°30' W., on a portion of line 1-5, Victory #1 lode, M.S. No. 4355.</p>
3.71	<p>Intersect line 1-2, Santa Rosa lode, M.S. No. 3740.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with ground, with brass cap mkd.</p> <div data-bbox="792 1024 1058 1276" style="text-align: center;"> <p>T4N R3E SR MS3740</p> <p>V1 MS4355 1996</p> <p>AP S22</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Cor. is located S., 11 lks. dist., from a sidewalk, bears NW. and SE.</p> <p>From this cor. point, cor. 5, Victory #1 lode, M.S. No. 4355, hereinbefore described, bears N. 57°30' W., 7.825 chs. dist.</p> <p>From this same cor. point, the point for cor. 2, Santa Rosa lode, M.S. No. 3740, hereinbefore described, bears S. 50°49' W., 0.04 chs. dist.</p>
9.04	<p>N. 50°49' E., on line 2-1, Santa Rosa lode, M.S. No. 3740.</p> <p>Cor. 1, Santa Rosa lode, M.S. No. 3740, determined from a tie to the 1/4 sec. cor. of secs. 22 and 27, as shown on the plat of Turkey Track # 1 Placer, M.S. No. 4574.</p>

BOOK 5493

Dependent Resurvey of Portions of Certain Mineral Surveys,
T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div data-bbox="792 451 982 703" data-label="Diagram"> </div> <p>From this cor. point, the 1/4 sec. cor. of secs. 22 and 27, hereinbefore described, bears S. 41°19'10" E., 10.049 chs. (663.26 ft.) dist.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on E., 17 lks. dist. from a block fence, bears SE. and NW.</p> <hr/> <p>N. 50°23' W., on line 1-4, Santa Rosa lode, M.S. No. 3740.</p>
17.25	<p>Point for cor. 4, Santa Rosa lode, identical to cor. 2, South Extension lode, M.S. No. 3740, determined by the grant boundary adjustment of the record survey as shown on the plat for Project No. 93222, Scarlet Canyon, sheets 2 and 4, surveyed by Lawrence R. Gates, Arizona Registered Land Surveyor No. 11116; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div data-bbox="792 1470 1079 1753" data-label="Diagram"> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>

BOOK 5493

Dependent Resurvey of Portions of Certain Mineral Surveys,
T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
11.60	<p>Cor. is located, E., 24 lks. dist., of a block fence, bears SE. and NW.</p> <hr/> <p>N. 51°07' W., on line 2-1, South Extension lode, M.S. No. 3740.</p> <p>Over nearly level land.</p> <p>Cor. 1, South Extension lode, identical to cor. 2, Red Dog lode, M.S. No. 3740, monumented by person(s) unknown with a reinforcing rod, 3/8 in. diam., firmly set, 6 ins. below ground. This is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div data-bbox="792 898 1075 1180" data-label="Diagram"> </div> <p>Deposit the reinforcing rod inside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Cor. is located E., 1 lk. dist., of a block fence, bears SE. and NW.</p> <hr/> <p>N. 36°08' W., on line 2-1, Red Dog lode, M.S. No. 3740.</p> <p>Over nearly level land.</p>
16.72	<p>Intersect the E. and W. centerline of sec. 22.</p> <p>Not monumented.</p>
20.69	<p>Intersect the line bet. secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>


BOOK 5493

Dependent Resurvey of Portions of Certain Mineral Surveys,
T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<div data-bbox="836 300 1047 583" data-label="Diagram"> </div> <p data-bbox="396 617 1325 678">Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p data-bbox="396 714 1422 772">Cor. is located NE., 3 lks. dist., of a cut bank, bears NNW. and SSE.</p> <p data-bbox="396 808 1435 898">From this cor. point, the point for the 1/4 sec. cor. of secs. 21 and 22, hereinbefore described, bears S. 0°27' W., 3.23 chs. dist.</p>
21.14	<p data-bbox="396 934 1432 1056">Cor. 1, Red Dog lode, identical to cor. 1, Mary Ann lode, M.S. No. 3740, monumented with an iron pipe, 1 in. diam. firmly set, projecting 16 ins. above the ground, in a mound of stone, 2 ft. base, 12 ins. high, with brass cap mkd., U S MINERAL SURVEY 3740.</p> <p data-bbox="396 1092 667 1119">Not remonumented.</p> <hr data-bbox="716 1144 1084 1150"/> <p data-bbox="396 1186 1336 1245">N. 23°30' W., on a portion of line 1-4, Mary Ann lode, M.S. No. 3740.</p> <p data-bbox="396 1281 764 1308">Over nearly level land.</p>
11.73	<p data-bbox="396 1344 1224 1371">Intersect line 1-2, Golden Star lode, M.S. No. 3740.</p> <p data-bbox="396 1407 1336 1465">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div data-bbox="776 1535 1052 1753" data-label="Diagram"> </div> <p data-bbox="396 1789 1325 1848">Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>


BOOK 5493

Dependent Resurvey of Portions of Certain Mineral Surveys,
T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point, cor. 4, Mary Ann lode, M.S. No. 3740, determined by the grant boundary adjustment of the record survey as shown on the plat for Project No. 94138, Red Dog Claim, surveyed by Lawrence R. Gates, Arizona Registered Land Surveyor No. 11116; there is no remaining evidence of the original cor., bears N. 23°30' W., 6.76 ch. dist.</p>
	<p>Not monumented.</p>
	<p>From this same cor. point, cor. 2, Golden Star lode, M.S. No. 3740, determined by the grant boundary adjustment of the record survey as shown on the plat for Project No. 94138, Red Dog Claim, surveyed by Lawrence R. Gates, Arizona Registered Land Surveyor No. 11116; there is no remaining evidence of the original cor., bears S. 25°12' W., 1.60 ch. dist.</p>
	<p>Not monumented.</p>
	<p>_____</p> <p>N. 25°12' E., on a portion of line 2-1, Golden Star lode, M.S. No. 3740.</p>
	<p>Over nearly level land.</p>
8.50	<p>Toe of steep rocky ridge</p>
12.01	<p>Intersect the line bet. secs. 21 and 22.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T4N R3E GS MS3740</p>  <p>1996</p> </div>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
	<p>Cor. is located on the S. slope of a steep rocky ridge, bears E. and W.</p>
	<p>Raised a mound of stone, 4 ft. base, 3 ft. high, S. of cor.</p>
	<p>From this cor. point, the cor. of secs. 15, 16, 21 and 22, hereinbefore described, bears N. 0°27' E., 16.97 chs, dist.</p>

BOOK 5493

Dependent Resurvey of Portions of Certain Mineral Surveys,
T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
13.91	Cor. 1, Golden Star lode, M.S. No.3740, hereinbefore described.
	<p>From cor. 4, Scarlet Wedge lode, M.S. No. 4429, identical with cor. 6, Union lode, M.S. No. 1139, and cor. 2, Scarlet lode, M.S. No. 4293, hereinbefore described.</p> <p>S. 52°06' W., on line 4-3, Scarlet Wedge lode, M.S. No. 4429.</p> <p>Over nearly level land.</p>
8.98	SW. location cor. of Tilden mineral claim, monumented with an iron pipe, 1 in. diam., firmly set, 2 ins. below ground in imbedded mound of stone.
9.38	<p>Cor. 3, Scarlet Wedge lode, identical to cor. 4, Scarlet Wedge No. 2 lode, M.S. No. 4429, monumented by person(s) unknown with a rock and concrete column, 4 ft. square on bottom, 30 ins. high, 18 ins. square on top, with fence post in center, projecting 25 ins. from top of concrete, with concrete erroneously mkd. SW COR TILDEN AP on top. This is accepted as the best available evidence of the original cor. position.</p> <p>Not remonumented.</p>
	<p>S. 51°52' W., on line 4-3, Scarlet Wedge No. 2 lode, M.S. No. 4429.</p> <p>Over nearly level land.</p>
9.42	<p>Cor. 3, Scarlet Wedge No. 2 lode, M.S. No. 4429, monumented with a mound of stone, 2 ft. high. This is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	 <p>T4N R3E</p> <p>AP S21 COR 3 SW2 MS4429</p> <p>1996</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

BOOK 5493

Dependent Resurvey of Portions of Certain Mineral Surveys,
T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
13.475	<p>Cor. is located on SE. slope of ridge, bears NE. and SW.</p> <hr/> <p>S. 23°24' E., on a portion of line 3-2, Scarlet Wedge No. 2 lode, M.S. No. 4429.</p> <p>Over nearly level land.</p> <p>Intersect the line bet. secs. 21 and 28.</p> <p>Set a PK nail in the center of Beardsley Rd., bears E. and W. from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, for a reference monument, bears N. 20°40' E., 60.3 ft. dist., with brass cap mkd. RM T4N R3E S21 AP 60.3 FT TO COR 1996, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, cor. 2, Scarlet Wedge No. 2 lode, M.S. No. 4429, monumented with an iron pipe, 1 in. diam., firmly set, projecting 7 ins. above ground, with a screw on iron cap mkd., 4429 and S.W.2.2 on a side, bears S. 23°24' E., 9.265 chs. dist.</p> <p>From this same cor. point, the 1/4 sec. cor. of secs. 21 and 28, hereinbefore described, bears S. 89°22' W., 22.20 chs. dist.</p> <hr/> <p>From a point at the intersection of line 1-2, Scarlet Wedge lode, M.S. No. 4429, with the line bet. secs. 21 and 28.</p> <p>Set a PK nail in the center of Beardsley Rd., bears E. and W. from which</p> <p style="padding-left: 40px;">A concrete curb on the W. side of a median, bearing N. and S., bears N. 51°50' E., 377 lks. dist., mkd. X B0 on top.</p> <p>From this cor. point, cor. 2, Scarlet Wedge lode, identical to cor. 1, Scarlet Wedge No. 2 lode, M.S. No. 4429, monumented with an iron pipe, 1 in. diam., firmly set, projecting 11 ins. above ground with screw on iron cap mkd. 4429 and S.W.2 S.W.2.1 on a side, bears S. 52°01' W., 4.69 chs. dist.</p> <p>N. 52°01' E., on a portion of line 2-1, Scarlet Wedge lode, M.S. No. 4429.</p> <p>Over nearly level land.</p>

BOOK 5493

Dependent Resurvey of Portions of Certain Mineral Surveys,
T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
3.71	<p>Intersect the line bet. secs. 21 and 22.</p> <p>Set a 3 in. spike flush with pavement in S. bound lane of housing division access road, bears E. and W., with top mkd. SURVEY MARKER.</p> <p>from which</p> <p style="padding-left: 40px;">A concrete curb on the W. side of a median, bearing N. and S., bears N. 40°26' E., 6 lks. dist., mkd. X B0 on top. This is the same bearing object as described at the intersection point with the line bet. secs. 21 and 28.</p>
4.70	<p>Cor. 1, Scarlet Wedge lode, M.S. No. 4429, identical to cor. 1, Scarlet lode, M.S. No. 4293, hereinbefore described.</p> <hr/> <p style="text-align: center;">Subdivision of Section 21, T. 4 N., R. 3 E. Gila and Salt River Meridian, Arizona</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 21 and 28.</p> <p>N. 0°20' E., on the N. and S. center line of sec. 21.</p> <p>Over rolling land.</p>
40.05	<p>Point for the center 1/4 sec. cor. of sec. 21 at intersection with the E. and W. center line, monumented by person(s) unknown with a reinforcing bar, 5/8 in. diam., 20 ins. long. firmly set, 4 ins. below the ground, incased in concrete 4 ins. diam., with concrete mkd. LS 5 57.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the ground, with brass cap mkd.</p> <p style="text-align: center;">T4N R3E C 1/4 S 21 1996</p> <p>Deposit the reinforcing rod inside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in center of graded road bears S. and NE.</p> <p>Over rolling land.</p>

BOOK 5493

Subdivision of Section 21,
T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
81.17	The 1/4 sec. cor. of secs. 16 and 21.
	<hr/> <p>From the point for the 1/4 cor. of secs. 21 and 22. S. 89°34' W., on the E. and W. center line of sec. 21. Over rolling land.</p>
8.16	Intersect line 2-3, Mary Ann lode, M.S. No. 3740, hereinbefore described.
8.87	Intersect line 2-3, Union lode, M.S. No. 1139, hereinbefore described.
20.19	Intersect line 5-6, Union lode, M.S. No. 1139, hereinbefore described.
39.52	The center 1/4 sec. cor. of sec. 21.
	Over rolling land.
78.84	<p>The 1/4 sec. cor. of secs. 20 and 21, monumented by the City of Phoenix, with a brass cap, 3 ins. diam., firmly set, flush with asphalt road, with brass cap mkd. CITY OF PHOENIX 19. This is accepted as the best available evidence of the original cor. position.</p> <p>Cor. is located in the center of 7th. St., bears E. and W.</p>
	<hr/> <p style="text-align: center;">Subdivision of Section 22, T. 4 N., R. 3 E. Gila and Salt River Meridian, Arizona</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 22 and 27. N. 0° 48' W., on the N. and S. center line of sec. 22. Over rolling land.</p>
39.76	<p>Point for the center 1/4 sec. cor. of sec. 22, at intersection with the E. and W. center line of the sec., monumented by person(s) unknown with a reinforcing bar, 5/8 in. diam., 18 ins. long. firmly set, 8 ins. in the ground.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone 4 ft. base to top, with brass cap mkd.</p>

28
BOOK 5493

Subdivision of Section 22,
T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
59.85	<p style="text-align: center;">T4N R3E C1/4 S 22 1996</p> <p>Deposit the reinforcing rod inside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on the SW. slope of a prominent rocky knoll.</p> <p>Over rolling land.</p> <p>Point for the center N 1/16 sec. cor of sec. 22, monumented by person(s) unknown with an iron pipe, 1 in. diam., 15 ins. long. firmly set flush with the ground.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
69.895	<p style="text-align: center;">T4N R3E C N1/16 S 22 C 1996</p> <p>Deposit the iron pipe inside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Over rolling land.</p> <p>Point for the center N-N 1/64 sec. cor. of sec. 22., monumented by person(s) unknown with a iron pipe, 1 in. diam., 16 ins. long. firmly set 4 ins. below the ground surface.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4N R3E C N-N1/64 S 22 C 1996</p> <p>Deposit the iron pipe inside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>

BOOK 5493

Subdivision of Section 22,
T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling land.
79.94	The 1/4 sec. cor. of secs. 15 and 22.
	From the 1/4 cor. of secs. 22 and 23.
	S. 89°22' W., on the E. and W. center line of sec. 22.
	Along Rose Garden Lane
20.00	Point for the center E 1/16 sec. cor. of sec. 22, monumented by the City of Phoenix, with a brass cap, 3 ins. diam., firmly set, 1 in. below asphalt surface, with brass cap mkd., CITY OF PHOENIX 19.
	Cor. is located at intersection of Rose Garden Lane, bears E. and W., and 22nd. St., bears N. and S.
20.30	Center of graveled road.
30.00	Point for the center W-E 1/64 sec. cor. of sec. 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. below the graded road surface, with brass cap mkd.
	<p style="text-align: center;">T4N R3E W-E1/64 C——C S 22 C 1996</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
	Cor. is located N., 41 lks. dist. from a block fence, bears E. and W.
40.00	The C 1/4 sec. cor. of sec. 22.
78.24	Intersect line 1-2, Red Dog lode, M.S. No. 3740, hereinbefore described.
80.61	The 1/4 sec. cor. of secs. 21 and 22.
	NE 1/4 Sec. 22
	From the center E 1/16 sec. cor of sec. 22.

Subdivision of Section 22,
T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>N. 0°47' W., on the N. and S. center line of the NE 1/4 of sec. 22.</p>
	<p>Along the center of 22nd. St.</p>
20.07	<p>Point for the NE 1/16 sec. cor. of sec. 22, at intersection with the E. and W. center line of the NE 1/4 of sec. 22, monumented by person(s) unknown with a steel spike, firmly set, 4 ins. below asphalt surface.</p>
	<p>Not remonumented.</p>
	<p>Cor. is located at the intersection of Lone Cactus Dr., bears E. and W., and 22nd. St., bears S.</p>
	<p>Over nearly level land.</p>
20.37	<p>Enter City of Phoenix Water Treatment Plant.</p>
40.15	<p>The point for the E 1/16 sec. cor. of secs. 15 and 22.</p>
	<hr/>
	<p>From the N 1/16 sec. cor. of secs. 22 and 23.</p>
	<p>S. 89°24' W., on the E. and W. center line of the NE 1/4 of sec. 22.</p>
	<p>Along the center of Lone Cactus Dr.</p>
20.00	<p>The NE 1/16 sec. cor. of sec. 22</p>
	<p>Along the center of Lone Cactus Dr.</p>
30.00	<p>Point for the center W-NE 1/64 sec. cor. of sec. 22, monumented by person(s) unknown with a reinforcing bar, 3/8 in. diam., 16 ins. long, firmly set flush with graveled road.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. below the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T4N R3E S22 C-W-NE 1/64 1996</p>
	<p>Deposit the reinforcing rod inside the stainless steel post.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>

BOOK 5493

Subdivision of Section 22,
T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located at the corner of graveled roads, Lone Cactus Dr., bears E. and 21st. St., bears S.</p> <p>Over nearly level land.</p>
30.40	Begin graded road.
35.00	<p>Point for the center W-W-NE 1/256 sec. cor. of sec. 22, monumented by person(s) unknown with an iron pipe, 1 in. diam., 15 ins. long, firmly set flush with graded road.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T4N R3E S22 C-W-W-NE 1/256 1996</p> <p>Deposit the iron pipe inside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in a graded road, bears E. and W.</p> <p>Along center of graded road.</p>
40.00	The center N 1/16 sec. cor. of sec. 22.
	<hr/> <p>From the center W-E 1/64 sec. cor. of sec. 22.</p> <p>N. 0°47' W., on the N. and S. center line of the SW 1/4 of the NE 1/4 of sec. 22.</p> <p>Along a graveled road.</p>
20.08	The center W-NE 1/64 sec. cor. of sec. 22.
	<hr/> <p>From the center W-W-NE 1/256 sec. cor. of sec. 22.</p> <p>N. 0°48' W., on the N and S center line of the SW 1/4 of the NW 1/4 of the NE 1/4 of sec. 22.</p> <p>Over rolling land.</p>

BOOK 5493

Subdivision of Section 22,
T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
10.04	<p>Point for the center W-NW-NE 1/256, monumented by person(s) unknown with a reinforcing rod, 5/8 in. diam., 15 ins. long, firmly set 11 ins. in a 2 ft. square concrete base.</p> <p>Set an aluminum tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in concrete slab, with top mkd.</p> <p style="text-align: center;">T4N R3E S22 C-W-NW-NE 1/256 1996</p> <p>Deposit a magnet in drill hole beneath the brass cap.</p> <p>Raised a mound of stone 4 ft. base, 3 ft. high, W. of cor.</p> <p>Deposit the reinforcing bar, in concrete, in mound of stone.</p>
5.00	<p>S. 89°25' W., on a portion of the E. and W. center line of the NW 1/4 of the NE 1/4 of sec. 22.</p> <p>Over rolling land.</p> <p>The center N-N 1/64 sec. cor. of sec. 22.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The section lines between Sections 21 and 28 and Sections 22 and 27 is along the center of Beardsley Rd.</p> <p>The terrain consists of scattered palo verde, grease wood and bunch grass. The average elevation is 1500 feet above sea level.</p> <p>There is extensive occupancy in the area.</p>

BOOK 5493

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Robert J. Lyle	Surveying Technician
Cheryl A. Baier	Surveying Technician

CERTIFICATE OF SURVEY

I, Joe R. Salazar, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 25th day of September, 1996, I have dependently resurveyed a portion of the subdivisional lines and portions of certain mineral surveys, and subdivided sections 21 and 22 in Township 4 North, Range 3 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

MAY 05 1997

(Date)

Joe R. Salazar

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines and portions of certain mineral surveys, and the subdivision of sections 21 and 22 in Township 4 North, Range 3 East, Gila and Salt River Meridian, Arizona, executed by Joe R. Salazar, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

JUN 12 1997

(Date)

Kenny D. Lavender

(Chief Cadastral Surveyor of Arizona)

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 4 N., R. 3 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.

(Date)

(Chief Cadastral Surveyor of Arizona)