

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE
DEPENDENT RESURVEY AND CORRECTIVE DEPENDENT RESURVEY

OF PORTIONS OF THE SUBDIVISIONAL LINES,

THE SUBDIVISION OF SECTION 28,

AND

A METES-AND-BOUNDS SURVEY,

IN

TOWNSHIP 18 SOUTH, RANGE 21 EAST

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY

Stephen K. Hansen

Cadastral Surveyor

Under Special Instructions dated November 19, 1997, approved November 19, 1997, which provided for the surveys included under Group Number 821, and assignment instructions dated November 19, 1997.

Survey Commenced December 2, 1997

Survey Completed December 11, 1997

INDEX DIAGRAM

TOWNSHIP 18 SOUTH, RANGE 21 EAST,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
		7			
30	29	5	28	4	27
31	32	33	34	35	36

Subdivision of Section 28
Metes-and-Bounds Survey

pp. 8-11
pp. 12-15

T. 18 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>The following field notes describe the dependent resurvey and corrective dependent resurvey of portions of the subdivisional lines, the subdivision of section 28, and a metes-and-bounds survey, in Township 18 South, Range 21 East, Gila and Salt River Meridian, Arizona.</p> <p>Theo. F. White surveyed the subdivisional lines in 1881. William P. Carpender and Stephen K. Hansen dependently resurveyed a portion of the subdivisional lines in 1987-1993.</p> <p>The survey was executed in accordance with the specifications as set forth in the <u>Manual of Surveying Instructions, 1973</u>, and the Special Instructions dated November 19, 1997, for Group No. 821, Arizona.</p> <p>Preliminary to the resurvey, the lines of the previous survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.</p> <p>The directions and distances of all lines were determined by use of Global Positioning System Trimble 4400 real time kinematic survey system, and refer to the true meridian.</p> <p>The geographic position of the corner of sections 27, 28, 33 and 34, as determined from a relative global positioning vector made to U.S. Coast and Geodetic Survey Triangulation station "CURTIS 1946", with published latitude of 31°51'04.9622" N., and longitude of 110°11'56.7164" W., NAD 83(1992), is as follows:</p> <p>Latitude: 31°49'56.92" N. Longitude: 110°11'48.14" W. NAD 83</p> <p>The mean magnetic declination of 11 1/2°, was derived from the U.S. Geological Survey computer program MAGPOINT, utilizing the Regional Magnetic Field Model for Epoch 1995 for the dates of survey.</p>
--------	--

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">Restoring the survey executed by Theo. F. White in 1881</p> <hr style="width: 20%; margin: auto;"/> <p>Beginning at the cor. of secs. 27, 28, 33 and 34, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 8 ins. below the surface of ground, with brass cap mkd. T18S R21E S28 S27 S33 S34 1988. Add the marks 1997 to the brass cap.</p> <p>from which the 1987-93 reference monument</p> <p style="padding-left: 40px;">An aluminum post, 3/4 in. diam., firmly set, projecting 12 ins. above ground, bears S. 45°58' W., 41.4 ft. dist., with aluminum cap mkd. RM T18S R21E S33 41.4 FT TO COR. 1988, and an arrow pointing to the cor.</p> <p>From this cor. point, an iron pipe, 2 ins. diam., firmly set, projecting 12 ins. above ground, bears N. 89°30' W., 30.3 ft. dist., with lead cap mkd. 27 28 33 34 30.00' EAST, and an arrow pointing to the cor., as identified in the 1987-93 resurvey.</p> <p>Cor. is located in the center of Curtis Flat road, graded dirt surfaced, bears N. and S.</p> <p>N. 0°03' W., bet. secs. 27 and 28, along the center of Curtis Flat road.</p> <p>40.00 The 1/4 sec. cor. of secs. 27 and 28, monumented by Robert Gregg Dodson, R.L.S. 13056, with an iron pipe, 3/4 in. diam., firmly set, 2 ins. below the surface of ground, with aluminum cap mkd. COCHISE COUNTY 1/4 COR S28 S27 LS 13056 T18SR21E. This is consistent with accepted monuments to the south of this position, in relation to the center of Curtis Flat road, and right-of-way widths, and is accepted as the best available evidence of the original cor. position.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set, 19 ins. in the ground, for a reference monument, bears S. 58°50' E., 35.1 ft. dist., with brass cap mkd. RM T18S R21E S27 35.1 FT TO 1/4 COR 1997, and an arrow pointing to the cor.</p> <p>From this cor. point, an iron pipe, 1 in. diam., firmly set, on the E. side of a cor. of barbed wire fences extending N., S., and W., projecting 2 ins. above ground, bears N. 89°19' W., 30.1 ft. dist., with a rebar, 5/8 in. diam., firmly set, 3 ins. below the surface of ground, alongside and E. of the iron pipe.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located in the center of Curtis Flat road, graded dirt surfaced, bears N. and S.</p> <hr/> <p>N. 0°19' W., beginning new measurement.</p>
40.02	<p>The cor. of secs. 21, 22, 27 and 28, monumented with and "X" chiseled in a concrete curb, as described in the 1987-93 resurvey, on the W. edge of Curtis Flat road.</p> <p>from which the 1987-93 reference monuments</p> <p>An aluminum post, 3/4 in. diam. firmly set, projecting 12 ins. above ground, bears N. 56°22' E., 53.3 ft. dist., with aluminum cap mkd. RM T18S R21E S22 53.3 FT TO COR 1988, with an arrow pointing to the cor.</p> <p>An aluminum post, 3/4 in. diam. firmly set, projecting 10 ins. above ground, bears S. 50°10' E., 59.4 ft. dist., with aluminum cap mkd. RM T18S R21E S27 59.4 FT TO COR 1988, with an arrow pointing to the cor.</p> <p>An aluminum post, 3/4 in. diam. firmly set, projecting 6 ins. above ground, bears S. 23°49' W., 43.0 ft. dist., with aluminum cap mkd. RM T18S R21E S28 43.0 FT TO COR 1988, with an arrow pointing to the cor.</p> <p>An aluminum post, 3/4 in. diam. firmly set, projecting 2 ins. above ground, bears N. 43°29' W., 25.9 ft. dist., with aluminum cap mkd. RM T18S R21E S21 25.9 FT TO COR 1988, with an arrow pointing to the cor.</p>
	<hr/> <p>Restoring the resurvey executed by William P. Carpender and Stephen K. Hansen in 1987-93</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T18S R21E S29 S28 S32 S33 1988. Add the marks 1997 to the brass cap.</p> <p>from which the 1987-93 reference monuments</p> <p>An aluminum post, 3/4 in. diam., firmly set, projecting 4 ins. above ground, bears N. 44°30' E., 76.8 ft. dist., with aluminum cap mkd. RM T18S R21E S28 76.8 FT TO COR.1988, and an arrow pointing to the cor.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>An aluminum post, 3/4 in. diam., firmly set, projecting 4 ins. above ground, bears S. 72°56' E., 64.4 ft. dist., with aluminum cap mkd. RM T18S R21E S33 64.4 FT TO COR.1988, and an arrow pointing to the cor.</p> <p>From this cor. point, an iron pipe, 2 1/4 ins. diam., firmly set in cement, projecting 25 ins. above ground, with an iron pipe cap, bears S. 25°58' E., 88 lks. dist., as identified in the 1987-93 resurvey.</p> <p>N. 0°09' E., bet. secs. 28 and 29.</p>
16.85	Point for AP 9, hereinafter described.
20.10	<p>The S. 1/16 sec. cor. of secs. 28 and 29, monumented with a magnet in a 1 x 1 x 2 5/8 in. white plastic case, 28 ins. below the surface of ground, there is no remaining evidence of the stainless steel post set in the 1987-1993 resurvey.</p> <p>At the corner point, and over the existing magnet</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T18S R21E S 1/16 S29 S28 1997</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°09' E., beginning new measurement.</p>
20.10	<p>The 1/4 sec. cor. of secs. 28 and 29, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with a mound of stone, 3 ft. base, 1 1/2 ft. high to the W., with brass cap mkd. T18S R21E 1/4 S29 S28 1988. Add the marks 1997 to the brass cap.</p> <p>from which the 1987-1993 bearing tree</p> <p style="text-align: center;">A multi-trunked mesquite, bears S. 4 1/2° E., 133 lks. dist., no visible marks.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°03' E., beginning new measurement.</p>
18.57	<p>A witness point, set in the 1987-1993 survey, monumented with an aluminum post, 3/4 in. diam., firmly set, projecting 4 ins. above ground, with aluminum cap mkd. T18S R21E WP S29 S28 1988. Add the marks 1997 to the aluminum cap.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
19.92	Point for the N. 1/16 sec. cor. of secs. 28 and 29. Not monumented.
24.90	<p>Point for the S-N-N 1/256 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T18S R21E S-N-N 1/256 S29 S28 1997</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 32 lks. E. of a fence, 4 strand barbed wire, bears N. and S.</p>
29.88	Point for the N-N 1/64 sec. cor. of secs. 28 and 29. Not monumented.
39.84	The cor. of secs. 20, 21, 28 and 29, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. T18S R21E S20 S21 S29 S28 1988. Add the marks 1997 to the brass cap.
	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N. 89°22' W., bet. secs. 21 and 28., correcting the 1987-93 dependent resurvey.</p>
39.76	<p>Point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>From this point, the 1/4 sec. cor. of secs. 21 and 28 reestablished in the 1987-93 dependent resurvey, bears S. 1°03' W., 0.028 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T18S R21E 1/4 S21 S28 1988.</p> <p>I remove and reset the stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T18S R21E S21 1/4 ——— S28 1997 1988</p>
59.64	<p>Cor. is located in a barbed wire fence, 4 strand, bears N. and S.</p> <p>Point for the W. 1/16 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T18S R21E S21 W 1/16 ——— S28 1997</p>
69.58	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 39 lks. N. of a cor. of 4 strand barbed wire fences extending N., E., and S.</p> <p>Point for the W-W 1/64 sec. cor. of secs. 21 and 28. Not monumented.</p>
79.52	<p>The cor. of secs. 20, 21, 28 and 29.</p>
<hr/> <p>Subdivision of Section 28, T. 18 S., R. 21 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
19.80	<p>From the 1/4 sec. cor. of secs. 28 and 33, monumented with an aluminum post, 3/4 ins. diam., firmly set, 4 ins. below the surface of ground, with aluminum cap mkd. T18S R21E S28 1/4 S33 1988. Add the marks 1997 to the aluminum cap.</p> <p>Cor. is located in a track road.</p> <p>N. 0°03' W., on the N. and S. center line of sec. 28.</p> <p>Point for AP 4, hereinafter described.</p>
20.05	<p>Point for the center S. 1/16 sec. cor. of sec. 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 28,
T. 18 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T18S R21E C S 1/16 S28 C 1997
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 6 lks. W. of a woven wire fence, bears N. and S.
40.10	Point for the center 1/4 sec. cor. of sec. 28, at intersection with the E. and W. center line of sec. 28. Not monumented.
	From this point, a cor. of barbed wire fences extending N., S. and E., bears S. 4 1/2° W., 18 lks. dist.
60.06	Point for the center N. 1/16 sec. cor. of sec. 28. Not monumented.
80.02	The 1/4 sec. cor. of secs. 21 and 28.
	<hr/> From the 1/4 sec. cor. of secs. 27 and 28. N. 89°14' W., on the E. and W. center line of sec. 28.
39.96	The point for the center 1/4 sec. cor. of sec. 28.
59.87	Point for the center W. 1/16 sec. cor. of sec. 28. Not monumented.
79.78	The 1/4 sec. cor. of secs. 28 and 29.
	<hr/> SW 1/4
	From the center S. 1/16 sec. cor. of sec. 28. N. 89°19' W., on the E. and W. center line of the SW 1/4 of sec. 28.
36.90	Point for AP 2, hereinafter described.
39.90	The S. 1/16 sec. cor. of secs. 28 and 29.

Subdivision of Section 28,
T. 18 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>NW 1/4</p> <hr style="width: 20%; margin: auto;"/>
	<p>From the point for the center W. 1/16 sec. cor. of sec. 28. North, on the N. and S. center line of the NW 1/4 of sec. 28.</p>
19.94	<p>Point for the NW 1/16 sec. cor. of sec. 28, at intersection with the E. and W. center line of the NW 1/4 of sec. 28. Not monumented.</p>
29.91	<p>Point for the center N-NW 1/64 sec. cor. of sec. 28, falls in the bed of the San Pedro River, where it is impracticable to establish a permanent monument.</p>
	<p>From this point the point selected for a witness cor. to the N-NW 1/64 sec. cor. of sec. 28, bears N. 65°53' W., 1.41 chs. dist.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd. WC T18S R21E S28 C-N-NW 1/64 1997, with an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
39.88	<p>The W. 1/16 sec. cor. of secs. 21 and 28.</p> <hr/>
	<p>From the point for the center N. 1/16 sec. cor. of sec. 28. N. 89°18' W., on the E. and W. center line of the NW 1/4 of sec. 28.</p>
19.90	<p>The point for the NW 1/16 sec. cor. of sec. 28.</p>
29.85	<p>Point for the center W-NW 1/64 sec. cor. of sec. 28. Not monumented.</p>
39.80	<p>The point for the N. 1/16 sec. cor. of secs. 28 and 29.</p> <hr/>
	<p>From the point for the center W-NW 1/64 sec. cor. of sec. 28. N. 0°01' E., on the N. and S. center line of the NW 1/4 of the NW 1/4 of sec. 28.</p>
4.98	<p>Point for the center S-NW-NW 1/256 sec. cor. of sec. 28.</p>

Subdivision of Section 28,
T. 18 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T18S R21E S28 C-S-NW-NW 1/256 1997</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
9.96	<p>Point for the NW-NW 1/64 sec. cor. of sec. 28, at intersection with the E. and W. center line of the NW 1/4 of the NW 1/4 of sec. 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T18S R21E S28 NW-NW 1/64 1997</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
19.92	<p>The point for the W-W 1/64 sec. cor. of secs. 21 and 28.</p>
9.95	<p>From the center N-NW 1/64 sec. cor. of sec. 28.</p> <p>N. 89°20' W., on the E. and W. center line of the NW 1/4 of the NW 1/4 of sec. 28.</p> <p>The NW-NW 1/64 sec. cor. of sec. 28.</p>
19.90	<p>The point for the N-N 1/64 sec. cor. of secs. 28 and 29.</p>
9.95	<p>From the center S-NW-NW 1/256 sec. cor. of sec. 28.</p> <p>N. 89°19' W., on the E. and W. center line of the SW 1/4 of the NW 1/4 of the NW 1/4 of sec. 28.</p> <p>The S-N-N 1/256 sec. cor. of secs. 28 and 29.</p>



Metes-and-Bounds Survey,
T. 18 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>The following metes-and-bounds survey is based upon a general warranty deed of Tract A401-004, FEE # 921127597, recorded in the Cochise County Courthouse, dated the 9th of November, 1992.</p> <hr/> <p>From AP 1, identical with the 1/4 sec. cor. of secs. 28 and 29, hereinbefore described.</p> <p>S. 8°19' E., on line 1-2.</p> <p>20.35 Point for AP 2, on the E. and W. center line of the SW 1/4 of sec. 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div data-bbox="841 800 1003 982" style="text-align: center;"> <p>T18S R21E S28 S — — S AP2 1997</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 50 lks. SE of a pond.</p> <hr/> <p>S. 89°19' E., on line 2-3, along the E. and W. center line of the SW 1/4 of sec. 28.</p> <p>36.90 AP 3, identical with the center S. 1/16 sec. cor. of sec. 28, hereinbefore described.</p> <hr/> <p>S. 0°03' E., on line 3-4, along the N. and S. center line of sec. 28.</p> <p>0.25 Point for AP 4, on the N. and S. center line of sec. 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>

Metes-and-Bounds Survey,
T. 18 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
30.00	<div data-bbox="824 283 993 504" data-label="Diagram"> </div> <p data-bbox="397 535 1347 598">Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p data-bbox="397 630 1437 693">Cor. is located 20 lks. N. of the center line of an improved dirt road, bears E. and W.</p> <div data-bbox="714 714 1088 735" data-label="Diagram"> </div> <p data-bbox="397 756 690 787">West, on line 4-5.</p> <p data-bbox="397 819 641 850">Point for AP 5.</p> <p data-bbox="397 882 1339 945">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 32 ins. in the ground, with brass cap mkd.</p>
1.87	<div data-bbox="841 976 993 1197" data-label="Diagram"> </div> <p data-bbox="397 1228 1347 1291">Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p data-bbox="397 1323 1372 1386">Cor. is located in the center of an improved dirt road, bears E. and W.</p> <div data-bbox="714 1407 1088 1428" data-label="Diagram"> </div> <p data-bbox="397 1449 706 1480">South, on line 5-6.</p> <p data-bbox="397 1512 641 1543">Point for AP 6.</p> <p data-bbox="397 1575 1339 1638">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 29 ins. in the ground, with brass cap mkd.</p>
	<div data-bbox="841 1669 993 1869" data-label="Diagram"> </div>

Metes-and-Bounds Survey,
T. 18 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
2.50	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on the E. edge of an improved dirt road, bears NE and SW, and W. of an irrigation ditch, 8 ft. wide, 2 ft. deep, drains SW.</p> <hr/> <p>West, on line 6-7, through mesquite thickets.</p> <p>Point for AP 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T18S R21E S28 AP7</p>  <p>1997</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <hr/> <p>South, on line 7-8, through mesquite thickets.</p>
1.12	<p>Point for AP 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T18S R21E S28 AP8</p>  <p>1997</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <hr/> <p>N. 86°17' W., on line 8-9.</p>
7.43	<p>Point for AP 9, on the line bet. secs. 28 and 29.</p>

Metes-and-Bounds Survey,
T. 18 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located in a cultivated field.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p>The area of the survey is about 2 miles southerly from Saint David, Arizona. Access is by way of Arizona Highway 80.</p> <p>Elevation is about 3600 to 3900 feet above sea level.</p> <p>Vegetation consists of mesquite, creosote, and catclaw, as well as various grasses in the lower and wetter areas.</p> <p>Principal uses of the area are cattle grazing, farming, and recreational activities.</p>
--------	--

UNITED STATES
 DEPARTMENT OF THE INTERIOR
 BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
W. William Foster	Surveying Technician
Geoffrey A. Graham	Surveying Technician
Cheryl A. Hansen	Surveying Technician
Robert J. Lyle	Surveying Technician
Mark S. Searles	Surveying Technician

CERTIFICATE OF SURVEY

I, Stephen K. Hansen, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 19th day of November, 1997, I have dependently resurveyed and corrected portions of the subdivisinal lines, subdivided section 28, and performed a metes-and-bounds survey in Township 18 South, Range 21 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

1/28/98

(Date)

Stephen K. Hansen

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the dependent resurvey and corrective dependent resurvey of portions of the subdivisinal lines, the subdivision of section 28, and a metes-and-bounds survey in Township 18 South, Range 21 East, Gila and Salt River Meridian, Arizona, executed by Stephen K. Hansen, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JAN 29 1998

(Date)

Kenny D. Ravnikar

(Chief Cadastral Surveyor of Arizona)

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 18 S., R. 21 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.

(Date)

(Chief Cadastral Surveyor of Arizona)