

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES  
OF THE

---

DEPENDENT RESURVEY OF

---

A PORTION OF THE SUBDIVISIONAL LINES

---

AND

---

THE METES-AND-BOUNDS SURVEY

---

IN

---

SECTIONS 11, 12 AND 14,

---

TOWNSHIP 6 SOUTH, RANGE 26 EAST

---

Of the Gila and Salt River Meridian,  
In the State of Arizona

EXECUTED BY  
Gordon R. Bube1, Cadastral Surveyor

---

Under Special Instructions dated January 29, 1999, approved January 29, 1999, which provided for the surveys included under Group Number 838 and assignment instructions dated January 29, 1999.

Survey commenced February 8, 1999  
Survey completed February 24, 1999

INDEX DIAGRAM

TOWNSHIP 6 SOUTH, RANGE 26 EAST,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Metes-and-Bounds Survey in Secs. 11, 12 and 14

pp. 8-23

## T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and the metes-and-bounds surveys in sections 11, 12 and 14, Township 6 South, Range 26 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this resurvey is as follows: In 1895-1896, Philip Contzen surveyed the subdivisional lines. In 1960, Dell Cazier, Glen B. Hatch and Eldon W. Sibley, dependently resurveyed the subdivisional lines. In 1976, Harry K. Smith and Paul L. Reeves dependently resurveyed a portion of the east boundary and a portion of the subdivisional lines and surveyed Tract Nos. 37 and 38.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated January 29, 1999, for Group No. 838, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The exterior boundaries of certain mining claim locations known as the Melody Claims located May 24, 1961, July 29, 1976, and August 13, 1980, controlled the metes-and-bounds survey in sections 11, 12, and 14. A search was made for all location corners. The NW cor. of Melody 6A, identical with the NE cor. of Melody 4A, the NW cor. of Melody 4A, identical with the NE cor. of Melody 2A, the NE cor. of Melody 18, identical with the NW cor. of Melody #32, and the SE cor. of Melody #31 were not recovered.


The distance and directions of all lines were determined by NAVSTAR GPS, using real time kinematic techniques, and refer to horizontal distances and the true meridian. Trimble model 4400 GPS receivers were utilized to obtain the observables.

The geographic position of the 1/4 sec. cor. of secs. 13 and 14 was determined by NAVSTAR GPS, using the technique of real time kinematic positioning. United States Soil Erosion Service triangulation station "THATCHER 1935" was used as the control station. The coordinates refer to the top of the monument.

Latitude 32°54'38.53" N. Longitude 109°38'52.32" W. NAD83(1992)

The mean magnetic declination of 11 1/2° E. was derived from U.S. Geological Survey computer program MAGPOINT, utilizing the Regional Magnetic Field Model for Epoch 1995 for the dates of the survey.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">Restoring the resurvey executed by Dell Cazier, Glen B. Hatch and Eldon W. Sibley in 1960</p> <hr style="width: 20%; margin: auto;"/>
10.46	<p>Beginning at the 1/4 sec. cor. of secs. 13 and 14, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 17 ins. above ground, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd. T6S R26E 1/4 S14 S13 1960.</p> <p>Add the marks 1999 to the brass cap.</p> <p>N. 0°05' W., bet. secs. 13 and 14.</p> <p>Ascend over rolling land, through scattered creosote.</p> <p>Point for AP 16, sec. 14, of the metes-and-bounds survey, at intersection with the easterly side line of Melody #31 mining claim .</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R26E S14 S13</p>  <p>AP 16 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the NE location cor. of Melody #31 mining claim, identical with SE location cor. of Melody #32 mining claim, bears N. 32°41' E., 1.11 chs. dist., monumented with a mound of stone, 3 ft. base, 1 1/2 ft. high, with a weathered wood post, 2 x 2 ins., lying loose nearby.</p>
36.24	<p>Point for AP 1, sec. 14 of the metes-and-bounds survey, at intersection with the northerly end line of Melody 18 mining claim.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p>



Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.16	<div data-bbox="844 289 987 478" style="text-align: center;"> <p>T6S R26E AP 1 S14   S13 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the NE location cor. of Melody #32 mining claim, bears S. 62°38' E., 12.31 chs. dist., monumented with a mound of stone, 2 ft. base, 2 ft. high.</p> <p>The cor. of secs. 11, 12, 13 and 14, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 14 ins. above ground, in a mound of stone, 3 1/2 ft. base to top, with brass cap mkd. T6S R26E S11 S12 S14 S13 1960.</p> <p>Add the marks 1999 to the brass cap.</p> <p>Cor. is located on the face of a spur, sloping westerly.</p> <hr/> <p>N. 0°37' E., bet. secs. 11 and 12.</p> <p>Descend along the westerly face of spur, through scattered creosote.</p>
16.11	<div data-bbox="836 1459 987 1648" style="text-align: center;"> <p>T6S R26E S11   S12 AP1 AP18 1999</p> </div> <p>Point for AP 1, sec. 12, identical with AP 18, sec. 11, of the metes-and-bounds survey, at intersection with the easterly side line of Melody #15 mining claim.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on the face of a spur, sloping westerly.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.77	<p>The 1/4 sec. cor. of secs. 11 and 12, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 20 ins. above ground, in a mound of stone, 4 ft. base to top, with brass cap mkd. T6S R26E 1/4 S11 S12 1960.</p> <p>Add the marks 1999 to the brass cap.</p> <hr/> <p>N. 0°10' W., beginning new measurement.</p> <p>Over rolling land, through moderate creosote.</p>
8.60	<p>Point for AP 1, sec. 11, identical with AP 6, sec. 12, of the metes-and-bounds survey, at intersection with the northerly end line of Melody 14A mining claim.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div data-bbox="852 930 990 1113" style="text-align: center;"> <p>T6S R26E AP1   AP6 S11   S12 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p>
40.06	<p>The cor. of secs. 1, 2, 11 and 12, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 18 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. T6S R26E S2 S1 S11 S12 1960.</p> <p>Add the marks 1999 to the brass cap.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 89°49' W., bet. secs. 11 and 14.</p> <p>Over rolling land, through moderate creosote.</p>
7.36	<p>Point for AP 3, sec. 14, identical with AP 16, sec. 11, of the metes-and-bounds survey, at intersection with the northerly end line of Melody #20 mining claim.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>



Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.70	<div style="text-align: center;"> <p>T6S R26E</p>  </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>The 1/4 sec. cor. of secs. 11 and 14, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 18 ins. above ground, in a mound of stone, 4 ft. base to top, with brass cap mkd. T6S R26E 1/4 S11 S14 1960.</p> <p>Add the marks 1999 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°47' W., beginning new measurement.</p> <p>Over rolling land, through moderate creosote.</p>
27.05	<p>Point for AP 15, sec. 11, identical with AP 4, sec. 14, of the metes-and-bounds survey in sec. 14, at intersection with the westerly side line of Melody #29 mining claim.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
40.11	<div style="text-align: center;"> <p>T6S R26E</p>  </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 10, 11, 14 and 15, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, in a mound of stone 3 1/2 ft. base, to top, with brass cap mkd. T6S R26E S10 S11 S15 S14 1960.</p> <p>Add the marks 1999 to the brass cap.</p> <p>Cor. is located on the westerly edge of a bladed road, 15 lks. wide, bears N. and S.</p> <hr style="width: 60%; margin: 10px auto;"/>


Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.08	<p>N. 0°01' E., bet. secs. 10 and 11.</p> <p>Over rolling land, through medium creosote.</p> <p>The 1/4 sec. cor. of secs. 10 and 11, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 24 ins. above ground, in a mound of stone, 4 ft. base to top, with brass cap mkd. T6S R26E 1/4 S10 S11 1960.</p> <p>Add the marks 1999 to the brass cap.</p> <hr/>
40.15	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°21' W., bet. secs. 2 and 11.</p> <p>Over rolling land, through medium creosote.</p> <p>The 1/4 sec. cor. of secs. 2 and 11, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, with a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of the cor., with brass cap mkd. T6S R26E 1/4 S2 S11 1960.</p> <p>Add the marks 1999 to the brass cap.</p> <hr/>
<p style="text-align: center;">Metes-and-Bounds Survey in Sections 11, 12 and 14, T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
<p style="text-align: center;">Section 14</p> <hr/>	
5.81	<p>From AP 1, sec. 14, on the line bet. secs. 13 and 14, hereinbefore described.</p> <p>N. 62°38' W., on line 1-2, sec. 14, along a portion of the northerly end line of Melody 18 mining claim.</p> <p>Point for AP 2, sec. 14, identical with the NW location cor. of Melody 18 mining claim, and the NE location cor. of Melody #20 mining claim, monumented with a mound of stone, 4 ft. base, 3 ft. high.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, at the center of the mound of stone, 7 ft. base, to top, with brass cap mkd.</p>




Metes-and-Bounds Survey in Sections 11, 12 and 14,  
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<div style="text-align: center;"> <p>T6S R26E AP2 S14 1999</p>  </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <hr/> <p>N. 60°03' W., on line 2-3, sec. 14, along a portion of the northerly end line of Melody #20 mining claim.</p> <p>2.54 AP 3, sec. 14, identical with AP 16, sec. 11, on the line bet. secs. 11 and 14, hereinbefore described.</p>
	<div style="text-align: center;"> <p>Section 11</p> <hr/> </div> <p>From AP 16, sec. 11, identical with AP 3, sec. 14, on the line bet. secs. 11 and 14.</p> <p>N. 60°03' W., on line 16-17, sec. 11, along a portion of the northerly end line of Melody #20 mining claim.</p> <p>1.86 Point for AP 17, sec. 11, identical with the north end center of Melody #20 mining claim, and the SE location cor. of Melody #15 mining claim, monumented with a mound of stone, 3 ft. base, 2 ft. high.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, at the center of the mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R26E S11  AP17 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the north end center of Melody 22A mining claim, identical with the SW location cor. of Melody #15 mining claim and the SE location cor. of Melody #13 mining claim, bears N. 60°28' W., 9.06 chs., dist., monumented with a mound of stone, 3 ft. base, 2 ft. high.</p> <hr/>


Metes-and-Bounds Survey in Sections 11, 12 and 14,  
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
17.70	<p>N. 31°06' E., on line 17-18, sec. 11, along a portion of the easterly side line of Melody #15 mining claim.</p> <p>AP 18, sec. 11, identical with AP 1, sec. 12, on the line bet. secs. 11 and 12, hereinbefore described.</p>
4.98	<p style="text-align: center;">Section 12</p> <hr/> <p>From AP 1, sec. 12, identical with AP 18, sec. 11, on the line bet. secs. 11 and 12.</p> <p>N. 31°06' E., on line 1-2, sec. 12, along a portion of the easterly side line of Melody #15 mining claim.</p> <p>Point for AP 2, sec. 12, identical with the NE location cor. of Melody #15 mining claim and the SE location cor. of Melody #16 mining claim, monumented with a mound of stone, 4 ft. base, 3 ft. high.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, at the center of the mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R26E</p>  </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on a steep rocky west facing slope.</p>
23.38	<p>N. 31°26' E., on line 2-3, sec. 12, along the easterly side line of Melody #16 mining claim.</p> <p>Point for AP 3, sec. 12, identical with the NE location cor. of Melody #16 mining claim, monumented with a mound of stone, 4 ft. base, 2 ft. high.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, at the center of the mound of stone, 4 ft. base, to top, with brass cap mkd.</p>



Metes-and-Bounds Survey in Sections 11, 12 and 14,  
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<div style="text-align: center;">  <p>T6S R26E S12 AP3 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 60°25' W., on line 3-4, sec. 12, along a portion of the northerly end line of Melody #16 mining claim.</p>
4.60	<p>Point for AP 4, sec. 12, identical with the north end center of Melody #16 mining claim, monumented with a mound of stone, 3 ft. base, 1 ft. high.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, at the center of the mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;">  <p>T6S R26E S12 AP4 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 61°58' W., on line 4-5, sec. 12, along a portion of the northerly end line of Melody #16 mining claim.</p>
4.64	<p>Point for AP 5, sec. 12, identical with the NW location cor. of Melody #16 mining claim and the NE location cor. of Melody 14A mining claim, monumented with a mound of stone, 4 ft. base, 2 1/2 ft. high.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, at the center of the mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;">  <p>T6S R26E S12 AP5 1999</p> </div>

Metes-and-Bounds Survey in Sections 11, 12 and 14,  
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <hr/>
	<p>N. 60°46' W., on line 5-6, sec. 12, along a portion of the northerly end line of Melody 14A mining claim.</p>
4.57	<p>The north end center of Melody 14A mining claim, monumented with a mound of stone, 4 ft. base, 1 1/2 ft. high.</p>
7.38	<p>AP 6, sec. 12, identical with AP 1, sec. 11, on the line bet. secs. 11 and 12, hereinbefore described.</p> <hr/>
	<p style="text-align: center;">Section 11</p> <hr/>
	<p>From AP 1, sec. 11, identical with AP 6, sec. 12, on the line bet. secs. 11 and 12.</p>
	<p>N. 60°46' W., on line 1-2, sec. 11, along a portion of the northerly end line of Melody 14A mining claim.</p>
1.73	<p>Point for AP 2, sec. 11, identical with the NW location cor. of Melody 14A mining claim, and the NE location cor. of Melody 12A mining claim, monumented with a mound of stone, 4 ft. base, 2 1/2 ft. high.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, at the center of the mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">  </p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <hr/>
	<p>N. 60°11' W., on line 2-3, sec. 11, along the northerly end line of Melody 12A mining claim.</p>
4.58	<p>The north end center of Melody 12A mining claim, monumented with a mound of stone, 4 ft. base, 2 ft. high.</p>
9.09	<p>Point for AP 3, sec. 11, identical with the NW location cor. of Melody 12A mining claim, and the NE location cor. of Melody 10 mining claim, monumented with a mound of stone, 4 ft. base, 1 1/2 ft. high.</p>

Metes-and-Bounds Survey in Sections 11, 12 and 14,  
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, at the center of the mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/>
4.55	<p>N. 59°22' W., on line 3-4, sec. 11, along the northerly end line of Melody 10 mining claim.</p> <p>The north end center of Melody 10 mining claim, monumented with a mound of stone, 4 ft. base, 2 ft. high.</p>
9.03	<p>Point for AP 4, sec. 11, identical with the NW location cor. of Melody 10 mining claim, and the NE location cor. of Melody 8 mining claim, monumented with a mound of stone, 4 ft. base, 2 1/2 ft. high.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, at the center of the mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/>
4.56	<p>N. 57°42' W., on line 4-5, sec. 11, along the northerly end line of Melody 8 mining claim.</p> <p>The north end center of Melody 8 mining claim, monumented with a mound of stone, 3 ft. base, 1 1/2 ft. high.</p>
9.15	<p>Point for AP 5, sec. 11, identical with the NW location cor. of Melody 8 mining claim, and the NE location cor. of Melody 6A mining claim, monumented with a mound of stone, 4 ft. base, 1 1/2 ft. high.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 11 ins. in the ground, at the center of the mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p>

Metes-and-Bounds Survey in Sections 11, 12 and 14,  
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T6S R26E AP5 S11 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/>
	<p>N. 58°54' W., on line 5-6, sec. 11, along the northerly end line of Melody 6A mining claim, and a portion of the northerly end line of Melody 4A mining claim.</p>
4.52	<p>The north end center of Melody 6A mining claim, monumented with a mound of stone, 4 ft. base, 2 ft. high.</p>
13.62	<p>Point for AP 6, sec. 11, identical with the north end center of Melody 4A mining claim, monumented with a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, at the center of the mound of stone, 5 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T6S R26E AP6 S11 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/>
	<p>N. 59°38' W., on line 6-7, sec. 11, along a portion of the northerly end line of Melody 4A mining claim, and a portion of the northerly end line of Melody 2A mining claim.</p>
9.16	<p>Point for AP 7, sec. 11, identical with the north end center of Melody 2A mining claim, monumented with a mound of stone, 4 ft. base, 1 1/2 ft. high.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, at the center of the mound of stone, 5 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T6S R26E AP7 S11 1999</p>



Metes-and-Bounds Survey in Sections 11, 12 and 14,  
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
4.58	<p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <hr/> <p>N. 59°18' W., on line 7-8, sec. 11, along a portion of the northerly end line of Melody 2A mining claim.</p> <p>Point for AP 8, sec. 11, identical with the NW location cor. of Melody 2A mining claim, monumented with a mound of stone, 4 1/2 ft. base, 2 1/2 ft. high.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, at the center of the mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R26E AP8 /S11 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <hr/>
22.41	<p>S. 31°03' W., on line 8-9, sec. 11, along the westerly side line of Melody 2A mining claim.</p> <p>Point for AP 9, sec. 11, identical with the SW location cor. of Melody 2A mining claim, and the NW location cor. of Melody #1 mining claim, monumented with a mound of stone, 3 1/2 ft. base, 2 1/2 ft. high.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 11 ins. in the ground, at the center of the mound of stone, 5 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R26E AP9 /S11 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <hr/> <p>S. 31°02' W., on line 9-10, sec. 11, along the westerly side line of Melody #1 mining claim.</p>

Metes-and-Bounds Survey in Sections 11, 12 and 14,  
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
22.76	<p>Point for AP 10, sec. 11, identical with the SW location cor. of Melody #1 mining claim, monumented with a mound of stone, 4 ft. base, 2 1/2 ft. high, with a weathered 2 x 2 ins., squared wood post, lying loose nearby.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 9 ins. in the ground, at the center of the mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div data-bbox="852 577 990 735" style="text-align: center;"> <p>T6S R26E AP10 S11 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 57°29' E., on line 10-11, sec. 11, along the southerly end line of Melody #1 mining claim.</p>
4.45	<p>The south end center of Melody #1 mining claim, monumented with a mound of stone, 2 1/2 ft. base, 1 ft. high.</p>
8.99	<p>Point for AP 11, sec. 11, identical with the SE location cor. of Melody #1 mining claim, and the SW location cor. of Melody #3 mining claim, monumented with a mound of stone, 4 ft. base, 2 ft. high, with a weathered 2 x 2 ins., squared wood post, lying loose nearby.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 11 ins. in the ground, at the center of the mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div data-bbox="836 1396 1015 1533" style="text-align: center;"> <p>T6S R26E S11 AP11 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 58°07' E., on line 11-12, sec. 11, along the southerly end line of Melody #3 mining claim.</p>
4.58	<p>The south end center of Melody #3 mining claim, monumented with a mound of stone, 3 ft. base, 1 ft. high, with a weathered 2 x 2 ins., squared wood post, lying loose nearby.</p>



Metes-and-Bounds Survey in Sections 11, 12 and 14,  
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
9.15	<p>Point for AP 12, sec. 11, identical with the SE location cor. of Melody #3 mining claim, and the SW location cor. of Melody #5 mining claim, monumented with a mound of stone, 3 1/2 ft. base, 2 1/2 ft. high, with a weathered 2 x 2 ins., squared wood post, lying loose nearby.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground, at the center of the mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;">  <p>T6S R26E S11 AP12 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 57°26' E., on line 12-13, sec. 11, along a portion of the southerly end line of Melody #5 mining claim.</p>
4.59	<p>Point for AP 13, sec. 11, identical with the south end center of Melody #5 mining claim, and the NW location cor. of Melody 30A mining claim, monumented with a mound of stone, 4 ft. base, 2 ft. high, with a weathered 2 x 2 ins., squared wood post, lying loose nearby.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground, at the center of the mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;">  <p>T6S R26E S11 AP13 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the SE location cor. of Melody #5 mining claim, identical with the SW location cor. of Melody 7 mining claim, and the north end center of Melody 30A mining claim, bears S. 57°39' E., 4.57 chs., dist., monumented with a mound of stone, 4 1/2 ft. base, 1 1/2 ft. high.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 26°16' W., on line 13-14, sec. 11, along the westerly side line of Melody 30A mining claim.</p>



Metes-and-Bounds Survey in Sections 11, 12 and 14,  
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
19.43	<p>Point for AP 14, sec. 11, identical with the SW location cor. of Melody 30A mining claim, and the NW location cor. of Melody #29 mining claim, monumented with a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, at the center of the mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T6S R26E AP14 / S11 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>S. 34°45' W., on line 14-15, sec. 11, along a portion of the westerly side line of Melody #29 mining claim.</p>
10.64	<p>AP 15, sec. 11, identical with AP 4, sec. 14, on the line bet. secs. 11 and 14, hereinbefore described.</p> <hr style="width: 60%; margin: 10px auto;"/>
	<p style="text-align: center;">Section 14</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>From AP 4, sec. 14, identical with AP 15, sec. 11, on the line bet. secs. 11 and 14.</p>
	<p>S. 34°45' W., on line 4-5, sec. 14, along a portion of the westerly side line of Melody #29 mining claim.</p>
12.10	<p>Point for AP 5, sec. 14, identical with the SW location cor. of Melody #29 mining claim, monumented with a mound of stone, 3 1/2 ft. base, 2 ft. high.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, at the center of the mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T6S R26E AP5 / S14 1999</p>



Metes-and-Bounds Survey in Sections 11, 12 and 14,  
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <hr/>
	<p>S. 58°23' E., on line 5-6, sec. 14, along the southerly end line of Melody #29 mining claim.</p>
4.55	<p>The south end center of Melody #29 mining claim, monumented with a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high.</p>
9.08	<p>Point for AP 6, sec. 14, identical with the SE location cor. of Melody #29 mining claim, and the SW location cor. of Melody #27 mining claim, monumented with a mound of stone, 4 ft. base, 2 1/2 ft. high.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, at the center of the mound of stone, 5 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">  </p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <hr/>
	<p>S. 58°20' E., on line 6-7, sec. 14, along the southerly end line of Melody #27 mining claim.</p>
4.54	<p>The south end center of Melody #27 mining claim, monumented with a mound of stone, 4 ft. base, 2 ft. high.</p>
9.10	<p>Point for AP 7, sec. 14, identical with the SE location cor. of Melody #27 mining claim, and the SW location cor. of Melody #25 mining claim, monumented with a mound of stone, 4 ft. base, 2 1/2 ft. high.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, at the center of the mound of stone, 6 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">  </p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <hr/>




Metes-and-Bounds Survey in Sections 11, 12 and 14,  
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
4.55	<p>S. 58°05' E., on line 7-8, sec. 14, along the southerly end line of Melody #25 mining claim.</p> <p>The south end center of Melody #25 mining claim, monumented with a mound of stone, 5 ft. base, 2 1/2 ft. high.</p> <p>Point for AP 8, sec. 14, identical with the SE location cor. of Melody #25 mining claim, and the SW location cor. of Melody #23 mining claim, monumented with a mound of stone, 5 1/2 ft. base, 2 ft. high, with a weathered 2 x 2 ins., squared wood post, lying loose nearby.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, at the center of the mound of stone, 6 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;">  <p>T6S R26E S14 AP8 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <hr/>
4.53	<p>S. 58°20' E., on line 8-9, sec. 14, along a portion of the southerly end line of Melody #23 mining claim.</p> <p>Point for AP 9, sec. 14, identical with the south end center of Melody #23 mining claim, monumented with a mound of stone, 4 ft. base, 2 ft. high.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 3 ins. in the ground, to bedrock, at the center of the mound of stone, 7 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;">  <p>T6S R26E S14 AP9 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <hr/> <p>S. 59°32' E., on line 9-10, sec. 14, along a portion of the southerly end line of Melody #23 mining claim.</p>

Metes-and-Bounds Survey in Sections 11, 12 and 14,  
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
4.57	<p>Point for AP 10, sec. 14, identical with the SE location cor. of Melody #23 mining claim, and the SW location cor. of Melody #21 mining claim, monumented with a mound of stone, 4 ft. base, 3 ft. high, with a weathered 2 x 2 ins., squared wood post, lying loose nearby.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, at the center of the mound of stone, 5 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R26E S14 AP10 1999</p>  </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 58°41' E., on line 10-11, sec. 14, along a portion of the southerly end line of Melody #21 mining claim.</p>
4.53	<p>Point for AP 11, sec. 14, identical with the south end center of Melody #21 mining claim, monumented with a mound of stone, 4 ft. base, 2 1/2 ft. high.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, at the center of the mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R26E S14 AP11 1999</p>  </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 58°12' E., on line 11-12, sec. 14, along a portion of the southerly end line of Melody #21 mining claim.</p>
4.57	<p>Point for AP 12, sec. 14, identical with the SE location cor. of Melody #21 mining claim, and the SW location cor. of Melody 19 mining claim, monumented with a mound of stone, 5 ft. base, 2 ft. high.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, at the center of the mound of stone, 5 ft. base, to top, with brass cap mkd.</p>

Metes-and-Bounds Survey in Sections 11, 12 and 14,  
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
4.56	<div style="text-align: center;"> <p>T6S R26E S14 AP12 1999</p>  </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 57°53' E., on line 12-13, sec. 14, along a portion of the southerly end line of Melody 19 mining claim.</p> <p>Point for AP 13, sec. 14, identical with the south end center of Melody 19 mining claim, monumented with a mound of stone, 3 ft. base, 1 1/2 ft. high.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, at the center of the mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>
4.57	<div style="text-align: center;"> <p>T6S R26E S14 AP13 1999</p>  </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 59°49' E., on line 13-14, sec. 14, along a portion of the southerly end line of Melody 19 mining claim.</p> <p>Point for AP 14, sec. 14, identical with the SE location cor. of Melody 19 mining claim, and the SW location cor. of Melody #17 mining claim, monumented with a mound of stone, 4 ft. base, 2 ft. high.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, at the center of the mound of stone, 5 ft. base, to top, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T6S R26E S14 AP14 1999</p>  </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/>

Metes-and-Bounds Survey in Sections 11, 12 and 14,  
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	S. 58°01' E., on line 14-15, sec. 14, along the southerly end line of Melody #17 mining claim, and the southerly end line of Melody #31 mining claim.
4.55	The south end center of Melody #17 mining claim, monumented with a mound of stone 5 ft. base, 2 1/2 ft. high.
9.11	The SE location cor. of Melody #17 mining claim, identical with the SW location cor. of Melody #31 mining claim, monumented with a mound of stone, 5 ft. base, 3 ft. high.
18.20	Point for AP 15, sec. 14, identical with the SE location cor. of Melody #31 mining claim. Reestablished at the projection of the line between the south end center and the SE location cors. of Melody #17 mining claim, at record distance (600 ft.) from the SE location cor; there is no remaining evidence of the original location cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, encircled in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T6S R26E S14 AP15 1999</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	N. 32°41' E., on line 15-16, sec. 14, along a portion of the easterly side line of Melody #31 mining claim.
21.62	AP 16, sec. 14, on the line bet. secs. 13 and 14, hereinbefore described.
	GENERAL DESCRIPTION
	The land encompassed in this survey is located approximately 7 miles northeast of Safford, Arizona. Elevations range from about 3500 to 4000 feet above sea level.
	The vegetation is dominated by creosote, with a scattering of catclaw, prickly pear, cholla and native grasses.
	Access is by way of the San Juan road.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Robert J. Lyle	Surveying Technician
Mark R. Searles	Surveying Technician

CERTIFICATE OF SURVEY

I, Gordon R. Bubel, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 29th day of January, 1999, I have dependently resurveyed a portion of the subdivisional lines and executed the metes-and-bounds survey in sections 11, 12 and 14, Township 6 South, Range 26 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

APRIL 22, 1999  
(Date)

Gordon R. Bubel  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Arizona State Office  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines and the metes-and-bounds survey in sections 11, 12 and 14, Township 6 South, Range 26 East, Gila and Salt River Meridian, Arizona, executed by Gordon R. Bubel, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

May 24, 1999  
(Date)

Kenny D Lavonkar  
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~\_\_\_\_\_~~  
~~(Date)~~

~~\_\_\_\_\_~~  
~~(Chief Cadastral Surveyor of Arizona)~~