

ORIGINAL

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

**FIELD NOTES  
OF THE  
DEPENDENT RESURVEY OF  
A PORTION OF THE EAST BOUNDARY AND  
A PORTION OF THE SUBDIVISIONAL LINES  
AND  
THE SUBDIVISION OF SECTION 25,  
TOWNSHIP 10 NORTH, RANGE 6 WEST,  
OF THE GILA AND SALT RIVER MERIDIAN,  
IN THE STATE OF ARIZONA.**

**EXECUTED BY**

**Gordon R. Bubel, Cadastral Surveyor**

Under Special Instructions dated November 15, 1999, approved November 15, 1999, which provided for the surveys included under Group No. 848, and assignment instructions dated December 2, 1999.

**Survey commenced December 7, 1999**

**Survey completed December 16, 1999**

# INDEX DIAGRAM

TOWNSHIP 10 NORTH      RANGE 6 WEST

<b>6</b>	<b>5</b>	<b>4</b>	<b>3</b>	<b>2</b>	<b>1</b>
<b>7</b>	<b>8</b>	<b>9</b>	<b>10</b>	<b>11</b>	<b>12</b>
<b>18</b>	<b>17</b>	<b>16</b>	<b>15</b>	<b>14</b>	<b>13</b>
<b>19</b>	<b>20</b>	<b>21</b>	<b>22</b>	<b>23</b>	<b>24</b>
<b>30</b>	<b>29</b>	<b>28</b>	<b>27</b>	<b>26</b>	<b>25</b> 5      2 3
<b>31</b>	<b>32</b>	<b>33</b>	<b>34</b>	<b>35</b>	<b>36</b>

Subdivision of Section 25 ..... Pages 5-16

## T. 10 N., R. 6 W., Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes describe the dependent resurvey of a portion of the east boundary and a portion of the subdivisional lines and the subdivision of section 25, T. 10 N., R. 6 W., Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this resurvey is as follows: In 1871, Solomon W. Foreman surveyed a portion of the east boundary. In 1904, John F. Hesse resurveyed a portion of the east boundary and surveyed a portion of the subdivisional lines. In 1916, Theo. O. Johnston and Chas. M. Pidgeon resurveyed a portion of the east boundary. In 1952, Ty White resurveyed a portion of the subdivisional lines. In 1983, Will C. Gaboney and Duane R. Garroure resurveyed a portion of the east boundary.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated November 15, 1999, for Group No. 848, Arizona.

The directions of all lines were determined and distances measured, by the system of differential positioning using Trimble Navigation 4400 Series Global Positioning System receivers utilizing the Real-Time Kinematic technique.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the cor. of secs. 25, 30, 31 and 36 on the east boundary of the township, was determined by the system of differential positioning using the Trimble Navigation 4400 Series Global Positioning System. Second order U. S. Geological Survey triangulation station CONGRESS 1969 was used as the control station. The geographic position is as follows:

Latitude: 34°10'21.65" N.      Longitude: 112°49'26.20" W.  
NAD83(1992)

The mean magnetic declination is 12 1/2° E.

**Dependent Resurvey of a Portion of the East Boundary,  
T. 10 N., R. 6 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">Restoring the resurvey executed by Will C. Gabonay and Duane R. Garoutte, in 1983</p> <hr/> <p>Beginning at the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with an aluminum post, 3/4 in. diam., firmly set, projecting 5 ins. above ground, with aluminum cap mkd. T10N R6W R5W S25 S30 S36 S31 1983.</p> <p>Add the marks 1999 to the aluminum cap.</p> <p>From this cor. point, the cor. of 4 strand barbed wire fences, with fences extending N. and W., bears S. 45° W., 3 lks. dist.</p> <p>From this same cor. point, a wood post, 4 ins. square, firmly set, projecting 5 ft. above ground, bears N. 45° E., 9 lks. dist.</p> <p>N. 0°02' E., bet. secs. 25 and 30, on the E. bdy. of the Tp.</p> <p>Over open, rolling land.</p>
20.02	<p>Point for the S. 1/16 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p align="center">T10N R6W R5W S 1/16 S25   S30 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
30.03	<p>Point for the N-S 1/64 sec. cor. of secs. 25 and 30.</p> <p>Not monumented.</p>
40.04	<p>The 1/4 sec. cor. of secs. 25 and 30, monumented with an aluminum post, 3/4 in. diam., firmly set projecting 5 ins. above ground, with aluminum cap mkd. T10N 1/4 R6W R5W S25 S30 1983.</p> <p>Add the marks 1999 to the aluminum cap.</p> <p>An aluminum washer, 2 ins. diam., mkd. YAVAPAI COUNTY GIS GPS PT # 667 RLS 13190, is attached to the aluminum post.</p> <p>Cor. is located on the W. edge of a pit, 25 lks. diam., 5 ft. deep.</p>

**Dependent Resurvey of a Portion of the East Boundary,  
T. 10 N., R. 6 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this cor. point, the cor. of 4 strand barbed wire fences, with fences extending N., E. and S., bears N. 60° E., 90 lks. dist.</p> <hr/> <p style="text-align: center;"><b>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 10 N., R. 6 W., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p style="text-align: center;">Restoring the resurvey executed by John F. Hesse, in 1904</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°53' W., bet. secs. 25 and 36.</p> <p>Over broken land.</p>
18.37	Overhead telephone line, single wire, bears N. 7° E. and S. 7° W.
18.75	Track road, 12 lks. wide, bears N. and S.
20.01	Point for the E. 1/16 sec. cor. of secs. 25 and 36.
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T10N R6W S25 E 1/16 ——— S36 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 18 lks. S. of a 4 strand barbed wire fence, bears E. and W.</p>
37.55	Center of Martinez Wash, 50 lks. wide, drains SSE.
40.02	<p>Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 10 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T10N R6W S25 1/4 ——— S36 1999</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor.</p>
40.91	<p>A brass disk, 3 ins. diam., set in concrete, flush with the ground, on the easterly R.O.W. of Arizona Highway No. 89, with top mkd. ARIZONA HIGHWAY DEPT. P.O.T. STA. 1393 + 30.27 1969.</p>
	<p>From this point, P.T. station 1390 + 33.49, bears N. 14°42' E., 4.10 chs. dist., monumented with a brass disk, 3 ins. diam., set in concrete flush with the ground, with top mkd. ARIZONA HIGHWAY DEPT. PT STA 1390 + 33.49 1969.</p>
40.92	<p>Easterly R.O.W. fence, 4 strand barbed wire, bears NNE and SSW.</p>
42.48	<p>Center line of Az. Highway No. 89, paved asphalt, 64 lks. wide, bears NNE and SSW.</p>
44.05	<p>A brass disk, 3 ins. diam., set in concrete, projecting 6 ins. above the ground, on the westerly R.O.W. to Arizona Highway No. 89, with top mkd. ARIZONA HIGHWAY DEPT. P.O.T. STA. 1393 + 30.27 1969.</p>
	<p>Monument is located in the westerly R.O.W. fence, 4 strand barbed wire, bears NNE and SSW.</p>
80.04	<p>The cor. of secs. 25, 26, 35 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 15 ins. above ground, in a mound of stone, 2½ ft. base, 1 ft., high, with a mound of stone, 3½ ft. base, 1½ ft. high, W. of cor., with brass cap mkd. T10N R6W S26 S25 S35 S36 1904 1952.</p>
	<p>Add the marks 1999 to the brass cap.</p>
	<p>From this cor. point, a wood post, 4 ins. square, firmly set, projecting 3 ft. above ground, bears N. 55° E., 4 lks. dist.</p>
	<p>From this same cor. point, U.S. Geological Survey triangulation station "CONGRESS 1969", with published latitude of 34°10'32.40813" N. and longitude of 112°51'38.55410" W., NAD83(1992), bears N. 79°21' W., 90.03 chs. dist., monumented with a standard brass disk, 4 ins. diam., cemented flush with</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 10 N., R. 6 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>the surface of granite bedrock, with top of disk mkd. CONGRESS 1969 and a triangle.</p> <hr/> <p align="center">Restoring the resurvey executed by Ty White, in 1952</p> <hr/> <p>N. 0°04' W., bet. secs. 25 and 26.</p> <p>Over broken land.</p>
3.31	Center of A.T. and Sante Fe Railroad track, bears E. and W.
40.23	<p>The 1/4 sec. cor. of secs. 25 and 26, monumented with an iron post, 1 in. diam., firmly set, projecting 19 ins. above ground, in a mound of stone, 3 ft. base, 1½ ft., high, with a mound of stone, 2½ ft. base, 2 ft. high, W. of cor., with brass cap mkd. 1/4 S26 S25 1904 1952.</p> <p>Add the marks T10N R6W 1999 to the brass cap.</p> <p>From this cor. point, a mound of stone, 3 ft. base, 2 ft. high, bears S. 65° E., 11 lks. dist.</p> <hr/> <p align="center"><b>Subdivision of Section 25, T. 10 N., R. 6 W., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of 25 and 36.</p> <p>N. 0°03' W., on the N. and S. center line of sec. 25.</p>
3.38	<p>Intersect the easterly R.O.W. of Az. Highway No. 87.</p> <p>From this point, P.T. station 1390 + 33.49, bears N. 14°42' E., 0.60 chs. dist.</p>
7.78	Intersect the easterly side of Martinez Wash Bridge, on a curve, bears NNE and SSW.
8.73	<p>Center line of Az. Highway No. 87, at Martinez Wash Bridge, on a curve.</p> <p>From this point, center line P.T. station 1390 + 33.49, bears S. 16°36' W., 4.58 chs. dist.</p> <p>From this same point, center line P.C. station 1370 + 31.93, bears N. 29°06' E., 25.60 chs. dist.</p>

**Subdivision of Section 25,  
T. 10 N., R. 6 W., Gila and Salt River Meridian, Arizona**

CHAINS	
9.67	Intersect the westerly side of Martinez Wash Bridge, on a curve, bears NNE and SSW.
20.07	Point for the center S. 1/16 sec. cor. of sec. 25.  Not monumented.
30.105	Point for the center N-S 1/64 sec. cor. of sec. 25.  Not monumented.
40.14	Point for the center 1/4 sec. cor. of sec. 25, at intersection with the E. and W. center line of sec. 25.  Not monumented.
59.23	Center of A.T. and Sante Fe Railroad track, bears NE curving westerly and SW curving easterly.
80.28	The 1/4 sec. cor. of secs. 24 and 25, monumented with a granite stone, 14 X 12 X 3 ins., firmly set, 8 ins. in the ground, mkd. 1/4 on the N. face, with a mound of stone, 2½ ft. base, 2 ft., high, N. of cor.  At the corner point  Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.  <div style="text-align: center;">           T10N R6W            S24            1/4 ———            S25            1999         </div> Deposit a magnet in a white plastic case at the base of the stainless steel post.  Bury the original stone alongside the stainless steel post.
	From the 1/4 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp.  N. 89°59' W., on the E. and W. center line of sec. 25.  Over broken terrain.
14.15	Overhead power line, 5 wire, bears NNE and SSW.
17.80	Graded road, 30 lks. wide, bears NE and SW.

**Subdivision of Section 25,  
T. 10 N., R. 6 W., Gila and Salt River Meridian, Arizona**

CHAINS	
19.54	Easterly edge of pavement, Az. Highway No. 87, bears NE and SW.
20.04	Point for the center E. 1/16 sec. cor. of sec. 25.  Set a railroad spike, 6½ ins. long, 1¼ ins. wide, flush with the pavement of Az. Highway No. 87.  from which  A stainless steel post, 28 ins. long, 2½ ins. diam., set 23 ins. in the ground for a reference monument, bears S. 75°50' W., 88.3 ft. dist., with brass cap mkd. RM T10N R6W C-E 1/16 S25 88.3 FT. TO COR. and an arrow pointing to the corner.  A stainless steel post, 28 ins. long, 2½ ins. diam., set 26 ins. in the ground for a reference monument, bears N. 21°37' W., 69.8 ft. dist., with brass cap mkd. RM T10N R6W C-E 1/16 S25 69.8 FT. TO COR. and an arrow pointing to the corner.
20.10	Center line of Az. Highway No. 87, bears NE and SW.  From this point, center line P.C. station 1370 + 31.93, bears S. 39°43' W., 11.75 chs. dist.  From this same point, center line P.O.T. station 1360 + 00.00, bears N. 39°43' W., 3.89 chs. dist.
20.54	Westerly edge of pavement, Az. Highway No. 87, bears NE and SW.
22.05	Westerly R.O.W. fence, 4 strand barbed wire, bears NE and SW.
22.06	Intersect the westerly R.O.W. of Az. Highway No. 87.  From this point, P.C. station 1370 + 31.93, bears S. 39°43' W., 10.49 chs. dist., monumented with a brass disk, 3 ins. diam., set in concrete, projecting 6 ins. above the ground, with top mkd. ARIZONA HIGHWAY DEPT. P.C. STA. 1370 + 31.93 1969.  From this same point, P.O.T. station 1360 + 00.00, bears N. 39°43' W., 5.15 chs. dist., monumented with a brass disk, 3 ins. diam., set in concrete, projecting 4 ins. above the ground, with top mkd. ARIZONA HIGHWAY DEPT. P.O.T. STA. 1360 + 00.00 1969.
30.06	Point for the center W-E 1/64 sec. cor. of sec. 25.  Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

**Subdivision of Section 25,  
T. 10 N., R. 6 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	T10N R6W W-E 1/64 C ——— C S25 1999
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
33.50	Center of left fork of Martinez Wash, 50 lks. wide, course SSW.
35.70	Center of right fork of Martinez Wash, 35 lks. wide, course S.
40.08	The point for the center 1/4 sec. cor. of sec. 25.
48.76	Center of A.T. and Sante Fe Railroad track, bears N. curving easterly and S. curving easterly.
80.10	The 1/4 sec. cor. of secs. 25 and 26.
	<hr/> SE 1/4 Section 25 <hr/>
	From the E. 1/16 sec. cor. of secs. 25 and 36.
	N. 0°01' W., on the N. and S. center line of the SE 1/4 of sec. 25.
20.045	Point for the SE 1/16 sec. cor. of sec. 25, at intersection with the E. and W. center line of the SE 1/4 of sec. 25.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with brass cap mkd.
	T10N R6W SE 1/16 S25 1999
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
27.56	Point for the 1/1024 sec. cor. of sec. 25.
	Not monumented.
30.065	Point for the center N-SE 1/64 sec. cor. of sec. 25.
	Not monumented.

**Subdivision of Section 25,  
T. 10 N., R. 6 W., Gila and Salt River Meridian, Arizona**

CHAINS	
37.58	Point for the 1/1024 sec. cor. of sec. 25.  Not monumented.
40.085	The center E. 1/16 sec. cor. of sec. 25. <hr/>
	From the S. 1/16 sec. cor. of secs. 25 and 30.  S. 89°57' W., on the E. and W. center line of the SE 1/4 of sec. 25.
16.50	Center of graded road, 17 lks. wide, bears N. and S.
20.025	The SE 1/16 sec. cor. of sec. 25.
21.35	Overhead telephone line, single wire, bears N. and S.
25.55	Center of graded road, 20 lks. wide, bears N. and S.
27.75	Overhead power line, 4 strand, bears NNE and SSW.
30.035	Point for the center W-SE 1/64 sec. cor. of sec. 25.  Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.  T10N R6W S25 C-W-SE 1/64 1999  Deposit a magnet in a white plastic case at the base of the stainless steel post.
35.09	Center line of Az. Highway No. 87, on a curve, bears NE and SSW.  From this point, center line P.C. station 1370 + 31.93, bears N. 34°13' E., 13.33 chs. dist.  From this same point, center line P.T. station 1390 + 33.49, bears S. 21°42' W., 16.93 chs. dist.
36.79	Westerly R.O.W. fence, 4 strand barbed wire, bears NNE and SSW.
40.045	The point for the center S. 1/16 sec. cor. of sec. 25. <hr/>

**Subdivision of Section 25,  
T. 10 N., R. 6 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>NE 1/4 of the SE 1/4 Section 25</p> <hr style="width: 20%; margin: auto;"/>
	<p>From the point for the N-S 1/64 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp.</p> <p>S. 89°59' W., on the E. and W. center line of the NE 1/4 of the SE 1/4 of sec. 25.</p>
15.025	<p>Point for the center W-NE-SE 1/256 sec. cor. of sec. 25, occupied with a wood stake, 1 in. square, 8 ins. long, set in concrete, origin unknown.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R6W C-W-NE-SE 1/256 S25 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the wood stake alongside the stainless steel post.</p> <p>From this cor. point, an iron drill bit, 7/8 in. diam., firmly set, projecting 1 in. above ground, bears N. 63 3/4° E., 2 lks. dist., origin unknown.</p> <p>Along yard of private residence, through scattered debris.</p>
17.53	<p>Point for the 1/1024 sec. cor. of sec.25.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R6W 1/1024 S25 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located on the S. edge of a wooden platform, surrounded by abandoned restaurant and mining equipment.</p>
20.035	<p>The point for the center N-SE 1/64 sec. cor. of sec. 25.</p> <hr style="width: 80%; margin: auto;"/>

**Subdivision of Section 25,  
T. 10 N., R. 6 W., Gila and Salt River Meridian, Arizona**

CHAINS	
7.515	<p>From the center W-NE-SE 1/256 sec. cor. of sec. 25.</p> <p>North, on a portion of the N. and S. center line of the NW 1/4 of the NE 1/4 of the SE 1/4 of sec. 25.</p> <p>Point for the 1/1024 sec. cor. of sec. 25.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R6W 1/1024 S25 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 89°59.5' W., on the E. and W. center line of the NW 1/4 of the NE 1/4 of the SE 1/4 of sec. 25.</p>
2.65	Easterly edge of graded parking area, bears NNE and SSW.
5.01	The point for the 1/1024 sec. cor. of sec. 25, on the N. and S. center line of the SE 1/4 of sec. 25.
2.505	<p>From the point for the 1/1024 sec. cor. of sec. 25, on the N. and S. center line of the SE 1/4.</p> <p>N. 89°58.5' E., on a portion of the E. and W. center line of the NW 1/4 of the SW 1/4 of the NE 1/4 of the SE 1/4 of sec. 25.</p> <p>Point for the 1/1024 sec. cor. of sec. 25.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R6W 1/1024 S25 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located in graded area.</p> <hr/>

**Subdivision of Section 25,  
T. 10 N., R. 6 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	North, on a portion of the N. and S. center line of the NW 1/4 of the SW 1/4 of the NE 1/4 of the SE 1/4 of sec. 25. Across mining, restaurant and household debris.
2.505	The 1/1024 sec. cor. of sec. 25, on the E. and W. center line of the NE 1/4 of the SE 1/4 of sec. 25.
<hr/> NW 1/4 of the SE 1/4 Section 25 <hr/>	
	From the center W-SE 1/64 sec. cor. of sec. 25.
	N. 0°02' W., on the N. and S. center line of the NW 1/4 of the SE 1/4 of sec. 25.
7.89	Center line of Az. Highway No. 87, on curve, bears NE and SSW.  From this point, center line P.C. station 1370 + 31.93, bears N. 38°05' E., 3.98 chs. dist.  From this same point, center line P.T. station 1390 + 33.49, bears S. 25°35' W., 26.19 chs. dist.
10.03	Point for the NW-SE 1/64 sec. cor. of sec. 25, at intersection with the E. and W. center line of the NW 1/4 of the SE 1/4 of sec. 25.  Not monumented.
10.36	Westerly R.O.W. fence, 4 strand barbed wire, bears NNE and SSW.
20.06	The center W-E 1/64 sec. cor. of sec. 25.
<hr/>	
	From the point for the center N-SE 1/64 sec. cor. of sec. 25.
	S. 89°59' W., on the E. and W. center line of the NW 1/4 of the SE 1/4 of sec. 25.
7.51	Point for the 1/1024 sec. cor. of sec. 25.  Not monumented.
10.015	The point for the NW-SE 1/64 sec. cor. of sec. 25.
20.03	The point for the center N-S 1/64 sec. cor. of sec. 25.
<hr/>	
	From the point for the 1/1024 sec. cor. of sec. 25, on the N. and S. center line of the SE 1/4 of sec. 25.

**Subdivision of Section 25,  
T. 10 N., R. 6 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>N. 89°59.5' W., on a portion of the E. and W. center line of the NE 1/4 of the NE 1/4 of the NW 1/4 of the SE 1/4 of sec. 25.</p> <p>Over graded area.</p>
0.63	Center of paved private driveway, 40 lks. wide, bears ESE and WNW.
1.59	East edge of pavement of Az. Highway No. 87, bears NE and SW.
2.14	Center line of Az. Highway No. 87, bears NE and SW.
2.505	<p>Point for the 1/1024 sec. cor. of sec. 25.</p> <p>Set a railroad spike, 6½ ins. long, 1½ ins. wide, flush with the pavement of Az. Highway No. 87.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2½ ins. diam., set 26 ins. in the ground for a reference monument, bears S. 78°47' W., 39.6 ft. dist., with brass cap mkd. RM T10N R6W 1/1024 S25 39.6 FT TO COR. 1999 and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2½ ins. diam., set 26 ins. in the ground for a reference monument, bears N. 18°43' W., 29.6 ft. dist., with brass cap mkd. RM T10N R6W 1/1024 S25 29.6 FT TO COR. 1999 and an arrow pointing to the corner.</p> <p>Cor. is located 4.5 lks. W. of the east edge of pavement of Az. Highway No. 87, bears NE and SW.</p>
	<hr/> <p>S. 0°01' E., on a portion of the N. and S. center line of the NE 1/4 of the NE 1/4 of the NW 1/4 of the SE 1/4 of sec. 25.</p> <p>Across pavement of Az. Highway No. 87.</p>
0.44	Center line of Az. Highway No. 87, bears NE and SW.
1.11	East edge of pavement of Az. Highway No. 87, bears NE and SW.
2.505	<p>Point for the 1/1024 sec. cor. of sec. 25.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

**Subdivision of Section 25,  
T. 10 N., R. 6 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>T10N R6W 1/1024 S25 1999</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>West, on a portion of the E. and W. center line of the NE 1/4 of the NW 1/4 of the SE 1/4 of sec. 25.</p>
0.40	Center of paved entrance to Arrowhead Café, from Az. Highway No. 87, 42 lks. wide, bears N. and S.
1.18	East edge of pavement of Az. Highway No. 87, bears NE and SW.
1.71	Center line of Az. Highway No. 87, bears NE and SW.
2.13	West edge of pavement of Az. Highway No. 87, bears NE and SW.
2.505	Point for the NE-NW-SE 1/256 sec. cor. of sec. 25.
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p>T10N R6W NE-NW-SE 1/256 S25 1999</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>S. 0°01.5' E., on a portion of the N. and S. center line of the NE 1/4 of the NW 1/4 of the SE 1/4 of sec. 25.</p>
0.45	West edge of pavement of Az. Highway No. 87, bears NE and SW.
0.95	Center line of Az. Highway No. 87, bears NE and SW.
1.59	East edge of pavement of Az. Highway No. 87, bears NE and SW.
2.505	Point for the 1/1024 sec. cor. of sec. 25.
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Subdivision of Section 25,  
T. 10 N., R. 6 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	T10N R6W 1/1024 S25 1999
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	S. 89°59.5' W., on a portion of the E. and W. center line of the SW 1/4 of the NE 1/4 of the NW 1/4 of the SE 1/4 of sec. 25.
0.74	East edge of pavement of Az. Highway No. 87, bears NE and SW.
1.29	Center line of Az. Highway No. 87, bears NE and SW.
1.73	West edge of pavement of Az. Highway No. 87, bears NE and SW.
2.505	Point for the 1/1024 sec. cor. of sec. 25.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.
	T10N R6W 1/1024 S25 1999
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	S. 0°02' E., on a portion of the N. and S. center line of the SW 1/4 of the NE 1/4 of the NW 1/4 of the SE 1/4 of sec. 25.
0.94	West edge of pavement of Az. Highway No. 87, bears NE and SW.
1.46	Center line of Az. Highway No. 87, bears NE and SW.
2.32	East edge of pavement of Az. Highway No. 87, bears NE and SW.
2.505	The point for the 1/1024 sec. cor. of sec. 25, on the E. and W. center line of the NW 1/4 of the SE 1/4 of sec. 25.
	S. 0°02' E., on a portion of the N. and S. center line NW 1/4 of the SE 1/4 of the NW 1/4 of the SE 1/4 of sec. 25.
2.505	Point for the 1/1024 sec. cor. of sec. 25.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.

**Subdivision of Section 25,  
T. 10 N., R. 6 W., Gila and Salt River Meridian, Arizona**

CHAINS	<p style="text-align: center;">T10N R6W 1/1024 S25 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located in a graded area, surrounded by abandoned motor vehicles, gasoline pumps, restaurant equipment and mining equipment.</p> <p>From this cor. point, a galvanized iron pipe, 1 in. diam., firmly set, projecting 7 ins. above ground, bears S. 19°09' E., 37 lks. dist., unknown origin.</p> <hr/> <p>N. 89°58.5' E., on a portion of the E. and W. center line of the NW 1/4 of the SE 1/4 of the NW 1/4 of the SE 1/4 and the E. and W. center line of the NE 1/4 of the SE 1/4 of the NW 1/4 of the SE 1/4 of sec. 25.</p> <p>Across graded area, surrounded by abandoned motor vehicles, mining equipment, restaurant equipment and household junk.</p>
7.51	<p>The point for the 1/1024 sec. cor. of sec. 25, on the N. and S. center line of the SE 1/4 of sec. 25.</p> <hr/> <p style="text-align: center;"><b>GENERAL DESCRIPTION</b></p> <hr/> <p>The land in sec. 25, T. 10 N., R. 6 W., varies from nearly level in the SW 1/4, mountainous in the NW 1/4 to rolling in the remainder. The vegetation is dominated by creosote and catclaw, with palo verde and grasses along the draws and washes.</p> <p>A café, saloon, mobile home park and the offices of the Weaver Mining District are located in the patented lands in the SE 1/4 of the section. Extensive restaurant, mining, auto, and personal debris were found on federal lands adjacent to the patented lands.</p> <p>Access is by way of Arizona Highway No. 89, which crosses the SE 1/4 of sec. 25 in a SW direction.</p> <p>The mean magnetic declination of 12 1/2° E., was derived from the United States Geological Survey computer program GEOMAGIX, utilizing the Regional Magnetic Field Model for Epoch 1995 for the dates of survey.</p>



CERTIFICATE OF SURVEY

I, Gordon R. Bubel, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 15<sup>th</sup> day of November, 1999, I have dependently resurveyed a portion of the east boundary and a portion of the subdivisional lines and subdivided section 25, T. 10 N., R. 6 W., Gila and Salt River Meridian, Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

AUGUST 4, 2000  
(Date)

Gordon R. Bubel  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the east boundary and a portion of the subdivisional lines and the subdivision of section 25, T. 10 N., R. 6 W., Gila and Salt River Meridian, Arizona, executed by Gordon R. Bubel, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

August 25, 2000  
(Date)

Lenny D. Rawntar  
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 10 N., R. 6 W., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~\_\_\_\_\_~~  
~~(Date)~~

~~\_\_\_\_\_~~  
~~(Chief Cadastral Surveyor of Arizona)~~