

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF

THE FOURTH GUIDE MERIDIAN EAST,

THROUGH TOWNSHIP 28 NORTH (WEST BOUNDARY),

THE SOUTH AND EAST BOUNDARIES

AND A PORTION OF THE SUBDIVISIONAL LINES,

AND THE SURVEY OF A PORTION OF THE

SUBDIVISIONAL LINES,

TOWNSHIP 28 NORTH, RANGE 17 EAST,

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA.

EXECUTED BY

Joe R. Salazar, Cadastral Surveyor

Under Special Instructions dated March 23, 1999, approved March 25, 1999, which provided for the surveys included under Group No. 840, and assignment instructions dated April 12, 1999.

Survey commenced May 13, 1999

Survey completed August 3, 1999

INDEX DIAGRAM

TOWNSHIP 28 NORTH

RANGE 17 EAST

57	57	45	37	30	23
5 6	56 5	44 4	36 3	29 2	22 1 13
55	55	43	35	29	22
4 7	54 8	43 9	34 10	28 11	21 12 12
53	53	42	34	27	17
4 18	52 17	41 16	33 15	26 14	17 13 12
51	51	40	32	26	17
3 19	50 20	40 21	32 22	25 23	16 24 11
49	49	39	31	24	15
3 30	48 29	38 28	30 27	24 26	15 25 11
47	47	38	20	19 19	14
2 31	46 32	37 33	19 34	18 35	14 36 10
10	9	21 8	7	7	6

T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of the Fourth Guide Meridian East, through Township 28 North (west bdy.), the south and east boundaries and a portion of the subdivisional lines, and the survey of a portion of the subdivisional lines, T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this resurvey is as follows:

John C. Smith surveyed the south and east boundaries and a portion of the subdivisional lines, in 1891. Sidney E. Blout surveyed the Seventh Standard Parallel North (north bdy.) and the Fourth Guide Meridian East (west bdy.), in 1908. Stephen K. Hansen dependently resurveyed the Seventh Standard Parallel North, through Range 16 East, in 1998, and through Range 17 East, in 1999 (north bdy.).

During the course of this survey, certain corners dated 1908 were recovered which are not of record. Documents exist that indicate Sidney E. Blout conducted surveys and resurveys in this township while performing Indian allotment surveys under detail to the U. S. Indian Service during this time period. Specific information is contained in the Group file. Because these corners may have been utilized and their rejection may disturb satisfactory local conditions, those monuments which were recovered and found to be within limits were accepted as the corners for the completion of this survey.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated March 23, 1999, for Group No. 840, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble 4400 model receivers.

Preliminary to the resurvey and survey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Unrecovered corners were either reestablished or established based on the positions of the recovered monuments. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from first order U. S. Coast and Geodetic Survey triangulation station "N 70 1934" as published by the National Geodetic Survey, NAD 83(1992). The geographic position of the cor. of Tps. 27 and 28 N., Rs. 17 and 18 E. is as follows:

T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Latitude: 35°46'49.99" N. Longitude: 110°27'49.64" W.</p> <p>The mean magnetic declination is 12½° E.</p> <hr/>
	<p>Dependent Resurvey of the 4th Guide Mer. E., through T. 28 N., (West Bdy.), Gila and Salt River Meridian, Arizona</p> <hr/>
	<p>Restoring the survey executed by Sidney E. Blout, in 1908.</p> <hr/>
	<p>Beginning at the cor. of Tps. 27 and 28 N., Rs. 16 and 17 E, monumented with an iron post, 3 ins. diam., firmly set, projecting 5 ins. above the ground, with the brass cap mkd. T28N R16E R17E S36 S31 S1 S6 T27N, witnessed with a mound of stone, 2 ft. base, 1 ft. high, S. of cor.</p> <p>Add the marks 1999 to the brass cap.</p> <p>N. 0°03' W., bet. secs. 31 and 36, on the W. bdy. of the Tp.</p> <p>Over rolling sandy terrain, through sagebrush and grasses.</p>
40.03	<p>The 1/4 sec. cor. of secs. 31 and 36, determined E. of a mound of stone, 2 ft. base, 1 ft. high.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R16E R17E 1/4 S36 S31 1999</p>
	<p>Add the marks 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Rebuild mound of stone, 3 ft. base, 1½ ft. high, W. of cor.</p> <hr/> <p>N. 0°01' E., beginning new measurement.</p>
39.99	<p>The cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above the</p>

Dependent Resurvey of the 4th Guide Mer. E., through T. 28 N.,
(West Bdy.), Gila and Salt River Meridian, Arizona

CHAINS	
	<p>ground, with brass cap mkd. T28N R16E R17E S25 S30 S36 S31, witnessed with a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Add the marks 1999 to the brass cap.</p>
40.06	<p>NORTH, bet. secs. 25 and 30.</p> <p>Over rocky, steep W. slope of mesa.</p> <p>The 1/4 sec. cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above the ground, in a mound of stone, 3 ft. base, 1½ ft. high, with brass cap mkd. S25 S30 1/4 1908, witnessed with a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Add the marks T28N R16E R17E 1999 to the brass cap.</p>
40.00	<p>N. 0°01' E., beginning new measurement.</p> <p>The cor. of secs. 19, 24, 25 and 30, monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. T28N R16E R17E S24 S19 S25 S30, witnessed with a scattered mound of stone, 1½ ft. base, 1½ ft. high, W. of cor.</p> <p>Add the marks 1999 to the brass cap.</p> <p>Rebuild mound of stone, 2 ½ ft. base, 2 ft. high, W. of cor.</p>
40.00	<p>N. 0°01' W., bet. secs. 19 and 24.</p> <p>Over rocky steep W. slope of mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R16E R17E 1/4 S24 S19 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Dependent Resurvey of the 4th Guide Mer. E., through T. 28 N.,
(West Bdy.), Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. T28N R16E R17E S13 S18 S24 S19.</p> <p>Add the marks 1999 to the brass cap.</p> <hr/>
	<p>NORTH, bet. secs. 13 and 18.</p> <p>Over broken rocky terrain.</p>
40.02	<p>The 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. S13 S18 1/4 1908.</p> <p>Add the marks T28N R16E R17E 1999 to the brass cap.</p> <hr/>
	<p>NORTH, beginning new measurement.</p>
40.06	<p>The cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 3 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T28N R16E R17E S12 S7 S13 S18.</p> <p>Add the marks 1999 to the brass cap.</p> <p>Cor. is located on N. slope of wash, drains S. 30° W.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 7 and 12.</p> <p>Over broken rocky terrain.</p>
40.02	<p>The 1/4 sec. cor. of secs. 7 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. S12 S7 1/4 1908.</p> <p>Add the marks T28N R16E R17E 1999 to the brass cap.</p> <hr/>
	<p>NORTH, beginning new measurement.</p>
40.01	<p>The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 3 ins. diam., firmly set, projecting 16 ins. above the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. T28N R16E R17E S1 S6 S12 S7, witnessed with a mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p>Add the marks 1999 to the brass cap.</p>

Dependent Resurvey of the 4th Guide Mer. E., through T. 28 N.,
(West Bdy.), Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point, U. S. Coast and Geodetic Survey triangulation station N 70 1934, bears N. 83°28' W., 259.86 chs. dist., monumented with a standard brass disk, 3 ins. diam., cemented in a concrete post, 8 ins. square, firmly set, projecting 3 ins. above ground, with top mkd. N 70 1934.</p>
	<p>N. 0°01' E., bet. secs. 1 and 6.</p>
	<p>Over rocky S. slope of mesa.</p>
2.10	<p>S. edge of mesa.</p>
31.00	<p>N. edge of mesa.</p>
39.94	<p>Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate dist.; there is no remaining evidence of the original witness cor.</p>
	<p>Chiseled an X on the side of a sandstone boulder, 16 X 15 X 8 ft. high.</p>
	<p>From this point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 1 and 6, bears N. 63°49' W., 0.32 ch. dist.</p>
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ½ ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;"> W C T28N R16E R17E 1/4 S 1 S 6 1999 ↘ </p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.88	<p>The closing cor. of Tps. 28 N., Rs. 16 and 17 E., at intersection with the Seventh Standard Parallel North, monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T29N R16E R17E S36 S31 CC R16E R17E S1 S6 T28N 1998.</p>
	<p>From this cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 29 N., R. 16 E., bears S. 89°55' W., 0.18 ch. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. SC T29N R16E S36 1/4 1908 1998.</p>

**Dependent Resurvey of the 4th Guide Mer. E., through T. 28 N.,
(West Bdy.), Gila and Salt River Meridian, Arizona**

CHAINS

From this same cor. point, the stan. cor. of Tps. 29 N., Rs. 16 and 17 E., bears N. 89°55' E., 39.85 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. below the surface of ground, with brass cap mkd. SC T29N R16E R17E S36 S31 1998.

**Dependent Resurvey of the South Boundary,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

Restoring the survey executed by
John C. Smith, in 1891

From the cor. of Tps. 27 and 28 N., Rs. 17 and 18 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. T28N R17E R18E S36 S31 S1 S6 R17E R18E T27N. This is accepted as the best available evidence of the original corner position.

Add the marks 1999 to the brass cap.

Deposit a magnet in a white plastic case alongside the iron post.

From this cor. point, the cor. of secs. 1, 6, 7 and 12, Tps. 27 N., Rs. 17 and 18 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. T27N R17E R18E S1 S6 S12 S7, with fragmented sandstone 17 X 14 X 2 ins., lying loose alongside, plainly mkd. with 1 groove on a face and 5 grooves on opposite face, bears S. 0°02' W., 80.07 chs. dist.

Add the marks 1999 to the brass cap.

Bury original stone alongside iron post.

S. 89°58' W., bet. secs. 1 and 36, on the S. bdy. of the Tp.

Over rolling sandy terrain through sagebrush and grasses.

40.03

The 1/4 sec. cor. of secs. 1 and 36, monumented with an iron post, 1 in. diam., firmly set, 3 ins. below the ground, with brass cap mkd. S36 1/4 S1 1908. This is accepted as the best available evidence of the original corner position.

Add the marks T28N R17E T27N 1999 to the brass cap.

Deposit a magnet in a white plastic case alongside the iron post.

**Dependent Resurvey of the South Boundary,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.04	<p>S. 89°58' W., beginning new measurement.</p> <p>The cor of secs. 1, 2, 35 and 36, monumented with an iron post, 3 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. T28N R17E S35 S36 S2 S1 T27N. This is accepted as the best available evidence of the original corner position.</p> <p>Add the marks 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>S. 89°56' W., bet. secs. 2 and 35.</p> <p>Over rolling sandy terrain, through sagebrush and grasses.</p>
40.03	<p>The 1/4 sec. cor. of secs. 2 and 35, monumented with an iron post, 1 in. diam., firmly set, 2 ins. below the ground, with brass cap mkd. S35 1/4 S2 1908. This is accepted as the best available evidence of the original corner position.</p> <p>Add the marks T28N R17E T27N 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>S. 89°59' W., beginning new measurement.</p>
40.04	<p>The cor. of secs. 2, 3, 34 and 35, monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. T28N R17E S34 S35 S3 S2 T27N. This is accepted as the best available evidence of the original corner position.</p> <p>Add the marks 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>From this cor. point, a rebar, 3/8 in. diam., firmly set, flush with ground, with alum. cap mkd. BIA, bears N. 1°32' E., 5.34 chs. dist.</p> <hr/> <p>S. 89°54' W., bet. secs. 3 and 34.</p> <p>Over rolling sandy terrain, through sagebrush and grasses.</p>

**Dependent Resurvey of the South Boundary,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
10.50	Arizona State Highway No. 87, asphalt surfaced, 28 ft. wide, bears N. 15° E. and S. 15° W.
40.04	<p>The 1/4 sec. cor. of secs. 3 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. S34 1/4 S3 1908. This is accepted as the best available evidence of the original corner position.</p> <p>Add the marks T28N R17E T27N 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°55' W., beginning new measurement.</p>
40.04	<p>The cor. of secs. 3, 4, 33 and 34, monumented with an iron post, 3 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. T28N R17E S33 S34 S4 S3 T27N. This is accepted as the best available evidence of the original corner position.</p> <p>Add the marks 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>WEST, bet. secs. 4 and 33.</p> <p>Over rolling sandy terrain, through sagebrush and grasses.</p>
40.03	<p>The 1/4 sec. cor. of secs. 4 and 33, monumented with an iron post, 1 in. diam., firmly set, 11 ins. below the ground, with upper 18 ins. of iron post lying loose alongside, with brass cap mkd. S4 S33 1908. This is accepted as the best available evidence of the original corner position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T28N R17E S33 1/4 ——— S 4 T27N 1999 </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Dependent Resurvey of the South Boundary,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS													
40.06	<p>Bury the iron post inside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°48' W., beginning new measurement.</p> <p>The cor. of secs. 4, 5, 32 and 33, monumented with an iron post, 3 ins. diam., firmly set, 1 in. below the ground, with brass cap mkd. T28N R17E S32 S33 S5 S4 T27N. This is accepted as the best available evidence of the original corner position.</p> <p>Add the marks 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>Note: Due to the discrepancy of Smith's record and this resurvey the following lost cors. were reestablished at record distances, placing the excess in the last half mile. The cors. so established are related to the existing local conditions within the Tp.</p> <p>S. 89°56' W., bet. secs. 5 and 32.</p> <p>Over rolling sandy terrain, through sagebrush and grasses.</p>												
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>T28N</td><td>R17E</td></tr> <tr><td></td><td>S32</td></tr> <tr><td>1/4</td><td>_____</td></tr> <tr><td></td><td>S 5</td></tr> <tr><td></td><td>T27N</td></tr> <tr><td></td><td>1999</td></tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T28N	R17E		S32	1/4	_____		S 5		T27N		1999
T28N	R17E												
	S32												
1/4	_____												
	S 5												
	T27N												
	1999												
80.00	<p>Point for the cor. of secs. 5, 6, 31 and 32</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>T28N</td><td>R17E</td></tr> <tr><td>S31</td><td>S32</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S 6</td><td>S 5</td></tr> <tr><td></td><td>T27N</td></tr> <tr><td></td><td>1999</td></tr> </table> </div>	T28N	R17E	S31	S32	-----		S 6	S 5		T27N		1999
T28N	R17E												
S31	S32												

S 6	S 5												
	T27N												
	1999												

**Dependent Resurvey of the South Boundary,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>S. 89°56' W., bet. secs. 6 and 31.</p> <p>Over rolling sandy terrain, through sagebrush and grasses.</p> <p>Point for the 1/4 sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R17E S31 1/4 ——— S 6 T27N 1999</p>
86.29	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of Tps. 27 and 28 N., Rs. 16 and 17 E., hereinbefore described.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of the East Boundary, T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona,</p> <hr/> <p style="text-align: center;">Restoring the survey executed by John C. Smith, in 1891</p> <hr/>
40.03	<p>From the cor. of Tps. 27 and 28 N., Rs. 17 and 18 E., hereinbefore described.</p> <p>N. 0°02' E., bet. secs. 31 and 36, on the E. bdy. of the Tp.</p> <p>Over rolling sandy terrain, through sagebrush and grass</p> <p>The 1/4 sec. cor. of secs. 31 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. S36 1/4 S31 1908. This is accepted as the best available evidence of the original corner position.</p> <p>Add the marks T28N R17E R18E 1999 to the brass cap.</p> <hr/> <p>N. 0°02' E., beginning new measurement.</p>

**Dependent Resurvey of the East Boundary,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.04	<p>The cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 3 ins. diam., firmly set, 8 ins. below the ground, with brass cap mkd. T28N R17E R18E S25 S30 S36 S31. This is accepted as the best available evidence of the original corner position.</p> <p>Add the marks 1999 to the brass cap.</p> <hr/> <p>N. 0°01' E., bet. secs. 25 and 30.</p> <p>Over rolling sandy terrain, through sagebrush and grasses.</p>
10.40	<p>Arizona State Highway No. 264, asphalt surfaced, 28 ft. wide, bears N. 75° E. and S. 75° W.</p>
40.05	<p>The 1/4 sec. cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., firmly set, 1 in. below the ground, with brass cap mkd. S25 1/4 S30 1908. This is accepted as the best available evidence of the original corner position.</p> <p>Add the marks T28N R17E R18E 1999 to the brass cap.</p> <hr/> <p>N. 0°01' E., beginning new measurement.</p>
40.04	<p>The cor. of secs. 19, 24, 25 and 30, monumented with an iron post, 3 ins. diam., firmly set, 23 ins. below the ground, with brass cap mkd. T28N R17E R18E S24 S19 S25 S30. This is accepted as the best available evidence of the original corner position.</p> <p>Add the marks 1999 to the brass cap.</p> <p>Cor. is located in a cultivated field.</p> <hr/> <p>N. 0°01' E., bet. secs. 19 and 24.</p> <p>Over rolling sandy terrain, through sagebrush and grasses.</p>
40.05	<p>The 1/4 sec. cor. of secs. 19 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. S24 1/4 S19 1908. This is accepted as the best available evidence of the original corner position.</p> <p>Add the marks T28N R17E R18E 1999 to the brass cap.</p> <hr/> <p>N. 0°01' E., beginning new measurement.</p>
40.05	<p>The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 3 ins. diam., firmly set, 2 ins. below the ground, with</p>

**Dependent Resurvey of the East Boundary,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.03	<p>brass cap mkd. T28N R17E R18E S13 S18 S24 S19. This is accepted as the best available evidence of the original corner position.</p> <p>Add the marks 1999 to the brass cap.</p> <hr/> <p>N. 0°02' E., bet. secs. 13 and 18.</p> <p>Over rolling sandy terrain, through sagebrush and grasses.</p> <p>The 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. S13 1/4 S18 1908. This is accepted as the best available evidence of the original corner position.</p> <p>Add the marks T28N R17E R18E 1999 to the brass cap.</p> <hr/> <p>N. 0°02' E., beginning new measurement.</p>
40.04	<p>The cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. T28N R17E R18E S12 S7 S13 S18. This is accepted as the best available evidence of the original corner position.</p> <p>Add the marks 1999 to the brass cap.</p> <hr/> <p>N. 0°01' E., bet. secs. 7 and 12.</p> <p>Over rolling sandy terrain, through sagebrush and grasses.</p>
39.96	<p>The 1/4 sec. cor. of secs. 7 and 12, monumented with an iron post, 1 in. diam., filled with concrete, firmly set, 6 ins. below the ground, with no brass cap. This is accepted as the best available evidence of the original corner position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T28N R17E R18E 1/4 S12 S 7 1999</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Dependent Resurvey of the East Boundary,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit the iron post alongside stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°03' E., beginning new measurement.</p>
39.92	<p>The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. T28N R17E R18E S1 S6 S12 S7. This is accepted as the best available evidence of the original corner position.</p> <p>Add the marks 1999 to the brass cap.</p> <hr/> <p>N. 0°02' E., bet. secs. 1 and 6.</p> <p>Over broken sandy terrain, through sagebrush and grasses.</p>
39.90	<p>The 1/4 sec. cor. of secs. 1 and 6, monumented with an iron post, 1 in. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. S1 1/4 S6. This is accepted as the best available evidence of the original corner position.</p> <p>Add the marks T28N R17E R18E 1999 to the brass cap.</p> <hr/> <p>N. 0°02' E., beginning new measurement.</p>
39.79	<p>The closing cor. of Tps. 28 N., Rs. 17 and 18 E., at intersection with the Seventh Standard Parallel North, monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. T29N R17E R18E S36 S31 CC S1 S6 R17E R18E T28N. This is accepted as the best available evidence of the original corner position.</p> <p>Add the marks 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 29 N., R. 17 E., bears N. 89°55' W., 5.78 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. SC T29N R17E S36 1/4 1908 1999.</p> <p>From this same cor. point, the stan. cor. of Tps. 29 N., Rs. 17 and 18 E., bears S. 89°55' E., 34.23 chs. dist., monumented with and iron post, 3 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T29N R17E R18E S36 S31 1999.</p> <hr/>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">Restoring the survey executed by John C. Smith, in 1891</p> <hr/>
	<p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p>
	<p>N. 0°02' W., bet. secs. 35 and 36.</p>
	<p>Over rolling sandy terrain, through sagebrush and grasses.</p>
40.01	<p>The 1/4 sec. cor. of secs. 35 and 36, monumented with an iron post, 1 in. diam., firmly set, 4 ins. below the ground, with brass cap mkd. S35 1/4 S36 1908. This is accepted as the best available evidence of the original corner position.</p>
	<p>Add the marks T28N R17E 1999 to the brass cap.</p>
	<p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/>
	<p>N. 0°01' W., beginning new measurement.</p>
30.80	<p>Arizona State Highway No. 264, asphalt surfaced, 28 ft. wide, bears N. 75° E. and S. 75° W.</p>
40.03	<p>The cor. of secs. 25, 26, 35 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. T28N R17E S26 S25 S35 S36 1908. This is accepted as the best available evidence of the original corner position.</p>
	<p>Add the marks 1999 to the brass cap.</p>
	<p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/>
	<p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p>
	<p>S. 89°57' W., bet. secs. 25 and 36.</p>
	<p>Over rolling sandy terrain, through sagebrush and grasses.</p>
40.07	<p>Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the original corner.</p>
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
<p>42.30</p> <p>80.14</p>	<p align="center">T28N R17E S25 1/4 ——— S36 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 30 ft. S. of the center line of Arizona State Highway No. 264.</p> <p>Arizona State Highway No. 264, asphalt surfaced, 28 ft. wide, bears N. 75° E. and S. 75° W.</p> <p>The cor. of secs. 25, 26, 35 and 36.</p>
<p>39.98</p>	<p>NORTH, bet. secs. 25 and 26.</p> <p>Over rolling sandy terrain, through sagebrush and grasses.</p> <p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a collar of stone, 3 ft. base, to top, with brass cap mkd.</p>
<p>79.96</p>	<p align="center">T28N R17E 1/4 S26 S25 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 23, 24, 25 and 26, monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd. T28N R17E S23 S24 S26 S25 1908, witnessed with a mound of stone, 3 ft. base, 1 ft. high, W. of cor. This is accepted as the best available evidence of the original corner position.</p> <p>Add the marks 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.07	<p>S. 89°51' W., bet. secs. 24 and 25.</p> <p>Over rolling sandy terrain, through sagebrush and grasses.</p> <p>Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p>
	<p>T28N R17E S24 1/4 ——— S25 1999</p>
80.14	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raised a mound of stone, 2 ft. base, 1 ft. high, N. of cor.</p> <p>The cor. of secs. 23, 24, 25 and 26.</p>
40.00	<p>N. 0°02' W., bet. secs. 23 and 24.</p> <p>Over rolling sandy terrain, through sagebrush and grasses.</p> <p>Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p>
	<p>T28N R17E 1/4 S23 S24 1999</p>
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 13, 14, 23 and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. T28N R17E S14 S13 S23 S24 1908. This is accepted as the best available evidence of the original corner position.</p> <p>Add the marks 1999 to the brass cap.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case alongside the iron post.</p>
40.10	<p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°46' W., bet. secs. 13 and 24.</p> <p>Over rolling sandy terrain, through sagebrush and grasses.</p>
40.10	<p>The 1/4 sec. cor. of secs. 13 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. S13 1/4 S24. This is accepted as the best available evidence of the original corner position.</p> <p>Add the marks T28N R17E 1999 to the brass cap.</p>
40.10	<p>S. 89°47' W., beginning new measurement.</p>
40.10	<p>The cor. of secs. 13, 14, 23 and 24.</p>
39.98	<p>N. 0°04' E., bet. secs. 13 and 14.</p> <p>Over rolling sandy terrain, through sagebrush and grasses.</p>
39.98	<p>The 1/4 sec. cor. of secs. 13 and 14, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. 1/4 S13 S14. This is accepted as the best available evidence of the original corner position.</p> <p>Add the marks T28N R17E 1999 to the brass cap.</p>
39.98	<p>N. 0°04' E., beginning new measurement.</p>
39.98	<p>The cor. of secs. 11, 12, 13 and 14, monumented with an iron post, 2 ins. diam., firmly set, 1 in. below the ground, with brass cap mkd. T28N R17E S11 S12 S14 S13 1908. This is accepted as the best available evidence of the original corner position.</p> <p>Add the marks 1999 to the brass cap.</p>
	<p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.</p>
	<p>S. 89°42' W., bet. secs. 12 and 13.</p>
	<p>Over rolling sandy terrain, through sagebrush and grasses.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.06	<p>Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T28N R17E S12 1/4 ——— S13 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.12	<p>The cor. of secs. 11, 12, 13 and 14.</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of Tp., hereinbefore described.</p> <p>N. 0°05' W., bet. secs. 34 and 35.</p> <p>Over rolling sandy terrain, through sagebrush and grasses.</p>
28.60	<p>Arizona State Highway No. 87, asphalt surfaced, 28 ft. wide, bears N. 15° E. and S. 15° W.</p>
39.99	<p>The 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. S34 1/4 S35 1908. This is accepted as the best available evidence of the original corner position.</p> <p>Add the marks T28N R17E 1999 to the brass cap.</p> <p>Raised a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. 0°05' W., beginning new measurement.</p>
40.00	<p>The cor. of secs. 26, 27, 34 and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. T28N R17E S27 S26 S34 S35 1908. This is accepted as the best available evidence of the original corner position.</p> <p>Add the marks 1999 to the brass cap.</p> <hr/>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.07	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 89°55' W., bet. secs. 26 and 35.</p> <p>Over rolling sandy terrain, through sagebrush and grasses.</p> <p>Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R17E S26 1/4 ——— S35 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raised a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
80.14	<p>The cor. of secs. 26, 27, 34 and 35.</p>
32.40	<p>N. 0°04' W., bet. secs. 26 and 27.</p> <p>Over rolling sandy terrain, through sagebrush and grasses.</p>
39.99	<p>Indian Reservation Rt. 17, asphalt surfaced, 28 ft. wide, bears N. 35° E. and N. 35° W.</p>
40.01	<p>The 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 1 in. diam., firmly set, projecting 1 in. above the ground, in an imbedded collar of stone, 2 ft. base, to top, with brass cap mkd. S27 1/4 S26. This is accepted as the best available evidence of the original corner position.</p> <p>Add the marks T28N R17E 1999 to the brass cap.</p>
40.01	<p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of Tp., hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over rolling sandy terrain, through sagebrush and grasses.</p> <p>Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate dist.; there is no remaining evidence of the original corner.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p align="center">T28N R17E 1/4 S33 S34 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raised a mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p>
76.50	Wash, drains E.
80.02	<p>The cor. of secs. 27, 28, 33 and 34, monumented with an iron post, 2 ins. diam., firmly set, 6 ins. below the ground, with upper 2 ins. of iron post lying loose alongside, with brass cap mkd. T28N R17E S28 S27 S33 S34 1908. This is accepted as the best available evidence of the original corner position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T28N R17E S28 S27 ----- S33 S34 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the iron post alongside the stainless steel post.</p> <p>Raised a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
40.00	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S. 89°56' W., bet. secs. 27 and 34.</p> <p>Over rolling sandy terrain, through sagebrush and grasses.</p> <p>Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">T28N R17E S27 1/4 _____ S34 1999</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
50.90	<p>Arizona State Highway No. 264, asphalt surfaced, 28 ft. wide, bears S. 45° E. and N. 45° W, on curve.</p>
80.00	<p>The cor. of secs. 27, 28, 33 and 34.</p> <hr/>
	<p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of Tp., hereinbefore described.</p> <p>N. 0°03' E., bet. secs. 32 and 33.</p> <p>Over rolling sandy terrain, through sagebrush and grasses.</p>
40.01	<p>The 1/4 sec. cor. of secs. 32 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. S32 1/4 S33 1908, witnessed with a mound of stone, 3 ft. base, 1 ft. high, W. of cor. This is accepted as the best available evidence of the original corner position.</p> <p>Add the marks T28N R17E 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/>
	<p align="center">Survey of a Portion of the Subdivisional Lines, T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona</p> <hr/>
	<p>From the cor. of secs. 11, 12, 13 and 14, hereinbefore described.</p> <p>NORTH, bet. secs. 11 and 12.</p> <p>Over rolling sandy terrain, through sagebrush and grasses.</p>
40.00	<p>Point accepted for the 1/4 sec. cor. of secs. 11 and 12, monumented with an iron post, 1 in. diam, firmly set, projecting 4 ins. above the ground, with brass cap mkd. S11 1/4 S12 1908.</p> <p>Add the marks T28N R17E 1999 to the brass cap.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.01	<p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>NORTH, beginning new measurement.</p> <p>Point accepted for the cor. of secs. 1, 2, 11 and 12, monumented with an iron post, 2 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. T28N R17E S2 S1 S11 S12 1908.</p> <p>Add the marks 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>Land, rolling. Soil, sandy. No timber; sagebrush and grasses.</p>
40.11	<p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°47' W., bet. secs. 1 and 12.</p> <p>Over rolling sandy terrain, through sagebrush and grasses.</p> <p>Point accepted for the 1/4 sec. cor. of secs. 1 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. S1 1/4 S12 1908.</p> <p>Add the marks T28N R17E 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>S. 89°48' W., beginning new measurement.</p>
40.06	<p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, rolling. Soil, sandy. No timber; sagebrush and grasses.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>N. 0°01' E., bet. secs. 1 and 2.</p> <p>Over rolling sandy terrain, through sagebrush and grasses.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.99	<p>Point accepted for the 1/4 sec. cor. of secs. 1 and 2, monumented with an iron post, 1 in. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. S2 1/4 S1 1908.</p> <p>Add the marks T28N R17E 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°01' E., beginning new measurement.</p>
39.87	<p>Point accepted for the closing cor. of secs. 1 and 2, at intersection with the Seventh Standard Parallel North, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. T29N R17E S35 S36 CC S2 S1 1908.</p> <p>Add the marks T28N 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>From this cor. point, the stan. 1/4 sec. cor of sec. 35, T. 29 N., R. 17 E., bears S. 89°53' W., 5.72 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. SC T29N R17E S35 1/4 1908 1999.</p> <p>From this same cor. point, the stan. cor. of secs. 35 and 36, T. 29 N., R. 17 E., bears N. 89°53' E., 34.35 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. SC T29N R17E S35 S36 1999.</p> <p>Land, rolling. Soil, sandy. No timber; sagebrush and grasses.</p> <hr/> <p>The point for the 1/4 sec. cor. of sec. 1 only, T. 28 N., R. 17 E., at midpoint on the N. bdy. of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R16E — 1/4 S 1 T28N 1999</p>

**Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the stan. cor. of secs. 35 and 36, T. 29 N., R. 17 E., bears S. 89°54' W., 5.74 chs. dist.

From this same cor. point the stan. 1/4 sec. cor. of sec. 36, T. 29 N., R. 17 E., bears N. 89°54' E., 34.31 chs. dist., hereinbefore described.

From the 1/4 sec. cor. of secs. 26 and 27, hereinbefore described.

N. 0°03' W., bet. secs. 26 and 27.


Over broken rocky terrain.

39.95

Point for the cor. of secs, 22, 23, 26 and 27, falls on steep W. slope of rock slide, impracticable to monument.

From this point, the point selected for a witness cor. to the cor. of secs. 22, 23, 26 and 27, bears N. 5°14' W., 0.54 ch. dist., occupied with an iron post, 2 ins. diam, firmly set, 4 ins. below the ground, with upper 30 ins. of iron post lying loose alongside, with brass cap mkd. T28N R17E S22 S23 S27 S26 WC 1908.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.



Deposit a magnet in a white plastic case alongside the iron post.

Bury the iron post alongside the stainless steel post.

Land, broken.

Soil, rocky.

No timber; sagebrush and grasses.

From the cor. of secs. 23, 24, 25 and 26, hereinbefore described.

**Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>S. 89°57' W., bet. secs. 23 and 26.</p> <p>Over broken, rocky terrain.</p>
40.12	<p>Point accepted for the 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. S23 1/4 S26 1908.</p> <p>Add the marks T28N R17E 1999, to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>Raised a mound of stone, 2 ft. base 1 ft. high, N. of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°54' W., beginning new measurement.</p>
28.30	<p>Indian Reservation Rt. 17, asphalt surfaced, 28 ft. wide, bears N. and S.</p>
40.08	<p>The true point for the cor. of secs 22, 23, 26 and 27.</p> <p>Land, broken. Soil, rocky. No timber; sagebrush and grasses.</p> <hr/>
	<p>N. 0°03' W., bet. secs. 22 and 23.</p> <p>Over rocky steep S. slope of mesa.</p>
24.30	<p>Top of mesa.</p>
39.95	<p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 19 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T28N R17E 1/4 S22 S23 1999</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
41.40	<p>Indian Reservation Rt. 17, asphalt surfaced, 28 ft. wide, bears N. 10° W. and S. 15° E., on curve.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.90	<p>Point accepted for the cor. of secs. 14, 15, 22 and 23, monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. T28N R17E S15 S14 S22 S23 1908.</p> <p>Add the marks 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>Land, broken. Soil, rocky. No timber; sagebrush and grasses.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24, hereinbefore described.</p> <p>S. 89°50' W., bet. secs. 14 and 23.</p> <p>Over broken terrain, through sagebrush and grasses.</p>
18.10	E. edge of mesa.
40.10	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R17E S14 1/4 ——— S23 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.20	<p>The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, broken. Soil, rocky. No timber; sagebrush and grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 14 and 15.</p> <p>Over top of mesa, through sagebrush and grasses.</p>
39.97	Point for the 1/4 sec. cor. of secs. 14 and 15.

Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.94	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T28N R17E 1/4 S15 S14 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point accepted for the cor. of secs. 10, 11, 14 and 15, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. T28N R17E S10 S11 S15 S14 1908.</p> <p>Add the marks 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>Land, nearly level and broken. Soil, sandy and rocky. No timber; sagebrush and grasses.</p>
40.16	<hr/> <p>From the cor. of secs. 11, 12, 13 and 14, hereinbefore described.</p> <p>S. 89°50' W., bet. secs. 11 and 14.</p> <p>Over broken terrain, through sagebrush and grasses.</p> <p>Point accepted for the 1/4 sec. cor. of secs. 11 and 14, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. S11 1/4 S14 1908.</p> <p>Add the marks T28N R17E 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p>
40.17	<hr/> <p>S. 89°49' W., beginning new measurement.</p> <p>The cor. of secs. 10, 11, 14 and 15.</p>

Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, broken. Soil, rocky. No timber; sagebrush and grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 10 and 11.</p> <p>Over top of mesa, through sagebrush and grasses.</p>
22.00	N. edge of mesa.
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11, falls on the face of cliff, impracticable to monument.</p> <p>From this point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 10 and 11, bears N. 44°27' W., 0.35 ch. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC T28N R17E 1/4 S10 S11 1999</p> </div>
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 2, 3, 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T28N R17E S 3 S 2 ----- S10 S11 1999</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located on the E. bank of wash, drains NNW.</p> <p>Land, broken. Soil, rocky. No timber; sagebrush and grasses.</p> <hr/>

**Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 89°49' W., bet. secs. 2 and 11.</p> <p>Over broken terrain, through sagebrush and grasses.</p>
0.10	Wash 15 ft. wide, 3 ft. deep, drains ESE.
40.16	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R17E S 2 1/4 ——— S11 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.32	<p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, broken. Soil, rocky. No timber; sagebrush and grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over broken terrain, through sagebrush and grasses.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R17E 1/4 S 3 S 2 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.98	<p>Point accepted for the closing cor. of secs. 2 and 3, at intersection with the Seventh Standard Parallel North, monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. T29N R17E S34 S35 CC S3 S2 1908.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS

Add the marks T28N 1999 to the brass cap.

Deposit a magnet in a white plastic case alongside the iron post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 29 N., R. 17 E., bears S. 89°54' W., 5.48 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 26 ins. above the ground, with brass cap mkd. SC T29N R17E S34 1/4 1908 1999.

From this same cor. point, the stan. cor. of secs. 34 and 35, T. 29 N., R. 17 E., bears N. 89°54' E., 34.59 chs. dist., monumented with an iron post, 3 in. diam., firmly set, projecting 15 ins. above the ground, with brass cap mkd. SC T29N R17E S34 S35 1999, witnessed with a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

from which the 1999 bearing object

An "XBO" chiseled on the top face of a sandstone boulder,
12 x 3 x 4 ft. high, bears S. 58 1/4° E., 15 lks. dist.

Land, broken.

Soil, rocky.

No timber; sagebrush and grasses.

The point for the 1/4 sec. cor. of sec. 2 only, T. 28 N., R. 17 E., at midpoint on the N. bdy. of sec. 2.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.

T29N R17E

1/4 S 2

T28N

1999

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the stan. cor. of secs. 34 and 35, T. 29 N., R. 17 E., bears S. 89°54' W., 5.58 chs. dist.

From this same cor. point, the stan., 1/4 sec. cor. of sec. 35, T. 29 N., R. 17 E., bears N. 89°54' E., 34.45 chs. dist.

From the cor. of secs. 27, 28, 33 and 34, hereinbefore described.

**Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.96	<p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over broken terrain, through sagebrush and grasses.</p> <p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R17E 1/4 S28 S27 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raised a mound of stone, 2 ft. base, 1 ½ ft. high, W. of cor.</p>
63.50	<p>Arizona State Highway No. 264, asphalt surfaced, 28 ft. wide, bears S. 80° E. and W, on curve.</p>
79.92	<p>Point accepted for the cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 ins. diam., firmly set, 3 ins. below the ground, with brass cap mkd. T28N R17E S21 S22 S28 S27 1908, witnessed with a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Add the marks 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>Land, broken. Soil, rocky. No timber; sagebrush and grasses.</p>
39.97	<p>From the true point for the cor. of secs. 22, 23, 26 and 27.</p> <p>S. 89°55' W., bet. secs. 22 and 27.</p> <p>Over broken terrain, through sagebrush and grasses.</p> <p>Point for the 1/4 sec. cor. of sec. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.94	<p style="text-align: center;">T28N R17E S22 1/4 ——— S27 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 21, 22, 27 and 28.</p> <p>Land, broken. Soil, rocky. No timber; sagebrush and grasses.</p>
39.98	<hr/> <p>N. 0°06' W., bet. secs. 21 and 22.</p> <p>Over broken terrain, through sagebrush and grasses.</p> <p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
79.96	<p style="text-align: center;">T28N R17E 1/4 S21 S22 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point accepted for the cor. of secs. 15, 16, 21 and 22, monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. T28N R17E S16 S15 S21 S22 1908, witnessed with a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Add the marks 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>Land, broken. Soil, rocky. No timber; sagebrush and grasses.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 89°57' W., bet. secs. 15 and 22.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.01	<p>Over rolling sandy terrain, through sagebrush and grasses.</p> <p>Point for the 1/4 sec. cor. of sec. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R17E S15 1/4 ——— S22 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raised a mound of stone, 3 ft. base, 3 ft. high, N. of cor.</p>
42.00	Enter broken terrain.
80.02	<p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, rolling and broken. Soil, sandy and rocky. No timber; sagebrush and grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 15 and 16.</p> <p>Over broken terrain, on S. slope of mesa.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T28N R17E 1/4 S16 S15 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.04	<p>Point accepted for the cor. of secs. 9, 10, 15 and 16, monumented with an iron post, 2 ins. diam., filled with concrete, firmly set, projecting 12 ins. above the ground, with no brass cap.</p>

Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <table border="1" data-bbox="836 415 1015 562"> <tr> <td>T28N</td> <td>R17E</td> </tr> <tr> <td>S 9</td> <td>S10</td> </tr> <tr> <td>S16</td> <td>S15</td> </tr> <tr> <td colspan="2" style="text-align: center;">1999</td> </tr> </table> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the iron post alongside the stainless steel post.</p> <p>Land, nearly level and broken. Soil, sandy and rocky. No timber; sagebrush and grasses.</p>	T28N	R17E	S 9	S10	S16	S15	1999			
T28N	R17E										
S 9	S10										
S16	S15										
1999											
	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 89°59' W., bet. secs. 10 and 15.</p> <p>Over broken terrain.</p>										
<p>40.01</p>	<p>Point for the 1/4 sec. cor. of sec. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 3 ins. in the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <table border="1" data-bbox="852 1281 998 1428"> <tr> <td>T28N</td> <td>R17E</td> </tr> <tr> <td></td> <td>S10</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td></td> <td>S15</td> </tr> <tr> <td colspan="2" style="text-align: center;">1999</td> </tr> </table> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T28N	R17E		S10	1/4	_____		S15	1999	
T28N	R17E										
	S10										
1/4	_____										
	S15										
1999											
<p>80.02</p>	<p>The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, broken. Soil, rocky. No timber; sagebrush and grasses.</p>										
	<p>N. 0°01' W., bet. secs. 9 and 10.</p> <p>Over top of mesa, through sagebrush and grasses.</p>										

**Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.02	<p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 5 ins. in the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T28N R17E 1/4 S 9 S10 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
57.00	Enter broken terrain on N. slope of mesa.
80.04	<p>Point accepted for the cor. of secs. 3, 4, 9 and 10, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. T28N R17E S4 S3 S9 S10 1908.</p> <p>Add the marks 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>Land, nearly level and broken. Soil, sandy and rocky. No timber; sagebrush and grasses.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 89°59' W., bet. secs. 3 and 10.</p> <p>Over broken terrain.</p>
40.01	<p>Point accepted for the 1/4 sec. cor. of secs. 3 and 10, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. S3 1/4 S10 1908.</p> <p>Add the marks T28N R17E 1999, to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. 89°55' W., beginning new measurement.</p>
39.99	The cor. of secs. 3, 4, 9 and 10.

**Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, broken. Soil, rocky. No timber; sagebrush and grasses.</p> <hr/> <p>N. 0°04' W., bet. secs. 3 and 4.</p> <p>Over broken terrain, through sagebrush and grasses.</p>
39.79	<p>Point accepted for the 1/4 sec. cor. of secs. 3 and 4, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. S4 1/4 S3 1908.</p> <p>Add the marks T28N R17E 1999, to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. 0°04' W., beginning new measurement.</p>
5.00	<p>S. edge of mesa, thence along top of mesa.</p>
40.07	<p>Point for the closing cor. of secs. 3 and 4, at intersection with the Seventh Standard Parallel North.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29N R17E S33</p> <hr style="width: 50%; margin: auto;"/> <p>S 4 S 3 CC T28N 1999</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor of sec. 33, T. 29 N., R. 17 E., bears S. 89°57' W., 5.54 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. SC T29N R17E S33 1/4 1908 1999.</p> <p>From this same cor. point, the stan. cor. of secs. 33 and 34, T. 29 N., R. 17 E., bears N. 89°57' E., 34.53 chs. dist., monumented with a stainless steel post, 2½ ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. SC T29N R17E S33 S34 1999.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A dead juniper, 10 ins. diam., bears N. 62 1/4° E., 211 lks. dist., with scribe marks T29N R17E S34 BT visible on open blaze.</p> <p style="padding-left: 40px;">A juniper stump, 8 ins. diam., bears N. 64 3/4° W., 90 lks. dist.</p> <p>Land, broken. Soil, rocky. Timber, juniper; sagebrush and grasses.</p> <hr/> <p>The point for the 1/4 sec. cor. of sec. 3 only, T. 28 N., R. 17 E., at midpoint on the N. bdy. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T29N R17E ——— 1/4 S 3 T28N 1999</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>From this cor. point, the stan. cor of secs. 33 and 34, T. 29 N., R. 17 E., bears S. 89°59' W., 5.505 chs. dist.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 29 N., R. 17 E., bears N. 89°59' E., 34.555 chs. dist.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 32 and 33, hereinbefore described.</p> <p>N. 0°09' W., bet. secs. 32 and 33.</p> <p>Over broken terrain, through sagebrush and grasses.</p>
40.07	<p>Point accepted for the cor. of secs. 28, 29, 32 and 33, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. T28N R17E S29 S28 S32 S33 1908.</p> <p>Add the marks 1999 to the brass cap.</p>

Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.05	<p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>Land, broken. Soil, rocky. No timber; sagebrush and grasses.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34, hereinbefore described.</p> <p>S. 89°57' W., bet. secs. 28 and 33.</p> <p>Over broken terrain, through sagebrush and grasses.</p> <p>Point for the 1/4 sec. cor. of sec. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R17E S28 1/4 ——— S33 1999</p>
80.10	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 28, 29, 32 and 33.</p> <p>Land, broken. Soil, rocky. No timber; sagebrush and grasses.</p> <hr/>
40.13	<p>N. 0°03' W., bet. secs. 28 and 29.</p> <p>Over broken terrain, through sagebrush and grasses.</p> <p>Point accepted for the 1/4 sec. cor. of secs. 28 and 29, monumented with an iron post, 1 in. diam., filled with concrete, firmly set, 4 ins. below the ground, with no brass cap.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R17E 1/4 S29 S28 1999</p>

**Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a 60 penny nail at the base of the stainless steel post.</p> <p>Bury the iron post alongside the stainless steel post.</p> <p>Raised a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p style="text-align: center;">_____.</p> <p>N. 0°02' W., beginning new measurement.</p>
39.96	<p>Point accepted for the cor. of secs. 20, 21, 28 and 29, monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. T28N R17E S20 S21 S29 S28 1908, witnessed with a mound of stone, 3 ft. base, 3 ft. high, W. of cor.</p> <p>Add the marks 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>Land, broken. Soil, rocky. No timber; sagebrush and grasses.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N. 89°55' W., bet. secs. 21 and 28.</p> <p>Over broken terrain, through sagebrush and grasses.</p>
28.30	<p>Arizona State Highway No. 264, asphalt surfaced, 28 ft. wide, bears S. 85° E. and N. 85° W.</p>
40.01	<p>Point accepted for the 1/4 sec. cor. of secs. 21 and 28, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. S21 1/4 S28 1908.</p> <p>Add the marks T28N R17E 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>Raised a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p style="text-align: center;">_____.</p> <p>N. 89°57' W., beginning new measurement.</p>
7.20	<p>E. edge of mesa.</p>
22.20	<p>Paved road, 28 ft. wide, bears S. 15° E. and N. 15° W.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS									
28.40	W. edge of mesa.								
40.10	The cor. of secs. 20, 21, 28 and 29. Land, nearly level and broken. Soil, sandy and rocky. No timber; sagebrush and grasses.								
	<hr/>								
	N. 0°04' W., bet. secs. 20 and 21. Over broken SW. slope of mesa.								
27.30	S. edge of mesa.								
40.01	Point accepted for the 1/4 sec. cor. of secs. 20 and 21, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. S20 1/4 S21 1908, witnessed with a mound of stone, 3 ft. base, 1½ ft. high, W. of cor. Add the marks T28N R17E 1999, to the brass cap. Deposit a magnet in a white plastic case alongside the iron post.								
	<hr/>								
	N. 0°01' W., beginning new measurement. Over rolling sandy terrain, through sagebrush and grasses.								
40.00	Point for the cor. of secs. 16, 17, 20 and 21. Set a brass tablet 3¼ ins. diam., 3½ in. stem, in a drill hole, cemented in place, flush with rock surface, with top mkd.								
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>T28N</td> <td>R17E</td> </tr> <tr> <td>S17</td> <td>S16</td> </tr> <tr> <td>S20</td> <td>S21</td> </tr> <tr> <td colspan="2" style="text-align: center;">1999</td> </tr> </table>	T28N	R17E	S17	S16	S20	S21	1999	
T28N	R17E								
S17	S16								
S20	S21								
1999									
	Deposit a magnet at the base of the brass tablet in drill hole. Raised a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Land, broken. Soil, rocky. No timber; sagebrush and grasses.								
	<hr/>								
	From the cor. of secs. 15, 16, 21 and 22.								

**Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>N. 89°47' W., bet. secs. 16 and 21.</p> <p>Over broken terrain.</p>
40.01	<p>Point accepted for the 1/4 sec. cor. of secs. 16 and 21, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. S16 1/4 S21 1908.</p> <p>Add the marks T28N R17E 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>WEST, beginning new measurement.</p>
26.50	<p>Arizona State Highway No. 264, asphalt surfaced, 28 ft. wide, bears N. and S.</p>
40.00	<p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, nearly level and broken. Soil, rocky. No timber; sagebrush and grasses.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 16 and 17.</p> <p>Over broken SW. slope of mesa.</p>
18.50	<p>S. edge of mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>True point falls in wash on W. slope of mesa, drains NW, impracticable to monument.</p> <p>From this point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 16 and 17, bears S. 26°53' W., 0.33 ch. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>WC T28N R17E 1/4 S17 S16 ↗ 1999</p> </div>

**Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
68.20	S. edge of mesa, thence along top of mesa.
80.00	Point accepted for the cor. of secs. 8, 9, 16 and 17, monumented with an iron post, 2 ins. diam., firmly set, projecting 16 ins. above the ground, with brass cap mkd. T28N R17E S8 S9 S17 S16 1908, witnessed with a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Add the marks 1999 to the brass cap.
	Deposit a magnet in a white plastic case alongside the iron post.
	Raised supporting mound of stone, 4 ft. base, to top of brass cap.
	Land, nearly level and broken. Soil, sandy and rocky. No timber; sagebrush and grasses.
<hr/>	
	From the cor. of secs. 9, 10, 15 and 16.
	N. 89°55' W., bet. secs. 9 and 16.
	Over top of mesa, through sagebrush and grasses.
28.10	Indian Reservation Rt. 17, asphalt surfaced, 28 ft. wide, bears S. 45° E. and N. 45° W
39.97	Point for the 1/4 sec. cor. of secs. 9 and 16.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 29 ins. in the ground, with brass cap mkd.
	T28N R17E S9 1/4 ——— S16 1999
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
42.30	Arizona State Highway No. 264, asphalt surfaced, 28 ft. wide, bears N. and S.
79.94	The cor. of secs. 8, 9, 16 and 17.

Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, nearly level. Soil, sandy. No timber; sagebrush and grasses.</p> <hr/>
40.00	<p>N. 0°02' W., bet. secs. 8 and 9.</p> <p>Over top of mesa, through sagebrush and grasses.</p> <p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 1 in. in the ground, in a mound of stone, 6 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T28N R17E 1/4 S 8 S 9 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raised a mound of stone, 2 ft. base., 2 ft. high, W. of cor.</p>
61.20	<p>Arizona State Highway No. 264, asphalt surfaced, 28 ft. wide, bears S. 45° E. and N. 45° W.</p>
80.00	<p>Point accepted for the cor. of secs. 4, 5, 8 and 9, monumented with an iron post 2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T28N R17E S5 S4 S8 S9 1908, witnessed with a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Add the marks 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 11 ins. diam., bears S. 65 3/4° W., 40 lks. dist., mkd. T28N R17E S8 BT.</p> <p>Land, nearly level and broken. Soil, sandy and rocky. Timber, juniper; sagebrush and grasses.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>WEST, bet. secs. 4 and 9.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over broken terrain, through sagebrush and grasses.
9.10	E. edge of mesa, thence along top of mesa.
23.00	Indian Reservation Rt. 4, asphalt surfaced, 28 ft. wide, bears N. 15° E. and S. 15° W
39.97	Point accepted for the 1/4 sec. cor. of secs. 4 and 9, monumented with an iron post, 1 in. diam., firmly set, projecting 28 ins. above the ground in a scattered mound of stone, with brass cap mkd. S4 1/4 S9 1908.
	Add the marks T28N R17E 1999 to the brass cap.
	Deposit a magnet in a white plastic case alongside the iron post.
	Rebuilt mound of stone, 3 ft. base, to top, of brass cap.
	Cor. is located on NW. slope of mesa.

	N. 89°53' W., beginning new measurement.
33.00	E. edge of mesa, thence along top of mesa.
39.98	The cor. of secs. 4, 5, 8 and 9.
	Land, nearly level and broken.
	Soil, rocky.
	Timber, juniper; sagebrush and grasses.

	N. 0°04' E., bet. secs. 4 and 5.
	Over top of mesa, through sagebrush and grasses.
7.10	N. edge of mesa.
39.98	Point accepted for the 1/4 sec. cor. of secs. 4 and 5, monumented with an iron post, 1 in. diam., firmly set, projecting 20 ins. above the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. S5 1/4 S4 1908, witnessed with a mound of stone, 2 ft. base, 3 ft. high, W. of cor.
	Add the marks T28N R17E 1999, to the brass cap.
	Deposit a magnet in a white plastic case alongside the iron post.

	N. 0°04' E., beginning new measurement.

**Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.02	<p>Point for the closing cor. of secs. 4 and 5, at intersection with the Seventh Standard Parallel North, falls on the NW. face of cliff, impracticable to monument.</p> <p>From this point, the point selected for a witness cor. to the closing cor. of secs. 4 and 5, bears N. 68°41' W., 0.40 ch. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 3 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <pre> WC T29N R17E S32 ----- S 5 S 4 CC T28N 1999 </pre> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this same point, the stan. 1/4 sec. cor of sec. 32, T. 29 N., R. 17 E., bears N. 89°36' W., 6.06 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd. SC T29N R17E S32 1/4 1908 1999, witnessed with a mound of stone, 2 ft. base, 1 ft. high, N. of cor.</p> <p>from which the 1999 bearing object</p> <p style="margin-left: 40px;">An "XBO" chiseled on a sandstone outcropping, 20 x 10 x 2 ft. high, bears N. 23 3/4° W., 15 lks. dist.</p> <p>From this same point, the stan. cor. of secs. 32 and 33, T. 29 N., R. 17 E., bears S. 89°36' E., 34.18 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd. SC T29N R17E S32 S33 1999.</p> <p>Land, broken. Soil, rocky. No timber; sagebrush and grasses.</p> <hr style="width: 60%; margin: 20px auto;"/> <p>The point for the 1/4 sec. cor. of sec. 4 only, T. 28 N., R. 17 E., at midpoint on the N. bdy. of sec. 4.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R17E ----- 1/4 S 4 T28N 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the stan. cor. of secs. 32 and 33, T. 29 N., R. 17 E., bears S. 89°58' W., 5.695 chs. dist.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 33, T. 29 N., R. 17 E., bears N. 89°58' E., 34.335 chs. dist.</p>
	<p>From the cor. of secs. 5, 6, 31 and 32 on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°05' W., bet. secs. 31 and 32.</p> <p>Over rolling sandy terrain, through sagebrush and grasses.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R17E 1/4 S31 S32 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.04	<p>Point for the cor. of secs. 29, 30, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T28N R17E S30 S29 ----- S31 S32 1999</p>

**Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.05	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raised a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Land, rolling. Soil, sandy. No timber; sagebrush and grasses.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>S. 89°51' W., bet. secs. 29 and 32.</p> <p>Over rolling sandy terrain, through sagebrush and grasses.</p> <p>Point accepted for the 1/4 sec. cor. of secs. 29 and 32, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. below the ground, with brass cap mkd. S29 1/4 S32 1908, witnessed with a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Add the marks T28N R17E 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/>
39.98	<p>S. 89°57' W., beginning new measurement.</p> <p>The cor. of secs. 29, 30, 31 and 32.</p> <p>Land, rolling. Soil, sandy. No timber; sagebrush and grasses.</p> <hr/>
39.93	<p>S. 89°52' W., bet. secs. 30 and 31.</p> <p>Over rolling sandy terrain, through sagebrush and grasses.</p> <p>Point accepted for the 1/4 sec. cor. of secs. 30 and 31, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. S30 1/4 S31 1908.</p> <p>Add the marks T28N R17E 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/>

**Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
46.25	<p>S. 89°57' W., beginning new measurement.</p> <p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy. No timber; sagebrush and grasses.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°05' W., bet. secs. 29 and 30.</p> <p>Over broken terrain, through sagebrush and grasses.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T28N R17E 1/4 S30 S29 1999</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raised a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p>
80.04	<p>Point accepted for the cor. of secs. 19, 20, 29 and 30, monumented with an iron post, 2 ins. diam., filled with concrete, firmly set, flush with ground, with no brass cap.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 11 ins. in the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T28N R17E S19 S20 ----- S30 S29 1999</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Deposit the iron post alongside stainless steel post.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.04	<p>Land, broken. Soil, rocky. No timber; sagebrush and grasses.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29. S. 89°52' W., bet. secs. 20 and 29. Over broken terrain, through sagebrush and grasses. Point for the 1/4 sec. cor. of secs. 20 and 29. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R17E S20 1/4 ——— S29 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.08	<p>The cor. of secs. 19, 20, 29 and 30. Land, broken. Soil, rocky. No timber; sagebrush and grasses.</p> <hr/> <p>S. 89°54' W., bet. secs. 19 and 30. Over broken terrain, through sagebrush and grasses.</p>
40.21	<p>Point accepted for the 1/4 sec. cor. of secs. 19 and 30, monumented with an iron post, 1 in. diam., filled with concrete, firmly set, flush with ground, with no brass cap. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 6 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T28N R17E S19 1/4 ——— S30 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS															
	<p>Deposit the iron post alongside stainless steel post.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>S. 89°56' W., beginning new measurement.</p>														
45.82	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, broken. Soil, rocky. No timber; sagebrush and grasses.</p> <hr/>														
40.00	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°04' W., bet. secs. 19 and 20.</p> <p>Over broken terrain, through sagebrush and grasses.</p> <p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: 0 auto;"> <tr><td colspan="2">T28N R17E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S19</td><td> </td><td>S20</td></tr> <tr><td colspan="3">1999</td></tr> </table> </div>	T28N R17E		1/4		S19		S20	1999						
T28N R17E															
1/4															
S19		S20													
1999															
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 17, 18, 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: 0 auto;"> <tr><td colspan="2">T28N R17E</td></tr> <tr><td>S18</td><td> </td><td>S17</td></tr> <tr><td colspan="3"><hr style="width: 50%; margin: 0 auto;"/></td></tr> <tr><td>S19</td><td> </td><td>S20</td></tr> <tr><td colspan="3">1999</td></tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raised a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>	T28N R17E		S18		S17	<hr style="width: 50%; margin: 0 auto;"/>			S19		S20	1999		
T28N R17E															
S18		S17													
<hr style="width: 50%; margin: 0 auto;"/>															
S19		S20													
1999															

Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.05	<p>Land, broken. Soil, rocky. No timber; sagebrush and grasses.</p> <hr/> <p>From the cor. of 16, 17, 20 and 21. S. 89°51' W., bet. secs. 17 and 20. Over broken terrain, through sagebrush and grasses. Point for the 1/4 sec. cor. of secs. 17 and 20. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T28N R17E S17 1/4 ——— S20 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post. from which An "XBO" chiseled on a sandstone boulder, 10 X 8 X 4 ft., bears S. 88°01' W., 41 lks. dist.</p>
80.10	<p>The cor. of secs. 17, 18, 19 and 20. Land, broken. Soil, rocky. No timber; sagebrush and grasses.</p> <hr/> <p>S. 89°55' W., bet. secs. 18 and 19. Over broken terrain, through sagebrush and grasses.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 18 and 19. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
85.93	<p style="text-align: center;">T28N R17E S18 1/4 ——— S19 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raised mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Cor. is located on E. slope of ridge, bears N. and S.</p> <p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, broken. Soil, rocky. No timber; sagebrush and grasses.</p>
40.00	<p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°04' W., bet. secs. 17 and 18.</p> <p>Over broken terrain, through sagebrush and grasses.</p> <p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
80.00	<p style="text-align: center;">T28N R17E 1/4 S18 S17 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raised a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Point accepted for the cor. of secs. 7, 8, 17 and 18, monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd. T28N R17E S7 S8 S18 S17 1908.</p> <p>Add the marks 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.15	<p>Raised a mound of stone, 4 ft. base, 3 ft. high, W. of cor.</p> <p>Land, broken. Soil, rocky. No timber; sagebrush and grasses.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>S. 89°54' W., bet. secs. 8 and 17.</p> <p>Over broken terrain, through sagebrush and grasses.</p> <p>Point accepted for the 1/4 sec. cor. of secs. 8 and 17, monumented with an iron post, 1 in. diam., loosely set, projecting 12 ins. above the ground, with upper 15 ins. of iron post broken off, lying loose alongside, with brass cap mkd. S8 1/4 S17 1908.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R17E S 8 1/4 ——— S17 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Deposit iron post alongside stainless steel post.</p> <hr/> <p>S. 89°48' W., beginning new measurement.</p>
40.01	<p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, broken. Soil, rocky. No timber; sagebrush and grasses.</p> <hr/> <p>S. 89°58' W., bet. secs. 7 and 18.</p> <p>Over broken terrain, through sagebrush and grasses.</p>
39.94	<p>Point accepted for the 1/4 sec. cor. of secs. 7 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. S7 1/4 S18 1908.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
45.89	<p>Add the marks T28N R17E 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>Raised a mound of stone, 3 ft. base, 1 ft. high, N. of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°58' W., beginning new measurement.</p> <p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, broken. Soil, rocky. No timber; sagebrush and grasses.</p>
40.04	<p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°01' E., bet. secs. 7 and 8.</p> <p>Over broken terrain, through sagebrush and grasses.</p> <p>Point for the 1/4 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in a crevice of a sandstone ledge, 12 X 6 X 2½ ft. high, with brass cap. mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T28N R17E 1/4 S7 S8 1999</p> </div>
80.08	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point accepted for the cor. of secs. 5, 6, 7 and 8, monumented with an iron post, 2 ins. diam., firmly set, projecting 23 ins. above the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. T28N R17E S6 S5 S7 S8 1908, witnessed with a mound of stone, 3 ft. base, 4 ft. high, W. of cor.</p> <p>Add the marks 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p>

Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, broken. Soil, rocky. No timber; sagebrush and grasses.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>S. 89°56' W., bet. secs. 5 and 8.</p> <p>Over broken terrain, through sagebrush and grasses.</p>
39.96	<p>Point accepted for the 1/4 sec. cor. of secs. 5 and 8, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. S5 1/4 S8 1908, witnessed with a mound of stone, 2 ft. base, 1 ft. high, N. of cor.</p> <p>Add the marks T28N R17E 1999 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>S. 89°54' W., beginning new measurement.</p>
40.12	<p>The cor. of secs. 5, 6, 7 and 8.</p> <p>Land, broken. Soil, rocky. No timber; sagebrush and grasses.</p> <hr/> <p>S. 89°56' W., bet. secs. 6 and 7.</p> <p>Over broken terrain, through sagebrush and grasses.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 7, falls on the face of bolder, impracticable to monument.</p> <p>From this point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 6 and 7, bears N. 69°51' W., 0.59 ch. dist., occupied with an iron post, 1 in. diam., firmly set, 18 ins. above the ground, in a mound of stone 4 ft. base, to top, with brass cap mkd. S6 1/4 S7 1908.</p> <p>Add the marks WC T28N R17E 1999 and an arrow pointing to cor., to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
85.84	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, broken. Soil, rocky. No timber; sagebrush and grasses.</p>
40.00	<p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°03' W., bet. secs. 5 and 6.</p> <p>Over broken sandy terrain, through sagebrush and grasses.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p align="center">T28N R17E 1/4 S 6 S 5 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.86	<p>Point for the closing cor. of secs. 5 and 6, at intersection with the Seventh Standard Parallel North.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p align="center">T29N R17E S31 ----- S 6 S 5 CC T28N 1999</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor of sec. 31, T. 29 N., R. 17 E., bears N. 89°56' W., 5.88 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. SC T29N R17E S31 1/4 1908 1999.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this same cor. point, the stan. cor. of secs. 31 and 32, T. 29 N., R. 17 E., bears S. 89°56' E., 34.12 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 18 ins. above the ground, with brass cap mkd. SC T29N R17E S31 S32 1999.

Land, broken.
Soil, rocky.
No timber; sagebrush and grasses.

The point for the 1/4 sec. cor. of sec. 5 only, T. 28 N., R. 17 E., at midpoint on the N. bdy. of sec. 5, falls in cultivated field, impracticable to set a permanent monument.

Deposit a magnet in a white plastic case 24 ins. in the ground.

from which

A stainless steel post, 28 ins. long, 2½ ins. diam., set 23 ins. in the ground, for a reference monument, bears N. 46°00' W., 80.5 ft. dist., with brass cap mkd. RM T29N R17E S31 80.5 FT TO 1/4 COR 1999 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the stan. cor of secs. 31 and 32 , T. 29 N., R. 17 E., bears S. 89°32' W., 5.99 chs. dist.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 32, T. 29 N., R. 17 E., bears N. 89°32' E., 34.05 chs. dist.

The point for the 1/4 sec. cor. of sec. 6 only, T. 28 N., R. 17 E., at 40.00 chs. dist. from the closing cor. of secs. 5 and 6, on the N. bdy. of sec. 6.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T29N R17E

1/4 S 6

T28N

1999

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the stan. cor. of Tps. 29 N., Rs. 16 and 17 E., bears S. 89°56' W., 5.88 chs. dist., hereinbefore described.

**Survey of a Portion of the Subdivisional Lines,
T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 29 N., R. 17 E., bears N. 89°56' E., 34.12 chs. dist.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p>This survey is located on the Hopi Indian Reservation, near the town of Shungopavi.</p> <p>A wide variety of terrain is found in the area. Many of the low lying areas are used for dryland farming. Much of the township contains rolling sand dunes and grassland, the remainder of the township is rocky and mountainous.</p> <p>Timber in the higher terrain consists of juniper and pinon pine. The grass lands are used for the grazing of cattle and sheep.</p> <p>Arizona State Highway 264 passes through the eastern portion of the Tp.</p> <p>Elevation ranges from 5500 to 6500 feet above sea level.</p> <p>Some past coal mining activity was noted along the northern portion of the Tp., no evidence of present mineral activity was noted.</p> <p>The mean magnetic declination of 12½° E., was derived from the United States Geological Survey Computer program GEOMAGIX, utilizing the Regional Magnetic Field Model for Epoch 1995 for the dates of survey.</p> <hr/>
--------	---

CERTIFICATE OF SURVEY

I, Joe R. Salazar, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 23rd day of March, 1999, I have, dependently resurveyed the Fourth Guide Meridian East, through Township 28 North (west boundary), the south and east boundaries and a portion of the subdivisional lines and surveyed a portion of the subdivisional lines, Township 28 North, Range 17 East, of the Gila and Salt River Meridian, Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

10/11/2000
(Date)

Joe R. Salazar
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the Fourth Guide Meridian East, through Township 28 North (west boundary), the south and east boundaries and a portion of the subdivisional lines and the survey of a portion of the subdivisional lines, Township 28 North, Range 17 East, of the Gila and Salt River Meridian, Arizona, executed by Joe R. Salazar, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

October 23, 2000
(Date)

Kenny D. Rowland
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 28 N., R. 17 E., Gila and Salt River Meridian, Arizona is a true copy of the original field notes.~~

~~_____~~
~~(Date)~~

~~_____~~
~~(Chief Cadastral Surveyor of Arizona)~~