

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF THE

FOURTH GUIDE MERIDIAN EAST THROUGH TOWNSHIP 27 NORTH (W. BDY.),

THE SOUTH AND EAST BOUNDARIES

AND

THE SUBDIVISIONAL LINES,

TOWNSHIP 27 NORTH, RANGE 17 EAST,

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA.

EXECUTED BY

Joe R. Salazar, Cadastral Surveyor

Under Special Instructions dated August 30, 2000, approved August 30, 2000, which provided for the surveys included under Group No. 856, and assignment instructions dated August 30, 2000.

Survey commenced September 6, 2000

Survey completed September 14, 2000

INDEX DIAGRAM

TOWNSHIP 27 NORTH

RANGE 17 EAST

5 6 45	45 5 44	37 4 37	31 3 31	25 2 24	19 1 13 18
5 7 43	43 8 43	36 9 35	30 10 30	24 11 23	18 12 12 17
4 18 41	42 17 41	35 16 34	29 15 28	23 14 22	17 13 12 16
3 19 40	40 20 40	34 21 33	28 22 27	22 23 21	16 24 11 15
3 30 39	39 29 38	33 28 32	27 27 26	21 26 20	15 25 11 14
2 31 10	37 32 9	32 33 8	25 34 8	19 35 7	14 36 10 6

T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of the Fourth Guide Meridian East through Township 27 North (W. Bdy.), the south and east boundaries and the subdivisional lines, T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this resurvey is as follows:

John C. Smith surveyed the Fourth Guide Meridian East through T. 27 N., the south, east and north boundaries, the subdivisional lines and the subdivision of sections by the three-mile method, in 1891. Sidney E. Blout resurveyed the Fourth Guide Meridian East through T. 27 N., and the south boundary, in 1908. Joe R. Salazar dependently resurveyed the north boundary, in 1999.

During the course of the survey, certain corners dated 1908 were recovered which are not of record. Documents exist that indicate Sidney E. Blout conducted surveys and resurveys in this township while performing Indian allotment surveys under detail to the U. S. Indian Service during this time period. The corners established by Blout have been in position for over ninety years, and their rejection could disturb satisfactory local conditions. In addition, direct evidence of Smith's survey is so limited that it is now impossible to reestablish his survey on that basis. For these reasons, Blout's monuments have been adopted in this resurvey.

Because there is no official record of Blout's measurements or what he may or may not have recovered of Smith's survey, and due to the consistency of Blout's corner locations, lost corners on the east boundary were reestablished equidistant from their respective controlling corners. Lost section corners and quarter section corners on longitudinal subdivisional lines were reestablished equidistant from controlling corners to the north and south. Quarter section corners on the latitudinal subdivisional lines were reestablished at midpoint between controlling section corners. Lost quarter section corners on the lines running into the north and west boundaries were reestablished at forty chains with the excess and deficiency placed in the last half mile. Areas against these boundaries were relotted to reflect their actual acreage. This township is entirely tribal land, and the subdivision of sections by the three mile-method is officially superseded by this resurvey.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated August 30, 2000, for Group No. 856, Arizona.

T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 4400 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners on the 4th Guide Mer. E. and on the south boundary were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from first order U. S. Coast and Geodetic Survey triangulation station L64 1934, as published by the National Geodetic Survey, NAD 83 (1992). The geographic position of the corner of Tps. 26 and 27 N., Rgs. 17 and 18 E., is as follows:

Latitude: 35° 41' 36.64" N. Longitude: 110° 27' 49.44" W.

The mean magnetic declination is 12° E.

Dependent Resurvey of the 4th Guide Mer. E. through T. 27 N. (W. Bdy.), T. 27 N., R. 17 E., Gila and Salt River Mer., Arizona

Restoring the resurvey executed by
Sidney E. Blout, in 1908

Beginning at the cor. of Tps. 26 and 27 N., Rgs. 16 and 17 E., monumented with an iron post, 3 ins. diam., loosely set, projecting 25 ins. above the ground, with brass cap mkd. T27N R16E R17E S36 S31 S1 S6 T26N.

Reset the iron post, 36 ins. long, 3 ins. diam., 32 ins. in the ground.

Add the marks 2000 to the brass cap.

Deposit a magnet in a white plastic case at the base of the iron post.

N. 0°03' W., bet. secs. 31 and 36, on the W. bdy. of the Tp.

Over rolling desert terrain, through scattered creosote and cacti.

Dependent Resurvey of the 4th Guide Mer. E. through T. 27 N.
(W. Bdy.), T. 27 N., R. 17 E., Gila and Salt River Mer., Arizona

CHAINS	
40.00	<p>The 1/4 sec. cor. of secs. 31 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. S36 1/4 S31 1908.</p> <p>Add the marks T27N R16E R17E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. 0°03' W., beginning new measurement.</p>
40.04	<p>The cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. T27N R16E R17E S25 S30 S36 S31.</p> <p>Add the marks 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. 0°03' W., bet. secs. 25 and 30.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.00	<p>The 1/4 sec. cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. S25 1/4 S30 1908.</p> <p>Add the marks T27N R16E R17E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. 0°05' W., beginning new measurement.</p>
40.00	<p>The cor. of secs. 19, 24, 25 and 30, monumented with an iron post, 3 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. T27N R16E R17E S24 S19 S25 S30.</p> <p>Add the marks 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. 0°05' W., bet. secs. 19 and 24.</p>

Dependent Resurvey of the 4th Guide Mer. E. through T. 27 N.
(W. Bdy.), T. 27 N., R. 17 E., Gila and Salt River Mer., Arizona

CHAINS	
	Over rolling desert terrain, through scattered creosote and cacti.
40.01	<p>The 1/4 sec. cor. of secs. 19 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. S24 1/4 S19 1908.</p> <p>Add the marks T27N R16E R17E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/>
	N. 0°05' W., beginning new measurement.
40.05	<p>The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. T27N R16E R17E S13 S18 S24 S19.</p> <p>Add the marks 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/>
	N. 0°01' W., bet. secs. 13 and 18.
	Over rolling desert terrain, through scattered creosote and cacti.
39.99	<p>The 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. S13 1/4 S18 1908.</p> <p>Add the marks T27N R16E R17E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/>
	North, beginning new measurement.
40.03	<p>Point for the cor. of secs. 7, 12, 13 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the 4th Guide Mer. E. through T. 27 N.
(W. Bdy.), T. 27 N., R. 17 E., Gila and Salt River Mer., Arizona

CHAINS													
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T27N</td></tr> <tr><td style="text-align: center;">R16E</td><td style="text-align: center;">R17E</td></tr> <tr><td style="text-align: center;">S12</td><td style="text-align: center;">S 7</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S13</td><td style="text-align: center;">S18</td></tr> <tr><td colspan="2" style="text-align: center;">2000</td></tr> </table>	T27N		R16E	R17E	S12	S 7	-----		S13	S18	2000	
T27N													
R16E	R17E												
S12	S 7												

S13	S18												
2000													
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>												
	<p>North, bet. secs. 7 and 12.</p>												
	<p>Over rolling desert terrain, through scattered creosote and cacti.</p>												
40.03	<p>The 1/4 sec. cor. of secs. 7 and 12, monumented with an iron post, badly corroded, 1 in. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. S7 1/4 S12 1908.</p>												
	<p>At the corner point</p>												
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>												
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T27N</td></tr> <tr><td style="text-align: center;">R16E</td><td style="text-align: center;">R17E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S12</td><td style="text-align: center;">S 7</td></tr> <tr><td colspan="2" style="text-align: center;">2000</td></tr> </table>	T27N		R16E	R17E	1/4		S12	S 7	2000			
T27N													
R16E	R17E												
1/4													
S12	S 7												
2000													
	<p>Deposit a magnet in a white plastic case and the remains of iron post at the base of the stainless steel post.</p> <hr/>												
	<p>N. 0°01' W., beginning new measurement.</p>												
30.30	<p>Graded road, 20 ft. wide, bears E. and W.</p>												
39.98	<p>The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 3 ins. diam., firmly set, projecting 13 ins. above the ground, with brass cap mkd. T27N R16E R17E S1 S6 S12 S7.</p>												
	<p>Add the marks 2000 to the brass cap.</p>												
	<p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/>												
	<p>N. 0°03' E., bet. secs. 1 and 6.</p>												

Dependent Resurvey of the 4th Guide Mer. E. through T. 27 N.
(W. Bdy.), T. 27 N., R. 17 E., Gila and Salt River Mer., Arizona

CHAINS	
39.79	<p>Over rolling desert terrain, through scattered creosote and cacti.</p> <p>The 1/4 sec. cor. of secs. 1 and 6, monumented with an iron post, badly corroded, 1 in. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. S1 1/4 S6 1908.</p>
40.20	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R16E R17E 1/4 S 1 S 6 2000</p> </div> <p>Deposit a magnet in a white plastic case and the remains of iron post at the base of the stainless steel post.</p> <hr/> <p>North, beginning new measurement.</p> <p>The cor. of Tps. 27 and 28 N., Rgs. 16 and 17 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 5 ins. above the ground, with the brass cap mkd. T28N R16E R17E S36 S31 S1 S6 T27N 1999, witnessed with a mound of stone, 2 ft. base, 1 ft. high, S. of cor.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of the South Boundary, T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;">Restoring the resurvey executed by Sidney E. Blout, in 1908</p> <hr/> <p>From the cor. of Tps. 26 and 27 N., Rgs. 17 and 18 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. T27N R17E R18E S36 S31 S1 S6 T26N, with a limestone, 7 X 7 X 18 ins., lying loose alongside, mkd. R18E on a face and 6 notches on a side.</p> <p>Add the marks 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case and the original limestone alongside the iron post.</p> <p>S. 89°58' W., bet. secs. 1 and 36, on the S. bdy. of the Tp.</p>

**Dependent Resurvey of the South Boundary,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling desert terrain, through scattered creosote and cacti.
40.09	<p>The 1/4 sec. cor. of secs. 1 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. S36 1/4 S1 1908.</p> <p>Add the marks T27N R17E T26N 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°58' W., beginning new measurement.</p>
40.03	<p>The cor. of secs. 1, 2, 35 and 36, monumented with an iron post, 3 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. T27N R17E S35 S36 S2 S1 T26N.</p> <p>Add the marks 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°57' W., bet. secs. 2 and 35.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.13	<p>The 1/4 sec. cor. of secs. 2 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. S35 1/4 S2 1908.</p> <p>Add the marks T27N R17E T26N 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°58' W., beginning new measurement.</p>
40.01	<p>The cor. of secs. 2, 3, 34 and 35, monumented with an iron post, 3 ins. diam., firmly set, 5 ins. below the ground, with brass cap mkd. T27N R17E S34 S35 S3 S2 T26N.</p> <p>Add the marks 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/>

**Dependent Resurvey of the South Boundary,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>S. 89°57' W., bet. secs. 3 and 34.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
25.50	<p>Center line of State Road 87, paved, 28 ft. wide, bears SSE. and NNW.</p>
40.10	<p>The 1/4 sec. cor. of secs. 3 and 34, monumented with an iron post, 1 in. diam., firmly set, 2 ins. below the ground, with brass cap mkd. S34 1/4 S3 1908.</p> <p>Add the marks T27N R17E T26N 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/>
	<p>S. 89°57' W., beginning new measurement.</p>
40.04	<p>The cor. of secs. 3, 4, 33 and 34, monumented with an iron post, 3 ins. diam., firmly set, projecting 20 ins. above the ground, with brass cap mkd. T27N R17E S33 S34 S4 S3 T26N.</p> <p>Add the marks 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/>
	<p>S. 89°56' W., bet. secs. 4 and 33.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.04	<p>The 1/4 sec. cor. of secs. 4 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. S33 1/4 S4 1908, with a sandstone, 12 X 8 X 4 ins., lying loose nearby, plainly mkd. 1/4 on a face.</p> <p>Add the marks T27N R17E T26N 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case and original sandstone alongside the iron post.</p> <hr/>
	<p>S. 89°56' W., beginning new measurement.</p>
40.07	<p>The cor. of secs. 4, 5, 32 and 33, monumented with an iron post, 3 ins. diam., loosely set and bent over, 24 ins. in the ground, with partial brass cap mkd. T27N R17E S32 S33 S4.</p>

**Dependent Resurvey of the South Boundary,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS																							
40.08	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 10px;">T27N</td> <td style="padding: 2px 10px;">R17E</td> </tr> <tr> <td style="padding: 2px 10px;">S32</td> <td style="padding: 2px 10px;">S33</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 10px;">S 5</td> <td style="padding: 2px 10px;">S 4</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 10px;">T26N</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 10px;">2000</td> </tr> </table> <p>Deposit a magnet in a white plastic case at the base and the iron post alongside the stainless steel post.</p> <hr style="border: 0.5px solid black;"/> <p>S. 89°55' W., bet. secs. 5 and 32.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 10px;">T27N</td> <td style="padding: 2px 10px;">R17E</td> </tr> <tr> <td style="padding: 2px 10px;">S32</td> <td></td> </tr> <tr> <td style="padding: 2px 10px;">1/4</td> <td style="border-top: 1px solid black; padding: 2px 10px;"></td> </tr> <tr> <td style="padding: 2px 10px;">S 5</td> <td></td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 10px;">T26N</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 10px;">2000</td> </tr> </table> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T27N	R17E	S32	S33	S 5	S 4	T26N		2000		T27N	R17E	S32		1/4		S 5		T26N		2000	
T27N	R17E																						
S32	S33																						
S 5	S 4																						
T26N																							
2000																							
T27N	R17E																						
S32																							
1/4																							
S 5																							
T26N																							
2000																							
80.16	<p>Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 10px;">T27N</td> <td style="padding: 2px 10px;">R17E</td> </tr> <tr> <td style="padding: 2px 10px;">S31</td> <td style="padding: 2px 10px;">S32</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 10px;">S 6</td> <td style="padding: 2px 10px;">S 5</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 10px;">T26N</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 10px;">2000</td> </tr> </table>	T27N	R17E	S31	S32	S 6	S 5	T26N		2000													
T27N	R17E																						
S31	S32																						
S 6	S 5																						
T26N																							
2000																							

**Dependent Resurvey of the South Boundary,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.08	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>S. 89°55' W., bet. secs. 6 and 31.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p> <p>The 1/4 sec. cor. of secs. 6 and 31, monumented with an iron post, 1 in. diam., filled with concrete, firmly set, projecting 1 in. above the ground, with brass cap missing.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over iron post, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R17E S31 1/4 ——— S6 T26N 2000</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>S. 89°54' W., beginning new measurement.</p>
46.31	<p>The cor. of Tps. 26 and 27 N., Rgs. 16 and 17 E., hereinbefore described.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of the East Boundary, T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of Tps. 26 and 27 N., Rgs. 17 and 18 E., hereinbefore described.</p> <p>N. 0°06' W., bet. secs. 31 and 36, on the E. bdy. of the Tp.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.01	<p>The 1/4 sec. cor. of secs. 31 and 36, monumented with an iron post, 1 in. diam., firmly set, 1 in. below the ground, with brass cap mkd. S36 1/4 S31 1908.</p> <p>Add the marks T27N R17E R18E 2000 to the brass cap.</p>

**Dependent Resurvey of the East Boundary,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.01	<p>Deposit a magnet in a white plastic case alongside the iron steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°05' W., beginning new measurement.</p> <p>The cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 3 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. T27N R17E R18E S25 S30 S36 S31.</p> <p>Add the marks 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. 0°04' W., bet. secs. 25 and 30.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.01	<p>The 1/4 sec. cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. S25 1/4 S30 1908.</p> <p>Add the marks T27N R17E R18E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. 0°03' W., beginning new measurement.</p>
40.01	<p>The cor. of secs. 19, 24, 25 and 30, monumented with an iron post, 3 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. T27N R17E R18E S24 S19 S25 S30.</p> <p>Add the marks 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>North, bet. secs. 19 and 24.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.01	<p>The 1/4 sec. cor. of secs. 19 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. S24 1/4 S19 1908.</p>

**Dependent Resurvey of the East Boundary,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.01	<p>Add the marks T27N R17E R18E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°02' W., beginning new measurement.</p> <p>The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. T27N R17E R18E S13 S18 S24 S19.</p> <p>Add the marks 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/>
40.02	<p>N. 0°02' W., bet. secs. 13 and 18.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 18, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T27N R17E R18E 1/4 S13 S18 2000 </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.04	<p>The cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 3 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. T27N R17E R18E S12 S7 S13 S18.</p> <p>Add the marks 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. 0°01' E., bet. secs. 7 and 12.</p>

**Dependent Resurvey of the East Boundary,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling desert terrain, through scattered creosote and cacti.
40.02	<p>The 1/4 sec. cor. of secs. 7 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. S12 1/4 S7 1908.</p> <p>Add the marks T27N R17E R18E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>North, beginning new measurement.</p>
40.02	<p>The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. T27N R17E R18E S1 S6 S12 S7 1999, with the original stone buried alongside the iron post, as described in the field notes of the dependent resurvey of the south boundary, T. 28 N., R. 17 E.</p> <hr/> <p>N. 0°02' E., bet. secs. 1 and 6.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.02	<p>The 1/4 sec. cor. of secs. 1 and 6, monumented with an iron post, 1 in. diam., firmly set, 2 ins. below the ground, with brass cap mkd. S1 1/4 S6 1908.</p> <p>Add the marks T27N R17E R18E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°02' E., beginning new measurement.</p>
40.05	<p>The cor. of Tps. 27 and 28 N., Rgs. 17 and 18 E., on the N. bdy. of Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. T28N R17E R18E S36 S31 S1 S6 R17E R18E T27N 1999.</p>

**Dependent Resurvey of the East Boundary,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this cor. point, U. S. Coast and Geodetic Survey triangulation station L64 1934, bears N. 21°55' W., 161.19 chs. dist., monumented with a standard brass disk, 3 ins. diam., cemented in a concrete post, 6 ins. square, firmly set, flush with ground, with top mkd. L64 1934 and a triangle.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of the Subdivisional Lines, T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of Tp., hereinbefore described.</p> <p>N. 0°07' W., bet. secs. 35 and 36.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.00	<p>The 1/4 sec. cor. of secs. 35 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. S35 1/4 S36 1908.</p> <p>Add the marks T27N R17E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°06' W., beginning new measurement.</p>
40.02	<p>The cor. of secs. 25, 26, 35 and 36, monumented with an iron post, 2 ins. diam., firmly set, 8 ins. below the ground, with brass cap mkd. T27N R17E S26 S25 S35 S36 1908.</p> <p>Add the marks 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of Tp., hereinbefore described.</p> <p>S. 89°57' W., bet. secs. 25 and 36.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.09	<p>The 1/4 sec. cor. of secs. 25 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. S25 1/4 S36 1908.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.04	<p>Add the marks T27N R17E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°59' W., beginning new measurement.</p> <p>The cor. of secs. 25, 26, 35 and 36.</p> <hr/>
40.07	<p>N. 0°03' W., bet. secs. 25 and 26.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p> <p>The 1/4 sec. cor. of secs. 25 and 26, monumented with an iron post, 1 in. diam., firmly set, 2 ins. below the ground, with brass cap mkd. S26 1/4 S25 1908.</p> <p>Add the marks T27N R17E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/>
40.09	<p>N. 0°01' W., beginning new measurement.</p> <p>The cor. of secs. 23, 24, 25 and 26, monumented with an iron post, 2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. T27N R17E S23 S24 S26 S25 1908.</p> <p>Add the marks 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/>
40.13	<p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of Tp., hereinbefore described.</p> <p>N. 89°56' W., bet. secs. 24 and 25.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p> <p>The 1/4 sec. cor. of secs. 24 and 25, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. S24 1/4 S25 1908.</p> <p>Add the marks T27N R17E 2000 to the brass cap.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.94	<p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. 89°56' W., beginning new measurement.</p>
39.99	<p>The cor. of secs. 23, 24, 25 and 26.</p> <hr/> <p>N. 0°04' W., bet. secs. 23 and 24.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p> <p>Point for the 1/4 sec. cor. of secs. 23 and 24, there is no remaining evidence of the original cor.</p> <p>Set a magnet in a white plastic case, 18 ins. below the ground, on the side of the left bank of Polacca Wash, impracticable to establish a permanent monument.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2½ ins. diam., set 23 ins. in the ground, for a reference monument, bears S. 64°46' E., 38.0 ft. dist., with brass cap mkd. RM T27N R17E S24 38.0 FT TO COR 2000 and an arrow pointing to cor.</p>
79.98	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 13, 14, 23 and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T27N R17E S14 S13 S23 S24 1908.</p> <p>Add the marks 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/>
40.06	<p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of Tp., hereinbefore described.</p> <p>N. 89°57' W., bet. secs. 13 and 24.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 24, there is no remaining evidence of the original cor.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R17E S13 1/4 ——— S24 2000</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.12	<p>The cor. of secs. 13, 14, 23 and 24.</p> <hr/> <p>N. 0°02' W., bet. secs. 13 and 14.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.05	<p>Point for the 1/4 sec. cor. of secs. 13 and 14, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R17E 1/4 S14 S13 2000</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.10	<p>The cor. of secs. 11, 12, 13 and 14, monumented with an iron post, 2 ins. diam., firmly set, 5 ins. below the ground, with brass cap mkd. T27N R17E S11 S12 S14 S13 1908.</p> <p>Add the marks 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of Tp., hereinbefore described.</p> <p>N. 89°55' W., bet. secs. 12 and 13.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.05	<p>Point for the 1/4 sec. cor. of secs. 12 and 13, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R17E S12 1/4 ——— S13 2000</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.10	<p>The cor. of secs. 11, 12, 13 and 14.</p> <hr/> <p>N. 0°02' W., bet. secs. 11 and 12.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.03	<p>The 1/4 sec. cor. of secs. 11 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. S11 1/4 S12 1908.</p> <p>Add the marks T27N R17E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. 0°03' W., beginning new measurement.</p>
40.00	<p>The cor. of secs. 1, 2, 11 and 12, monumented with an iron post, 2 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. T27N R17E S2 S1 S11 S12 1908.</p> <p>Add the marks 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of Tp., hereinbefore described.</p> <p>N. 89°55' W., bet. secs. 1 and 12.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.08	<p>Point for the 1/4 sec. cor. of secs. 1 and 12, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R17E S 1 1/4 ——— S12 2000</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.16	<p>The cor. of secs. 1, 2, 11 and 12.</p> <hr/> <p>N. 0°05' E., bet. secs. 1 and 2.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
39.99	<p>The 1/4 sec. cor. of secs. 1 and 2, monumented with an iron post, 1 in. diam., firmly set, 31 ins. below the ground, with brass cap mkd. S2 1/4 S1 1908.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over iron post, with brass cap mkd.</p> <p style="text-align: center;">T27N R17E 1/4 S 2 S 1 2000</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 0°06' E., beginning new measurement.</p>
39.92	<p>The cor. of secs. 1, 2, 35 and 36 on the N. bdy. of Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. T28N R17E S35 S36 S2 S1 T27N 1999.</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of Tp., hereinbefore described.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>N. 0°02' E., bet. secs. 34 and 35.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.03	<p>The 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. S34 1/4 S35 1908.</p> <p>Add the marks T27N R17E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr style="width: 30%; margin: 10px auto;"/>
	<p>N. 0°05' W., beginning new measurement.</p>
40.01	<p>The cor. of secs. 26, 27, 34 and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. T27N R17E S27 S26 S34 S35 1908.</p> <p>Add the marks 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/>
	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 89°58' W., bet. secs. 26 and 35.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 26 and 35, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T27N R17E</p> <p>S26</p> <p>1/4 ———</p> <p>S35</p> <p>2000</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.02	<p>The cor. of secs. 26, 27, 34 and 35.</p> <hr/>

Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.01	<p>N. 0°02' W., bet. secs. 26 and 27.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p> <p>Point for the 1/4 sec. cor. of secs. 26 and 27, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R17E 1/4 S27 S26 2000</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.02	<p>The cor. of secs. 22, 23, 26 and 27, monumented with an iron post, 2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. T27N R17E S22 S23 S27 S26 1908.</p> <p>Add the marks 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89°52' W., bet. secs. 23 and 26.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p> <p>Point for the 1/4 sec. cor. of secs. 23 and 26, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R17E S23 1/4 ——— S26 2000</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
40.00	

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>The cor. of secs. 22, 23, 26 and 27.</p> <hr/> <p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.01	<p>The 1/4 sec. cor. of secs. 22 and 23, monumented with an iron post, 1 in. diam., firmly set, 20 ins. below the ground, with brass cap mkd. S22 1/4 S23 1908.</p> <p>Add the marks T27N R17E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°03' W., beginning new measurement.</p>
40.02	<p>The cor. of secs. 14, 15, 22 and 23, monumented with an iron post, 2 ins. diam., firmly set, 15 ins. below the ground, with brass cap mkd. T27N R17E S15 S14 S22 S23 1908.</p> <p>Add the marks 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>Cor. is located in abandon cultivated field.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89°55' W., bet. secs. 14 and 23.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
39.97	<p>Point for the 1/4 sec. cor. of secs. 14 and 23, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>T27N R17E S14 1/4 ——— S23 2000</p> </div>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.94	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 14, 15, 22 and 23.</p> <hr/> <p>North, bet. secs. 14 and 15.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.00	<p>The 1/4 sec. cor. of secs. 14 and 15, monumented with an iron post, filled with concrete, 1 in. diam., firmly set, 31 ins. below the ground, with brass cap missing.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. below the ground, over iron post, in cultivated corn field, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R17E 1/4 S15 S14 2000</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 0°03' W., beginning new measurement.</p>
40.02	<p>The cor. of secs. 10, 11, 14 and 15, monumented with an iron post, 2 ins. diam., firmly set, 19 ins. below the ground, with brass cap mkd. T27N R17E S10 S11 S15 S14 1908.</p> <p>Add the marks 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>Cor. is located in abandon cultivated field.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 89°52' W., bet. secs. 11 and 14.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.96	<p>Point for the 1/4 sec. cor. of secs. 11 and 14, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R17E S11 1/4 ——— S14 2000</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.92	<p>The cor. of secs. 10, 11, 14 and 15.</p> <hr/> <p>N. 0°03' E., bet. secs. 10 and 11.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.01	<p>The 1/4 sec. cor. of secs. 10 and 11, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. S10 1/4 S11 1908.</p> <p>Add the marks T27N R17E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. 0°06' W., beginning new measurement.</p>
40.03	<p>The cor. of secs. 2, 3, 10 and 11, monumented with an iron post, 2 ins. diam., firmly set, projecting 15 ins. above the ground, with brass cap mkd. T27N R17E S3 S2 S10 S11 1908.</p> <p>Add the marks 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 89°52' W., bet. secs. 2 and 11.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.94	<p>Point for the 1/4 sec. cor. of secs. 2 and 11, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R17E S 2 1/4 ——— S11 2000</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.88	<p>The cor. of secs. 2, 3, 10 and 11.</p> <hr/> <p>N. 0°06' E., bet. secs. 2 and 3.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.02	<p>The 1/4 sec. cor. of secs. 2 and 3, monumented with an iron post, 1 in. diam., firmly set, 3 ins. below the ground, with brass cap mkd. S3 1/4 S2 1908.</p> <p>Add the marks T27N R17E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. 0°12' W., beginning new measurement.</p>
40.02	<p>The cor. of secs. 2, 3, 34 and 35 on the N. bdy. of Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. T28N R17E S34 S35 S3 S2 T27N 1999.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 33 and 34.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 33 and 34, there is no remaining evidence of the original cor.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R17E 1/4 S33 S34 2000</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.02	<p>The cor. of secs. 27, 28, 33 and 34, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T27N R17E S28 S27 S33 S34 1908.</p> <p>Add the marks 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S. 89°56' W., bet. secs. 27 and 34.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.05	<p>Point for the 1/4 sec. cor. of secs. 27 and 34, there is no remaining evidence of the original cor.</p> <p>Set a magnet in a white plastic case, 18 ins. below the ground, at base of left bank of Polacca Wash, impracticable to establish a permanent monument.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 22 ins. long, 2½ ins. diam., set 22 ins. in the ground, for a reference monument, bears S. 5°41' E., 31.3 ft. dist., with brass cap mkd. RM T27N R17E S34 31.3 FT TO COR 2000 and an arrow pointing to cor.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
49.40	<p>Center line of State Road 87, paved, 28 ft. wide, bears SSE. and NNW.</p>
80.10	<p>The cor. of secs. 27, 28, 33 and 34.</p> <hr/>

Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.01	<p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p> <p>The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, filled with concrete, 1 in. diam., firmly set, 36 ins. below the ground, with brass cap missing.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. below the ground, over remains of iron post, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R17E 1/4 S28 S27 2000</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located in a cultivated corn field.</p> <hr style="width: 30%; margin: 10px auto;"/>
40.01	<p>N. 0°02' W., beginning new measurement.</p> <p>The cor. of secs. 21, 22, 27 and 28, monumented with an iron post, severely rusted and bent over, 2 ins. diam., firmly set, projecting 16 ins. above the ground, with brass cap mkd. T27N R17E S21 S22 S28 S27 1908.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R17E S21 S22 ----- S28 S27 2000</p> </div> <p>Deposit a magnet in a white plastic case at the base and iron post alongside of the stainless steel post.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S. 89°56' W., bet. secs. 22 and 27.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling desert terrain, through scattered creosote and cacti.
39.98	<p>The 1/4 sec. cor. of secs. 22 and 27, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. S22 1/4 S27 1908.</p> <p>Add the marks T27N R17E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>S. 89°56' W., beginning new measurement.</p>
33.00	Center line of State Road 87, paved, 28 ft. wide, bears SSE. and NNW.
40.12	The cor. of secs. 21, 22, 27 and 28.
	<hr/> <p>N. 0°06' E., bet. secs. 21 and 22.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
23.60	Center line of State Road 87, paved, 28 ft. wide, bears SSE. and NNW.
40.00	<p>The 1/4 sec. cor. of secs. 21 and 22, monumented with an iron post, 1 in. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. S21 1/4 S22 1908.</p> <p>Add the marks T27N R17E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. 0°07' W., beginning new measurement.</p>
40.01	<p>The cor. of secs. 15, 16, 21 and 22, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T27N R17E S16 S15 S21 S22 1908.</p> <p>Add the marks 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>S. 89°56' W., bet. secs. 15 and 22.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.01	<p>The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 1 in. diam., firmly set, 2 ins. below the ground, with brass cap mkd. S15 1/4 S22 1908.</p> <p>Add the marks T27N R17E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>S. 89°54' W., beginning new measurement.</p>
40.04	<p>The cor. of secs. 15, 16, 21 and 22.</p> <hr/>
	<p>N. 0°03' W., bet. secs. 15 and 16.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T27N R17E 1/4 S16 S15 2000</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
50.50	<p>Center line of State Road 87, paved, 28 ft. wide, bears NNE. and SSW.</p>
80.00	<p>The cor. of secs. 9, 10, 15 and 16, monumented with an iron post, 2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T27N R17E S9 S10 S16 S15 1908.</p> <p>Add the marks 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 89°54' W., bet. secs. 10 and 15.</p>
40.03	<p>Point for the 1/4 sec. cor. of secs. 10 and 15, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R17E S10 1/4 ——— S15 2000</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
69.30	Center line of State Road 87, paved, 28 ft. wide, bears NNE. and SSW.
80.06	The cor. of secs. 9, 10, 15, and 16.
	<hr/> <p>N. 0°03' W., bet. secs. 9 and 10.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.02	<p>The 1/4 sec. cor. of secs. 9 and 10, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. S9 1/4 S10 1908.</p> <p>Add the marks T27N R17E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/>
	<p>N. 0°01' E., beginning new measurement.</p>
40.00	<p>The cor. of secs. 3, 4, 9 and 10, monumented with an iron post, 2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. T27N R17E S4 S3 S9 S10 1908.</p> <p>Add the marks 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.02	<p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. 89°53' W., bet. secs. 3 and 10.</p> <p>Point for the 1/4 sec. cor. of secs. 3 and 10, there is no remaining evidence of the original cor.</p> <p>Set rail road spike in center of N. bound lane of State Road 87, paved, 28 ft. wide, bears NNE. and SSW.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 81°17' E., 117.0 ft. dist., with brass cap mkd. RM T27N R17E S3 117.0 FT TO COR 2000 and an arrow pointing to cor.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 33°51' E., 126.6 ft. dist., with brass cap mkd. RM T27N R17E S10 126.6 FT TO COR 2000 and an arrow pointing to cor.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Reference monuments are located in W. right-of-way fence.</p>
80.04	<p>The cor. of secs. 3, 4, 9 and 10.</p> <hr/> <p>N. 0°05' W., bet. secs. 3 and 4.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.02	<p>The 1/4 sec. cor. of secs. 3 and 4, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. S4 1/4 S3 1908.</p> <p>Add the marks T27N R17E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>N. 0°05' W., beginning new measurement.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.05	<p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. T28N R17E S33 S34 S4 S3 T27N 1999.</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 32 and 33.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.03	<p>The 1/4 sec. cor. of secs. 32 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. S32 1/4 S33 1908.</p> <p>Add the marks T27N R17E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. 0°02' W., beginning new measurement.</p>
40.02	<p>The cor. of secs. 28, 29, 32 and 33, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T27N R17E S29 S28 S32 S33 1908.</p> <p>Add the marks 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p> <p>S. 89°57' W., bet. secs. 28 and 33.</p>
40.06	<p>Point for the 1/4 sec. cor. of secs. 28 and 33, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T27N R17E S28 1/4 ——— S33 2000</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>80.12 The cor. of secs. 28, 29, 32, and 33.</p> <hr/>
	<p>North, bet. secs. 28 and 29.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p> <p>40.02 The 1/4 sec. cor. of secs. 28 and 29, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. S29 1/4 S28 1908.</p> <p>Add the marks T27N R17E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron steel post.</p> <hr/> <p>North, beginning new measurement.</p>
	<p>40.01 The cor. of secs. 20, 21, 28 and 29, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T27N R17E S20 S21 S29 S28 1908.</p> <p>Add the marks 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/>
	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. 89°58' W., bet. secs. 21 and 28.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p> <p>39.92 The 1/4 sec. cor. of secs. 21 and 28, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. S21 1/4 S28 1908.</p> <p>Add the marks T27N R17E 2000 to the brass cap.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.14	<p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>S. 89°58' W., beginning new measurement.</p> <p>The cor. of secs. 20, 21, 28 and 29.</p> <hr/>
40.02	<p>N. 0°03' W., bet. secs. 20 and 21.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p> <p>The 1/4 sec. cor. of secs. 20 and 21, monumented with an iron post, 1 in. diam., firmly set, 26 ins. below the ground, with brass cap mkd. S20 1/4 S21 1908.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, over iron post, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R17E 1/4 S20 S21 2000</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>North, beginning new measurement.</p>
40.02	<p>The cor. of secs. 16, 17, 20 and 21, monumented with an iron post, 2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T27N R17E S17 S16 S20 S21 1908.</p> <p>Add the marks 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/>
8.40	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>West, bet. secs. 16 and 21.</p> <p>Center line of State Road 87, paved, 28 ft. wide, bears N. and S.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.04	<p>Point for the 1/4 sec. cor. of secs. 16 and 21, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 15 ins. below the ground, in cultivated corn field, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R17E S16 1/4 ——— S21 2000</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.08	<p>The cor. of secs. 16, 17, 20 and 21.</p> <hr/> <p>N. 0°02' W., bet. secs. 16 and 17.</p> <p>Over broken, rolling desert terrain, through scattered creosote and cacti.</p>
40.02	<p>The 1/4 sec. cor. of secs. 16 and 17, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. S17 1/4 S16 1908.</p> <p>Add the marks T27N R17E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron steel post.</p> <hr/>
	<p>N 0°02' W., beginning new measurement.</p>
40.01	<p>The cor. of secs. 8, 9, 16 and 17, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R17E S 8 S 9 ——— ——— S17 S16 2000</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>
	<p>From the cor. of secs. 9, 10, 15 and 16.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N 89°59' W., bet. secs. 9 and 16.
40.02	Point for the 1/4 sec. cor. of secs. 9 and 16, there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T27N R17E S 9 1/4 ——— S16 2000 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.04	The cor. of secs. 8, 9, 16 and 17.
	N. 0°02' W., bet. secs. 8 and 9. Over rolling desert terrain, through scattered creosote and cacti.
40.01	Point for the 1/4 sec. cor. of secs. 8 and 9, there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T27N R17E 1/4 S 8 S 9 2000 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
52.60	Graded road, 25 ft. wide, bears NE. and SW.
80.02	The cor. of secs. 4, 5, 8 and 9, monumented with an iron post, 2 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. T27N R17E S5 S4 S8 S9 1908. Add the marks 2000 to the brass cap. Deposit a magnet in a white plastic case alongside the iron post.

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.02	<p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 89°35' W., bet. secs. 4 and 9.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p> <p>The 1/4 sec. cor. of secs. 4 and 9, monumented with an iron post, 1 in. diam., firmly set, 3 ins. below the ground, with brass cap mkd. S4 1/4 S9 1908.</p> <p>Add the marks T27N R17E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>S. 89°37' W., beginning new measurement.</p>
40.02	<p>The cor. of secs. 4, 5, 8 and 9.</p> <hr/> <p>N. 0°08' W., bet. secs. 4 and 5.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.01	<p>The 1/4 sec. cor. of secs. 4 and 5, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. S5 1/4 S4 1908.</p> <p>Add the marks T27N R17E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. 0°09' W., beginning new measurement.</p>
39.91	<p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of Tp., monumented with an iron post, 3 ins. diam., firmly set, 1 in. below the ground, with brass cap mkd. T28N R17E S32 S33 S5 S4 T27N 1999.</p> <hr/> <p>From the cor of secs. 5, 6, 31 and 32, on the S. bdy. of Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 31 and 32.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.05	<p>The 1/4 sec. cor. of secs. 31 and 32, monumented with an iron post, 1 in. diam., filled with concrete, firmly set, 2 ins. below the ground, with brass cap missing.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, over iron post, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R17E 1/4 S31 S32 2000</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°05' W., beginning new measurement.</p>
40.02	<p>The cor. of secs. 29, 30, 31 and 32, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R17E S30 S29 ----- S31 S32 2000</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>S 89°56' W., bet. secs. 29 and 32.</p>
40.09	<p>Point for the 1/4 sec. cor. of secs. 29 and 32, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R17E S29 1/4 ----- S32 2000</p> </div>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.18	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 29, 30, 31 and 32.</p>
40.00	<p>S 89°53' W., bet. secs. 30 and 31.</p> <p>Point for the 1/4 sec. cor. of secs. 30 and 31; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R17E S30 1/4 ——— S31 2000</p>
86.38	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of Tp., hereinbefore described.</p>
40.02	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°05' W., bet. secs. 29 and 30.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p> <p>The 1/4 sec. cor. of secs. 29 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. S30 1/4 S29 1908.</p> <p>Add the marks T27N R17E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p>
39.96	<p>N. 0°05' W., beginning new measurement.</p> <p>The cor. of secs. 19, 20, 29 and 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T27N R17E S19 S20 S30 S29 1908.</p> <p>Add the marks 2000 to the brass cap.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89°59' W., bet. secs. 20 and 29.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.15	<p>The 1/4 sec. cor. of secs. 20 and 29, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. S20 1/4 S29 1908.</p> <p>Add the marks T27N R17E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the stainless steel post.</p> <hr/> <p>S 89°48' W., beginning new measurement.</p>
40.11	<p>The cor. of secs. 19, 20, 29 and 30.</p> <hr/> <p>S. 89°54' W., bet. secs. 19 and 30.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.07	<p>The 1/4 sec. cor. of secs. 19 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. S19 1/4 S30 1908.</p> <p>Add the marks T27N R17E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>S 89°54' W., beginning new measurement.</p>
46.29	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°04' W., bet. secs. 19 and 20.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.02	<p>Over rolling desert terrain, through scattered creosote and cacti.</p> <p>The 1/4 sec. cor. of secs. 19 and 20, monumented with an iron post, 1 in. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. S19 1/4 S20 1908.</p> <p>Add the marks T27N R17E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. 0°04' W., beginning new measurement.</p>
40.09	<p>The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T27N R17E S18 S17 S19 S20 1908.</p> <p>Add the marks 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>S. 89°56' W., bet. secs. 17 and 20.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.15	<p>Point for the 1/4 sec. cor. of secs. 17 and 20, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R17E S17 1/4 ——— S20 2000</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.30	<p>The cor. of secs. 17, 18, 19 and 20.</p> <hr/> <p>S. 89°52' W., bet. secs. 18 and 19.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling desert terrain, through scattered creosote and cacti.
40.00	<p>Point for the 1/4 sec. cor. of secs. 18 and 19; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R17E S18 1/4 ——— S19 2000</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
86.35	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°05' W., bet. secs. 17 and 18.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
39.98	<p>Point for the 1/4 sec. cor. of secs. 17 and 18, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R17E 1/4 S18 S17 2000</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
68.00	Graded road, 25 ft. wide, bears E. and W.
79.96	<p>The cor. of secs. 7, 8, 17 and 18, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. T27N R17E S7 S8 S18 S17 1908.</p> <p>Add the marks 2000 to the brass cap.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>S. 89°53' W., bet. secs. 8 and 17.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.18	<p>Point for the 1/4 sec. cor. of secs. 8 and 17, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T27N R17E S 8 1/4 ——— S17 2000</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.36	<p>The cor. of secs. 7, 8, 17 and 18.</p> <hr/> <p>S. 89°55' W., bet. secs. 7 and 18.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p>
40.07	<p>The 1/4 sec. cor. of secs. 7 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. S7 1/4 S18 1908.</p> <p>Add the marks T27N R17E 2000 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>S. 89°54' W., beginning new measurement.</p>
46.16	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.03	<p>N. 0°01' W., bet. secs. 7 and 8.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p> <p>Point for the 1/4 sec. cor. of secs. 7 and 8, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R17E 1/4 S 7 S 8 2000</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.06	<p>Point for the cor. of secs. 5, 6, 7 and 8, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R17E S 6 S 5 ----- S 7 S 8 2000</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
40.16	<hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>S. 89°55' W., bet. secs. 5 and 8.</p> <p>Over rolling desert terrain, through scattered creosote and cacti.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 8, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T27N R17E S 5 1/4 ——— S 8 2000
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.32	The cor. of secs. 5, 6, 7 and 8.
	<hr/> S. 89°53' W., bet. secs. 6 and 7. Over rolling desert terrain, through scattered creosote and cacti.
38.30	Graded road, 25 ft. wide, bears ENE. and WSW.
40.10	The 1/4 sec. cor. of secs. 6 and 7, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. S6 1/4 S7 1908.
	Add the marks T27N R17E 2000 to the brass cap.
	Deposit a magnet in a white plastic case alongside the iron post.
	<hr/> S. 89°53' W., beginning new measurement.
46.11	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of Tp., hereinbefore described.
	<hr/> From the cor. of secs. 5, 6, 7 and 8. N. 0°01' W., bet. secs. 5 and 6. Over rolling desert terrain, through scattered creosote and cacti.
20.80	Graded road, 25 ft. wide, bears ENE. and WSW.
40.03	The 1/4 sec. cor. of secs. 5 and 6, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. S6 1/4 S5 1908.
	Add the marks T27N R17E 2000 to the brass cap.

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°10' E., beginning new measurement.</p>
39.89	<p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of Tp., monumented with a stainless steel post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T28N R17E S31 S32 S6 S5 T27N 1999.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p>This survey is located on the Hopi Indian Reservation, south of the town of Second Mesa.</p> <p>Most of the township contains rolling sand dunes and grassland, Many of the low lying areas are used for dryland farming. The grass lands are used for the grazing of cattle and sheep.</p> <p>Arizona highway 87 traverses the township in a northerly and southerly direction.</p> <p>Elevation ranges from 5400 to 5500 feet above sea level.</p> <p>No evidence of past or present mineral activity was noted.</p> <p>The mean magnetic declination of 12° E., was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2000 for the dates of survey.</p> <hr/>

CERTIFICATE OF SURVEY

I, Joe R. Salazar, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 30th day of August, 2000, I have dependently resurveyed the Fourth Guide Meridian East through Township 27 North (W. Bdy.), the south and east boundaries and the subdivisional lines, T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

11/23/01
(Date)

Joe R. Salazar
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the Fourth Guide Meridian East through Township 27 North (W. Bdy.), the south and east boundaries and the subdivisional lines, T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona, executed by Joe R. Salazar, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

July 15, 2002
(Date)

Henry D. Rowmker
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 27 N., R. 17 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____~~
~~(Date)~~

~~_____~~
~~(Chief Cadastral Surveyor of Arizona)~~