

ORIGINAL

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

SURVEY

OF

THE SOUTH, EAST, WEST,

AND NORTH BOUNDARIES,

AND

THE SUBDIVISIONAL LINES,

TOWNSHIP 31 NORTH, RANGE 22 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Jones Curtiss, Cadastral Surveyor

Under Special Instructions dated and approved August 14, 2000, which provided for the surveys included under Group Number 855 and assignment instructions dated August 14, 2000.

Survey Commenced September 12, 2000

Survey Completed October 10, 2000

## INDEX DIAGRAM

TOWNSHIP 31 NORTH, RANGE 22 EAST,

GILA AND SALT RIVER MERIDIAN, ARIZONA

25 20 6	25 72 5	23 60 4	23 49 3	22 41 2	21 33 1 15
72 19 7	71 70 8	59 57 9	49 48 10	41 40 11	33 32 12 14
69 18 18	69 68 17	57 56 16	47 47 15	39 39 14	31 31 13 13
67 17 19	66 65 20	55 53 21	46 45 22	38 37 23	30 29 24 12
64 16 30	64 63 29	53 52 28	44 43 27	37 36 26	28 28 25 11
62 16 31 9	62 61 32 8	51 50 33 7	43 42 34 6	35 34 35 5	27 26 36 10 4

## T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes describe the survey of the south, east, west, and north boundaries, and the subdivisional lines, Township 31 North, Range 22 East, Gila and Salt River Meridian, Arizona.

The east boundary of the 1882 Executive Order Boundary of the Hopi Indian Reservation was surveyed by Leonard W. Murphy and Paul G. Bauer in 1964. The south boundary of T. 29 N., R. 24 E., identical with the Seventh Standard Parallel North, through R. 24 E., was surveyed by William F. Olver and Daniel N. Patterson in 1989.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated August 14, 2000, for Group No. 855, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic and static global positioning system observations using Trimble 4400 and 4700 model receivers.

Geodetic control was derived from first order or better U. S. Coast and Geodetic Survey triangulation stations "BEAUTIFUL 1951" and "LOHALI 1951" as published by the National Geodetic Survey, NAD83(1992). The geographic position of the southeast corner of the township is as follows:

Latitude: 36°02'29.35" N.                      Longitude: 109°55'18.44" W.

The mean magnetic declination is 12° E.

Survey of the South Boundary,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS															
	<p>Beginning at the point for the cor. of Tps. 30 and 31 N., Rs. 22 and 23 E., established at 6 miles (480.00 chs.) West and 12 miles (960.00 chs.) North of the stan. cor. of Tps. 29 N., Rs. 23 and 24 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. SC T29N R23E R24E S36 S31 1989.</p>														
	<p>from which the original bearing object</p>														
	<p>The chisel marks X B0, on a sandstone outcrop, 4 x 2 x 2 1/2 ft. high, bears N. 43 1/2° E., 22 lks. dist.</p>														
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>														
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T31N</td></tr> <tr><td style="text-align: center;">R22E</td><td style="text-align: center;">R23E</td></tr> <tr><td style="text-align: center;">S36</td><td style="text-align: center;">S31</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr><td colspan="2" style="text-align: center;">T30N</td></tr> <tr><td colspan="2" style="text-align: center;">2000</td></tr> </table>	T31N		R22E	R23E	S36	S31	-----		S 1	S 6	T30N		2000	
T31N															
R22E	R23E														
S36	S31														
-----															
S 1	S 6														
T30N															
2000															
	<p>from which</p>														
	<p>The marks X B0, chiseled on a sandstone outcrop, bear S. 84 1/2° W., 1.00 ch. dist.</p>														
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>														
	<p>Cor. is located on a steep slope, 15 lks. S. of a cliff at the head of a wash in a canyon, drains NNE.</p>														
	<p>West, bet. secs. 1 and 36.</p>														
	<p>Over broken and rugged land, along the northern slope of Balakai Mesa.</p>														
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p>														
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>														
	<table style="margin-left: auto; margin-right: auto;"> <tr><td style="text-align: center;">T31N</td><td style="text-align: center;">R22E</td></tr> <tr><td></td><td style="text-align: center;">S36</td></tr> <tr><td style="text-align: center;">1/4</td><td style="text-align: center;">---</td></tr> <tr><td></td><td style="text-align: center;">S 1</td></tr> <tr><td colspan="2" style="text-align: center;">T30N</td></tr> <tr><td colspan="2" style="text-align: center;">2000</td></tr> </table>	T31N	R22E		S36	1/4	---		S 1	T30N		2000			
T31N	R22E														
	S36														
1/4	---														
	S 1														
T30N															
2000															

Survey of the South Boundary,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS															
80.00	<p>from which</p> <p>The marks X B0, chiseled on a sandstone outcrop, bear N. 85 1/2° E., 17 lks. dist.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on the steep W. slope of a prominent ridge, bears N. and S.</p> <p>Point for the cor of secs. 1, 2, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T31N</td><td>R22E</td></tr> <tr><td>S35</td><td>S36</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td colspan="2" style="text-align: center;">T30N</td></tr> <tr><td colspan="2" style="text-align: center;">2000</td></tr> </table> <p>from which</p> <p>The marks X B0, chiseled on the face of a sandstone boulder, 6 X 2 X 4 ft. high, bear N. 57 3/4° E., 1.48 chs. dist.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on the W. edge of a sagebrush clearing.</p> <p>Land, broken and rugged. Soil, rocky and rocky clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p>	T31N	R22E	S35	S36			S 2	S 1			T30N		2000	
T31N	R22E														
S35	S36														
S 2	S 1														
T30N															
2000															
40.00	<p>West, bet. secs. 2 and 35.</p> <p>Over broken and rugged land.</p> <p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>														

Survey of the South Boundary,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p style="text-align: center;">T31N R22E S35 1/4 — S 2 T30N 2000</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 2, 3, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R22E S34   S35 —   — S3   S2 T30N 2000</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, broken and rugged. Soil, rocky and rocky clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>West, bet. secs. 3 and 34.</p> <p>Over broken and rugged land.</p>
40.00	<p style="text-align: center;">T31N R22E S34 1/4 — S 3 T30N 2000</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the South Boundary,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS																					
80.00	<p>Point for the cor. of secs. 3, 4, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td>T31N</td><td>R22E</td></tr> <tr><td>S33</td><td> </td><td>S34</td></tr> <tr><td colspan="3" style="border-top: 1px solid black;"></td></tr> <tr><td>S 4</td><td> </td><td>S 3</td></tr> <tr><td colspan="3" style="border-top: 1px solid black;"></td></tr> <tr><td colspan="3" style="text-align: center;">T30N</td></tr> <tr><td colspan="3" style="text-align: center;">2000</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, broken and rugged. Soil, rocky and rocky clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>West, bet. secs. 4 and 33.</p> <p>Over rolling and broken land.</p>	T31N	R22E	S33		S34				S 4		S 3				T30N			2000		
T31N	R22E																				
S33		S34																			
S 4		S 3																			
T30N																					
2000																					
37.10	Wash, 6 ft. wide, 5 ft. deep, drains NNE.																				
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td>T31N</td><td>R22E</td></tr> <tr><td colspan="2" style="text-align: center;">S33</td></tr> <tr><td colspan="2" style="text-align: center;">1/4 —</td></tr> <tr><td colspan="2" style="text-align: center;">S 4</td></tr> <tr><td colspan="2" style="text-align: center;">T30N</td></tr> <tr><td colspan="2" style="text-align: center;">2000</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 10 lks. W., and on the E. slope, of a wash, 5 ft. wide, 3 ft. deep, drains NNW.</p>	T31N	R22E	S33		1/4 —		S 4		T30N		2000									
T31N	R22E																				
S33																					
1/4 —																					
S 4																					
T30N																					
2000																					
80.00	Point for the cor. of secs. 4, 5, 32, and 33.																				

Survey of the South Boundary,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td colspan="2">T31N R22E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S32</td><td style="padding: 0 5px;">S33</td></tr> <tr><td colspan="2" style="border-top: 1px solid black; border-bottom: 1px solid black;"></td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 5</td><td style="padding: 0 5px;">S 4</td></tr> <tr><td colspan="2">T30N</td></tr> <tr><td colspan="2">2000</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy, rocky and rocky clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>West, bet. secs. 5 and 32.</p> <p>Over rolling land.</p>	T31N R22E		S32	S33			S 5	S 4	T30N		2000	
T31N R22E													
S32	S33												
S 5	S 4												
T30N													
2000													
10.10	Graded road, 15 ft. wide, bears SSE and NNW.												
33.08	Barbed wire fence, 5 strands, bears N. and S.												
40.00	Point for the 1/4 sec. cor. of secs. 5 and 32.												
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td colspan="2">T31N R22E</td></tr> <tr><td colspan="2" style="padding: 0 5px;">S32</td></tr> <tr><td colspan="2" style="padding: 0 5px;">1/4 —</td></tr> <tr><td colspan="2" style="padding: 0 5px;">S 5</td></tr> <tr><td colspan="2">T30N</td></tr> <tr><td colspan="2">2000</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>	T31N R22E		S32		1/4 —		S 5		T30N		2000	
T31N R22E													
S32													
1/4 —													
S 5													
T30N													
2000													
53.15	Trail road, bears N. and S.												
55.70	Barbed wire fence, 5 strands, bears SSE and NNW; enter cultivated field.												
60.34	Barbed wire fence, 3 strands, bears SSE and NNW; leave cultivated field.												

Survey of the South Boundary,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS																		
75.10	Trail road, bears SSE and NNW.																	
80.00	Point for the cor. of secs. 5, 6, 31, and 32.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T31N</td><td>R22E</td></tr> <tr><td>S31</td><td> </td><td>S32</td></tr> <tr><td colspan="3"><hr style="width: 100%;"/></td></tr> <tr><td>S 6</td><td> </td><td>S 5</td></tr> <tr><td colspan="3" style="text-align: center;">T30N</td></tr> <tr><td colspan="3" style="text-align: center;">2000</td></tr> </table> </div> Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.  Land, rolling. Soil, sandy and sandy clay. No timber; scattered brush, greasewood and native grasses.	T31N	R22E	S31		S32	<hr style="width: 100%;"/>			S 6		S 5	T30N			2000		
T31N	R22E																	
S31		S32																
<hr style="width: 100%;"/>																		
S 6		S 5																
T30N																		
2000																		
	West, bet. secs. 6 and 31.  Over rolling land.																	
2.80	Wash, 50 ft. wide, 10 ft. deep, drains NW.																	
29.90	Trail road, bears NNE and SSW.																	
40.00	Point for the 1/4 sec. cor. of secs. 6 and 31.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T31N</td><td>R22E</td></tr> <tr><td colspan="2" style="text-align: center;">S31</td></tr> <tr><td colspan="2" style="text-align: center;">1/4 —</td></tr> <tr><td colspan="2" style="text-align: center;">S 6</td></tr> <tr><td colspan="2" style="text-align: center;">T30N</td></tr> <tr><td colspan="2" style="text-align: center;">2000</td></tr> </table> </div> Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.	T31N	R22E	S31		1/4 —		S 6		T30N		2000						
T31N	R22E																	
S31																		
1/4 —																		
S 6																		
T30N																		
2000																		
57.90	Trail road, bears ESE and WNW.																	
68.40	Trail road, bears ENE and WSW.																	

Survey of the South Boundary,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS															
78.94	<p>Point for the cor. of Tps. 30 and 31 N., Rs. 21 and 22 E., established at 11.98675 miles (958.94 chs.) West and 12 miles (960.00 chs.) North of the stan. cor. of Tps. 29 N., Rs. 23 and 24 E, hereinbefore described.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T31N</td></tr> <tr><td>R21E</td><td>R22E</td></tr> <tr><td>S36</td><td>S31</td></tr> <tr><td colspan="2">— —</td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td colspan="2">T30N</td></tr> <tr><td colspan="2">2000</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy and sandy clay. No timber; scattered brush, greasewood and native grasses.</p> <hr/> <p style="text-align: center;">Survey of the East Boundary, T. 31 N., R. 22 E., Gila Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of Tps. 30 and 31 N., Rs. 22 and 23 E., hereinbefore described.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over broken and rugged land.</p>	T31N		R21E	R22E	S36	S31	— —		S 1	S 6	T30N		2000	
T31N															
R21E	R22E														
S36	S31														
— —															
S 1	S 6														
T30N															
2000															
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T31N</td></tr> <tr><td>R22E</td><td>R23E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S36</td><td>S31</td></tr> <tr><td colspan="2">2000</td></tr> </table> </div> <p>from which</p> <p style="text-align: center;">The marks X B0, chiseled on a sandstone outcrop, bear S. 53 1/4° W., 42 lks. dist.</p>	T31N		R22E	R23E	1/4		S36	S31	2000					
T31N															
R22E	R23E														
1/4															
S36	S31														
2000															

Survey of the East Boundary,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS													
80.00	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on a steep W. slope of a narrow ridge, bears N. and S.</p> <p>Point for the cor. of secs. 25, 30, 31, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T31N</td></tr> <tr><td>R22E</td><td>R23E</td></tr> <tr><td>S25</td><td>S30</td></tr> <tr><td colspan="2">— —</td></tr> <tr><td>S36</td><td>S31</td></tr> <tr><td colspan="2">2000</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, broken and rugged. Soil, rocky and rocky clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p>	T31N		R22E	R23E	S25	S30	— —		S36	S31	2000	
T31N													
R22E	R23E												
S25	S30												
— —													
S36	S31												
2000													
40.00	<p>North, bet. secs. 25 and 30.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T31N</td></tr> <tr><td>R22E</td><td>R23E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S25</td><td>S30</td></tr> <tr><td colspan="2">2000</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>	T31N		R22E	R23E	1/4		S25	S30	2000			
T31N													
R22E	R23E												
1/4													
S25	S30												
2000													
80.00	<p>Point for the cor. of secs. 19, 24, 25, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>												

Survey of the East Boundary,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<table style="margin: auto;"> <tr><td colspan="2">T31N</td></tr> <tr><td>R22E</td><td>R23E</td></tr> <tr><td>S24</td><td>S19</td></tr> <tr><td colspan="2">— —</td></tr> <tr><td>S25</td><td>S30</td></tr> <tr><td colspan="2">2000</td></tr> </table>	T31N		R22E	R23E	S24	S19	— —		S25	S30	2000	
T31N													
R22E	R23E												
S24	S19												
— —													
S25	S30												
2000													
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 1.20 chs. W. of a wash, 35 ft. wide, 10 ft. deep, drains NNE.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p>												
	<p>North, bet. secs. 19 and 24.</p> <p>Over rolling and broken land.</p>												
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>												
	<table style="margin: auto;"> <tr><td colspan="2">T31N</td></tr> <tr><td>R22E</td><td>R23E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S24</td><td>S19</td></tr> <tr><td colspan="2">2000</td></tr> </table>	T31N		R22E	R23E	1/4		S24	S19	2000			
T31N													
R22E	R23E												
1/4													
S24	S19												
2000													
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on a spur, 10 lks. E. of a white sandstone ledge, 30 ft. high, bears SSE and NNW.</p>												
50.71	<p>A third order U. S. Geological Survey benchmark, bears West, 4.54 chs. dist., monumented with a standard brass benchmark tablet, 3 1/2 ins. diam., set in a concrete cylinder, 7 ins. diam., firmly set, flush with the ground, with top mkd. BM 12 DOR.</p>												
53.81	<p>Navajo Route 4, asphalt pavement, 26 ft. wide, bears ENE and WSW.</p>												
55.70	<p>Power line, bears ENE and WSW.</p>												

Survey of the East Boundary,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS													
77.60	Apache County Route C435, a graded road, 20 ft. wide, bears E. and W.												
80.00	<p>Point for the cor. of secs. 13, 18, 19, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T31N</td></tr> <tr><td>R22E</td><td>R23E</td></tr> <tr><td>S13</td><td>S18</td></tr> <tr><td colspan="2">— —</td></tr> <tr><td>S24</td><td>S19</td></tr> <tr><td colspan="2">2000</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, sagebrush, greasewood and native grasses.</p> <hr/> <p>North, bet. secs. 13 and 18.</p> <p>Over rolling and broken land.</p>	T31N		R22E	R23E	S13	S18	— —		S24	S19	2000	
T31N													
R22E	R23E												
S13	S18												
— —													
S24	S19												
2000													
30.40	High voltage transmission line, bears ENE and WSW.												
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T31N</td></tr> <tr><td>R22E</td><td>R23E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S13</td><td>S18</td></tr> <tr><td colspan="2">2000</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>	T31N		R22E	R23E	1/4		S13	S18	2000			
T31N													
R22E	R23E												
1/4													
S13	S18												
2000													
80.00	<p>Point for the cor. of secs. 7, 12, 13, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>												

Survey of the East Boundary,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T31N</td></tr> <tr><td>R22E</td><td>R23E</td></tr> <tr><td>S12</td><td>S 7</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S13</td><td>S18</td></tr> <tr><td colspan="2">2000</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 1.95 chs. S. of a trail road, bears SSE and NNW.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, sagebrush, greasewood and native grasses.</p>	T31N		R22E	R23E	S12	S 7	-----		S13	S18	2000	
T31N													
R22E	R23E												
S12	S 7												
-----													
S13	S18												
2000													
40.00	<p>North, bet. secs. 7 and 12.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>												
80.00	<div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T31N</td></tr> <tr><td>R22E</td><td>R23E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S12</td><td>S 7</td></tr> <tr><td colspan="2">2000</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 1, 6, 7, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	T31N		R22E	R23E	1/4		S12	S 7	2000			
T31N													
R22E	R23E												
1/4													
S12	S 7												
2000													
	<div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T31N</td></tr> <tr><td>R22E</td><td>R23E</td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S12</td><td>S 7</td></tr> <tr><td colspan="2">2000</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>	T31N		R22E	R23E	S 1	S 6	-----		S12	S 7	2000	
T31N													
R22E	R23E												
S 1	S 6												
-----													
S12	S 7												
2000													

Survey of the East Boundary,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, rocky and rocky clay. Timber, piñon and juniper; undergrowth, sagebrush, greasewood and native grasses.</p> <hr/> <p>North, bet. secs. 1 and 6.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor, of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T31N R22E R23E 1/4 S 1   S 6 2000</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of Tps. 31 and 32 N., Rs. 22 and 23 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T32N R22E   R23E S36   S31 ----- S 1   S 6 T31N 2000</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, rocky and rocky clay. Timber, piñon and juniper; undergrowth, sagebrush, greasewood and native grasses.</p> <hr/> <p style="text-align: center;">Survey of the West Boundary, T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona</p> <hr/>

Survey of the West Boundary,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of Tps. 30 and 31 N., Rs. 21 and 22 E., hereinbefore described.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over rolling land.</p>
20.30	Graded road, 20 ft. wide, bears SE and NW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T31N R21E R22E 1/4 S36   S31 2000</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
46.70	Navajo Route 67, a graded road, 25 ft. wide, bears NNE and SSW.
61.90	Wash, 15 ft. wide, 5 ft. deep, drains SSW.
80.00	<p>Point for the cor. of secs. 25, 30, 31, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T31N R21E   R22E S25   S30 ----- S36   S31 2000</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy and sandy clay. No timber; scattered brush, greasewood and native grasses.</p> <hr/> <p>North, bet. secs. 25 and 30.</p> <p>Over rolling land.</p>

Survey of the West Boundary,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
6.30	High voltage transmission line, bears ENE and WSW, and S. bank of Polacca Wash, 40 ft. high, bears ENE and WSW.
10.10	N. bank of Polacca Wash, 40 ft. high, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 30.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T31N            R21E   R22E            1/4            S25   S30            2000         </div> Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
49.50	Trail road, bears E. and W.
80.00	Point for the cor. of secs. 19, 24, 25, and 30.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T31N            R21E   R22E            S24   S19            S25   S30            2000         </div> Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.  Land, rolling. Soil, sandy and sandy clay. No timber; scattered brush, greasewood and native grasses.
	North, bet. secs. 19 and 24.  Over rolling land.
11.21	S. right-of-way fence of Navajo Route 4, barbed wire, 5 strands, parallels highway.
12.76	Navajo Route 4, asphalt pavement, 26 ft. wide, bears E. and W.

Survey of the West Boundary,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
13.80	Power line, bears E. and W.
14.06	N. right-of-way fence of Navajo Route 4, barbed wire, 5 strands, parallels highway.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 24.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T31N            R21E   R22E            1/4            S24   S19            2000         </div> Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
69.30	Power line, bears NNE and SSW.
71.90	Navajo Route 29, a graded road, 20 ft. wide, bears NNE and SSW.
80.00	Point for the cor. of secs. 13, 18, 19, and 24.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T31N            R21E   R22E            S13   S18            ————            S24   S19            2000         </div> Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.  Land, rolling. Soil, sandy and sandy clay. No timber; scattered brush, greasewood and native grasses.
	North, bet. secs. 13 and 18.  Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 18.

Survey of the West Boundary,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R21E R22E 1/4 S13   S18 2000</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 7, 12, 13, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R21E   R22E S12   S 7 ----- S13   S18 2000</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy and sandy clay. No timber; scattered brush, greasewood and native grasses.</p>
40.00	<p>North, bet. secs. 7 and 12.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T31N R21E R22E 1/4 S12   S 7 2000</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the West Boundary,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS													
80.00	<p>Point for the cor. of secs. 1, 6, 7, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T31N</td></tr> <tr><td>R21E</td><td>R22E</td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td colspan="2"><hr style="width: 50%; margin: 0 auto;"/></td></tr> <tr><td>S12</td><td>S 7</td></tr> <tr><td colspan="2">2000</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, broken and rugged. Soil, rocky and rocky clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>North, bet. secs. 1 and 6.</p> <p>Over rolling and broken land.</p>	T31N		R21E	R22E	S 1	S 6	<hr style="width: 50%; margin: 0 auto;"/>		S12	S 7	2000	
T31N													
R21E	R22E												
S 1	S 6												
<hr style="width: 50%; margin: 0 auto;"/>													
S12	S 7												
2000													
34.10	<p>Top of mesa, bears NE and SW.</p>												
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T31N</td></tr> <tr><td>R21E</td><td>R22E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td colspan="2">2000</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>	T31N		R21E	R22E	1/4		S 1	S 6	2000			
T31N													
R21E	R22E												
1/4													
S 1	S 6												
2000													
76.20	<p>Trail road, bears NE and SW.</p>												
80.00	<p>Point for the cor. of Tps. 31 and 32 N., Rs. 21 and 22 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>												

Survey of the West Boundary,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS															
	<table style="margin: auto;"> <tr><td colspan="2">T32N</td></tr> <tr><td>R21E</td><td>R22E</td></tr> <tr><td>S36</td><td>S31</td></tr> <tr><td colspan="2">—</td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td colspan="2">T31N</td></tr> <tr><td colspan="2">2000</td></tr> </table>	T32N		R21E	R22E	S36	S31	—		S 1	S 6	T31N		2000	
T32N															
R21E	R22E														
S36	S31														
—															
S 1	S 6														
T31N															
2000															
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling, broken and rugged. Soil, rocky and rocky clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p>														
	<p>Survey of the North Boundary, T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona</p>														
	<p>From the cor. of Tps. 31 and 32 N., Rs. 22 and 23 E., hereinbefore described.</p> <p>West, bet. secs. 1 and 36.</p> <p>Over broken and rugged land.</p>														
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>														
	<table style="margin: auto;"> <tr><td>T32N</td><td>R22E</td></tr> <tr><td>S36</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 1</td><td></td></tr> <tr><td>T31N</td><td></td></tr> <tr><td>2000</td><td></td></tr> </table>	T32N	R22E	S36		1/4	—	S 1		T31N		2000			
T32N	R22E														
S36															
1/4	—														
S 1															
T31N															
2000															
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>														
80.00	<p>Point for the cor. of secs. 1, 2, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>														

Survey of the North Boundary,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<div style="text-align: center;"> <table border="1"> <tr><td>T32N R22E</td><td></td></tr> <tr><td>S35</td><td>S36</td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td>T31N</td><td></td></tr> <tr><td>2000</td><td></td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 30 lks. N. of a wash, 4 ft. wide, 2 ft. deep, drains WNW.</p> <p>Land, broken and rugged. Soil, rocky and rocky clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p>	T32N R22E		S35	S36	S 2	S 1	T31N		2000			
T32N R22E													
S35	S36												
S 2	S 1												
T31N													
2000													
40.00	<p>West, bet. secs. 2 and 35.</p> <p>Over broken and rugged land.</p> <p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>												
80.00	<div style="text-align: center;"> <table border="1"> <tr><td>T32N R22E</td><td></td></tr> <tr><td>S35</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 2</td><td></td></tr> <tr><td>T31N</td><td></td></tr> <tr><td>2000</td><td></td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 2, 3, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	T32N R22E		S35		1/4	—	S 2		T31N		2000	
T32N R22E													
S35													
1/4	—												
S 2													
T31N													
2000													
	<div style="text-align: center;"> <table border="1"> <tr><td>T32N R22E</td><td></td></tr> <tr><td>S34</td><td>S35</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td>T31N</td><td></td></tr> <tr><td>2000</td><td></td></tr> </table> </div>	T32N R22E		S34	S35	S 3	S 2	T31N		2000			
T32N R22E													
S34	S35												
S 3	S 2												
T31N													
2000													

Survey of the North Boundary,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, broken and rugged. Soil, rocky and rocky clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p>
40.00	<p>West, bet. secs. 3 and 34.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R22E S34 1/4 — S 3 T31N 2000</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 3, 4, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R22E S33   S34 —   — S 4   S 3 T31N 2000</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, rocky and rocky clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <p>West, bet. secs. 4 and 33.</p>

Survey of the North Boundary,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS													
	Over rolling land.												
3.39	Navajo Route 29, asphalt pavement, 29 ft. wide, bears NNE and SSW.												
5.50	Power line, bears NNE and SSW.												
37.60	E. bank of Polacca Wash, 15 ft. high, bears NNE and SSW.												
40.00	Point for the 1/4 sec. cor. of secs. 4 and 33.  Set a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case, 24 ins. below the surface of the ground.  from which  A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 50°00' E., 110.0 ft. dist., with brass cap mkd. T31N R22E 1/4 S4 RM 110.0 FT. TO COR. 2000 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.  A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 50°00' W., 50.0 ft. dist., with brass cap mkd. T32N R22E 1/4 S33 RM 50.0 FT. TO COR. 2000 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.  Cor. is located on the W. bank of Polacca Wash, 15 ft. high, bears N. and S.												
80.00	Point for the cor. of secs. 4, 5, 32, and 33.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T32N</td> <td style="padding: 0 5px;">R22E</td> </tr> <tr> <td style="padding: 0 5px;">S32</td> <td style="padding: 0 5px;">S33</td> </tr> <tr> <td colspan="2" style="text-align: center;">— —</td> </tr> <tr> <td style="padding: 0 5px;">S 5</td> <td style="padding: 0 5px;">S 4</td> </tr> <tr> <td colspan="2" style="text-align: center;">T31N</td> </tr> <tr> <td colspan="2" style="text-align: center;">2000</td> </tr> </table> Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.	T32N	R22E	S32	S33	— —		S 5	S 4	T31N		2000	
T32N	R22E												
S32	S33												
— —													
S 5	S 4												
T31N													
2000													

Survey of the North Boundary,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy and sandy clay. No timber; rabbitbrush, greasewood and native grasses.</p> <hr/> <p>West, bet. secs. 5 and 32.</p> <p>Over rolling land.</p>
30.10	Navajo Route 29, a graded road, 20 ft. wide, bears NNE and SSW.
32.75	Barbed wire fence, 5 strands, bears N. and S.
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T32N R22E S32 1/4 — S 5 T31N 2000</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T32N R22E S31   S32 —   — S 6   S 5 T31N 1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy, rocky and rocky clay. Timber, piñon and juniper; undergrowth, rabbitbrush, sagebrush greasewood and native grasses.</p> <hr/> <p>West, bet. secs. 6 and 31.</p>

Survey of the North Boundary,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over broken and rugged land.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 31.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">T32N R22E S31 1/4 — S 6 T31N 2000</div>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
53.40	Top of mesa, 200 ft. high, bears NNE and SSW.
73.20	Trail road, bears NE and SW.
78.41	The cor. of Tps. 31 and 32 N., Rs. 21 and 22 E., hereinbefore described.  Land, broken and rugged. Soil, rocky and rocky clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.
<hr/> Survey of the Subdivisional lines, T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona <hr/>	
	From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., hereinbefore described.  N. 0°01' W., bet. secs. 35 and 36.  Over broken and rugged land.
40.00	Point for the 1/4 sec. cor. of secs. 35 and 36.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">T31N R22E 1/4 S35   S36 2000</div>

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS											
80.00	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on the E. slope of a vegetated grey clay hill, bears N. and S.</p> <p>Point for the cor. of secs. 25, 26, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T31N</td><td>R22E</td></tr> <tr><td>S26</td><td>S25</td></tr> <tr><td>S35</td><td>S36</td></tr> <tr><td colspan="2">2000</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, broken and rugged. Soil, rocky and rocky clay. Timber, piñon and juniper; undergrowth, rabbitbrush, sagebrush and native grasses.</p>	T31N	R22E	S26	S25	S35	S36	2000			
T31N	R22E										
S26	S25										
S35	S36										
2000											
40.00	<p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 25 and 36.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T31N</td><td>R22E</td></tr> <tr><td></td><td>S25</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S36</td></tr> <tr><td colspan="2">2000</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>	T31N	R22E		S25	1/4	—		S36	2000	
T31N	R22E										
	S25										
1/4	—										
	S36										
2000											
80.00	<p>The cor. of secs. 25, 26, 35, and 36.</p>										

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, rabbitbrush, sagebrush, greasewood and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 25 and 26.</p>
	<p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R22E 1/4 S26   S25 2000</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
49.80	<p>Graded road, 20 ft. wide, bears ESE and WNW.</p>
80.00	<p>Point for the cor. of secs. 23, 24, 25, and 26.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R22E S23   S24 ----- S26   S25 2000</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, rabbitbrush, sagebrush, greasewood and native grasses.</p>
	<p>From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described.</p>
	<p>West, bet. secs. 24 and 25.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 24 and 25.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T31N R22E S24 1/4 — S25 2000</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
80.00	The cor. of secs. 23, 24, 25, and 26.
	Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, rabbitbrush, sagebrush, greasewood and native grasses.
	N. 0°01' W., bet. secs. 23 and 24.
	Over rolling land.
13.42	Navajo Route 4, asphalt pavement, 26 ft. wide, bears ENE and WSW.
15.60	Power line, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T31N R22E 1/4 S23   S24 2000</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
80.00	Point for the cor. of secs. 13, 14, 23, and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS						
	<div style="text-align: center;"> <table border="1"> <tr><td>T31N R22E</td></tr> <tr><td>S14   S13</td></tr> <tr><td>S23   S24</td></tr> <tr><td>2000</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 75 lks. W. of a high voltage transmission line, bears ENE and WSW, and 75 lks. S. of a trail road, bears NNE and SSW.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, rabbitbrush, sagebrush, greasewood and native grasses.</p> <hr/> <p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 13 and 24.</p> <p>Over rolling land.</p>	T31N R22E	S14   S13	S23   S24	2000	
T31N R22E						
S14   S13						
S23   S24						
2000						
7.40	Apache County Route C435, a graded road, 18 ft. wide, bears SE and NW.					
40.00	Point for the 1/4 sec. cor. of secs. 13 and 24.					
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.					
	<div style="text-align: center;"> <table border="1"> <tr><td>T31N R22E</td></tr> <tr><td>S13</td></tr> <tr><td>1/4 —</td></tr> <tr><td>S24</td></tr> <tr><td>2000</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>	T31N R22E	S13	1/4 —	S24	2000
T31N R22E						
S13						
1/4 —						
S24						
2000						
53.20	Apache County Route C435, a graded road, 18 ft. wide, bears SE and NW.					
80.00	The cor. of secs. 13, 14, 23, and 24.					

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, rabbitbrush, sagebrush, greasewood and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 13 and 14.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R22E 1/4 S14   S13 2000</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 11, 12, 13, and 14.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R22E S11   S12 ----- S14   S13 2000</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, rabbitbrush, sagebrush, greasewood and native grasses.</p>
	<p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described.</p>
	<p>West, bet. secs. 12 and 13.</p>
	<p>Over rolling land.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R22E S12 1/4 — S13 2000</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 11, 12, 13, and 14.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, rabbitbrush, sagebrush, greasewood and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over broken land; ascend the foothills of Toadindaaska Mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R22E 1/4 S11   S12 2000</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>True point for the cor. of secs. 1, 2, 11, and 12, falls on a steep slope, where it is impracticable to establish a monument.</p> <p>From this true cor. point, the point selected for the witness cor. to the cor. of secs. 1, 2, 11, and 12, bears N. 25°30' E., 68 lks. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<div style="text-align: center;"> <p>WC T31N R22E S 2   S 1 ----- S11   S12 ↙ ↘ 2000</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Witness cor. is located on a ridge, bears SSE and NNW.</p> <p>Land, rolling and broken. Soil, rocky and rocky clay. Timber, piñon and juniper; undergrowth, rabbitbrush, sagebrush, greasewood and native grasses.</p>
	<p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 1 and 12.</p> <p>Over broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T31N R22E S 1 1/4 — S12 2000</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>True point for the cor. of secs. 1, 2, 11, and 12.</p> <p>Land, rolling and broken. Soil, rocky and rocky clay. Timber, piñon and juniper; undergrowth, rabbitbrush, sagebrush, and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 1 and 2.</p> <p>Over broken and rugged land.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
28.60	S. rim of Toadindaaska Mesa, bears E. and W.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  T31N R22E 1/4 S 2   S 1 2000  Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
47.00	N. rim of Toadindaaska Mesa, bears E. and W.
80.00	The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., hereinbefore described.  Land, broken and rugged. Soil, rocky and rocky clay. Timber, piñon and juniper; undergrowth, rabbitbrush, sagebrush, scrub oak and native grasses.
	From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., hereinbefore described.  N. 0°01' W., bet. secs. 34 and 35.  Over broken and rugged land.
40.00	Point for the 1/4 sec. cor. of secs. 34 and 35.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  T31N R22E 1/4 S34   S35 2000  from which  The marks X B0, chiseled on the S. face of a sandstone boulder, 13 X 4 X 11 ft. high, bear N. 2 1/4° E., 67 1/2 lks. dist.

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS															
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.														
80.00	Point for the cor. of secs. 26, 27, 34, and 35.														
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.														
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T31N</td><td>R22E</td></tr> <tr><td>S27</td><td> </td><td>S26</td></tr> <tr><td colspan="3" style="border-top: 1px solid black;"></td></tr> <tr><td>S34</td><td> </td><td>S35</td></tr> <tr><td colspan="3" style="text-align: center;">2000</td></tr> </table>	T31N	R22E	S27		S26				S34		S35	2000		
T31N	R22E														
S27		S26													
S34		S35													
2000															
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.														
	<p>Land, broken and rugged. Soil, rocky and rocky clay. Timber, piñon and juniper; undergrowth, rabbitbrush, sagebrush and native grasses.</p>														
40.00	From the cor. of secs. 25, 26, 35, and 36.														
	West, bet. secs. 26 and 35.														
	Over rolling and broken land.														
40.00	Point for the 1/4 sec. cor. of secs. 26 and 35.														
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.														
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T31N</td><td>R22E</td></tr> <tr><td colspan="2" style="text-align: center;">S26</td></tr> <tr><td colspan="2" style="text-align: center;">1/4 —</td></tr> <tr><td colspan="2" style="text-align: center;">S35</td></tr> <tr><td colspan="2" style="text-align: center;">2000</td></tr> </table>	T31N	R22E	S26		1/4 —		S35		2000					
T31N	R22E														
S26															
1/4 —															
S35															
2000															
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.														
80.00	The cor. of secs. 26, 27, 34, and 35.														

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, rabbitbrush, sagebrush, and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T31N R22E 1/4 S27   S26 2000</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
58.48	<p>Navajo Route 4, asphalt pavement, 26 ft. wide, bears E. and W.</p>
59.15	<p>A brass tablet, 3 1/2 ins. diam., set in a concrete cylinder, 6 ins. diam., set flush with the surface of the ground, bears East, 65 lks. dist., unmarked, and witnessed by an angle iron set nearby, with marks STA. PI 1034+15.19.</p>
62.10	<p>Power line, bears E. and W.</p>
80.00	<p>Point for the cor. of secs. 22, 23, 26, and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T31N R22E S22   S23 ----- S27   S26 2000</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, rabbitbrush, sagebrush greasewood and native grasses.</p> <hr/>
	<p>From the cor. of secs. 23, 24, 25, and 26.</p>
	<p>West, bet. secs. 23 and 26.</p>
	<p>Over broken land.</p>
25.43	<p>Navajo Route 4, asphalt pavement, 26 ft. wide, bears ENE and WSW.</p>
29.90	<p>Power line, bears ENE and WSW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R22E S23 1/4 — S26 2000</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
42.00	<p>Graded road, 16 ft. wide, bears SSE and NNW.</p>
80.00	<p>The cor. of secs. 22, 23, 26, and 27.</p>
	<p>Land, broken. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, rabbitbrush, sagebrush, greasewood and native grasses.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 22 and 23.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T31N R22E 1/4 S22   S23 2000</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
48.90	<p>High voltage transmission line, bears ENE and WSW.</p>
80.00	<p>Point for the cor. of secs. 14, 15, 22, and 23.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R22E S15   S14 ----- S22   S23 2000</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, rabbitbrush, sagebrush greasewood and native grasses.</p>
	<p>From the cor. of secs. 13, 14, 23, and 24.</p>
	<p>West, bet. secs. 14 and 23.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R22E S14 1/4 — S23 2000</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The cor. of secs. 14, 15, 22, and 23.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, rabbitbrush, sagebrush, greasewood and native grasses.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R22E 1/4 S15   S14 2000</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 10, 11, 14, and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R22E S10   S11 ----- S15   S14 2000</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, rabbitbrush, sagebrush greasewood and native grasses.</p> <hr/>
	<p>From the cor. of secs. 11, 12, 13, and 14.</p>
	<p>West, bet. secs. 11 and 14.</p>
	<p>Over broken land.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R22E S11 1/4 — S14 2000</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 10, 11, 14, and 15.</p> <p>Land, broken. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, rabbitbrush, sagebrush, greasewood and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 10 and 11.</p> <p>Over broken and rugged land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R22E 1/4 S10   S11 2000</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 2, 3, 10, and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R22E S 3   S 2 ----- S10   S11 2000</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, broken and rugged. Soil, rocky and rocky clay. Timber, piñon and juniper; undergrowth, rabbitbrush, sagebrush scrub oak and native grasses.</p>
	<p>From the true point for the cor. of secs. 1, 2, 11, and 12.</p> <p>West, bet. secs. 2 and 11.</p> <p>Over rugged land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R22E S 2 1/4 — S11 2000</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
51.60	E. rim of Toadindaaska Mesa, bears ENE and WSW.
63.80	W. rim of Toadindaaska Mesa, bears N. and S.
80.00	The cor. of secs. 2, 3, 10, and 11.
	<p>Land, rugged. Soil, rocky and rocky clay. Timber, piñon and juniper; undergrowth, rabbitbrush, scrub oak, sagebrush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over rugged land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T31N R22E 1/4 S 3   S 2 2000</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rugged. Soil, rocky and rocky clay. Timber, piñon and juniper; undergrowth, rabbitbrush, sagebrush, scrub oak and native grasses.</p>
	<p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R22E 1/4 S33   S34 2000</p>
41.80	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
41.80	<p>Trail road, bears SSE and NNW.</p>
58.70	<p>Graded road, 18 ft. wide, bears NE and SW.</p>
80.00	<p>Point for the cor. of secs. 27, 28, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS						
	<div style="text-align: center;"> <table border="1"> <tr><td>T31N R22E</td></tr> <tr><td>S28   S27</td></tr> <tr><td>S33   S34</td></tr> <tr><td>2000</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy, rocky and sandy clay. Timber, piñon and juniper; undergrowth, greasewood, rabbitbrush, sagebrush and native grasses.</p>	T31N R22E	S28   S27	S33   S34	2000	
T31N R22E						
S28   S27						
S33   S34						
2000						
	<p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>West, bet. secs. 27 and 34.</p> <p>Over rolling land.</p>					
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>					
	<div style="text-align: center;"> <table border="1"> <tr><td>T31N R22E</td></tr> <tr><td>S27</td></tr> <tr><td>1/4 —</td></tr> <tr><td>S34</td></tr> <tr><td>2000</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 45 lks. S. of the S. bank of a wash, 75 ft. wide, bears E. and W.</p>	T31N R22E	S27	1/4 —	S34	2000
T31N R22E						
S27						
1/4 —						
S34						
2000						
55.00	<p>Graded road, 15 ft. wide, bears N. and S.</p>					
80.00	<p>The cor. of secs. 27, 28, 33, and 34.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, greasewood, rabbitbrush, sagebrush, and native grasses.</p>					
	<p>N. 0°02' W., bet. secs. 27 and 28.</p>					

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 28.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T31N R22E
	1/4
	S28   S27
	2000
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
71.26	A third order U. S. Geological Survey benchmark, bears East, 1.08 chs. dist., monumented with a standard brass benchmark tablet, 3 1/2 ins. diam., cemented in sandstone bedrock, with top mkd. 9 DOR 1972 6490.
72.92	Navajo Route 4, asphalt pavement, 26 ft. wide, bears E. and W.
78.30	Power line, bears ENE and WSW.
80.00	Point for the cor. of secs. 21, 22, 27, and 28.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T31N R22E
	S21   S22
	S28   S27
	2000
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
	Cor. is located 80 lks. W. of a trail road into a residential area, bears N. and S.
	From this cor. point, the SE cor. of a wood framed house, 28 X 16 ft., bears N. 17°57' E., 2.34 chs. dist., long side bears NNW.
	Land, rolling.
	Soil, sandy and sandy clay.
	No timber; greasewood, rabbitbrush, sagebrush and native grasses.
	From the cor. of secs. 22, 23, 26, and 27.

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	West, bet. secs. 22 and 27.  Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 27.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T31N R22E                  S22              1/4 —                  S27              2000         </div> Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
70.63	The SW cor. of a stuccoed house, 50 x 16 ft., bears South, 2.43 dist., long side bears NE.
75.07	The SW cor. of a wood sided house, 33 x 24 ft., bears North, 2.80 dist., long side bears NNE.
76.80	Graded road, 15 ft. wide, bears NE and SW.
80.00	The cor. of secs. 21, 22, 27, and 28.  Land, rolling. Soil, sandy and sandy clay. No timber; greasewood, rabbitbrush, sagebrush, and native grasses.
	N. 0°02' W., bet. secs. 21 and 22.  Over rolling land.
18.20	High voltage transmission line, bears ENE and WSW.
34.80	Power line, bears SE and NW.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 22.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T31N R22E 1/4 S21   S22 2000</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
56.40	Trail road, bears E. and W.
66.45	Trail road, bears SSE and NNW.
76.85	Trail road, bears E. and W.
80.00	Point for the cor. of secs. 15, 16, 21, and 22.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R22E S16   S15 ----- S21   S22 2000</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, greasewood, rabbitbrush, and native grasses.</p> <hr/>
	<p>From the cor. of secs. 14, 15, 22, and 23.</p>
	<p>West, bet. secs. 15 and 22.</p>
	<p>Over rolling land.</p>
40.00	Point for the 1/4 sec. cor. of secs. 15 and 22.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R22E S15 1/4 — S22 2000</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 15, 16, 21, and 22.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, greasewood, rabbitbrush, sagebrush, and native grasses.</p>
40.00	<p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T31N R22E 1/4 S16   S15 2000</p> </div>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 9, 10, 15, and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T31N R22E S 9   S10 ----- S16   S15 2000</p> </div>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, greasewood, rabbitbrush, and native grasses.</p>
	<p>From the cor. of secs. 10, 11, 14, and 15.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	West, bet. secs. 10 and 15.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 15.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T31N R22E S10 1/4 — S15 2000</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
80.00	The cor. of secs. 9, 10, 15, and 16.
	Land, rolling.
	Soil, sandy and sandy clay.
	Timber, piñon and juniper; undergrowth, greasewood, rabbitbrush, and native grasses.
	N. 0°02' W., bet. secs. 9 and 10.
	Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T31N R22E 1/4 S 9   S10 2000</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
43.86	Barbed wire fence, 5 strands, bears NNE and SSW.
80.00	Point for the cor. of secs. 3, 4, 9, and 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<div style="text-align: center;">           T31N R22E            S 4   S 3  <hr style="width: 100%;"/>           S 9   S10            2000         </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy, rocky and rocky clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbitbrush, and native grasses.</p>
40.00	<p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>West, bet. secs. 3 and 10.</p> <p>Over rugged land.</p> <p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
80.00	<div style="text-align: center;">           T31N R22E            S 3            1/4 —            S10            2000         </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 3, 4, 9, and 10.</p> <p>Land, rugged. Soil, rocky and rocky clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbitbrush, and native grasses.</p>
40.00	<p>N. 0°02' W., bet. secs. 3 and 4.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R22E 1/4 S 4   S 3 2000</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rugged. Soil, rocky and rocky clay. Timber, piñon and juniper; undergrowth, rabbitbrush, sagebrush and native grasses.</p>
	<p>From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 32 and 33.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R22E 1/4 S32   S33 2000</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
44.85	<p>Trail road, bears ENE and WSW.</p>
54.99	<p>The 219 mile cor. on the E. bdy. of the 1882 Executive Order Boundary of the Hopi Indian Reservation, bears West, 33.02 chs. dist., monumented with an iron post, 2 1/2 ins. diam., set flush with the surface of the ground, in a barbed wire fence, 5 strands, bears N. and S., with brass cap mkd. 219 M EO 1882 NAVAJO 1964. Add the marks 2000 to the brass cap.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS											
60.30	Apache County Route C518, a graded road, 18 ft. wide, bears SE and NW.										
80.00	<p>Point for the cor. of secs. 28, 29, 32, and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T31N R22E</td></tr> <tr><td>S29</td><td>S28</td></tr> <tr><td colspan="2">— —</td></tr> <tr><td>S32</td><td>S33</td></tr> <tr><td colspan="2">2000</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy and sandy clay. No timber; greasewood, rabbitbrush, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>West, bet. secs. 28 and 33.</p> <p>Over rolling land.</p>	T31N R22E		S29	S28	— —		S32	S33	2000	
T31N R22E											
S29	S28										
— —											
S32	S33										
2000											
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T31N R22E</td></tr> <tr><td colspan="2">S28</td></tr> <tr><td colspan="2">1/4 —</td></tr> <tr><td colspan="2">S33</td></tr> <tr><td colspan="2">2000</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>	T31N R22E		S28		1/4 —		S33		2000	
T31N R22E											
S28											
1/4 —											
S33											
2000											
80.00	<p>The cor. of secs. 28, 29, 32, and 33.</p> <p>Land, rolling. Soil, sandy and sandy clay. No timber; greasewood, rabbitbrush, sagebrush, and native grasses.</p> <hr/>										

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>N. 0°03' W., bet. secs. 28 and 29.</p> <p>Over rolling land.</p>
15.00	<p>The 219 1/2 mile cor. on the E. bdy. of the 1882 Executive Order Boundary of the Hopi Indian Reservation, bears West, 32.99 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, in a barbed wire fence, 5 strands, bears N. and S., with brass cap mkd. 219 1/2 M EO 1882 NAVAJO 1964. Add the marks 2000 to the brass cap.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T31N R22E 1/4 S29   S28 2000</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
55.05	<p>The 220 mile cor. on the E. bdy. of the 1882 Executive Order Boundary of the Hopi Indian Reservation, bears West, 32.94 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, in a barbed wire fence, 5 strands, bears N. and S., with brass cap mkd. EO 1882 220 M NAVAJO 1964. Add the marks 2000 to the brass cap.</p>
59.80	<p>Apache County Route C518, a graded road, 20 ft. wide, bears NNE and SSW.</p>
67.40	<p>High voltage transmission line, bears ENE and WSW.</p>
80.00	<p>Point for the cor. of secs. 20, 21, 28, and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T31N R22E S20   S21 ----- S29   S28 2000</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located 1.42 chs. W. of Apache County Route C518, a graded road, 20 ft. wide, bears NNE and SSW.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, greasewood, rabbitbrush, sagebrush and native grasses.</p>
	<p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>West, bet. secs. 21 and 28.</p> <p>Over rolling and broken land.</p>
19.86	Navajo Route 4, asphalt pavement, 26 ft. wide, bears ESE and WNW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R22E S21 1/4 — S28 2000</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
47.30	High voltage transmission line, bears ENE and WSW.
80.00	<p>The cor. of secs. 20, 21, 28, and 29.</p> <p>Land, rolling and broken. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, rabbitbrush, sagebrush, and native grasses.</p>
	<p>N. 0°03' W., bet. secs. 20 and 21.</p> <p>Over rolling land.</p>
6.05	Trail road, bears ESE and WNW.

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
15.08	The 220 1/2 mile cor. on the E. bdy. of the 1882 Executive Order Boundary of the Hopi Indian Reservation, bears West, 32.90 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, in a barbed wire fence, 5 strands, bears N. and S., with brass cap mkd. 220 1/2 M EO 1882 NAVAJO 1964. Add the marks 2000 to the brass cap.
17.58	The witness point on the E. bdy. of the 1882 Executive Order Boundary of the Hopi Indian Reservation, established at intersection with the S. side of main highway, bears West, 32.90 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, in a barbed wire fence, 5 strands, bears N. and S., with brass cap mkd. 220 1/2 M +2.50 EO 1882 NAVAJO 1964. Add the marks 2000 to the brass cap.
19.95	S. right-of-way fence of Navajo Route 4, barbed wire, 5 strands, parallels highway.
20.18	The witness point on the E. Bdy. of the 1882 Executive Order Boundary of the Hopi Indian Reservation, established at intersection with the N. side of highway, bears West, 32.90 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, in a barbed wire fence, 5 strands, bears N. and S., with brass cap mkd. different than record, 220 1/2 M +5.10 EO 1882 NAVAJO 1964. Add the marks 2000 to the brass cap.
20.71	Navajo Route 4, asphalt pavement, 26 ft. wide, bears E. and W.
21.46	N. right-of-way fence of Navajo Route 4, barbed wire, 5 strands, parallels highway.
27.90	Power line, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 21.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T31N R22E            1/4            S20   S21            2000         </div> Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS											
55.10	<p>The 221 mile cor. on the E. bdy. of the 1882 Executive Order Boundary of the Hopi Indian Reservation, bears West, 32.86 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, in a barbed wire fence, 5 strands, bears N. and S., with brass cap mkd. 221 M EO 1882 NAVAJO 1964. Add the marks 2000 to the brass cap.</p>										
80.00	<p>Point for the cor. of secs. 16, 17, 20, and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 10px;">T31N</td> <td style="padding: 0 10px;">R22E</td> </tr> <tr> <td style="padding: 0 10px;">S17</td> <td style="padding: 0 10px;">S16</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 10px;">S20</td> <td style="border-top: 1px solid black; padding: 0 10px;">S21</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">2000</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, greasewood, rabbitbrush, sagebrush and native grasses.</p>	T31N	R22E	S17	S16	S20	S21	2000			
T31N	R22E										
S17	S16										
S20	S21										
2000											
23.00	<p>From the cor. of secs. 15, 16, 21, and 22.</p> <p>West, bet. secs. 16 and 21.</p> <p>Over rolling land.</p> <p>Power line, bears NNE and SSW.</p>										
30.40	<p>Graded road, 20 ft. wide, bears SSE and NNW.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 10px;">T31N</td> <td style="padding: 0 10px;">R22E</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">S16</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">1/4 —</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">S21</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">2000</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>	T31N	R22E	S16		1/4 —		S21		2000	
T31N	R22E										
S16											
1/4 —											
S21											
2000											

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
66.12	Navajo Route 29, asphalt pavement, 26 ft. wide, bears N. and S.
80.00	The cor. of secs. 16, 17, 20, and 21.  Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, greasewood, rabbitbrush, sagebrush, and native grasses.
	N. 0°03' W., bet. secs. 16 and 17.  Over rolling land.
15.32	The 221 1/2 mile cor. on the E. bdy. of the 1882 Executive Order Boundary of the Hopi Indian Reservation, bears West, 32.84 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, in a barbed wire fence, 5 strands, bears N. and S., with brass cap mkd. EO 1882 221 1/2 M NAVAJO 1964. Add the marks 2000 to the brass cap.
32.80	Graded road, 20 ft. wide, bears SE and NW.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 17.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T31N R22E                  1/4            S17   S16                  2000         </div>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
80.00	Point for the cor. of secs. 8, 9, 16, and 17.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T31N R22E            S 8   S 9            ————            S17   S16                  2000         </div>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Cor. is located 28 lks. N. of a barbed wire fence, 5 strands, bears E. and W.
	Land, rolling. Soil, sandy and sandy clay. No timber; greasewood, rabbitbrush, sagebrush and native grasses.
	From the cor. of secs. 9, 10, 15, and 16.
	West, bet. secs. 9 and 16.
	Over rolling land.
29.48	Barbed wire fence, 5 strands, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T31N R22E S 9 1/4 — S16 2000</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
59.00	Power line, bears SSE and NNW.
69.62	E. right-of-way fence of Navajo Route 29, barbed wire, 5 strands, parallels highway.
70.77	Navajo Route 29, asphalt pavement, 26 ft. wide, bears N. and S.
71.91	W. right-of-way fence of Navajo Route 29, barbed wire, 5 strands, parallels highway.
80.00	The cor. of secs. 8, 9, 16, and 17.
	Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, greasewood, rabbitbrush, sagebrush, and native grasses.
	N. 0°03' W., bet. secs. 8 and 9.

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling land.
15.19	The 222 1/2 mile cor. on the E. bdy. of the 1882 Executive Order Boundary of the Hopi Indian Reservation, bears West, 32.82 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, in a barbed wire fence, 5 strands, bears N. and S., with brass cap mkd. 222 1/2 M EO 1882 NAVAJO 1964. Add the marks 2000 to the brass cap.
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R22E 1/4 S 8   S 9 2000</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
55.22	The 223 mile cor. on the E. bdy. of the 1882 Executive Order Boundary of the Hopi Indian Reservation, bears West, 32.79 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, in a barbed wire fence, 5 strands, bears N. and S., with brass cap mkd. 223 M EO 1882 Navajo 1964. Add the marks 2000 to the brass cap.
69.38	Barbed wire fence, 5 strands, bears NNE and SSW.
80.00	<p>Point for the cor. of secs. 4, 5, 8, and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R22E S 5   S 4 ----- S 8   S 9 2000</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
	<p>Land, rolling.</p> <p>Soil, sandy and sandy clay.</p> <p>No timber; greasewood, rabbitbrush and native grasses.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the cor. of secs. 3, 4, 9, and 10.
	West, bet. secs. 4 and 9.
	Over rolling and broken land.
12.98	Barbed wire fence, 5 strands, bears ESE and WNW.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T31N R22E S 4 1/4 — S 9 2000
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
41.41	A brass tablet, 3 ins. diam., set in a concrete cylinder, 6 ins. diam., firmly set, projecting 8 ins. above ground, bears North, 1.12 chs. dist., mkd. BIA ROADS 19, and witnessed by an angle iron set nearby.
41.91	E. right-of-way fence of Navajo Route 29, barbed wire, 5 strands, parallels highway.
43.18	Navajo Route 29, asphalt pavement, 29 ft. wide, bears NNE and SSW.
43.47	A brass tablet, 3 ins. diam., set in a concrete cylinder, 6 ins. diam., firmly set, projecting 6 ins. above ground, bears North, 2.08 chs. dist., mkd. BIA ROADS 19.
44.45	W. right-of-way fence of Navajo Route 29, barbed wire, 5 strands, parallels highway.
45.20	Power line, bears NNE and SSW.
76.06	Barbed wire fence, 5 strands, bears NNE and SSW.
80.00	The cor. of secs. 4, 5, 8, and 9.

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sandy, rocky and sandy clay. Timber, piñon and juniper; undergrowth, greasewood, rabbitbrush, sagebrush, and native grasses.</p>
	<p>N. 0°03' W., bet. secs. 4 and 5.</p>
	<p>Over rolling land.</p>
15.28	<p>The 223 1/2 mile cor. on the E. bdy. of the 1882 Executive Order Boundary of the Hopi Indian Reservation, bears West, 32.79 chs. dist., monumented with an iron post, 2 1/2 ins. diam., set flush with the surface of the ground, in a barbed wire fence, 5 strands, bears N. and S., with brass cap mkd. 223 1/2 M EO 1882 NAVAJO 1964. Add the marks 2000 to the brass cap.</p>
18.82	<p>Barbed wire fence, 5 strands, bears ESE and WNW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R22E 1/4 S 5   S 4 2000</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
44.10	<p>S. bank of Polacca Wash, 20 ft. high, bears NNE and SSW.</p>
50.39	<p>N. bank of Polacca Wash, 20 ft. high, bears NE and SW.</p>
55.29	<p>The 224 mile cor. on the E. bdy. of the 1882 Executive Order Boundary of the Hopi Indian Reservation, bears West, 32.77 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, in a barbed wire fence, 5 strands, bears N. and S., with brass cap mkd. 224 M EO 1882 NAVAJO 1964. Add the marks 2000 to the brass cap.</p>
80.00	<p>The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., hereinbefore described.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy and sandy clay. No timber; rabbitbrush, greasewood and native grasses.</p> <hr/> <p>From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over rolling land.</p>
6.00	Trail road, bears NE and SW.
7.40	Graded road, 20 ft. wide, bears SE and NW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R22E 1/4 S31   S32 2000</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 70 lks. S. of a trail road, bears ENE and WSW.</p>
60.50	S. bank of a wash, 15 ft. high, bears E. and W.
62.20	N. bank of the same wash, 15 ft. high, bears SE. and NW.
77.65	Trail road, bears ENE and WSW.
80.00	<p>Point for the cor. of secs. 29, 30, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R22E S30   S29 ----- S31   S32 2000</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy and sandy clay. No timber; greasewood, rabbitbrush and native grasses.</p> <hr/> <p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>West, bet. secs. 29 and 32.</p> <p>Over rolling land.</p>
6.50	Apache County Route C518, a graded road, 15 ft. wide, bears N. and S.
11.20	Trail road, bears NE and SW.
33.00	Barbed wire fence, 5 strands, bears N. and S.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 32.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R22E S29 1/4 — S32 2000</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
56.40	Trail road, bears NNE and SSW.
80.00	The cor. of secs. 29, 30, 31, and 32.
	<p>Land, rolling. Soil, sandy and sandy clay. No timber; greasewood, rabbitbrush and native grasses.</p> <hr/> <p>West, bet. secs. 30 and 31.</p> <p>Over rolling land.</p>
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T31N R22E S30 1/4 $\frac{\quad}{\quad}$ S31 2000
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
57.35	Navajo Route 67, a graded road, 25 ft. wide, bears NE and SW.
78.85	The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., hereinbefore described.
	Land, rolling. Soil, sandy and sandy clay. No timber; greasewood, rabbitbrush and native grasses.
	From the cor. of secs. 29, 30, 31, and 32.
	N. 0°03' W., bet. secs. 29 and 30.
	Over rolling land.
8.95	Trail road, bears SE and NW.
30.10	Trail road, bears ENE and WSW.
36.60	High voltage transmission line, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T31N R22E 1/4 S30   S29 2000
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
75.70	Wash, 20 ft. wide, 3 ft. deep, drains SW.
80.00	Point for the cor. of secs. 19, 20, 29, and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<div style="text-align: center;"> <table border="1"> <tr><td>T31N</td><td>R22E</td></tr> <tr><td>S19</td><td>S20</td></tr> <tr><td>S30</td><td>S29</td></tr> <tr><td colspan="2">2000</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy and sandy clay. No timber; greasewood, rabbitbrush and native grasses.</p>	T31N	R22E	S19	S20	S30	S29	2000			
T31N	R22E										
S19	S20										
S30	S29										
2000											
<p>32.92</p> <p>35.10</p> <p>40.00</p>	<p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>West, bet. secs. 20 and 29.</p> <p>Over rolling land.</p> <p>Barbed wire fence, 5 strands, bears N. and S.</p> <p>Power line, bears N. and S.</p> <p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										
<p>80.00</p>	<div style="text-align: center;"> <table border="1"> <tr><td>T31N</td><td>R22E</td></tr> <tr><td colspan="2">S20</td></tr> <tr><td colspan="2">1/4 —</td></tr> <tr><td colspan="2">S29</td></tr> <tr><td colspan="2">2000</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 19, 20, 29, and 30.</p> <p>Land, rolling. Soil, sandy and sandy clay. No timber; greasewood, rabbitbrush and native grasses.</p>	T31N	R22E	S20		1/4 —		S29		2000	
T31N	R22E										
S20											
1/4 —											
S29											
2000											
<p>14.55</p>	<p>West, bet. secs. 19 and 30.</p> <p>Over rolling and broken land.</p> <p>Navajo Route 67, a graded road, 25 ft. wide, bears NNE and SSW.</p>										

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R22E S19 1/4 — S30 2000</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
63.30	E. bank of Polacca Wash, 10 ft. high, bears N. and S.
63.75	W. bank of Polacca Wash, 10 ft. high, bears N. and S.
78.76	<p>The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling and broken. Soil, sandy, rocky and sandy clay. Timber, piñon and juniper; undergrowth, greasewood, rabbitbrush, sagebrush and native grasses.</p>
	<p>From the cor. of secs. 19, 20, 29, and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p> <p>Over rolling land.</p>
13.87	S. right-of-way fence of Navajo Route 4, barbed wire, 5 strands, parallels highway.
14.20	A brass tablet, a 3 1/2 ins. diam., set in concrete cylinder, 6 ins. diam., firmly set, projecting 8 ins. above ground, bears West, 2.39 chs. dist., unmarked, and witnessed by an angle iron, set nearby, with marks STA. PT EQ 1200+63.00 BK/1201+63.00 AHD.
15.46	Navajo Route 4, asphalt pavement, 26 ft. wide, bears E. and W.
15.68	A brass tablet, 3 1/2 ins. diam., set in a concrete cylinder, 6 ins. diam., set flush with the surface of the ground, bears West, 2.70 chs. dist., unmarked, and witnessed by an angle iron, set nearby, with marks STA. PT EQ 1200+63.00 BK/1201+63.00 AHD.
16.92	N. right-of-way fence of Navajo Route 4, barbed wire, 5 strands, parallels highway.

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
17.70	Power line, bears E. and W.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 20.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T31N R22E            1/4            S19   S20            2000         </div> Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
80.00	Point for the cor. of secs. 17, 18, 19, and 20.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T31N R22E            S18   S17            ---            S19   S20            2000         </div> Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.  Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, greasewood, rabbitbrush and native grasses.
	From the cor. of secs. 16, 17, 20, and 21.  West, bet. secs. 17 and 20.  Over broken land.
32.86	Barbed wire fence, 5 strands, bears N. and S.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 20.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T31N R22E S17 1/4 — S20 2000</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 17, 18, 19, and 20.</p> <p>Land, broken. Soil, sandy, rocky and sandy clay. Timber, piñon and juniper; undergrowth, greasewood, rabbitbrush and native grasses.</p>
	<p>West, bet. secs. 18 and 19.</p>
	<p>Over rolling land.</p>
20.90	<p>Polacca Wash, 30 ft. wide, 20 ft. deep, drains S.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 18 and 19.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R22E S18 1/4 — S19 2000</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
48.60	<p>Wash, 20 ft. wide, 15 ft. deep, drains SSE.</p>
72.40	<p>Power line, bears NNE and SSW.</p>
73.70	<p>Navajo Route 29, a graded road, 20 ft. wide, bears NNE and SSW.</p>
78.68	<p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., hereinbefore described.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, greasewood, rabbitbrush, and native grasses.</p>
	<p>From the cor. of secs. 17, 18, 19, and 20. N. 0°03' W., bet. secs. 17 and 18. Over rolling land.</p>
16.50	Trail road, bears NE and SW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R22E 1/4 S18   S17 2000</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
40.70	Power line, bears SE and NW.
44.90	S. bank of Polacca Wash, 20 ft. high, bears NE and SW.
48.50	N. bank of Polacca Wash, 20 ft. high, bears NE and SW.
80.00	<p>Point for the cor. of secs. 7, 8, 17, and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R22E S 7   S 8 ----- S18   S17 2000</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, greasewood, rabbitbrush and native grasses.</p> <hr/> <p>From the cor. of secs. 8, 9, 16, and 17. West, bet. secs. 8 and 17. Over rolling land.</p>
32.85	Barbed wire fence, 5 strands, bears N. and S.
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R22E S 8 1/4 — S17 2000</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
54.30	E. bank of Polacca Wash, 20 ft. high, bears SSE and NNW.
55.90	W. bank of Polacca Wash, 20 ft. high, bears SSE and NNW.
80.00	<p>The cor. of secs. 7, 8, 17, and 18.</p> <p>Land, rolling. Soil, sandy and sandy clay. No timber; greasewood, rabbitbrush and native grasses.</p> <hr/> <p>West, bet. secs. 7 and 18. Over rolling land.</p>
30.00	Navajo Route 29, a graded road, 20 ft. wide, bears NE and SW, and a power line, bears NNE and SSW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
78.59	<p style="text-align: center;">T31N R22E S 7 1/4 — S18 2000</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, greasewood, rabbitbrush, and native grasses.</p>
40.00	<p>From the cor. of secs. 7, 8, 17, and 18.</p> <p>N. 0°03' W., bet. secs. 7 and 8.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
50.70	<p style="text-align: center;">T31N R22E 1/4 S 7   S 8 2000</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Navajo Route 29, a graded road, 20 ft. wide, bears NNE and SSW.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 7, and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R22E S 6   S 5 —+— S 7   S 8 2000</p>

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 65 lks. S. of a trail road, bears ENE and WNW, and 90 lks. E. of a trail road, bears NNE and SSW.</p> <p>From this cor. point, the SE cor. of a wood framed house, 46 X 28 ft., bears N. 63°18' W., 3.58 chs. dist., long side bears W.</p> <p>From this same cor. point, the ESE cor. of a hexagonal hogan, 8 ft. sides, bears N. 43°00' W., 4.04 chs. dist., sides bear NNE and SW.</p> <p>Land, rolling. Soil, sandy and sandy clay. No timber; greasewood, rabbitbrush and native grasses.</p>
	<p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>West, bet. secs. 5 and 8.</p> <p>Over rolling land.</p>
11.20	Polacca Wash, 40 ft. wide, 20 ft. deep, drains SSE.
32.79	Barbed wire fence, 5 strands, bears N. and S.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 8.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R22E S 5 1/4 — S 8 2000</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
65.90	Navajo Route 29, a graded road, 20 ft. wide, bears NNE and SSW.
80.00	The cor. of secs. 5, 6, 7, and 8.

Survey of the Subdivisional Lines,  
T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy and sandy clay. No timber; greasewood, rabbitbrush and native grasses.</p>
	<p>West, bet. secs. 6 and 7.</p>
	<p>Over broken land.</p>
5.60	<p>Power line, bears NNE and SSW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R22E S 6 1/4 — S 7 2000</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
78.50	<p>The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., hereinbefore described.</p>
	<p>Land, broken. Soil, sandy, rocky and sandy clay. Timber, piñon and juniper; undergrowth, greasewood, rabbitbrush, sagebrush and native grasses.</p>
	<p>From the cor. of secs. 5, 6, 7, and 8.</p>
	<p>N. 0°03' W., bet. secs. 5 and 6.</p>
	<p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R22E 1/4 S 6   S 5 2000</p>



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## FIELD ASSISTANTS

NAMES	CAPACITY
William F. Olver	Cadastral Surveyor
Daniel Bryan	Engineering Technician
Wilfred Chee	Engineering Technician
Edward Clarke	Engineering Technician
Reuben Mason	Engineering Technician
Barney Woodie	Engineering Technician

CERTIFICATE OF SURVEY

I, Jones Curtiss, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 14th day of August, 2000, I have surveyed the south, east, west, and north boundaries, and the subdivisional lines, Township 31 North, Range 22 East, of the Gila and Salt River Meridian, in the state of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

December 24, 2002  
(Date)

Jones Curtiss  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Arizona State Office  
Phoenix, Arizona

The foregoing field notes of the survey of the south, east, west, and north boundaries, and the subdivisional lines, Township 31 North, Range 22 East, Gila and Salt River Meridian, Arizona, executed by Jones Curtiss, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

January 27, 2003  
(Date)

Lenny A. Rawnsley  
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 31 N., R. 22 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~\_\_\_\_\_  
(Date)~~

~~\_\_\_\_\_  
(Chief Cadastral Surveyor of Arizona)~~