

ORIGINAL

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE  
DEPENDENT RESURVEY  
OF  
A PORTION OF THE SUBDIVISIONAL LINES  
AND  
THE SUBDIVISION OF SECTION 17,  
TOWNSHIP 10 SOUTH, RANGE 9 EAST,  
OF THE GILA AND SALT RIVER MERIDIAN,  
IN THE STATE OF ARIZONA.

**EXECUTED BY**

**Gordon R. Bubel, Cadastral Surveyor**

Under Special Instructions dated March 19, 2004, approved March 19, 2004, which provided for the surveys included under Group No. 931, and assignment instructions dated March 19, 2004.

**Survey commenced March 22, 2004**

**Survey completed March 31, 2004**

**INDEX DIAGRAM**

TOWNSHIP 10 SOUTH

RANGE 09 EAST

|           |                  |             |           |           |           |
|-----------|------------------|-------------|-----------|-----------|-----------|
| <b>6</b>  | <b>5</b>         | <b>4</b>    | <b>3</b>  | <b>2</b>  | <b>1</b>  |
| <b>7</b>  | <b>8</b><br>8    | <b>9</b>    | <b>10</b> | <b>11</b> | <b>12</b> |
| <b>18</b> | 7 <b>17</b><br>5 | 4 <b>16</b> | <b>15</b> | <b>14</b> | <b>13</b> |
| <b>19</b> | <b>20</b>        | 3 <b>21</b> | <b>22</b> | <b>23</b> | <b>24</b> |
| <b>30</b> | <b>29</b>        | <b>28</b>   | <b>27</b> | <b>26</b> | <b>25</b> |
| <b>31</b> | <b>32</b>        | <b>33</b>   | <b>34</b> | <b>35</b> | <b>36</b> |

Subdivision of Section 17 ..... Pages 8-12

Informative Traverses in the SW 1/4 SE 1/4 SEC. 17 .. Pages 12-13

**T. 10 S., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS

The following field notes describe the dependent resurvey of a portion of the subdivisional lines and the subdivision of section 17, Township 10 South, Range 9 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

R.C. Powers surveyed the north boundary in 1883. Edgar C. Dietrich surveyed the west boundary, resurveyed the north boundary and subdivided the township in 1905. In 1913, Jesse B. Wright and William H. Elliot resurveyed the west boundary.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated March 19, 2004, for Group No. 931, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from first order National Geodetic Survey triangulation station NN-83, as published by the National Geodetic Survey, NAD 83 (1992). The geographic position of the corner of sections 16, 17, 20 and 21, is as follows:

Latitude: 32°32'42.06" N.                      Longitude: 111°25'55.69" W.

The mean magnetic declination is 11 1/2° E.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 10 S., R. 9 E., Gila and Salt River Meridian, Arizona**

---

Restoring the survey executed by  
Edgar C. Dietrich, in 1905

---

Beginning at the cor. of secs. 20, 21, 28 and 29, monumented with a rebar, 1/2 in. diam., firmly set, projecting 1 in. above ground, with aluminum cap, 1 1/2 ins. diam., stamped S/S RLS 7599, with a broken malapais stone, mkd. with 2 grooves on two faces, laying loose alongside. This is accepted as a careful and faithful reestablishment of the position of the original cor.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 10 S., R. 9 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
|        | <p>Not remonumented.</p> <p>from which the remaining original bearing trees</p> <p>A stumphole of a downed palo verde, 18 ins. diam., bears N. 40 1/2° E., 2.27 chs. dist., no marks remaining.</p> <p>A dead palo verde, 16 ins. diam., bears S. 20 3/4° E., 2.29 chs. dist., no marks remaining. (Record: S. 19 3/4° E.)</p> <p>N. 0°29' E., bet. secs. 20 and 21.</p>  |
| 40.24  | <p>The 1/4 sec. cor of secs. 20 and 21, monumented with a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, with aluminum cap, 1 1/2 ins. diam., stamped S/S RLS 7599, with a broken malapais stone, mkd 1/4 on a face, laying loose alongside. This is accepted as the best available evidence of the original cor. position.</p> <p>Not remonumented.</p> <hr/> <p>N. 0°18' E., beginning new measurement.</p>  |
| 40.24  | <p>The cor. of secs. 16, 17, 20 and 21, monumented with a rebar, 1/2 in. diam., firmly set projecting 2 ins. above ground, unknown origin. This is accepted as the best available evidence of the original cor. position.</p> <p>Cor. is located 20 lks. S. of a fence cor. with woven wire fences bearing N. and E., and 25 lks. N. of intersection of bladed roads, bearing E., S. and W.</p> <p>Not remonumented.</p> <p>From this cor., National Geodetic Survey, first order triangulation station "NN 83", with published latitude of 32°30'03.79" N. and longitude of 111°22'50.90" W. NAD 83 (1992), bears S. 44°42' E., (forward bearing), 340.92 chs. dist., monumented with a aluminum disk, 3 1/4 ins. diam., set in concrete, projecting 1 in. above ground, with top marked PIMA COUNTY GPS NN-83 1991 SURVEY POINT DEPT. OF TRANSPORTATION FLOOD CONTROL DISTRICT and a triangle.</p> <hr/> <p>N. 0°07' W., bet. secs. 16 and 17.</p> <p>Over nearly level, eroded land, scant vegetation.</p> |
| 19.965 | <p>Point for the S. 1/16 sec. cor. of secs. 16 and 17.</p> <p>Not monumented.</p>   |

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 10 S., R. 9 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
| 39.93  | <p>Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Not monumented.</p>  |
| 79.86  | <p>Point for the cor. of secs. 8, 9, 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Not monumented.</p> <p>From this cor. point, the closing cor. of secs. 4 and 5, on the N. bdy. of the Tp., bears N. 0°03' W., 160.69 chs. dist., monumented with a rebar, 1/2 in. diam., firmly set, 6 ins. below the surface. Reestablished by James R. Cristea, Arizona R.L.S. No. 15089, in 1989, as per the result of survey, on file and recorded in Pinal County Recorders Office. This is accepted as a careful and faithful reestablishment of the position of the original cor.</p> <p>Cor. is located under a 5 strand power line, bears E. and W., and 35 lks. S. of the center of Baumgarten road, improved bladed, 20 ft. wide, bears E. and W.</p> <p>Not remonumented.</p> <p>This control line was fully retraced and a careful search was made for evidence of intervening cors., none of which were recovered.</p> <p>From this same cor. point, the 1/4 sec. cor. of secs. 10 and 15, bears S. 89°59' E., 119.98 chs. dist., monumented with a malapais stone, 17 x 10 x 6 ins., set 2 ins. below the surface, mkd. 1/4 on the N. face.</p> <p>Cor. is located under the most northerly set of 3 strand power lines, bearing E. and W.</p> <p>Not remonumented.</p> <p>This control line was fully retraced and a careful search was made for evidence of intervening cors., none of which were recovered.</p> |
| 18.42  | <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>S. 89°50' W., bet. secs. 17 and 20.</p> <p>Over nearly level land, between barbed wire fence and power line.</p> <p>Intersection of bladed roads, bearing SE, W. and NW.</p>   |

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 10 S., R. 9 E., Gila and Salt River Meridian, Arizona**

| CHAINS |   |
|--------|---|
| 20.06  | <p>Point for the E. 1/16 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 10 S R 9 E<br/>S 17<br/>E 1/16 ———<br/>S 20</p> <p align="center">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 20 lks. N. of bladed road, 12 ft. wide, bears E. and W.</p>   |
| 40.12  | <p>Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 40 ins. in the ground, with brass cap mkd.</p> <p align="center">T 10 S R 9 E<br/>S 17<br/>1/4 ———<br/>S 20</p> <p align="center">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>from which</p> <p>    An aluminum drive rod, 42 ins. long, 3/4 in. diam., set 36 ins. in the ground for a reference monument, bears S. 47°04' E., 38.5 ft. dist., with aluminum cap mkd. RM T10S R9E 38.5 FT TO COR S20 2004 and an arrow pointing to the cor.</p> <p>    An aluminum drive rod, 42 ins. long, 3/4 in. diam., set 36 ins. in the ground for a reference monument, bears S. 49°41' W., 38.6 ft. dist., with aluminum cap mkd. RM T10S R9E 38.6 FT TO COR S20 2004 and an arrow pointing to the cor.</p> <p>Cor. is located beneath the surface of a bladed road, 12 ft. wide, bears E. and W., 3 lks. S. of the N. edge.</p> |

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 10 S., R. 9 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
| 80.24  | <p>Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Not monumented.</p> <p>From this cor. point, the 1/4 sec. cor. of secs. 19 and 20, bears S. 0°39' W., 40.00 chs. dist., monumented with a 3/4 in. diam., anchor bolt, projecting 9 ins. above ground, set in a 6 x 6 x 6 ins. concrete pillar, unknown origin, with a 12 x 9 x 6 ins. malapais stone, mkd. 1/4 on a face, laying loose nearby. This is accepted as the best available evidence of the original cor. position.</p> <p>Not remonumented.</p> <p>From this same cor. point, the point for the 1/4 sec. cor. of secs. 18 and 19, determined from the lone remaining bearing tree, bears S. 89°47' W., 40.12 chs. dist.</p> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 13 ins. diam., bears S. 38° E., 92 lks. dist., with a rotted blaze.</p> <hr/> <p>N. 0°01' W., bet. secs. 17 and 18.</p> <p>Over nearly level land, through creosote, mesquite and palo verde.</p> |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Not monumented.</p>  |
| 80.00  | <p>Point for the cor. of secs. 7, 8, 17 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Not monumented.</p> <p>From this cor. point, the point for the closing cor. of secs. 5 and 6, on the N. bdy. of the Tp., determined by proportionate measurement, bears N. 0°09' W., 159.59 chs. dist.</p> <p>Not monumented.</p> <p>from which</p> <p style="padding-left: 40px;">The cor. of secs. 31 and 32 only, T. 9 S., R. 9 E., bears S. 86°50' E., 5.04 chs. dist., monumented with an iron pipe, 1 1/2 ins. diam., set 4 ins. below the surface, origin unknown. This is accepted as the best available evidence of the original cor. position.</p>  |

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 10 S., R. 9 E., Gila and Salt River Meridian, Arizona**

| CHAINS |  |
|--------|--|
|        | <p>The cor. of secs. 31 and 36 only, T. 9 S., Rs. 8 and 9 E., bears N. 86°45' W., 75.53 chs. dist., monumented with a galvanized iron pipe, 1 in. diam., inside a decayed iron pipe, 2 1/2 ins. diam., with a brass disk, 3 ins. diam., incorrectly marked T9S R8E R9E S6 S31 S1 S6 RLS 6451, set 1 in. below the surface, by Dennis H. Brady, Arizona R.L.S. No. 6451. This is accepted as the best available evidence of the original cor. position.</p> |
|        | <p>This control line was fully retraced and a careful search was made for evidence of intervening cors., none of which were recovered.</p>   |
|        | <p>From this same cor. point, the cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., bears S. 89°58' W., 78.98 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 1 in. above ground, with a malapais stone 12 x 8 x 7 ins., with 2 grooves on a face, laying loose nearby. This is accepted as the best available evidence of the original cor. position.</p>  |
|        | <p>This control line was fully retraced and a careful search was made for evidence of intervening cors., none of which were recovered.</p>   |
|        | <hr/> <p>From the point for the cor. of secs. 8, 9, 16 and 17.<br/>S. 89°57' W., bet. secs. 8 and 17.</p>  |
|        | <p>Over nearly level land, across numerous eroded gulches.</p>   |
| 40.04  | <p>Point for the 1/4 sec. cor. of sec. 8 and 17, at proportionate dist.; there is no remaining evidence of the orig. cor.<br/><br/>Not monumented.</p>   |
| 80.08  | <p>The point for the cor. of secs. 7, 18, 17 and 18.</p>   |
|        | <hr/> <p align="center"><b>Subdivision of Section 17,<br/>T. 10 S., R. 9 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>   |
|        | <p>From the 1/4 sec. cor. of secs. 17 and 20.<br/>N. 0°04' W., on the N. and S. center line of sec. 17.</p>  |
|        | <p>Over bulldozed and bladed area.</p>   |
| 15.41  | <p>Point selected for a witness point.</p>   |

Subdivision of Section 17,  
T. 10 S., R. 9 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
|        | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP<br/>T 10 S R 9 E<br/>C<br/>  S 17<br/>C</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>thence; leave bladed and bulldozed area.</p>   |
| 16.40  | Center of improved bladed road, 15 ft. wide, bears SE and NW.  |
| 16.75  | 5 strand barbed wire fence, parallels road.  |
| 18.65  | Top of earthen berm, 5 ft. wide at top, bears E. and W.  |
| 19.65  | Top of earthen berm, 5 ft. wide at top, bears E. and W.  |
| 19.985 | Point for the center S. 1/16 sec. cor. of sec. 17.   |
|        | <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 10 S R 9 E<br/>C<br/>S 1/16   S 17<br/>C</p> <p style="text-align: center;">2004</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 21 ins. in the ground, for a reference monument, bears N. 35°45' E., 40.9 ft. dist., with brass cap mkd. RM T10S R9E 40.9 FT TO COR S17 2004, and an arrow pointing to the cor. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, for a reference monument, bears S. 45°05' E., 34.9 ft. dist., with brass cap mkd. RM T10S R9E 34.9 FT TO COR S17 2004, and an arrow pointing to the cor. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |

**Subdivision of Section 17,  
T. 10 S., R. 9 E., Gila and Salt River Meridian, Arizona**

| CHAINS |  |
|--------|--|
|        | Cor. is located at bottom of gully, 10 ft. deep, bears E. and W.   |
| 22.10  | Southerly edge of landing strip, bears S. 60° E. and N. 60° W. thence; across landing strip.   |
| 24.60  | Northerly edge of landing strip, bears S. 60° E. and N. 60° W. thence; across native desert.   |
| 29.45  | Overhead power line, 3 wire, bears S. 60° E. and N. 60° W.   |
| 39.97  | Point for the center 1/4 sec. of sec. 17, at intersection with the E. and W. center line of sec. 17.<br><br>Not monumented.  |
| 79.94  | The point for the 1/4 sec. cor. of secs. 8 and 17.<br><hr/><br>From the 1/4 sec. cor. of secs. 16 and 17.<br><br>S. 89°53' W., on the E. and W. center line of sec. 17.<br><br>Over nearly level land, through creosote and mesquite.  |
| 20.04  | Point for the center E. 1/16 sec. cor. of sec. 17.<br><br>Not monumented.  |
| 40.08  | The point for the center 1/4 sec. cor. of sec. 17.   |
| 71.10  | 5 strand barbed wire fence, bears SE and NW.   |
| 71.65  | Center of bladed road, 15 ft. wide, bears SE and NW.   |
| 80.16  | The point for the 1/4 sec. cor. of secs. 17 and 18.<br><hr/><br>SE 1/4<br><hr/><br>From the E. 1/16 sec. cor. of secs. 17 and 20.<br><br>N. 0°06' W., on the N. and S. center line of the SE 1/4 of sec. 17.<br><br>Over nearly level land, through greasewood, mesquite and palo verde. |
| 1.00   | Center of bladed road, 15 ft. wide, bears SE and NW.   |

Subdivision of Section 17,  
T. 10 S., R. 9 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
| 1.72   | 5 strand barbed wire fence, bears SE and NW.   |
| 19.975 | <p>Point for the SE 1/16 sec. cor. of sec. 17, at intersection with the E. and W. center line of the SE 1/4 of sec. 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 10 S R 9 E</p> <p style="text-align: center;">SE 1/16 S 17</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>   |
| 39.95  | <p>The point for the center E. 1/16 sec. cor. of sec. 17.</p> <hr/> <p>From the point for the S. 1/16 sec. cor. of secs. 16 and 17.</p> <p>S. 89°52' W., on the E. and W. center line of the SE 1/4 of sec. 17.</p> <p>Over nearly level land.</p>   |
| 20.05  | The SE 1/16 sec. cor. of sec. 17.  |
| 26.20  | Track road, 8 ft. wide, bears NNE curving westerly and SSW.  |
| 28.21  | <p>Point selected for a witness point, at intersection with the northerly edge of landing strip.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP</p> <p style="text-align: center;">T 10 S R 9 E</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S 17</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this witness point, the northeasterly cor. of landing strip bears S. 62°41' E., 1.99 chs. dist.</p> <p>thence; across landing strip.</p> |

**Subdivision of Section 17,  
T. 10 S., R. 9 E., Gila and Salt River Meridian, Arizona**

| CHAINS |  |
|--------|--|
| 37.69  | <p>Point selected for a witness point, at intersection with the southerly edge of landing strip.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP<br/>T 10 S R 9 E</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S 17</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this witness point, the southeasterly cor. of landing strip bears S. 57°53' E., 10.65 chs. dist.</p> <p>thence; leave landing strip.</p>  |
| 40.10  | <p>The center S. 1/16 sec. cor. of sec. 17.</p> <hr/> <p style="text-align: center;"><b>Informative Traverses in the SW 1/4 SE 1/4 of Section 17,<br/>T. 10 S., R. 9 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>The following informative traverses in the SW 1/4 SE 1/4 of section 17, T. 10 S., R. 9 E., represent the extent of evidence of unauthorized use and disturbance of public lands and are for informational purposes only.</p> <hr/> <p style="text-align: center;">Traverse One</p> <hr style="width: 20%; margin: auto;"/> <p>Beginning at the witness point on the E. and W. center line of the SE 1/4 of sec. 17, at intersection with the northerly edge of bladed landing strip, hereinbefore described.</p> <p>thence S. 62°41' E., 1.99 chs. dist., along the edge of bladed landing strip, to Angle Point 1, sec. 17, not monumented;</p> <p>thence S. 24°42' W., 2.19 chs. dist., along the edge of bladed landing strip, to Angle Point 2, sec. 17, not monumented;</p> <p>thence S. 25°09' W., 3.08 chs. dist., along the edge of bladed landing strip, to Angle Point 3, sec. 17, not monumented;</p> |

**Informative Traverses in the SW 1/4 SE 1/4 of Section 17,  
T. 10 S., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS

thence N. 53°18' W., 4.58 chs. dist., along the edge of bladed landing strip, to Angle Point 4, sec. 17, not monumented;

thence N. 63°32' W., 3.06 chs. dist., along the edge of bladed landing strip, to Angle Point 5, sec. 17, not monumented;

thence N. 59°06' W., 3.04 chs. dist., along the edge of bladed landing strip, to the witness point on the E. and W. center line of the SE 1/4 of sec. 17, at intersection with the southerly edge of bladed landing strip, hereinbefore described.

---

Traverse Two

---

Beginning at the witness point on the N. and S. center line of sec. 17, at intersection with the northerly edge of a bulldozed and bladed area, hereinbefore described.

thence S. 51°46' E., 10.69 chs. dist., along the edge of a bulldozed and bladed area, to Angle Point 6, sec. 17, not monumented;

thence S. 40°43' W., 4.69 chs. dist., along the edge of a bulldozed and bladed area, to Angle Point 7, sec. 17, not monumented;

thence S. 30°55' W., 3.11 chs. dist., along the edge of a bulldozed and bladed area, to Angle Point 8, sec. 17, not monumented;

thence S. 40°08' W., 3.09 chs. dist., along the edge of a bulldozed and bladed area, to Angle Point 9, sec. 17, not monumented;

thence S. 83°10' W., 1.74 chs. dist., along the edge of a bulldozed and bladed area, to the 1/4 cor. of secs. 17 and 20, hereinbefore described.

## T. 10 S., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS

## GENERAL DESCRIPTION

---

This survey is located approximately 8 mile WSW of Red Rock Arizona. The elevation averages about 1800 ft. above sea level. The terrain is nearly level with sandy soil, and vegetation predominated by creosote, mesquite and native grasses, with scattered palo verde and ironwood.

The La Osa Ranch headquarters is located adjacent to the surveyed area in the SW 1/4 of sec. 16. A goat ranch is located in the NW 1/4 of sec. 17. Two trespasses were noted in the SW 1/4 of the SE 1/4 of sec. 17, consisting of a bladed area with mining slag dumps, encompassing 7.0 acres and the extension of an existing airplane landing strip encompassing 3.06 acres.

Access is by way of Sasco Road and two bladed roads.

The mean magnetic declination of  $11\ 1/2^\circ$  E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2000 for the dates of survey.

---



