

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF A

PORTION OF THE SUBDIVISIONAL LINES

AND THE SUBDIVISION OF SECTIONS 15, 23 AND 26

TOWNSHIP 18 NORTH, RANGE 13 WEST,

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA.

EXECUTED BY

Joe R. Salazar, Cadastral Surveyor

Under Special Instructions dated May 28, 2003, approved May 28, 2003, which provided for the surveys included under Group No. 904, and assignment instructions dated May 28, 2003.

Survey commenced June 3, 2003

Survey completed June 17, 2003

INDEX DIAGRAM

TOWNSHIP 18 NORTH RANGE 13 WEST

6	5	4	3	2	1
7	8	9	10 11	11	12
18	17	16 10	15 8 9	14	13
19	20	21	22 7	23 4 6	24
30	29	28	27 5	26 4 5	25
31	32	33	34	35	36

Subdivision of Section 15 Pages 11-12
 Subdivision of Section 23 Pages 13-16
 Subdivision of Section 26 Pages 16-19

T. 18 N., R. 13 W., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the subdivisional lines and the subdivision of sections 15, 23 and 26, T. 18 N., R. 13 W., Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

C. Burton Foster surveyed the exterior boundaries in 1874. W. O. Secor resurveyed the exterior boundaries in 1911. Jesse B. Wright surveyed the subdivisional lines in 1911.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated May 28, 2003, for Group No. 904, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from second order Arizona Department of Transportation triangulation station NITE, as published by the National Geodetic Survey, NAD 83(1993). The graphic position of the corner of sections 25, 26, 35 and 36 is as follows:

Latitude: 34°54'21.18" N. Longitude: 113°37'01.51" W.

The mean magnetic declination is 12 1/2° E.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 N., R. 13 W., Gila and Salt River Meridian, Arizona**

Restoring the survey executed by
Jesse B. Wright, in 1911

Beginning at the cor. of secs. 25, 26, 35 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above the ground with brass cap mkd., T18N R13W S26 S25 S35 S36 1911.

Add the marks 2003 to the brass cap.

**Dependent Resurvey of a portion of the Subdivisional Lines
T. 18 N., R. 13 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>N. 0°18' W., bet. secs. 25 and 26.</p> <p>Over rolling desert terrain, through scattered mesquite and native grasses.</p>
39.62	<p>The witness cor. for the 1/4 sec. cor. of secs. 25 and 26, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above the ground, with brass cap mkd. S26 S25 1/4 WC 1911.</p> <p>There is no remaining evidence of original mound of stone.</p> <p>Add the marks T18N R13W 2003 to the brass cap.</p> <p>Cor. is located in fence corner, extending N. and W.</p> <hr/> <p>N. 0°12' W., beginning new measurement.</p>
0.40	<p>True point for the 1/4 sec. cor. of secs. 25 and 26. The true point falls in wash, draining SSW, impracticable to establish a permanent monument.</p>
20.425	<p>Point for the N. 1/16 sec. cor. of secs. 25 and 26.</p> <p>Cor. not monumented.</p>
40.45	<p>The cor. of secs. 23, 24, 25 and 26, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd. T18N R13W S23 S24 S26 S25 1911.</p> <p>Add the marks 2003 to the brass cap.</p> <p>Cor. is located at the intersection of fences, extending N., S., E. and W.</p> <hr/> <p>N. 0°04' W., bet. secs. 23 and 24.</p>
39.97	<p>Over rolling desert terrain, through scattered mesquite and native grasses.</p> <p>The 1/4 sec. cor. of secs. 23 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above the ground, with brass cap mkd. 1/4 S23 S24 1911.</p> <p>Add the marks T18N R13W 2003 to the brass cap.</p> <p>Cor. is located at the intersection of fences, extending N., E. and S.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p>


**Dependent Resurvey of a portion of the Subdivisional Lines
T. 18 N., R. 13 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>N. 89°58' W., bet. secs. 26 and 35.</p> <p>Over rolling desert terrain, through scattered mesquite and native grasses.</p>
12.50	Center of the dry, Big Sandy River, drains S.
40.13	<p>Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original cor., occupied by a rebar, of unknown origin, 5/8 ins. diam., firmly set, projecting 3 in. above the ground.</p> <p>Cor. not monumented.</p>
60.10	Track rd., bears N. and S.
60.195	<p>Point for the W 1/16 sec. cor. of secs. 26 and 35. Occupied by a rebar, of unknown origin, 5/8 ins. diam., firmly set 1 in. below the ground.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T18N R13W S 26 W 1/16 ——— S 35</p> <p align="center">2003</p>
	<p>Deposit a magnet in a white plastic case and the rebar at the base of the stainless steel post.</p> <p>Cor. is located 12 lks. E. of fence, extending E. and W.</p>
80.26	<p>The cor. of secs. 26, 27, 34 and 35, monumented with an iron post, 2 ins. diam. firmly set, projecting 20 ins. above the ground, in a mound of stone 2 ft. base, 1 ft. high, with brass cap mkd. T18N R13W S27 S26 S34 S35 1911.</p> <p>Witnessed with a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Add the marks 2003 to the brass cap.</p> <hr/>
	<p>N. 0°16' W., bet. secs. 26 and 27.</p> <p>Over rolling desert terrain, through scattered mesquite and native grasses.</p>

**Dependent Resurvey of a portion of the Subdivisional Lines
T. 18 N., R. 13 W., Gila and Salt River Meridian, Arizona**

CHAINS	
40.02	<p>The 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 1 in. diam., firmly set, projecting 13 ins. above the ground with brass cap mkd. 1/4 S27 S26 1911.</p> <p>Add the mks. T18N R13W 2003 to the brass cap.</p> <p>Cor. is located in fence, extending N. and S.</p> <hr/> <p>N. 0°05' W., beginning new measurement.</p>
40.02	<p>The cor. of secs. 22, 23, 26 and 27, monumented with an iron post, 2 ins. diam., firmly set, projecting 20 ins. above the ground, in a mound of stone, 3 ft. base 18 ins. high, with brass cap mkd. T18N R13W S22 S23 S27 S26 1911.</p> <p>Add the marks 2003 to the brass cap.</p> <p>Cor. is located at the intersection of fences, extending N., S. and W.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 89°59' W., bet. secs. 23 and 26.</p> <p>Over rolling desert terrain, through scattered mesquite and native grasses.</p>
10.02	<p>Point for the E-E 1/64 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T18N R13W S 23 E-E 1/64 S 26</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 8 lks. N. of a fence, extending E. and W.</p>
20.04	<p>Point for the E 1/16 sec. cor. of secs. 23 and 26.</p> <p>Cor. not monumented.</p>

**Dependent Resurvey of a portion of the Subdivisional Lines
T. 18 N., R. 13 W., Gila and Salt River Meridian, Arizona**

CHAINS	
40.08	<p>True point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate distance, there is no remaining evidence of the original witness cor. The cor. point falls in Big Sandy River, impracticable to establish a permanent monument.</p> <p>From this cor. an X chiseled on a concrete well head, 30 ins. square projecting 24 ins. above the ground, bears S. 87°40' E., 4.40 chs. dist.</p> <p>From this same cor. the point selected for the witness 1/4 sec. cor. of secs. 23 and 26, bears S. 74°42' E., 4.04 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC</p> <p>T 18 N R 13 W</p>  <p>S 23</p> <p>1/4 ———</p> <p>S 26</p> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
60.12	<p>Point for the W 1/16 sec. cor. of secs. 23 and 26.</p> <p>Cor. not monumented.</p>
80.16	<p>The cor. of secs. 22, 23, 26 and 27.</p> <hr/> <p>N. 0°02'W., bet. secs. 22 and 23.</p> <p>Over rolling desert terrain, through scattered mesquite and native grasses.</p>
19.895	<p>Point for the S. 1/16 sec. cor. of secs. 22 and 23.</p> <p>Cor. not monumented.</p>
39.79	<p>True point for the 1/4 sec. cor. of secs. 22 and 23 at proportionate distance, there is no remaining evidence of the original witness cor.</p> <p>Cor. not monumented.</p> <p>From this cor. point an open ended iron pipe, 1 in. diam., of unknown origin, firmly set, projecting 2 ins. above the ground, bears N. 1°47' E., 20 lks. dist.</p>

**Dependent Resurvey of a portion of the Subdivisional Lines
T. 18 N., R. 13 W., Gila and Salt River Meridian, Arizona**

CHAINS	
59.685	Point for the N. 1/16 sec. cor. of secs. 22 and 23.
	Cor. not monumented.
79.58	The cor. of secs. 14, 15, 22 and 23, monumented with an iron post, 2 ins. diam, firmly set, projecting 18 ins. above the ground in a mound of stone, 3 ft. base to top, with brass cap mkd. T18N R13W S15 S14 S22 S23 1911.
	Add the marks 2003 to the brass cap.
	<hr/> From the 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above the ground, with brass cap mkd. 1/4 S14 S23 1911.
	Witnessed with a mound of stone 4 ft. base 3 ft. high, N. of cor.
	Add the marks T18N R13W 2003 to the brass cap.
	N. 89°53' W., bet. secs. 14 and 23.
	Over rolling desert terrain, through scattered mesquite and native grasses.
20.055	Point for the W. 1/16 sec. cor. of secs. 14 and 23.
	Cor. not monumented.
40.11	The cor. of secs. 14, 15, 22 and 23.
	<hr/> N. 0°03' E., bet. secs. 14 and 15.
	Over very rugged, mountainous terrain, through scattered mesquite and native grasses.
40.22	The 1/4 sec. cor. of secs. 14 and 15, monumented with a granite stone, 18 X 13 X 6 ins., firmly set 12 ins. in the ground, clearly mkd. 1/4 on W. face and 1/4 on E. face, with mound of stone, 3 ft. base, 2 ft. high W. of cor.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">T 18 N R 13 W 1/4 S 15 S 14</p>
	<p align="center">2003</p>

**Dependent Resurvey of a portion of the Subdivisional Lines
T. 18 N., R. 13 W., Gila and Salt River Meridian, Arizona**

CHAINS							
	<p>Bury the original stone alongside of and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located on NE slope of ridge, bears SE and NW, 15 lks. E. of fence, extending N. and S.</p> <hr/> <p>N. 0°15' W., beginning new measurement.</p>						
39.96	<p>The cor. of secs 10, 11, 14 and 15, monumented with a granite stone, 18 X 7 X 6 ins., firmly set 10 ins. in the ground, clearly mkd. with 2 notches on E. edge and 4 notches on S. edge. With scattered mound of stone W. of cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table data-bbox="808 890 1036 989" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 18 N</td> <td>R 13 W</td> </tr> <tr> <td>S 10</td> <td>S 11</td> </tr> <tr> <td>S 15</td> <td>S 14</td> </tr> </table> <p style="text-align: center;">2003</p>	T 18 N	R 13 W	S 10	S 11	S 15	S 14
T 18 N	R 13 W						
S 10	S 11						
S 15	S 14						
	<p>Bury the original stone alongside of and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Rebuild mound of stone 3 ft. base 2 ft. high W. of cor.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 89°52' W., bet. secs. 15 and 22.</p> <p>Over very rugged, mountainous terrain, through scattered mesquite and native grasses.</p>						
24.00	<p>Leave mountainous terrain, enter nearly level land, along Knight Creek bottom.</p>						
40.00	<p>The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 1 in. diam., firmly set 8 ins. below the ground, with brass cap mkd. 1/4 S15 S22 1911.</p> <p>Add the marks T18N R13W 2003 to the brass cap.</p> <p>Cor. is located 9 lks. N. of fence, extending E. and W., under abandon power line, bears SE and NW.</p> <hr/> <p>N. 89°54' W., beginning new measurement.</p>						

**Dependent Resurvey of a portion of the Subdivisional Lines
T. 18 N., R. 13 W., Gila and Salt River Meridian, Arizona**

CHAINS	
19.90	Begin ascent, thence along rugged, mountainous terrain.
39.95	<p>The cor. of secs. 15, 16, 21 and 22, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd. T18N R13W S16 S15 S21 S22 1911.</p> <p>Add the marks 2003 to the brass cap.</p> <p>Cor. is located on the E. slope of wash, drains S, in fence, extending E. and W.</p> <hr/> <p>N. 0°03' W., bet. secs. 15 and 16.</p> <p>Over very rugged, mountainous terrain, through scattered mesquite and native grasses.</p>
19.965	<p>Point for the S. 1/16 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p align="center">T18N R13W S 1/16 S 16 S 15</p> <p align="center">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
39.93	<p>The 1/4 sec. cor. of secs. 15 and 16, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above the ground, in a mound of stone, 4 ft. base to top, and a mound of stone, 4 ft. base, 2 ft. high to W., with brass cap mkd. S16 1/4 S15 1911.</p> <p>Add the mks. T18N R13W 2003 to the brass cap.</p> <p>Cor. is located on E. slope of ridge bears N. and S.</p> <hr/> <p>N.0°03' W., beginning new measurement.</p>
40.21	<p>The cor. of secs. 9, 10, 15 and 16, monumented with an iron post, 2 ins. diam., firmly set, projecting 24 ins. above the ground in a mound of stone 4 ft. base to top, and a mound of stone, 4 ft. base, 3 ft. high to W., with brass cap mkd. T18N R13W S9 S10 S16 S15 1911.</p> <p>Add the marks 2003 to the brass cap.</p>

**Subdivision of Section 15
T. 18 N., R. 13 W., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Over rolling desert terrain, through scattered mesquite and native grasses.</p>
20.03	<p>Point for the center S. 1/16 sec. cor. of sec. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>C T 18 N R 13 W S 1/16 S 15 C</p> </div> <p align="center">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
40.06	<p>Point for the center 1/4 sec. cor. of sec. 15, at intersection with the E. and W. center line of sec. 26.</p> <p>Cor. not monumented.</p>
80.17	<p>The 1/4 sec. cor. of secs. 10 and 15.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the 1/4 sec. cor. of secs. 14 and 15.</p> <p>S.89°55'W., on the E. and W. center line of sec. 15.</p> <p>Over rolling desert terrain, through scattered mesquite and native grasses.</p>
40.02	<p>The center 1/4 sec. cor. of sec 15.</p>
80.01	<p>The 1/4 sec. cor. of secs. 15 and 16.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p align="center">SW 1/4 Section 15</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the center S. 1/16 sec. cor. of sec. 15.</p> <p>West, along the E. and W. center line of the SW 1/4 of sec. 15.</p> <p>Over rolling desert terrain, through scattered mesquite and native grasses.</p>
39.97	<p>The S. 1/16 sec. cor. of secs. 15 and 16.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/>

**Subdivision of Section 23
T. 18 N., R. 13 W., Gila and Salt River Meridian, Arizona**

CHAINS	
19.94	<p>From the true point for the 1/4 sec. cor. of secs. 23 and 26. North, on the N. and S. center line of sec. 23.</p> <p>Over rolling desert terrain, through scattered mesquite and native grasses.</p> <p>True point for the center S. 1/16 sec. cor. of sec. 23. The cor. point falls in Trout Creek, impracticable to establish a permanent monument.</p> <p>From this cor. the point selected for the witness S. 1/16 sec. cor. of secs 23, bears S.60°56'E., 1.47 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>WC T18N R13W C S 1/16 S 23 C</p> </div> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located on the right bank of Trout Creek, drains S.</p>
39.88	<p>True point for the center 1/4 sec. cor. of sec. 23, at intersection with the E. and W. center line of sec. 23. The cor. point falls in Trout Creek, impracticable to establish a permanent monument.</p> <p>From this cor. the point selected for the witness center 1/4 sec. cor. of secs. 23, bears S.87°24'W., 1.01 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>WC T 18 N R 13 W C 1/4 S 23</p> </div> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located on the right bank of Trout Creek, drains S.</p>
59.695	<p>Point for the center N. 1/16 sec. cor. of sec. 23.</p>

**Subdivision of Section 23
T. 18 N., R. 13 W., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p align="center">T18N R13W C N 1/16 S 23 C</p> <p align="center">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located in abandoned fence, bears N. and S., on the left bank of Trout Creek, drains S.</p> <p>From this cor. a 1 in. diam. rebar, of unknown origin, firmly set, projecting 4 ins. above the ground, bears S.9°43'E., 13 lks. dist.</p>
79.51	<p>The 1/4 sec. cor. of secs. 14 and 23.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 23 and 24.</p> <p>S.89°54'W., on the E. and W. center line of sec. 23.</p> <p>Over rolling desert terrain, through scattered mesquite and native grasses.</p>
40.03	<p>True point for the center 1/4 sec. cor. of sec. 23.</p>
60.08	<p>Point for the center W. 1/16 sec. cor. of sec. 23.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T18N R13W W 1/16 C—C S 23</p> <p align="center">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.13	<p>The 1/4 sec. cor. of secs. 22 and 23.</p> <hr/> <p align="center">SW 1/4 Section 23</p> <hr/>

**Subdivision of Section 23
T. 18 N., R. 13 W., Gila and Salt River Meridian, Arizona**

CHAINS	
19.92	<p>From the W. 1/16 sec. cor. of secs. 23 and 26.</p> <p>N.0°01'W., on the N. and S. center line of the SW 1/4 of sec. 23.</p> <p>Over rolling desert terrain, through scattered mesquite and native grasses.</p> <p>True point for the SW 1/16 sec. cor. of sec. 23 at intersection with the E. and W. center line of the SW 1/4 of sec. 23. The cor. point falls in Knight Creek, impracticable to establish a permanent monument.</p> <p>From this cor. the point selected for the witness SW 1/16 sec. cor. of secs 23, bears S.40°40'W., 49 lks. dist.</p> <div style="text-align: center; margin: 10px 0;"> <p style="margin: 0;">WC T18N R13W SW 1/16 S 23 2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located on the right bank of Knight Creek, drains SE.</p>
39.84	<p>The center W. 1/16 sec. cor. of sec. 23.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the true point for the center S. 1/16 sec. cor. of sec. 23.</p> <p>S.89°57'W., on the E. and W. center line of the SW 1/4 of sec. 23.</p> <p>Over rolling desert terrain, through scattered mesquite and native grasses.</p>
20.04	<p>True point for the SW 1/16 sec. cor. of sec. 23.</p>
40.08	<p>The S. 1/16 sec. cor. of secs. 22 and 23.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p style="text-align: center;">NW 1/4 Section 23</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the center W. 1/16 sec. cor. of sec. 23.</p> <p>N.0°01'W., on the N. and S. center line of the NW 1/4 of sec. 23.</p> <p>Over rolling desert terrain, through scattered mesquite and native grasses.</p>

**Subdivision of Section 23
T. 18 N., R. 13 W., Gila and Salt River Meridian, Arizona**

CHAINS	
19.855	<p>Point for the NW 1/16 sec. cor. of sec. 23. at intersection with the E. and W. center line of the NW 1/4 of sec. 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T18N R13W NW 1/16 S 23</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
39.71	<p>The W. 1/16 sec. cor. of secs. 14 and 23.</p> <hr/> <p>From the center N. 1/16 sec. cor. of sec. 23.</p> <p>West, on the E. and W. center line of the NW 1/4 of sec. 23.</p> <p>Over rolling desert terrain, through scattered mesquite and native grasses.</p>
1.60	Center of Trout Creek, drains S.
3.31	<p>Barbed wire fence line and E. edge of cultivated field, bears N. and S.</p> <p>From this point a corner of fences, bears S.1°38'E., 2.81 chs. dist., extending N. and WSW.</p>
11.97	<p>Barbed wire fence line and W. edge of cultivated field, bears N. and S.</p> <p>From this point a corner of fences, bears S.13°36'E., 5.02 chs. dist., extending ENE and NNW.</p>
12.25	From this point a well head with electric pump, bears S., 12 lks. dist.
20.05	The NW 1/16 sec. cor. of sec. 23.
40.10	The N. 1/16 sec. cor. of secs. 22 and 23.
	<p>Subdivision of Section 26, T. 18 N., R. 13 W., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 26 and 35.</p>

Subdivision of Section 26
T. 18 N., R. 13 W., Gila and Salt River Meridian, Arizona

CHAINS	
	N.0°13'W., on the N. and S. center line of sec. 26. Over rolling desert terrain, through scattered mesquite and native grasses.
40.02	Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E. and W. center line of sec. 26. Cor. not monumented.
60.035	Point for the center N. 1/16 sec. cor. of sec. 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 18 N R 13 W C N 1/16 S 26 C 2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.05	True point for the 1/4 sec. cor. of secs. 23 and 26. <hr/>
	From the true point for the 1/4 sec. cor. of secs. 25 and 26. N.89°57'W., on the E. and W. center line of sec. 26. Over rolling desert terrain, through scattered mesquite and native grasses.
20.035	Point for the center E. 1/16 sec. cor. of sec. 26 Cor. not monumented.
40.07	The center 1/4 sec. cor. of sec. 26.
60.15	True point for the center W. 1/16 sec. cor. of secs. 26. The cor. point falls in wash, impracticable to establish a permanent monument. From this cor. the point selected for the witness W. 1/16 sec. cor. of secs. 26, bears N.51°19'W., 1.28 chs. dist. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Subdivision of Section 26
 T. 18 N., R. 13 W., Gila and Salt River Meridian, Arizona

CHAINS	
80.23	<p style="text-align: center;">WC T 18 N R 13 W W 1/16 C ——— C S 26 ↘</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The 1/4 sec. cor. of secs. 26 and 27.</p> <hr/> <p style="text-align: center;">NE 1/4 of section 26</p> <hr/> <p>From the center E. 1/16 sec. cor. of sec. 26.</p> <p>N.0°12'W., on the N. and S. center line of the NE. 1/4 of sec. 26.</p> <p>Over rolling desert terrain, through scattered mesquite and native grasses.</p>
20.02	<p>Point for the NE 1/16 sec. cor. of sec. 26.</p> <p>Cor. not monumented.</p>
40.04	<p>The E. 1/16 sec. cor. of secs. 23 and 26.</p> <hr/> <p>From the N. 1/16 sec. cor. of secs. 25 and 26.</p> <p>N.89°58'W., on the E. and W. center line of the NE 1/4 of sec. 26.</p> <p>Over rolling desert terrain, through scattered mesquite and native grasses.</p>
10.02	<p>Point for the C-E-NE 1/64 sec. cor. of sec. 26.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T18N R13W E-NE 1/64 C ——— C S 26</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Subdivision of Section 26
T. 18 N., R. 13 W., Gila and Salt River Meridian, Arizona**

CHAINS	
20.04	The NE 1/16 sec. cor. of sec. 26.
40.08	The center N. 1/16 sec. cor. of sec. 26.
	<hr/> <p>From the E-NE 1/64 sec. cor. of sec. 26.</p> <p>N.0°12'W., on the N. and S. center line of the NE 1/4 of the NE 1/4 sec. 26.</p> <p>Over rolling desert terrain, through scattered mesquite and native grasses.</p>
20.02	The E-E 1/64 sec. cor. of secs. 23 and 26.
	<hr/> <p style="text-align: center;">SW 1/4 of section 26</p> <hr/> <p>From the W. 1/16 sec. cor. of secs. 26 and 35.</p> <p>N.0°14'W., on the N. and S. center line of the SW 1/4 of sec. 26.</p> <p>Over rolling desert terrain, through scattered mesquite and native grasses.</p>
40.02	The center W. 1/16 sec. cor. of sec. 26.
	<hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p>The survey is approximately 38 miles SE of the town of Kingman, Arizona. State Road 90 traverses the Tp. from N. to S., scattered dirt roads provide access to the area.</p> <p>Trout Creek and Knight Creek join to form Big Sandy River, in section 26, which is the main drainage in the area. The land generally slopes toward these creeks and is very rugged on both sides of their banks. The elevation ranges from 2600 to 3000 feet above sea level.</p> <p>There is scattered paloverde and mesquite trees in this area and salt cedar and cottonwood trees along the creeks. There is some farming in section 23; the rest of the Tp. is used for grazing.</p> <p>The mean magnetic declination of 12 1/2° E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2000 for the dates of survey.</p> <hr/>

CERTIFICATE OF SURVEY

I, Joe R. Salazar, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 28, day of May, 2003, I dependently resurveyed a portion of the subdivisional lines and subdivided sections 15, 23 and 26, T. 18 N., R. 13 W., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

3/30/04
(Date)

Joe R. Salazar
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines and the subdivision of sections 15, 23 and 26, T. 18 N., R. 13 W., Gila and Salt River Meridian, in the State of Arizona, executed by Joe R. Salazar, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

2/08/05
(Date)

Stephen K. Hansen
Acting (Chief Cadastral Surveyor of Arizona)

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 18 N., R. 13 W., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____~~
~~(Date)~~

~~_____~~
~~(Chief Cadastral Surveyor of Arizona)~~