

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF THE SIXTH STANDARD PARALLEL NORTH

(SOUTH BOUNDARY),

THE EAST, WEST AND NORTH BOUNDARIES,

AND THE SURVEY OF THE SUBDIVISIONAL LINES,

TOWNSHIP 25 NORTH, RANGE 26 EAST,

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA

EXECUTED BY

JONES CURTISS, Cadastral Surveyor

Under Special Instructions dated and approved May 1, 2002, which provided for the surveys included under Group No. 886, and assignment instructions dated May 1, 2002.

Survey commenced June 6, 2002

Survey completed July 3, 2002

INDEX DIAGRAM

TOWNSHIP 25 NORTH RANGE 26 EAST
GILA AND SALT RIVER MERIDIAN, ARIZONA

24	23	22	21	21	20
19 6 63	5 53	4 46	3 39	2 32	1 14
62	62	52	46	39	31
18 7 61	8 52	9 45	10 38	11 30	12 13
60	60	51	44	37	30
18 18 59	17 50	16 44	15 36	14 29	13 12
58	58	50	43	36	29
17 19 57	20 49	21 42	22 35	23 28	24 11
56	56	49	42	34	27
16 30 55	29 48	28 41	27 34	26 26	25 10
55	54	47	41	33	26
16 31 53	32 47	33 40	34 32	35 25	36 9
4	4	5	6	7	8

T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of the Sixth Standard Parallel North (south boundary), the east, west and north boundaries, and the survey of the subdivisional lines, Township 25 North, Range 26 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

The Sixth Standard Parallel North through Ranges 25 and 26 East was surveyed by Frank Follman in 1883. The east, west and north boundaries were surveyed by Frederick C. Miller in 1915. A portion of the Sixth Standard Parallel North (south boundary), Township 25 North, Range 25 East, was dependently resurveyed by Jones Curtiss, in 2002, concurrently under this same group.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated May 1, 2002, for Group No. 886, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation Model 5700 receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey's Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) FLAGSTAFF, AZTEC AND PIE TOWN VLBA. The NAD83(CORS96)(EPOCH:2002) geographic position of the southeast corner of the township is as follows:

Latitude: 35°31'03.49" N. Longitude: 109°30'26.12" W.

The mean magnetic declination is 12 1/2° E.

Dependent Resurvey of the Sixth Standard Parallel North (South Boundary),
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">Restoring the survey executed by Frank Follman, in 1883</p> <hr/> <p>Beginning at the stan. cor. of Tp. 25 N., Rs. 25 and 26 E., monumented with an iron post, 3 ins. diam., set, marked and witnessed as described in the field notes of the dependent resurvey of a portion of the Sixth Standard Parallel North (south boundary), T. 25 N., R. 25 E., executed concurrently under this same group.</p> <p>S. 89°54' E., on the S. bdy. of sec. 31.</p> <p>Over rolling land.</p> <p>40.02 Point for the stan. 1/4 sec. cor. of sec. 31, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T25N R26E 1/4 S31 <hr/>2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>80.04 Point for the stan. cor. of secs. 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T25N R26E S31 S32 <hr/>2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>S. 89°54' E., on the S. bdy. of sec. 32.</p> <p>Over rolling land.</p> <p>40.02 Point for the stan. 1/4 sec. cor. of sec. 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Sixth Standard Parallel North (South Boundary),
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">SC T25N R26E 1/4 S32 <hr/>2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 45 lks. N. of a trail road and 2.35 chs. N. of the most northerly underground gas pipeline, both bear N. 70° E and S. 70° W.</p>
80.04	<p>The stan. cor. of secs. 32 and 33, determined from the remains of an original bearing tree</p> <p style="padding-left: 40px;">A root hole, bears S. 30° W., 1.20 chs. dist., with an uprooted piñon, 12 ins. diam., with illegible scribe marks on open blaze, lying alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T25N R26E S32 S33 <hr/>2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>S. 89°58' E., on the S. bdy. of sec. 33.</p> <p>Over rolling land.</p>
39.82	<p>Point for the stan. 1/4 sec. cor. of sec. 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T25N R26E 1/4 S33 <hr/>2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Dependent Resurvey of the Sixth Standard Parallel North (South Boundary),
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS					
79.64	<p>The stan. cor. of secs. 33 and 34, determined from the remaining original bearing tree</p> <p style="padding-left: 40px;">A multi-trunk juniper, 24 ins. diam. at base, bears N. 85° W., 48 lks. dist., mkd. TIIIVN RXVIE S7IIIII on open blaze on a branch, 12 ins. diam.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>SC</td></tr> <tr><td>T25N R26E</td></tr> <tr><td>S33 S34</td></tr> <tr><td style="border-top: 1px solid black;">2002</td></tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 60%; margin: 10px auto;"/>	SC	T25N R26E	S33 S34	2002
SC					
T25N R26E					
S33 S34					
2002					
	<p>S. 89°40' E., on the S. bdy. of sec. 34.</p> <p>Over rolling land.</p>				
40.38	<p>The stan. 1/4 sec. cor. of sec. 34, determined from the original bearing tree</p> <p style="padding-left: 40px;">A multi-trunk juniper, 26 ins. diam. at base, bears S. 82 1/2° W., 38 lks. dist., with illegible scribe marks on open blaze on a branch, 6 ins. diam.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>SC</td></tr> <tr><td>T25N R26E</td></tr> <tr><td>1/4 S34</td></tr> <tr><td style="border-top: 1px solid black;">2002</td></tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 60%; margin: 10px auto;"/>	SC	T25N R26E	1/4 S34	2002
SC					
T25N R26E					
1/4 S34					
2002					
	<p>N. 89°53' E., beginning new measurement.</p>				
39.96	<p>Point for the stan. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p>				

Dependent Resurvey of the Sixth Standard Parallel North (South Boundary),
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T25N R26E S34 S35 ----- 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>
	<p>N. 89°53' E., on the S. bdy. of sec. 35.</p> <p>Over rolling land.</p>
39.96	<p>The stan. 1/4 sec. cor. of sec. 35, determined from the remains of an original bearing tree</p> <p style="padding-left: 40px;">A root hole, bears N. 30° W., 26 lks. dist., with an uprooted piñon, 8 ins. diam., mkd. 1/4 BT on open blaze, lying alongside. (Record: 12 ins. diam.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T25N R26E 1/4 S35 ----- 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>
	<p>N. 89°56' E., beginning new measurement.</p>
32.95	<p>W. right-of-way fence of U. S. Highway No. 191, barbed wire, 5 strands, parallels highway.</p>
34.45	<p>U. S. Highway No. 191, asphalt pavement, 35 ft. wide, bears S. 10° E. and N. 10° W.</p>
35.96	<p>E. right-of-way fence of U. S. Highway No. 191, barbed wire, 5 strands, parallels highway.</p>
39.86	<p>Point for the stan. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p>

Dependent Resurvey of the Sixth Standard Parallel North (South Boundary),
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T25N R26E S35 S36 ----- 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>
39.86	<p>N. 89°56' E., on the S. bdy. of sec. 36.</p> <p>Over rolling land.</p> <p>Point for the stan. 1/4 sec. cor. of sec. 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T25N R26E 1/4 S36 ----- 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located in a dry lake bed behind an earthen dam, 2.00 chs. N. of old shore line, bears East and West.</p>
79.72	<p>The stan. cor. of Tp. 25 N., Rs. 26 and 27 E., monumented with a sandstone, 20 x 14 x 4 ins., firmly set, projecting 1 in. above ground, mkd. with 6 grooves on N. face and 6 grooves on S. face, from which the 1915 bearing tree</p> <p style="padding-left: 40px;">A standing dead piñon, 16 ins. diam., bears N. 29 1/2° E., 2.87 chs. dist., mkd. T25N R27E S31 BT on open blaze. (Record: N. 28 3/4° E.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Sixth Standard Parallel North (South Boundary),
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">SC T25N R26E R27E S36 S31 ----- 2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the 1915 stone alongside the stainless steel post.</p>
	<hr/> <p style="text-align: center;">Dependent Resurvey of the East Boundary, T. 25 N., R. 26., Gila and Salt River Meridian, Arizona</p> <hr/>
	<p style="text-align: center;">Restoring the survey executed by Frederick C. Miller, in 1915</p> <hr/>
	<p>N. 0°10' E., bet. secs. 31 and 36.</p> <p>Over rolling land.</p>
<p>39.98</p>	<p>Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T25N R26E R27E 1/4 S36 S31 ----- 2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 30 lks. N. of a trail road, bears N. 25° E. and S. 25° W.</p>
<p>79.96</p>	<p>The cor. of secs. 25, 30, 31 and 36, monumented with a sandstone, 21 x 10 x 9 ins., firmly set, projecting 13 ins. above ground, mkd. with 5 grooves on N. face and 1 groove on S. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the East Boundary,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	<table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">T25N</td></tr> <tr><td style="text-align: center;">R26E</td><td style="text-align: center;">R27E</td></tr> <tr><td style="text-align: center;">S25</td><td style="text-align: center;">S30</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S36</td><td style="text-align: center;">S31</td></tr> <tr><td colspan="2" style="text-align: center;">2002</td></tr> </table> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <hr/> <p>N. 0°06' E., bet. secs. 25 and 30.</p> <p>Over rolling and broken land.</p> <p>32.70 Underground gas pipeline, bears N. 70° E. and S. 70° W.</p> <p>39.22 Asphalt paved road, 16 ft. wide, bears N. 70° E. and S. 70° W.</p> <p>39.98 Point for the 1/4 sec. cor. of secs. 25 and 30, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">T25N</td></tr> <tr><td style="text-align: center;">R26E</td><td style="text-align: center;">R27E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S25</td><td style="text-align: center;">S30</td></tr> <tr><td colspan="2" style="text-align: center;">2002</td></tr> </table> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>46.70 Wide Ruins Wash, 15 ft. wide, 4 ft. deep, drains S. 50° W.</p> <p>79.96 The cor. of secs. 19, 24, 25 and 30, monumented with a sandstone, 22 x 10 x 4 ins., firmly set, projecting 9 ins. above ground, mkd. with 4 grooves on N. face and 2 grooves on S. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">T25N</td></tr> <tr><td style="text-align: center;">R26E</td><td style="text-align: center;">R27E</td></tr> <tr><td style="text-align: center;">S24</td><td style="text-align: center;">S19</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S25</td><td style="text-align: center;">S30</td></tr> <tr><td colspan="2" style="text-align: center;">2002</td></tr> </table>	T25N		R26E	R27E	S25	S30	-----		S36	S31	2002		T25N		R26E	R27E	1/4		S25	S30	2002		T25N		R26E	R27E	S24	S19	-----		S25	S30	2002	
T25N																																			
R26E	R27E																																		
S25	S30																																		

S36	S31																																		
2002																																			
T25N																																			
R26E	R27E																																		
1/4																																			
S25	S30																																		
2002																																			
T25N																																			
R26E	R27E																																		
S24	S19																																		

S25	S30																																		
2002																																			

Dependent Resurvey of the East Boundary,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <p>Cor. is located 1.60 chs. S. of a trail road, bears N. 40° E. and S. 40° W.</p> <hr/> <p>N. 0°02' E., bet. secs. 19 and 24.</p> <p>Over rolling land.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate dist. A sandstone 20 x 9 x 4 ins., lying loose nearby, mkd. 1/4 on up face.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R26E R27E 1/4 S24 S19 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <p>Cor. is located 60 lks. S. of S. bank of a wash, 10 ft. high, bears N. 50° E. and S. 50° W.</p>
80.04	<p>Point for the cor. of secs. 13, 18, 19 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R26E R27E S13 S18 ----- S24 S19 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Dependent Resurvey of the East Boundary,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Cor. is located 2.20 chs. E. of Navajo Route 203, a graded road, 38 ft. wide, bears N. 35° E. and S. 35° W.</p> <hr/> <p>N. 0°02' E., bet. secs. 13 and 18.</p> <p>Over rolling land.</p>
3.00	<p>Navajo Route 203, a graded road, 25 ft. wide, bears N. 35° E. and N. 35° E.</p>
40.02	<p>The 1/4 sec. cor. of secs. 13 and 18, monumented with a sandstone, 20 x 10 x 8 ins., firmly set, projecting 10 ins. above ground, mkd. 1/4 on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R26E R27E 1/4 S13 S18 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <hr/> <p>N. 0°06' E., beginning new measurement.</p>
39.98	<p>The cor. of secs. 7, 12, 13 and 18, monumented with a sandstone, 22 x 12 x 4 ins., firmly set, projecting 8 ins. above ground, mkd. with 2 grooves on N. face and 4 grooves on S. face</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R26E R27E S12 S 7 ----- S13 S18 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p>

**Dependent Resurvey of the East Boundary,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Cor. is located 40 lks. S. of a trail road, bears N. 40° E. and S. 40° W.</p> <hr/> <p>N. 0°04' E., bet. secs. 7 and 12.</p> <p>Over rolling and broken land.</p>
39.91	<p>The 1/4 sec. cor. of secs. 7 and 12, monumented with a sandstone, 21 x 9 x 7 ins., firmly set, projecting 7 ins. above ground, mkd. 1/4 on W. face, from which the original bearing trees</p> <p style="padding-left: 40px;">A piñon, 17 ins. diam., bears N. 14 1/2° E., 36 lks. dist., mkd. 1/4 S7 BT on open blaze.</p> <p style="padding-left: 40px;">A piñon, 11 ins. diam., bears S. 38 3/4° W., 55 1/2 lks. dist., mkd. 1/4 S12 BT on open blaze. (Record: S. 39 3/4° W., 54 lks.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R26E R27E 1/4 S12 S 7 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <hr/> <p>N. 0°02' E., beginning new measurement.</p>
39.95	<p>The cor. of secs. 1, 6, 7 and 12, monumented with a sandstone, 19 x 9 x 4 ins., firmly set, projecting 11 ins. above ground, mkd. with 1 groove on N. face and 5 grooves on S. face, from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A juniper, 24 ins. diam., bears S. 77° W., 28 lks. dist., mkd. T25N R26E S12 BT on open blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the East Boundary,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T25N</td></tr> <tr><td>R26E</td><td>R27E</td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S12</td><td>S 7</td></tr> <tr><td colspan="2">2002</td></tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <hr/> <p>N. 0°01' W., bet. secs. 1 and 6.</p> <p>Over rolling land.</p>	T25N		R26E	R27E	S 1	S 6	<hr/>		S12	S 7	2002	
T25N													
R26E	R27E												
S 1	S 6												
<hr/>													
S12	S 7												
2002													
39.95	<p>The 1/4 sec. cor. of secs. 1 and 6, monumented with a sandstone, 23 x 5 x 5 ins., loosely set, projecting 18 ins. above ground, mkd. 1/4 on W. face, from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears S. 55° W., 60 lks. dist., mkd. 1/4 S1 BT on open blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>												
	<div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T25N</td></tr> <tr><td>R26E</td><td>R27E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td colspan="2">2002</td></tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <hr/> <p>N. 0°05' E., beginning new measurement.</p> <p>Over rolling land.</p>	T25N		R26E	R27E	1/4		S 1	S 6	2002			
T25N													
R26E	R27E												
1/4													
S 1	S 6												
2002													
39.98	<p>The cor. of Tps. 25 and 26 N., Rs. 26 and 27 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. T26N R26E S36 S31 S1 S6 T25N R27E 1915.</p> <p>Remark the brass cap to read</p>												

**Dependent Resurvey of the East Boundary,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS

T26N		
R26E		T26N
S 36		R27E
<hr/>		
S 1		S 6
T25N		
1915		
2002		

From this cor. point, the cor. of Tp. 26 N., Rs. 27 and 28 E., bears N. 89° 35' E., 473.21 chs. dist., perpetuated by persons unknown, monumented with a rebar, 20 ins. long, 5/8 in. diam., firmly set, projecting 4 ins. above ground, in a scattered mound of stone; and is accepted as a careful and faithful perpetuation of the position of the original cor., from which the original bearing tree

A piñon, 14 ins. diam., bears N. 5 3/4° E., 64 lks. dist., with healed blaze. (Record: N. 7 1/4° E.)

and the 1920 bearing trees

A forked piñon, 14 ins. diam. at base, bears N. 29° E., 1.74 chs. dist., with illegible scribe marks on open blaze, on a branch, 9 ins. diam.

A piñon, 15 ins. diam., bears N. 76 1/2° E., 1.78 chs. dist., with illegible scribe marks on open blaze.

A forked piñon, 12 ins. diam. at base, bears N. 82° W., 40 lks. dist., with illegible scribe marks on open blaze, on a branch, 8 ins. diam.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 5 ft. base to top, with brass cap mkd.

T26N		
R27E		R28E
S36		S31
<hr/>		
T25N		R27E
2002		

Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Dependent Resurvey of the East Boundary,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS

Bury the rebar alongside the stainless steel post.

Dependent Resurvey of the West Boundary,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

Restoring the survey executed by
Frederick C. Miller, in 1915

From the stan. cor. of Tp. 25 N., Rs. 25 and 26 E., on the S. bdy. of the Tp., hereinbefore described.

N. 0°04' E., bet. secs. 31 and 36.

Over rolling land.

40.03 Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T25N
R25E R26E
1/4
S36 | S31
2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

80.06 Point for the cor. of secs. 25, 30, 31 and 36, at proportionate dist. An iron post, 3 ins. diam., lying loose nearby, mkd. T25N R25E R26E S25 S30 S36 S31 1915.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T25N
R25E | R26E
S25 | S30
S36 | S31
2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Bury the iron post alongside the stainless steel post.

N. 0°04' E., bet. secs. 25 and 30.

Dependent Resurvey of the West Boundary,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling land.
40.03	<p>Point for the 1/4 sec. cor. of secs. 25 and 30, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R25E R26E 1/4 S25 S30 2002</p>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.06	<p>The cor. of secs. 19, 24, 25 and 30, monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T25N R26E S24 S19 S25 S30 R25E 1915, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A root hole, bears S. 36 1/2° W., 1.15 chs. dist., with an uprooted decayed piñon, 12 ins. diam., mkd. T25N R25E S25 BT on open blaze, lying alongside. (Record: S. 38° W., 119 lks.)</p> <p style="padding-left: 40px;">A root hole, bears N. 81 3/4° W., 1.00 ch. dist., with an uprooted decayed piñon, 8 ins. diam., mkd. T25N R25E S24 BT on open blaze, lying alongside. (Record: N. 81° W., 103 lks.)</p> <p>Add the marks 2002 to the brass cap.</p> <hr/>
	N. 0°12' E., bet. secs. 19 and 24.
	Over rolling land.
39.95	<p>The 1/4 sec. cor. of secs. 19 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. 1/4 S24 S19 1915, from which the original bearing tree</p> <p style="padding-left: 40px;">A piñon, 20 ins. diam., bears S. 78° E., 1.28 chs. dist., with illegible scribe marks on partially healed blaze.</p> <p>Add the marks T25N R25E R26E 2002 to the brass cap.</p> <hr/>
	N. 0°10' E., beginning new measurement.

Dependent Resurvey of the West Boundary,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.01	<p>The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. T25N R26E S13 S18 S19 S24 R25E 1915, from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A juniper, 22 ins. diam., bears S. 46 3/4° W., 67 lks. dist., mkd. T25N R26E S25 BT on open blaze.</p> <p>Add the marks 2002 to the brass cap.</p> <hr/> <p>N. 0°01' E., bet. secs. 13 and 18.</p> <p>Over rolling and broken land.</p>
4.15	<p>Navajo Route 9205, a graded road, 22 ft. wide, bears N. 80° E. and S. 80° W.</p>
40.01	<p>The 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. 1/4 S13 S18 1915, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A forked piñon, 10 ins. diam., bears N. 11 1/4° E., 2.00 chs. dist., mkd. 1/4 S18 BT on open blaze. (Record: N. 8 1/2 ° E.)</p> <p style="padding-left: 40px;">A root hole, bears S. 15 1/2° W., 1.26 chs. dist., with a decayed piñon, 7 ins. diam., mkd. 1/4 S13 BT on open blaze, lying alongside.</p> <p>Add the marks T25N R25E R26E 2002 to the brass cap.</p> <hr/> <p>North, beginning new measurement.</p>
39.97	<p>The cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. T25N R26E S7 S12 S13 S18 R25E 1915.</p> <p>Add the marks 2002 to the brass cap.</p> <hr/> <p>North, bet. secs. 7 and 12.</p> <p>Over rolling land.</p>
23.40	<p>High voltage transmission line, bears N. 40° E. and S. 40° W.</p>

**Dependent Resurvey of the West Boundary,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.99	<p>The 1/4 sec. cor. of secs. 7 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. 1/4 S7 S12 1915, from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A piñon, 14 ins. diam., bears N. 15 1/4° W., 42 lks. dist., mkd. 1/4 S12 BT on open blaze. (Record: N. 11° W.)</p> <p>Add the marks T25N R25E R26E 2002 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>North, beginning new measurement.</p>
39.99	<p>The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T25N R26E S1 S6 S7 S12 R25E 1915.</p> <p>Add the marks 2002 to the brass cap.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>N. 0°01' W., bet. secs. 1 and 6.</p> <p>Over rolling land.</p>
40.03	<p>The 1/4 sec. cor. of secs. 1 and 6, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. 1/4 S1 S6 1915.</p> <p>Add the marks T25N R25E R26E 2002 to the brass cap.</p> <p>Cor. is located 2.30 chs. N. of a trail road, bears N. 10° E. and S. 10° W. and 1.70 chs. S. of the same trail road, bears S. 10° E. and N. 10° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°01' E., beginning new measurement.</p>
16.25	<p>Underground gas pipeline, bears N. 60° E. and S. 60° W.</p>
39.94	<p>The cor. of Tps. 25 and 26 N., Rs. 25 and 26 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. T26N S1 S6 S31 S36 R25E R26E T25N 1915.</p>

Dependent Resurvey of the West Boundary,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>Add the marks 2002 to the brass cap.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of the North Boundary, T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;">Restoring the survey executed by Frederick C. Miller, in 1915</p> <hr/> <p>From the cor. of Tps. 25 and 26 N., Rs. 26 and 27 E., hereinbefore described.</p> <p>N. 89°54' W., bet. secs. 1 and 36.</p> <p>Over rolling land.</p>												
39.99	<p>Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>T26N</td><td>R26E</td></tr> <tr><td></td><td>S36</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S 1</td></tr> <tr><td>T25N</td><td></td></tr> <tr><td>2002</td><td></td></tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T26N	R26E		S36	1/4	—		S 1	T25N		2002	
T26N	R26E												
	S36												
1/4	—												
	S 1												
T25N													
2002													
79.98	<p>Point for the cor. of secs. 1, 2, 35 and 36, at proportionate dist. A sandstone, 24 x 9 x 4 ins., lying loose nearby, mkd. with 5 grooves on up face and 1 groove on down face.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>T26N</td><td>R26E</td></tr> <tr><td>S35</td><td>S36</td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td>T25N</td><td></td></tr> <tr><td>2002</td><td></td></tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T26N	R26E	S35	S36	S 2	S 1	T25N		2002			
T26N	R26E												
S35	S36												
S 2	S 1												
T25N													
2002													

Dependent Resurvey of the North Boundary,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS													
	Bury the original stone alongside the stainless steel post.												
	<hr/>												
	N. 89°54' W., bet. secs. 2 and 35.												
	Over rolling land.												
39.99	Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate dist.; there is no remaining evidence of the original cor.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T26N</td><td>R26E</td></tr> <tr><td></td><td>S35</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S 2</td></tr> <tr><td>T25N</td><td></td></tr> <tr><td>2002</td><td></td></tr> </table>	T26N	R26E		S35	1/4	—		S 2	T25N		2002	
T26N	R26E												
	S35												
1/4	—												
	S 2												
T25N													
2002													
	Deposit a magnet in a white plastic case at the base of the stainless steel post.												
67.40	E. right-of-way fence of U. S. Highway No. 191, barbed wire, 5 strands, parallels highway.												
68.90	U. S. Highway No. 191, asphalt pavement, 25 ft. wide, bears S. 10° E. and N. 10° W.												
70.46	W. right-of-way fence of U. S. Highway No. 191, barbed wire, 5 strands, parallels highway.												
79.98	Point for the cor. of secs. 2, 3, 34 and 35, at proportionate dist. A sandstone, 22 x 10 x 7 ins., lying loose nearby, mkd. with 4 grooves on up face and 2 grooves on down face.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T26N</td><td>R26E</td></tr> <tr><td>S34</td><td>S35</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td>T25N</td><td></td></tr> <tr><td>2002</td><td></td></tr> </table>	T26N	R26E	S34	S35	S 3	S 2	T25N		2002			
T26N	R26E												
S34	S35												
S 3	S 2												
T25N													
2002													
	Deposit a magnet in a white plastic case at the base of the stainless steel post.												
	Bury the original stone alongside the stainless steel post.												
	<hr/>												
	N. 89°54' W., bet. secs. 3 and 34.												

Dependent Resurvey of the North Boundary,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS													
39.99	<p>Over rolling land.</p> <p>The 1/4 sec. cor. of secs. 3 and 34, determined from the remaining original bearing tree</p> <p style="padding-left: 40px;">A forked piñon, 16 ins. diam., bears S. 89° W., 32 lks. dist., mkd. 1/4 S3 BT on open blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 10px;">T26N</td> <td style="padding: 0 10px;">R26E</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">S34</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="border-top: 1px solid black; padding: 0 10px;">—</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">S 3</td> </tr> <tr> <td style="padding: 0 10px;">T25N</td> <td></td> </tr> <tr> <td style="padding: 0 10px;">2002</td> <td></td> </tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 89°58' W., beginning new measurement.</p>	T26N	R26E		S34	1/4	—		S 3	T25N		2002	
T26N	R26E												
	S34												
1/4	—												
	S 3												
T25N													
2002													
39.95	<p>The cor. of secs. 3, 4, 33 and 34, monumented with a broken sandstone, 16 x 6 x 5 ins., with top missing, firmly set, projecting 2 ins. above ground, mkd. with 1 groove on E. face and 1 groove on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 10px;">T26N</td> <td style="padding: 0 10px;">R26E</td> </tr> <tr> <td style="padding: 0 10px;">S33</td> <td style="padding: 0 10px;">S34</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 10px;">S 4</td> <td style="padding: 0 10px;">S 3</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">T25N</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">2002</td> </tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 89°57' W., bet. secs. 4 and 33.</p> <p>Over rolling land.</p>	T26N	R26E	S33	S34	S 4	S 3		T25N		2002		
T26N	R26E												
S33	S34												
S 4	S 3												
	T25N												
	2002												

Dependent Resurvey of the North Boundary,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
39.99	<p>The 1/4 sec. cor. of secs. 4 and 33, monumented with a bent iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. 1/4 S4 S33 1915.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R26E S33 1/4 ——— S 4 T25N 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the iron post alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/>										
39.97	<p>The cor. of secs. 4, 5, 32 and 33, monumented with a sandstone 21 x 8 x 8 ins., firmly set, projecting 11 ins. above ground, mkd. with 4 grooves on E. face and 2 grooves on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1" style="margin: auto;"> <tr> <td>T26N</td> <td>R26E</td> </tr> <tr> <td>S32</td> <td>S33</td> </tr> <tr> <td>S 5</td> <td>S 4</td> </tr> <tr> <td colspan="2">T25N</td> </tr> <tr> <td colspan="2">2002</td> </tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/>	T26N	R26E	S32	S33	S 5	S 4	T25N		2002	
T26N	R26E										
S32	S33										
S 5	S 4										
T25N											
2002											
	<p>N. 89°59' W., beginning new measurement.</p>										
	<p>Over rolling land.</p>										
28.80	<p>Underground gas pipeline, bears N. 80° E. and S. 80° W.</p>										
33.90	<p>High voltage transmission line, bears N. 40° E. and S. 40° W.</p>										

Dependent Resurvey of the North Boundary,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.98	<p>The 1/4 sec. cor. of secs. 5 and 32, monumented with an iron post, 1 in. diam., loosely set, projecting 12 ins. above ground, with brass cap mkd. 1/4 S5 S32 1915.</p> <p>At the corner point</p> <p>Reset the iron post 29 ins. in the ground.</p> <p>Deposit a magnet in a white plastic case at the base of the iron post.</p> <p>Add the marks T26N R26E T25N 2002 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°58' W., beginning new measurement.</p>
40.04	<p>The cor. of secs. 5, 6, 31 and 32, monumented with an iron post, 3 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. T26N R26E S5 S6 S31 S32 T25N 1915, from which the original bearing trees</p> <p style="padding-left: 40px;">A juniper, 30 ins. diam., bears N. 77° E., 82 lks. dist., with illegible scribe marks on partially healed blaze.</p> <p style="padding-left: 40px;">A forked piñon, 19 ins. diam., bears S. 14 1/2° E., 89 lks. dist., mkd. T25N R26E S5 BT on open blaze. (Record: S. 13° E.)</p> <p style="padding-left: 40px;">A forked juniper, 13 ins. diam. at base, bears S. 29 3/4° W., 1.30 chs. dist., mkd. T25N R26E S6 BT on open blaze on the southerly fork. (Record: S. 30 1/2° W., 132 lks.)</p> <p>Add the marks 2002 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°58' W., bet. secs. 6 and 31.</p> <p>Over rolling land.</p>
39.90	<p>The 1/4 sec. cor. of secs. 6 and 31, monumented with a bent iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. 1/4 S1 S6 1915.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the North Boundary,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T26N R26E S31 1/4 ——— S 6 T25N 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Bury the iron post alongside the stainless steel post. <hr style="width: 20%; margin: auto;"/> N. 89°56' W., beginning new measurement.
39.48	The cor. of Tps. 25 and 26 N., Rs. 25 and 26 E., hereinbefore described. <hr style="width: 80%; margin: auto;"/> <div style="text-align: center;"> Survey of the Subdivisional Lines, T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona </div> <hr style="width: 80%; margin: auto;"/> From the stan. cor. of secs. 35 and 36, on the S. bdy. of the Tp., hereinbefore described. N. 0°04' E., bet. secs. 35 and 36. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 35 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T25N R26E 1/4 S35 S36 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Cor. is located 1.00 ch. N. of a trail road, bears N. 70° E. and S. 70° W.
80.00	Point for the cor. of secs. 25, 26, 35 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS											
	<table border="1"> <tr> <td>T25N</td> <td>R26E</td> </tr> <tr> <td>S26</td> <td>S25</td> </tr> <tr> <td>S35</td> <td>S36</td> </tr> <tr> <td colspan="2">2002</td> </tr> </table>	T25N	R26E	S26	S25	S35	S36	2002			
T25N	R26E										
S26	S25										
S35	S36										
2002											
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°58' W., bet. secs. 25 and 36.</p> <p>Over rolling land.</p>										
39.92	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										
	<table border="1"> <tr> <td>T25N</td> <td>R26E</td> </tr> <tr> <td></td> <td>S25</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S36</td> </tr> <tr> <td colspan="2">2002</td> </tr> </table>	T25N	R26E		S25	1/4	—		S36	2002	
T25N	R26E										
	S25										
1/4	—										
	S36										
2002											
79.84	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 0°04' E., bet. secs. 25 and 26.</p> <p>Over rolling land.</p>										
7.70	Underground gas pipeline, bears N. 80° E. and S. 80° W.										
13.88	Asphalt paved road, 16 ft. wide, bears N. 80° E. and S. 80° W.										
40.00	Point for the 1/4 sec. cor. of secs. 25 and 26.										

**Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R26E 1/4 S26 S25 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
53.40	Navajo Route 203, a graded road, 25 ft. wide, bears N. 40° E. and S. 40° W.
80.00	<p>Point for the cor. of secs. 23, 24, 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R26E S23 S24 S26 S25 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet secs. 24 and 25.</p> <p>Over rolling land.</p>
39.94	<p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R26E S24 1/4 ——— S25 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS									
58.70	Navajo Route 203, a graded road, 22 ft. wide, bears N. 40° E. and S. 40° W.								
79.88	The cor. of secs. 23, 24, 25 and 26. Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.								
	N. 0°04' E., bet. secs. 23 and 24. Over rolling land.								
22.10	A graded road, 14 ft. wide, bears N. 40° E. and S. 40° W.								
40.00	Point for the 1/4 sec. cor. of secs. 23 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T25N</td><td>R26E</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S23</td><td> S24</td></tr> <tr><td>2002</td><td></td></tr> </table> </div>	T25N	R26E	1/4		S23	S24	2002	
T25N	R26E								
1/4									
S23	S24								
2002									
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Cor. is located 2.60 chs. W. of a graded road, 12 ft. wide, bears S. 20° E. and N. 20° W.								
48.70	A graded road, 12 ft. wide, bears S. 10° E. and N. 10° W.								
80.00	Point for the cor. of secs. 13, 14, 23 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T25N</td><td>R26E</td></tr> <tr><td>S14</td><td> S13</td></tr> <tr><td>S23</td><td> S24</td></tr> <tr><td>2002</td><td></td></tr> </table> </div>	T25N	R26E	S14	S13	S23	S24	2002	
T25N	R26E								
S14	S13								
S23	S24								
2002									
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Cor. is located 1.30 chs. N. of a trail road, bears N. 30° E. and S. 30° W., and 90 lks. W. of the same trail road, bears N. 40° E. and S. 40° W.								

Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°59' W., bet. secs. 13 and 24.</p> <p>Over rolling land.</p>
39.91	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R26E S13 1/4 ——— S24 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.82	<p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 0°04' E., bet. secs. 13 and 14.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R26E 1/4 S14 S13 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 11, 12, 13 and 14.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS											
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T25N</td> <td>R26E</td> </tr> <tr> <td>S11</td> <td>S12</td> </tr> <tr> <td>S14</td> <td>S13</td> </tr> <tr> <td colspan="2" style="text-align: center;">2002</td> </tr> </table> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°59' W., bet. secs. 12 and 13.</p> <p>Over rolling land.</p>	T25N	R26E	S11	S12	S14	S13	2002			
T25N	R26E										
S11	S12										
S14	S13										
2002											
39.91	<p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T25N</td> <td>R26E</td> </tr> <tr> <td></td> <td>S12</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S13</td> </tr> <tr> <td colspan="2" style="text-align: center;">2002</td> </tr> </table> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T25N	R26E		S12	1/4	—		S13	2002	
T25N	R26E										
	S12										
1/4	—										
	S13										
2002											
79.82	<p>The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 0°04' E., bet. secs. 11 and 12.</p> <p>Over rolling land.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p>										

**Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R26E 1/4 S11 S12 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R26E S 2 S 1 ----- S11 S12 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°55' W., bet. secs. 1 and 12.</p> <p>Over rolling land.</p>
39.89	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R26E S 1 1/4 ——— S12 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.78	<p>The cor. of secs. 1, 2, 11 and 12.</p>

Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 0°07' W., bet. secs. 1 and 2.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R26E 1/4 S 2 S 1 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.97	<p>The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the stan. cor. of secs. 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°03' E., bet. secs. 34 and 35.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R26E 1/4 S34 S35 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
62.60	<p>Underground gas pipeline, bears N. 70° E. and S. 70° W.</p>

Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
80.00	<p>Point for the cor. of secs. 26, 27, 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T25N</td> <td style="padding: 0 5px;">R26E</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S27</td> <td style="padding: 0 5px;">S26</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S34</td> <td style="padding: 0 5px;">S35</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">2002</td> </tr> </table> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr style="width: 50%; margin-left: auto; margin-right: auto;"/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 89°55' W., bet. secs. 26 and 35.</p>	T25N	R26E	S27	S26	S34	S35	2002			
T25N	R26E										
S27	S26										
S34	S35										
2002											
14.30	E. right-of-way fence of U. S. Highway No. 191, barbed wire, 5 strands, parallels highway.										
15.80	U. S. Highway No. 191, asphalt surfaced, 35 ft. wide, bears S. 10° E. and N. 10° W.										
17.34	W. right-of-way fence of U. S. Highway No. 191, barbed wire, 5 strands, parallels highway.										
17.60	Underground water line, bears S. 10° E. and N. 10° W.										
24.30	Underground gas pipeline, bears N. 70° E. and S. 70° W.										
39.91	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T25N</td> <td style="padding: 0 5px;">R26E</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S26</td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="padding: 0 5px;">—</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S35</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">2002</td> </tr> </table> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T25N	R26E		S26	1/4	—		S35	2002	
T25N	R26E										
	S26										
1/4	—										
	S35										
2002											
79.82	The cor. of secs. 26, 27, 34 and 35.										

Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 0°03' E., bet. secs. 26 and 27.</p> <p>Over rolling land.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T25N</td> <td style="padding: 0 10px;">R26E</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">1/4</td> </tr> <tr> <td style="padding: 0 10px;">S27</td> <td style="padding: 0 10px;"> S26</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">2002</td> </tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T25N	R26E		1/4	S27	S26		2002
T25N	R26E								
	1/4								
S27	S26								
	2002								
80.00	<p>Point for the cor. of secs. 22, 23, 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T25N</td> <td style="padding: 0 10px;">R26E</td> </tr> <tr> <td style="padding: 0 10px;">S22</td> <td style="padding: 0 10px;"> S23</td> </tr> <tr> <td style="padding: 0 10px;">S27</td> <td style="padding: 0 10px;"> S26</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">2002</td> </tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89°55' W., bet. secs. 23 and 26.</p> <p>Over rolling land.</p>	T25N	R26E	S22	S23	S27	S26		2002
T25N	R26E								
S22	S23								
S27	S26								
	2002								
24.99	<p>E. right-of-way fence of U. S. Highway No. 191, barbed wire, 5 strands, parallels highway.</p>								
26.45	<p>U. S. Highway No. 191, asphalt surfaced, 35 ft. wide, bears S. 10° E. and N. 10° W.</p>								

**Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS											
28.01	W. right-of-way fence of U. S. Highway No. 191, barbed wire, 5 strands, parallels highway.										
28.40	Underground water line, bears S. 10° E. and N. 10° W.										
39.91	Point for the 1/4 sec. cor. of secs. 23 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T25N</td><td>R26E</td></tr> <tr><td></td><td>S23</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S26</td></tr> <tr><td></td><td>2002</td></tr> </table> </div>	T25N	R26E		S23	1/4	—		S26		2002
T25N	R26E										
	S23										
1/4	—										
	S26										
	2002										
79.82	Deposit a magnet in a white plastic case at the base of the stainless steel post. The cor. of secs. 22, 23, 26 and 27. Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses. <hr/>										
	N. 0°03' E., bet. secs. 22 and 23. Over rolling land.										
40.00	Point for the 1/4 sec. cor. of secs. 22 and 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T25N</td><td>R26E</td></tr> <tr><td></td><td>1/4</td></tr> <tr><td>S22</td><td> S23</td></tr> <tr><td></td><td>2002</td></tr> </table> </div>	T25N	R26E		1/4	S22	S23		2002		
T25N	R26E										
	1/4										
S22	S23										
	2002										
	Deposit a magnet in a white plastic case at the base of the stainless steel post.										
80.00	Point for the cor. of secs. 14, 15, 22 and 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T25N</td><td>R26E</td></tr> <tr><td>S15</td><td> S14</td></tr> <tr><td>S22</td><td> S23</td></tr> <tr><td></td><td>2002</td></tr> </table> </div>	T25N	R26E	S15	S14	S22	S23		2002		
T25N	R26E										
S15	S14										
S22	S23										
	2002										

**Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.40 chs. S. of a trail road, bears S. 50° E. and N. 50° W.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89°55' W., bet. secs. 14 and 23.</p>
3.20	A graded road, 12 ft. wide, bears N. and S.
35.63	E. right-of-way fence of U. S. Highway No. 191, barbed wire, 5 strands, parallels highway.
37.15	U. S. Highway No. 191, asphalt surfaced, 35 ft. wide, bears S. 10° E. and N. 10° W.
38.68	W. right-of-way fence of U. S. Highway No. 191, barbed wire, 5 strands, parallels highway.
38.95	Underground water line, bears S. 10° E. and N. 10° W.
39.91	Point for the 1/4 sec. cor. of secs. 14 and 23.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T25N R26E S14 1/4 ——— S23 2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.82	<p>The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 0°03' E., bet. secs. 14 and 15.</p>

Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	Over rolling land.										
40.00	Point for the 1/4 sec. cor. of secs. 14 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table> <tr><td>T25N</td><td>R26E</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S15</td><td> S14</td></tr> <tr><td>2002</td><td></td></tr> </table> </div>	T25N	R26E	1/4		S15	S14	2002			
T25N	R26E										
1/4											
S15	S14										
2002											
	Deposit a magnet in a white plastic case at the base of the stainless steel post.										
80.00	Point for the cor. of secs. 10, 11, 14 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table> <tr><td>T25N</td><td>R26E</td></tr> <tr><td>S10</td><td> S11</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S15</td><td> S14</td></tr> <tr><td>2002</td><td></td></tr> </table> </div>	T25N	R26E	S10	S11	<hr/>		S15	S14	2002	
T25N	R26E										
S10	S11										
<hr/>											
S15	S14										
2002											
	Deposit a magnet in a white plastic case at the base of the stainless steel post.										
	Cor. is located 20 lks. N. of a trail road, bears N. 60° E. and S. 60° W.										
	Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.										
	<hr/>										
	From the cor. of secs. 11, 12, 13 and 14. S. 89°55' W., bet. secs. 11 and 14.										
	Over rolling land.										
39.91	Point for the 1/4 sec. cor. of secs. 11 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table> <tr><td>T25N</td><td>R26E</td></tr> <tr><td>S11</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S14</td><td></td></tr> <tr><td>2002</td><td></td></tr> </table> </div>	T25N	R26E	S11		1/4	—	S14		2002	
T25N	R26E										
S11											
1/4	—										
S14											
2002											

**Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 2.10 chs. E. of a trail road, bears S. 20° E. and N. 20° W.</p>
46.28	E. right-of-way fence of U. S. Highway No. 191, barbed wire, 5 strands, parallels highway.
47.80	U. S. Highway No. 191, asphalt surfaced, 35 ft. wide, bears S. 10° E. and N. 10° W.
49.35	W. right-of-way fence of U. S. Highway No. 191, barbed wire, 5 strands, parallels highway.
79.82	<p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 0°03' E., bet. secs. 10 and 11.</p> <p>Over rolling and broken land.</p>
15.80	Navajo Route 9205, a graded road, 26 ft. wide, bears E. and W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R26E 1/4 S10 S11 2002</p> </div>
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 2, 3, 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R26E S 3 S 2 S10 S11 2002</p> </div>

Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 89°55' W., bet. secs. 2 and 11.</p> <p>Over rolling and broken land.</p>
39.91	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R26E S 2 1/4 ——— S11 2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
56.98	<p>E. right-of-way fence of U. S. Highway No. 191, barbed wire, 5 strands, parallels highway.</p>
58.45	<p>U. S. Highway No. 191, asphalt surfaced, 35 ft. wide, bears S. 10° E. and N. 10° W.</p>
60.00	<p>W. right-of-way fence of U. S. Highway No. 191, barbed wire, 5 strands, parallels highway.</p>
79.82	<p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/>
40.00	<p>N. 0°14' W., bet. secs. 2 and 3.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p>

Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R26E 1/4 S 3 S 2 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.24	<p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the stan. cor. of secs. 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°03' E., bet. secs. 33 and 34.</p>
36.80	Underground gas pipeline, bears N. 70° E. and S. 70° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R26E 1/4 S33 S34 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 2.40 chs. N. of a trail road, bears N. 70° E. and S. 70° W.</p>
80.00	<p>Point for the cor. of secs. 27, 28, 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R26E S28 S27 S33 S34 2002</p>

Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°53' W., bet. secs. 27 and 34.</p> <p>Over rolling land.</p>
40.17	<p>Point for the 1/4 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R26E S27 1/4 ——— S34 2002</p>
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 27, 28, 33 and 34.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 0°03' E., bet. secs. 27 and 28.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R26E 1/4 S28 S27 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
80.00	<p>Point for the cor. of secs. 21, 22, 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">T25N</td> <td style="text-align: center;">R26E</td> </tr> <tr> <td style="text-align: center;">S21</td> <td style="text-align: center;">S22</td> </tr> <tr> <td style="text-align: center;">S28</td> <td style="text-align: center;">S27</td> </tr> <tr> <td colspan="2" style="text-align: center;">2002</td> </tr> </table> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 89°53' W., bet. secs. 22 and 27.</p> <p>Over rolling land.</p>	T25N	R26E	S21	S22	S28	S27	2002			
T25N	R26E										
S21	S22										
S28	S27										
2002											
40.17	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">T25N</td> <td style="text-align: center;">R26E</td> </tr> <tr> <td></td> <td style="text-align: center;">S22</td> </tr> <tr> <td style="text-align: center;">1/4</td> <td style="text-align: center;">—</td> </tr> <tr> <td></td> <td style="text-align: center;">S27</td> </tr> <tr> <td colspan="2" style="text-align: center;">2002</td> </tr> </table> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T25N	R26E		S22	1/4	—		S27	2002	
T25N	R26E										
	S22										
1/4	—										
	S27										
2002											
80.34	<p>The cor. of secs. 21, 22, 27 and 28.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 0°03' E., bet. secs. 21 and 22.</p> <p>Over rolling land.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p>										

Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R26E 1/4 S21 S22 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 15, 16, 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R26E S16 S15 ----- S21 S22 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 50 lks. N. of a trail road, bears N. 70° E. and S. 70° W.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 89°53' W., bet. secs. 15 and 22.</p> <p>Over rolling land.</p>
40.17	<p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R26E S15 1/4 ——— S22 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.34	<p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 0°03' E., bet. secs. 15 and 16.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R26E 1/4 S16 S15 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 9, 10, 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R26E S 9 S10 S16 S15 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 89°53' W., bet. secs. 10 and 15.</p>
40.17	<p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T25N R26E S10 1/4 ——— S15 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.34	The cor. of secs. 9, 10, 15 and 16.
	Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.

	N. 0°03' E., bet. secs. 9 and 10.
	Over rolling and broken land.
9.30	Navajo Route 9205, a graded road, 26 ft. wide, bears E. and W.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T25N R26E 1/4 S 9 S10 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 3, 4, 9 and 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T25N R26E S 4 S 3 ——— S 9 S10 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located 50 lks. S. of a trail road, bears N. 20° E. and S. 20° W.

Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11. N. 89°53' W., bet. secs. 3 and 10. Over rolling and broken land.</p>
40.17	<p>Point for the 1/4 sec. cor. of secs. 3 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R26E S 3 1/4 ——— S10 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.34	<p>The cor. of secs. 3, 4, 9 and 10. Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 0°03' E., bet. secs. 3 and 4. Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R26E 1/4 S 4 S 3 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.17	<p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described.</p>

Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the stan. cor. of secs. 32 and 33, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°02' E., bet. secs. 32 and 33.</p> <p>Over rolling land.</p>								
11.60	Underground gas pipeline, bears N. 70° E. and S. 70° W.								
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T25N</td><td>R26E</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S32</td><td> S33</td></tr> <tr><td>2002</td><td></td></tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T25N	R26E	1/4		S32	S33	2002	
T25N	R26E								
1/4									
S32	S33								
2002									
80.00	<p>Point for the cor. of secs. 28, 29, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T25N</td><td>R26E</td></tr> <tr><td>S29</td><td> S28</td></tr> <tr><td>S32</td><td> S33</td></tr> <tr><td>2002</td><td></td></tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 89°58' W., bet. secs. 28 and 33.</p> <p>Over rolling land.</p>	T25N	R26E	S29	S28	S32	S33	2002	
T25N	R26E								
S29	S28								
S32	S33								
2002									

**Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS											
39.82	<p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T25N</td><td>R26E</td></tr> <tr><td></td><td>S28</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S33</td></tr> <tr><td></td><td>2002</td></tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T25N	R26E		S28	1/4	—		S33		2002
T25N	R26E										
	S28										
1/4	—										
	S33										
	2002										
79.64	<p>The cor. of secs. 28, 29, 32 and 33.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 0°02' E., bet. secs. 28 and 29.</p> <p>Over rolling land.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T25N</td><td>R26E</td></tr> <tr><td></td><td>1/4</td></tr> <tr><td>S29</td><td> S28</td></tr> <tr><td></td><td>2002</td></tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T25N	R26E		1/4	S29	S28		2002		
T25N	R26E										
	1/4										
S29	S28										
	2002										
80.00	<p>Point for the cor. of secs. 20, 21, 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T25N</td><td>R26E</td></tr> <tr><td>S20</td><td> S21</td></tr> <tr><td>S29</td><td> S28</td></tr> <tr><td></td><td>2002</td></tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T25N	R26E	S20	S21	S29	S28		2002		
T25N	R26E										
S20	S21										
S29	S28										
	2002										

Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28. N. 89°58' W., bet. secs. 21 and 28. Over rolling land.</p>
39.82	<p>Point for the 1/4 sec. cor. of secs. 21 and 28. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R26E S21 1/4 ——— S28 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.64	<p>The cor. of secs. 20, 21, 28 and 29. Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 0°02' E., bet. secs. 20 and 21. Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R26E 1/4 S20 S21 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 16, 17, 20 and 21.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T25N</td> <td style="padding: 0 10px;">R26E</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S17</td> <td style="padding: 0 10px;">S16</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S20</td> <td style="padding: 0 10px;">S21</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">2002</td> </tr> </table> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22. N. 89°58' W., bet. secs. 16 and 21. Over rolling land.</p>	T25N	R26E	S17	S16	S20	S21	2002	
T25N	R26E								
S17	S16								
S20	S21								
2002									
39.82	<p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T25N</td> <td style="padding: 0 10px;">R26E</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S16</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="padding: 0 10px; border-top: 1px solid black;">S21</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">2002</td> </tr> </table> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T25N	R26E		S16	1/4	S21	2002	
T25N	R26E								
	S16								
1/4	S21								
2002									
79.64	<p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 0°02' E., bet. secs. 16 and 17. Over rolling land.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								

Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T25N R26E 1/4 S17 S16 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 8, 9, 16 and 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T25N R26E S 8 S 9 --- --- S17 S16 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	From this cor. point, U. S. Geodetic Survey triangulation station "HOOVER 1972", bears N. 8°22' E., 18.78 chs. dist., monumented with a standard aluminum tablet, 3 1/2 ins. diam., cemented flush in a concrete block, 7 ins. sq., firmly set, projecting 5 ins. above ground, with top mkd. HOOVER 1972 and a triangle.
	Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.
	<hr/>
	From the cor. of secs. 9, 10, 15 and 16.
	N. 89°58' W., bet. secs. 9 and 16.
	Over rolling land.
39.82	Point for the 1/4 sec. cor. of secs. 9 and 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T25N R26E S 9 1/4 ——— S16 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS									
79.64	<p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 0°02' E., bet. secs. 8 and 9.</p> <p>Over rolling and broken land.</p>								
17.00	Navajo Route 9205, a graded road, 25 ft. wide, bears N. 80° E. and S. 80° W.								
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T25N</td><td>R26E</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S 8</td><td> S 9</td></tr> <tr><td>2002</td><td></td></tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T25N	R26E	1/4		S 8	S 9	2002	
T25N	R26E								
1/4									
S 8	S 9								
2002									
80.00	<p>Point for the cor. of secs. 4, 5, 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T25N</td><td>R26E</td></tr> <tr><td>S 5</td><td> S 4</td></tr> <tr><td>S 8</td><td> S 9</td></tr> <tr><td>2002</td><td></td></tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 89°58' W., bet. secs. 4 and 9.</p> <p>Over rolling and broken land.</p>	T25N	R26E	S 5	S 4	S 8	S 9	2002	
T25N	R26E								
S 5	S 4								
S 8	S 9								
2002									

Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.82	<p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R26E S 4 1/4 ——— S 9 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.64	<p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 0°12' W., bet. secs. 4 and 5.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R26E 1/4 S 5 S 4 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.10 chs. S. of a wash, 5 ft. wide, 4 ft. deep, drains S. 50° W.</p>
80.18	<p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the stan. cor. of secs. 31 and 32, on the S. bdy. of the Tp., hereinbefore described.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS											
	<p>N. 0°01' E., bet. secs. 31 and 32.</p> <p>Over rolling land.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T25N</td><td>R26E</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S31</td><td> S32</td></tr> <tr><td colspan="2">2002</td></tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T25N	R26E	1/4		S31	S32	2002			
T25N	R26E										
1/4											
S31	S32										
2002											
80.00	<p>Point for the cor. of secs. 29, 30, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T25N</td><td>R26E</td></tr> <tr><td>S30</td><td> S29</td></tr> <tr><td>S31</td><td> S32</td></tr> <tr><td colspan="2">2002</td></tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 89°54' W., bet. 29 and 32.</p> <p>Over rolling land.</p>	T25N	R26E	S30	S29	S31	S32	2002			
T25N	R26E										
S30	S29										
S31	S32										
2002											
40.02	<p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T25N</td><td>R26E</td></tr> <tr><td>S29</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S32</td><td></td></tr> <tr><td colspan="2">2002</td></tr> </table> </div>	T25N	R26E	S29		1/4	—	S32		2002	
T25N	R26E										
S29											
1/4	—										
S32											
2002											

**Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.04	The cor. of secs. 29, 30, 31 and 32. Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.
	<hr/>
	N. 89°51' W., bet. secs. 30 and 31. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T25N R26E S30 1/4 ——— S31 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.97	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described. Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.
	<hr/>
	From the cor. of secs. 29, 30, 31 and 32. N. 0°01' E., bet. secs. 29 and 30. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T25N R26E 1/4 S30 S29 2002

**Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>										
80.00	<p>Point for the cor. of secs. 19, 20, 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 5px;">T25N</td> <td style="padding: 2px 5px;">R26E</td> </tr> <tr> <td style="padding: 2px 5px; border-right: 1px solid black;">S19</td> <td style="padding: 2px 5px;">S20</td> </tr> <tr> <td style="padding: 2px 5px; border-right: 1px solid black;">S30</td> <td style="padding: 2px 5px;">S29</td> </tr> <tr> <td colspan="2" style="padding: 2px 5px; text-align: center;">2002</td> </tr> </table> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>N. 89°54' W., bet. secs. 20 and 29.</p> <p>Over rolling land.</p>	T25N	R26E	S19	S20	S30	S29	2002			
T25N	R26E										
S19	S20										
S30	S29										
2002											
40.02	<p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 5px;">T25N</td> <td style="padding: 2px 5px;">R26E</td> </tr> <tr> <td></td> <td style="padding: 2px 5px;">S20</td> </tr> <tr> <td style="padding: 2px 5px;">1/4</td> <td style="padding: 2px 5px; border-top: 1px solid black;">———</td> </tr> <tr> <td></td> <td style="padding: 2px 5px;">S29</td> </tr> <tr> <td colspan="2" style="padding: 2px 5px; text-align: center;">2002</td> </tr> </table> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T25N	R26E		S20	1/4	———		S29	2002	
T25N	R26E										
	S20										
1/4	———										
	S29										
2002											
80.04	<p>The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 89°49' W., bet. secs. 19 and 30.</p> <p>Over rolling land.</p>										

Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T25N</td><td>R26E</td></tr> <tr><td></td><td>S19</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S30</td></tr> <tr><td></td><td>2002</td></tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T25N	R26E		S19	1/4	—		S30		2002
T25N	R26E										
	S19										
1/4	—										
	S30										
	2002										
79.90	<p>The cor. of secs. 19, 24, 25 and 30.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°01' E., bet. secs. 19 and 20.</p> <p>Over rolling land.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T25N</td><td>R26E</td></tr> <tr><td></td><td>1/4</td></tr> <tr><td>S19</td><td> S20</td></tr> <tr><td></td><td>2002</td></tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T25N	R26E		1/4	S19	S20		2002		
T25N	R26E										
	1/4										
S19	S20										
	2002										
80.00	<p>Point for the cor. of secs. 17, 18, 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T25N</td><td>R26E</td></tr> <tr><td>S18</td><td> S17</td></tr> <tr><td>S19</td><td> S20</td></tr> <tr><td></td><td>2002</td></tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T25N	R26E	S18	S17	S19	S20		2002		
T25N	R26E										
S18	S17										
S19	S20										
	2002										

Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21. N. 89°54' W., bet. secs. 17 and 20. Over rolling land.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 17 and 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R26E S17 1/4 ——— S20 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.04	<p>The cor. of secs. 17, 18, 19 and 20. Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 89°50' W., bet. secs. 18 and 19. Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 18 and 19. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R26E S18 1/4 ——— S19 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.66	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°01' E., bet. secs. 17 and 18.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R26E 1/4 S18 S17 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
58.80	<p>Navajo Route 9205, a graded road, 25 ft. wide, bears N. 60° E. and S. 60° W.</p>
80.00	<p>Point for the cor. of secs. 7, 8, 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R26E S 7 S 8 ----- S18 S17 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 89°54' W., bet. secs. 8 and 17.</p> <p>Over rolling land.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T25N R26E S 8 1/4 ——— S17 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 10 lks. W. of a power line, bears S. 30° E. and N. 30° W.</p>
48.30	<p>Navajo Route 9205, a graded road, 24 ft. wide, bears N. 60° E. and S. 60° W.</p>
80.04	<p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 89°51' W., bet. secs. 7 and 18.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T25N R26E S 7 1/4 ——— S18 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.66	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.
	Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.
	From the cor. of secs. 7, 8, 17 and 18.
	N. 0°01' E., bet. secs. 7 and 8.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of sec. 7 and 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T25N R26E 1/4 S 7 S 8 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 5, 6, 7 and 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T25N R26E S 6 S 5 ——— S 7 S 8 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9. N. 89°54' W., bet. secs. 5 and 8. Over rolling land.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R26E S 5 1/4 ——— S 8 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.04	<p>The cor. of secs. 5, 6, 7 and 8.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 89°52' W., bet. secs. 6 and 7. Over rolling land.</p>
27.70	<p>High voltage transmission line, bears N. 40° E. and S. 40° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R26E S 6 1/4 ——— S 7 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.67	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°12' W., bet. secs. 5 and 6.</p> <p>Over rolling land.</p>
30.10	High voltage transmission line, bears N. 40° E. and S. 40° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R26E 1/4 S 6 S 5 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
73.10	Underground gas pipeline, bears N. 80° E. and S. 80° W.
80.09	<p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/>

T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

The area surveyed is within the Navajo Indian Reservation, approximately 7 miles south of Ganado, Arizona and north of the community of Klagetoh, Arizona. The terrain is rolling with some areas of broken land in the north central and the southeastern portions along Wide Ruins Wash. Drainage is southerly in the southeast, with Wide Ruins Wash being the principal drainage. The southwest and central portions drain southwesterly and the north drains northerly into Sage Wash.

The elevation varies from 6400 to 6900 feet above sea level. The soil is mostly sand and sandy clay. There are heavy stands of piñon and juniper throughout the entire township. Undergrowth principally consists of sagebrush, rabbit brush, cacti and native grasses.

Principal access to the township is provided by U. S. Highway No. 191, which enters the township in section 35 and runs northerly and exits in section 2. Navajo Route 9205, begins at its junction with U. S. Highway No. 191 in section 11 and heads westerly and exits the township in section 18. There are some graded roads and trail roads throughout the township. Much of the area is used for livestock grazing. There are numerous permanent homesites throughout the entire township. There is no mining activity in the township.

The mean magnetic declination of $12\ 1/2^\circ$ E. was derived from the computer program GEOMAGIX, utilizing the World Magnetic Model for Epoch 2000 for the dates of survey.

CERTIFICATE OF SURVEY

I, Jones Curtiss, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the May 1, 2002. I have dependently resurveyed the Sixth Standard Parallel North (south boundary), the east, west and north boundaries, and surveyed the subdivisional lines of Township 25 North, Ranges 26 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

February 22, 2005
(Date)

Jones Curtiss
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the Sixth Standard Parallel North (south boundary), the east, west and north boundaries, and the survey of the subdivisional lines of Township 25 North, Ranges 26 East, of the Gila and Salt River Meridian, in the State of Arizona, executed by Jones Curtiss, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

MARCH 29, 2005
(Date)

Stephen K. Hansen
(Acting Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____~~
(Date)

~~_____~~
(Acting Chief Cadastral Surveyor of Arizona)