

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF THE
EAST AND WEST BOUNDARIES
AND
A PORTION OF THE SUBDIVISIONAL LINES,
AND THE SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 26 NORTH, RANGE 26 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA
EXECUTED BY
JONES CURTISS, Cadastral Surveyor

Under Special Instructions dated and approved May 1, 2002, which provided for the surveys included under Group No. 886, and assignment instructions dated May 1, 2002.

Survey commenced July 8, 2002

Survey completed August 19, 2002

T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of the east and west boundaries and a portion of the subdivisional lines, and the survey of a portion of the subdivisional lines, Township 26 North, Ranges 26 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

The east and west boundaries, and a portion of the subdivisional lines, certain meanders, and the subdivision of sections 5 and 6 were surveyed, and the north boundary was resurveyed by Frederick C. Miller in 1915. The north boundary was dependently resurveyed by Leonard R. Sandoval in 1990. The south boundary was dependently resurveyed by Jones Curtiss, in 2002, concurrently under this same group.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated May 1, 2002, for Group No. 886, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation Model 5700 receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey's Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) FLAGSTAFF, AZTEC, AND PIE TOWN VLBA. The NAD83(CORS96)(EPOCH:2002) geographic position of the southeast corner of the township is as follows:

Latitude: 35°36'16.52" N. Longitude: 109°30'25.62" W.

The mean magnetic declination is 12 1/2° E.

**Dependent Resurvey of the East Boundary,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS

Restoring the survey executed by
Frederick C. Miller, in 1915

NOTE: During the 1915 original survey of the E. bdy., the corners were designated to be common to Rs. 26 and 27 E. The tie, N. 89°35' E., 473.21 chs. dist., made to the corner of Tps. 26 N., Rs. 26 and 27 E. from the following corner during the dependent resurvey of the E. bdy. of T. 25 N., R. 26 E., executed concurrently under this same group, determined that the limits for rectangularity for alinement were exceeded for the corners to be utilized to control the subdivision of T. 26 N., R. 27 E. Therefore the corners on the E. bdy. will be redesignated to refer to corners in R. 26 E. only.

Beginning at the cor. of Tps. 25 and 26 N., R. 26 E. only, monumented with an iron post, 3 ins. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of the E. bdy., T. 25 N., R. 26 E., executed concurrently under this same group.

From this cor. point, second order U. S. Geological Survey triangulation station "HOOVER", bears S. 66°00' W., 346.97 chs. dist., monumented with a standard aluminum tablet, 3 1/2 ins. diam., cemented flush in a concrete block, 7 ins. square, firmly set, projecting 5 ins. above ground, with top mkd. HOOVER 1972 and a triangle.

North, on the E. bdy. of sec. 36.

Over rolling land.

39.98

Point for the 1/4 sec. cor. of secs. 31 and 36, now functions as the 1/4 sec. cor. of sec. 36 only, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 N
R 26 E R 27 E
1/4 |
S 36 |

2002

from which a bearing tree irreconcilable with record

A piñon, 13 ins. diam., bears N. 36 1/2° W., 10 lks. dist., mkd. 1/4 S36 BT, on open blaze

**Dependent Resurvey of the East Boundary,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
58.40	Underground gas pipeline, bears E. and W.								
79.96	The cor. of secs. 25, 30, 31 and 36, now functions as the cor. of secs. 25 and 36 only, monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap missing, from which the remains of an original bearing tree A dead piñon, 10 ins. diam., bears N. 56 1/2° W., 63 lks. dist., mkd. T26N R 6E S25 BT on partially healed blaze. (Record: 61 lks.) At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 26 N</td> <td style="border-left: 1px solid black; padding: 0 10px;">T 26 N</td> </tr> <tr> <td style="padding: 0 10px;">R 26 E</td> <td style="border-left: 1px solid black; padding: 0 10px;">R 27 E</td> </tr> <tr> <td style="padding: 0 10px;">S 25</td> <td style="border-left: 1px solid black; padding: 0 10px;"></td> </tr> <tr> <td style="padding: 0 10px;">S 36</td> <td style="border-left: 1px solid black; padding: 0 10px;">S 31</td> </tr> </table> 2002	T 26 N	T 26 N	R 26 E	R 27 E	S 25		S 36	S 31
T 26 N	T 26 N								
R 26 E	R 27 E								
S 25									
S 36	S 31								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Bury the iron post alongside the stainless steel post.								
	<hr/>								
	N. 0°02' W., on the E. bdy. of sec. 25.								
	Over rolling land.								
39.95	The 1/4 sec. cor. of secs. 25 and 30, now functions as the 1/4 sec. cor. of sec. 25 only, determined from the remaining original bearing tree A piñon, 11 ins. diam., bears S. 56 3/4° W., 40 lks. dist., with illegible marks on healing blaze. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								

**Dependent Resurvey of the East Boundary,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 26 N R 26 E R 27 E 1/4 S 25 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post. <hr style="width: 30%; margin: auto;"/> North, beginning new measurement.
39.98	The cor. of secs. 19, 24, 25 and 30, now functions as the cor. of secs. 24 and 25 only, monumented with an iron post, 3 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. T26N R26E R27E S24 S19 S25 S30 1915. Remark the brass cap to read
	T 26 N T 26 N R 26 E R 27 E S 24 S 25 S 30
	2002 1915
	Deposit a magnet in a white plastic case at the base of the stainless steel post. <hr style="width: 30%; margin: auto;"/> N. 0°04' E., on the E. bdy. of sec. 24. Over rolling land.
39.97	The 1/4 sec. cor. of secs. 19 and 24, now functions as the 1/4 sec. cor. of sec. 24 only, monumented with a bent iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd. 1/4 S24 S19 1915, from which the remaining original bearing tree A forked juniper, 12 ins. diam., bears S. 38 1/4° E., 41 lks. dist., mkd. 1/4 S19 BT, on open blaze. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the East Boundary,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 26 N
R 26 E R 27 E
1/4 |
S 24 |

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Bury the iron post alongside the stainless steel post.

N. 0°10' E., beginning new measurement.

40.00

The cor. of secs. 13, 18, 19 and 24, now functions as the cor. of secs. 13 and 24 only, monumented with a bent iron post, 3 ins. diam., loosely set, projecting 16 ins. above ground, with brass cap mkd. T26N R26E R27E S13 S18 S24 S19 1915, from which the remaining original bearing trees

A forked juniper, 19 ins. diam., bears N. 76 1/2° E., 75 lks. dist., with illegible marks on partially decayed blaze.

A forked juniper, 14 ins. diam., bears S. 70 3/4° W., 11 lks. dist., with a healed blaze.

A forked piñon, 10 ins. diam., bears N. 34 1/2° W., 33.5 lks. dist., with illegible marks on open blaze.
(Record: N. 31 3/4° E., 36 lks.)

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 N
R 26 E R 27 E
S 13 |
S 24 | S 19

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Bury the iron post alongside the stainless steel post.

N. 0°01' E., on the E. bdy. of sec. 13.

**Dependent Resurvey of the East Boundary,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS											
	Over rolling and broken land.										
39.99	<p>The 1/4 sec. cor. of secs. 13 and 18, now functions as the 1/4 sec. cor. of sec. 13 only, determined from the remaining bearing tree</p> <p style="padding-left: 40px;">A piñon, 8 ins. diam., bears N. 87° W., 31 lks. dist., mkd., 1/4 S13 BT, on open blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 26 N</td><td></td></tr> <tr><td>R 26 E</td><td>R 27 E</td></tr> <tr><td>1/4 </td><td></td></tr> <tr><td>S 13 </td><td></td></tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>North, beginning new measurement.</p>	T 26 N		R 26 E	R 27 E	1/4		S 13			
T 26 N											
R 26 E	R 27 E										
1/4											
S 13											
18.20	Power line, bears ESE and WNW.										
39.87	<p>The cor. of secs. 7, 12, 13 and 18, now functions as the cor. of secs. 12 and 13 only, monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd., T26N R26E R27E S12 S7 S13 S18 1915, from which the remaining original bearing trees</p> <p style="padding-left: 40px;">A dead piñon, 15 ins. diam., bears S. 39 3/4° W., 16 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A dead piñon, 9 ins. diam., bears S. 36 3/4° W., 22 lks. dist., mkd. T26N R26E S13 BT on open blaze.</p> <p>Remark the brass cap to read</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 26 N</td><td>T 27 N</td></tr> <tr><td>R 26 E</td><td>R 27 E</td></tr> <tr><td>S 12</td><td> </td></tr> <tr><td colspan="2"><hr style="width: 10%; margin: 0 auto;"/></td></tr> <tr><td>S 13</td><td>S 18</td></tr> </table> <p>2002 1915</p> </div>	T 26 N	T 27 N	R 26 E	R 27 E	S 12		<hr style="width: 10%; margin: 0 auto;"/>		S 13	S 18
T 26 N	T 27 N										
R 26 E	R 27 E										
S 12											
<hr style="width: 10%; margin: 0 auto;"/>											
S 13	S 18										

**Dependent Resurvey of the East Boundary,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 0°02' W., on the E. bdy. of sec. 12.</p> <p>Over rolling land.</p>
39.995	<p>Point for the 1/4 sec. cor. of secs. 7 and 12, now functions as the 1/4 sec. cor. of sec. 12 only, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> T 26 N R 26 E R 27 E 1/4 S 12 </p> <p align="center">2002</p>
65.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>High voltage transmission line, bears NE and SW.</p>
79.99	<p>The cor. of secs. 1, 6, 7 and 12, now functions as the cor. of secs. 1 and 12 only, monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. T26N R26E R27E S1 S6 S12 S7 1915.</p> <p>Remark the brass cap to read</p> <p align="center"> T 26 N T 26 N R 26 E R 27 E S 1 S 12 S 7 </p> <p align="center">2002 1915</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 75 lks. N. of a graded road, 25 ft. wide, bears SSE and NNW.</p> <hr/> <p>N. 0°01' W., on the E. bdy. of sec. 1.</p> <p>Over rolling land.</p>

**Dependent Resurvey of the East Boundary,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>40.005 Point for the 1/4 sec. cor. of secs. 1 and 6, now functions as the 1/4 sec. cor. of sec. 1 only, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 26 N R 26 E R 27 E 1/4 S 1 2002 </p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>76.50 High voltage transmission line, bears NE and SW.</p> <p>80.01 The cor. of Tps. 26 and 27 N., Rs. 26 and 27 E., now functions as the cor. of Tps. 26 and 27 N., R. 26 E. only, monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd., T27N R26E R27E S36 S31 S6 S1 T26N 1915 1990.</p> <p>Remark the brass cap to read</p> <p style="text-align: center;"> T 27 N T 26 N R 26 E R 27 E S 36 S 1 S 6 T 26 N 1990 1915 2002 </p> <hr/> <p align="center">Dependent Resurvey of the West Boundary, T. 26 N., R. 26 E., Gila and Salt River, Meridian, Arizona</p> <hr/> <p align="center">Restoring the survey executed by Frederick C. Miller, in 1915</p> <hr/> <p>From the cor. of Tps. 25 and 26 N., Rs. 25 and 26 E., monumented with an iron post, 3 ins. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of the W. bdy., T. 25 N., R. 26 E., executed concurrently under this same group.</p> <p>N. 0°02' E., bet. secs. 31 and 36.</p>
--------	--

**Dependent Resurvey of the West Boundary,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
39.95	<p>Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N 1/4 R 25 E R 26 E S 36 S 31</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.90	<p>The cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. T26N S25 S30 S36 S31 R25E R26E 1915, from which the remaining original bearing trees</p> <p style="padding-left: 40px;">A dead piñon, 8 ins. diam., bears N. 43° E., 1.61 chs. dist., mkd. T26N R26E S30 BT on partially healed blaze. (Record: 168 lks.)</p> <p style="padding-left: 40px;">A piñon, 7 ins. diam., bears S. 39 1/4° W., 91 lks. dist., mkd. T26N R26E S36 BT on partially healed blaze. (Record: S. 40 3/4° W.)</p> <p style="padding-left: 40px;">A piñon, 11 ins. diam., bears N. 6° W., 1.01 chs. dist., mkd. T26N R26E S25 BT on partially healed blaze.</p> <hr/> <p>N. 0°01' W., bet. secs. 25 and 30.</p> <p>Over rolling land.</p>
39.99	<p>The 1/4 sec. cor. of secs. 25 and 30, monumented with a bent iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd. 1/4 S25 S30 1915.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the West Boundary,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 26 N 1/4 R 25 E R 26 E S 25 S 30 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Bury the iron post alongside the stainless steel post. <hr style="width: 20%; margin: auto;"/> N. 0°01' E., beginning new measurement.
6.60	High voltage transmission line, bears NE and SW.
39.99	The cor. of secs. 19, 24, 25 and 30, monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. T26N S24 S19 S25 S30 R25E R26E 1915, from which the remaining original bearing tree A forked juniper, 18 ins. diam., bears S. 57° W., 81.5 lks. dist., mkd. T26N R25E S25 BT on open blaze. (Record: 80 lks.) Add the marks 2002 to the brass cap. Cor. is located 1.10 chs. N. of a wash, 30 ft. wide, 6 ft. deep, drains WSW. <hr style="width: 80%; margin: auto;"/> North, bet. secs. 19 and 24. Over rolling and broken land.
39.98	The 1/4 sec. cor. of secs. 19 and 24, monumented with an iron post, 1 in. diam., loosely set, projecting 18 ins. above ground, with brass cap mkd. 1/4 S24 S19 1915, from which the remains of the original bearing trees A juniper stump, 13 ins. diam. at base, 34 ins. high, bears N. 38 1/2° W., 2.68 chs. dist., mkd. 1/4 S19 BT on open blaze. (Record: piñon, N. 39 1/2° E.) A juniper, 12 ins. diam. at base, bears N. 80° W., 4 lks. dist., mkd. 1/4 S24 BT on open blaze. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the West Boundary,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 26 N 1/4 R 25 E R 26 E S 24 S 19 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Bury the iron post alongside the stainless steel post. <hr style="width: 20%; margin: auto;"/> N. 0°02' E., beginning new measurement.
39.99	The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 3 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. T26N S13 S18 S24 S19 R25E R26E 1915, from which the remains of the original bearing trees A root hole, bears N. 62° E., 38 lks. dist., with a piñon, 8 ins. diam., mkd. T26N R26E S18 BT on open blaze, lying alongside. A multiple trunked juniper, 16 ins. diam., bears S. 41° W., 10 lks. dist., mkd. T26N R256E on partially healed blaze. Add the marks 2002 to the brass cap. <hr style="width: 20%; margin: auto;"/> N. 0°03' E., bet. secs. 13 and 18. Over rolling land.
36.80	Apache County Road C416, a graded road, 20 ft. wide, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N 1/4 R 25 E R 26 E S 13 S 18 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Dependent Resurvey of the West Boundary,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>63.90 Navajo Route 151, a graded road, 25 ft. wide, bears ESE and WNW.</p> <p>80.00 The cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. T26N S12 S7 S13 S18 R25E R26E 1915, from which the original bearing trees</p> <p style="padding-left: 40px;">A forked piñon, 18 ins. diam., bears S. 25° E., 5.555 chs. dist., mkd. T26N R26E S8 BT on open blaze on the N. fork. Bearing tree is located in the backyard of a residence, 25 lks. W. of a house. (Record: S. 25°20' E., 557 lks.)</p> <p style="padding-left: 40px;">A forked piñon, 10 ins. diam., bears S. 74 1/4° W., 2.72 chs. dist., mkd. T26N R25E S13 BT on open blaze on the N. fork. (Record: S. 74°25' W., 172 lks.)</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears N. 68 1/2° W., 1.59 chs. dist., mkd. T26N R25E S12 BT on open blaze. (Record: N. 67°15' W.)</p> <p>Add the marks 2002 to the brass cap.</p> <hr/> <p>N. 0°04' E., bet. secs. 7 and 12.</p> <p>Over rolling and broken land.</p> <p>39.95 The 1/4 sec. cor. of secs. 7 and 12, monumented with a bent iron post, 1 in. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd. 1/4 S12 S7 1915, from which the original bearing trees</p> <p style="padding-left: 40px;">A forked piñon, 14 ins. diam. at base, bears S. 86 1/4° W., 62.5 lks. dist., mkd. 1/4 S12 BT on open blaze. (Record: 61 lks.)</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears N. 47 1/2° W., 63 lks. dist., mkd. 1/4 S12 BT on open blaze. (Record: 61 lks.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>T 26 N 1/4 R 25 E R 26 E S 12 S 7</p> <p>2002</p> </div>
--------	--

**Dependent Resurvey of the West Boundary,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS							
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the iron post alongside the stainless steel post.</p> <hr/> <p>N. 0°01' E., beginning new measurement.</p>						
39.97	<p>The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. T26N S1 S6 S12 S7 R25E R26E 1915.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Cor. is located 85 lks. W. of a trail road, bears SSE and NNW.</p> <hr/> <p>N. 0°01' E., bet. secs. 1 and 6.</p> <p>Over rolling land.</p>						
10.005	<p>The S-S 1/64 sec. cor. of secs. 1 and 6, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. 1/64 S1 S6 1915.</p> <p>Add the marks T26N R25E R26E S-S 2002 to the brass cap.</p> <hr/> <p>N. 0°01' E., beginning new measurement.</p>						
10.005	<p>Point for the S 1/16 sec. cor. of secs. 1 and 6, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N</p> <p>S</p> <p>1/16</p> <table border="0"> <tr> <td>R 25 E</td> <td> </td> <td>R 26 E</td> </tr> <tr> <td>S 1</td> <td> </td> <td>S 6</td> </tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 2 lks. S. of S. edge of a wash, 12 ft. deep, bears ESE and WNW.</p>	R 25 E		R 26 E	S 1		S 6
R 25 E		R 26 E					
S 1		S 6					
13.60	<p>N. bank of a wash, bears SE and NW.</p>						

**Dependent Resurvey of the West Boundary,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
17.80	Apache County Road C413, a graded road, 20 ft. wide, bears E. and W.
20.01	<p>Point for the N-S 1/64 sec. cor. of secs. 1 and 6, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N N-S 1/64 R 25 E R 26 E S 1 S 6</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
30.01	<p>Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N 1/4 R 25 E R 26 E S 1 S 6</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located in the flood plain of Pueblo Colorado Wash.</p>
31.40	Point for the original meander cor. of secs. 1 and 6, on the left bank of the Pueblo Colorado River, at proportionate distance; there is no remaining evidence of the original cor. Point falls in the Pueblo Colorado Wash, where it is impracticable to establish a permanent monument. Not remonumented.
40.01	<p>Point for the S-N 1/64 sec. cor., identical with the original meander cor. on the right bank of the Pueblo Colorado River, of secs. 1 and 6, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the West Boundary,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">T 26 N S-N 1/64 R 25 E R 26 E S 1 S 6</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 40 lks. N. of N. bank of Pueblo Colorado Wash, 5 ft. high, bears NE and SW.</p>
50.015	<p>Point for the N 1/16 sec. cor. of secs. 1 and 6, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 26 N N 1/16 R 25 E R 26 E S 1 S 6</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
60.02	<p>Point for the N-N 1/64 sec. cor. of secs. 1 and 6, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 26 N N-N 1/64 R 25 E R 26 E S 1 S 6</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Cor. is located 1.80 chs. S. of Apache County Road C426, a graded road, 20 ft. wide, bears ENE and WSW.</p>

**Dependent Resurvey of the West Boundary,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS

70.02

The cor. of Tps. 26 and 27 N., Rs. 25 and 26 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. T27N R25E R26E S36 S31 S1 S6 T26N 1915 1990.

Add the marks 2002 to the brass cap.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona**

Restoring the survey executed by
Frederick C. Miller, in 1915

From cor. of secs. 4, 5, 8 and 9, determined from the remains of the original bearing trees

A piñon stump, 12 ins. diam. at base, 23 ins. high, bears N. 44° E., 6 lks. dist., mkd. BT on open blaze.

A piñon, 12 ins. diam., bears S. 45° E., 1.23 chs. dist., mkd. T26N R26E S9 BT on open blaze.

A piñon stump, 8 ins. diam. at base, 24 ins. high, bears S. 74° W., 19 lks. dist., mkd. 8 BT on partially healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 N	R 26 E
S 5	S 4
S 8	S 9

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Cor. is located 2.70 chs. N. of a trail road, bears ENE and WSW.

N. 0°03' E., bet. secs. 4 and 5.

Over rolling and broken land.

39.98

The 1/4 sec. cor. of secs. 4 and 5, determined from the remaining bearing tree

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS

A piñon, 11 ins. diam., bears N. 27 1/2° W., 33 lks. dist., mkd. 1/4 S5 BT on partially healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 N R 26 E

1/4

S 5 | S 4

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Cor. is located 80 lks. W. and 1.25 chs. S. of a wash, 9 ft. wide, 4 ft. deep, drains NNW, and 2.40 chs. S. of another wash, 15 ft. wide, 7 ft. deep, drains NNW.

N. 0°01' E., beginning new measurement.

39.96

The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd. T27N R26E S32 S33 S5 S4 T26N 1990 1915, from which the remaining original bearing tree

A piñon, 12 ins. diam., bears N. 33 1/2° W., 1.14 chs. dist., mkd. T27N R26E S32 BT on open blaze.

Add the marks 2002 to the brass cap.

From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented with an iron post, 3 ins. diam., with brass cap, set, mkd. and witnessed as described in the field notes of the dependent resurvey of the N. bdy., T. 25 N., R. 26 E., executed concurrently under this same group.

N. 0°02' W., bet. secs. 31 and 32.

Over rolling land.

39.97

The 1/4 sec. cor. of secs. 31 and 32, monumented with an iron post, 1 in. diam., loosely set, projecting 11 ins. above ground, with brass cap mkd. 1/4 S31 S32 1915, from which the remains of the original bearing trees

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>A forked piñon, 14 ins. diam. at base, bears S. 72 1/2° E., 25 lks. dist., mkd. 1/4 S32 BT on open blaze on the N. fork. (Record: S. 77° E.)</p> <p>A root hole, bears N. 72° W., 52 lks. dist., with a piñon, 12 ins. diam., mkd. 1/4 S31 BT on open blaze, lying alongside.</p> <p>At the corner point</p> <p>Reset the iron post, 29 ins. in the ground.</p> <p>Deposit a magnet in a white plastic case at the base of the iron post.</p> <p>Add the marks T26N R26E 2002 to the brass cap.</p> <hr/> <p>N. 0°06' W., beginning new measurement.</p>
40.04	<p>The cor. of secs. 29, 30, 31 and 32, monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. T26N R26E S30 S29 S31 S32 1915.</p> <p>Add the marks 2002 to the brass cap.</p> <hr/>
	<p>North, bet. secs. 29 and 30.</p> <p>Over rolling land.</p>
39.98	<p>The 1/4 sec. cor. of secs. 29 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. 1/4 S30 S29 1915, from which the original bearing trees</p> <p>A dead piñon, 9 ins. diam., bears S. 16 3/4° E., 43 lks. dist., mkd. 1/4 S29 BT on open blaze. (Record: S. 6 1/2° E.)</p> <p>A dead forked piñon, 9 ins. diam., bears N. 53° W., 66 lks. dist., mkd. 1/4 S30 BT on open blaze.</p> <p>At the corner point</p> <p>Reset the iron post, 30 ins. in the ground.</p> <p>Deposit a magnet in a white plastic case at the base of the iron post.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Add the marks T26N R26E 2002 to the brass cap.</p> <hr/>
	<p>N. 0°04' W., beginning new measurement.</p>
39.95	<p>The cor. of secs. 19, 20, 29 and 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. T26N R26E S19 S20 S30 S29 1915, from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A piñon stump, 19 ins. diam. at base, 3 ft. high, bears S. 81° W., 61 lks. dist., mkd. 30 BT on open blaze. (Record: 30 ins., S. 31 1/4° W.)</p>
	<p>Add the marks 2002 to the brass cap.</p> <hr/>
	<p>N. 0°09' E., bet. secs. 19 and 20.</p>
	<p>Over rolling land.</p>
24.50	<p>High voltage transmission line, bears NE and SW.</p>
39.97	<p>The 1/4 sec. cor. of secs. 19 and 20, determined from the original bearing trees</p> <p style="padding-left: 40px;">A piñon, 8 ins. diam., bears N. 54 3/4° E., 70 lks. dist., mkd. 1/4 S20 BT on open blaze.</p> <p style="padding-left: 40px;">A forked juniper, 9 ins. diam., bears S. 80 3/4° W., 29 lks. dist., with a healed blaze on the N. fork. (Record: S. 84 1/2° W.)</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 26 N R 26 E 1/4 S 19 S 20 2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>
	<p>North, beginning new measurement.</p>
40.00	<p>Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist.; there is no remaining evidence of the original cor.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> T 26 N R 26 E S 18 S 17 S 19 S 20 ----- 2002 </p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<hr/> <p>North, bet. secs. 17 and 18.</p>
	<p>Over rolling and broken land.</p>
40.00	<p>The 1/4 sec. cor. of secs. 17 and 18, monumented with a bent iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. 1/4 S18 S17 1915, from which the remaining original bearing tree</p> <p align="center">A piñon, 8 ins. diam., bears S. 39° E., 1.045 chs. dist., with a healed blaze. (Record: S. 14 1/2° E., 127 lks.)</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center"> T 26 N R 26 E 1/4 S 18 S 17 ----- 2002 </p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Bury the iron post alongside the stainless steel post.</p>
	<p>Cor. is located 4.55 chs. N. of a trail road, bears NNE and SSW.</p>
	<hr/> <p>North, beginning new measurement.</p>
7.80	<p>Navajo Route 151, a graded road, 30 ft. wide, bears E. and W.</p>
8.20	<p>Apache County Road C427, a graded road, 30 ft. wide, bears ESE and NWW.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS							
39.95	<p>The cor. of secs. 7, 8, 17 and 18, determined from the remaining original bearing tree</p> <p style="padding-left: 40px;">A juniper, 15 ins. diam., bears N. 69 1/2° W., 72 lks. dist., mkd. T26N R26E S7 on partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1" style="margin: auto;"> <tr><td>T 26 N</td><td>R 26 E</td></tr> <tr><td>S 7</td><td>S 8</td></tr> <tr><td>S 18</td><td>S 17</td></tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>	T 26 N	R 26 E	S 7	S 8	S 18	S 17
T 26 N	R 26 E						
S 7	S 8						
S 18	S 17						
40.00	<p>N. 0°06' W., bet. secs. 7 and 8.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1" style="margin: auto;"> <tr><td>T 26 N</td><td>R 26 E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td>S 7</td><td>S 8</td></tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 75 lks. S. of a trail road, bears SE and NW.</p>	T 26 N	R 26 E	1/4		S 7	S 8
T 26 N	R 26 E						
1/4							
S 7	S 8						
80.00	<p>Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>						

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">T 26 N R 26 E S 6 S 5 ----- S 7 S 8</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.55 chs. N. and 20 lks. E. of E. bank of a wash, 15 ft. deep, 200 ft. wide, drains NNW.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>N. 89°56' W., bet. secs. 5 and 8.</p> <p>Over rolling and broken land.</p>
39.945	<p>Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate dist.; there is no remaining evidence of the original cor. The original bearing tree, a decaying piñon, 5 ins. diam., mkd. 1/4 S on partially healed blaze, was found nearby, uprooted and alongside an area disturbed by road and power line construction. Its original position could not be determined.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 26 N R 26 E S 5 1/4 ——— S 8</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.89	<p>The cor. of secs. 5, 6, 7 and 8.</p> <hr/> <p>S. 89°54' W., bet. secs. 6 and 7.</p> <p>Over rolling land.</p>
26.50	<p>Apache County Road C427, a graded road, 25 ft. wide, bears N. and S.</p>
39.95	<p>The 1/4 sec. cor. of secs. 6 and 7, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T26N R26E 1/4 S6 S7 1915.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS							
	Add the marks 2002 to the brass cap.						
	<hr/> N. 89°55' W., beginning new measurement.						
38.98	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.						
	<hr/> From the cor. of secs. 5, 6, 7 and 8.						
	N. 0°04' E., bet. secs. 5 and 6.						
	Over rolling land.						
19.98	Point for the S 1/16 sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of original temporary cor. Not remonumented.						
35.46	The meander cor. of secs. 5 and 6, N. bdy. of right-of-way of South Side Canal, monumented with a bent iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. T26N R26E S6 S5 MC 1915.						
	At the corner point						
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.						
	<div style="text-align: center;"> <table border="0"> <tr> <td>T 26 N</td> <td>R 26 E</td> </tr> <tr> <td>S 6</td> <td>S 5</td> </tr> <tr> <td colspan="2" style="text-align: center;">MC</td> </tr> </table> </div>	T 26 N	R 26 E	S 6	S 5	MC	
T 26 N	R 26 E						
S 6	S 5						
MC							
	2002						
	Deposit a magnet in a white plastic case at the base of the stainless steel post.						
	Bury the iron post alongside the stainless steel post.						
	From this cor. point, a meander cor. in sec. 5, on the N. bdy. of the right-of-way of South Side Canal, bears N. 28°57' E., 5.14 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. 1/4 S5 MC 1915.						
	<hr/> N. 0°06' W., beginning new measurement.						
4.50	Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate dist.						

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 26 E 1/4 S 6 S 5 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the 1915 iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. T26N R26E 1/4 S6 S5 1915, bears N. 17°00' W., 3.37 chs. dist. The position of this monument exceeds the limits for rectangularity and is not utilized in the course of this resurvey. Add the marks AM 2002 to the brass cap and bury in place.</p>
14.50	<p>Point for the S-N 1/64 sec. cor. of secs. 5 and 6, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Deposit a magnet in a white plastic case, 24 ins. in the ground.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 45°00' E., 50 ft. dist. with brass cap mkd. T26N R26E S5 50 FT. TO COR. 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 45°00' W., 30 ft. dist. with brass cap mkd. T26N R26E S6 30 FT. TO COR. 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located in a wash 20 ft. wide, 6 ft. deep, drains W.</p>
24.50	<p>The N 1/16 sec. cor. of secs. 5 and 6, determined from the original bearing tree</p> <p>A forked juniper, 12 ins. diam., bears N. 1° E., 84 lks. dist., mkd. N 1/16 S5 BT on open blaze on the S. fork.</p> <p>At the corner point</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 26 N R 26 E N 1/16 S 6 S 5 2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Cor. is located 55 lks. N. of a wash, 8 ft. wide, 1 ft. deep, drains SW.</p>
	<hr/> <p>N. 0°08' E., beginning new measurement.</p>
10.00	<p>The N-N 1/64 sec. cor. of secs. 5 and 6, monumented with a bent iron post, 1 in. diam., loosely set, projecting 16 ins. above ground, with brass cap mkd. 1/64 S6 S5 1915.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 26 N R 26 E N-N 1/64 S 6 S 5 2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Bury the iron post alongside the stainless steel post.</p>
	<hr/> <p>N. 0°04' W., beginning new measurement.</p>
6.10	<p>Apache County Road C427, a graded road, 25 ft. wide, bears NE and SW.</p>
9.96	<p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T27N R26E S31 S32 S6 S5 T26N 1990 1915, from which the original bearing tree</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS

A piñon, 20 ins. diam., bears N. 84° W., 24 lks. dist.,
mkd. T27N R26E S BT. on partially healed blaze.

Add the marks 2002 to the brass cap.

**Survey of a Portion of the Subdivisional Lines,
T. 25 N., R. 26 E., Gila and Salt River Meridian, Arizona**

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the
Tp., monumented with a stainless steel post, 2 1/2 ins. diam.,
with brass cap, set and mkd. as described in the field notes of
the dependent resurvey of the N. bdy., T. 25 N., R. 26 E.,
executed concurrently under this same group.

North, bet. secs. 35 and 36.

Over rolling land.

40.00

Point for the 1/4 sec. cor. of secs. 35 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T 26 N R 26 E
1/4
S 35 | S 36

2002

Deposit a magnet in a white plastic case at the base of the
stainless steel post.

46.70

Underground gas pipeline, bears E. and W.

80.00

Point for the cor. of secs. 25, 26, 35 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T 26 N R 26 E
S 26 | S 25
S 35 | S 36

2002

Deposit a magnet in a white plastic case at the base of the
stainless steel post.

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 25 and 36 only, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°52' W., bet. secs. 25 and 36.</p> <p>Over rolling land.</p>
39.98	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 26 E S 25 1/4 ——— S 36</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.96	<p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/>
40.00	<p>North, bet. secs. 25 and 26.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 26 E 1/4 S 26 S 25</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS									
80.00	<p>Point for the cor. of secs. 23, 24, 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 26 N</td> <td>R 26 E</td> </tr> <tr> <td>S 23</td> <td>S 24</td> </tr> <tr> <td>S 26</td> <td>S 25</td> </tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, third order U. S. Geological Survey triangulation station "SAGEWOOD", bears N. 32° 47' W., 41.69 chs. dist., monumented with a standard brass tablet, 4 ins. diam., cemented flush in a sandstone block, 7 X 5 ins., firmly set, projecting 5 ins. above ground, with top mkd. SAGEWOOD 1955 and a triangle.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p>	T 26 N	R 26 E	S 23	S 24	S 26	S 25		
T 26 N	R 26 E								
S 23	S 24								
S 26	S 25								
	<p>From the cor. of secs. 24 and 25 only, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°49' W., bet. secs. 24 and 25.</p> <p>Over rolling land.</p>								
39.96	<p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 26 N</td> <td>R 26 E</td> </tr> <tr> <td></td> <td>S 24</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 25</td> </tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 26 N	R 26 E		S 24	1/4	—		S 25
T 26 N	R 26 E								
	S 24								
1/4	—								
	S 25								
79.92	<p>The cor. of secs. 23, 24, 25 and 26.</p>								

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/>
	<p>North, bet. secs. 23 and 24.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 26 E 1/4 S 23 S 24</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post near the stainless steel post.</p> <p>Cor. is located 5 lks. N. of a trail road, bears NNE and SSW.</p>
80.00	<p>Point for the cor. of secs. 13, 14, 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 26 E S 14 S 13 S 23 S 24</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 13 and 24 only, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°48' W., bet. secs. 13 and 24.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
40.04	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 26 E S 13 1/4 ——— S 24</p> <p align="center">2002</p>
80.08	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/>
	North, bet. secs. 13 and 14.
	Over rolling land.
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 26 E 1/4 S 14 S 13</p> <p align="center">2002</p>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located 1.60 chs. N. of a trail road, bears SSE and NNW.
57.70	High voltage transmission line, bears NE and SW.
80.00	<p>Point for the cor. of secs. 11, 12, 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table border="0"> <tr> <td>T 26 N</td> <td>R 26 E</td> </tr> <tr> <td>S 11</td> <td>S 12</td> </tr> <tr> <td>S 14</td> <td>S 13</td> </tr> </table>	T 26 N	R 26 E	S 11	S 12	S 14	S 13		
T 26 N	R 26 E								
S 11	S 12								
S 14	S 13								
	2002								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.								
	<hr/>								
	From the cor. of secs. 12 and 13 only, on the E. bdy. of the Tp., hereinbefore described.								
	N. 89°42' W., bet. secs. 12 and 13.								
	Over rolling land.								
40.04	Point for the 1/4 sec. cor. of secs. 12 and 13.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="0"> <tr> <td>T 26 N</td> <td>R 26 E</td> </tr> <tr> <td></td> <td>S 12</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 13</td> </tr> </table>	T 26 N	R 26 E		S 12	1/4	—		S 13
T 26 N	R 26 E								
	S 12								
1/4	—								
	S 13								
	2002								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
46.90	Power line, bears ESE and WNW.								
59.70	High voltage transmission line, bears NE and SW.								
80.08	The cor. of secs. 11, 12, 13 and 14.								
	Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.								
	<hr/>								
	North, bet. secs. 11 and 12.								
	Over rolling land.								

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
15.30	Power line, bears ESE and WNW.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">T 26 N R 26 E 1/4 S 11 S 12 2002</p>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 1, 2, 11 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">T 26 N R 26 E S 2 S 1 ----- S 11 S 12 2002</p>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	<p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p>
	<hr/> <p>From the cor. of secs. 1 and 12 only, on the E, bdy. of the Tp., hereinbefore described.</p>
	N. 89°42' W., bet. secs. 1 and 12.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p align="center">T 26 N R 26 E S 1 1/4 ——— S 12</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.15 chs. E. of a trail road, bears NE and SW.</p> <p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p>
17.80	<p>N. 0°01' W., bet. secs. 1 and 2.</p> <p>Over rolling land.</p> <p>High voltage transmission line, bears NE and SW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
79.74	<p align="center">T 26 N R 26 E 1/4 S 2 S 1</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T27N R26E S35 S36 S2 S1 T26N 1915 1990.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Cor. is located 25 lks. W. of a trail road, bears N. and S.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of the N. bdy., T. 25 N., R. 26 E., executed concurrently under this same group.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over rolling land.</p>
33.50	Underground gas pipeline, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 34 and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">T 26 N R 26 E 1/4 S 34 S 35 2002</p>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
71.99	W. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
80.00	Point for the cor. of secs. 26, 27, 34 and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">T 26 N R 26 E S 27 S 26 S 34 S 35 2002</p>

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

<p>CHAINS</p>	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 45°00' E., 166 ft. dist. with brass cap mkd. T26N R26E S26 166 FT. TO COR. 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°00' W., 88 ft. dist. with brass cap mkd. T26N R26E S34 88 FT. TO COR. 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 45 lks. W. of the centerline of U. S. Highway 191, asphalt pavement, 28 ft. wide, bears SSE and NNW, and 2.00 chs. W. of E. right-of-way fence, barbed wire, 5 strands, and 2.25 chs. W. of underground pipeline, both parallel highway, and 1.05 chs. E. of W. right-of-way fence, barbed wire, 5 strands, and 1.10 chs. E. of power line, both parallel highway.</p> <p>From this cor. point, a brass tablet, 3 ins. diam., set flush in a concrete collar, 6 ins. diam., firmly set, projecting 5 ins. above ground, bears N. 73°06' E., 2.01 chs. dist., with top mkd. B.I.A. ROADS 19, with an angle iron set nearby, mkd. STA. POT 331+00.</p> <p>From this same cor. point, a brass tablet, 3 ins. diam., set flush in a concrete collar, 6 ins. diam., firmly set, projecting 3 ins. above ground, bears N. 81°21' W., 1.09 chs. dist., with top mkd. B.I.A. ROADS.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 89°54' W., bet. secs. 26 and 35.</p> <p>Over rolling land.</p> <p>39.99 Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
---------------	---

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 26 N R 26 E S 26 1/4 ——— S 35 2002 Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.98	The cor. of secs. 26, 27, 34 and 35. Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.
	<hr/> N. 0°01' W., bet. secs. 26 and 27. Over rolling land.
3.52	U. S. Highway 191, asphalt pavement, 28 ft. wide, bears SSE and NNW.
15.22	E. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
16.70	Underground gas pipeline, parallels E. right-of-way fence.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 26 E 1/4 S 27 S 26 2002 Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 22, 23, 26 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	<div style="text-align: center; margin-bottom: 10px;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 26 N</td> <td style="padding: 0 10px;">R 26 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 22</td> <td style="padding: 0 5px;">S 23</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 27</td> <td style="padding: 0 5px;">S 26</td> </tr> </table> </div> <div style="text-align: center; margin-bottom: 10px;">2002</div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 89°54' W., bet. secs. 23 and 26.</p> <p>Over rolling land.</p> <p>39.99 Point for the 1/4 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-bottom: 10px;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 26 N</td> <td style="padding: 0 10px;">R 26 E</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S 23</td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="border-top: 1px solid black; padding: 0 5px;">—</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S 26</td> </tr> </table> </div> <div style="text-align: center; margin-bottom: 10px;">2002</div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>79.98 The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over rolling land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	T 26 N	R 26 E	S 22	S 23	S 27	S 26	T 26 N	R 26 E		S 23	1/4	—		S 26
T 26 N	R 26 E														
S 22	S 23														
S 27	S 26														
T 26 N	R 26 E														
	S 23														
1/4	—														
	S 26														

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">T 26 N R 26 E 1/4 S 22 S 23</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
50.70	High voltage transmission line, bears NE and SW.
80.00	Point for the cor. of secs. 14, 15, 22 and 23.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 26 N R 26 E S 15 S 14 S 22 S 23</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p>
	<hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 89°54' W., bet. secs. 14 and 23.</p> <p>Over rolling land.</p>
39.99	Point for the 1/4 sec. cor. of secs. 14 and 23.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 26 N R 26 E S 14 1/4 ——— S 23</p> <p align="center">2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
53.10	High voltage transmission line, bears NE and SW.
79.98	The cor. of secs. 14, 15, 22 and 23. Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.
	N. 0°01' W., bet. secs. 14 and 15. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 26 E 1/4 S 15 S 14 2002 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 10, 11, 14 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 26 E S 10 S 11 S 15 S 14 2002 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post. Cor. is located 1.40 chs. S. of a trail road, bears SSE and NNW. Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.
	From the cor. of secs. 11, 12, 13 and 14.

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 89°54' W., bet. secs. 11 and 14.
	Over rolling land.
39.99	Point for the 1/4 sec. cor. of secs. 11 and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">T 26 N R 26 E S 11 1/4 ——— S 14</p>
	2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located 80 lks. S. of a trail road, bears ENE and WSW.
79.98	The cor. of secs. 10, 11, 14 and 15.
	Land, rolling.
	Soil, sand and sandy clay.
	Timber, piñon and juniper; undergrowth, sagebrush and native grasses.
	N. 0°01' W., bet. secs. 10 and 11.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">T 26 N R 26 E 1/4 S 10 S 11</p>
	2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located 60 lks. N. of high voltage transmission line, bears NE and SW.
52.40	Power line, bears ESE and WNW.
80.00	Point for the cor. of secs. 2, 3, 10 and 11.

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> <table border="0"> <tr> <td>T 26 N</td> <td>R 26 E</td> </tr> <tr> <td>S 3</td> <td>S 2</td> </tr> <tr> <td>S 10</td> <td>S 11</td> </tr> </table> </p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°54' W., bet. secs. 2 and 11.</p> <p>Over rolling land.</p>	T 26 N	R 26 E	S 3	S 2	S 10	S 11		
T 26 N	R 26 E								
S 3	S 2								
S 10	S 11								
24.40	High voltage transmission line, bears NE and SW.								
39.99	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> <table border="0"> <tr> <td>T 26 N</td> <td>R 26 E</td> </tr> <tr> <td></td> <td>S 2</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td></td> <td>S 11</td> </tr> </table> </p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 26 N	R 26 E		S 2	1/4	_____		S 11
T 26 N	R 26 E								
	S 2								
1/4	_____								
	S 11								
79.98	<p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>North, bet. secs. 2 and 3.</p> <p>Over rolling land.</p>								

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 26 E 1/4 S 3 S 2</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.67	<p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. T27N R26E S34 S35 S3 S2 T26N 1915 1990.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of the N. bdy., T. 25 N., R. 26 E., executed concurrently under this same group.</p> <p>N. 0°01' W., bet. secs. 33 and 34.</p> <p>Over rolling land.</p>
14.30	<p>Underground gas pipeline, bears E. and W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 26 E 1/4 S 33 S 34</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS									
80.00	<p>Point for the cor. of secs. 27, 28, 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="812 472 1039 577"> <tr> <td>T 26 N</td> <td>R 26 E</td> </tr> <tr> <td>S 28</td> <td>S 27</td> </tr> <tr> <td>S 33</td> <td>S 34</td> </tr> </table> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, native grasses.</p>	T 26 N	R 26 E	S 28	S 27	S 33	S 34		
T 26 N	R 26 E								
S 28	S 27								
S 33	S 34								
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°56' W., bet. secs. 27 and 34.</p> <p>Over rolling land.</p>								
31.10	Underground gas pipeline, bears SSE and NNW.								
39.97	<p>Point for the 1/4 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="812 1323 1039 1438"> <tr> <td>T 26 N</td> <td>R 26 E</td> </tr> <tr> <td></td> <td>S 27</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 34</td> </tr> </table> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 2.00 chs. E. of a wash, 4 ft. wide, 2 ft. deep, drains SSW.</p>	T 26 N	R 26 E		S 27	1/4	—		S 34
T 26 N	R 26 E								
	S 27								
1/4	—								
	S 34								
79.94	The cor. of secs. 27, 28, 33 and 34.								

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS

Land, rolling.
Soil, sand and sandy clay.
Timber, piñon and juniper; undergrowth, sagebrush, native
grasses.

N. 0°01' W., bet. secs. 27 and 28.

Over rolling land.

40.00

Point for the 1/4 sec. cor. of secs. 27 and 28.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T 26 N R 26 E
1/4
S 28 | S 27

2002

Deposit a magnet in a white plastic case at the base of the
stainless steel post.

43.80

High voltage transmission line, bears NE and SW.

80.00

Point for the cor. of secs. 21, 22, 27 and 28.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T 26 N R 26 E
S 21 | S 22
S 28 | S 27

2002

Deposit a magnet in a white plastic case at the base of the
stainless steel post.

Land, rolling.
Soil, sand and sandy clay.
Timber, piñon and juniper; undergrowth, sagebrush, native
grasses.

From the cor. of secs. 22, 23, 26 and 27.

N. 89°56' W., bet. secs. 22 and 27.

Over rolling land.

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
8.40	Underground gas pipeline, parallels E. right-of-way fence.
8.58	E. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
10.12	U. S. Highway 191, asphalt pavement, 28 ft. wide, bears SSE and NNW.
11.62	W. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
39.97	Point for the 1/4 sec. cor. of secs. 22 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 26 E S 22 1/4 ——— S 27 2002 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post.
46.40	Underground gas pipeline, bears N. and S.
46.70	High voltage transmission line, bears NE and SW.
79.94	The cor. of secs. 21, 22, 27 and 28. Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, native grasses.
	<hr/> N. 0°01' W., bet. secs. 21 and 22. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 26 E 1/4 S 21 S 22 2002 </div>

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>								
80.00	<p>Point for the cor. of secs. 15, 16, 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 26 N</td> <td>R 26 E</td> </tr> <tr> <td>S 16</td> <td>S 15</td> </tr> <tr> <td>S 21</td> <td>S 22</td> </tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, native grasses.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 89°56' W., bet. secs. 15 and 22.</p> <p>Over rolling land.</p>	T 26 N	R 26 E	S 16	S 15	S 21	S 22		
T 26 N	R 26 E								
S 16	S 15								
S 21	S 22								
18.90	Underground gas pipeline, parallels E. right-of-way fence.								
19.17	E. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.								
20.67	U. S. Highway 191, asphalt pavement, 28 ft. wide, bears SSE and NNW.								
22.20	W. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.								
39.97	<p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 26 N</td> <td>R 26 E</td> </tr> <tr> <td></td> <td>S 15</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td></td> <td>S 22</td> </tr> </table> <p>2002</p> </div>	T 26 N	R 26 E		S 15	1/4	_____		S 22
T 26 N	R 26 E								
	S 15								
1/4	_____								
	S 22								

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
44.00	Underground gas pipeline, bears N. and S.
79.94	<p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 15 and 16.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 26 E 1/4 S 16 S 15</p> <p align="center">2002</p>
61.10	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>High voltage transmission line, bears NE and SW.</p>
80.00	<p>Point for the cor. of secs. 9, 10, 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 26 E S 9 S 10 ----- S 16 S 15</p> <p align="center">2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, native grasses.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15. N. 89°56' W., bet. secs. 10 and 15. Over rolling land.</p>
29.50	Underground gas pipeline, parallels E. right-of-way fence.
29.73	E. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
31.25	U. S. Highway 191, asphalt pavement, 30 ft. wide, bears SSE and NNW.
32.79	W. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
39.97	<p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 26 E S 10 1/4 ——— S 15</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
40.50	Underground gas pipeline, bears N. and S.
54.00	High voltage transmission line, bears NE and SW.
79.94	<p>The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs., 9 and 10. Over rolling land.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 26 E 1/4 S 9 S 10</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
58.10	Navajo Route 151, a graded road, 25 ft. wide, bears NE and SW.
65.30	Power line, bears E. and W.
80.00	<p>Point for the cor. of secs. 3, 4, 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 26 E S 4 S 3 S 9 S 10</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, native grasses.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 89°56' W., bet. secs. 3 and 10.</p> <p>Over rolling land.</p>
28.10	Underground gas pipeline, parallels E. right-of-way fence.
28.33	E. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
28.84	From this point, a brass disk, 3 1/2 ins. diam., set flush in a concrete collar, 6 ins. diam., set flush with the ground, bears North, 69 lks. dist., with top mkd. ELEV. 6734 FT 38 HLS 1990.

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
29.86	U. S. Highway 191, asphalt pavement, 30 ft. wide, bears NNE and SSW.
31.40	W. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
36.70	Underground gas pipeline, bears NE and SW.
39.97	Point for the 1/4 sec. cor. of secs. 3 and 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">T 26 N R 26 E S 3 1/4 ——— S 10</p>
	2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located 75 lks. W. of a trail road, bears N. and S.
58.40	Navajo Route 151, a graded road, 25 ft. wide, bears NE and SW.
79.94	The cor. of secs. 3, 4, 9 and 10.
	<p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, native grasses.</p>
	N. 0°02' W., bet. secs. 3 and 4.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">T 26 N R 26 E 1/4 S 4 S 3</p>
	2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.60	<p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. T27N R26E S33 S34 S4 S3 T26N 1915 1990.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, native grasses.</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of the N. bdy., T. 25 N., R. 26 E., executed concurrently under this same group.</p> <p>N. 0°02' W., bet. secs. 32 and 33.</p> <p>Over rolling land.</p>
3.70	Underground gas pipeline, bears ENE and WSW.
36.90	High voltage transmission line, bears NE and SW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ns. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 26 E 1/4 S 32 S 33</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
61.13	Barbed wire fence, 5 strands, bears ENE and WSW.
80.00	<p>Point for the cor. of secs. 28, 29, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 26 N	R 26 E
S 29	S 28
S 32	S 33

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Land, rolling.

Soil, sand and sandy clay.

Timber, piñon and juniper; undergrowth, sagebrush, native grasses.

From the cor. of secs. 27, 28, 33 and 34.

N. 89°58' W., bet. secs. 28 and 33.

Over rolling land.

39.98

Point for the 1/4 sec. cor. of secs. 28 and 33.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 N	R 26 E
	S 28
1/4	—
	S 33

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Cor. is located 30 lks. E. of a high voltage transmission line, bears NE and SW.

41.82

Barbed wire fence, 5 strands, bears NE and SW.

79.96

The cor. of secs. 28, 29, 32 and 33.

Land, rolling.

Soil, sand and sandy clay.

Timber, piñon and juniper; undergrowth, sagebrush, native grasses.

N. 0°02' W., bet. secs. 28 and 29.

Over rolling land.

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 26 E 1/4 S 29 S 28</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
45.16	Barbed wire fence, 5 strands, bears NE and SW.
80.00	<p>Point for the cor. of secs. 20, 21, 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 26 E S 20 S 21 S 29 S 28</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, native grasses.</p>
	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N. 89°58' W., bet. secs. 21 and 28.</p> <p>Over rolling land.</p>
39.98	<p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">T 26 N R 26 E S 21 1/4 ——— S 28</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.00 ch. W. of a trail road, bears SSE and NNW.</p> <p>43.60 Barbed wire fence, 5 strands, bears SSE and NNW.</p> <p>79.96 The cor. of secs. 20, 21, 28 and 29.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 20 and 21.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 26 N R 26 E 1/4 S 20 S 21</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 16, 17, 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 26 N R 26 E S 17 S 16 ——— S 20 S 21</p> <p align="center">2002</p>

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, native grasses.</p> <hr/>
	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 89°58' W., bet. secs. 16 and 21.</p> <p>Over rolling land.</p>
39.98	<p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with ground, with brass cap mkd.</p>
	<p align="center">T 26 N R 26 E S 16 1/4 ——— S 21 2002</p>
79.96	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 10 lks. E. of a trail road, bears SSE and NNW.</p> <p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, native grasses.</p> <hr/>
2.80	<p>N. 0°02' W., bet. secs. 16 and 17.</p> <p>Over rolling land.</p> <p>High voltage transmission line, bears NE and SW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 26 N R 26 E 1/4 S 17 S 16 2002 Deposit a magnet in a white plastic case at the base of the stainless steel post.
69.70	Navajo Route 151, a graded road, 30 ft. wide, bears ENE and WSW.
80.00	Point for the cor. of secs. 8, 9, 16 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T 26 N R 26 E S 8 S 9 S 17 S 16 2002 Deposit a magnet in a white plastic case at the base of the stainless steel post. Cor. is located 25 lks. S. of a wash, 5 ft. wide, 5 ft. deep, drains NE and 35 lks. E. of another wash, 5 ft. wide, 5 ft. deep, drains N. Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, native grasses.
	<hr/> From the cor. of secs. 9, 10, 15 and 16. N. 89°58' W., bet. secs. 9 and 16. Over rolling land.
39.98	Point for the 1/4 sec. cor. of secs. 9 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 26 N R 26 E S 9 1/4 ——— S 16 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
61.50	Navajo Route 151, a graded road, 30 ft. wide, bears NE and SW.
79.96	The cor. of secs. 8, 9, 16 and 17. Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, native grasses.
	N. 0°03' W., bet. secs. 8 and 9.
	Over rolling and broken land.
39.91	Point for the 1/4 sec. cor. of secs. 8 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 26 E 1/4 S 8 S 9 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
75.00	Power line, bears E. and W.
79.82	The cor. of secs. 4, 5, 8 and 9, hereinbefore described. Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, native grasses.
	From the cor. of secs. 3, 4, 9 and 10.
	S. 89°54' W., bet. secs. 4 and 9.
	Over rolling land.

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.99	<p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 26 E S 4 1/4 ——— S 9</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 85 lks. E. of a trail road, bears ENE and WSW.</p>
79.98	<p>The cor. of secs. 4, 5, 8 and 9, hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, native grasses.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 89°58' W., bet. secs. 29 and 32.</p> <p>Over rolling land.</p>
36.40	Barbed wire fence, 5 strands, bears NE and SW.
40.03	<p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 26 E S 29 1/4 ——— S 32</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
44.47	Barbed wire fence, 5 strands, bears SSE and NNW.
80.06	The cor. of secs. 29, 30, 31 and 32, hereinbefore described.

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, native grasses.</p> <hr/>
	<p>S. 89°58' W., bet. secs. 30 and 31.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 26 E S 30 1/4 ——— S 31</p> <p align="center">2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.22	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, native grasses.</p> <hr/>
	<p>From the cor. of secs. 20, 21, 28 and 29.</p>
	<p>S. 89°59' W., bet. secs. 20 and 29.</p>
	<p>Over rolling land.</p>
40.03	<p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 26 E S 20 1/4 ——— S 29</p> <p align="center">2002</p>

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.90 chs. W. of a fence, barbed wire, 5 strands, bears ENE and WSW.</p>
80.06	<p>The cor. of secs. 19, 20, 29 and 30, hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, native grasses.</p> <hr/> <p>N. 89°59' W., bet. secs. 19 and 30.</p> <p>Over rolling land.</p>
35.40	High voltage transmission line, bears NE and SW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole in sandstone bedrock, with top mkd.</p> <div style="text-align: center;"> <p>T 26 N R 26 E S 19 1/4 ——— S 30</p> <p>2002</p> </div>
79.16	<p>Deposit a magnet in a white plastic case at the base of the brass tablet.</p> <p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, native grasses.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>S. 89°58' W., bet. secs. 17 and 20.</p> <p>Over rolling land.</p>
3.80	High voltage transmission line, bears NE and SW.
39.94	Point for the 1/4 sec. cor. of secs. 17 and 20.

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 26 E S 17 1/4 ——— S 20</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.88	<p>The cor. of secs. 17, 18, 19 and 20, hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, native grasses.</p> <hr/>
	<p>N. 89°59' W., bet. secs. 18 and 19.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 26 E S 18 1/4 ——— S 19</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Cor. is located 55 lks. E. of a wash, 30 ft. wide, 5 ft. deep, drains S.</p>
79.22	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, native grasses.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	S. 89°56' W., bet. secs. 8 and 17.
	Over rolling and broken land.
39.92	Point for the 1/4 sec. cor. of secs. 8 and 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">T 26 N R 26 E S 8 1/4 ——— S 17</p>
	2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.84	The cor. of secs. 7, 8, 17 and 18, hereinbefore described.
	Land, rolling and broken.
	Soil, sand and sandy clay.
	Timber, piñon and juniper; undergrowth, sagebrush, native grasses.
	N. 89°57' W., bet. secs. 7 and 18.
	Over rolling and broken land.
21.60	Apache County Road C427, a graded road, 30 ft. wide, bears N. and S.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">T 26 N R 26 E S 7 1/4 ——— S 18</p>
	2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located 1.60 chs. S. of a trail road, bears ENE and WSW.
79.14	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.

**Survey of a Portion of the Subdivisional Lines,
T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p data-bbox="412 317 1317 432">Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, native grasses.</p> <hr data-bbox="412 464 1430 468"/> <p data-bbox="724 499 1024 520" style="text-align: center;">GENERAL DESCRIPTION</p> <hr data-bbox="412 552 1430 556"/> <p data-bbox="406 590 1446 793">The area surveyed is within the Navajo Indian Reservation, approximately 1 mile south of Ganado, Arizona. The terrain is mostly rolling, except in the northwest portion of the township where there are areas of broken land along mesas and in the valleys. The drainage in the southern portion of the township is south and westerly. The northern portion is northerly and drains into Pueblo Colorado Wash.</p> <p data-bbox="402 831 1446 1005">The elevation varies from 6200 to 6900 feet above sea level. The soil is mostly sand and sandy clay. There are dense stands of piñon and juniper throughout the entire township and some heavy stands of salt cedar and tamarack along the flood plain of Pueblo Colorado Wash. Undergrowth principally consists of sagebrush, rabbit brush, cacti, greasewood and native grasses.</p> <p data-bbox="402 1043 1446 1247">Principal access to the township is provided by U. S. Highway 191, which enters the township in section 35 and runs northerly through the township and exits in section 3. There are some major graded roads and numerous trail roads throughout the township. Much of this area is used for grazing livestock, with numerous permanent home sites through out the township. There is no mining activity in this township.</p> <p data-bbox="402 1285 1446 1367">The mean magnetic declination of 12 1/2° E. was derived from the computer program GEOMAGIX, utilizing the World Magnetic Model for Epoch 2000 for the dates of survey.</p> <hr data-bbox="406 1398 1430 1402"/>
--------	--

CERTIFICATE OF SURVEY

I, Jones Curtiss, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 1st day of May, 2002, I have dependently resurveyed the east and west boundaries and a portion of the subdivisional lines, and surveyed a portion of the subdivisional lines, T. 26 N., R. 26 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

April 06, 2005
(Date)

Jones Curtiss
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the east and west boundaries and a portion of the subdivisional lines, and the survey of a portion of the subdivisional lines, T. 26 N., R. 26 E., Gila and Salt River Meridian, in the State of Arizona, executed by Jones Curtiss, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

April 20, 2005
(Date)

Stephen K. Hansen
(Acting Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 26 N., R. 26 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____~~
~~(Date)~~

~~_____~~
~~(Acting Chief Cadastral Surveyor of Arizona)~~

