

ORIGINAL

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE
DEPENDENT RESURVEY
OF THE SOUTH, EAST, WEST AND NORTH BOUNDARIES
AND THE SUBDIVISIONAL LINES,
THE SUBDIVISION OF CERTAIN SECTIONS
AND THE METES-AND-BOUNDS SURVEY IN SECTION 12
TOWNSHIP 23 NORTH, RANGE 21 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

Dale C. Wilson, Cadastral Surveyor

Under Special Instructions dated April 26, 2004, approved April 26, 2004, and Supplemental Special Instructions dated June 28, 2004, approved June 28, 2004, which provided for the surveys included under Group No. 935, and assignment instructions dated April 26, 2004.

Survey commenced May 10, 2004

Survey completed August 26, 2004

INDEX DIAGRAM

TOWNSHIP 23 NORTH RANGE 21 EAST

28 22 6	27 74 5	26 61 4	25 52 3	24 44 2	24 36 1 16
73 21 7	73 71 8	61 60 9	52 51 10	44 43 11	35 35 12 15
71 20 18	70 69 17	59 58 16	50 49 15	42 41 14	34 33 13 14
68 19 19	67 66 20	58 57 21	49 48 22	40 39 23	32 31 24 14
66 18 30	65 64 29	56 55 28	47 46 27	39 38 26	31 30 25 13
64 18 31 10	63 62 32 9	54 53 33 8	46 45 34 6	37 36 35 5	29 28 36 12 4

Subdivision of Sections 8, 12, 14, 18, 20,
22, 24, 26, 28, 32 and 34
Metes-and Bounds Survey in Section 12

Pages 74-85

Pages 85-86

T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of the south, east, west and north boundaries and the subdivisional lines, the subdivision of certain sections and the metes-and-bounds survey in section 12, T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

The exterior boundaries and the subdivisional lines were surveyed by A. P. Johnson in 1883. A portion of the east boundary and a portion of the subdivisional lines were dependently resurveyed and section 12 was subdivided by Benjamin J. Kinsey in 1938.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated April 26, 2004, and Supplemental Special Instructions dated June 28, 2004, for Group No. 935, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 4700 and 4800 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey's Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) FERNO MESA CORS ARP, FLAGSTAFF 1 CORS ARP and GILA COUNTY CORS ARP. The NAD83 (CORS96) (EPOCH:2002) geographic position of the southeast corner of the township is as follows:

Latitude: 35°20'38.19" N. Longitude: 110°03'18.02" W.

The mean magnetic declination is 13° E.

**Dependent Resurvey of the South Boundary,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

Restoring the survey executed by
A. P. Johnson, in 1883

**Dependent Resurvey of the South Boundary,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS

Beginning at the point for the cor. of Tps. 22 and 23 N., Rs. 21 and 22 E., at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 23 N	
R 21 E	R 22 E
S 36	S 31
S 1	S 6
T 22 N	

2004

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high to the S.

From this cor. point, the cor. of Tps. 22 and 23 N., Rs. 25 and 26 E., bears N. 89°46'20" E., 1912.24 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, encircled with a small collar of stone, mkd. T23N R25E R26E S36 S31 S1 S6 T22N 2003.

Add 2004 to the brass cap.

From this same cor. point, the cor. of secs. 1, 6, 7 and 12, T. 22 N., Rs. 21 and 22 E., bears S. 2°15' W., 79.81 chs. dist., monumented with an embedded mound of stone, 3 ft. base, 1/2 ft. high, no mkd. stone found. This monument is accepted as the best available remaining evidence of the original cor.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N	
R 21 E	R 22 E
S 1	S 6
S 12	S 7

2004

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high to the W.

**Dependent Resurvey of the South Boundary,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>These control lines were fully retraced and careful search was made for evidence of intervening cors., none of which was recovered.</p> <p>N. 89°53' W., bet. secs. 1 and 36.</p> <p>Over nearly level terrain.</p>
40.09	<p>Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 21 E S 36 1/4 ——— S 1 T 22 N</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
48.70	<p>Center of Navajo Route 6, asphalt, 26 ft. wide, bears N. 10° E. and S. 10° W.</p>
80.18	<p>Point for the cor. of secs. 1, 2, 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 21 E S 35 S 36 S 2 S 1 T 22 N</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 89°53' W., bet. secs. 2 and 35.</p> <p>Over nearly level terrain.</p>
40.09	<p>The 1/4 sec. cor. of secs. 2 and 35, monumented with an embedded mound of stone, 1 1/2 ft. diam., flush with surface, no mkd.</p>

**Dependent Resurvey of the South Boundary,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>stone found. This monument is accepted as the best available remaining evidence of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a small collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 23 N R 21 E</p> <p>S 35</p> <p>1/4 ———</p> <p>S 2</p> <p>T 22 N</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 89°59' W., beginning new measurement.</p> <p>Over gently rolling terrain.</p>								
40.09	<p>The cor. of secs. 2, 3, 34 and 35, monumented with an embedded mound of stone, 1 1/2 ft. diam., flush with surface, no mkd. stone found. This monument is accepted as the best available remaining evidence of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a small collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T 23 N R 21 E</td> </tr> <tr> <td style="text-align: center; border-right: 1px solid black;">S 34</td> <td style="text-align: center;">S 35</td> </tr> <tr> <td style="text-align: center; border-right: 1px solid black;">S 3</td> <td style="text-align: center;">S 2</td> </tr> <tr> <td colspan="2" style="text-align: center;">T 22 N</td> </tr> </table> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>West, bet. secs. 3 and 34.</p> <p>Over nearly level terrain.</p>	T 23 N R 21 E		S 34	S 35	S 3	S 2	T 22 N	
T 23 N R 21 E									
S 34	S 35								
S 3	S 2								
T 22 N									

**Dependent Resurvey of the South Boundary,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS											
40.15	<p>The 1/4 sec. cor. of secs. 3 and 34, monumented with an embedded mound of stone, 2 1/2 ft. base, 1/2 ft. high, no mkd. stone found. This monument is accepted as the best available remaining evidence of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, 2 1/2 ft. diam., with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 23 N R 21 E</p> <p style="margin-left: 100px;">S 34</p> <p style="margin-left: 80px;">1/4 ———</p> <p style="margin-left: 100px;">S 3</p> <p>T 22 N</p> <p style="margin-top: 10px;">2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°56' W., beginning new measurement.</p> <p>Over rolling and broken terrain.</p>										
39.68	<p>The cor. of secs. 3, 4, 33 and 34, monumented with a malpais stone, 19 x 11 x 6 ins., mkd. 3 grooves on a face, loosely set in an embedded mound of stone, 2 1/2 ft. base, 1/2 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T 23 N R 21 E</td> </tr> <tr> <td style="text-align: center; border-right: 1px solid black; padding: 0 5px;">S 33</td> <td style="text-align: center; padding: 0 5px;">S 34</td> </tr> <tr> <td style="text-align: center; border-right: 1px solid black; padding: 0 5px;">S 4</td> <td style="text-align: center; padding: 0 5px;">S 3</td> </tr> <tr> <td colspan="2" style="text-align: center;">T 22 N</td> </tr> <tr> <td colspan="2" style="text-align: center; margin-top: 10px;">2004</td> </tr> </table> </div> <p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/>	T 23 N R 21 E		S 33	S 34	S 4	S 3	T 22 N		2004	
T 23 N R 21 E											
S 33	S 34										
S 4	S 3										
T 22 N											
2004											

**Dependent Resurvey of the South Boundary,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS							
41.89	<p>N. 88°56' W., bet. secs. 4 and 33.</p> <p>Over heavily rolling and broken terrain.</p> <p>The 1/4 sec. cor. of secs. 4 and 33, monumented with an embedded mound of stone, 3 ft. base, 1/2 ft. high, no mkd. stone found. This monument is accepted as the best available remaining evidence of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 23 N R 21 E</p> <p style="margin-left: 100px;">S 33</p> <p style="margin-left: 100px;">1/4 ———</p> <p style="margin-left: 100px;">S 4</p> <p style="margin-left: 100px;">T 22 N</p> <p style="margin-left: 100px;">2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/>						
38.72	<p>S. 89°40' W., beginning new measurement.</p> <p>Over gently rolling top of high mesa.</p> <p>The cor. of secs. 4, 5, 32 and 33, monumented with a lava stone, 16 x 12 x 5 ins. mkd. with 4 grooves on E. edge and 2 grooves on W. edge, loosely set, 4 ins. in ground, with a mound of stone, 3 ft. base, 1 ft. high to N.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, encircled with a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 23 N R 21 E</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 32</td> <td style="padding: 0 5px;">S 33</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 5</td> <td style="padding: 0 5px;">S 4</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">T 22 N</td> </tr> </table> <p style="margin-left: 100px;">2004</p> </div> <p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	S 32	S 33	S 5	S 4	T 22 N	
S 32	S 33						
S 5	S 4						
T 22 N							

**Dependent Resurvey of the South Boundary,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.67	<p>Set a steel fence post alongside the stainless steel post.</p> <hr style="width: 80%; margin-left: 0;"/> <p>N. 89°52' W., bet. secs. 5 and 32.</p> <p>Over rolling mesa tops.</p> <p>The 1/4 sec. cor. of secs. 5 and 32, monumented with a sandstone, 20 x 12 x 10 ins., mkd. 1/4 on N. face, set in a mound of stone, 3 ft. base, 1 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 23 N R 21 E S 32 1/4 ——— S 5 T 22 N</p> <p>2004</p> </div> <p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high to the N.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr style="width: 30%; margin-left: 0;"/> <p>N. 89°56' W., beginning new measurement.</p> <p>Over heavily rolling mesas.</p>
40.12	<p>The cor. of secs. 5, 6, 31 and 32, monumented with a mound of stone, 5 ft. base, 2 ft. high, no mkd. stone found. This monument is accepted as the best available remaining evidence of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the South Boundary,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 23 N R 21 E S 31 S 32 ----- S 6 S 5 T 22 N</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>S. 88°53' W., bet. secs. 6 and 31.</p> <p>Over gently rolling high mesa.</p>
<p>41.21</p>	<p>True point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate dist.; there is no remaining evidence of the original cor., point falls in stream bed, 8 ft. wide, 2 ft. deep, drains S. 30° W., from N. 60° E., where it is impracticable to establish a permanent monument.</p> <p>From this point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 6 and 31, bears S. 28°05' E., 0.34 ch. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W C T 23 N R 21 E S 31 1/4 ——— ↑ S 6 T 22 N</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high to the N.</p>
<p>78.39</p>	<p>Point for the cor. of Tps. 22 and 23 N., Rs. 20 and 21 E., at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

**Dependent Resurvey of the South Boundary,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	<div style="text-align: center; margin-bottom: 20px;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 23 N</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R 20 E</td><td style="padding: 0 5px;">R 21 E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 36</td><td style="padding: 0 5px;">S 31</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 1</td><td style="padding: 0 5px;">S 6</td></tr> <tr><td colspan="2">T 22 N</td></tr> </table> </div> <div style="text-align: center; margin-bottom: 20px;">2004</div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. falls on steep S. slope on the SW. side of Malpais Mesa.</p> <p>From this point, the cor. of secs. 13, 18, 19 and 24, T. 22 N., Rs. 20 and 21 E., bears S. 1°47' E., 241.39 chs. dist., monumented with a lava stone, 20 x 10 x 7 ins., firmly set, 10 ins. in the ground, in a mound of stone, 2 ft. base, 1/2 ft. high, no marks found.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-bottom: 20px;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 22 N</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R 20 E</td><td style="padding: 0 5px;">R 21 E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 13</td><td style="padding: 0 5px;">S 18</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 24</td><td style="padding: 0 5px;">S 19</td></tr> </table> </div> <div style="text-align: center; margin-bottom: 20px;">2004</div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this same point, the cor. of secs. 1, 2, 35 and 36, Tps. 22 and 23 N., R. 20 E., bears N. 87°24' W., 82.49 chs. dist., monumented with a basalt stone, 12 x 6 x 4 ins., mkd. with 1 groove on E. face and 5 grooves on W. face, with an embedded mound of stone, 3 ft. diam. alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>	T 23 N		R 20 E	R 21 E	S 36	S 31	S 1	S 6	T 22 N		T 22 N		R 20 E	R 21 E	S 13	S 18	S 24	S 19
T 23 N																			
R 20 E	R 21 E																		
S 36	S 31																		
S 1	S 6																		
T 22 N																			
T 22 N																			
R 20 E	R 21 E																		
S 13	S 18																		
S 24	S 19																		

**Dependent Resurvey of the South Boundary,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 23 N	R 20 E
S 35	S 36
S 2	S 1
T 22 N	

2004

Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high to the N.

These control lines were fully retraced and careful search was made for evidence of intervening cors., none of which was recovered.

**Dependent Resurvey of the East Boundary,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

Restoring the survey executed by A. P. Johnson, in 1883
and the resurvey executed by Benjamin J. Kinsey, in 1938

From the cor. of Tps. 22 and 23 N., Rs. 21 and 22 E., hereinbefore described.

N. 0°02' W., bet. secs. 31 and 36.

Over nearly level terrain.

39.88 Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 N	
1/4	
R 21 E	R 22 E
S 36	S 31

2004

Deposit a magnet in a white plastic case at the base of the stainless steel post.

79.76 Point for the cor. of secs. 25, 30, 31 and 36, at proportionate dist.; there in no remaining evidence of the original cor.

**Dependent Resurvey of the East Boundary,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 23 N</td></tr> <tr><td style="border-right: 1px solid black; padding: 2px 10px;">R 21 E</td><td style="padding: 2px 10px;">R 22 E</td></tr> <tr><td style="border-right: 1px solid black; padding: 2px 10px;">S 25</td><td style="padding: 2px 10px;">S 30</td></tr> <tr style="border-top: 1px solid black;"><td style="border-right: 1px solid black; padding: 2px 10px;">S 36</td><td style="padding: 2px 10px;">S 31</td></tr> </table> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 0°02' W., bet. secs. 25 and 30.</p> <p>Over nearly level terrain.</p>	T 23 N		R 21 E	R 22 E	S 25	S 30	S 36	S 31
T 23 N									
R 21 E	R 22 E								
S 25	S 30								
S 36	S 31								
39.88	<p>Point for the 1/4 sec. cor. of secs. 25 and 30, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 23 N</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="border-right: 1px solid black; padding: 2px 10px;">R 21 E</td><td style="padding: 2px 10px;">R 22 E</td></tr> <tr><td style="border-right: 1px solid black; padding: 2px 10px;">S 25</td><td style="padding: 2px 10px;">S 30</td></tr> </table> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 23 N		1/4		R 21 E	R 22 E	S 25	S 30
T 23 N									
1/4									
R 21 E	R 22 E								
S 25	S 30								
79.76	<p>The cor. of secs. 19, 24, 25 and 30, monumented with a limestone, 22 x 9 x 3 ins., mkd. 4 grooves on SW face, firmly set, 16 ins. in ground, in a mound of stone, 2 ft. base, 1/2 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 23 N</td></tr> <tr><td style="border-right: 1px solid black; padding: 2px 10px;">R 21 E</td><td style="padding: 2px 10px;">R 22 E</td></tr> <tr><td style="border-right: 1px solid black; padding: 2px 10px;">S 24</td><td style="padding: 2px 10px;">S 19</td></tr> <tr style="border-top: 1px solid black;"><td style="border-right: 1px solid black; padding: 2px 10px;">S 25</td><td style="padding: 2px 10px;">S 30</td></tr> </table> <p>2004</p> </div>	T 23 N		R 21 E	R 22 E	S 24	S 19	S 25	S 30
T 23 N									
R 21 E	R 22 E								
S 24	S 19								
S 25	S 30								

**Dependent Resurvey of the East Boundary,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS									
39.99	<p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 0°09' E., bet. secs. 19 and 24.</p> <p>Over gently rolling terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 23 N</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R 21 E</td><td style="padding: 0 5px;">R 22 E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 24</td><td style="padding: 0 5px;">S 19</td></tr> </table> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high to the W.</p>	T 23 N		1/4		R 21 E	R 22 E	S 24	S 19
T 23 N									
1/4									
R 21 E	R 22 E								
S 24	S 19								
79.98	<p>Point for the cor. of secs. 13, 18, 19 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 23 N</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R 21 E</td><td style="padding: 0 5px;">R 22 E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 13</td><td style="padding: 0 5px;">S 18</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 24</td><td style="padding: 0 5px;">S 19</td></tr> </table> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 0°09' E., bet. secs. 13 and 18.</p> <p>Over gently rolling terrain.</p>	T 23 N		R 21 E	R 22 E	S 13	S 18	S 24	S 19
T 23 N									
R 21 E	R 22 E								
S 13	S 18								
S 24	S 19								
39.99	<p>The 1/4 sec. cor. of secs. 13 and 18, monumented with an embedded mound of stone, 2 ft. base, 1/2 ft. high, no mkd. stone found. This monument is accepted as the best available remaining evidence of the original cor.</p>								

**Dependent Resurvey of the East Boundary,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 23 N 1/4 R 21 E R 22 E S 13 S 18</p> </div> <p style="text-align: center; margin: 10px 0;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°45' W., beginning new measurement.</p> <p>Ascend steep precipitous south slope of Bidahochi Butte.</p>
45.18	<p>The cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 2 ins. diam., firmly set, projecting 19 ins. above ground, in a mound of stone, 4 1/2 ft. base, 1 ft. high, with brass cap mkd. T23N R21E R22E S12 S7 S13 S18 1883 1938.</p> <p>Add the marks 2004 to the brass cap.</p> <p>From this cor. point, a cor. established by the Soil Conservation Service in 1937, bears S. 3°32' E., 5.05 chs. dist., monumented with a basalt stone, firmly set, projecting 10 x 9 x 7 ins. above ground, mkd. S18 on SE. face, 13 on SW. face and 12 on NW. face, with a mound of stone, 2 ft. base, 1 ft. high to the S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°39' E., bet. secs. 7 and 12.</p> <p>Descend, steep, precipitous north slope of Bidahochi Butte.</p>
37.40	<p>Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate dist., falls on an inaccessible, near vertical N. slope; there is no remaining evidence of the original cor.</p> <p>From this point, the point selected for a witness cor. bears N. 60°08' E., 1.54 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>


**Dependent Resurvey of the East Boundary,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS

40.53

Point for the cor. of Tps. 23 and 24 N., Rs. 21 and 22 E. at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.




2004

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high to the S.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the cor. of secs. 25, 30, 31 and 36, T. 24 N., Rs. 21 and 22 E. bears N. 0°19' W., 81.06 chs. dist., monumented with an embedded mound of stone, 3 1/2 ft. base, 1 ft. high, no mkd. stone found. This monument is accepted as the best available remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



2004

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high to the W.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

This control lines was fully retraced and careful search was made for evidence of intervening cors., none of which was recovered.

**Dependent Resurvey of the West Boundary,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

Restoring the survey executed by
A. P. Johnson, in 1883

Dependent Resurvey of the West Boundary,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>From the cor. of Tps. 22 and 23 N., Rs. 20 and 21 E., hereinbefore described.</p> <p>N. 0°13' E., bet. secs. 31 and 36.</p> <p>Over steep, broken terrain along the W. slopes of Malpais Mesa.</p> <p>40.21 True point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate dist., falls on an inaccessible steep SW. cut bank of wash, drains N. 50° W.; there is no remaining evidence of the original cor.</p> <p>From this point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 31 and 36, bears N. 48°42' E., 0.77 ch. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <pre> WC T 23 N 1/4 R 20 E R 21 E S 36 S 31 ↙ 2004 </pre> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>80.42 The cor. of secs. 25, 30, 31 and 36, monumented with a basalt stone, 15 x 11 x 5 ins., firmly set, 10 ins. in the ground, no marks visible, with an embedded mound of stone, 1 ft. base, 1/2 ft. high to the W. and a steel fence post projecting 19 ins. above ground.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <pre> T 23 N R 20 E R 21 E S 25 S 30 ----- S 36 S 31 </pre> <p style="text-align: center;">2004</p> </div> <p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 0°11' E., bet. secs. 25 and 30.</p>
--------	---

Dependent Resurvey of the West Boundary,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Over gently rolling terrain.</p> <p>39.86 True point for the 1/4 sec. cor. of secs. 25 and 30 at proportionate dist., falls in a wash, 2 chs. wide, drains S.; there is no remaining evidence of the original cor.</p> <p>From this point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 25 and 30, bears N. 73°31' E., 1.85 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>WC T 23 N 1/4 R 20 E R 21 E S 25 S 30</p> <p>↙</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>79.72 Point for the cor. of secs. 19, 24, 25 and 30, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 23 N R 20 E R 21 E S 24 S 19 ----- S 25 S 30</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, a basalt stone, 20 x 7 x 4 ins., firmly set 10 ins. in the ground, in a small mound of stone, 1 1/2 ft. base, 1/2 ft. high, with a reinforcement rod, 3/8 in. diam., set alongside, projecting 4 ins. above ground,, bears N. 12°34' E., 2.17 chs. dist. This monument is of unknown origin and is not accepted as a corner of this survey.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>N. 0°11' E., bet. secs. 19 and 24.</p>
--------	--

Dependent Resurvey of the West Boundary,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over gently rolling terrain.
39.86	Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 23 N 1/4 R 20 E R 21 E S 24 S 19</p>
	2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
45.05	Center of asphalt, Navajo Route 15, 26 ft. wide, bears E. and W.
79.72	Point for the cor. of secs. 13, 18, 19 and 24, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 23 N R 20 E R 21 E S 13 S 18 S 24 S 19</p>
	2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Set a steel fence post alongside the stainless steel post.
	N. 0°11' E., bet. secs. 13 and 18.
	Over gently rolling terrain.
39.86	The 1/4 sec. cor. of secs. 13 and 18, monumented with a basalt stone, 22 x 10 x 3 ins., firmly set, 10 ins. in the ground, plainly mkd. 1/4 on W. face, with a mound of stone, 1 1/2 ft. base, 1/2 ft. high to the W.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the West Boundary,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 23 N 1/4 R 20 E R 21 E S 13 S 18</p> <p style="text-align: center;">2004</p> <p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 0°02' W., beginning new measurement.</p> <p>Over rolling terrain through scattered juniper.</p>
40.13	<p>Point for the cor. of secs. 7, 12, 13 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E R 21 E S 12 S 7 S 13 S 18</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high to the W.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/>
40.13	<p>N. 0°02' W., bet. secs. 7 and 12.</p> <p>Over heavily rolling and broken terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the West Boundary,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 23 N 1/4 R 20 E R 21 E S 12 S 7</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>80.26 The cor. of secs. 1, 6, 7 and 12, monumented with a conglomerate stone, 14 x 10 x 2 ins., loosely set, 2 ins. in the ground, no marks visible, with an embedded mound of stone, 1 1/2 ft. base, 1 ft. high to the W.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E R 21 E S 1 S 6 S 12 S 7</p> <p style="text-align: center;">2004</p> <p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Rebuild the mound of stone, 2 ft. base, 1 ft. high to the W.</p> <hr/>
	<p>N. 0°22' W., bet. secs. 1 and 6.</p> <p>Over gently rolling terrain, through scattered juniper.</p> <p>40.76 The 1/4 sec. cor. of secs. 1 and 6, monumented with a basalt stone, 13 x 13 x 6 ins. plainly mkd. 1/4 on W. face, set in an embedded mound of stone, 4 ft. base, 1 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bed rock, encircled with a mound of stone, 4 1/2 ft. base to top, with brass cap mkd.</p>

**Dependent Resurvey of the West Boundary,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 23 N
1/4
R 20 E | R 21 E
S 1 | S 6

2004

Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.

N. 0°24' E., beginning new measurement.

Over rolling terrain, through scattered juniper.

39.78

The cor. of Tps. 23 and 24 N., Rs. 20 and 21 E., monumented with a conglomerate stone, 17 x 17 x 5 ins. plainly mkd. with 6 grooves on E. and W. faces and faint chisel marks on N. and S. edges, firmly set, 6 ins. in the ground, in a mound of stone, 4 ft. base, 1 ft. high.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, encircled with a mound of stone, 5 ft. base, to top, with brass cap mkd.

T 24 N
R 20 E | R 21 E
S 36 | S 31
S 1 | S 6
T 23 N

2004

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Incorporate the original stone in the supporting mound of stone.

**Dependent Resurvey of the North Boundary,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

Restoring the survey executed by
A. P. Johnson, in 1883

Dependent Resurvey of the North Boundary,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of Tps. 23 and 24 N., Rs. 21 and 22 E., hereinbefore described.</p>
	<p>S. 89°49' W., bet. secs. 1 and 36.</p>
	<p>Over nearly level terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;"> T 24 N R 21 E S 36 1/4 ——— S 1 T 23 N </p>
	<p style="text-align: center;">2004</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
48.40	<p>Center of asphalt, Navajo Route 6, 26 ft. wide, bears N. and S.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;"> T 24 N R 21 E S 35 S 36 ———— S 2 S 1 T 23 N </p>
	<p style="text-align: center;">2004</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<hr/> <p>S. 89°49' W., bet. secs. 2 and 35.</p>
	<p>Over nearly level terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the North Boundary,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 21 E S 35 1/4 ——— S 2 T 23 N 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	The cor. of secs. 2, 3, 34 and 35, determined at the corner of fences, extending S. and W. This position is accepted as the best available remaining evidence of the original cor. position. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 24 N R 21 E S 34 S 35 S 3 S 2 T 23 N 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	<hr/> S. 89°57' W., bet. secs. 3 and 34. Over rolling terrain through scattered juniper.
40.10	Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 24 N R 21 E S 34 1/4 ——— S 3 T 23 N 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Dependent Resurvey of the North Boundary,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS																			
80.20	<p>Cor. falls 6 ft. S. of a fence, bears E. and meandering W.</p> <p>The cor. of secs. 3, 4, 33 and 34, determined at the corner of fences, extending E. and S. This position is accepted as the best available evidence of the original cor. position.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td>T 24 N</td><td>R 21 E</td></tr> <tr><td>S 33</td><td>S 34</td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td colspan="2">T 23 N</td></tr> </table> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 89°43' W., bet. secs. 4 and 33.</p> <p>Over heavily rolling terrain through scattered juniper.</p>	T 24 N	R 21 E	S 33	S 34	S 4	S 3	T 23 N											
T 24 N	R 21 E																		
S 33	S 34																		
S 4	S 3																		
T 23 N																			
40.59	<p>Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate dist., falls on an abrupt W. periphery of a cut bank of wash; there is no remaining evidence of the original cor.</p> <p>From this point, the point selected for a witness cor. bears S. 86°44' W., 0.58 ch. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td></td><td>WC</td><td></td></tr> <tr><td>T 24 N</td><td>R 21 E</td><td>↗</td></tr> <tr><td></td><td>S 33</td><td></td></tr> <tr><td></td><td>1/4</td><td>—</td></tr> <tr><td></td><td>S 4</td><td></td></tr> <tr><td></td><td>T 23 N</td><td></td></tr> </table> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>		WC		T 24 N	R 21 E	↗		S 33			1/4	—		S 4			T 23 N	
	WC																		
T 24 N	R 21 E	↗																	
	S 33																		
	1/4	—																	
	S 4																		
	T 23 N																		
81.18	<p>The cor. of secs. 4, 5, 32 and 33, monumented with an embedded mound of stone, 3 ft. base, 1 ft. high, no mkd. stone found. This monument is accepted as the best available remaining evidence of the original cor.</p>																		

**Dependent Resurvey of the North Boundary,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS											
	<p>At the corner point</p>										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, encircled with a mound of stone, 4 ft. base to top, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 24 N</td><td>R 21 E</td></tr> <tr><td>S 32</td><td>S 33</td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td colspan="2">T 23 N</td></tr> </table>	T 24 N	R 21 E	S 32	S 33	S 5	S 4	T 23 N			
T 24 N	R 21 E										
S 32	S 33										
S 5	S 4										
T 23 N											
	<p style="text-align: center;">2004</p>										
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>										
	<hr/> <p>West, bet. secs. 5 and 32.</p>										
	<p>Over heavily rolling high mesa.</p>										
<p>40.23</p>	<p>Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p>										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground to bedrock, encircled with a mound of stone, 4 ft. base to top, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 24 N</td><td>R 21 E</td></tr> <tr><td>S 32</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 5</td><td></td></tr> <tr><td colspan="2">T 23 N</td></tr> </table>	T 24 N	R 21 E	S 32		1/4	—	S 5		T 23 N	
T 24 N	R 21 E										
S 32											
1/4	—										
S 5											
T 23 N											
	<p style="text-align: center;">2004</p>										
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>										
<p>80.46</p>	<p>Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p>										
	<p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in solid rock, with top mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 24 N</td><td>R 21 E</td></tr> <tr><td>S 31</td><td>S 32</td></tr> <tr><td>S 6</td><td>S 5</td></tr> <tr><td colspan="2">T 23 N</td></tr> </table>	T 24 N	R 21 E	S 31	S 32	S 6	S 5	T 23 N			
T 24 N	R 21 E										
S 31	S 32										
S 6	S 5										
T 23 N											
	<p style="text-align: center;">2004</p>										

**Dependent Resurvey of the North Boundary,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
<p>40.23</p>	<p>Deposit a magnet in a white plastic case at the base of the brass stem.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high to the N.</p> <hr/> <p>West, bet. secs. 6 and 31.</p> <p>Over rolling and broken terrain, through scattered juniper.</p> <p>Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to bedrock, encircled with a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p align="center">T 24 N R 21 E S 31 1/4 ——— S 6 T 23 N</p> <p align="center">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
<p>75.94</p>	<p>The cor. of Tps. 23 and 24 N., Rs. 20 and 21 E., hereinbefore described.</p> <hr/> <p align="center">Dependent Resurvey of the Subdivisional Lines, T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona</p> <hr/>
<p>39.94</p>	<p align="center">Restoring the survey executed by A. P. Johnson, in 1883 and the resurvey executed by Benjamin J. Kinsey, in 1938</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>North, bet. secs. 35 and 36.</p> <p>Over nearly level terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p style="text-align: center;">T 23 N R 21 E 1/4 S 35 S 36</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.88	<p>Point for the cor. of secs. 25, 26, 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E S 26 S 25 S 35 S 36</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°48' W., bet. secs. 25 and 36.</p> <p>Over nearly level terrain.</p>
36.60	<p>Center of asphalt, Navajo Route 6, 26 ft. wide, bears N. 5° E. and S. 5° W.</p>
40.06	<p>Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E S 25 1/4 ——— S 36</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.12	<p>The cor. of secs. 25, 26, 35 and 36.</p> <hr/> <p>N. 0°01' E., bet. secs. 25 and 26.</p> <p>Over nearly level terrain.</p>
39.94	<p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E 1/4 S 26 S 25</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high to the W.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
79.88	<p>The cor. of secs. 23, 24, 25 and 26, monumented with a basalt stone, 14 x 10 x 9 ins., plainly mkd. 1 groove on E. face and 2 grooves on S. face, firmly set, 5 ins. in the ground in an embedded mound of stone, 2 ft. base, 1 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E S 23 S 24 S 26 S 25</p> <p style="text-align: center;">2004</p> <p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high to the W.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°43' W., bet. secs. 24 and 25.</p> <p>Over gently rolling terrain.</p>
39.45	Center of asphalt, Navajo Route 6, 26 ft. wide, bears S. 35° E. and N. 35° W.
40.02	<p>Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 21 E</p> <p>S 24</p> <p>1/4 ———</p> <p>S 25</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 1 1/2 ft. base, 1 ft. high to the N.</p> <p>Cor. falls on the westerly shoulder of Navajo Route 6.</p>
80.04	<p>The cor. of secs. 23, 24, 25 and 26.</p> <hr/> <p>N. 0°10' W., bet. secs. 23 and 24.</p> <p>Over nearly level terrain.</p>
39.89	<p>The 1/4 sec. cor. of secs. 23 and 24, monumented with a basalt stone, 20 x 8 x 7 ins., plainly mkd. 1 on E. face, firmly set, 10 ins. in the ground, with an embedded mound of stone, 2 ft. base, 1/2 ft. high to the W.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 21 E</p> <p>1/4</p> <p>S 23 S 24</p> <p>2004</p> </div>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS							
40.19	<p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high to the W.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°04' E., beginning new measurement.</p> <p>Over nearly level terrain.</p> <p>The cor. of secs. 13, 14, 23 and 24, monumented with a lava stone, 17 x 8 x 5 ins., plainly mkd. 3 grooves on S. face, firmly set, 17 ins. in the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="padding: 0 5px;">T 23 N</td> <td style="padding: 0 5px;">R 21 E</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 14</td> <td style="padding: 0 5px;">S 13</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 23</td> <td style="padding: 0 5px;">S 24</td> </tr> </table> </div> <p style="text-align: center; margin: 5px 0;">2004</p> <p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°58' W., bet. secs. 13 and 24.</p> <p>Over gently rolling terrain.</p>	T 23 N	R 21 E	S 14	S 13	S 23	S 24
T 23 N	R 21 E						
S 14	S 13						
S 23	S 24						
40.07	<p>The 1/4 sec. cor. of secs. 13 and 24, monumented with a volcanic stone, 15 x 11 x 8 ins., mkd. /4 on N. face, firmly set, 5 ins. below the surface, with an embedded mound of stone, 3 ft. base, flush with surface to the N.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>						

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>T 23 N R 21 E S 13 1/4 _____ S 24 2004</p>
	<p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>N. 89°15' W., beginning new measurement.</p> <p>Over gently rolling terrain.</p>
5.30	Center of asphalt, Navajo Route 6, 26 ft. wide, bears N. and S.
40.23	The cor. of secs. 13, 14, 23 and 24.
	<hr style="width: 60%; margin: 10px auto;"/> <p>N. 0°10' E., bet. secs. 13 and 14.</p> <p>Over gently rolling terrain.</p>
40.13	<p>The 1/4 sec. cor. of secs. 13 and 14, monumented with an iron post, 1 in. diam., firmly set flush with the surface, with brass cap mkd. 1/4 S14 S13 1883 1938, with a mound of stone, 1 1/2 ft. base, 1 ft. high to the W.</p> <p>Add the marks T23N R21E 2004 to the brass cap.</p> <p>Set a steel fence post alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>N. 0°09' W., beginning new measurement.</p> <p>Over gently rolling terrain.</p>
15.20	Center of asphalt, Navajo Route 15, 26 ft. wide, bears N. 65° E. and S. 65° W.
39.73	<p>The cor. of secs. 11, 12, 13 and 14, reestablished at proportionate dist. by Ronald P. Matkin, Arizona Registered Professional Land Surveyor No. 16165, in 2002, monumented with a reinforcement rod, 5/8 in. diam., 38 ins. long, set 4 ins. below the surface in an embedded mound of stone, 2 ft. base, flush with surface, with aluminum cap inscribed RM ENG LS 16165 and mkd. T23N R21E S11 S12 S14 S13. This position is accepted as a careful and faithful reestablishment of the original corner position.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS							
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="820 512 1047 611"> <tr> <td>T 23 N</td> <td>R 21 E</td> </tr> <tr> <td>S 11</td> <td>S 12</td> </tr> <tr> <td>S 14</td> <td>S 13</td> </tr> </table> <p>2004</p> <p>Bury the reinforcement rod alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high to the N.</p> <p>Set a steel fence post alongside the stainless steel post.</p>	T 23 N	R 21 E	S 11	S 12	S 14	S 13
T 23 N	R 21 E						
S 11	S 12						
S 14	S 13						
	<hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 86°35' W., bet. secs. 12 and 13.</p> <p>Descend over very steep, broken W. slope of Bidahochi Butte.</p>						
<p>39.96</p>	<p>The 1/4 sec. cor. of secs. 12 and 13, monumented with an iron post, 1 in. diam., firmly set, projecting 28 ins. above ground, with brass cap mkd. 1/4 S12 S13 1883 1938.</p> <p>Raise a supporting mound of stone, 3 1/2 ft. base, 2 1/2 ft. high.</p> <p>Add the marks T23N R21E 2004 to the brass cap.</p> <p>Set a steel fence post alongside the iron post.</p>						
	<p>From this cor. point, a cor. established by the Soil Conservation Service in 1937, bears S. 3°17' E., 2.57 chs. dist., monumented with a sandstone, 14 x 7 x 4 ins., fragmented into 7 pieces laying loose on steep S. slope with one piece 7 x 5 x 1 ins. mkd. 13 on a face.</p>						
	<hr/> <p>S. 86°31' W., beginning new measurement.</p> <p>Over rolling and broken W. slope.</p>						
<p>4.60</p>	<p>Center of asphalt, Navajo Route 6, 26 ft. wide, bears N. and S.</p>						
<p>39.96</p>	<p>The cor. of secs. 11, 12, 13 and 14.</p> <hr/>						

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.74	<p>N. 0°33' E., bet. secs. 11 and 12.</p> <p>Over gently rolling terrain.</p> <p>The 1/4 sec. cor. of secs. 11 and 12, determined to the E. of an embedded mound of stone, 2 1/2 ft. base, 1 ft. high. This mound and position are consistent and in harmony with existing original evidence throughout this township and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E 1/4 S 11 S 12</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Rebuild the mound of stone, 2 1/2 ft. base, 1 1/2 ft. high to the W.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/>
39.68	<p>N. 0°06' W., beginning new measurement.</p> <p>Over nearly level terrain.</p> <p>The cor. of secs. 1, 2, 11 and 12, monumented with an iron post, 2 ins. diam., firmly set projecting 5 ins. above ground in a mound of stone, 3 ft. base, 1/2 ft. high, with brass cap mkd. T23N R21E S2 S1 S11 S12 1883 1938.</p> <p>Add the marks 2004 to the brass cap.</p> <p>Set a steel fence post alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°53' W., bet. secs. 1 and 12.</p> <p>Over gently rolling terrain.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.16	<p>The 1/4 sec. cor. of secs. 1 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. 1/4 S1 S12 1883 1938.</p> <p>Add the marks T23N R21E 2004 to the brass cap.</p> <p>Set a steel fence post alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°51' W., beginning new measurement.</p> <p>Over gently rolling terrain.</p>
6.80	Center of asphalt, Navajo Route 6, 26 ft. wide, bears N. and S.
40.15	<p>The cor. of secs. 1, 2, 11 and 12.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 0°01' E., bet. secs. 1 and 2.</p> <p>Over gently rolling terrain.</p>
40.27	<p>Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 23 N R 21 E</p> <p>1/4</p> <p>S 2 S 1</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.65	<p>The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., hereinbefore described.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°10' W., bet. secs. 34 and 35.</p> <p>Over gently rolling terrain.</p>
40.12	<p>The 1/4 sec. cor. of secs. 34 and 35, monumented with an embedded mound of stone, 2 ft. base, 1/2 ft. high, no mkd. stone found. This monument is accepted as the best available remaining evidence of the original cor.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E 1/4 S 34 S 35 2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°14' E., beginning new measurement.</p> <p>Over gently rolling terrain.</p>
<p>39.98</p>	<p>Point for the cor. of secs. 26, 27, 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E S 27 S 26 S 34 S 35 2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 1 1/2 ft. high to the W.</p> <hr style="width: 20%; margin: auto;"/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 89°48' W., bet. secs. 26 and 35.</p> <p>Over nearly level terrain.</p>
<p>40.06</p>	<p>Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">T 23 N R 21 E S 26 1/4 ——— S 35</p> <p align="center">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
80.12	<p>The cor. of secs. 26, 27, 34 and 35.</p> <hr/> <p>N. 0°04' E., bet. secs. 26 and 27.</p> <p>Over nearly level terrain.</p>
39.98	<p>The 1/4 sec. cor. of secs. 26 and 27, monumented with a malpais stone, 14 x 10 x 9 ins., no marks visible, firmly set, 10 ins. in the ground, with an embedded mound of stone, 1 1/2 ft. base, 1/2 ft. high to the W.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p align="center">T 23 N R 21 E 1/4 S 27 S 26</p> <p align="center">2004</p> <p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Rebuild the mound of stone, 1 1/2 ft. base, 1 ft. high to the W.</p> <hr/> <p>N. 0°05' E., beginning new measurement.</p> <p>Over gently rolling terrain.</p>
40.01	<p>Point for the cor. of secs. 22, 23, 26 and 27, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<div style="text-align: center;"> <table border="1"> <tr> <td>T 23 N</td> <td>R 21 E</td> </tr> <tr> <td>S 22</td> <td>S 23</td> </tr> <tr> <td>S 27</td> <td>S 26</td> </tr> </table> <p>2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 89°45' W., bet. secs. 23 and 26.</p> <p>Over gently rolling ground.</p> </div>	T 23 N	R 21 E	S 22	S 23	S 27	S 26		
T 23 N	R 21 E								
S 22	S 23								
S 27	S 26								
40.20	<p>The 1/4 sec. cor. of secs. 23 and 26, monumented with an embedded mound of stone, 2 ft. base, 1 ft. high, no mkd. stone found. This monument is accepted as the best available remaining evidence of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 23 N</td> <td>R 21 E</td> </tr> <tr> <td></td> <td>S 23</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td></td> <td>S 26</td> </tr> </table> <p>2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 89°43' W., beginning new measurement.</p> <p>Over nearly level terrain.</p> </div>	T 23 N	R 21 E		S 23	1/4	_____		S 26
T 23 N	R 21 E								
	S 23								
1/4	_____								
	S 26								
39.83	<p>The cor. of secs. 22, 23, 26 and 27.</p> <hr/> <p>N. 0°33' W., bet. secs. 22 and 23.</p> <p>Over gently rolling terra firma.</p>								

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.01	<p>The 1/4 sec. cor. of secs. 22 and 23, monumented with a basalt stone, 17 x 9 x 6 ins., plainly mkd. 1/4 on S. face and an A on E. face, firmly set, 9 ins. in the ground, with a mound of stone, 2 1/2 ft. base, 1/2 ft. high to the W.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E 1/4 S 22 S 23</p> <p style="text-align: center;">2004</p> <p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°01' W., beginning new measurement.</p> <p>Over rolling and broken terrain.</p>
40.05	<p>The cor. of secs. 14, 15, 22 and 23, monumented with a basalt stone, 18 x 11 x 5 ins., plainly mkd. 3 notches on S. edge, firmly set, 10 ins. in the ground, with a mound of stone, 1 1/2 ft. base, 1/2 ft. high to the W.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E S 15 S 14 S 22 S 23</p> <p style="text-align: center;">2004</p> <p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Rebuild the mound of stone, 2 ft. base, 1 ft. high to the W.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of secs. 13, 14, 23 and 24.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>N. 89°33' W., bet. secs. 14 and 23.</p> <p>Over rolling and broken terrain.</p>
40.32	<p>The 1/4 sec. cor. of secs. 14 and 23, monumented with a malpais stone, 13 x 9 x 5 ins., no marks visible, firmly set 10 ins. in the ground, with an embedded mound of stone, 1 1/2 ft. base, 1/2 ft. high to the N.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 21 E</p> <p>S 14</p> <p>1/4 ———</p> <p>S 23</p> <p>2004</p> </div> <p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>N. 89°57' W., beginning new measurement.</p> <p>Over undulating terra firma.</p>
40.03	<p>The cor. of secs. 14, 15, 22 and 22.</p> <hr style="width: 80%; margin: 10px auto;"/>
	<p>N. 0°19' E., bet. secs. 14 and 15.</p> <p>Over rolling terrain.</p>
23.20	<p>Center of asphalt, Navajo Route 15, 26 ft. wide, bears N. 80° E. and S. 80° W.</p>
39.82	<p>Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate dist.; falls on the E. edge of a small mound of stone, with a lava stone, 16 x 9 x 4 ins., lying loose nearby, plainly mkd. 1/4 on a face.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 21 E 1/4 S 15 S 14 2004
	Bury the stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post. Raise a mound of stone, 3 ft. base, 1 ft. high to the W.
79.64	The cor. of secs. 10, 11, 14 and 15, monumented with a lava stone, 16 x 6 x 4 ins., plainly mkd. 2 grooves on E. face and 1 groove on S. face, firmly set, 10 ins. in the ground, in a mound of stone, 3 ft. base, 1 ft. high. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled by a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T 23 N R 21 E S 10 S 11 S 15 S 14 2004
	Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.
	<hr/> From the cor. of secs. 11, 12, 13, and 14. N. 89°52' W., bet. secs. 11 and 14. Over gently rolling blow sand.
39.92	The 1/4 sec. cor. of sec. 11 and 14, monumented with an iron post, 1 in. diam., set 5 ins. below the surface, with brass cap mkd. 1/4 S11 S14 1883 1938. Add the marks T23N R21E 2004 to the brass cap. Cor. is located 2 lks. N. of railroad tie fence post, projecting 5 ft. high in a fence, bears E. and W.
	<hr/> N. 89°58' W., beginning new measurement. Over rolling terrain through scattered juniper.

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.99	<p>The cor. of sec. 10, 11, 14 and 15.</p> <hr/> <p>N. 0°18' E., bet. secs. 10 and 11.</p> <p>Over rolling terrain through scattered juniper.</p>
39.81	<p>The 1/4 sec. cor. of secs. 10 and 11, monumented with a lava stone, 12 x 9 x 4 ins., mkd. 1 on top, firmly set, 4 ins. in the ground, in a mound of stone, 3 ft. base, 1 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E 1/4 S 10 S 11 2004</p> <p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>
40.17	<p>N. 0°17' E., beginning new measurement.</p> <p>Over rolling terrain through scattered juniper.</p> <p>The cor. of secs. 2, 3, 10 and 11, monumented with a basalt stone, 10 x 6 x 2 ins., mkd. 5 grooves on S. face and 2 grooves on E. face, set 10 ins. below the surface on the N. side of a fence corner post, with dilapidated fences extending N., S., E. and W., with a mound of stone, 2 ft. base, 1 ft. high, to the W.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E S 3 S 2 S 10 S 11 2004</p> <p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.07	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°37' W., bet. secs. 2 and 11.</p> <p>Over rolling terrain through scattered juniper.</p> <p>The 1/4 sec. cor. of secs. 2 and 11, monumented with a mound of stone, 2 ft. base, 1 ft. high, no mkd. stone found. This monument is accepted as the best available remaining evidence of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 21 E</p> <p>S 2</p> <p>1/4 ———</p> <p>S 11</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high to the N.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°23' W., beginning new measurement.</p> <p>Over heavily rolling terrain through juniper.</p>
39.72	<p>The cor. of secs. 2, 3, 10 and 11.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 0°09' W., bet. secs. 2 and 3.</p> <p>Over heavily rolling terrain through scattered juniper.</p>
39.91	<p>Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 21 E</p> <p>1/4</p> <p>S 3 S 2</p> <p>2004</p> </div>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.71	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. falls 10 lks. E. of a fence, meandering N. and S.</p> <p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., hereinbefore described.</p>
40.01	<p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°24' W., bet. sec. 33 and 34.</p> <p>Over rolling and broken E. slope of Malpais Mesa.</p>
40.02	<p>The 1/4 sec. cor. of secs. 33 and 34, monumented with a deeply embedded mound of stone, 3 ft. base, 1 ft. high, no mkd. stone found, with a 5/8 in. reinforcement rod, 14 ins. long, firmly set, projecting 2 ins. above ground in the center. This monument is accepted as the best available remaining evidence of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 21 E</p> <p>1/4</p> <p>S 33 S 34</p> <p>2004</p> </div> <p>Bury the reinforcement rod alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high to the W.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
40.02	<p>N. 0°03' W., beginning new measurement.</p> <p>Over rolling terrain.</p> <p>Point for the cor. of secs. 27, 28, 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 23 N R 21 E S 28 S 27 S 33 S 34</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 26, 27, 33 and 34.</p> <p>N. 89°54' W., bet. secs. 27 and 34.</p> <p>Over gently rolling terrain.</p>
40.22	<p>The 1/4 sec. cor. of secs. 27 and 34, monumented with an embedded mound of stone, 3 ft. base, 1/2 ft. high, no mkd. stone found. This monument is accepted as the best available remaining evidence of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 23 N R 21 E S 27 1/4 ——— S 34</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>S. 89°46' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
39.96	<p>The cor. of secs. 27, 28, 33 and 34.</p> <hr/> <p>N. 0°16' E., bet. secs. 27 and 28.</p> <p>Over gently rolling terrain.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.02	<p>Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E 1/4 S 28 S 27 2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
80.04	<p>Point for the cor. of secs. 21, 22, 27 and 28, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E S 21 S 22 S 28 S 27 2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S. 89°58' W., bet. secs. 22 and 27.</p> <p>Over rolling terrain.</p>
39.95	<p>Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">T 23 N R 21 E S 22 1/4 ——— S 27</p> <p align="center">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
79.90	<p>The cor. of secs. 21, 22, 27 and 28.</p> <hr/>
	<p>N. 0°55' W., bet. secs. 21 and 22.</p> <p>Over rolling and broken terrain.</p>
40.03	<p>The 1/4 sec. cor. of secs. 21 and 22, monumented with a deeply embedded mound of stone, 3 ft. base, 1 ft. high, no mkd. stone found. This monument is accepted as the best available remaining evidence of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 23 N R 21 E 1/4 S 21 S 22</p> <p align="center">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high to the W.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/>
	<p>N. 0°05' E., beginning new measurement.</p> <p>Over gently rolling terrain.</p>
40.13	<p>The cor. of secs. 15, 16, 21 and 22, monumented with a basalt stone, 13 x 8 x 5 ins., plainly mkd. 3 grooves on E. face and 3 grooves on S. face, firmly set, 5 ins. in the ground.</p> <p>At the corner point</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E S 16 S 15 S 21 S 22</p> <p style="text-align: center;">2004</p> <p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 89°57' W., bet. secs. 15 and 22.</p> <p>Over nearly level terrain.</p>
40.08	<p>The 1/4 sec. cor. of secs. 15 and 22, monumented with a basalt stone, 13 x 8 x 7 ins., no marks visible, loosely set, 5 ins. in the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E S 15 1/4 ——— S 22</p> <p style="text-align: center;">2004</p> <p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 89°58' W., beginning new measurement.</p> <p>Over nearly level terrain.</p>
40.01	<p>The cor. of secs. 15, 16, 21 and 22.</p> <hr/> <p>N. 0°09' E., bet. secs. 15 and 16.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over gently rolling terrain.
8.70	Center of asphalt, Navajo Route 15, 26 ft. wide, bears N. 80° E. and S. 80° W.
39.99	Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 23 N R 21 E 1/4 S 16 S 15 2004 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Raise a mound of stone, 3 ft. base, 1 ft. high to the W.
79.98	Point for the cor. of secs. 9, 10, 15 and 16, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, encircled with a mound of stone, 4 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> T 23 N R 21 E S 9 S 10 <hr style="width: 50%; margin: 0 auto;"/> S 16 S 15 2004 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. falls on steep N. slope.
	<hr style="border: 0.5px solid black;"/>
	From the cor. of secs. 10, 11, 14 and 15.
	N. 89°43' W., bet. secs. 10 and 15.
	Over steep, mountainous, broken terrain.
40.15	Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 23 N R 21 E S 10 1/4 ——— S 15</p> <p style="text-align: center;">2004</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. falls on steep E. slope, raise a supporting mound of stone, 4 ft. base, 1 1/2 ft. high to E.</p>
80.30	<p>The cor. of secs. 9, 10, 15 and 16.</p> <hr/>
	<p>N. 0°37' W., bet. secs. 9 and 10.</p> <p>Over steep, mountainous, broken terrain.</p>
39.99	<p>Point for the cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 3 ins. in the ground to bedrock, encircled with a mound of stone, 6 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T 23 N R 21 E 1/4 S 9 S 10</p> <p style="text-align: center;">2004</p>
79.98	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 3, 4, 9 and 10, monumented with a deeply embedded mound of stone, 2 1/2 ft. base, 1 ft. high, no mkd. stone found. This monument is accepted as the best available remaining evidence of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<div style="text-align: center;"> <table border="1"> <tr> <td>T 23 N</td> <td>R 21 E</td> </tr> <tr> <td>S 4</td> <td>S 3</td> </tr> <tr> <td>S 9</td> <td>S 10</td> </tr> </table> <p>2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high to the N.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. 89°32' W., bet. secs. 3 and 10.</p> <p>Over heavily rolling terrain through scattered juniper.</p> </div>	T 23 N	R 21 E	S 4	S 3	S 9	S 10		
T 23 N	R 21 E								
S 4	S 3								
S 9	S 10								
41.36	<p>The 1/4 sec. cor. of secs. 3 and 10, monumented with a deeply embedded mound of stone, 2 ft. base, 1 ft. high, no mkd. stone found. This monument is accepted as the best available remaining evidence of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 23 N</td> <td>R 21 E</td> </tr> <tr> <td>S 3</td> <td></td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td>S 10</td> <td></td> </tr> </table> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. falls in a fence, bears E. and W.</p> <hr/> <p>N. 88°58' W., beginning new measurement.</p> <p>Over heavily rolling terrain through scattered juniper.</p>	T 23 N	R 21 E	S 3		1/4	_____	S 10	
T 23 N	R 21 E								
S 3									
1/4	_____								
S 10									
40.23	<p>The cor. of secs. 3, 4, 9 and 10.</p> <hr/> <p>N. 2°18' E., bet. secs. 3 and 4.</p> <p>Over heavily rolling mountainous terrain through dense juniper.</p>								

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.50	<p>The 1/4 sec. cor. of secs. 3 and 4, monumented with a mound of stone, 3 ft. base, 1 ft. high, no mkd. stone found. This monument is accepted as the best available remaining evidence of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E 1/4 S 4 S 3 2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. falls in a fence, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°36' W., beginning new measurement.</p> <p>Over heavily rolling terrain.</p>
39.78	<p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°15' E., bet. secs. 32 and 33.</p> <p>Over heavily rolling mesa tops.</p>
39.89	<p>The 1/4 sec. cor. of secs. 32 and 33, monumented with a lava stone, 17 x 12 x 7 ins., plainly mkd. 1/4 on N. face, firmly set, 10 ins. in the ground, with a mound of stone, 3 ft. base, 1 1/2 ft. high to the W.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E 1/4 S 32 S 33 2004</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 21 E S 28 1/4 ——— S 33 2004
	Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post. Set a steel fence post alongside the stainless steel post. <hr style="width: 20%; margin: auto;"/> N. 89°50' W., beginning new measurement. Over rolling terrain through scattered juniper.
40.07	The cor. of secs. 28, 29, 32 and 33. <hr style="width: 80%; margin: auto;"/> N. 0°09' E., bet. secs. 28 and 29. Over rolling and broken terrain.
39.94	The 1/4 sec. cor. of secs. 28 and 29, monumented with a deeply embedded mound of stone, 2 1/2 ft. base, 1 ft. high, no mkd. stone found, with a reinforcement rod, 5/8 in. diam., 18 ins. long, firmly set, projecting 1 in. above ground in center. This monument is accepted as the best available remaining evidence of the original cor. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 23 N R 21 E 1/4 S 29 S 28 </div> 2004 Bury the reinforcement rod inside and deposit a magnet in a white plastic case at the base of the stainless steel post. Set a steel fence post alongside the stainless steel post. <hr style="width: 20%; margin: auto;"/> N. 0°11' W., beginning new measurement. Over gently rolling terrain.

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS									
39.95	<p>Point for the cor. of secs. 20, 21, 28 and 29, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="818 499 1040 604" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 23 N</td> <td>R 21 E</td> </tr> <tr> <td>S 20</td> <td>S 21</td> </tr> <tr> <td>S 29</td> <td>S 28</td> </tr> </table> <p align="center">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/>	T 23 N	R 21 E	S 20	S 21	S 29	S 28		
T 23 N	R 21 E								
S 20	S 21								
S 29	S 28								
	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N. 89°45' W., bet. secs. 21 and 28.</p> <p>Over steep boulder strewn S. slope of high mesa.</p>								
40.22	<p>Point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="818 1224 1040 1339" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 23 N</td> <td>R 21 E</td> </tr> <tr> <td></td> <td>S 21</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td></td> <td>S 28</td> </tr> </table> <p align="center">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>From this cor. point, a steel bolt, grade 3, S.A.E. coarse, 1/4 in. diam., 6 ins. long, set flush with the surface in a small collar of stone, set by person(s) unknown, bears N. 48°18' W., 0.31 ch. dist. This position is not relative to any other evidence found in this township and is not accepted as a corner position.</p> <p>From this same cor. point, a drill hole, with remnants of cement, 1 in. diam., 4 ins. deep, in cap rock on the highest point on top of a high mesa, bears N. 54°35' E., 16.57 chs.</p>	T 23 N	R 21 E		S 21	1/4	_____		S 28
T 23 N	R 21 E								
	S 21								
1/4	_____								
	S 28								

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>dist. This hole was determined to be the remains of the position of U. S. Geological Survey Triangulation Station "COLISEUM 1966", from which</p> <p style="padding-left: 40px;">A brass disk, 3 1/2 ins. diam., with severe surface damage, cemented in solid cap rock on top of high mesa, with partial inscription GE GI SUR Y and mkd. RM No. 1, bears N. 77°33' W. (Az., 282°27'), 0.412 ch. dist. (Record Az., 182°20').</p>
80.44	<p>The cor. of secs. 20, 21, 28 and 29.</p> <hr/> <p>N. 0°12' W., bet. secs. 20 and 21.</p> <p>Over gently rolling terrain.</p>
39.95	<p>Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E 1/4 S 20 S 21 2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high to the W.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
71.45	<p>Center of asphalt, Navajo Route 15, 26 ft. wide, bears N. 70° E. and S. 70° W.</p>
79.90	<p>The cor. of secs. 16, 17, 20 and 21, monumented with a sandstone, 24 x 14 x 4 ins., plainly mkd. 4 grooves on E. face and faint chisel marks on S. edge, firmly set, 6 ins. in the ground, with a mound of stone, 2 ft. base, 1/2 ft. high to the W.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS							
	<table border="1" style="margin: auto;"> <tr> <td>T 23 N</td> <td>R 21 E</td> </tr> <tr> <td>S 17</td> <td>S 16</td> </tr> <tr> <td>S 20</td> <td>S 21</td> </tr> </table> <p>2004</p>	T 23 N	R 21 E	S 17	S 16	S 20	S 21
T 23 N	R 21 E						
S 17	S 16						
S 20	S 21						
	<p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high to the N.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 89°56' W., bet. secs. 16 and 21.</p> <p>Over gently rolling terrain.</p>						
40.06	<p>Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate dist., falls in a wash, 15 ft. wide, 4 ft. deep, drains S. 46° E.; there is no remaining evidence of the original cor.</p> <p>Set a magnet in a white plastic case 15 ins. below the surface of the wash.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground for a reference monument, bears S. 69°52' E., 61.0 ft. dist. with brass cap mkd. T23N R21E 1/4 S21 61.0 FT TO COR 2004 and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2½ ins. diam., set 23 ins. in the ground for a reference monument, bears S. 33°25' W., 34.5 ft. dist. with brass cap mkd. T23N R21E 1/4 S21 34.5 FT TO COR 2004 and an arrow pointing to the corner.</p>						
48.20	<p>Center of asphalt, Navajo Route 15, 26 ft. wide, bears N. 80° E. and S. 80° W.</p>						
80.12	<p>The cor. of secs. 16, 17, 20 and 21.</p> <hr/> <p>N. 0°07' E., bet. secs. 16 and 17.</p> <p>Over rolling and broken terrain.</p>						

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.99	<p>Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E 1/4 S 17 S 16</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.98	<p>The cor. of secs. 8, 9, 16 and 17, monumented with a sandstone, 22 x 11 x 8 ins., mkd. with 3 grooves on S. face, firmly set 6 ins. in the ground, in a mound of stone, 4 ft. base, 1/2 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, encircled with a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E S 8 S 9 S 17 S 16</p> <p style="text-align: center;">2004</p> <p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 89°56' W., bet. 9 and 16.</p> <p>Over steep, mountainous terrain.</p>
40.07	<p>Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, encircled with a mound of stone, 5 ft. base to top, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p style="text-align: center;">T 23 N R 21 E S 9 1/4 ——— S 16</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>80.14 The cor. of secs. 8, 9, 16 and 17.</p> <hr/> <p>N. 0°19' W., bet. secs. 8 and 9.</p> <p>Over heavily rolling and broken terrain through scattered juniper.</p> <p>39.93 The 1/4 sec. cor. of secs. 8 and 9, monumented with a deeply embedded mound of stone, 3 ft. base, 1 ft. high, no mkd. stone found. This monument is accepted as the best available remaining evidence of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, encircled with a mound of stone, 5 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E 1/4 S 8 S 9</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 0°08' E., beginning new measurement.</p> <p>Over mountainous terrain through dense juniper.</p> <p>40.00 The cor. of secs. 4, 5, 8 and 9, determined at the E. edge of a mound of stone, 3 ft. base, 1 ft. high, with a lava stone, 24 x 16 x 8 ins., mkd. 4 grooves on a face and 5 grooves on adjoining face, lying loose nearby.</p> <p>At the corner point</p>
--------	---

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS							
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="812 441 1039 546"> <tr> <td>T 23 N</td> <td>R 21 E</td> </tr> <tr> <td>S 5</td> <td>S 4</td> </tr> <tr> <td>S 8</td> <td>S 9</td> </tr> </table> <p>2004</p> <p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 89°59' W., bet. secs. 4 and 9.</p> <p>Over steep, broken, mountainous terrain.</p>	T 23 N	R 21 E	S 5	S 4	S 8	S 9
T 23 N	R 21 E						
S 5	S 4						
S 8	S 9						
39.69	<p>Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="812 1155 1039 1281"> <tr> <td>T 23 N</td> <td>R 21 E</td> </tr> <tr> <td>S 4</td> <td>1/4 ———</td> </tr> <tr> <td>S 9</td> <td></td> </tr> </table> <p>2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high to the N.</p>	T 23 N	R 21 E	S 4	1/4 ———	S 9	
T 23 N	R 21 E						
S 4	1/4 ———						
S 9							
79.38	<p>The cor. of secs. 4, 5, 8 and 9.</p> <hr/> <p>N. 0°20' W., bet. secs. 4 and 5.</p> <p>Over steep, broken, mountainous terrain.</p>						
39.92	<p>The 1/4 sec. cor. of secs. 4 and 5, monumented with a sandstone, 13 x 10 x 1 ins., no marks found, set in a mound of stone, 4 ft. base, 1 ft. high.</p> <p>At the corner point</p>						

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E 1/4 S 5 S 4</p> <p style="text-align: center;">2004</p> <p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 4 ft. base, 2 ft. high to the W.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°36' W., beginning new measurement.</p> <p>Over steep, rugged, mountainous terrain.</p>
39.68	<p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., hereinbefore described.</p> <hr style="width: 80%; margin: auto;"/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' E., bet. secs. 31 and 32.</p> <p>Over steep, rugged top of Malpais Mesa.</p>
39.89	<p>The 1/4 sec. cor. of secs. 31 and 32, monumented with a deeply embedded mound of stone, 3 ft. base, 1 ft. high, no mkd. stone found. This monument is accepted as the best available remaining evidence of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E 1/4 S 31 S 32</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°03' E., beginning new measurement.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS									
40.28	<p>Descend steep N. slope of Malpais Mesa.</p> <p>The cor. of secs. 29, 30, 31 and 32, monumented with a deeply embedded mound of stone, 2 ft. base, 1 ft. high, no mkd. stone found. This monument is accepted as the best available remaining evidence of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 23 N</td> <td>R 21 E</td> </tr> <tr> <td>S 30</td> <td>S 29</td> </tr> <tr> <td>S 31</td> <td>S 32</td> </tr> </table> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>	T 23 N	R 21 E	S 30	S 29	S 31	S 32		
T 23 N	R 21 E								
S 30	S 29								
S 31	S 32								
39.97	<hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 89°46' W., bet. secs. 29 and 32.</p> <p>Over abrupt cut bank washes generally draining N.</p> <p>Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate dist., falls on an eroding cut bank of a wash; there is no remaining evidence of the original cor.</p> <p>From this point, the point selected for a witness cor. bears S. 48°30' E., 0.36 ch. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC</p> <table border="1"> <tr> <td>T 23 N</td> <td>R 21 E</td> </tr> <tr> <td></td> <td>S 29</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>↙</td> <td>S 32</td> </tr> </table> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 23 N	R 21 E		S 29	1/4	—	↙	S 32
T 23 N	R 21 E								
	S 29								
1/4	—								
↙	S 32								

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.94	<p>Set a steel fence post alongside the stainless steel post.</p> <p>The cor. of secs. 29, 30, 31 and 32.</p> <hr/> <p>West, bet. secs. 30 and 31.</p> <p>Over rolling terrain through scattered juniper.</p>
39.97	<p>The 1/4 sec. cor. of secs. 30 and 31, monumented with a basalt stone, 8 x 7 x 6 ins., with faint chisel marks visible, firmly set in a deeply embedded mound of stone, 2 ft. base, 1 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E S 30 1/4 ——— S 31</p> <p style="text-align: center;">2004</p> <p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>S. 88°06' W., beginning new measurement.</p> <p>Over rolling and broken terrain.</p>
38.15	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°22' W., bet. secs. 29, and 30.</p> <p>Over gently rolling terrain.</p>
39.72	<p>The 1/4 sec. cor. of secs. 29 and 30, monumented with a sandstone, 12 x 8 x 4 ins., mkd. with faint chisel marks on W. face, firmly set, 4 ins. in the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS							
	T 23 N R 21 E 1/4 S 30 S 29 2004						
	Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post. <hr style="width: 20%; margin: 10px auto;"/>						
	N. 0°35' W., beginning new measurement. Over gently rolling terrain.						
40.26	Point for the cor. of secs. 19, 20, 29 and 30, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <table style="margin: 10px auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T 23 N</td> <td style="padding: 0 5px;">R 21 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 19</td> <td style="padding: 0 5px;">S 20</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 30</td> <td style="padding: 0 5px;">S 29</td> </tr> </table>	T 23 N	R 21 E	S 19	S 20	S 30	S 29
T 23 N	R 21 E						
S 19	S 20						
S 30	S 29						
	2004						
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Set a steel fence post alongside the stainless steel post. <hr style="width: 20%; margin: 10px auto;"/>						
	From the cor. of secs. 20, 21, 28 and 29. N. 89°38' W., bet. secs. 20 and 29. Over gently rolling terrain.						
39.92	The 1/4 sec. cor. of secs. 20 and 29, monumented with a deeply embedded mound of stone, 3 ft. base, 1/2 ft. high, with a 8 x 6 in. wood post set alongside, projecting 44 ins. This monument is accepted as the best available remaining evidence of the original cor. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.						

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p style="text-align: center;">T 23 N R 21 E S 20 1/4 ——— S 29</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89°48' W., beginning new measurement.</p> <p>Over gently rolling terrain.</p> <p>40.64 The cor. of secs. 19, 20, 29 and 30.</p> <hr style="width: 80%; margin: auto;"/> <p>S. 88°53' W., bet. secs. 19 and 30.</p> <p>Over gently rolling terrain.</p> <p>40.72 Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E S 19 1/4 ——— S 30</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>77.18 The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <hr style="width: 80%; margin: auto;"/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°45' E., bet. secs. 19 and 20.</p> <p>Over gently rolling terrain.</p> <p>40.26 The 1/4 sec. cor. of secs. 19 and 20, monumented with a sandstone, 18 x 15 x 3 ins., with faint chisel marks on W. face,</p>
---------------	---

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>firmly set 10 ins. in ground, with a mound of stone, 2 ft. base, 1/2 ft. high to the W.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 21 E 1/4 S 19 S 20</p> <p>2004</p> </div> <p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°04' W., beginning new measurement.</p> <p>Over gently rolling terrain.</p> <p>5.40 Center of asphalt, Navajo Route 15, 26 ft. wide, bears N. 70° E. and S. 70° W.</p> <p>39.85 Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist., falls in a cut bank of a wash, drains N.; there is no remaining evidence of the original cor.</p> <p>From this point, the point selected for a witness cor. bears N. 45°17' E., 0.42 ch. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC T 23 N R 21 E S 18 S 17 S 19 S 20</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of secs. 16, 17, 20 and 21.</p>
--------	--

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>N. 89°53' W., bet. secs. 17 and 20.</p> <p>Over rolling terrain.</p>
39.95	<p>The 1/4 sec. cor. of secs. 17 and 20, monumented with a sandstone, 16 x 8 x 3 ins., no marks found, firmly set, 10 ins. in the ground, in a deeply embedded mound of stone, 2 ft. base, 1/2 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 21 E</p> <p>S 17</p> <p>1/4 ———</p> <p>S 20</p> <p>2004</p> </div> <p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>N. 89°16' W., beginning new measurement.</p> <p>Over gently rolling terrain, through a bowl shaped sandstone formation named Coliseum.</p>
39.84	<p>True point for the cor. of secs. 17, 18, 19 and 20.</p> <hr style="width: 60%; margin: 10px auto;"/>
	<p>S. 89°44' W., bet. secs. 18 and 19.</p> <p>Over gently rolling terrain.</p>
39.99	<p>The 1/4 sec. cor. of secs. 18 and 19, monumented with a lava stone, 12 x 10 x 6 ins., with faint chisel marks on N. face, firmly set, 4 ins. in the ground, in a small mound of stone, 1 1/2 ft. base, 1/2 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 23 N R 21 E S 18 1/4 ——— S 19 2004</p>
	<p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/>
	<p>S. 87°24' W., beginning new measurement.</p>
	<p>Over gently rolling terrain.</p>
37.43	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described.</p> <hr style="width: 80%; margin: auto;"/>
	<p>From the true point for the cor. of secs. 17, 18, 19 and 20.</p>
	<p>N. 0°36' W., bet. secs. 17 and 18.</p>
	<p>Over rolling and broken terrain.</p>
39.85	<p>Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 23 N R 21 E 1/4 S 18 S 17</p>
	<p style="text-align: center;">2004</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Raise a mound of stone, 2 ft. base, 1/2 ft. high to the W.</p>
79.70	<p>Point for the cor. of secs. 7, 8, 17 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<div style="text-align: center;"> <table border="1"> <tr> <td>T 23 N</td> <td>R 21 E</td> </tr> <tr> <td>S 7</td> <td>S 8</td> </tr> <tr> <td>S 18</td> <td>S 17</td> </tr> </table> <p>2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high to the W.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 89°47' W., bet. secs. 8 and 17.</p> <p>Over heavily rolling, mountainous terrain.</p> </div>	T 23 N	R 21 E	S 7	S 8	S 18	S 17		
T 23 N	R 21 E								
S 7	S 8								
S 18	S 17								
40.39	<p>Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 23 N</td> <td>R 21 E</td> </tr> <tr> <td>S 8</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 17</td> </tr> </table> <p>2004</p> </div>	T 23 N	R 21 E	S 8		1/4	—		S 17
T 23 N	R 21 E								
S 8									
1/4	—								
	S 17								
60.585	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Point for the W. 1/16 sec. cor. of secs. 8 and 17, falls on a steep inaccessible NE. slope.</p> <p>From this point, the point selected for a witness cor. bears N. 23°38' E., 0.63 ch. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>								

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">WC T23N R21E S 8 W 1/16 ——— S 17</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
80.78	<p>The cor. of secs. 7, 8, 17 and 18.</p> <hr/> <p>S. 88°49' W., bet. secs. 7 and 18.</p> <p>Over rolling and broken terrain.</p>
40.43	<p>Point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 23 N R 21 E S 7 1/4 ——— S 18</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound stone, 3 ft. base, 1 ft. high, to the N.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
76.45	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°41' E., bet. secs. 7 and 8.</p> <p>Over rolling and broken terrain.</p>
19.925	<p>Point for the S. 1/16 sec. cor. of secs. 7 and 8.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23N R21E S 1/16 S 7 S 8</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
39.85	<p>Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E 1/4 S 7 S 8</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
79.70	<p>The cor. of secs. 5, 6, 7 and 8, monumented with a lava stone, 26 x 8 x 6 ins., plainly mkd. 5 grooves on E. face and 5 grooves on S. face, loosely set, 4 ins. in the ground, in a mound of stone, 3 ft. base, 1 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, encircled with a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E S 6 S 5 S 7 S 8</p> <p style="text-align: center;">2004</p> <p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>N. 89°57' W., bet. secs. 5 and 8.</p> <p>Over heavily rolling and broken mountainous terrain.</p>
39.84	<p>Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 23 N R 21 E</p> <p>S 5</p> <p>1/4 ———</p> <p>S 8</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
79.68	<p>The cor. of secs. 5, 6, 7 and 8.</p> <hr/> <p>S. 89°15' W., bet. secs. 6 and 7.</p> <p>Over rolling and broken terrain through scattered juniper.</p>
41.08	<p>Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 23 N R 21 E</p> <p>S 6</p> <p>1/4 ———</p> <p>S 7</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
77.42	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 1°02' W., bet. secs. 5 and 6.</p> <p>Over heavily rolling and broken terrain.</p>
39.74	<p>Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, encircled with a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E 1/4 S 6 S 5</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.55	<p>The cor. of secs. 5, 6, 31 an 32, on the N. bdy. of the Tp.</p> <hr/> <p style="text-align: center;">Subdivision of Section 8, T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 8 and 17.</p> <p>N. 0°18' E., on the N. and S. center line of sec. 8.</p> <p>Over steep broken terrain through scattered juniper.</p>
19.94	<p>Point for the center S. 1/16 sec. cor. of sec. 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23N R21E C S 1/16 S 8 C</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Subdivision of Section 8,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a steel fence post alongside the stainless steel post.</p>
39.88	<p>Point for the center 1/4 sec. cor. of sec. 8, at intersection with the E. and W. center line.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 23 N R 21 E C 1/4 S 8</p> <p style="text-align: center;">2004</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Set a steel fence post alongside the stainless steel post.</p>
	<p>From this cor. point, a sandstone, firmly set, projecting 13 x 12 x 5 ins. above ground, plainly mkd. CENTER OF on S. face, in an embedded mound of stone, 3 ft. base, 1/2 ft. high, origin unknown, bears N. 60°10' W., 0.18 ch. dist.</p>
79.80	<p>The 1/4 sec. cor. of secs. 5 and 8.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 8 and 9.</p>
	<p>N. 89°50' W., on the E. and W. center line of sec. 8.</p>
	<p>Over rolling and broken terrain.</p>
39.96	<p>The center 1/4 sec. cor. of sec. 8.</p>
60.02	<p>Point for the center W. 1/16 sec. cor. of sec. 8.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, encircled with a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T23N R21E W 1/16 C———C S 8</p> <p style="text-align: center;">2004</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Set a steel fence post alongside the stainless steel post.</p>

**Subdivision of Section 8,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.08	<p>The 1/4 sec. cor. of secs. 7 and 8.</p> <hr/> <p style="text-align: center;">SW 1/4</p> <hr/> <p>From the true point for the W. 1/16 sec. cor. of secs. 8 and 17. N. 0°30' E., on the N. and S. center line of the SW 1/4 of sec. 8.</p> <p>Over heavily rolling and broken terrain.</p>
19.93	<p>Point for the SW. 1/16 sec. cor. of sec. 8, at intersection with the E. and W. center line of the SW 1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23N R21E SW 1/16 S 8</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>From this cor. point, an embedded mound stone, 5 ft. base, 1 ft. high, origin unknown, bears S. 72°55' E., 0.43 chs. dist.</p>
39.86	<p>The center W. 1/16 sec. cor. of sec. 8.</p> <hr/> <p>From the center S. 1/16 sec. cor. of sec. 8.</p> <p>N. 89°49' W., on the E. and W. center line of the SW 1/4 of sec. 8.</p> <p>Over heavily rolling and broken terrain.</p>
20.13	<p>The SW. 1/16 sec. cor. of sec. 8.</p>
40.26	<p>The S. 1/16 sec. cor. of secs. 7 and 8.</p> <hr/> <p style="text-align: center;">Subdivision of Section 12, T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 12 and 13.</p>

**Subdivision of Section 12,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 0°25' E., on the N. and S. center line of sec. 12. Over broken terrain.
9.98	Point for Angle Point 2, sec. 12, hereinafter described.
29.98	Point for Angle Point 1, sec. 12, hereinafter described.
38.55	The center 1/4 sec. cor. of sec. 12, at intersection with the E. and W. center line, monumented with an iron post, 1 in. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd. C1/4 S12 1883 1938, encircled by an embedded mound stone, 3 ft. base, 1 ft. high. Add the marks T23N R21E 2004 to the brass cap. From this cor. point, a monument established in 1937 by the Soil Conservation Service, bears S. 5°21' E., 1.26 chs. dist., monumented with a sandstone, 18 x 12 x 4 ins., plainly mkd. SCS on N. face, firmly set, 12 ins. in the ground, in a mound of stone, 3 ft. base, 1/2 ft. high. Bury the stone, 10 ins. below the surface and scatter the mound of stone.
	—————
	N. 0°25' E., beginning new measurement.
38.54	The 1/4 sec. cor. of secs. 1 and 12. —————
	From the true point for the 1/4 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp.
	S. 88°14' W., on the E. and W. center line of sec. 12. Over rolling and broken terrain.
40.05	The center 1/4 sec. cor. of sec. 12. —————
	S. 88°14' W., beginning new measurement.
5.70	Center of asphalt, Navajo Route 6, 26 ft. wide, bears N. and S.
39.81	The 1/4 sec. cor. of secs. 11 and 12. —————
	Subdivision of Section 14, T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 14 and 23.
	N. 0°18' E., on the N. and S. center line of sec. 14.

**Subdivision of Section 14,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling terrain.
36.40	Center of asphalt, Navajo Route 15, 26 ft. wide, bears N. 65° E. and S. 65° W.
39.83	Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T 23 N R 21 E C 1/4 S 14 2004 Deposit a magnet in a white plastic case at the base of the stainless steel post. Set a steel fence post alongside the stainless steel post.
79.64	The 1/4 sec. cor. of secs. 11 and 14. <hr/>
	From the 1/4 sec. cor. of secs. 13 and 14. N. 89°59' W., on the E. and W. center line of sec. 14. Over rolling terrain.
32.90	Center of asphalt, Navajo Route 15, 26 ft. wide, bears N. 65° E. and S. 65° W.
40.23	The center 1/4 sec. cor. of sec. 14.
80.24	The 1/4 sec. cor. of secs. 14 and 15. <hr/>
	Subdivision of Section 18, T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 18 and 19. N. 0°55' W., on the N. and S. center line of sec. 18. Over rolling terrain.
39.06	Point for the center 1/4 sec. cor. of sec. 18, at intersection with the E. and W. center line.

**Subdivision of Section 18,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E C 1/4 S 18</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
79.05	<p>The 1/4 sec. cor. of secs. 7 and 18.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 17 and 18.</p> <p>S. 88°37' W., on the E. and W. center line of sec. 18.</p> <p>Over gently rolling terrain.</p>
40.21	<p>The center 1/4 sec. cor. of sec. 18.</p>
76.85	<p>The 1/4 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp.</p> <hr/> <p style="text-align: center;">Subdivision of Section 20, T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 20 and 29.</p> <p>N. 0°14' W., on the N. and S. center line of sec. 20.</p> <p>Over rolling terrain through scattered juniper.</p>
40.04	<p>Point for the center 1/4 sec. cor. of sec. 20, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E C 1/4 S 20</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>

**Subdivision of Section 20,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	From this cor. point, an embedded mound stone, 3 ft. base, 1/2 ft. high, origin unknown, bears N. 18°06' E., 0.40 ch. dist.
58.40	Center of asphalt, Navajo Route 15, 26 ft. wide, bears N. 70° E. and S. 70° W.
79.72	The 1/4 sec. cor. of secs. 17 and 20.
	<hr/>
	From the 1/4 sec. cor. of secs. 20 and 21.
	N. 89°30' W., on the E. and W. center line of sec. 20.
	Over rolling and broken terrain.
39.94	The center 1/4 sec. cor. of sec. 20.
79.89	The 1/4 sec. cor. of secs. 19 and 20.
	<hr/>
	Subdivision of Section 22, T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona
	<hr/>
	From the 1/4 sec. cor. of secs. 22 and 27.
	N. 0°23' W., on the N. and S. center line of sec. 22.
	Over gently rolling terrain.
40.01	Point for the center 1/4 sec. cor. of sec. 22, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 21 E C 1/4 S 22
	2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Set a steel fence post alongside the stainless steel post.
80.11	The 1/4 sec. cor. of secs. 5 and 8.
	<hr/>
	From the 1/4 sec. cor. of secs. 22 and 23.
	S. 89°59' W., on the E. and W. center line of sec. 22.

**Subdivision of Section 22,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Over rolling and broken terrain.</p> <p>39.83 The center 1/4 sec. cor. of sec. 22.</p> <p>80.16 The 1/4 sec. cor. of secs. 21 and 22.</p> <hr/> <p style="text-align: center;">Subdivision of Section 24, T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 24 and 25.</p> <p>N. 0°06' E., on the N. and S. center line of sec. 24.</p> <p>Over nearly level terrain.</p> <p>39.94 Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E C 1/4 S 24</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>79.76 The 1/4 sec. cor. of secs. 13 and 24.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp.</p> <p>N. 89°47' W., on the E. and W. center line of sec. 24.</p> <p>Over rolling and broken terrain.</p> <p>40.05 The center 1/4 sec. cor. of sec. 24.</p> <p>46.00 Center of asphalt, Navajo Route 6, 26 ft. wide, bears N. and S.</p> <p>80.26 The 1/4 sec. cor. of secs. 23 and 24.</p> <hr/>
--------	--

**Subdivision of Section 26,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	Subdivision of Section 26, T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona
	<hr/> <p>From the 1/4 sec. cor. of secs. 26 and 35.</p> <p>N. 0°05' W., on the N. and S. center line of sec. 26.</p> <p>Over gently rolling terrain.</p>
39.96	<p>Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E C 1/4 S 26</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
79.92	<p>The 1/4 sec. cor. of secs. 23 and 26.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 25 and 26.</p> <p>N. 89°47' W., on the E. and W. center line of sec. 26.</p> <p>Over nearly level terrain.</p>
40.13	<p>The center 1/4 sec. cor. of sec. 26.</p>
80.08	<p>The 1/4 sec. cor. of secs. 26 and 27.</p> <hr/> <p style="text-align: center;">Subdivision of Section 28, T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 28 and 33.</p> <p>N. 0°06' E., on the N. and S. center line of sec. 28.</p> <p>Over rolling and broken terrain.</p>
39.85	<p>Point for the center 1/4 sec. cor. of sec. 28, at intersection with the E. and W. center line.</p>

**Subdivision of Section 28,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E C 1/4 S 28</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. falls on E. edge of trail road, bears N. 45° E. and S. 45° W.</p>
79.84	<p>The 1/4 sec. cor. of secs. 21 and 28.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 27 and 28.</p> <p>N. 89°42' W., on the E. and W. center line of sec. 28.</p> <p>Over rolling and broken terrain.</p>
40.11	<p>The center 1/4 sec. cor. of sec. 28.</p>
80.14	<p>The 1/4 sec. cor. of secs. 28 and 29.</p> <hr/> <p style="text-align: center;">Subdivision of Section 32, T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp.</p> <p>N. 0°04' W., on the N. and S. center line of sec. 32.</p> <p>Over steep broken terrain through scattered juniper.</p>
39.87	<p>Point for the center 1/4 sec. cor. of sec. 32, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E C 1/4 S 32</p> <p style="text-align: center;">2004</p>

**Subdivision of Section 32,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>From this cor. point, an embedded mound stone, 3 ft. base, 1/2 ft. high, origin unknown, bears N. 35°35' W., 0.72 ch. dist.</p>
80.06	<p>The true point for the 1/4 sec. cor. of secs. 29 and 32.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 32 and 33.</p> <p>N. 89°54' W., on the E. and W. center line of sec. 32.</p> <p>Over steep, mountainous broken terrain.</p>
39.90	<p>The center 1/4 sec. cor. of sec. 32.</p>
79.96	<p>The 1/4 sec. cor. of secs. 31 and 32.</p> <hr/> <p style="text-align: center;">Subdivision of Section 34, T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 5 and 34, on the S. bdy. of the Tp.</p> <p>N. 0°01' W., on the N. and S. center line of sec. 34.</p> <p>Over steep broken terrain.</p>
40.04	<p>Point for the center 1/4 sec. cor. of sec. 34, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 21 E C 1/4 S 34</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
80.16	<p>The 1/4 sec. cor. of secs. 27 and 34.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 34 and 35.</p>

**Subdivision of Section 34,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>S. 89°54' W., on the E. and W. center line of sec. 34. Over rolling terrain.</p>
40.05	The center 1/4 sec. cor. of sec. 34.
79.99	The 1/4 sec. cor. of secs. 33 and 34.
<p>Metes-and-Bounds Survey in Section 12, T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona</p>	
	<p>From the point for Angle Point 1, sec. 12, on the N. and S. center line of sec. 12.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 23 N R 21 E S 12</p> <div style="display: inline-block; vertical-align: middle; margin-left: 100px;"> <div style="border-left: 1px solid black; border-top: 1px solid black; width: 20px; height: 20px; display: flex; align-items: center; justify-content: center;"> AP 1 </div> </div> <p style="margin-top: 5px;">2004</p> </div> <p>From this cor. point, a mound of stone, 3 ft. base, 1/2 ft. high, bears S. 40°49' E., 0.93 ch. dist. Bury mound of stone.</p> <p>From this same cor. point, the center 1/4 sec. cor. of sec. 12, bears N. 0°25' E., 8.57 chs. dist., hereinbefore described.</p> <p>S. 0°25' W., on line 1-2, sec. 12, along the N. and S. center line of sec. 12.</p> <p>Over broken terrain.</p>
20.00	<p>Point for Angle Point 2, sec. 12.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 23 N R 21 E S 12</p> <div style="display: inline-block; vertical-align: middle; margin-left: 100px;"> <div style="border-left: 1px solid black; border-top: 1px solid black; width: 20px; height: 20px; display: flex; align-items: center; justify-content: center;"> AP 2 </div> </div> <p style="margin-top: 5px;">2004</p> </div> <p>From this cor. point, the 1/4 sec. cor. of secs. 12 and 13, bears S. 0°25' W., 9.98 chs. dist., hereinbefore described.</p>

Metes-and-Bounds Survey in Section 12,
T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>S. 89°35' E., on line 2-3, sec. 12.</p> <p>Over broken terrain.</p> <p>10.00 Point for Angle Point 3, sec. 12.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, encircled with a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 23 N R 21 E</p> <p>AP 3</p> <p>└───┘</p> <p>S 12</p> <p>2004</p> </div> <p>Cor. is located on steep N. slope.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 0°25' E., on line 3-4, sec. 12.</p> <p>Over broken terrain.</p> <p>20.00 Point for Angle Point 4, sec. 12.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 23 N R 21 E</p> <p>S 12</p> <p>└───┘</p> <p>AP 4</p> <p>2004</p> </div> <p>N. 89°35' W., on line 4-1, sec. 12.</p> <p>Over broken terrain.</p> <p>10.00 Angle Point 1, sec. 12.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <hr style="width: 80%; margin: 10px auto;"/> <p>The area encompassed by this survey lies approximately 35 miles north of Holbrook, Arizona. The terrain varies from nearly level in the southeast portion of the township to steep and mountainous in the west and northern portions.</p>
--------	--

T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS

The soil is mostly sandy loam in the flats and volcanic rock on the steeper slopes and mesa tops. The elevation varies from 5500 to 6400 feet above sea level. The vegetation ranges from open grass lands to scattered stands of juniper.

There is an operating gravel operation in section 11, a housing subdivision near the center of section 15 and numerous home sites throughout the township. Lokasakad Spring is located in the SW1/4 SW1/4, section 8 and Dog Spring is in the SE 1/4, section 22.

The magnetic declination was observed to be 13° E.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Robert J. Lyle	Surveying Technician
Nelson Kinsel	Surveying Technician
John J. Heintel	Surveying Technician
Michelle Meece	Surveying Technician
Heather M. Pierce	Surveying Technician
Daniel P. Engle	Surveying Technician
Daniel T. Howarth	Surveying Technician
Chad Bucsher	Surveying Technician
Geoffrey A. Graham	Land Surveyor

CERTIFICATE OF SURVEY

I, Dale C. Wilson, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 26th day of April, 2004, and supplemental special instructions bearing date of the 28th day of June, 2004, I have dependently resurveyed the south, east, west and north boundaries and the subdivisional lines, subdivided certain sections and executed the metes-and-bounds survey in section 12, T. 23 N., R. 21 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with the special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Dale C. Wilson is no longer assigned to this office and is unavailable for signature.

DEC 6, 2005
(Date)

M. R. Baber
(Acting Cadastral Survey Field Chief)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey the south, east, west and north boundaries and the subdivisional lines, the subdivision of certain sections and the metes-and-bounds survey in section 12, T. 23 N., R. 21 E., Gila and Salt River Meridian, in the State of Arizona, executed by Dale C. Wilson, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

Jan 9, 2006
(Date)

Stephen K. Hansen
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 23 N., R. 21 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~

