

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF THE EAST BOUNDARY,
AND
THE SURVEY OF THE SOUTH BOUNDARY,
THE GOVERNING SECTION LINE
AND
THE SUBDIVISIONAL LINES
TOWNSHIP 26 NORTH, RANGE 27 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

Leonard R. Sandoval, Cadastral Surveyor

Under Special Instructions dated June 21, 2004, approved June 21, 2004, which provided for the surveys included under Group No. 926 and assignment instructions dated June 21, 2004.

Survey commenced August 12, 2004

Survey completed September 23, 2004

INDEX DIAGRAM

TOWNSHIP 26 NORTH RANGE 27 EAST
GILA AND SALT RIVER MERIDIAN, ARIZONA

6 69 67	5 52 66	4 45 52	3 36 44	2 21 36	1 10 27
7 65 64	8 51 63	9 43 50	10 35 43	11 21 34	12 9 26
18 62 60	17 50 60	16 42 49	15 33 41	14 20 33	13 8 24
19 59 58	20 48 57	21 40 48	22 32 39	23 19 32	24 7 23
30 56 55	29 47 54	28 39 46	27 31 38	26 18 30	25 5 22
31 53 16	32 45 15	33 37 15	34 29 14	35 17 13	36 4 11

T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of the east boundary and the survey of the south boundary, the governing section line and the subdivisional lines, Township 26 North, Range 27 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

The survey of the south and west boundaries of Township 26 North, Range 28 East, was originally performed by Frank Follman in 1883. The survey of the south boundary of the Navajo Indian Reservation through Township 26 North, Range 27 East, was performed by John G. Evans in 1884. The survey of the east boundary of Township 26 North, Range 26 East, was performed by Frederick C. Miller in 1915. The dependent resurvey of the south boundary of Township 26 North, Range 28 East, was performed by Sidney E. Blout in 1920-27. The dependent resurvey of the east boundary of Township 26 North, Range 26 East and a survey tie to the southwest corner of Township 26 North, Range 28 East, was performed by Jones Curtiss, in 2002, executed concurrently under Group 886, Arizona. Resurvey of the south boundary of Township 27 North, Range 27 East, was performed by Leonard R. Sandoval, in 2003, executed concurrently under Group 902, Arizona.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973 and the Special Instructions dated June 21, 2004, for Group 926, Arizona.

Preliminary to the survey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Geodetic control was derived from Global Positioning System (GPS) static post observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) ALBUQUERQUE 1 CORS ARP, AZTEC CORS ARP and FLAGSTAFF 1 CORS ARP. The NAD83(CORS96) (EPOCH:2002), geographic position of the southeast township cor., is as follows:

Latitude: 35°36'18.73" N. Longitude: 109°24'07.55" W.

The mean magnetic declination is 11 1/4° E.

Dependent Resurvey of the East Boundary,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

Restoring the survey executed by
Frank Follman, in 1883

Beginning at the cor. of Tps. 26 N., Rs. 27 and 28 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd. T26N R27E R28E S36 S31 T25N R27E 2002 and witnessed as described as a survey tie in the field notes of the dependent resurvey of the east boundary, T. 25 N., R. 26 E., executed concurrently under Group 886, Arizona.

From this cor. point, the closing cor. of Tps. 25 N., Rs. 27 and 28 E., bears S. 89°50' E., 6.05 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 14 ins. above ground, in embedded mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. T26N R28E S31 S1 S6 R27E R28E CC T25N 1920.

from which the remains of 1920 bearing tree

A dead piñon, 25 ins. diam., bears S. 35 1/2° W., 1.80 chs. dist., with scribe marks T25N R27E S1 BT visible on open blaze.

Add the marks 2004 on the brass cap.

N. 0°19' W., bet. secs. 31 and 36.

Over rolling and broken land.

23.90 Wide Ruins Wash, 25 ft. wide, 5 ft. deep, drains S. 50° W. (Record: Cross Canyon, 26.00 chs.)

40.10 Point for the 1/4 sec. cor. of secs. 31 and 36, determined from the orig. bearing tree

A piñon, 15 ins. diam., bears N. 88° E., 1.32 chs. dist., with scribe marks BT visible on mostly healed blaze.

at the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 N
R 27 E R 28 E
1/4
S 36 | S 31

2004

**Dependent Resurvey of the East Boundary,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS																	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 0°08' E., beginning new measurement.</p> <p>Over rolling land.</p>																
5.52	High voltage transmission line, bears S. 60° E. and N. 60° W.																
35.20	Underground gas pipeline line, bears N. 75° E. and S. 75° W.																
39.99	<p>Point for the cor. of secs. 25, 30, 31 and 36, determined from the remaining orig. bearing tree</p> <p style="padding-left: 40px;">A forked piñon, 16 ins. diam. at the base, bears S. 44 1/4° W., 1.36 chs. dist., with scribe marks N R26E visible on partially healed blaze.</p> <p>at the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr><td colspan="4">T 26 N</td></tr> <tr><td style="border-right: 1px solid black; padding: 2px;">R 27 E</td><td style="padding: 2px;"></td><td style="border-right: 1px solid black; padding: 2px;">R 28 E</td><td style="padding: 2px;"></td></tr> <tr><td style="border-right: 1px solid black; padding: 2px;">S 25</td><td style="padding: 2px;"></td><td style="border-right: 1px solid black; padding: 2px;">S 30</td><td style="padding: 2px;"></td></tr> <tr><td style="border-right: 1px solid black; padding: 2px;">S 36</td><td style="padding: 2px;"></td><td style="border-right: 1px solid black; padding: 2px;">S 31</td><td style="padding: 2px;"></td></tr> </table> </div> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located at 85 lks. S. of a trail road, bears N. 40° E. and S. 40° W.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 0°33' W., bet. secs. 25 and 30.</p> <p>Over rolling and broken land.</p>	T 26 N				R 27 E		R 28 E		S 25		S 30		S 36		S 31	
T 26 N																	
R 27 E		R 28 E															
S 25		S 30															
S 36		S 31															
39.50	Wash, 15 ft. wide, 4 ft. deep, drains S. 25° W.																
40.49	<p>Point for the 1/4 sec. cor. orig. set for secs. 25 and 30, determined from the orig. bearing tree</p> <p style="padding-left: 40px;">A piñon, 19 ins. diam., bears N. 60° E., 1.54 chs. dist., with healed blaze.</p> <p>This cor. now functions as the 1/4 sec. cor. of sec. 30, T. 26 N., R. 28 E. only.</p>																

**Dependent Resurvey of the East Boundary,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 27 E R 28 E 1/4 S 30</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1°36' W., beginning new measurement.</p> <p>Over rolling land.</p>
8.80	Navajo Route 203, a graded road, 20 ft. wide, bears N. 70° E. and S. 70° W.
41.91	<p>The cor. orig. set for secs. 19, 24, 25 and 30, monumented with a sandstone, 24 x 15 x 2 ins., loosely set, projecting 11 ins. above ground and leaning, faintly mkd. with 4 grooves on the N. face and illegible marks on the S. face, overgrown with lichen.</p> <p>from which the remains of the orig. bearing trees</p> <p style="padding-left: 40px;">A piñon, 20 ins. diam., bears S. 89 1/2° E., 57 lks. dist., with illegible scribe marks on partially healed blaze. (Record: N. 10 1/2° E., 54 lks.)</p> <p>and the remains of a bearing tree not of record</p> <p style="padding-left: 40px;">A root hole, bears S. 9 1/2° E., 81 lks. dist., with a fallen dead piñon alongside, 10 ins. diam., with scribe marks 6N R28E S30 BT visible on partially healed blaze.</p> <p>This cor. now functions as the cor. of secs. 19 and 30, T. 26 N., R. 28 E. only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the East Boundary,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS																					
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 10px;">T 26 N</td> <td style="border-left: 1px solid black; padding-left: 10px;">T 26 N</td> </tr> <tr> <td style="padding-right: 10px;">R 27 E</td> <td style="border-left: 1px solid black; padding-left: 10px;">S 19</td> </tr> <tr> <td style="padding-right: 10px;">S 24</td> <td style="border-left: 1px solid black; padding-left: 10px;">S 30</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 10px;">R 28 E</td> </tr> </table> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 1°29' W., bet. secs. 19 and 24.</p> <p>Over rolling land.</p> <p>37.55 Trail road, bear N. 35° E. and S. 35° W.</p> <p>41.68 Point for the 1/4 sec. cor. orig. set for secs. 19 and 24, determined from the remains of the orig. bearing tree</p> <p style="padding-left: 40px;">A root hole, bears N. 15 1/2° W., 13 lks. dist., with a fallen, badly decayed piñon alongside, 12 ins. diam., with illegible scribe marks on an open blaze.</p> <p>This cor. now functions as the 1/4 sec. cor. of sec. 19, T. 26 N., R. 28 E. only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td></td> <td style="padding: 0 10px;">T 26 N</td> <td></td> </tr> <tr> <td style="padding-right: 10px;">R 27 E</td> <td style="border-left: 1px solid black; padding-left: 10px;"></td> <td style="padding-left: 10px;">R 28 E</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 10px;"> </td> <td style="padding-left: 10px;">1/4</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 10px;"> </td> <td style="padding-left: 10px;">S 19</td> </tr> </table> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 0°41' E., beginning new measurement.</p> <p>Over rolling land.</p> <p>39.64 Point for the cor. orig. set for secs. 13, 18, 19 and 24, determined from the remains of the orig. bearing tree</p> <p style="padding-left: 40px;">A root hole, bears S. 7 1/2° E., 14 lks. dist., with a fallen, badly decayed piñon alongside, 8 ins. diam., with illegible scribe marks on an open blaze.</p>	T 26 N	T 26 N	R 27 E	S 19	S 24	S 30		R 28 E		T 26 N		R 27 E		R 28 E			1/4			S 19
T 26 N	T 26 N																				
R 27 E	S 19																				
S 24	S 30																				
	R 28 E																				
	T 26 N																				
R 27 E		R 28 E																			
		1/4																			
		S 19																			

**Dependent Resurvey of the East Boundary,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>This cor. now functions as the cor. of secs. 18 and 19, T. 26 N., R. 28 E. only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 10px;">T 26 N</td> <td style="border-left: 1px solid black; padding-left: 10px;">T 26 N</td> </tr> <tr> <td>R 27 E</td> <td style="border-left: 1px solid black; padding-left: 10px;">S 18</td> </tr> <tr> <td style="padding-right: 10px;">S 13</td> <td style="border-left: 1px solid black; padding-left: 10px;">S 19</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 10px;">R 28 E</td> </tr> </table> <p style="text-align: center;">2004</p> <p>from which a bearing tree not of record</p> <p style="padding-left: 40px;">A dead piñon, 9 ins. diam., bears N. 80 1/4° E., 29 lks. dist., with scribe marks 18 BT visible on a partially healed blaze.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 0°02' W., bet. secs. 13 and 18.</p> <p>Over rolling land.</p>	T 26 N	T 26 N	R 27 E	S 18	S 13	S 19		R 28 E
T 26 N	T 26 N								
R 27 E	S 18								
S 13	S 19								
	R 28 E								
39.95	<p>Point for the 1/4 sec. cor. orig. set for secs. 13 and 18, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>This cor. now functions as the 1/4 sec. cor. of sec. 18, T. 26 N., R. 28 E. only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 20px;">T 26 N</td> <td></td> </tr> <tr> <td>R 27 E</td> <td style="padding-left: 20px;">R 28 E</td> </tr> <tr> <td></td> <td style="padding-left: 40px;"> 1/4</td> </tr> <tr> <td></td> <td style="padding-left: 40px;"> S 18</td> </tr> </table> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 26 N		R 27 E	R 28 E		1/4		S 18
T 26 N									
R 27 E	R 28 E								
	1/4								
	S 18								
65.65	<p>Trail road, bears N. 85° E. and S. 85° W.</p>								
76.70	<p>Cross Canyon Wash, 40 ft. wide, 5 ft. deep, drains N. 85° W. (Record: Cross low sag, 77.00 chs.)</p>								

**Dependent Resurvey of the East Boundary,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
79.90	<p>Point for the cor. orig. set for secs. 7, 12, 13 and 18, determined from the remains of the orig. bearing tree</p> <p style="padding-left: 40px;">A root hole, bears N. 44° W., 27 lks. dist., with a fallen and dead piñon alongside, 18 ins. diam., with scribe marks T26N R28E S12 BT visible on an open blaze.</p> <p>This cor. now functions as the cor. of secs. 7 and 18, T. 26 N., R. 28 E. only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 26 N</td> <td style="border-left: 1px solid black; padding: 0 10px;">T 26 N</td> </tr> <tr> <td style="padding: 0 10px;">R 27 E</td> <td style="border-left: 1px solid black; padding: 0 10px;">S 7</td> </tr> <tr> <td style="padding: 0 10px;">S 12</td> <td style="border-left: 1px solid black; padding: 0 10px;">S 18</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding: 0 10px;">R 28 E</td> </tr> </table> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 1°02' E., bet. secs. 7 and 12.</p> <p>Over rolling land.</p>	T 26 N	T 26 N	R 27 E	S 7	S 12	S 18		R 28 E
T 26 N	T 26 N								
R 27 E	S 7								
S 12	S 18								
	R 28 E								
39.58	<p>Point for the 1/4 sec. cor. orig. set for secs. 7 and 12, determined from the orig. bearing tree</p> <p style="padding-left: 40px;">A dead piñon, 9 ins. diam., bears N. 10 1/2° W., 1.31 chs. dist., with scribe marks 1/4 S BT visible on a partially healed blaze.</p> <p>This cor. now functions as the 1/4 sec. cor. of sec. 7, T. 26 N., R. 28 E. only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 26 N</td> <td></td> </tr> <tr> <td style="padding: 0 10px;">R 27 E</td> <td style="padding: 0 10px;">R 28 E</td> </tr> <tr> <td></td> <td style="padding: 0 10px;"> 1/4</td> </tr> <tr> <td></td> <td style="padding: 0 10px;"> S 7</td> </tr> </table> <p style="text-align: center;">2004</p>	T 26 N		R 27 E	R 28 E		1/4		S 7
T 26 N									
R 27 E	R 28 E								
	1/4								
	S 7								

**Dependent Resurvey of the East Boundary,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 55 lks. N. of a trail road, bears E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°12' W., beginning new measurement.</p> <p>Over rolling land.</p>								
40.19	<p>Point for the cor. orig. set for secs. 1, 6, 7 and 12, determined from the orig. bearing trees</p> <p style="padding-left: 40px;">A piñon, 14 ins. diam., bears N. 15 1/4° E., 25 lks. dist., with illegible scribe marks visible on a partially healed blaze. (Record: N. 44° E.)</p> <p style="padding-left: 40px;">A root hole, bears S. 56 1/2° E., 11 lks. dist., with a fallen and badly decayed piñon alongside, 8 ins. diam., with remains of scribe marks T26N R visible on an open blaze. (Record: S. 11 1/2° E.)</p> <p style="padding-left: 40px;">A piñon, 13 ins. diam., bears S. 53 1/4° W., 35 lks. dist., with scribe marks BT visible on a partially healed blaze. (Record: S. 15° W.)</p> <p>This cor. now functions as the cor. of secs. 6 and 7, T. 26 N., R. 28 E. only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">T 26 N</td> <td style="padding: 2px 5px;">T 26 N</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">R 27 E</td> <td style="padding: 2px 5px;">S 6</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 1</td> <td style="padding: 2px 5px;">S 7</td> </tr> <tr> <td style="border-right: 1px solid black;"></td> <td style="padding: 2px 5px;">R 28 E</td> </tr> </table> </div> <p style="text-align: center; margin: 5px 0;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°08' E., bet. secs. 1 and 6.</p> <p>Over rolling and broken land.</p>	T 26 N	T 26 N	R 27 E	S 6	S 1	S 7		R 28 E
T 26 N	T 26 N								
R 27 E	S 6								
S 1	S 7								
	R 28 E								
33.00	<p>Burnt Piñon Wash, 30 ft. wide, 3 ft. deep, drains S. 55° W. (Record: S. 60° W.)</p>								

**Dependent Resurvey of the East Boundary,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
33.75	N. rim of the Burnt Piñon Wash canyon, top of sandstone ledge, bears N. 55° E. and S. 55° W.
39.66	<p>The 1/4 sec. cor. orig. set for secs. 1 and 6, monumented with a piñon, 17 ins. diam., with scribe marks 1/4 S visible on an open blaze on the N. side, leaning to the east</p> <p>from which the remains of the orig. bearing tree</p> <p style="padding-left: 40px;">A piñon stump, 6 1/2 ft. high, 13 ins. diam., bears S. 41° E., 36 lks. dist., with scribe marks 1/4 6 BT visible on open blaze. (Record: S. 45° E., 25 lks.)</p> <p>from which new accessories</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 45°01' E., 100.0 ft. dist. with brass cap mkd. T26N R28E 1/4 S6 RM 100.0 FT. TO COR. 2004 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p style="padding-left: 40px;">A brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, set in drill hole, cemented in place on sandstone bedrock, for a reference monument, bears S. 45°00' E., 100.0 ft. dist. with top mkd. T26N R28E 1/4 S6 RM 100.0 FT. TO COR. 2004 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the brass tablet.</p> <p>This cor. now functions as the 1/4 sec. cor. of sec. 6, T. 26 N., R. 28 E. only.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°32' W., beginning new measurement.</p> <p>Over rolling land.</p>
39.64	<p>The cor. of Tps. 26 and 27 N., Rs. 27 and 28 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T27N R27E R28E S36 S31 S1 S6 T26N 2003.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">Survey of the South Boundary, T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of Tps. 26 N., Rs. 27 and 28 E., hereinbefore described.</p> <p>West, bet. secs. 1 and 36.</p>

Survey of the South Boundary,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling and broken land, through the valley floor of Wide Ruins Wash Canyon.
27.55	Wide Ruins Wash, 60 ft. wide, 5 ft. deep, drains S. 5° W.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 27 E S 36 1/4 ——— S 1 T 25 N 2004 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Cor. is located on the N. bank of Wide Ruins Wash, 4 ft. high, bears E. and W.
40.60	Wide Ruins Wash, 25 ft. wide, 4 ft. deep, drains N. 55° W.
47.20	Wide Ruins Wash, 30 ft. wide, 5 ft. deep, drains S. 65° W.
57.40	Power line, bears N. 29° E. and S. 29° W.
58.85	Wide Ruins Wash, 25 ft. wide, 5 ft. deep, drains N. 70° W., thence along the wash.
70.50	S. rim of Wide Ruins Wash Canyon, top of sandstone ledge, bears S. 25° E. and N. 25° W., thence over rolling land.
80.00	Point for the cor. of secs. 1, 2, 35 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 27 E S 35 S 36 S 2 S 1 T 25 N 2004 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

Survey of the South Boundary,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, pinon and juniper; undergrowth, brush and native grasses.</p> <hr/>
	<p>West, bet. secs. 2 and 35.</p> <p>Over rolling land.</p>
5.70	Trail road, bears S. 10° E. and N. 10° W.
6.75	Trail road, bears N. 15° E. and S. 15° W.
19.00	Wide Ruins Wash, 30 ft. wide, 10 ft. deep, drains S. 5° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 27 E S 35 1/4 ——— S 2 T 25 N</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 2, 3, 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 27 E S 34 S 35 S 3 S 2 T 25 N</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/>

Survey of the South Boundary,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	West, bet. secs. 3 and 34.
	Over rolling and broken land.
39.40	Wide Ruins Wash, 30 ft. wide, 10 ft. deep, drains N. 50° W.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 27 E S 34 1/4 ——— S 3 T 25 N 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
48.55	Wide Ruins Wash, 150 ft. wide, 20 ft. deep, drains S. 45° W.
79.60	Wash, 25 ft. wide, 6 ft. deep, drains S. 25° E.
80.00	Point for the cor. of secs. 3, 4, 33 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 27 E S 33 S 34 S 4 S 3 T 25 N 2004
	from which
	An iron pipe, 3 ins. diam., bears S. 14° E., 1.925 chs. dist., in the center of a concrete well casting, 3 1/2 ft. square, on top of a concrete and sandstone masonry well tank, 4 1/2 x 3 ft., projecting 4 1/2 ft. high.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling and broken.
	Soil, sandy and rocky clay with sandstone outcrops.
	Timber, piñon and juniper; undergrowth, brush and native grasses.

Survey of the South Boundary,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>West, bet. secs. 4 and 33.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E S 33 1/4 ——— S 4 T 25 N</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
43.45	<p>Navajo Route 203, a graded road, 25 ft. wide, bears N. 45° E. and S. 45° W.</p>
80.00	<p>Point for cor. of secs. 4, 5, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E S 32 S 33 S 5 S 4 T 25 N</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>West, bet. secs. 5 and 32.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the South Boundary,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 26 N R 27 E S 32 1/4 ——— S 5 T 25 N</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E S 31 S 32 S 6 S 5 T 25 N</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>West, bet. secs. 6 and 31.</p> <p>Over rolling land.</p>
1.10	<p>Trail road, bears S. 25° E. and N. 25° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E S 31 1/4 ——— S 6 T 25 N</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Survey of the South Boundary,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS													
73.20	<p>Point for the closing cor. of Tps. 25 and 26 N., R. 27 E., at intersection with the E. bdy. of T. 26 N., R. 26 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td></td> <td style="border-right: 1px solid black; padding: 0 5px;">T 26 N</td> <td style="padding: 0 5px;">R 27 E</td> <td></td> </tr> <tr> <td></td> <td style="border-right: 1px solid black; padding: 0 5px;">S 36</td> <td style="padding: 0 5px;">S 31</td> <td></td> </tr> <tr> <td></td> <td style="border-right: 1px solid black; padding: 0 5px;">R 26 E</td> <td style="padding: 0 5px;">T 25 N</td> <td style="border-left: 1px solid black; padding: 0 5px;">CC</td> </tr> </table> </div> <p align="center">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the cor. of Tps. 25 and 26 N., R. 26 E, bears South, 3.38 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. T26N T25N R26E R27E S36 S1 S6 T25N 1915 2002.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr style="width: 50%; margin: 20px auto;"/> <p align="center">Survey of the Governing Section Line, T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona</p> <hr style="width: 50%; margin: 20px auto;"/> <p>Note: The original survey of the east boundary was determined to be defective. However the errors in the alignment are compensable and do not leave the north boundary defective in position with reference to the position of the corners on the south boundary. Therefore the first meridional section line is projected as the Governing Section Line as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973.</p> <hr style="width: 50%; margin: 20px auto;"/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°15' W., bet. secs. 35 and 36.</p> <p>Over rolling and broken land.</p>		T 26 N	R 27 E			S 36	S 31			R 26 E	T 25 N	CC
	T 26 N	R 27 E											
	S 36	S 31											
	R 26 E	T 25 N	CC										
5.50	<p>S. bank of Wide Ruins Wash, 5 ft. high, bears S. 85° E. and N. 85° W.</p>												

**Survey of the Governing Section Line,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
5.90	N. bank of Wide Ruins Wash, 5 ft. high, bears S. 75° E. and N. 75° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 26 N R 27 E 1/4 S 35 S 36</p>
	<p align="center">2004</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
64.40	Underground gas pipeline, bears N. 80° E. and S. 80° W.
79.70	Trail road, bears N. 15° E. and S. 15° W.
80.00	<p>Point for the cor. of secs. 25, 26, 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 26 N R 27 E S 26 S 25 S 35 S 36</p>
	<p align="center">2004</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Cor. is located 9 lks. W. of a trail road, bears N. 15° E. and S. 15° W.</p>
	<p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p>
	<hr/> <p>N. 0°15' W., bet. secs. 25 and 26.</p>
	<p>Over rolling land.</p>
11.38	High voltage transmission line, bears S. 60° E. and N. 60° W.
36.30	Navajo Route 203, a graded road, 20 ft. wide, bears S. 80° E. and N. 80° W.

Survey of the Governing Section Line,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E 1/4 S 26 S 25</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 23, 24, 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E S 23 S 24 ----- S 26 S 25</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°15' W., bet. secs. 23 and 24.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E 1/4 S 23 S 24</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 13, 14, 23 and 24.</p>

Survey of the Governing Section Line,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E S 14 S 13 S 23 S 24</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy and gravelly clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°15' W., bet. secs. 13 and 14.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E 1/4 S 14 S 13</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 11, 12, 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E S 11 S 12 S 14 S 13</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Survey of the Governing Section Line,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy and gravelly clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°15' W., bet. secs. 11 and 12.</p> <p>Over rolling land.</p>
22.65	Trail road, bears S. 85° E. and N. 85° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E 1/4 S 11 S 12</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
71.05	Trail road, bears S. 55° E. and N. 55° W.
80.00	<p>Point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E S 2 S 1 S 11 S 12</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy and gravelly clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°15' W., bet. secs. 1 and 2.</p> <p>Over rolling land.</p>

**Survey of the Governing Section Line,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
15.80	S. rim of Burnt Piñon Wash canyon, top of sandstone ledge, bears N. 85° E. and S. 85° W.
17.45	Burnt Piñon Wash, 50 ft. wide, 4 ft. deep, drains N. 85° W.
19.70	N. rim of Burnt Piñon Wash canyon, top of sandstone ledge, bears N. 75° E. and S. 75° W.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 27 E 1/4 S 2 S 1 2004 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post.
53.50	Graded road, 15 ft. wide, bears S. 80° E. and N. 80° W.
82.74	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R27E S35 S36 S2 S1 T26N 2003. Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.
<hr/> Survey of the Subdivisional Lines, T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona <hr/>	
	From the cor. of secs. 25, 26, 35 and 36, on the governing section line, hereinbefore described. N. 89°56' E., bet. secs. 25 and 36. Over rolling land.
3.40	Trail road, bears S. 10° E. and N. 10° W.
19.95	High voltage transmission line, bears S. 60° E. and N. 60° W.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 36.

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E S 25 1/4 ——— S 36</p> <p style="text-align: center;">2004</p>
80.21	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p>
40.00	<hr/> <p>From the cor. of secs. 23, 24, 25 and 26, on the governing section line, hereinbefore described.</p> <p>East, bet. secs. 24 and 25.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E S 24 1/4 ——— S 25</p> <p style="text-align: center;">2004</p>
79.06	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the closing cor. of secs. 24 and 25, at intersection with the W. bdy. of T. 26 N., R. 28 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

T 26 N	T 26 N
S 24	R 28 E
CC	
S 25	S 30
R 27 E	

2004

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the cor. of secs. 19 and 30, T. 26 N., R. 28 E., bears N. 1°36' W., 2.47 chs. dist., hereinbefore described.

Land, rolling.
Soil, sandy and gravelly clay.
Timber, piñon and juniper; undergrowth, brush and native grasses.

Point for the 1/4 sec. cor. of sec. 25, T. 26 N., R. 27 E., at midpoint on the E. bdy. of sec. 25.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 N	
R 27 E	R 28 E
1/4	
S 25	

2004

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the 1/4 sec. cor. of sec. 30, T. 26 N., R. 28 E., bears N. 0°33' W., 53 lks. dist., hereinbefore described.

From the cor. of secs. 13, 14, 23 and 24, on the governing section line, hereinbefore described.

East, bet. secs. 13 and 24.

Over rolling land.

40.00

Point for the 1/4 sec. cor. of secs. 13 and 24.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

T 26 N R 27 E
S 13
1/4 ———
S 24

2004

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, a third order U. S. Geological bench mark "Cross Canyon 1955", bears N. 64°17' E., 18.77 chs. dist., monumented with a standard brass tablet, 3 3/4 ins. diam., firmly set flush, cemented in place on top of a sandstone, 8 x 7 ins., firmly set, projecting 8 ins. above ground, with top mkd. U. S. GEOLOGICAL BENCH MARK CROSS CANYON 1955 and a triangle.

78.67

Point for the closing cor. of secs. 13 and 24, at intersection with the W. bdy. of T. 26 N., R. 28 E.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 N	T 26 N
S 13	R 28 E
CC ———	
S 24	S 19
R 27 E	
	2004

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the cor. of secs. 18 and 19, T. 26 N., R. 28 E., bears N. 0°41' E., 3.79 chs. dist., hereinbefore described.

Land, rolling.

Soil, sandy and gravelly clay.

Timber, piñon and juniper; undergrowth, brush and native grasses.

Point for the 1/4 sec. cor. of sec. 24, T. 26 N., R. 27 E., at midpoint on the E. bdy. of sec. 24.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 26 N R 27 E R 28 E 1/4 S 24 </p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 19, T. 26 N., R. 28 E., bears N. 1°29' W., 4.14 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14, on the governing section line, hereinbefore described.</p> <p>East, bet. secs. 12 and 13.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E S 12 1/4 ——— S 13</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
44.90	Trail road, bears S. 4° E. and N. 4° W.
59.05	Trail road, bears S. 65° E. and N. 65° W.
79.02	<p>Point for the closing cor. of secs. 12 and 13, at intersection with the W. bdy. of T. 26 N., R. 28 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 5px;">T 26 N</td> <td style="border-left: 1px solid black; padding: 2px 5px;">T 26 N</td> </tr> <tr> <td style="padding: 2px 5px;">S 12</td> <td style="border-left: 1px solid black; padding: 2px 5px;">R 28 E</td> </tr> <tr> <td style="padding: 2px 5px;">CC</td> <td style="border-left: 1px solid black; padding: 2px 5px;"></td> </tr> <tr> <td style="padding: 2px 5px;">S 13</td> <td style="border-left: 1px solid black; padding: 2px 5px;">S 18</td> </tr> <tr> <td style="padding: 2px 5px;">R 27 E</td> <td style="border-left: 1px solid black; padding: 2px 5px;"></td> </tr> </table> <p style="text-align: center; margin-top: 10px;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the cor. of secs. 7 and 18, T. 26 N., R. 28 E., bears N. 0°02' W., 3.68 chs. dist., hereinbefore described.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 13, T. 26 N., R. 27 E., at midpoint on the E. bdy. of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 5px;">T 26 N</td> <td style="padding: 2px 5px;"></td> </tr> <tr> <td style="padding: 2px 5px;">R 27 E</td> <td style="padding: 2px 5px;">R 28 E</td> </tr> <tr> <td style="padding: 2px 5px;">1/4</td> <td style="border-left: 1px solid black; padding: 2px 5px;"></td> </tr> <tr> <td style="padding: 2px 5px;">S 13</td> <td style="border-left: 1px solid black; padding: 2px 5px;"></td> </tr> </table> <p style="text-align: center; margin-top: 10px;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 18, T. 26 N., R. 28 E., bears N. 0°02' W., 3.73 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12, on the governing section line, hereinbefore described.</p> <p>East, bet. secs. 1 and 12.</p> <p>Over rolling and broken land.</p> <p>17.15 W. rim of Cross Canyon, top of sandstone ledge, 60 ft. high, bears S. 40° E. and N. 40° W.</p> <p>18.10 Cross Canyon Wash, 20 ft. wide, 5 ft. deep, drains North.</p>	T 26 N	T 26 N	S 12	R 28 E	CC		S 13	S 18	R 27 E		T 26 N		R 27 E	R 28 E	1/4		S 13	
T 26 N	T 26 N																		
S 12	R 28 E																		
CC																			
S 13	S 18																		
R 27 E																			
T 26 N																			
R 27 E	R 28 E																		
1/4																			
S 13																			

**Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
19.80	E. rim of Cross Canyon, top of sandstone ledge, 60 ft. high, bears S. 25° E. and N. 25° W.								
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 27 E</p> <p>S 1</p> <p>1/4 ———</p> <p>S 12</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>								
79.95	<p>Point for the closing cor. of secs. 1 and 12, at intersection with the W. bdy. of T. 26 N., R. 28 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1" style="margin: auto;"> <tr> <td style="padding: 2px;">T 26 N</td> <td style="padding: 2px;">T 26 N</td> </tr> <tr> <td style="padding: 2px;">S 1</td> <td style="padding: 2px;">R 28 E</td> </tr> <tr> <td style="padding: 2px;">CC ———</td> <td style="padding: 2px;">S 7</td> </tr> <tr> <td style="padding: 2px;">S 12</td> <td style="padding: 2px;">R 27 E</td> </tr> </table> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the cor. of secs. 6 and 7, T. 26 N., R. 28 E., bears N. 0°12' W., 3.44 chs. dist., hereinbefore described.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 12, T. 26 N., R. 27 E., at midpoint on the E. bdy. of sec. 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	T 26 N	T 26 N	S 1	R 28 E	CC ———	S 7	S 12	R 27 E
T 26 N	T 26 N								
S 1	R 28 E								
CC ———	S 7								
S 12	R 27 E								

**Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 26 N R 27 E R 28 E 1/4 S 12 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post. From this cor. point, the 1/4 sec. cor. of sec. 7, T. 26 N., R. 28 E., bears N. 1°02' E., 3.25 chs. dist., hereinbefore described.
	<hr/> Point for the 1/4 sec. cor. of sec. 1, T. 26 N., R. 27 E., at 40.00 chs. northerly from the closing cor. of secs. 1 and 12, on the E. bdy. of sec. 1. Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place on sandstone bedrock, with top mkd.
	T 26 N R 27 E R 28 E 1/4 S 1 2004
	Deposit a magnet in a white plastic case at the base of the brass tablet. From this cor. point, the 1/4 sec. cor. of sec. 6, T. 26 N., R. 28 E., bears N. 0°08' E., 3.10 chs. dist., hereinbefore described.
	<hr/> From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described. N. 0°16' W., bet. secs. 34 and 35. Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 34 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 26 N R 27 E 1/4 S 34 S 35 2004 Deposit a magnet in a white plastic case at the base of the stainless steel post.
53.90	Underground gas pipeline, bears S. 85° E. and N. 85° W.
80.00	Point for the cor. of secs. 26, 27, 34 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 27 E S 27 S 26 S 34 S 35 2004 Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.
	<hr/> From the cor. of secs. 25, 26, 35 and 36, on the governing section line, hereinbefore described.
	West, bet. secs. 26 and 35. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 27 E S 26 1/4 ——— S 35 2004 Deposit a magnet in a white plastic case at the base of the stainless steel post.

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The cor. of secs. 26, 27, 34 and 35.</p> <p>Land, rolling. Soil, sandy and gravelly clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/>
	<p>N. 0°16' W., bet. secs. 26 and 27.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E 1/4 S 27 S 26</p> <p style="text-align: center;">2004</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
41.65	<p>Trail road, bears S. 10° E. and N. 10° W.</p>
56.20	<p>Navajo Route 203, a graded road, 20 ft. wide, bears N. 35° E. and S. 35° W.</p>
57.10	<p>High voltage transmission line, bears S. 60° E. and N. 60° W.</p>
80.00	<p>Point for the cor. of secs. 22, 23, 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E S 22 S 23 S 27 S 26</p> <p style="text-align: center;">2004</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/>

**Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 23, 24, 25 and 26, on the governing section line, hereinbefore described.</p> <p>West, bet. secs. 23 and 26.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E S 23 1/4 ——— S 26</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°16' W., bet. secs. 22 and 23.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E 1/4 S 22 S 23</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
59.05	<p>Trail road, bears N. 50° E. and S. 50° W.</p>
80.00	<p>Point for the cor. of secs. 14, 15, 22 and 23.</p>

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS							
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="812 451 1039 556"> <tr> <td>T 26 N</td> <td>R 27 E</td> </tr> <tr> <td>S 15</td> <td>S 14</td> </tr> <tr> <td>S 22</td> <td>S 23</td> </tr> </table> <p>2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p>	T 26 N	R 27 E	S 15	S 14	S 22	S 23
T 26 N	R 27 E						
S 15	S 14						
S 22	S 23						
	<hr/> <p>From the cor. of secs. 13, 14, 23 and 24, on the governing section line, hereinbefore described.</p> <p>West, bet. secs. 14 and 23.</p> <p>Over rolling land.</p>						
<p>40.00</p>	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="812 1270 1039 1386"> <tr> <td>T 26 N</td> <td>R 27 E</td> </tr> <tr> <td>S 14</td> <td>1/4 —</td> </tr> <tr> <td>S 23</td> <td></td> </tr> </table> <p>2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 26 N	R 27 E	S 14	1/4 —	S 23	
T 26 N	R 27 E						
S 14	1/4 —						
S 23							
<p>47.60</p>	<p>Trail road, bears N. 60° E. and S. 60° W.</p>						
<p>80.00</p>	<p>The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°16' W., bet. secs. 14 and 15.</p> <p>Over rolling land.</p>						

**Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E 1/4 S 15 S 14</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 10, 11, 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E S 10 S 11 S 15 S 14</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14, on the governing section line, hereinbefore described.</p> <p>West, bet. secs. 11 and 14.</p> <p>Over rolling land.</p>
26.60	Trail road, bears S. 20° E. and N. 20° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 26 N R 27 E S 11 1/4 ——— S 14 2004 Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	The cor. of secs. 10, 11, 14 and 15. Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.
	N. 0°16' W., bet. secs. 10 and 11. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 27 E 1/4 S 10 S 11 2004 Deposit a magnet in a white plastic case at the base of the stainless steel post.
60.30	Trail road, bears S. 60° E. and N. 60° W.
69.40	Trail road, bears N. 85° E. and N. 85° W.
80.00	Point for the cor. of secs. 2, 3, 10 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 27 E S 3 S 2 ——— S 10 S 11 2004 Deposit a magnet in a white plastic case at the base of the stainless steel post.

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12, on the governing section line, hereinbefore described.</p> <p>West, bet. secs. 2 and 11.</p> <p>Over rolling land.</p>
11.00	Trail road, bears S. 55° E. and N. 55° W.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 11.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E S 2 1/4 ——— S 11</p> <p style="text-align: center;">2004</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
54.90	Trail road, bears S. 40° E. and N. 40° W.
80.00	The cor. of secs. 2, 3, 10 and 11.
	<p>Land, rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°16' W., bet. secs. 2 and 3.</p> <p>Over rolling and broken land.</p>
17.35	Trail road, bears N. 30° E. and S. 30° W.
38.55	Trail road, bears S. 80° E. and N. 80° W.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 3.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 26 N R 27 E 1/4 S 3 S 2 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located 1.53 chs. E. of a trail road, bears N. 10° E. and S. 10° W.
66.60	Trail road, bears S. 25° E. and N. 25° W.
70.65	Fish Wash, 50 ft. wide, 4 ft. deep, drains N. 25° W.
76.50	Trail road, bears S. 65° E. and N. 65° W.
82.74	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R27E S34 S35 S3 S2 T26N 2003.
	Land, rolling and broken. Soil, sandy and rocky clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.
	<hr/> From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°16' W., bet. secs. 33 and 34.
	Over rolling land.
6.40	Graded road, 15 ft. wide, bears S. 60° E. and N. 60° W.
19.05	Graded road, 15 ft. wide, bears N. 15° E. and S. 15° W.
39.50	Navajo Route 203, a graded road, 20 ft. wide, bears N. 20° E. and S. 20° W.
40.00	Point for the 1/4 sec. cor. of secs. 33 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 27 E 1/4 S 33 S 34 2004

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located on the W. edge of Navajo Route 203, a graded road, 20 ft. wide, bears NNE and SSW.</p>								
62.10	Underground gas pipelines, bear S. 80° E. and N. 80° W.								
80.00	<p>Point for the cor. of secs. 27, 28, 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="812 798 1039 903" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 26 N</td> <td>R 27 E</td> </tr> <tr> <td>S 28</td> <td>S 27</td> </tr> <tr> <td>S 33</td> <td>S 34</td> </tr> </table> <p style="text-align: center;">2004</p>	T 26 N	R 27 E	S 28	S 27	S 33	S 34		
T 26 N	R 27 E								
S 28	S 27								
S 33	S 34								
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p>								
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>West, bet. secs. 27 and 34.</p> <p>Over rolling land.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="812 1585 1039 1711" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 26 N</td> <td>R 27 E</td> </tr> <tr> <td>S 27</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 34</td> <td></td> </tr> </table> <p style="text-align: center;">2004</p>	T 26 N	R 27 E	S 27		1/4	—	S 34	
T 26 N	R 27 E								
S 27									
1/4	—								
S 34									
43.95	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Navajo Route 203, a graded road, 20 ft. wide, bears N. 60° E. and S. 60° W.</p>								

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
69.50	Trail road, bears N. and S.
80.00	<p>The cor. of secs. 27, 28, 33 and 34.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/>
40.00	<p>N. 0°16' W., bet. secs. 27 and 28.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E 1/4 S 28 S 27</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 21, 22, 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E S 21 S 22 S 28 S 27</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/>
	<p>From the cor of secs. 22, 23, 26 and 27.</p> <p>West, bet. secs. 22 and 27.</p> <p>Over rolling land.</p>

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E S 22 1/4 ——— S 27</p> <p style="text-align: center;">2004</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Cor. is located in center of trail road under the high voltage transmission line, bears S. 60° E. and N. 60° W.</p>
60.70	<p>Apache County Road C450, a graded road, 20 ft. wide, bears S. 30° E. and N. 30° W.</p>
62.45	<p>Trail road, bears N. 15° E. and S. 15° W.</p>
80.00	<p>The cor. of secs. 21, 22, 27 and 28.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/>
	<p>N. 0°16' W., bet. secs. 21 and 22.</p> <p>Over rolling land.</p>
7.40	<p>Trail road, bears N. 60° E. and S. 60° W.</p>
22.50	<p>Apache County Road C450, a graded road, 20 ft. wide, bears S. 30° E. and N. 30° W.</p>
22.85	<p>High voltage transmission line, bears S. 60° E. and N. 60° W.</p>
35.35	<p>Graded road, 15 ft. wide, bears N. 35° E. and S. 35° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p style="text-align: center;">T 26 N R 27 E 1/4 S 21 S 22</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 15, 16, 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E S 16 S 15 S 21 S 22</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p>
40.00	<hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>West, bet. secs. 15 and 22.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E S 15 1/4 ——— S 22</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 89 lks. E. of a woven wire fence, with barbed wire, 3 strands, bears N. 45° E. and S. 45° W.</p>

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
49.90	Woven wire fence, with barbed wire, 3 strands, bears N. 45° E. and S. 45° W.
50.35	Trail road, bears N. 50° E. and S. 50° W.
80.00	<p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°16' W., bet. secs. 15 and 16.</p> <p>Over rolling land.</p>
37.45	Apache County Road C450, a graded road, 20 ft. wide, bears N. 20° E. and S. 20° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
<p>T 26 N R 27 E 1/4 S 16 S 15 2004</p>	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	<p>Point for the cor. of secs. 9, 10, 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
<p>T 26 N R 27 E S 9 S 10 ----- S 16 S 15 2004</p>	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy and gravelly clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15. West, bet. secs. 10 and 15. Over rolling land.</p>
31.55	Trail road, bears N. 25° E. and S. 25° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E S 10 1/4 ——— S 15</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
63.55	Apache County Road C450, a graded road, 20 ft. wide, bears N. 30° E. and S. 30° W.
80.00	<p>The cor. of secs. 9, 10, 15 and 16. Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°16' W., bet. secs. 9 and 10. Over rolling land.</p>
38.73	Barbed wire fence, 5 strands, bears N. 33° E. and S. 33° W.
39.45	Trail road, bears N. 40° E. and S. 40° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 26 N R 27 E 1/4 S 9 S 10 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
40.62	Barbed wire fence, 5 strand, bears N. 35° E. and S. 35° W.
44.55	Trail road, bears N. 75° E. and S. 75° W.
80.00	Point for the cor. of secs. 3, 4, 9 and 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 27 E S 4 S 3 <hr style="width: 50%; margin: 0 auto;"/> S 9 S 10 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.
	From the cor. of secs. 2, 3, 10 and 11.
	West, bet. secs. 3 and 10.
	Over rolling land.
33.95	Trail road, bears N. 30° E. and S. 30° W.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 27 E S 3 1/4 ——— S 10 2004

**Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
59.20	Apache County Road C450, a graded road, 20 ft. wide, bears N. and S.
80.00	The cor. of secs. 3, 4, 9 and 10. Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.
	<hr/>
	N. 0°16' W., bet. secs. 3 and 4. Over rolling land.
23.05	Trail road, bears S. 55° E. and N. 55° W.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 27 E 1/4 S 4 S 3 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
59.76	Trail road, bears N. 35° E. and S. 35° W.
82.74	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R27E S33 S34 S4 S3 T26N 2003. Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.
	<hr/>
	From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described. N. 0°17' W., bet. secs. 32 and 33. Over rolling land.

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E 1/4 S 32 S 33</p> <p style="text-align: center;">2004</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
57.00	<p>Trail road, bears S. 45° E. and N. 45° W.</p>
63.70	<p>Underground gas pipelines, bear E. and W.</p>
80.00	<p>Point for the cor. of secs. 28, 29, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E S 29 S 28 S 32 S 33</p> <p style="text-align: center;">2004</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Land, rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p>
	<hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p>
	<p>West, bet. secs. 28 and 33.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 26 N R 27 E S 28 1/4 ——— S 33</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
47.50	Trail road, bears S. 35° E. and N. 35° W.
80.00	The cor. of secs. 28, 29, 32 and 33.
	<p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°17' W., bet. secs. 28 and 29.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 26 N R 27 E 1/4 S 29 S 28</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
41.20	Trail road, bears S. 75° E. and S. 75° W.
80.00	Point for the cor. of secs. 20, 21, 28 and 29.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 26 N R 27 E S 20 S 21 S 29 S 28</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28. West, bet. secs. 21 and 28. Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 28. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E S 21 1/4 ——— S 28</p> <p style="text-align: center;">2004</p>
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 20, 21, 28 and 29.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/>
40.00	<p>N. 0°17' W., bet. secs. 20 and 21. Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 20 and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E 1/4 S 20 S 21</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
63.90	High voltage transmission line, bears S. 65° E. and N. 65° W.								
80.00	Point for the cor. of secs. 16, 17, 20 and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 26 N</td><td>R 27 E</td></tr> <tr><td>S 17</td><td>S 16</td></tr> <tr><td>S 20</td><td>S 21</td></tr> </table> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>West, bet. secs. 16 and 21.</p> <p>Over rolling land.</p>	T 26 N	R 27 E	S 17	S 16	S 20	S 21		
T 26 N	R 27 E								
S 17	S 16								
S 20	S 21								
16.65	Apache County Road C450, a graded road, 20 ft. wide, bears N. 10° E. and S. 10° W.								
40.00	Point for the 1/4 sec. cor. of secs. 16 and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 26 N</td><td>R 27 E</td></tr> <tr><td></td><td>S 16</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S 21</td></tr> </table> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 26 N	R 27 E		S 16	1/4	—		S 21
T 26 N	R 27 E								
	S 16								
1/4	—								
	S 21								
80.00	The cor. of secs. 16, 17, 20 and 21. Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.								

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>N. 0°17' W., bet. secs. 16 and 17.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E 1/4 S 17 S 16</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 8, 9, 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E S 8 S 9 S 17 S 16</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>West, bet. secs. 9 and 16.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 26 N R 27 E S 9 1/4 ——— S 16</p> <p style="text-align: center;">2004</p>
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/>
	<p>N. 0°17' W., bet. sec. 8 and 9.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 26 N R 27 E 1/4 S 8 S 9</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located in the center of an abandoned sheep corral, 85 ft. diam.</p>
42.50	<p>Trail road, bears S. 35° E. and N. 35° W.</p>
80.00	<p>Point for the cor. of secs. 4, 5, 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 26 N R 27 E S 5 S 4 ——— S 8 S 9</p> <p style="text-align: center;">2004</p>

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>West, bet. secs. 4 and 9.</p> <p>Over rolling land.</p>
36.60	Trail road, bears S. 25° E. and N. 25° W.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 9.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E S 4 1/4 ——— S 9</p> <p style="text-align: center;">2004</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
41.20	Trail road, bears N. 20° E. and S. 20° W.
80.00	The cor. of secs. 4, 5, 8 and 9.
	<p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°17' W., bet. secs. 4 and 5.</p> <p>Over rolling land.</p>
25.15	Trail road, bears N. 25° E. and S. 25° W.
39.90	Trail road, bears S. 40° E. and N. 40° W.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5.

**Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E 1/4 S 5 S 4 2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
40.35	Graded road, 17 ft. wide, bears S. 85° E. and N. 85° W.
76.80	Trail road, bears N. 45° E. and S. 45° W.
82.74	<p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R27E S32 S33 S5 S4 T26N 2003.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°18' W., bet. secs. 31 and 32.</p> <p>Over rolling land.</p>
4.60	Trail road, bears N. 25° E. and S. 25° W.
34.55	Barbed wire fence, 5 strand, bears N. 85° E. and S. 85° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E 1/4 S 31 S 32 2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
62.66	Barbed wire fence, 5 strand, bears N. 70° E. and S. 70° W.

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS									
65.80	Underground gas pipelines, bear N. 80° E. and S. 80° W.								
80.00	<p>Point for the cor. of secs. 29, 30, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 26 N</td> <td>R 27 E</td> </tr> <tr> <td>S 30</td> <td>S 29</td> </tr> <tr> <td>S 31</td> <td>S 32</td> </tr> </table>	T 26 N	R 27 E	S 30	S 29	S 31	S 32		
T 26 N	R 27 E								
S 30	S 29								
S 31	S 32								
	2004								
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>								
	<p>Land, rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p>								
	<hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p>								
	<p>West, bet. secs. 29 and 32.</p>								
	<p>Over rolling land.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 26 N</td> <td>R 27 E</td> </tr> <tr> <td></td> <td>S 29</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td></td> <td>S 32</td> </tr> </table>	T 26 N	R 27 E		S 29	1/4	_____		S 32
T 26 N	R 27 E								
	S 29								
1/4	_____								
	S 32								
	2004								
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>								
51.10	Trail road, bears N. 25° E. and S. 25° W.								
57.25	Trail road, bears N. 30° E. and S. 30° W.								
80.00	The cor. of secs. 29, 30, 31 and 32.								

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>West, bet. secs. 30 and 31.</p> <p>Over rolling land.</p>
22.00	Trail road, bears N. 30° E. and S. 30° W.
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 26 N R 27 E S 30 1/4 ——— S 31 2004 </p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
72.78	Point for the closing cor. of secs. 30 and 31, at intersection with the E. bdy. of T. 26 N., R. 26 E.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 26 N T 26 N R 26 E S 30 ———— ———CC S 25 S 31 R 27 E 2004 </p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the cor. of secs. 25 and 36, T. 26 N., R. 26 E, bears S. 0°02' E., 3.41 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T26N R26E S25 S36 T26N R27E S31 2002.</p> <p>from which</p>

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A dead piñon, 10 ins. diam., bears N. 56 1/2° W., 63 lks. dist., with scribe marks T26N R6E S25 BT visible on partially healed blaze. (Record: 61 lks.)</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 31, T. 26 N., R. 27 E., at midpoint on the W. bdy. of sec. 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 26 E R 27 E 1/4 S 31</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 36, T. 26 N., R. 26 E., bears South, 3.40 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground with brass cap mkd. T26N R26E R27E 1/4 S36 2002.</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 13 ins. diam., bears N. 36 1/2° W., 10 lks. dist., with scribe marks 1/4 S36 BT visible on an open blaze.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°18' W., bet. secs. 29 and 30.</p> <p>Over rolling land.</p>
28.00	Trail road, bears N. 45° E. and S. 45° W.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 30.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E 1/4 S 30 S 29</p> <p style="text-align: center;">2004</p>

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>								
80.00	<p>Point for the cor. of secs. 19, 20, 29 and 30.</p>								
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 0 10px;">T 26 N</td> <td style="padding: 0 10px;">R 27 E</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 19</td> <td style="padding: 0 10px;">S 20</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 30</td> <td style="padding: 0 10px;">S 29</td> </tr> </table>	T 26 N	R 27 E	S 19	S 20	S 30	S 29		
T 26 N	R 27 E								
S 19	S 20								
S 30	S 29								
	<p style="text-align: center;">2004</p>								
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/>								
	<p>From the cor. of secs. 20, 21, 28 and 29.</p>								
	<p>West, bet. secs. 20 and 29.</p>								
17.20	<p>Apache County Road C428, a graded road, 20 ft. wide, bears S. 40° E. and N. 40° W.</p>								
33.85	<p>Trail road, bears N. 35° E. and S. 35° W.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p>								
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 0 10px;">T 26 N</td> <td style="padding: 0 10px;">R 27 E</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 20</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="padding: 0 10px;">—</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 29</td> </tr> </table>	T 26 N	R 27 E		S 20	1/4	—		S 29
T 26 N	R 27 E								
	S 20								
1/4	—								
	S 29								
	<p style="text-align: center;">2004</p>								
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>								
80.00	<p>The cor. of secs. 19, 20, 29 and 30.</p>								

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/>
	<p>West, bet. secs. 19 and 30. Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E S 19 1/4 ——— S 30</p> <p style="text-align: center;">2004</p>
72.38	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the closing cor. of secs. 19 and 30, at intersection with the E. bdy. of T. 26 N., R. 26 E. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N T 26 N R 26 E S 19 S 24 ——— CC S 30 R 27 E</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>From this cor. point, the cor. of secs. 24 and 25, T. 26 N., R. 26 E, bears S. 0°04' W., 3.48 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. T26N T26N R26E R27E S24 S30 S25 2002 1915.</p> <p>Land, rolling. Soil, sandy and gravelly clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/>

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Point for the 1/4 sec. cor. of sec. 30, T. 26 N., R. 27 E., at midpoint on the W. bdy. of sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 26 E R 27 E 1/4 S 30</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 25, T. 26 N., R. 26 E., bears South, 3.46 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground with brass cap mkd. T26N R26E R27E 1/4 S25 2002.</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 11 ins. diam., bears S. 56 3/4° W., 40 lks. dist., with illegible scribe marks on a partially open blaze.</p>
	<hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°18' W., bet. secs. 19 and 20.</p> <p>Over rolling land.</p>
<p>40.00</p>	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E 1/4 S 19 S 20</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
<p>80.00</p>	<p>Point for the cor. of secs. 17, 18, 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<table border="0"> <tr> <td>T 26 N</td> <td>R 27 E</td> </tr> <tr> <td>S 18</td> <td>S 17</td> </tr> <tr> <td>S 19</td> <td>S 20</td> </tr> </table> <p>2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy and gravelly clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>West, bet. secs. 17 and 20.</p> <p>Over rolling land.</p>	T 26 N	R 27 E	S 18	S 17	S 19	S 20		
T 26 N	R 27 E								
S 18	S 17								
S 19	S 20								
34.50	High voltage transmission line, bears S. 65° E. and N. 65° W.								
40.00	Point for the 1/4 sec. cor. of secs. 17 and 20.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="0"> <tr> <td>T 26 N</td> <td>R 27 E</td> </tr> <tr> <td>S 17</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 20</td> <td></td> </tr> </table> <p>2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 26 N	R 27 E	S 17		1/4	—	S 20	
T 26 N	R 27 E								
S 17									
1/4	—								
S 20									
60.65	Apache County Road C428, a graded road, 20 ft. wide, bears S. 25° E. and N. 25° W.								
80.00	The cor. of secs. 17, 18, 19 and 20.								
	Land, rolling. Soil, sandy and gravelly clay. Timber, piñon and juniper; undergrowth, brush and native grasses. <hr/> <p>West, bet. secs. 18 and 19.</p> <p>Over rolling land.</p>								

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E S 18 1/4 ——— S 19</p> <p style="text-align: center;">2004</p>
71.79	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the closing cor. of secs. 18 and 19, at intersection with the E. bdy. of T. 26 N., R. 26 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N T 26 N R 26 E S 18 S 13 ——— CC S 19 R 27 E</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the cor. of secs. 13 and 24, T. 26 N., R. 26 E, bears S. 0°01' W., 3.50 chs. dist., monumented with stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T26N R26E R27E S13 S24 S19 2002.</p> <p>from which</p> <ul style="list-style-type: none"> A forked juniper, 19 ins. diam., bears N. 76 1/2° E., 75 lks. dist., with illegible scribe marks on a partially healed blaze. A forked juniper, 14 ins. diam., bears S. 70 3/4° W., 11 lks. dist., with a healed blaze. A forked piñon, 10 ins. diam., bears N. 34 1/2° W., 33 1/2 lks. dist., with illegible scribe marks on an open blaze. (Record: N. 31 3/4° W., 36 lks. dist.)

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy and gravelly clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 19, T. 26 N., R. 27 E., at midpoint on the W. bdy. of sec. 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 26 E R 27 E 1/4 S 19</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 24, T. 26 N., R. 26 E., bears S. 0°10' W., 3.50 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground with brass cap mkd. T26N R26E R27E 1/4 S24 2002.</p> <p>from which</p> <div style="margin-left: 40px;"> <p>A forked juniper, 12 ins. diam., bears S. 38 1/4° E., 41 lks. dist., with scribe marks 1/4 S24 S19 BT visible on an open blaze.</p> </div> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°18' W., bet. secs. 17 and 18.</p> <p>Over rolling land.</p> <p>21.29 High voltage transmission line, bears S. 65° E. and N. 65° W.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 27 E 1/4 S 18 S 17</p> <p>2004</p> </div>

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS									
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
43.55	Apache County Road C428, a graded road, 20 ft. wide, bears S. 30° E. and N. 30° W.								
80.00	Point for the cor. of secs. 7, 8, 17 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="1" style="margin: auto;"> <tr> <td>T 26 N</td> <td>R 27 E</td> </tr> <tr> <td>S 7</td> <td>S 8</td> </tr> <tr> <td>S 18</td> <td>S 17</td> </tr> </table>	T 26 N	R 27 E	S 7	S 8	S 18	S 17		
T 26 N	R 27 E								
S 7	S 8								
S 18	S 17								
	2004								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Land, rolling. Soil, sandy and gravelly clay. Timber, piñon and juniper; undergrowth, brush and native grasses.								
	From the cor. of secs. 8, 9, 16 and 17.								
	West, bet. secs. 8 and 17.								
	Over rolling land.								
40.00	Point for the 1/4 sec. cor. of secs. 8 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="1" style="margin: auto;"> <tr> <td>T 26 N</td> <td>R 27 E</td> </tr> <tr> <td></td> <td>S 8</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 17</td> </tr> </table>	T 26 N	R 27 E		S 8	1/4	—		S 17
T 26 N	R 27 E								
	S 8								
1/4	—								
	S 17								
	2004								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
80.00	The cor. of secs. 7, 8, 17 and 18.								

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy and gravelly clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p>
	<p>West, bet. secs. 7 and 18.</p>
	<p>Over rolling land.</p>
26.20	<p>Apache County Road C428, a graded road, 20 ft. wide, bears S. 40° E. and N. 40° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 26 N R 27 E S 7 1/4 ——— S 18</p>
	<p style="text-align: center;">2004</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
71.36	<p>Point for the closing cor. of secs. 7 and 18, at intersection with the E. bdy. of T. 26 N., R. 26 E. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 26 N T 26 N R 26 E S 7 ——— CC S 12 S 18 R 27 E</p>
	<p style="text-align: center;">2004</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>From this cor. point, the cor. of secs. 12 and 13, T. 26 N., R. 26 E, bears S. 0°02' E., 3.64 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. T26N T26N R26E R27E S12 S13 S18 2002 1915.</p>
	<p>from which</p>

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>A dead piñon, 15 ins. diam., bears S. 39 3/4° W., 16 lks. dist., with a healed blaze.</p> <p>A dead piñon, 9 ins. diam., bears S. 36 3/4° W., 22 lks. dist., with scribe marks T26N R26E S13 BT visible on an open blaze.</p> <p>Land, rolling. Soil, sandy and gravelly clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 18, T. 26 N., R. 27 E., at midpoint on the W. bdy. of sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 26 E R 27 E 1/4 S 18</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 13, T. 26 N., R. 26 E., bears South, 3.51 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground with brass cap mkd. T26N R26E R27E 1/4 S13 2002.</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 8 ins. diam., bears N. 87° W., 31 lks. dist., with scribe marks 1/4 S13 BT visible on open blaze.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°18' W., bet. secs. 7 and 8.</p> <p>Over rolling land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
--------	--

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 26 N R 27 E 1/4 S 7 S 8 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
78.56	Woven wire fence, with 3 strands of barbed wire, bears S. 60° E. and N. 60° W.
80.00	Point for the cor. of secs. 5, 6, 7 and 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 27 E S 6 S 5 <hr style="width: 50%; margin: 0 auto;"/> S 7 S 8 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.
	From the cor. of secs. 4, 5, 8 and 9.
	West, bet. secs. 5 and 8.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 27 E S 5 1/4 ——— S 8 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The cor. of secs. 5, 6, 7 and 8.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/>
	<p>West, bet. secs. 6 and 7.</p>
	<p>Over rolling land.</p>
2.45	<p>Woven wire fence, with 3 strands of barbed wire, bears S. 60° E. and N. 60° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 26 N R 27 E S 6 1/4 ——— S 7</p>
	<p style="text-align: center;">2004</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
40.20	<p>Wash, 10 ft. wide, 6 ft. deep, drains N. 55° W.</p>
53.80	<p>High voltage transmission line, bears N. 45° E. and S. 45° W.</p>
70.98	<p>Point for the closing cor. of secs. 6 and 7, at intersection with the E. bdy. of T. 26 N., R. 26 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 26 N T 26 N R 26 E S 6 S 1 ——— CC S 7 R 27 E</p>
	<p style="text-align: center;">2004</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this cor. point, the cor. of secs. 1 and 12, T. 26 N., R. 26 E, bears S. 0°01' E., 3.64 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. T26N T26N R26E R27E S1 S12 S7 2002 1915.

Land, rolling.
Soil, sandy clay.
Timber, scattered piñon and juniper; undergrowth, brush and native grasses.

Point for the 1/4 sec. cor. of sec. 7, T. 26 N., R. 27 E., at midpoint on the W. bdy. of sec. 7.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 N
R 26 E R 27 E
 | 1/4
 | S 7

2004

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the 1/4 sec. cor. of sec. 12, T. 26 N., R. 26 E., bears S. 0°02' E., 3.64 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground with brass cap mkd. T26N R26E R27E 1/4 S12 2002.

Point for the 1/4 sec. cor. of sec. 6, T. 26 N., R. 27 E., at 40.00 chs. northerly from the closing cor. of secs. 6 and 7, on the W. bdy. of sec. 6.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 N
R 26 E R 27 E
 | 1/4
 | S 6

2004

Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this cor. point, the 1/4 sec. cor. of sec. 1, T. 26 N., R. 26 E., bears S. 0°01' E., 3.635 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground with brass cap mkd. T26N R26E R27E 1/4 S1 2002.</p> <p>From this same cor. point, the cor. of Tps. 26 and 27 N., R. 26 E., bears N. 0°01' W., 36.37 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. T27N T26N R26E R27E S36 S1 S6 T26N 1990 1915 2002.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°18' W., bet. secs. 5 and 6.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E 1/4 S 6 S 5 2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
54.85	Trail road, bears S. 70° E. and N. 70° W.
58.05	High voltage transmission line, bears N. 45° E. and S. 45° W.
82.74	<p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R27E S31 S32 S6 S5 T26N 2003.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/>

T. 26 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

The area surveyed is about 3 miles southeast of the community of Ganada, Arizona, on the Navajo Indian Reservation. The terrain is mostly rolling land. The drainage is to the north and south, where the Wide Ruins Wash partially runs along the south boundary and drains southwesterly. The Burnt Piñon Wash enters the township in section 1 and drains into Fish Wash in section 3 and exits northwesterly.

The elevation varies from 6700 to 7200 feet above sea level. The soil is mostly sandy clay with various areas as gravel clay. The timber consists of primarily piñon and juniper. Undergrowth consists of various brush and native grasses.

The main access to the area is provided by three graded roads, the Apache County Road C428, C450 and Navajo Route 203. From these roads there are numerous trail roads to permanent residents throughout the township. There are several scattered pastures for grazing livestock. There is no evidence of any current mining activity.

The mean magnetic declination of 11 1/4' E. was derived from the computer program GEOMAGIX utilizing the World Magnetic Model for Epoch 2000 for the dates of survey.
