

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

SURVEY OF A PORTION OF THE TENTH STANDARD PARALLEL NORTH (SOUTH BOUNDARY),
TOWNSHIP 41 NORTH, RANGE 9 EAST

AND THE

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
THE SURVEY OF A PORTION OF THE SECOND GUIDE MERIDIAN EAST (WEST BOUNDARY),
THE SOUTH AND EAST BOUNDARIES

AND

A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 NORTH, RANGE 9 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA

EXECUTED BY

Leonard R. Sandoval, Cadastral Surveyor

Under Special Instructions dated April 26, 2005, approved April 26, 2005,
which provided for the surveys included under Group No. 950 and assignment
instructions dated January 20, 2005.

Survey commenced January 25, 2005

Survey completed June 23, 2005

INDEX DIAGRAM

TOWNSHIP 40 NORTH RANGE 9 EAST
 GILA AND SALT RIVER MERIDIAN, ARIZONA

Tenth Standard Parallel North (south boundary), T. 41 N., R. 9 E.

			34 4		35 5		36 7				
6		5		4		49 12 3		49 47 2		40 38 1 29	
7		8		9		55 11 10		47 46 11		38 37 12 28	
8 18 18		9 69 17		10 619 16		55 54 15		45 45 14		36 35 13 27	
67 17 19		67 66 20		60 59 21		53 53 22		44 43 23		35 34 24 26	
66 16 30		65 64 29		58 57 28		52 51 27		42 42 26		33 32 25 26	
63 14 31 24		63 62 32 23		57 56 33 22		51 50 34 21		41 40 35 20		32 31 36 25 19	

Tps. 40 and 41 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the survey of a portion of the Tenth Standard Parallel North (south boundary), Township 41 North, Range 9 East and the dependent resurvey of a portion of the subdivisional lines, the survey of a portion of the Second Guide Meridian East (west boundary), the south and east boundaries and a portion of the subdivisional lines, Township 40 North, Range 9 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

W. E. Hiester and Otis O. Gould surveyed a portion of the Ninth Standard Parallel North (south boundary), Township 37 North, Range 5 East, in 1927. Robert C. Yundt, Boyd S. Owens and Virgil E. Spratt surveyed a portion of the Tenth Standard Parallel North (south boundary), Township 41 North, Range 9 East, in 1959. Robert C. Yundt and Boyd S. Owens surveyed a portion of the east boundary (Second Guide Meridian East), Township 40 North, Range 8 East and a portion of the subdivisional lines, Township 40 North, Range 9 East, in 1959. Jones Curtiss, William F. Olver and Leonard R. Sandoval dependently resurveyed a portion of the subdivisional lines, Township 41 North, Range 9 East, in 2001.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, the Assignment Instructions dated January 20, 2005 and the Special Instructions dated April 26, 2005, for Group No. 950, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of the record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System(GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) FLAGSTAFF, FERNO MESA AND FREDONIA VLBA. The NAD83(CORS96)(EPOCH:2002) geographic position of the southeast corner of the township is as follows:

Latitude: 36°48'59.12" N. Longitude: 111°22'15.36" W.

The mean magnetic declination is 12° E.

Survey of a Portion of the Tenth Standard Parallel North
 (South Boundary),
 T. 41 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Beginning at the stan. cor. of secs. 33 and 34, monumented with an iron post, 2 1/2 ins. diam., set flush with the surface of the ground, with brass cap mkd. SC T41N R9E S33 S34 2001 1959.</p> <p>At the corner point</p> <p>Reset the iron post, 30 ins. long, 24 ins. in ground.</p> <p>Deposit a magnet, in a white plastic case, at the base of the iron post.</p> <p>Add the marks 2005 to the brass cap.</p> <p>East, on the S. bdy. of sec. 34.</p> <p>Over rolling and broken land.</p>
23.90	W. rim of canyon of Antelope Creek, bears N. 5° E. and S. 5° W.
34.10	E. rim of canyon of Antelope Creek, bears S. 20° E. and N. 20° W.
40.00	<p>Point for the stan. 1/4 sec. cor. of sec. 34.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole in a sandstone outcrop, with top mkd.</p> <p style="text-align: center;">SC T 41 N R 9 E 1/4 S 34 <hr style="width: 10%; margin: auto;"/> 2005</p> <p>Deposit a magnet, in the drill hole, at the base of the brass tablet.</p>
56.09	W. right-of-way fence of Navajo Route 22B, barbed wire, 5 strands, parallels highway.
56.49	A brass tablet, 3 ins. diam., firmly set in a concrete collar, 6 ins. diam., set flush with surface of the ground, bears South, 83 lks. dist., with top mkd. B. I. A. ROADS 19, witnessed by an angle iron, firmly set nearby, with side mkd. STA.22+67.76.
57.76	Navajo Route 22B, asphalt pavement, 38 ft. wide, bears S. 25° E. and N. 25° W.

Survey of a Portion of the Tenth Standard Parallel North
 (South Boundary),
 T. 41 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
59.19	A brass tablet, 3 ins. diam., firmly set in a concrete collar, 6 ins. diam., set flush with surface of the ground, bears South, 53 lks. dist., with top mkd. B. I. A. ROADS 19, witnessed by an angle iron, firmly set nearby, with side mkd. STA.22+67.76.
59.45	E. right-of-way fence of Navajo Route 22B, barbed wire, 5 strands, parallels highway.
74.36	Power line, bears N. 10° E. and S. 10° W.
80.00	Point for the stan. cor. of secs. 34 and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	SC T 41 N R 9 E S 34 S 35
	2005
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling and broken. Soil, sand and sandy clay with sandstone outcrops. No timber, scattered brush and native grasses.
	East, on the S. bdy. of sec. 35.
	Over rolling land.
10.55	The westerly fence surrounding the Navajo Generating Station, woven wire with 1 strand of barbed wire, bears N. 10° E. and S. 10° W.,.
18.40	W. rim of a mesa, top of a sandstone ledge, bears N. 50° E. and S. 50° W.
22.85	Road, graded gravel, 15 ft. wide, bears N. 30° E. and S. 30° W.
25.10	High voltage transmission line, bears N. 70° E. and S. 70° W.
27.22	The westerly fence surrounding a high voltage transformer substation, chain link, 6 ft. high, with 3 strands of barbed wire, bears N. 70° E. and S. 70° W.

Survey of a Portion of the Tenth Standard Parallel North
(South Boundary),
T. 41 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>True point for the stan. 1/4 sec. cor. of sec. 35, falls on an electrical transformer; where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for the witness cor. to the stan. 1/4 sec. cor. of sec. 35, bears N. 40°00' W., 5.00 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC SC T 41 N R 9 E 1/4 S 35</p> <hr style="width: 50px; margin: 0 auto;"/> <p style="margin-left: 100px;">↘</p> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Witness cor. is located along the N. side of a chain link fence, 6 ft. high, with 3 strands of barbed wire, bears N. 70° E. and S. 70° W.</p>
47.30	<p>The easterly fence surrounding the high voltage transformer substation, chain link, 6 ft. high, bears S. 20° E. and N. 20° W.</p>
49.30	<p>Road, on the westerly side of the Navajo Generating Station, asphalt pavement, 15 ft. wide, bears S. 20° E. and N. 20° W.</p>
80.00	<p>True point for the stan. cor. of secs. 35 and 36, falls on a coal storage stockpile, where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for the witness cor. to the stan. cor. of secs. 35 and 36, bears N. 59°17' W., 4.00 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC SC T 41 N R 9 E S 35 S 36</p> <hr style="width: 100px; margin: 0 auto;"/> <p style="margin-left: 100px;">↘</p> <p>2005</p> </div>

Survey of a Portion of the Tenth Standard Parallel North
 (South Boundary),
 T. 41 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, rolling and broken. Soil, sand and sandy rocky clay. No timber; scattered brush and native grasses.</p> <hr/> <p>East, on the S. bdy. of sec. 36.</p> <p>Over rolling land.</p>
8.00	E. edge of the coal storage stockpile, bears S. 15° E. and N. 15° W.
9.95	Road, graded gravel, 40 ft. wide, bears S. 25° E. and N. 25° W.
10.65	Center of railroad tracks, bears S. 25° E. and N. 25° W.
11.25	Center of railroad tracks, bears S. 25° E. and N. 25° W.
15.09	Chain link fence, 6 ft. high, bears S. 25° E. and N. 25° W.
17.10	Road, graded gravel, 70 ft. wide, bears S. 35° E. and N. 35° W.
17.95	Chain link fence, 8 ft. high, bears S. 40° E. and N. 40° W.
22.71	Chain link fence, 8 ft. high, bears N. 15° E. and S. 15° W.
22.80	The easterly fence surrounding the Navajo Generating Station, woven wire with 2 strands of barbed wire, bears N. 15° E. and S. 15° W.
40.00	Point for the stan. 1/4 sec. cor. of sec. 36.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T 41 N R 9 E 1/4 S 36</p> <hr style="width: 10%; margin: auto;"/>
	<p style="text-align: center;">2005</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Survey of a Portion of the Tenth Standard Parallel North
 (South Boundary),
 T. 41 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>42.10 Northerly woven wire fence with 2 strands of barbed wire, parallels gravel road.</p> <p>45.20 Road, graded gravel, 45 ft. wide, bears N. 65° E. and S. 65° W.</p> <p>48.15 Southerly woven wire fence with 2 strands of barbed wire, parallels gravel road.</p> <p>80.00 Point for the stan. cor. of Tps. 41 N., Rs. 9 and 10 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">SC</td></tr> <tr><td colspan="2">T 41 N</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R 9 E</td><td style="padding: 0 5px;">R 10 E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 36</td><td style="padding: 0 5px;">S 31</td></tr> </table> </div> <p style="text-align: center; margin: 10px 0;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 2.47 chs. S. of the southerly woven wire fence with 2 strands of barbed wire, which parallels the gravel road, bears S. 75° E. and N. 75° W.</p> <p>Land, rolling. Soil, sand and sandy rocky clay. No timber; scattered brush and native grasses.</p> <hr style="width: 50%; margin: 20px auto;"/> <p style="text-align: center;">Dependent Resurvey of a Portion of the Subdivisional Lines, T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona</p> <hr style="width: 50%; margin: 20px auto;"/> <p style="text-align: center;">Restoring the survey executed by Robert C. Yundt and Boyd S. Owens, in 1959</p> <hr style="width: 50%; margin: 20px auto;"/> <p>From the cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with a brass tablet, 3 1/2 ins. diam., firmly set flush in sandstone bedrock, with a mound of stone, 3 ft. base, 1 ft. high, to the W., with top mkd. T40N R8E R9E S12 S7 S13 S18 1959.</p> <p>Add the marks 2005 to the brass cap.</p> <p>Cor. is located 13 lks. S. of a barbed wire fence, 5 strands, bears East and West.</p>	SC		T 41 N		R 9 E	R 10 E	S 36	S 31
SC									
T 41 N									
R 9 E	R 10 E								
S 36	S 31								

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
38.02	<p>East, bet. secs. 7 and 18.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole in a sandstone outcrop, with top mkd.</p> <p style="text-align: center;">T 40 N R 9 E S 7 1/4 ——— S 18</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in the drill hole, at the base of the brass tablet.</p>
60.60	<p>Honey Draw, a wash, 60 ft. wide, 4 ft. deep, drains N. 20° W.</p>
75.77	<p>High voltage transmission line, bears S. 35° E. and N. 35° W.</p>
78.02	<p>The cor. of secs. 7, 8, 17 and 18, monumented with an iron post, 2 1/2 ins. diam., firmly set, 3 ins. below the surface of the ground, with brass cap mkd. T40N R9E S7 S8 S18 S17 1959.</p> <p>Add the marks 2005 to the brass cap.</p> <p>Cor. is located 16 lks. N. of a barbed wire fence, 4 strands, bears East and West.</p> <hr/>
39.99	<p>East, bet. secs. 8 and 17.</p> <p>Over rolling and broken land.</p> <p>The 1/4 sec. cor. of secs. 8 and 17, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T40N R9E 1/4 S8 S17 1959.</p> <p>Add the marks 2005 to the brass cap.</p> <p>Cor. is located 2 lks. S. of a barbed wire fence, 5 strands, bears East and West.</p> <hr/>
	<p>East, beginning new measurement.</p> <p>Over rolling land.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.98	<p>The cor. of secs. 8, 9, 16 and 17, monumented with an iron post, 2 1/2 ins. diam., firmly set, 12 ins. below the surface of the ground, with brass cap mkd. T40N R9E S8 S9 S17 S16 1959.</p> <p>Add the marks 2005 to the brass cap.</p> <p>Cor. is located beneath a chain link fence, 4 ft. high, bears East and West.</p> <hr/>
	<p>East, bet. secs. 9 and 16.</p>
	<p>Over rolling land.</p>
19.16	<p>W. right-of-way fence of Navajo Route 20, barbed wire, 4 strands, parallels highway.</p>
20.70	<p>Navajo Route 20, asphalt pavement, 32 ft. wide, bears N. 5° E. and S. 5° W.</p>
22.22	<p>E. right-of-way fence of Navajo Route 20, barbed wire, 4 strands, parallels highway.</p>
39.98	<p>The 1/4 sec. cor. of secs. 9 and 16, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 11 ins. above ground, encircled with a collar of stone, with brass cap mkd. T40N R9E 1/4 S9 S16 1959.</p> <p>Add the marks 2005 to the brass cap and rebuild the mound of stone, 2 ft. base, to top.</p> <hr/>
	<p>N. 89°59' E., beginning new measurement.</p>
	<p>Over rolling land.</p>
13.60	<p>Wash, 40 ft. wide, 6 ft. deep, drains N. 10° E.</p>
39.97	<p>The cor. of secs. 9, 10, 15 and 16, monumented with a badly decayed wooden hub, of unknown origin, 12 ins. long, 3 1/2 ins. square, firmly set, 6 ins. below the surface of the ground, with the remains of a wooden sign post and sign pieces, alongside. This is accepted as the best available evidence of the position of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 5 ft. long, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS

T 40 N	R 9 E
S 9	S 10
S 16	S 15

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post, alongside the steel fence post.

Bury the wooden hub alongside the stainless steel post.

From this cor. point, a rebar, of unknown origin, 1 in. diam., firmly set, projecting 5 ins. above ground, bears N. 66°00' E., 3.5 lks. dist.

From this same cor. point, a rebar, 5/8 in. diam., firmly set flush with surface of the ground, encircled with a collar of stone, 2 ft. base, bears N. 72°11' E., 2.035 chs. dist., with yellow plastic cap mkd. AZ 17423, with 4 other rebars set nearby. Established by Earl G. Peacock, Arizona R.L.S. No. 17423 during environment studies performed in the area.

N. 0°01' E., bet. secs. 9 and 10.

Over rolling land.

39.96

Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 5 ft. long, with brass cap mkd.

T 40 N	R 9 E
1/4	
S 9	S 10

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

A rebar, 24 ins. long, 5/8 in. diam., was found lying loose nearby, with an aluminum cap mkd. LAPS A482D E326 RLS 7492, established by Robert Lloyd Carpenter, Arizona R.L.S. No. 7492 for the 1/4 sec. cor. of secs. 9 and 10, in 1972, during the survey of the right-of-way of a high voltage transmission line, according to an unrecorded plat entitled Cedar Mountain Division, dated July 6, 1972, obtained from the Los Angeles Department of Water and Power. Return the rebar to its' found location.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS							
71.20	<p>High voltage transmission line, bears N. 75° E. and S. 75° W. From this point on line, a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with an aluminum cap mkd. LAPS C426 RLS 7492, bears East, 1 lk. dist., established by Robert Lloyd Carpenter, Arizona R.L.S. No. 7492, in 1972, during the survey of the right-of-way of a high voltage transmission line, according to an unrecorded plat entitled Cedar Mountain Division, dated July 6, 1972, obtained from the Los Angeles Department of Water and Power.</p>						
79.92	<p>The cor. of secs. 3, 4, 9 and 10, monumented with a rebar, 5/8 in. diam., firmly set, cemented in a drill hole, projecting 3 ins. above sandstone bedrock, in a scattered mound of stone, with an aluminum cap mkd. LAPS A429D C429 RLS 7492, perpetuated by Robert Lloyd Carpenter, Arizona R.L.S. No. 7492, in 1972, during the survey of the right-of-way of a high voltage transmission line, according to an unrecorded plat entitled Cedar Mountain Division, dated July 6, 1972, obtained from the Los Angeles Department of Water and Power. This is accepted as a careful and faithful perpetuation of the position of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in sandstone bedrock, with brass cap mkd.</p> <table border="1" data-bbox="812 1165 1031 1270" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 40 N</td> <td>R 9 E</td> </tr> <tr> <td>S 4</td> <td>S 3</td> </tr> <tr> <td>S 9</td> <td>S 10</td> </tr> </table> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the rebar, 12 ins. long, alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 1 ft. high, to the W. of cor.</p>	T 40 N	R 9 E	S 4	S 3	S 9	S 10
T 40 N	R 9 E						
S 4	S 3						
S 9	S 10						
40.18	<p>N. 0°01' W., bet. secs. 3 and 4.</p> <p>Over rolling and broken land.</p> <p>The 1/4 sec. cor. of secs. 3 and 4, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, in a mound of stone, 1 1/2 ft. base, 6 ins. high, with brass cap mkd. T40N R9E 1/4 S4 S3 1959.</p>						

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Add the marks 2005 to the brass cap.
	N. 0°01' W., beginning new measurement.
	Over rolling land.
15.97	Intersect a brass tablet, 3 ins. diam., firmly set flush in a concrete collar, 6 ins. diam., projecting 5 ins. above sandstone bedrock, with top mkd. B.I.A. ROADS 1968, witnessed by an angle iron to the W., with side mkd. POT 149+59.00.
15.98	S. right-of-way fence of Arizona State Highway 98, barbed wire, 4 strands, parallels highway.
16.12	A brass tablet, 3 ins. diam., firmly set flush in a concrete collar, 6 ins. diam., projecting 5 ins. above sandstone bedrock, bears East, 45.5 lks. dist., with top mkd. B.I.A. ROADS 1968, witnessed by an angle iron to the W., with side mkd. POT 149+90.18.
17.56	Arizona State Highway 98, asphalt pavement, 38 ft. wide, bears N. 70° E. and S. 70° W.
19.01	A brass tablet, 3 ins. diam., firmly set flush in a concrete collar, 6 ins. diam., projecting 5 ins. above sandstone bedrock, bears West, 46 lks. dist., with top mkd. B.I.A. ROADS 1968, witnessed by an angle iron to the W., with side mkd. POT 149+90.18.
19.13	N. right-of-way fence of Arizona State Highway 98, barbed wire, 4 strands, parallels highway.
22.75	High voltage transmission line, bears S. 80° E. and N. 80° W.
23.74	Power line, bears S. 80° E. and N. 80° W.
39.89	The closing cor. of secs. 3 and 4, at intersection with the Tenth Standard Parallel North, on the N. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd. T41N R9E S33 S4 S3 T40N R9E CC 1959.
	Add the marks 2005 to the brass cap and set a steel fence post nearby.
	From this cor. point, the stan. cor. of secs. 33 and 34, bears East, 17.97 chs. dist., hereinbefore described.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this same cor. point, the stan. cor. of secs. 32 and 33, bears West, 62.06 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, in a scattered mound of stone, with brass cap mkd. PTS SC T41N R9E S32 S33 T40N R9E 1959.

Add the marks 2005 to the brass cap.

The control line was fully retraced, and the only remaining evidence of the stan. 1/4 sec. cor. of sec. 33, was an iron post, 30 ins. long, 2 1/2 ins. diam., was found lying loose at approximately midpoint between its' control corners, with brass cap mkd. SC 1/4 S33 1959. Return the iron post to its' found location.

Survey of a Portion of the Second Guide Meridian East
(West Boundary),
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

Point for the stan. cor. of Tps. 37 N., Rs. 8 and 9 E., established, geodetically, at the intersection of the Ninth Standard Parallel North, East, from the witness cor. to the stan. 1/4 sec. cor. of sec. 35, T. 37 N., R. 5 E., established in 1927 and on the Second Guide Meridian East, South, from the cor. of secs. 7, 12, 13 and 18, Tps. 40 N., Rs. 8 and 9 E., established in 1959.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

SC	
T 37 N	
R 8 E	R 9 E
S 36	S 31

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

From this cor. point, the witness cor. to the stan. 1/4 sec. cor. of sec. 35, T. 37 N., R. 5 E., bears West, 1566.30 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 30 ins. above ground, in a supporting mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd. SC 1/4 S35 WC 1927. Add the marks T37NR5E 2005 to the brass cap. Witness cor. is located on the W. rim of Marble Canyon, a sandstone ledge, bears N. 45° E. and S. 45° W.

**Survey of a Portion of the Second Guide Meridian East
(West Boundary),
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of Tps. 39 and 40 N., Rs. 8 and 9 E., established, geodetically, on the Second Guide Meridian East, North, 1440.00 chs. dist., from the stan. cor. of Tps. 37 N., Rs. 8 and 9 E., on the Ninth Standard Parallel North. The true point falls on a steep sandstone cliff; where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for a witness cor. to the cor. of Tps. 39 and 40 N., Rs. 8 and 9 E., bears N. 24°00' E., 50 lks. dist.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole in sandstone bedrock, with top mkd.</p> <div style="text-align: center;"> <p>WC T 40 N R 8 E R 9 E S 36 S 31 ----- S 1 S 6 T 39 N ↙ 2005</p> </div> <p>Deposit a magnet, in the drill hole, at the base of the brass tablet.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over rolling and broken land.</p>
12.75	Base of a sandstone rocky ridge, bears S. 30° E. and N. 30° W.
30.70	Water Holes Canyon, a wash, 60 ft. wide, 50 ft. deep, drains N. 50° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 40 N 1/4 R 8 E R 9 E S 36 S 31 2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of a Portion of the Second Guide Meridian East
(West Boundary),
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS									
44.75	Wash, 15 ft. wide, 5 ft. deep, drains N. 85° W.								
80.00	Point for the cor. of secs. 25, 30, 31 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 5 ft. long, with brass cap mkd. <table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td align="center" colspan="2">T 40 N</td></tr> <tr><td align="center">R 8 E</td><td align="center">R 9 E</td></tr> <tr><td align="center">S 25</td><td align="center">S 30</td></tr> <tr><td align="center">S 36</td><td align="center">S 31</td></tr> </table> <p align="center">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, alongside the steel fence post.</p> <p>Land, rolling and broken. Soil, sand and sandy clay with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 25 and 30.</p> <p>Over rolling land.</p>	T 40 N		R 8 E	R 9 E	S 25	S 30	S 36	S 31
T 40 N									
R 8 E	R 9 E								
S 25	S 30								
S 36	S 31								
38.20	Wash, 40 ft. wide, 6 ft. deep, drains N. 10° E.								
40.00	Point for the 1/4 sec. cor. of secs. 25 and 30. Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole in sandstone bedrock, with top mkd. <table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td align="center" colspan="2">T 40 N</td></tr> <tr><td align="center" colspan="2">1/4</td></tr> <tr><td align="center">R 8 E</td><td align="center">R 9 E</td></tr> <tr><td align="center">S 25</td><td align="center">S 30</td></tr> </table> <p align="center">2005</p> <p>Deposit a magnet, in the drill hole, at the base of the brass tablet.</p>	T 40 N		1/4		R 8 E	R 9 E	S 25	S 30
T 40 N									
1/4									
R 8 E	R 9 E								
S 25	S 30								
47.05	Wash, 20 ft. wide, 5 ft. deep, drains N. 30° W.								
80.00	Point for the cor. of secs. 19, 24, 25 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								

Survey of a Portion of the Second Guide Meridian East
(West Boundary),
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	<table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">T 40 N</td></tr> <tr><td style="text-align: center;">R 8 E</td><td style="text-align: center;">R 9 E</td></tr> <tr><td style="text-align: center;">S 24</td><td style="text-align: center;">S 19</td></tr> <tr style="border-top: 1px solid black;"><td style="text-align: center;">S 25</td><td style="text-align: center;">S 30</td></tr> </table> <p style="text-align: center; margin-top: 10px;">2005</p>	T 40 N		R 8 E	R 9 E	S 24	S 19	S 25	S 30
T 40 N									
R 8 E	R 9 E								
S 24	S 19								
S 25	S 30								
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>North, bet. secs. 19 and 24.</p> <p>Over rolling and broken land.</p>								
38.00	Trail road, bears N. 45° E. and S. 45° W.								
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>								
	<table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">T 40 N</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">R 8 E</td><td style="text-align: center;">R 9 E</td></tr> <tr><td style="text-align: center;">S 24</td><td style="text-align: center;">S 19</td></tr> </table> <p style="text-align: center; margin-top: 10px;">2005</p>	T 40 N		1/4		R 8 E	R 9 E	S 24	S 19
T 40 N									
1/4									
R 8 E	R 9 E								
S 24	S 19								
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>								
52.20	Trail road, bears S. 70° E. and N. 70° W.								
66.10	Base of a mesa, bears S. 65° E. and N. 65° W., thence along the rocky W. slope of the mesa.								
80.00	<p>Point for the cor. of secs. 13, 18, 19 and 24.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole in sandstone bedrock, with top mkd.</p>								

Survey of a Portion of the Second Guide Meridian East
 (West Boundary),
 T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<table border="1"> <tr><td colspan="2">T 40 N</td></tr> <tr><td>R 8 E</td><td>R 9 E</td></tr> <tr><td>S 13</td><td>S 18</td></tr> <tr><td>S 24</td><td>S 19</td></tr> </table> <p>2005</p> <p>Deposit a magnet, in the drill hole, at the base of the brass tablet.</p> <p>Cor. is located in a sandstone cove, 50 x 20 ft., 20 ft. high, below the W. rim of the mesa, bears North and South.</p> <p>Land, rolling and broken. Soil, sand and sandy rocky clay with sandstone outcrop. No timber; scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 13 and 18.</p> <p>Over rolling and broken land.</p>	T 40 N		R 8 E	R 9 E	S 13	S 18	S 24	S 19
T 40 N									
R 8 E	R 9 E								
S 13	S 18								
S 24	S 19								
20.95	W. rim of a mesa, top of a sandstone ledge, bears S. 65° E. and N. 65° W., thence over rolling land atop the mesa.								
30.73	High voltage transmission line, with a trail road, bears S. 10° E. and N. 10° W.								
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								
	<table border="1"> <tr><td colspan="2">T 40 N</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>R 8 E</td><td>R 9 E</td></tr> <tr><td>S 13</td><td>S 18</td></tr> </table> <p>2005</p>	T 40 N		1/4		R 8 E	R 9 E	S 13	S 18
T 40 N									
1/4									
R 8 E	R 9 E								
S 13	S 18								
79.68	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 7, 12, 13 and 18, hereinbefore described.</p>								

**Survey of a Portion of the Second Guide Meridian East
(West Boundary),
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona**


CHAINS

Land, rolling and broken.
Soil, sand and sandy rocky clay with sandstone outcrops.
No timber; scattered brush and native grasses.

Survey of the South Boundary,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

From the cor. of Tps. 39 and 40 N., Rs. 9 and 10 E., established, geodetically, 480.00 chs. East and 1440.00 chs. North of the stan. cor. of Tps. 37 N., Rs. 8 and 9 E., on the Ninth Standard Parallel North, hereinbefore described.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.



2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

West, bet. secs. 1 and 36.

Over rugged and broken land.

2.60 E. rim of a narrow rocky gorge, bears S. 15° E. and N. 15° W.

5.45 W. rim of the same gorge, bears N. 10° E. and S. 10° W.


33.70 N. rim of a mesa, top of a sandstone cliff, 100 ft. high, bears S. 10° E. and N. 10° W.

40.00 True point for the 1/4 sec. cor. of secs. 1 and 36, falls on the N. face of a steep sandstone cliff; where it is impracticable to establish a permanent monument.

From this true point, the point selected for the witness cor. to the 1/4 sec. cor. of secs. 1 and 36, bears S. 25°00' E., 53 lks. dist.

Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole in sandstone bedrock, with top mkd.

Survey of the South Boundary,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<div style="text-align: center;">  <p>WC T 40 N R 9 E S 36 1/4 ——— S 1 T 39 N</p> </div> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in the drill hole, at the base of the brass tablet.</p> <p>Point for the cor. of secs. 1, 2, 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 5 ft. long, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 40 N R 9 E S 35 S 36 ——— ——— S 2 S 1 T 39 N</p> </div> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, alongside the steel fence post.</p> <p>Land, rugged and broken. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p>
40.00	<hr/> <p>West, bet. secs. 2 and 35.</p> <p>Over rugged and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in sandstone bedrock, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 40 N R 9 E S 35 1/4 ——— S 2 T 39 N</p> </div> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the South Boundary,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS											
73.97	High voltage transmission line, bears N. 5° E. and S. 5° W.										
75.98	High voltage transmission line, bears N. 5° E. and S. 5° W.										
80.00	Point for the cor. of secs. 2, 3, 34 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table border="0"> <tr> <td>T 40 N</td> <td>R 9 E</td> </tr> <tr> <td>S 34</td> <td>S 35</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S 3</td> <td>S 2</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;">T 39 N</td> </tr> </table>	T 40 N	R 9 E	S 34	S 35			S 3	S 2	T 39 N	
T 40 N	R 9 E										
S 34	S 35										
S 3	S 2										
T 39 N											
	2005										
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.										
	Land, rugged and broken to rolling. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.										
	<hr/>										
	West, bet. secs. 3 and 34.										
	Over rolling land.										
14.50	Trail road, bears S. 10° E. and N. 10° W.										
40.00	Point for the 1/4 sec. cor. of secs. 3 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table border="0"> <tr> <td>T 40 N</td> <td>R 9 E</td> </tr> <tr> <td>S 34</td> <td></td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td>S 3</td> <td></td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;">T 39 N</td> </tr> </table>	T 40 N	R 9 E	S 34		1/4	_____	S 3		T 39 N	
T 40 N	R 9 E										
S 34											
1/4	_____										
S 3											
T 39 N											
	2005										
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.										
65.80	E. rim of a canyon, top of a sandstone ledge, bears South and N. 75° W., thence descend into the canyon.										
80.00	Point for the cor. of secs. 3, 4, 33 and 34.										

**Survey of the South Boundary,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS											
	<p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole in sandstone bedrock, with top mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T 40 N</td> <td style="padding: 0 5px;">R 9 E</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 33</td> <td style="padding: 0 5px;">S 34</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 4</td> <td style="padding: 0 5px;">S 3</td> </tr> <tr> <td colspan="2" style="padding: 0 5px; text-align: center;">T 39 N</td> </tr> </table> </div> <p style="text-align: center; margin: 10px 0;">2005</p> <p>Deposit a magnet, in the drill hole, at the base of the brass tablet.</p> <p>Cor. is located at the base of a sandstone cliff, 12 ft. high, bears North and South.</p> <p>Land, rolling to rugged and broken. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr style="width: 80%; margin: 20px auto;"/> <p>West, bet. secs. 4 and 33.</p> <p>Over rugged and broken land, across the canyon.</p>	T 40 N	R 9 E	S 33	S 34	S 4	S 3	T 39 N			
T 40 N	R 9 E										
S 33	S 34										
S 4	S 3										
T 39 N											
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 33.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole in sandstone bedrock, with top mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T 40 N</td> <td style="padding: 0 5px;">R 9 E</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S 33</td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="padding: 0 5px; border-top: 1px solid black;"></td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S 4</td> </tr> <tr> <td colspan="2" style="padding: 0 5px; text-align: center;">T 39 N</td> </tr> </table> </div> <p style="text-align: center; margin: 10px 0;">2005</p> <p>Deposit a magnet, in the drill hole, at the base of the brass tablet.</p> <p>Thence ascend out of the canyon.</p>	T 40 N	R 9 E		S 33	1/4			S 4	T 39 N	
T 40 N	R 9 E										
	S 33										
1/4											
	S 4										
T 39 N											
67.08	<p>E. right-of-way fence of Navajo Route 20, barbed wire, 4 strands, parallels highway.</p>										
68.62	<p>Navajo Route 20, asphalt pavement, 32 ft. wide, bears N. 5° E. and S. 5° W.</p>										
70.13	<p>W. right-of-way fence of Navajo Route 20, barbed wire, 4 strands, parallels highway.</p>										
80.00	<p>Point for the cor. of secs. 4, 5, 32 and 33.</p>										

Survey of the South Boundary,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 9 E S 32 S 33 ----- S 5 S 4 T 39 N</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rugged and broken to rolling. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/> <p>West, bet. secs. 5 and 32.</p> <p>Over rolling land.</p>
3.20	Trail road, bears North and South.
4.10	High voltage transmission line, bears North and South.
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T 40 N R 9 E S 32 1/4 ——— S 5 T 39 N</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in the drill hole, at the base of the brass tablet.</p>
68.20	High voltage transmission line, bears S. 30° E. and N. 30° W.
80.00	<p>Point for the cor. of secs. 5, 6, 31 and 32.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole in sandstone bedrock, with top mkd.</p>

Survey of the South Boundary,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>T 40 N R 9 E S 31 S 32 S 6 S 5 T 39 N</p> <p>2005</p> <p>Deposit a magnet, in the drill hole, at the base of the brass tablet.</p> <p>Cor. is located 30 lks. E. of the N. rim of a canyon, bears S. 10° E. and N. 10° W.</p> <p>Land, rolling. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/> <p>West, bet. secs. 6 and 31.</p> <p>Over rugged and broken land, descend into a canyon.</p> <p>33.25 Wash, 90 ft. wide, 6 ft. deep, drains West.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 5 ft. long, with brass cap mkd.</p> <p style="text-align: center;"> T 40 N R 9 E S 31 1/4 ——— S 6 T 39 N </p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, alongside the steel fence post.</p> <p>55.20 Water Holes Canyon, a wash, 100 ft. wide, 6 ft. deep, drains N. 35° W.</p> <p>77.55 E. edge of the base of a sandstone rocky ridge, bears N. 5° E. and S. 5° W.</p> <p>78.36 The true point for the cor. of Tps. 39 and 40 N., Rs. 8 and 9 E., on the W. bdy. of the Tp., hereinbefore described.</p>

**Survey of the South Boundary,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Land, rugged and broken. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/> <p style="text-align: center;">Survey of the East Boundary, T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of Tps. 39 and 40 N., Rs. 9 and 10 E., hereinbefore described.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over rugged and broken land.</p>								
7.40	N. rim of a mesa, top of a sandstone cliff, bears N. 80° E. and S. 80° W., descend abruptly into a canyon.								
37.50	N. edge of the base of a sandstone butte, bears N. 50° E. and S. 50° W.								
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td colspan="2">T 40 N</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>R 9 E</td><td>R 10 E</td></tr> <tr><td>S 36</td><td>S 31</td></tr> </table> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 40 N		1/4		R 9 E	R 10 E	S 36	S 31
T 40 N									
1/4									
R 9 E	R 10 E								
S 36	S 31								
57.95	S. rim of a canyon, bears N. 65° E. and S. 65° W.								
69.10	N. rim of the same canyon, bears N. 60° E. and S. 60° W.								
80.00	<p>Point for the cor. of secs. 25, 30, 31 and 36.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole in sandstone bedrock, with top mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td colspan="2">T 40 N</td></tr> <tr><td>R 9 E</td><td>R 10 E</td></tr> <tr><td>S 25</td><td>S 30</td></tr> <tr><td>S 36</td><td>S 31</td></tr> </table> <p>2005</p> </div>	T 40 N		R 9 E	R 10 E	S 25	S 30	S 36	S 31
T 40 N									
R 9 E	R 10 E								
S 25	S 30								
S 36	S 31								

**Survey of the East Boundary,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in the drill hole, at the base of the brass tablet.</p> <p>Land, rugged and broken. Soil, sand and sandy rocky clay, with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 25 and 30.</p> <p>Over rugged and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole in sandstone bedrock, with top mkd.</p> <div style="text-align: center;"> <p>T 40 N 1/4 R 9 E R 10 E S 25 S 30</p> </div> <p align="center">2005</p> <p>Deposit a magnet, in the drill hole, at the base of the brass tablet.</p> <p>Cor. is located in a wash, 20 ft. wide, 5 ft. deep, drains N. 25° E.</p>
80.00	<p>Point for the cor. of secs. 19, 24, 25 and 30.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole in sandstone bedrock, with top mkd.</p> <div style="text-align: center;"> <p>T 40 N R 9 E R 10 E S 24 S 19 <hr/>S 25 S 30</p> </div> <p align="center">2005</p> <p>Deposit a magnet, in the drill hole, at the base of the brass tablet.</p> <p>Land, rugged and broken. Soil, sand and sandy rocky clay, with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 19 and 24.</p>

Survey of the East Boundary,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rugged and broken land.
30.70	Wash, 80 ft. wide, 40 ft. deep, drains N. 55° E.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 40 N 1/4 R 9 E R 10 E S 24 S 19 2005 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
66.10	Antelope Creek, a wash, 125 ft. wide, 50 ft. deep, drains N. 50° W.
80.00	Point for the cor. of secs. 13, 18, 19 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 5 ft. long, with brass cap mkd. <div style="text-align: center;"> T 40 N R 9 E R 10 E S 13 S 18 S 24 S 19 2005 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post, alongside the steel fence post.
	Land, rugged and broken. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.

	North, bet. secs. 13 and 18.
	Over rolling and broken land.
21.85	S. edge of the base of a butte, bears N. 60° E. and S. 60° W.
31.15	N. face of the same butte, 50 ft. high, bears N. 40° E. and S. 40° W.

**Survey of the East Boundary,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 5 ft. long, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 40 N 1/4 R 9 E R 10 E S 13 S 18</p> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, alongside the steel fence post.</p>
80.00	<p>Point for the cor. of secs. 7, 12, 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 40 N R 9 E R 10 E S 12 S 7 S 13 S 18</p> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sand and rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 7 and 12.</p> <p>Over rolling and broken land.</p>
4.85	<p>S. rim of a mesa, top of a sandstone ledge, bears N. 75° E. and S. 75° W.</p>
7.25	<p>Trail road, bears N. 20° E. and S. 20° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the East Boundary,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 40 N 1/4 R 9 E R 10 E S 12 S 7 2005
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
41.15	N. rim of a mesa, top of a sandstone ledge, bears N. 55° E. and S. 55° W.
48.25	Trail road, bears S. 75° E. and N. 75° W.
77.90	Trail road, bears S. 70° E. and N. 70° W.
80.00	Point for the cor. of secs. 1, 6, 7 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 N R 9 E R 10 E S 1 S 6 S 12 S 7 2005
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located 77 lks. S. of a high voltage transmission line, bears S. 50° E. and N. 50° W.
	Land, rolling. Soil, sand and sandy rocky clay. No timber; scattered brush and native grasses.
	North, bet. secs. 1 and 6.
	Over rolling land.
1.60	Trail road, bears S. 50° E. and N. 50° W.
10.30	S. right-of-way fence of Arizona State Highway 98, barbed wire, 5 strands, parallels highway.
11.97	Arizona State Highway 98, asphalt pavement, 32 ft. wide, bears S. 65° E. and N. 65° W.

**Survey of the East Boundary,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS																									
13.63	N. right-of-way fence of Arizona State Highway 98, barbed wire, 5 strands, parallels highway.																								
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 40 N</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R 9 E</td><td style="padding: 0 5px;">R 10 E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 1</td><td style="padding: 0 5px;">S 6</td></tr> </table> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 40 N		1/4		R 9 E	R 10 E	S 1	S 6																
T 40 N																									
1/4																									
R 9 E	R 10 E																								
S 1	S 6																								
58.70	W. right-of-way fence of the Navajo Generating Station railroad, barbed wire, 5 strands, parallels railroad tracks.																								
58.89	Center of railroad tracks, bears S. 65° E. and N. 65° W.																								
60.24	Center of railroad tracks, bears S. 65° E. and N. 65° W.																								
61.22	E. right-of-way fence of the same railroad, barbed wire, 5 strands, parallels railroad tracks.																								
79.68	<p>Point for the closing cor. of Tps. 40 N., Rs. 9 and 10 E., at intersection with the Tenth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 5 ft. long, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 41 N</td><td colspan="2">R 9 E</td></tr> <tr><td colspan="4">S 36</td></tr> <tr><td colspan="2" style="border-right: 1px solid black; padding: 0 5px;">S 1</td><td colspan="2" style="padding: 0 5px;">S 6</td></tr> <tr><td colspan="2" style="border-right: 1px solid black; padding: 0 5px;">R 9 E</td><td colspan="2" style="padding: 0 5px;">R 10 E</td></tr> <tr><td colspan="4">T 40 N</td></tr> <tr><td colspan="4">CC</td></tr> </table> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, alongside the steel fence post.</p>	T 41 N		R 9 E		S 36				S 1		S 6		R 9 E		R 10 E		T 40 N				CC			
T 41 N		R 9 E																							
S 36																									
S 1		S 6																							
R 9 E		R 10 E																							
T 40 N																									
CC																									

Survey of the East Boundary,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point, the stan. cor. of Tps. 41 N., Rs. 9 and 10 E., bears East, 18.02 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 41 N., R. 9 E., bears West, 21.98 chs. dist., hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/> <p style="text-align: center;">Survey of a Portion of the Subdivisional Lines, T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over rugged and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground, to sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 40 N R 9 E 1/4 S 35 S 36</p> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
43.40	<p>S. rim of a mesa, top of a sandstone ledge, bears S. 70° E. and N. 70° W., thence over rolling land atop the mesa.</p>
80.00	<p>Point for the cor. of secs. 25, 26, 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 40 N R 9 E S 26 S 25 S 35 S 36</p> <p>2005</p> </div>

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rugged and broken to rolling. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p>
	<p>West, bet. secs. 25 and 36.</p>
	<p>Over rugged and broken land.</p>
36.30	<p>E. rim of a mesa, top of a sandstone ledge, bears N. 60° E. and S. 60° W., thence over rolling land atop the mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole in sandstone bedrock, with top mkd.</p>
	<p style="text-align: center;">T 40 N R 9 E S 25 1/4 ——— S 36</p> <p style="text-align: center;">2005</p>
	<p>Deposit a magnet, in the drill hole, at the base of the brass tablet.</p>
80.00	<p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, rugged and broken to rolling. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 40 N R 9 E 1/4 S 26 S 25</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
50.40	S. rim of a rocky ridge, bears N. 50° E. and S. 50° W.
64.80	N. rim of the same rocky ridge, bears N. 80° E. and S. 80° W.
80.00	Point for the cor. of secs. 23, 24, 25 and 26.
	<p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T 40 N R 9 E S 23 S 24 S 26 S 25</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in the drill hole, at the base of the brass tablet.</p> <p>Land, rolling and broken. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 24 and 25.</p> <p>Over rugged and broken land.</p>
37.20	Base of a sandstone cliff, 100 ft. high, bears N. 50° E. and S. 50° W., thence ascend over SE slope of a mesa.
40.00	True point for the 1/4 sec. cor. of secs. 24 and 25, falls on the SE face of a steep sandstone cliff; where it is impracticable to establish a permanent monument.
	<p>From this true point, the point selected for the witness cor. to the 1/4 sec. cor. of secs. 24 and 25, bears S. 45°00' E., 1.00 ch. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	WC T 40 N R 9 E S 24 ↙ 1/4 ——— S 25 2005
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
53.95	SE rim of a mesa, top of a sandstone ridge, bears N. 50° E. and S. 50° W.
65.60	W. rim of the same mesa, bears N. 60° E. and S. 60° W.
80.00	The cor. of secs. 23, 24, 25 and 26.
	Land, rugged and broken. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.
	N. 0°01' W., bet. secs. 23 and 24. Over rugged and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 5 ft. long, with brass cap mkd.
	T 40 N R 9 E 1/4 S 23 S 24 2005
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post, alongside the steel fence post.
80.00	Point for the cor. of secs. 13, 14, 23 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 N R 9 E S 14 S 13 S 23 S 24 2005

**Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rugged and broken to rolling. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 13 and 24.</p> <p>Over rolling and broken land.</p>
13.35	Antelope Creek, a wash, 100 ft. wide, 15 ft. deep, drains N. 10° E.
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 40 N R 9 E S 13 1/4 ——— S 24</p> <p align="center">2005</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
51.45	E. edge of the base of a rocky butte, bears N. 25° E. and S. 25° W.
52.45	W. edge of the base of the same butte, bears N. 30° E. and S. 30° W.
80.00	<p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, rolling and broken. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over rolling land.</p>
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14.

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 5 ft. long, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 9 E 1/4 S 14 S 13</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, alongside the steel fence post.</p>
80.00	<p>Point for the cor. of secs. 11, 12, 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 5 ft. long, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 9 E S 11 S 12 S 14 S 13</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, alongside the steel fence post.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p>
40.00	<p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 12 and 13.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 5 ft. long, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 9 E S 12 1/4 ——— S 13</p> <p style="text-align: center;">2005</p>

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post, alongside the steel fence post.
66.40	Antelope Creek, a wash, 200 ft. wide, 2 ft. deep, drains N. 10° W.
80.00	The cor. of secs. 11, 12, 13 and 14. Land, rolling and broken. Soil, sand and sandy clay. No timber; scattered brush and native grasses.
	N. 0°01' W., bet. secs. 11 and 12. Over rolling and broken land.
13.10	Antelope Creek, a wash, 200 ft. wide, 3 ft. deep, drains N. 55° W.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 40 N R 9 E 1/4 S 11 S 12 2005</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 1, 2, 11 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 5 ft. long, with brass cap mkd.
	<p style="text-align: center;">T 40 N R 9 E S 2 S 1 S 11 S 12 2005</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post, alongside the steel fence post.

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 1 and 12.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 9 E S 1 1/4 ——— S 12</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 1 and 2.</p> <p>Over rolling land.</p>
28.00	High voltage transmission line, bears S. 80° E. and N. 80° W.
29.37	S. right-of-way fence of Arizona Highway 98, barbed wire, 4 strands, parallels highway.
30.85	Arizona Highway 98, asphalt pavement, 32 ft. wide, bears S. 80° E. and N. 80° W.
32.42	N. right-of-way fence of Arizona Highway 98, barbed wire, 4 strands, parallels highway.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2.

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 5 ft. long, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 9 E 1/4 S 2 S 1 2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, alongside the steel fence post.</p> <p>71.57 S. edge of a large asphalt paved area for the main power plant of the Navajo Generating Station.</p> <p>79.68 True point for the closing cor. of secs. 1 and 2, at intersection with the Tenth Standard Parallel North, on the N. bdy. of the Tp., falls on top of the main power generator of the Navajo Generating Station, where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for the witness cor. to the closing cor. of secs. 1 and 2, bears S. 70°00' E., 4.00 chs. dist.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole in a concrete sidewalk, with top mkd.</p> <p style="text-align: center;">WC T 41 N R 9 E ← S 35 ----- S 2 S 1 T 40 N R 9 E CC 2005</p> <p>Deposit a magnet, in the drill hole, at the base of the brass tablet.</p> <p>From this true point, the true point for the stan. cor. of secs. 35 and 36, T. 41 N., R. 9 E., bears East, 18.01 chs. dist., hereinbefore described.</p> <p>From this same true point, the true point for the stan. 1/4 sec. cor. of sec. 35, T. 41 N., R. 9 E., bears West, 21.99 chs. dist., hereinbefore described.</p>
--------	--

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS

Land, rolling.
Soil, sand and sandy gravelly clay.
No timber; scattered brush and native grasses.

Point for the 1/4 sec. cor. of sec. 1 only, at midpoint on the N. bdy. of sec. 1, on the Tenth Standard Parallel North.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 41 N R 9 E

1/4 S 1

T 40 N R 9 E

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

From this cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 41 N., R. 9 E., bears East, 18.015 chs. dist., hereinbefore described.

From this same cor. point, the true point for the stan. cor. of secs. 35 and 36, T. 41 N., R. 9 E., bears West, 21.985 chs. dist., hereinbefore described.

From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.

N. 0°01' W., bet. secs. 34 and 35.

Over rolling land.

40.00

Point for the 1/4 sec. cor. of secs. 34 and 35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 40 N R 9 E

1/4

S 34 | S 35

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS									
80.00	<p>Point for the cor. of secs. 26, 27, 34 and 35.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole in sandstone bedrock, with top mkd.</p> <table border="1" data-bbox="812 514 1023 619"> <tr><td>T 40 N</td><td>R 9 E</td></tr> <tr><td>S 27</td><td>S 26</td></tr> <tr><td>S 34</td><td>S 35</td></tr> </table> <p>2005</p> <p>Deposit a magnet, in the drill hole, at the base of the brass tablet.</p> <p>Land, rolling and broken. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p>	T 40 N	R 9 E	S 27	S 26	S 34	S 35		
T 40 N	R 9 E								
S 27	S 26								
S 34	S 35								
37.10	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>West, bet. secs. 26 and 35.</p> <p>Over rugged and broken land.</p> <p>W. rim of a narrow canyon, top of a sandstone ledge, bears N. 50° E. and S. 50° W.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <table border="1" data-bbox="812 1396 1023 1512"> <tr><td>T 40 N</td><td>R 9 E</td></tr> <tr><td>S 26</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 35</td><td></td></tr> </table> <p>2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 40 N	R 9 E	S 26		1/4	—	S 35	
T 40 N	R 9 E								
S 26									
1/4	—								
S 35									
44.45	<p>Top of a rocky ridge, bears N. 50° E. and S. 50° W.</p>								
66.42	<p>High voltage transmission line, bears N. 5° E. and S. 5° W.</p>								
67.50	<p>Trail road, bears N. 5° E. and S. 5° W.</p>								
68.38	<p>High voltage transmission line, bears N. 5° E. and S. 5° W.</p>								

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
75.65	W. rim of a mesa, top of a sandstone ledge, bears S. 5° W. and N. 50° W., thence descend over rocky W. slope.
80.00	The cor. of secs. 26, 27, 34 and 35. Land, rugged and broken. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.
40.00	N. 0°01' W., bet. secs. 26 and 27. Over rugged and broken land. Point for the 1/4 sec. cor. of secs. 26 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<p>T 40 N R 9 E 1/4 S 27 S 26 2005</p>
74.90	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	S. rim of a rocky knoll, bears S. 75° E. and N. 75° W. Point for the cor. of secs. 22, 23, 26 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<p>T 40 N R 9 E S 22 S 23 S 27 S 26 2005</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rugged and broken. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.
	From the cor. of secs. 23, 24, 25 and 26.

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	West, bet. secs. 23 and 26.
	Over rugged and broken land.
39.25	E. rim of a rocky ridge, bears N. 20° E. and S. 20° W.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T 40 N R 9 E S 23 1/4 ——— S 26</p>
	2005
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
46.60	W. rim of the same rocky ridge, bears N. 65° E. and S. 65° W.
58.88	High voltage transmission line, bears N. 5° E. and S. 5° W.
60.85	High voltage transmission line, bears N. 5° E. and S. 5° W.
73.35	E. rim of the rocky knoll, bears N. 30° E. and S. 30° W.
80.00	The cor. of secs. 22, 23, 26 and 27.
	<p>Land, rugged and broken. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p>
	N. 0°01' W., bet. secs. 22 and 23.
	Over rugged and broken land.
16.00	N. rim of a mesa, top of a sandstone ledge, bears N. 60° E. and S. 60° W., descend abruptly into a valley.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 5 ft. long, with brass cap mkd.

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 40 N R 9 E 1/4 S 22 S 23</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, alongside the steel fence post.</p>
80.00	<p>Point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 5 ft. long, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 9 E S 15 S 14 S 22 S 23</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, alongside the steel fence post.</p> <p>Land, rugged and broken to rolling. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>West, bet. secs. 14 and 23.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 9 E S 14 1/4 ——— S 23</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
50.34	<p>High voltage transmission line, bears N. 5° E. and S. 5° W.</p>
52.34	<p>High voltage transmission line, bears N. 5° E. and S. 5° W.</p>

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, rolling. Soil, sand and sandy clay with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 14 and 15.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 5 ft. long, with brass cap mkd.</p>
	<p style="text-align: center;">T 40 N R 9 E 1/4 S 15 S 14 2005</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, alongside the steel fence post.</p>
80.00	<p>Point for the cor. of secs. 10, 11, 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 5 ft. long, with brass cap mkd.</p>
	<p style="text-align: center;">T 40 N R 9 E S 10 S 11 S 15 S 14 2005</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, alongside the steel fence post.</p>
	<p>Land, rolling and broken. Soil, sand and sandy rocky clay. No timber; scattered brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 11, 12, 13 and 14.</p>
	<p>West, bet. secs. 11 and 14.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 14.</p>

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole in sandstone outcrop, with top mkd.</p> <p style="text-align: center;">T 40 N R 9 E S 11 1/4 ——— S 14</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in the drill hole, at the base of the brass tablet.</p>
43.56	High voltage transmission line, bears N. 5° E. and S. 5° W.
45.53	High voltage transmission line, bears N. 5° E. and S. 5° W.
80.00	<p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, rolling. Soil, sand and sandy rocky clay. No timber; scattered brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 10 and 11.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 9 E 1/4 S 10 S 11</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 2, 3, 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 9 E S 3 S 2 S 10 S 11</p> <p style="text-align: center;">2005</p>

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy rocky clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>West, bet. secs. 2 and 11.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 9 E S 2 1/4 ——— S 11</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in a abandoned trail road.</p>
40.48	High voltage transmission line, bears North and South.
42.40	High voltage transmission line, bears North and South.
58.40	Antelope Creek, a wash, 200 ft. wide, 5 ft. deep, drains N. 50° W.
75.50	Trail road, bears S. 30° E. and N. 30° W.
80.00	<p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over rolling and broken land.</p>
7.35	Trail road, bears S. 30° E. and N. 30° W.

**Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
12.58	High voltage transmission line, bears N. 75° E. and S. 75° W.
26.10	Antelope Creek, a wash, 200 ft. wide, 5 ft. deep, drains N. 40° W.
35.80	Trail road, bears S. 40° E. and N. 40° W.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 3. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 5 ft. long, with brass cap mkd.
T 40 N R 9 E 1/4 S 3 S 2 2005	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post, alongside the steel fence post.
43.85	Road to Antelope Creek Visitor Center, graded gravel, bears S. 80° E. and N. 80° W.
45.40	High voltage transmission line, bears S. 80° E. and N. 80° W.
46.62	S. right-of-way fence of Arizona State Highway 98, barbed wire, 4 strands, parallels highway.
48.17	Arizona State Highway 98, asphalt pavement, 65 ft. wide, bears S. 80° E. and N. 80° W.
49.68	N. right-of-way fence of Arizona State Highway 98, barbed wire, 4 strands, parallels highway.
67.97	W. right-of-way fence of Navajo Route 22B, barbed wire, 5 strands, parallels highway.
71.25	Navajo Route 22B, asphalt pavement, 38 ft. wide, bears S. 25° E. and N. 25° W.
74.60	E. right-of-way fence of Navajo Route 22B, barbed wire, 5 strands, parallels highway.
76.30	Trail road, bears S. 60° E. and N. 60° W.
79.68	Point for the closing cor. of secs. 2 and 3, at intersection with the Tenth Standard Parallel North, on the N. bdy. of the Tp.

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 5 ft. long, with brass cap mkd.

T 41 N R 9 E
S 34

S 3 | S 2
T 40 N R 9 E
CC

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post, alongside the steel fence post

From this cor. point, the stan. cor. of secs. 34 and 35, T. 41 N., R. 9 E., bears East, 18.01 chs. dist., hereinbefore described.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 41 N., R. 9 E., bears West, 21.99 chs. dist., hereinbefore described.

Point for the 1/4 sec. cor. of sec. 2 only, at midpoint on the N. bdy. of sec. 2, on the Tenth Standard Parallel North.

Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole in sandstone bedrock, with top mkd.

T 41 N R 9 E

1/4 S 2
T 40 N R 9 E

2005

Deposit a magnet, in the drill hole, at the base of the brass tablet.

From this cor. point, the true point for stan. 1/4 sec. cor. of sec. 35, T. 41 N., R. 9 E., bears East, 18.01 chs. dist., hereinbefore described.

From this same cor. point, the stan. cor. of secs. 34 and 35, T. 41 N., R. 9 E., bears West, 21.99 chs. dist., hereinbefore described.

Point for the 1/4 sec. cor. of sec. 3 only, at 40.00 chs. in westing from the closing cor. of secs. 2 and 3, on the N. bdy. of sec. 3, on the Tenth Standard Parallel North.

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 5 ft. long, with brass cap mkd.</p>
	<p style="text-align: center;">T 41 N R 9 E ----- 1/4 S 3 T 40 N R 9 E</p>
	<p style="text-align: center;">2005</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, alongside the steel fence post.</p>
	<p>From this cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 41 N., R. 9 E., bears East, 18.01 chs. dist., hereinbefore described.</p>
	<p>From this same cor. point, the stan. cor. of secs. 33 and 34, T. 41 N., R. 9 E., bears West, 21.99 chs. dist., hereinbefore described.</p>
	<hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p>
	<p>N. 0°02' W., bet. secs. 33 and 34.</p>
	<p>Over rolling and broken land.</p>
<p>40.00</p>	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 40 N R 9 E 1/4 S 33 S 34</p>
	<p style="text-align: center;">2005</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
<p>45.00</p>	<p>N. rim of a mesa, top of a sandstone cliff, bears N. 75° E. and S. 75° W., thence descend abruptly into a canyon.</p>
<p>80.00</p>	<p>Point for the cor. of secs. 27, 28, 33 and 34.</p>
	<p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole in sandstone bedrock, with top mkd.</p>

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 40 N R 9 E S 28 S 27 ----- S 33 S 34</p>
	<p style="text-align: center;">2005</p>
	<p>Deposit a magnet, in the drill hole, at the base of the brass tablet.</p>
	<p>Land, rolling to rugged and broken. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p>
	<hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p>
	<p>West, bet. secs. 27 and 34.</p>
	<p>Over rugged and broken land.</p>
<p>40.00</p>	<p>Point for the 1/4 sec. cor. of secs. 27 and 34.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 40 N R 9 E S 27 1/4 ----- S 34</p>
	<p style="text-align: center;">2005</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
<p>80.00</p>	<p>The cor. of secs. 27, 28, 33 and 34.</p>
	<p>Land, rugged and broken. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p>
	<hr/> <p>N. 0°02' W., bet. secs. 27 and 28.</p>
	<p>Over rugged and broken land.</p>
<p>40.00</p>	<p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 5 ft. long, with brass cap mkd.</p>

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 40 N R 9 E 1/4 S 28 S 27</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, alongside the steel fence post.</p>
80.00	<p>Point for the cor. of secs. 21, 22, 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 5 ft. long, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 9 E S 21 S 22 ----- S 28 S 27</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, alongside the steel fence post.</p> <p>Land, rugged and broken. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>West, bet. secs. 22 and 27.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T 40 N R 9 E S 22 1/4 ——— S 27</p> <p style="text-align: center;">2005</p>
80.00	<p>Deposit a magnet, in the drill hole, at the base of the brass tablet.</p> <p>The cor. of secs. 21, 22, 27 and 28.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sand and sandy clay with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 21 and 22.</p> <p>Over rugged and broken land.</p>
31.50	<p>E. rim of a mesa, top of a sandstone ledge, bears S. 80° E. and S. 30° W. thence over rolling land atop the mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to sandstone bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p align="center">T 40 N R 9 E 1/4 S 21 S 22</p> <p align="center">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
41.90	<p>N. rim of a mesa, top of a sandstone ledge, bears N. 70° E. and S. 70° W., thence descend into a valley.</p>
80.00	<p>Point for the cor. of secs. 15, 16, 21 and 22.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole in sandstone bedrock, with top mkd.</p> <p align="center">T 40 N R 9 E S 16 S 15 S 21 S 22</p> <p align="center">2005</p> <p>Deposit a magnet, in the drill hole, at the base of the brass tablet.</p> <p>Land, rolling, rugged and broken. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>West, bet. secs. 15 and 22.</p>

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling land.
2.90	E. rim of a narrow rocky draw, bears N. 50° E. and S. 50° W.
4.10	Wash, 75 ft. wide, 5 ft. deep, drains N. 25° E.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T 40 N R 9 E S 15 1/4 ——— S 22</p>
	2005
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located at the base of a sandstone ledge, bears North and South.
40.95	Wash, 10 ft. wide, 20 ft. deep, drains N. 35° E.
80.00	The cor. of secs. 15, 16, 21 and 22.
	Land, rolling and broken. Soil, sand and sandy clay with sandstone outcrops. No timber; scattered brush and native grasses.
	N. 0°04' W., bet. secs. 15 and 16.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 5 ft. long, with brass cap mkd.
	<p style="text-align: center;">T 40 N R 9 E 1/4 S 16 S 15</p>
	2005
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post, alongside the steel fence post.

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.70	<p>The cor. of secs. 9, 10, 15 and 16, hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 89°47' W., bet. secs. 10 and 15.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 40 N R 9 E S 10 1/4 ——— S 15</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.05	<p>The cor. of secs. 9, 10, 15 and 16, hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. 89°44' W., bet. secs. 3 and 10.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 40 N R 9 E S 3 1/4 ——— S 10</p> <p style="text-align: center;">2005</p>

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Cor. is located 1.35 chs. S. of a trail road, bears N. 75° E. and S. 75° W.</p>
47.20	<p>High voltage transmission line, bears N. 75° E. and S. 75° W.</p>
79.99	<p>The cor. of secs. 3, 4, 9 and 10, hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 32 and 33.</p> <p>Over rolling land.</p>
29.80	<p>Trail road, bears N. 70° E. and S. 70° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole in sandstone bedrock, with top mkd.</p>
	<p style="text-align: center;">T 40 N R 9 E 1/4 S 32 S 33 2005</p> <p>Deposit a magnet, in the drill hole, at the base of the brass tablet.</p> <p>Cor. is located on a sandstone ledge, 10 ft. high, bears N. 10° E. and S. 10° W.</p>
80.00	<p>Point for the cor. of secs. 28, 29, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 9 E S 29 S 28 S 32 S 33 2005</p>

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Cor. is located 1.10 chs. E. of a wash, 10 ft. wide, 3 ft. deep, drains N. 30° E.</p>
	<p>Land, rolling to rugged and broken. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p>
	<hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p>
	<p>West, bet. secs. 28 and 33.</p>
	<p>Over rugged and broken land.</p>
<p>40.00</p>	<p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T 40 N R 9 E S 28 1/4 ——— S 33</p>
	<p style="text-align: center;">2005</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
<p>68.45</p>	<p>Navajo Route 20, asphalt pavement, 30 ft. wide, bears S. 15° E. and N. 15° W.</p>
<p>70.03</p>	<p>W. right-of-way fence of Navajo Route 20, barbed wire, 4 strands, parallels highway.</p>
<p>70.75</p>	<p>A brass tablet, 3 ins. diam., firmly set flush in a concrete collar, 6 ins. diam., projecting 6 ins. above ground, bears North, 2.50 chs. dist., with top mkd. BIA ROAD 1976, witnessed by an angle iron to the N., with side mkd. POC 757+00.</p>
<p>80.00</p>	<p>The cor. of secs. 28, 29, 32 and 33.</p>
	<p>Land, rugged and broken to rolling. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p>
	<hr/> <p>N. 0°03' W., bet. secs. 28 and 29.</p>

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rugged and broken land.
23.66	W. right-of-way fence of Navajo Route 20, barbed wire, 4 strands, parallels highway.
26.62	Navajo Route 20, asphalt pavement, 30 ft. wide, bears S. 35° E. and N. 35° W.
29.39	E. right-of-way fence of Navajo Route 20, barbed wire, 4 strands, parallels highway.
36.77	Barbed wire fence, 5 strands, bears N. 80° E. and S. 80° W.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 40 N R 9 E 1/4 S 29 S 28</p>
	2005
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 20, 21, 28 and 29. Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole in sandstone bedrock, with top mkd.
	<p style="text-align: center;">T 40 N R 9 E S 20 S 21 S 29 S 28</p>
	2005
	Deposit a magnet, in the drill hole, at the base of the brass tablet.
	Land, rugged and broken. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.
	From the cor. of secs. 21, 22, 27 and 28.
	West, bet. secs. 21 and 28.
	Over rugged and broken land.

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
22.10	E. rim of a mesa, top of a sandstone cliff, 50 ft. high, bears N. 30° E. and S. 30° W., thence over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 28. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 N R 9 E S 21 1/4 ——— S 28
	2005
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
42.70	Top of a rocky ridge, bears N. 50° E. and S. 50° W.
80.00	The cor. of secs. 20, 21, 28 and 29. Land, rugged and broken to rolling. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.
	<hr/> N. 0°03' W., bet. secs. 20 and 21. Over rolling land.
33.85	Wash, 12 ft. wide, 4 ft. deep, drains N. 50° W.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in sandstone bedrock, with brass cap mkd.
	T 40 N R 9 E 1/4 S 20 S 21
	2005
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
77.86	A brass tablet, 3 ins. diam., set flush in a concrete collar, 6 ins. diam., firmly set, projecting 3 ins. above ground, bears West, 2.10 chs. dist., with top mkd. BIA ROADS 1976, witnessed by an angle iron to the N., with side mkd. 865+43.57.
80.00	Point for the cor. of secs. 16, 17, 20 and 21.

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in sandstone bedrock, with brass cap mkd.</p>
	<p style="text-align: center;">T 40 N R 9 E S 17 S 16 ----- S 20 S 21</p>
	<p style="text-align: center;">2005</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Land, rolling. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p>
	<hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p>
	<p>West, bet. secs. 16 and 21.</p>
	<p>Over rugged and broken land.</p>
<p>33.30</p>	<p>E. rim of a mesa, top of a sandstone ledge, bears S. 10° E. and N. 10° W., thence over rolling land.</p>
<p>40.00</p>	<p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T 40 N R 9 E S 16 1/4 ——— S 21</p>
	<p style="text-align: center;">2005</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
<p>56.45</p>	<p>E. rim of a canyon, top of a sandstone ledge, bears S. 25° E. and N. 25° W.</p>
<p>80.00</p>	<p>The cor. of secs. 16, 17, 20 and 21.</p>

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rugged and broken to rolling. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 16 and 17.</p> <p>Over rolling land.</p>
8.20	Trail road, bears N. 85° E. and S. 85° W.
31.28	E. right-of-way fence of Navajo Route 20, barbed wire, 4 strands, parallels highway.
35.23	Navajo Route 20, asphalt pavement, 30 ft. wide, bears N. 20° E. and S. 20° W.
39.24	W. right-of-way fence of Navajo Route 20, barbed wire, 4 strands, parallels highway.
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. below the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 9 E 1/4 S 17 S 16</p> <p style="text-align: center;">2005</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in sandstone bedrock, for a reference monument, bears East, 240.0 ft. dist., with brass cap mkd. RM T40N R9E 1/4 S16 240.0 FT. TO COR. 2005 and an arrow pointing to the cor. Deposit a magnet in white plastic case beneath the stainless steel post. Set a steel fence post nearby.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 27°00' W., 80.0 ft. dist., with brass cap mkd. RM T40N R9E 1/4 S17 80.0 FT TO COR. 2005 and an arrow pointing to the cor. Deposit a magnet in white plastic case beneath the stainless steel post.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post at the 1/4 sec. cor.</p> <p>Cor. is located in the center of a graded road, 15 ft. wide, bears N. 20° E. and S. 20° W.</p>

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.38	Trail road, bears N. 20° E. and S. 20° W.
42.60	Trail road, bears S. 30° E. and N. 30° W.
79.68	<p>The cor. of secs. 8, 9, 16 and 17, hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over rugged and broken land.</p>
22.84	High voltage transmission line, bears S. 30° E. and N. 30° W.
23.20	S. rim of a mesa, top of a sandstone ledge, bears N. 55° E. and S. 55° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 40 N R 9 E</p> <p>1/4</p> <p>S 31 S 32</p> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 29, 30, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 40 N R 9 E</p> <p>S 30 S 29</p> <hr style="width: 50%; margin: 0 auto;"/> <p>S 31 S 32</p> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rugged and broken. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 28, 29, 32 and 33.</p>
	<p>West, bet. secs. 29 and 32.</p>
	<p>Over rugged and broken land.</p>
3.85	<p>High voltage transmission line, bears North and South.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p>
	<p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole in sandstone bedrock, with top mkd.</p>
	<p style="text-align: center;">T 40 N R 9 E S 29 1/4 ——— S 32</p>
	<p style="text-align: center;">2005</p>
	<p>Deposit a magnet, in the drill hole, at the base of the brass tablet.</p>
80.00	<p>The cor. of secs. 29, 30, 31 and 32.</p>
	<p>Land, rugged and broken. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/>
	<p>West, bet. secs. 30 and 31.</p>
	<p>Over rolling land.</p>
16.25	<p>Trail road, bears S. 30° E. and N. 30° W.</p>
20.36	<p>High voltage transmission line, S. 20° E. and N. 20° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in sandstone bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
78.27	<p style="text-align: center;">T 40 N R 9 E S 30 1/4 ——— S 31</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/>
40.00	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
80.00	<p style="text-align: center;">T 40 N R 9 E 1/4 S 30 S 29</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 1.60 chs. E. of the E. rim of a canyon, bears N. 15° E. and S. 15° W.</p> <p>Point for the cor. of secs. 19, 20, 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 5 ft. long, with brass cap mkd.</p>
	<p style="text-align: center;">T 40 N R 9 E S 19 S 20 S 30 S 29</p> <p style="text-align: center;">2005</p>

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, alongside the steel fence post.</p>
	<p>Land, rolling and broken. Soil, sand and sandy clay with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 20, 21, 28 and 29.</p>
	<p>West, bet. secs. 20 and 29.</p>
	<p>Over rolling and broken land.</p>
<p>3.70</p>	<p>High voltage transmission line, bears North and South.</p>
<p>14.89</p>	<p>E. right-of-way fence of Navajo Route 20, barbed wire, 4 strands, parallels highway.</p>
<p>16.43</p>	<p>Navajo Route 20, asphalt pavement, 30 ft. wide, bears N. 10° E. and S. 10° W.</p>
<p>17.96</p>	<p>W. right-of-way fence of Navajo Route 20, barbed wire, 4 strands, parallels highway.</p>
<p>40.00</p>	<p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T 40 N R 9 E S 20 1/4 _____ S 29</p>
	<p style="text-align: center;">2005</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
<p>57.00</p>	<p>E. rim of canyon of Honey Draw, top of a sandstone ledge, bears S. 5° E. and N. 5° W.</p>
<p>66.10</p>	<p>W. rim of canyon of Honey Draw, top of a sandstone ledge, bears S. 15° E. and N. 15° W.</p>
<p>80.00</p>	<p>The cor. of secs. 19, 20, 29 and 30.</p>

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sand and sandy clay with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/> <p>West, bet. secs. 19 and 30.</p> <p>Over rolling and broken land.</p>
7.10	E. rim of a canyon, top of a sandstone ledge, bears N. 35° E. and S. 35° W.
22.10	W. rim of the same canyon, top of a steep sandstone ridge, 50 ft. high, bears S. 5° E. and N. 5° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 5 ft. long, with brass cap mkd.</p>
	<p style="text-align: center;">T 40 N R 9 E S 19 1/4 ——— S 30</p> <p style="text-align: center;">2005</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, alongside the steel fence post.</p>
44.90	High voltage transmission line with a trail road, bears S. 20° E. and N. 20° W.
78.18	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling and broken. Soil, sand and sandy clay with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p> <p>Over rolling and broken land.</p>
12.80	W. rim of canyon of Honey Draw, top of a sandstone ledge, bears S. 50° E. and N. 50° W., thence descend into the canyon.
26.20	Honey Draw, a wash, 80 ft. wide, 50 ft. deep, drains N. 20° W.

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 9 E 1/4 S 19 S 20</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
47.20	<p>Honey Draw, a wash, 30 ft. wide, 50 ft. deep, drains N. 20° E.</p>
80.00	<p>Point for the cor. of secs. 17, 18, 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 6 ft. long, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 9 E S 18 S 17 S 19 S 20</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, alongside the steel fence post.</p>
	<p>Land, rolling and broken. Soil, sand and sandy clay with sandstone outcrops. No timber; scattered brush and native grasses.</p>
	<hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p>
	<p>West, bet. secs. 17 and 20.</p>
	<p>Over rolling land.</p>
2.23	<p>E. right-of-way fence of Navajo Route 20, barbed wire, 4 strands, parallels highway.</p>
3.73	<p>Navajo Route 20, asphalt pavement, 30 ft. wide, bears S. 5° E. and N. 5° W.</p>
5.09	<p>W. right-of-way fence of Navajo Route 20, barbed wire, 4 strands, parallels highway, enter Leche-e Chapter community.</p>
19.15	<p>Street, asphalt pavement, 20 ft. wide, bears N. 40° E. and S. 40° W., leave Leche-e Chapter community.</p>

**Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
26.46	High voltage transmission line, bears S. 35° E. and N. 35° W.
38.60	E. rim of canyon of Honey Draw, top of a steep sandstone cliff, bears N. 15° E. and S. 15° W., thence descend into the canyon.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 20. Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole in sandstone bedrock with top mkd. <div style="text-align: center;"> T 40 N R 9 E S 17 1/4 ——— S 20 2005 </div> Deposit a magnet, in the drill hole, at the base of the brass tablet. Cor. is located midway up the W. slope of a sandstone cliff.
70.95	Honey Draw, a wash, 30 ft. wide, 15 ft. deep, drains N. 10° E.
80.00	The cor. of secs. 17, 18, 19 and 20. Land, rolling and broken. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.
	<hr/> West, bet. secs. 18 and 19. Over rolling and broken land.
12.40	W. rim of canyon of Honey Draw, top of a sandstone ledge, bears S. 25° E. and N. 25° W.
15.90	E. rim of canyon of W. fork of Honey Draw, top of a sandstone ledge, bears N. 40° E. and S. 40° W.
29.75	Wash, 30 ft. wide, 20 ft. deep, drains N. 40° E.
40.00	Point for the 1/4 sec. cor. of secs. 18 and 19. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 6 ft. long, with brass cap mkd.

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>T 40 N R 9 E S 18 1/4 ——— S 19</p> <p>2005</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, alongside the steel fence post.</p>
69.24	High voltage transmission line, S. 10° E. and N. 10° W.
71.35	Trail road, bears S. 20° E. and N. 20° W.
76.10	W. rim of a mesa, top of a sandstone ledge, bears S. 30° W. and curves N.
78.09	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described.
	<p>Land, rolling and broken. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°03' W., bet. secs. 17 and 18.</p> <p>Over rolling and broken land.</p>
8.75	Honey Draw, a wash, 50 ft. wide, 8 ft. deep, drains N. 65° W.
39.30	Base of a steep sandstone cliff, 100 ft. high, bears S. 70° E. and N. 70° W., the E. rim of canyon of Honey Draw.
40.00	<p>True point for the 1/4 sec. cor. of secs. 17 and 18, falls on the S. face of a steep sandstone cliff; where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for the witness cor. to the 1/4 sec. cor. of secs. 17 and 18, bears S. 45°00' W., 1.00 ch. dist.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole in sandstone bedrock, with top mkd.</p>
	<p>WC </p> <p>T 40 N R 9 E 1/4 S 18 S 17</p> <p>2005</p>

Survey of a Portion of the Subdivisional Lines,
T. 40 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet, in the drill hole, at the base of the brass tablet.
	Witness cor. is located at the base of the steep sandstone cliff.
76.47	High voltage transmission line, bears S. 35° E. and N. 35° W.
79.36	Telephone line, bears East and West.
79.68	The cor. of secs. 7, 8, 17 and 18, hereinbefore described.
	Land, rolling and broken. Soil, sand and sandy rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.
	<hr/>

Tps. 40 and 41 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

The area surveyed is within the Navajo Indian Reservation and adjacent to the townsite of Page, Arizona, approximately three miles south southeast of Page, Arizona. The terrain is mostly rolling with mesas extending from the south with numerous narrow rock canyons. The drainage is northerly, with Antelope Creek being the main drainage, which drains through the eastern portion of the township and Honey Draw which drains through the western portion.

The elevation varies from 4100 to 5300 feet above sea level. The soil is mostly sand with sand dunes and sandy clay with exposed sandstone bedrock and outcrops. There is no timber, only scattered native brush and native grasses.

Principal access to the township is by Arizona State Highway 98 which enters in section 1 and exits the surveyed area in section 3 and Navajo Route 20 which enters the township in section 33 and exits the surveyed area in section 16, both roads go to Page, Arizona. There are livestock grazing in the vicinity of Antelope Creek and atop the mesa to the south. There is no mining activity in the township.

The mean magnetic declination of 12° E. was derived from the computer program GEOMAGIX utilizing the World Magnetic Model for Epoch 2005 for the dates of survey.

CERTIFICATE OF SURVEY

I, Leonard R. Sandoval, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of assignment instructions bearing date of the 20th day of January, 2005 and special instructions bearing date of the 26th day of April, 2005, I have surveyed a portion of the Tenth Standard Parallel North (south boundary), T. 41 N., R. 9 E. and dependently resurveyed a portion of the subdivisional lines and surveyed a portion of the Second Guide Meridian East (west boundary), the south and east boundaries and a portion of the subdivisional lines, T. 40 N., R. 9 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said assignment instructions, special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

6-5-06
(Date)

Leonard R. Sandoval
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the survey of a portion of the Tenth Standard Parallel North (south boundary), T. 41 N., R. 9 E. and the dependent resurvey of a portion of the subdivisional lines, the survey of a portion of the Second Guide Meridian East (west boundary), the south and east boundaries and a portion of the subdivisional lines, T. 40 N., R. 9 E., Gila and Salt River Meridian, in the State of Arizona, executed by Leonard R. Sandoval, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

6/07/06
(Date)

Stephen K. Hansen
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in Tps. 40 and 41 N., R. 9 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor of Arizona)~~

