

ORIGINAL

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE  
DEPENDENT RESURVEY OF THE SOUTH AND NORTH BOUNDARIES  
AND THE  
SUBDIVISIONAL LINES  
AND THE  
SUBDIVISION  
OF  
CERTAIN SECTIONS  
**TOWNSHIP 23 NORTH, RANGE 20 EAST,**  
OF THE GILA AND SALT RIVER MERIDIAN,  
IN THE STATE OF ARIZONA.

**EXECUTED BY**

**Geoffrey A. Graham, Cadastral Surveyor**

Under Special Instructions dated September 22, 2004, approved September 22, 2004, which provided for the surveys included under Group No. 945, and assignment instructions dated September 22, 2004.

**Survey commenced November 17, 2004**

**Survey completed February 23, 2005**

INDEX DIAGRAM

TOWNSHIP 23 NORTH RANGE 20 EAST  
 GILA AND SALT RIVER MERIDIAN, ARIZONA

13	12	12	11	10	9
6	57 5	47 4	39 3	32 2	23 1
57	55	46	39	31	22
7	55 8	45 9	38 10	30 11	21 12
55	54	45	38	29	20
18	53 17	44 16	37 15	28 14	19 13
53	52	43	36	28	18
19	51 20	43 21	36 22	26 23	17 24
51	50	42	35	26	17
30	49 29	41 28	34 27	25 26	16 25
49	48	41	33	24	15
31	47 32	40 33	33 34	23 35	14 36
8	7	6	5	4	4

Subdivision of Section 2 ..... Page 58  
 Subdivision of Section 6 ..... Pages 58-59  
 Subdivision of Section 12 ..... Pages 59-60  
 Subdivision of Section 14 ..... Pages 60-61  
 Subdivision of Section 18 ..... Pages 61-62  
 Subdivision of Section 20 ..... Page 62  
 Subdivision of Section 22 ..... Pages 62-63  
 Subdivision of Section 24 ..... Pages 63-64  
 Subdivision of Section 26 ..... Pages 64-65  
 Subdivision of Section 28 ..... Page 65  
 Subdivision of Section 30 ..... Pages 65-66

**T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS

The following field notes describe the dependent resurvey of the south and north boundaries, the subdivisional lines, and the subdivision of certain sections, Township 23 North, Range 20 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

A. P. Johnson surveyed the Fifth Guide Meridian East (east boundary), the south, west, and north boundaries, and the subdivisional lines in 1883. Dale C. Wilson, Cadastral Surveyor, resurveyed the east boundary in 2004, under Group No. 935. The west boundary was resurveyed by Geoffrey A. Graham, in 2004, under Group No. 927.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated September 22, 2004, for Group No. 945, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 and 5800 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) FERN FERNO MESA CORS ARP, FST1 FLAGSTAFF 1 CORS ARP, AZGB GILA COUNTY CORS ARP. The NAD 83 (CORS96)(EPOCH:2002), geographic position of the southeast township corner, is as follows:

Latitude: 35°20'37.77" N.                      Longitude: 110°09'39.28" W.

The mean magnetic declination is 11 1/4° E.

---

**Dependent Resurvey of the South Boundary,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Restoring the survey executed by A.P. Johnson, in 1883</p> <hr/>
	<p>Beginning at the cor. of Tps. 22 and 23 N., Rs. 20 and 21 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush in a supporting mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. T23N R20E R21E S36 S31 S1 S6 T22N 2004.</p>
	<p>N. 87°24' W., bet. secs. 1 and 36.</p>
	<p>Descending W. aspect of Malpais Mesa</p>
41.25	<p>Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 20 E S 36 1/4 ——— S 1 T 22 N</p> <p>2005</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p> <p>Cor. is located on right bank of Gleshbito Wash, 100 ft. wide, drains S. 20° W., from N. 20° E.</p> <p>Ascend over rolling terrain, broken by steep washes.</p>
82.50	<p>The cor. of secs. 1, 2, 35 and 36, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. T23N R20E S35 S36 S2 S1 T22N 2004. An accessory mound of stone, 3 ft. base, 1 1/2 ft. high, is N. of the cor.</p> <hr/> <p>S. 87°11' W., bet. secs. 2 and 35.</p> <p>Ascend over rolling terrain, broken by steep washes.</p>
38.01	<p>The 1/4 sec. cor. of secs. 2 and 35, monumented with a basalt stone, 12 x 10 x 2 1/2 ins., laying loose on the ground, mkd. 1/4 on a face.</p>

**Dependent Resurvey of the South Boundary,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
16 ins. in the ground to bedrock, in a supporting mound of  
stone, 4 ft. base, to top, with brass cap mkd.

T 23 N R 20 E  
S 35  
1/4 ———  
S 2  
T 22 N

2005

Deposit a magnet in a white plastic case at the base of the  
stainless steel post.

Incorporate the mkd. stone into mound of stone, alongside of the  
stainless steel post.

Cor. is located on top of a small spur ridge, curving S. 30° W.,  
from N. 30° W.

---

S. 89°45' W., beginning new measurement.

Ascend over increasingly steep terrain to top of large mesa.

39.615 Point for the cor. of secs. 2, 3, 34 and 35, at proportionate  
dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
23 ins. in the ground, with brass cap mkd.

T 23 N R 20 E  
S 34 | S 35  
S 3 | S 2  
T 22 N

2004

Deposit a magnet in a white plastic case at the base of the  
stainless steel post.

---

S. 89°45' W., bet. secs. 3 and 34.

Cross nearly level terrain.

39.615 Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate  
dist.; there is no remaining evidence of the original cor.

**Dependent Resurvey of the South Boundary,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.23	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E S 34 1/4 ——— S 3 T 22 N</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
39.615	<p>Point for the cor. of secs. 3, 4, 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E S 33   S 34 S 4   S 3 T 22 N</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>S. 89°45' W., bet. secs. 4 and 33.</p> <p>Over nearly level terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E S 33 1/4 ——— S 4 T 22 N</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Dependent Resurvey of the South Boundary,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS									
79.23	<p>The cor. of secs. 4, 5, 32 and 33, monumented with a basalt stone, 16 x 12 x 8 ins., firmly set, projecting 6 ins. above the ground, plainly mkd. with 4 grooves on E. face, and 2 grooves on the W.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T 23 N</td> <td style="padding: 0 5px;">R 20 E</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 32</td> <td style="padding: 0 5px;">S 33</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 5</td> <td style="padding: 0 5px;">S 4</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">T 22 N</td> </tr> </table> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base, and the mkd. stone alongside of the stainless steel post.</p> <p>Raise an accessory mound of stone, 3 ft. base, 1 ft. high, N. of the cor.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>N. 86°01' W., bet. secs. 5 and 32.</p> <p>Over increasingly rolling terrain.</p>	T 23 N	R 20 E	S 32	S 33	S 5	S 4	T 22 N	
T 23 N	R 20 E								
S 32	S 33								
S 5	S 4								
T 22 N									
37.14	<p>The 1/4 sec. cor. of secs. 5 and 32, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set flush in a supporting mound of stone, 5 ft. base, 28 ins. high, with brass cap mkd. T23N R20E 1/4 S32 S5 T22N 2004.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 89°55' W., beginning new measurement.</p> <p>Ascending E. aspect of mesa, thence over nearly level terrain.</p>								
40.165	<p>Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T 23 N</td> <td style="padding: 0 5px;">R 20 E</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 31</td> <td style="padding: 0 5px;">S 32</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 6</td> <td style="padding: 0 5px;">S 5</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">T 22 N</td> </tr> </table> <p>2004</p> </div>	T 23 N	R 20 E	S 31	S 32	S 6	S 5	T 22 N	
T 23 N	R 20 E								
S 31	S 32								
S 6	S 5								
T 22 N									

Dependent Resurvey of the South Boundary,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.165	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 89°55' W., bet. secs. 6 and 31.</p> <p>Over nearly level terrain, and descend W. aspect of mesa.</p> <p>True point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate dist.; there is no remaining evidence of the original cor. Point falls in a deep, narrow wash, 30 ft. wide, 8 ft. deep, draining N. 40° W., from S. 30° E., where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 6 and 31, bears N. 73°56' W., 92 lks. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC</p> <p>T 23 N R 20 E</p> <p>S 31</p> <p>1/4 ———→</p> <p>S 6</p> <p>T 22 N</p> <p>2004</p> </div>
77.32	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone, 2 ft. base, 1 ft. high N. of the cor.</p> <p>The cor. of Tps. 22 and 23 N., Rs. 19 and 20 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. T23N R19E R20E S36 S31 S1 S6 T22N 2004.</p> <hr/>

**Dependent Resurvey of the North Boundary,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS

Restoring the survey executed by  
A. P. Johnson, in 1883

---

From the cor. of Tps. 23 and 24 N., Rs. 20 and 21 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set flush in a supporting mound of stone, 5 ft. base, 1 1/2 ft. high, with brass cap mkd. T24N R20E R21E S36 S31 S1 S6 T23N 2004.

N. 89°35' W., bet. secs. 1 and 36.

Ascending over broken terrain.

40.07 Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. into solid sand stone, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 24 N R 20 E  
S 36  
1/4 ———  
S 1  
T 23 N

2004

Deposit a magnet in a white plastic case at the base of the stainless steel post.

The mound of stone contains a 19 x 10 x 6 ins., blood red, granite stone.

80.14 The cor. of secs. 1, 2, 35 and 36, monumented with an iron reinforcement rod, 5/8 in. diam., firmly set, projecting 5 ins. above the ground, in a mound of stone, 3 ft. diam., 1 ft. high, no mkd. stone found.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T 24 N R 20 E  
S 35 | S 36  
S 2 | S 1  
T 23 N

2004

**Dependent Resurvey of the North Boundary,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.52	<p>Deposit a magnet in a white plastic case at the base, and the 16 ins. long reinforcement rod inside of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p> <hr/> <p>N. 89°40' W., bet. secs. 2 and 35.</p> <p>Descending over broken terrain.</p> <p>The 1/4 sec. cor. of secs. 2 and 35, monumented with an embedded mound of stone, 3 ft. base, 1 ft. high. A basalt stone of record dimensions, 15 x 11 x 6 ins., with no marks, was found in the mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 20 E</p> <p>S 35</p> <p>1/4 ———</p> <p>S 2</p> <p>T 23 N</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Incorporate record dimensioned stone into mound of stone.</p> <p>Set a steel fence post southerly of the cor.</p> <hr/> <p>S. 89°40' W., beginning new measurement.</p> <p>Ascending over broken terrain.</p>
39.61	<p>The cor. of secs. 2, 3, 34 and 35, monumented with a basalt stone, 11 x 5 x 3 ins., mkd. with 4 grooves on a face, laying loose in an embedded mound of stone, 3 ft. diam., 1/2 ft. high. An iron reinforcement rod, 1/2 in. diam., firmly set, projecting 2 ins. above the ground was found in the mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p>

**Dependent Resurvey of the North Boundary,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 24 N	R 20 E
S 34	S 35
S 3	S 2
T 23 N	

2004

Deposit a magnet in a white plastic case at the base, the mkd. stone alongside, and the 16 ins. long reinforcement rod inside of the stainless steel post.

Set a steel fence post northerly of the cor.

---

S. 89°46' W., bet. secs. 3 and 34.

Over broken terrain.

39.94

The 1/4 sec. cor. of secs. 3 and 34, monumented with a small embedded mound of stone, 2 ft. diam., 1/2 ft. high, no mkd. stone found.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.

T 24 N	R 20 E
S 34	
1/4	—
S 3	
T 23 N	

2004

Deposit a magnet in a white plastic case at the base of the stainless steel post.

---

N. 89°54' W., beginning new measurement.

Descending over broken terrain.

39.67

Point accepted for the cor. of secs. 3, 4, 33 and 34, occupied with an iron reinforcement rod, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, in a collar of stone, 2 ft. diam. This is accepted as the best available evidence of the position of the original cor.

At the corner point

**Dependent Resurvey of the North Boundary,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 20 E S 33   S 34 ----- S 4   S 3 T 23 N</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base, and the 18 ins. long reinforcement rod inside of the stainless steel post.</p> <hr/> <p>N. 87°55' W., bet. secs. 4 and 33.</p> <p>Generally descending over nearly level terrain.</p>
37.60	<p>Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 20 E S 33 1/4 ——— S 4 T 23 N</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
75.20	<p>The cor. of secs. 4, 5, 32 and 33, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. T24N R20E S32 S33 S5 S4 T23N 2004.</p> <p>From this cor., the 1/4 sec. cor. of secs. 32 and 33, T. 24 N., R. 20 E., monumented with a juniper post, 5 x 4 ins. squared, firmly set, projecting 8 ins. above the ground, mkd. 1/4 on W. face, bears N. 0°15' E., 39.89 chs. dist.</p> <hr/> <p>S. 89°52' W., bet. secs. 5 and 32.</p> <p>Over nearly level terrain.</p>

**Dependent Resurvey of the North Boundary,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.76	<p>Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 20 E S 32 1/4 ——— S 5 T 23 N</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.52	<p>Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 20 E S 31   S 32 S 6   S 5 T 23 N</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 9 lks. W. of a fence bearing N. and S.</p> <hr/> <p>S. 89°52' W., bet. secs. 6 and 31.</p> <p>Over nearly level terrain.</p>
39.76	<p>Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the North Boundary,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

<p>CHAINS</p>	<p style="text-align: center;">T 24 N R 20 E S 31 1/4 ——— S 6 T 23 N</p> <p style="text-align: center;">.2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p> <p>77.03 The cor. of Tps. 23 and 24 N., Rs. 19 and 20 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T24N R19E R20E S36 S31 S1 S6 T23N 2004.</p> <hr/> <p style="text-align: center;"><b>Dependent Resurvey of the Subdivisional Lines, T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p style="text-align: center;">Restoring the survey executed by A. P. Johnson, in 1883</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 3°14' E., bet. secs. 35 and 36.</p> <p>Ascending over broken terrain.</p> <p>37.14 The 1/4 sec. cor. of secs. 35 and 36, monumented with a mound of stone, 3 ft. base, 1 1/2 ft. high, no mkd. stone found.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E 1/4 S 35   S 36</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
---------------	---

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Raise an accessory mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°08' W., beginning new measurement.</p> <p>Continuing ascent over broken terrain.</p>								
38.70	<p>The cor. of secs. 25, 26, 35 and 36, monumented with an embedded mound of stone, 4 ft. diam., no mkd. stone found.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="padding: 0 10px;">T 23 N</td> <td style="padding: 0 10px;">R 20 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 26</td> <td style="padding: 0 5px;">S 25</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 35</td> <td style="padding: 0 5px;">S 36</td> </tr> </table> </div> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T23N R20E R21E S25 S30 S36 S31 2004.</p> <p>S. 89°21' W., bet. secs. 25 and 36.</p> <p>Ascending over broken terrain.</p>	T 23 N	R 20 E	S 26	S 25	S 35	S 36		
T 23 N	R 20 E								
S 26	S 25								
S 35	S 36								
40.35	<p>Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="padding: 0 10px;">T 23 N</td> <td style="padding: 0 10px;">R 20 E</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S 25</td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="border-bottom: 1px solid black; width: 20px;"></td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S 36</td> </tr> </table> </div> <p style="text-align: center;">2005</p>	T 23 N	R 20 E		S 25	1/4			S 36
T 23 N	R 20 E								
	S 25								
1/4									
	S 36								

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p>
80.70	<p>The cor. of secs. 25, 26, 35 and 36.</p> <hr/> <p>N. 0°31' E., bet. secs. 25 and 26.</p> <p>Ascending increasingly steep terrain to top of mesa.</p>
38.70	<p>The 1/4 sec. cor. of secs. 25 and 26, monumented with an embedded mound of stone, 3 ft. diam., with a basalt stone, 9 x 9 x 4 ins., mkd. 1/4 on a face laying loose in the mound.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 20 E 1/4 S 26   S 25</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base, and the mkd. stone alongside of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p> <hr/> <p>N. 0°03' E., beginning new measurement.</p> <p>Over mesa top and descend over steep broken terrain.</p>
40.07	<p>The cor. of secs. 23, 24, 25 and 26, monumented with an embedded mound of stone, 3 ft. diam., no mkd. stone found, no sandstone found.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 20 E S 23   S 24 S 26   S 25</p> <p>2004</p> </div>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone, 2 1/2 ft. base, 1 ft. high, N. of the cor.</p> <p>Cor. is located 7 lks. S. of a stubbed fence, bearing E. and W.</p> <p>From this cor. point, an iron reinforcement rod, 5/8 in. diam., firmly set, projecting 1 in. above the ground, bears N. 85°29' W., 3.92 chs. dist. A second iron reinforcement rod, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, bears N. 60°41' W., 0.85 chs. dist. These are for an unidentified home site.</p> <hr/> <p>From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. T23N R20E R21E S24 S19 S25 S30 2004.</p> <p>S. 88°40' W., bet. secs. 24 and 25.</p> <p>Passing through the Gleshbito Wash plain.</p>
40.28	<p>Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 20 E</p> <p>S 24</p> <p>1/4 ———</p> <p>S 25</p> <p>2004</p> </div>
80.57	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p> <p>The cor. of secs. 23, 24, 25 and 26.</p> <hr/> <p>N. 0°06' W., bet. secs. 23 and 24.</p> <p>Over broken terrain.</p>
40.24	<p>The 1/4 sec. cor. of secs. 23 and 24, monumented with a basalt stone, 21 x 11 x 6 ins., firmly set, projecting 10 ins. above the ground, mkd. faintly 1/4 on W. face.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E 1/4 S 23   S 24</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base, and the mkd. stone alongside of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°10' W., beginning new measurement.</p> <p>Over broken terrain.</p>
7.19	Center line of Navajo Route 15, asphalt surfaced, 30 ft. wide, bears N. 88° E. and S. 88° W.
40.18	<p>Point accepted for the cor. of secs. 13, 14, 23 and 24, occupied with an iron reinforcement rod, 5/8 in. diam., firmly set, projecting 8 ins. above the ground, in a collar of stone. This rod was set in the course of an unrecorded 2001 survey under the direction of Gerald K. Wood, Professional Land Surveyor, RLS No. 22290. This position is accepted as the best available evidence of the position of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, under pinned with a steel fence post, 5 ft. long, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E S 14   S 13 S 23   S 24</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base, and the 29 ins. long reinforcement rod inside of the stainless steel post.</p> <p>Set steel fence post northerly of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/>

Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T23N R20E R21E S13 S18 S24 S19 2004.</p> <p>S. 89°10' W., bet. secs. 13 and 24.</p> <p>Over rolling terrain.</p>
40.49	<p>Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E S 13 1/4 ——— S 24</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p>
80.98	<p>The cor. of secs. 13, 14, 23 and 24.</p> <hr/> <p>N. 0°06' W., bet. secs. 13 and 14.</p> <p>Ascending over rolling terrain.</p>
40.23	<p>Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E 1/4 S 14   S 13</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located at corner of fences, under construction, extending N. and W.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS							
80.46	<p>The cor. of secs. 11, 12, 13 and 14, monumented with an iron reinforcement rod, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, in a scattered mound of stone, with an aluminum cap, 2 1/2 ins. diam., mkd. T23N S11 S12 S14 S13 R20E 22290. Find broken basalt stone, 12 x 8 x 2 ins., mkd with 3 grooves on a face, laying loose in the scattered mound.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 23 N</td> <td>R 20 E</td> </tr> <tr> <td>S 11</td> <td>S 12</td> </tr> <tr> <td>S 14</td> <td>S 13</td> </tr> </table> <p>2005</p> </div> <p>Deposit a magnet in a white plastic case at the base, the 24 ins. long reinforcement rod with aluminum cap inside, and the mkd. stone alongside of the stainless steel post.</p> <p>Cor. is located at corner of fences, under construction, extending S. and W.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. T23N R20E R21E S12 S7 S13 S18 2004. An accessory mound of stone, 3 ft. base, 1 ft. high, is W. of the cor.</p> <p>S. 89°01' W., bet. secs. 12 and 13.</p> <p>Ascending over broken terrain.</p>	T 23 N	R 20 E	S 11	S 12	S 14	S 13
T 23 N	R 20 E						
S 11	S 12						
S 14	S 13						
40.22	<p>Point accepted for the 1/4 sec. cor. of secs. 12 and 13, monumented with a mound of stone, 3 ft. base, 2 ft. high, no mkd. stone or remains of wood post found. This is accepted as the best available evidence of the position of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>						

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 20 E S 12 1/4 ——— S 13  2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.  Set a steel fence post northerly of the cor.  <hr style="width: 20%; margin: auto;"/> S. 89°58' W., beginning new measurement.  Descending over broken terrain.
40.99	The cor. of secs. 11, 12, 13 and 14.  <hr style="width: 80%; margin: auto;"/> N. 0°33' E., bet. secs. 11 and 12.  Crossing W. aspect of broken mesa.
40.68	Point accepted for the 1/4 sec. cor. of secs. 11 and 12, monumented with an embedded mound of stone, 2 1/2 ft. base, 1 ft. high, no mkd. stone or remains of wood post found. This is accepted as the best available evidence of the position of the original cor.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">             T 23 N R 20 E                        1/4              S 11   S 12               2005           </div> Deposit a magnet in a white plastic case at the base of the stainless steel post.  Raise an accessory mound of stone, 2 1/2 ft. base, 1 ft. high, W. of the cor.  Set a steel fence post northerly of the cor.  <hr style="width: 20%; margin: auto;"/> N. 0°39' E., beginning new measurement.  Ascending over rolling terrain.

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS									
40.40	<p>The point accepted for the cor. of secs. 1, 2, 11 and 12, monumented with an embedded mound of stone, 3 ft. diam., no mkd. stone or remains of wood post found. This is accepted as the best available evidence of the position of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T 23 N R 20 E</td> </tr> <tr> <td style="text-align: center;">S 2</td> <td style="text-align: center;">S 1</td> </tr> <tr> <td style="text-align: center;">S 11</td> <td style="text-align: center;">S 12</td> </tr> </table> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p> <hr/> <p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T23N R20E R21E S1 S6 S12 S7 2004. An accessory mound of stone, 2 ft. base, 1 ft. high, is W. of the cor.</p> <p>S. 89°57' W., bet. secs. 1 and 12.</p> <p>Ascending over broken terrain.</p>	T 23 N R 20 E		S 2	S 1	S 11	S 12		
T 23 N R 20 E									
S 2	S 1								
S 11	S 12								
40.15	<p>The 1/4 sec. cor. of secs. 1 and 12, monumented with a basalt stone, 12 x 9 x 9 ins., firmly set, projecting 3 ins. above the ground, mkd. 1/4 on N. face. An embedded accessory mound of stone, 2 ft. diam., is N. of the stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T 23 N R 20 E</td> </tr> <tr> <td></td> <td style="text-align: center;">S 1</td> </tr> <tr> <td style="text-align: center;">1/4</td> <td style="text-align: center;">—</td> </tr> <tr> <td></td> <td style="text-align: center;">S 12</td> </tr> </table> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base, and the mkd. stone alongside of the stainless steel post.</p>	T 23 N R 20 E			S 1	1/4	—		S 12
T 23 N R 20 E									
	S 1								
1/4	—								
	S 12								

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>This cor. is located bet. 2 scrub junipers, which provided protection for the monument for the last 122 years, I did not alter the condition of the accessory mound as one of the trees is growing out of it.</p> <hr/> <p>N. 89°49' W., beginning new measurement.</p> <p>Descending over rolling terrain.</p>
40.14	<p>The cor. of secs. 1, 2, 11 and 12.</p> <hr/> <p>N. 0°09' E., bet. secs. 1 and 2.</p> <p>Ascending over rolling terrain.</p>
40.08	<p>Point accepted for the 1/4 sec. cor. of secs. 1 and 2, monumented with a mound of stone, 2 ft. base, 1 ft. high, no mkd. stone or remains of wood post found. This is accepted as the best available evidence of the position of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E 1/4 S 2   S 1  2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p> <hr/> <p>N. 0°05' E., beginning new measurement.</p> <p>Enter broken terrain and ascend.</p>
40.96	<p>The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°09' W., bet. secs. 34 and 35.</p> <p>Over nearly level terrain.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
38.36	<p>Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E 1/4 S 34   S 35  .2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
76.72	<p>The cor. of secs. 26, 27, 34 and 35, monumented with a mound of stone, 3 ft. base, 1 ft. high, with a basalt stone of record dimensions, 18 x 14 x 6 ins., laying loose in the mound, no marks found.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E S 27   S 26 S 34   S 35  2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 88°32' W., bet. secs. 26 and 35.</p> <p>Ascending steep E. aspect of mesa to top.</p>
39.63	<p>The 1/4 sec. cor. of secs. 26 and 35, monumented with a juniper post, 6 x 6 ins. squared, firmly set, projecting 19 ins. above the ground, no marks found.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 23 N R 20 E S 26 1/4 ——— S 35</p> <p style="text-align: center;">2004</p>
	<p>Deposit a magnet in a white plastic case at the base, and the 38 ins. long post alongside of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p> <p style="text-align: center;">—————</p> <p>S. 89°52' W., beginning new measurement.</p> <p>Over nearly level terrain.</p>
40.16	<p>The cor. of secs. 26, 27, 34 and 35.</p> <p style="text-align: center;">—————</p>
	<p>N. 2°16' E., bet. secs. 26 and 27.</p> <p>Enter broken terrain.</p>
40.61	<p>The 1/4 sec. cor. of secs. 26 and 27, monumented with an embedded mound of stone, 3 ft. diam., no mkd. stone found.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T 23 N R 20 E 1/4 S 27   S 26</p> <p style="text-align: center;">2004</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post southerly of the cor.</p> <p style="text-align: center;">—————</p> <p>N. 0°33' E., beginning new measurement.</p> <p>Descending over broken terrain.</p>
38.90	<p>The cor. of secs. 22, 23, 26 and 27, monumented with a mound of stone, 3 ft. base, 1 ft. high, no mkd. stone found.</p> <p>At the corner point</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>								
	<table border="1"> <tr> <td>T 23 N</td> <td>R 20 E</td> </tr> <tr> <td>S 22</td> <td>S 23</td> </tr> <tr> <td>S 27</td> <td>S 26</td> </tr> </table>	T 23 N	R 20 E	S 22	S 23	S 27	S 26		
T 23 N	R 20 E								
S 22	S 23								
S 27	S 26								
	2005								
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p> <hr/>								
	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89°43' W., bet. secs. 23 and 26.</p> <p>Ascending over rolling terrain.</p>								
39.08	<p>Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>								
	<table border="1"> <tr> <td>T 23 N</td> <td>R 20 E</td> </tr> <tr> <td></td> <td>S 23</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 26</td> </tr> </table>	T 23 N	R 20 E		S 23	1/4	—		S 26
T 23 N	R 20 E								
	S 23								
1/4	—								
	S 26								
	2005								
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p>								
78.17	<p>The cor. of secs. 22, 23, 26 and 27.</p> <hr/>								
	<p>N. 1°37' E., bet. secs. 22 and 23.</p> <p>Descending through broken terrain.</p>								
40.39	<p>Point accepted for the 1/4 sec. cor. of secs. 22 and 23, monumented with an embedded mound of stone, 3 ft. diam., no mkd. stone or remains of wood post found. This is accepted as the best available evidence of the position of the original cor.</p>								

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E 1/4 S 22   S 23</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone, 2 ft. base, 1 ft. high, W. of the cor.</p> <p>Set a steel fence post northerly of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 5°05' W., beginning new measurement.</p> <p>Over nearly level terrain.</p>
3.18	Center line of Navajo Route 15, asphalt surfaced, 30 ft. wide, bears N. 87° E. and S. 87° W.
40.44	<p>Point accepted for the cor. of secs. 14, 15, 22 and 23, monumented with an iron reinforcement rod, 5/8 in. diam., firmly set, projecting 5 ins. above the ground, in a collar of stone. This rod was set in the course of an unrecorded 2001 survey under the direction of Gerald K. Wood, Professional Land Surveyor, RLS No. 22290. This position is accepted as the best available evidence of the position of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E S 15   S 14 S 22   S 23</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base, and the 24 ins. long reinforcement rod inside of the stainless steel post.</p> <p>Raise an accessory mound of stone, 2 ft. base, 1 ft. high, N. of the cor.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.21	<p>Set a steel fence post northerly of the cor.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89°53' W., bet. secs. 14 and 23.</p> <p>Generally ascending through rolling terrain.</p> <p>Point accepted for the 1/4 sec. cor. of secs. 14 and 23, at proportionate dist.; occupied with an iron reinforcement rod, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, in a collar of stone. This rod was set in the course of an unrecorded 2001 survey under the direction of Gerald K. Wood, Professional Land Surveyor, RLS No. 22290. This point is accepted as a careful and faithful reestablishment of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 20 E</p> <p>S 14</p> <p>1/4 ———</p> <p>S 23</p> <p>2005</p> </div> <p>Deposit a magnet in a white plastic case at the base, and the 30 ins. long reinforcement rod inside of the stainless steel post.</p> <p>Raise an accessory mound of stone, 2 ft. base, 1 ft. high, N. of the cor.</p> <p>Set a steel fence post northerly of the cor.</p> <hr/> <p>S. 89°53' W., beginning new measurement.</p>
40.22	<p>The cor. of secs. 14, 15, 22 and 23.</p> <hr/> <p>N. 0°03' E., bet. secs. 14 and 15.</p> <p>Over broken terrain.</p>
40.26	<p>Point accepted for the 1/4 sec. cor. of secs. 14 and 15, at proportionate dist.; occupied with an iron reinforcement rod, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, in a collar of stone. This rod was set in the course of an</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>unrecorded 2001 survey under the direction of Gerald K. Wood, Professional Land Surveyor, RLS No. 22290. This point is accepted as a careful and faithful reestablishment of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E 1/4 S 15   S 14</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base, and the 29 ins. long reinforcement rod inside of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°03' E., beginning new measurement.</p>
40.26	<p>Point accepted for the cor. of secs. 10, 11, 14 and 15, monumented with an iron reinforcement rod, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, in a collar of stone. This rod was set in the course of an unrecorded 2001 survey under the direction of Gerald K. Wood, Professional Land Surveyor, RLS No. 22290. This position is accepted as the best available evidence of the position of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E S 10   S 11 S 15   S 14</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base, and the 18 ins. long reinforcement rod inside of the stainless steel post.</p> <p>Set steel fence post northerly of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of secs. 11, 12, 13 and 14.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>S. 89°56' W., bet. secs. 11 and 14.</p> <p>Descending through rolling terrain.</p>
40.04	<p>Point accepted for the 1/4 sec. cor. of secs. 11 and 14, monumented with an iron reinforcement rod, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, an accessory mound of stone, 2 ft. base 1 ft. high, is N. of the rod. This rod was set in the course of an unrecorded 2001 survey under the direction of Gerald K. Wood, Professional Land Surveyor, RLS No. 22290. This position is accepted as the best available evidence of the position of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 20 E</p> <p>S 11</p> <p>1/4 ———</p> <p>S 14</p> <p>2005</p> </div> <p>Deposit a magnet in a white plastic case at the base, and the 24 ins. long reinforcement rod inside of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>S. 89°55' W., beginning new measurement.</p> <p>Over nearly level terrain.</p>
40.14	<p>The cor. of secs. 10, 11, 14 and 15.</p> <hr style="width: 80%; margin: 10px auto;"/>
	<p>N. 4°45' E., bet. secs. 10 and 11.</p> <p>Through gently rolling terrain.</p>
41.36	<p>Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 20 E</p> <p>1/4</p> <p>S 10   S 11</p> <p>2005</p> </div>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS							
82.72	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 2, 3, 10 and 11, monumented with a basalt stone, 16 x 13 x 6 ins., mkd. 5 grooves on a face and 2 grooves on an adjacent face, laying loose, with an embedded accessory mound of stone, 3 ft. diam., W. of the stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 23 N</td> <td>R 20 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 3</td> <td>S 2</td> </tr> <tr> <td style="border-right: 1px solid black;">S 10</td> <td>S 11</td> </tr> </table> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Incorporate the mkd. stone and the accessory mound into supporting mound of stone.</p> <p>Set a steel fence post northerly of the cor.</p> <p>Cor. is located 1.50 chs. E. of a steep talus slope, bears N. and S.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 87°53' W., bet. secs. 2 and 11.</p> <p>Ascending over steep mesa slopes.</p>	T 23 N	R 20 E	S 3	S 2	S 10	S 11
T 23 N	R 20 E						
S 3	S 2						
S 10	S 11						
36.34	<p>The 1/4 sec. cor. of secs. 2 and 11, monumented with a basalt stone, 9 x 7 x 7 ins., firmly set, projecting 6 ins. above the ground, mkd. 1/4 on N. face, with an embedded accessory mound of stone, 2 ft. diam., N. of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground, in a supporting mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>						

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 20 E S 2 1/4 ——— S 11  2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Incorporate the mkd. stone and the accessory mound into the supporting mound of stone.
	—————
	S. 89°53' W., beginning new measurement.
	Descending over steep mesa slopes.
37.85	The cor. of secs. 2, 3, 10 and 11.
	—————
	N. 3°41' W., bet. secs. 2 and 3.
	Ascending along the Gleshbito Wash floor.
39.30	The 1/4 sec. cor. of secs. 2 and 3, monumented with a basalt stone, 13 x 7 x 7 ins., mkd. 1/4 on a face, laying loose on the ground, with an embedded mound of stone, 2 ft. diam., N. of the stone.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 20 E 1/4 S 3   S 2  2004
	Deposit a magnet in a white plastic case at the base, and the mkd. stone alongside of the stainless steel post.
	Raise an accessory mound of stone, 2 ft. base, 1 ft. high, W. of the cor.
	Set a steel fence post northerly of the cor.
	—————
	N. 3°12' W., beginning new measurement.
	Ascending over broken terrain.

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.62	<p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°32' E., bet. secs. 33 and 34.</p> <p>Over nearly level terrain.</p>
38.90	<p>Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E 1/4 S 33   S 34</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
77.80	<p>Point for the cor. of secs. 27, 28, 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E S 28   S 27 S 33   S 34</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°28' W., bet. secs. 27 and 34.</p> <p>Over nearly level terrain.</p>
39.15	<p>Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E S 27 1/4 ——— S 34</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
78.31	<p>The cor. of secs. 27, 28, 33 and 34.</p> <hr/> <p>N. 2°03' E., bet. secs. 27 and 28.</p> <p>Over nearly level terrain.</p>
38.93	<p>Point accepted for the 1/4 sec. cor. of secs. 27 and 28, monumented with an embedded mound of stone, 1 1/2 ft. diam., no mkd. stone or remains of wood stake found. This is accepted as the best available evidence of the position of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E 1/4 S 28   S 27</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p> <hr/> <p>N. 0°05' W., beginning new measurement.</p> <p>Over nearly level terrain.</p>
40.18	<p>Point accepted for the cor. of secs. 21, 22, 27 and 28, monumented with a mound of stone, 2 ft. diam., 1/2 ft. high, no mkd. stone or remains of wood post found. This is accepted as the best available evidence of the position of the original cor.</p> <p>At the corner point</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
25 ins. in the ground, in a collar of stone, with brass cap mkd.

T 23 N	R 20 E
S 21	S 22
S 28	S 27

2005

Deposit a magnet in a white plastic case at the base of the  
stainless steel post.

Set a steel fence post northerly of the cor.

---

From the cor. of secs. 22, 23, 26 and 27.

N. 89°47' W., bet. secs. 22 and 27.

Ascending over broken terrain.

38.75

Point accepted for the 1/4 sec. cor. of secs. 22 and 27,  
monumented with an embedded mound of stone, 3 ft. diam., no mkd.  
stone or remains of wood post found. This is accepted as the  
best available evidence of the position of the original cor.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
25 ins. in the ground, with brass cap mkd.

T 23 N	R 20 E
	S 22
1/4	—
	S 27

2005

Deposit a magnet in a white plastic case at the base of the  
stainless steel post.

Raise an accessory mound of stone, 2 1/2 ft. base, 1 ft. high,  
N. of the cor.

Set a steel fence post northerly of the cor.

---

N. 89°45' W., beginning new measurement.

Over nearly level terrain.

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.19	<p>The cor. of secs. 21, 22, 27 and 28.</p> <hr/> <p>N. 0°07' W., bet. secs. 21 and 22.</p> <p>Over nearly level terrain.</p>
38.78	<p>Center line of Navajo Route 15, asphalt surfaced, 30 ft. wide, bears N. 87° E. and S. 87° W.</p>
40.39	<p>Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 20 E 1/4 S 21   S 22</p> <p>2005</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 10 lks. N. of the northerly right-of-way fence for Navajo Route 15, bears E. and W.</p>
80.78	<p>Point for the cor. of secs. 15, 16, 21 and 22, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 20 E S 16   S 15 S 21   S 22</p> <p>2005</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 89°40' W., bet. secs. 15 and 22.</p> <p>Ascending over broken terrain.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
38.32	<p>Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">           T 23 N   R 20 E                      S 15            1/4 ———                      S 22         </div> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p>
76.64	<p>The cor. of secs. 15, 16, 21 and 22.</p> <hr/> <p>N. 0°42' W., bet. secs. 15 and 16.</p> <p>Over nearly level terrain.</p>
40.39	<p>Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">           T 23 N   R 20 E                      1/4            S 16   S 15         </div> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.78	<p>Point for the cor. of secs. 9, 10, 15 and 16, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">           T 23 N   R 20 E            S 9   S 10            ———            S 16   S 15         </div> <p style="text-align: center;">2005</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 88°09' W., bet. secs. 10 and 15.</p> <p>Ascending over rolling terrain.</p>
38.63	<p>Point accepted for the 1/4 sec. cor. of secs. 10 and 15, monumented with an iron reinforcement rod, 1/2 in. diam., firmly set flush with the ground, with an unmarked yellow plastic cap. No record was recovered for the origin of this rod. This is accepted as the best available evidence of the position of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 20 E</p> <p>S 10</p> <p>1/4 ———</p> <p>S 15</p> <p>2005</p> </div> <p>Deposit a magnet in a white plastic case at the base, and the 18 ins. long reinforcement rod inside of the stainless steel post.</p> <p>Raise an accessory mound of stone, 2 ft. base, 1 1/2 ft. high, N. of the cor.</p> <hr/> <p>S. 89°12' W., beginning new measurement.</p> <p>Leaving rolling and enter nearly level terrain.</p>
39.09	<p>The cor. of secs. 9, 10, 15 and 16.</p> <hr/> <p>N. 3°33' E., bet. secs. 9 and 10.</p> <p>Over nearly level terrain.</p>
40.46	<p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 20 E 1/4 S 9   S 10  2005  Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.92	Point for the cor. of secs. 3, 4, 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  T 23 N R 20 E S 4   S 3 S 9   S 10  2005  Deposit a magnet in a white plastic case at the base of the stainless steel post.
	<hr/> From the cor. of secs. 2, 3, 10 and 11.  S. 89°18' W., bet. secs. 3 and 10.  Ascending over broken terrain.
39.77	Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate dist.; there is no remaining evidence of the original cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.  T 23 N R 20 E S 3 1/4 ——— S 10  2005  Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.53	The cor. of secs. 3, 4, 9 and 10.  <hr/> N. 3°29' W., bet. secs. 3 and 4.

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling terrain.
40.46	Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate dist.; there is no remaining evidence of the original cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.  <div style="text-align: center;">T 23 N R 20 E 1/4 S 4   S 3  2005</div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.79	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described.  <hr/> From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described.  N. 1°16' E., bet. secs. 32 and 33.  Over nearly level terrain.
39.95	Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.  <div style="text-align: center;">T 23 N R 20 E 1/4 S 32   S 33  2005</div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.90	Point for the cor. of secs. 28, 29, 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table style="margin: auto;"> <tr> <td>T 23 N</td> <td>R 20 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 29</td> <td>S 28</td> </tr> <tr> <td style="border-right: 1px solid black;">S 32</td> <td>S 33</td> </tr> </table> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 88°44' W., bet. secs. 28 and 33.</p> <p>Over nearly level terrain.</p>	T 23 N	R 20 E	S 29	S 28	S 32	S 33		
T 23 N	R 20 E								
S 29	S 28								
S 32	S 33								
39.10	<p>Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 23 N</td> <td>R 20 E</td> </tr> <tr> <td></td> <td style="text-align: center;">S 28</td> </tr> <tr> <td style="text-align: center;">1/4</td> <td style="text-align: center;">—</td> </tr> <tr> <td></td> <td style="text-align: center;">S 33</td> </tr> </table> </p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p>	T 23 N	R 20 E		S 28	1/4	—		S 33
T 23 N	R 20 E								
	S 28								
1/4	—								
	S 33								
78.20	<p>The cor. of secs. 28, 29, 32 and 33.</p> <hr/> <p>N. 0°10' W., bet. secs. 28 and 29.</p> <p>Over nearly level terrain.</p>								
39.94	<p>Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>								

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 20 E 1/4 S 29   S 28  2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.  Set a steel fence post northerly of the cor.
79.88	Point for the cor. of secs. 20, 21, 28 and 29, at proportionate dist.; there is no remaining evidence of the original cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 23 N R 20 E S 20   S 21 S 29   S 28  2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.  Set a steel fence post northerly of the cor.
	<hr/> From the cor. of secs. 21, 22, 27 and 28.  N. 88°11' W., bet. secs. 21 and 28.  Over nearly level terrain.
39.88	Point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate dist.; there is no remaining evidence of the original cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 23 N R 20 E S 21 1/4 ——— S 28  2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.  Set a steel fence post northerly of the cor.

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.77	<p>The cor. of secs. 20, 21, 28 and 29.</p> <hr/> <p>N. 2°09' E., bet. secs. 20 and 21.</p> <p>Ascending over gently rising terrain to top of mesa.</p>
31.93	<p>Center line of Navajo Route 15, asphalt surfaced, 30 ft. wide, bears N. 87° E. and S. 87° W.</p>
39.97	<p>Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E 1/4 S 20   S 21  2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p>
79.94	<p>The cor. of secs. 16, 17, 20 and 21, monumented with an embedded mound of stone, 3 1/2 ft. diam., no mkd. stone found.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E S 17   S 16 S 20   S 21  2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 85°44' W., bet. secs. 16 and 21.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over nearly level terrain.
38.34	<p>Point accepted for the 1/4 sec. cor. of secs. 16 and 21, monumented with an embedded mound of stone, 3 ft. diam., no mkd. stone or remains of wood post found. This is accepted as the best available evidence of the position of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 20 E</p> <p>S 16</p> <p>1/4 ———</p> <p>S 21</p> <p>2005</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 88°10' W., beginning new measurement.</p> <p>Ascending over gently rising terrain to top of mesa.</p>
38.33	<p>The cor. of secs. 16, 17, 20 and 21.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>N. 2°03' W., bet. secs. 16 and 17.</p> <p>Descending over rolling terrain.</p>
40.63	<p>Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 20 E</p> <p>1/4</p> <p>S 17   S 16</p> <p>2005</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone, 2 ft. base, 1 ft. high, W. of the cor.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS									
81.26	<p>Point for the cor. of secs. 8, 9, 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 23 N</td> <td>R 20 E</td> </tr> <tr> <td>S 8</td> <td>S 9</td> </tr> <tr> <td>S 17</td> <td>S 16</td> </tr> </table> <p>2005</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>	T 23 N	R 20 E	S 8	S 9	S 17	S 16		
T 23 N	R 20 E								
S 8	S 9								
S 17	S 16								
	<p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 88°30' W., bet. secs. 9 and 16.</p> <p>Over nearly level terrain.</p>								
39.23	<p>Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 23 N</td> <td>R 20 E</td> </tr> <tr> <td></td> <td>S 9</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td></td> <td>S 16</td> </tr> </table> <p>2005</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 23 N	R 20 E		S 9	1/4	_____		S 16
T 23 N	R 20 E								
	S 9								
1/4	_____								
	S 16								
78.46	<p>The cor. of secs. 8, 9, 16 and 17.</p> <hr/> <p>N. 5°20' E., bet. secs. 8 and 9.</p> <p>Over nearly level terrain.</p>								
40.78	<p>Point accepted for the 1/4 sec. cor. of secs. 8 and 9, monumented with a mound of stone, 5 ft. base, 1 ft. high, no mkd. stone or remains of wood stake found. This is accepted as the best available evidence of the position of the original cor.</p> <p>At the corner point</p>								

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 23 N R 20 E  
1/4  
S 8 | S 9

2005

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Raise an accessory mound of stone, 3 ft. base, 2 ft. high, W. of the cor.

---

N. 0°19' W., beginning new measurement.

Over nearly level terrain.

40.56 Point for the cor. of secs. 4, 5, 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

T 23 N R 20 E  
S 5 | S 4  
S 8 | S 9

2005

Deposit a magnet in a white plastic case at the base of the stainless steel post.

---

From the cor. of secs. 3, 4, 9 and 10.

N. 88°15' W., bet. secs. 4 and 9.

Over nearly level terrain.

39.95 Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 23 N R 20 E S 4 1/4 ——— S 9</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.90	<p>The cor. of secs. 4, 5, 8 and 9.</p> <hr/> <p>N. 0°09' W., bet. secs. 4 and 5.</p> <p>Over nearly level terrain.</p>
40.56	<p>Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 23 N R 20 E 1/4 S 5   S 4</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.94	<p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32 on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°36' E., bet. secs. 31 and 32.</p> <p>Over nearly level terrain and descend mesa slope.</p>
39.50	<p>Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 20 E 1/4 S 31   S 32  2005
79.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point accepted for the cor. of secs. 29, 30, 31 and 32, monumented with the remains of a mound of earth, identified by quantity of gravel on surface, where the finer earth had blown away. There are no other such deposits in the vicinity. No remains of wood stake or memorial stone found. This is accepted as the best available evidence of the position of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	T 23 N R 20 E S 30   S 29 S 31   S 32  2005
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 88°42' W., bet. secs. 29 and 32.</p> <p>Over nearly level terrain.</p>
39.08	<p>Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	T 23 N R 20 E S 29 1/4 ——— S 32  2005

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
78.16	The cor. of secs. 29, 30, 31 and 32. <hr/>
	N. 89°09' W., bet. secs. 30 and 31.  Over nearly level terrain.
40.46	Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate dist.; there is no remaining evidence of the original cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 23 N    R 20 E                      S 30                  1/4 ———                      S 31             2005         </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.  Set a steel fence post northerly of the cor.
77.78	The cor. of secs. 25, 30, 31 and 36 on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. T23N R19E R20E S25 S30 S36 S31 2004, with a steel fence post northerly of the cor. <hr/>
	From the cor. ofsecs. 29, 30, 31 and 32.  N. 0°22' E., bet. secs. 29 and 30.  Over nearly level terrain.
39.99	Point accepted for the 1/4 sec. cor. of secs. 29 and 30, monumented with an embedded mound of stone, 3 ft. diam., no mkd. stone or remains of wood post found. This is accepted as the best available evidence of the position of the original cor.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 23 N R 20 E  
1/4  
S 30 | S 29  
  
2005

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Raise an accessory mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of the cor.

Set a steel fence post northerly of the cor.

---

N. 2°06' W., beginning new measurement.

Ascending through broken terrain and the steep slopes of Paddock Butte.

40.38 Point for the cor. of secs. 19, 20, 29 and 30, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T 23 N R 20 E  
S 19 | S 20  
S 30 | S 29  
  
2005

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Set a steel fence post southerly of the cor.

Cor. is located on the NE aspect of Paddock Butte.

From this cor. point, U. S. Geological Survey triangulation station designated PADDOCK 1966, bears S. 28°50' E., 6.85 chs. dist., monumented with a standard aluminum tablet, 3 5/8 ins. diam., firmly cemented flush with the surface of a basalt outcrop, mkd. PADDOCK 1966 and a triangle.

---

From the cor. of secs. 20, 21, 28 and 29.

N. 88°23' W., bet. secs. 20 and 29.

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Ascending over gently rising terrain.
39.56	Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate dist.; there is no remaining evidence of the original cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 23 N   R 20 E                      S 20            1/4 ———                      S 29             2005         </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Set a steel fence post northerly of the cor.
79.13	The cor. of secs. 19, 20, 29 and 30. <hr/>
	N. 89°22' W., bet. secs. 19 and 30.
	Crossing Paddock Butte and descending over rolling terrain.
39.68	Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate dist.; there is no remaining evidence of the original cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 23 N   R 20 E                      S 19            1/4 ———                      S 30             2005         </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Set a steel fence post northerly of the cor.
76.18	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. T23N R19E R20E S24 S19 S25 S30 2004, with a steel fence post northerly of the cor. <hr/>
	From the cor. of secs. 19, 20, 29 and 30.

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 1°10' E., bet. secs. 19 and 20.  Descending over steep slope entering gently rolling terrain.
26.27	Center line of Navajo Route 15, asphalt surfaced, 30 ft. wide, bears N. 87° E. and S. 87° W.
40.36	Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate dist.; there is no remaining evidence of the original cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 23 N R 20 E                  1/4              S 19   S 20              2005         </div> Deposit a magnet in a white plastic case at the base of the stainless steel post.  Set a steel fence post northerly of the cor.
80.72	Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist.; there is no remaining evidence of the original cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 23 N R 20 E              S 18   S 17              S 19   S 20              2005         </div> Deposit a magnet in a white plastic case at the base of the stainless steel post.  Raise an accessory mound of stone, 2 ft. base, 1 ft. high, W. of the cor.  Set a steel fence post northerly of the cor.  <hr style="width: 50%; margin-left: 0;"/> From the cor. of secs. 16, 17, 20 and 21.  N. 87°50' W., bet. secs. 17 and 20.  Crossing small butte and descending over rolling terrain.

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.25	<p>Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E S 17 1/4 ——— S 20</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p>
80.50	<p>The cor. of secs. 17, 18, 19 and 20.</p> <hr/> <p>N. 89°53' W., bet. secs. 18 and 19.</p> <p>Ascending over increasingly steep slope to top of mesa.</p>
40.45	<p>Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E S 18 1/4 ——— S 19</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p>
77.45	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. T23N R19E R20E S13 S18 S24 S19 2004, with an accessory mound of stone, 3 ft. base, 2 1/2 ft. high, W. of the cor.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°34' W., bet. secs. 17 and 18.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Ascending over increasingly rolling lands.
40.35	Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate dist.; there is no remaining evidence of the original cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 23 N R 20 E                  1/4            S 18   S 17             2005         </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Set a steel fence post northerly of the cor.
80.70	The cor. of secs. 7, 8, 17 and 18, monumented with a mound of stone, 3 ft. base, 1 ft. high, no mkd. stone found.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.  <div style="text-align: center;">           T 23 N R 20 E            S 7   S 8            S 18   S 17             2004         </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	From the cor. of secs. 8, 9, 16 and 17.
	N. 88°08' W., bet. secs. 8 and 17.
	Over increasingly rolling terrain.
39.18	Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate dist.; there is no remaining evidence of the original cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 20 E S 8 1/4 ——— S 17  2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
78.36	The cor. of secs. 7, 8, 17 and 18.  <hr/> S. 89°32' W., bet. secs. 7 and 18.  Ascending and then descending steep rocky slope.
39.49	The point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate dist.; there is no remaining evidence of the original cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 23 N R 20 E S 7 1/4 ——— S 18  2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.  Raise an accessory mound of stone, 2 ft. base, 1 1/2 ft. high, W. of the cor.
76.07	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T23N R19E R20E S12 S7 S13 S18 2004.  <hr/> From the cor. of secs. 7, 8, 17 and 18.  N. 1°12' E., bet. secs. 7 and 8.  Descending over rolling land, entering nearly level terrain.
39.93	Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor.

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
26 ins. in the ground, with brass cap mkd.

T 23 N R 20 E  
1/4  
S 7 | S 8

2005

Deposit a magnet in a white plastic case at the base of the  
stainless steel post.

Raise an accessory mound of stone, 2 ft. base, 1 ft. high, W. of  
the cor.

79.86

Point for the cor. of secs. 5, 6, 7 and 8, at proportionate  
dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
25 ins. in the ground, with brass cap mkd.

T 23 N R 20 E  
S 6 | S 5  
S 7 | S 8

2005

Deposit a magnet in a white plastic case at the base of the  
stainless steel post.

---

From the cor. of secs. 4, 5, 8 and 9.

N. 89°08' W., bet. secs. 5 and 8.

Over nearly level terrain.

40.11

Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate  
dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with brass cap mkd.

T 23 N R 20 E  
S 5  
1/4 ———  
S 8

2005

Deposit a magnet in a white plastic case at the base of the  
stainless steel post.

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.22	<p>The cor. of secs. 5, 6, 7 and 8.</p> <hr/> <p>S. 89°35' W., bet. secs. 6 and 7.</p> <p>Over nearly level terrain.</p>
39.94	<p>Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate dist.; find a juniper post, 18 x 3 x 2 ins., mkd. IA, laying loose on the ground nearby.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E S 6 1/4 ——— S 7</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base, and the wood post alongside of the stainless steel post.</p>
77.15	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, in a collar of stone, with brass cap mkd. T23N R19E R20E S1 S6 S12 S7 2004.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°20' E., bet. secs. 5 and 6.</p> <p>Over nearly level terrain.</p>
39.92	<p>Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate dist.; find a juniper post, 30 x 3 x 3 ins., mkd. 1/4, laying loose on the ground nearby.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E 1/4 S 6   S 5</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base, and the wood post alongside of the stainless steel post.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Raise an accessory mound of stone, 2 1/2 ft. base, 2 ft. high, W. of the cor.
79.53	The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., hereinbefore described.
<hr/> <b>Subdivision of Section 2, T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona</b> <hr/>	
	From the 1/4 sec. cor. of secs. 2 and 11.
	N. 2°10' W., on the N. and S. center line of sec. 2.
38.97	Point for the center 1/4 sec. cor. of sec. 2, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T 23 N R 20 E C 1/4 S 2  2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Set a steel fence post westerly of the cor.
79.99	The 1/4 sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp.
	From the 1/4 sec. cor. of secs. 1 and 2.
	N. 89°41' W., on the E. and W. center line of sec. 2.
37.90	The center 1/4 sec. cor. of sec. 2.
76.80	The 1/4 sec. cor. of secs. 2 and 3.
<hr/> <b>Subdivision of Section 6, T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona</b> <hr/>	
	From the 1/4 sec. cor. of secs. 6 and 7.
	N. 0°28' E., on the N. and S. center line of sec. 6.

**Subdivision of Section 6,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.94	<p>Point for the center 1/4 sec. cor. of sec. 6, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E C 1/4 S 6</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p>
79.73	<p>The 1/4 sec. cor. of secs. 6 and 31, on the N. bdy. of the Tp.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 5 and 6.</p> <p>S. 89°36' W., on the E. and W. center line of sec. 6.</p>
39.85	<p>The center 1/4 sec. cor. of sec. 6.</p>
77.09	<p>The 1/4 sec. cor. of secs. 1 and 6, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T23N R19E R20E 1/4 S1 S6 2004.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 12, T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 12 and 13.</p> <p>N. 0°01' E., on the N. and S. center line of sec. 12.</p>
40.74	<p>Point for the center 1/4 sec. cor. of sec. 12, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E C 1/4 S 12</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case in a drill hole at the base of the stainless steel post.</p>

**Subdivision of Section 12,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Set a steel fence post in the supporting mound of stone, southerly of the cor.
80.92	The 1/4 sec. cor. of secs. 1 and 12.
	<hr/> From the 1/4 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T23N 1/4 R20E R21E S12 S7 2004.  S. 89°53' W., on the E. and W. center line of sec. 12.
40.18	The center 1/4 sec. cor. of sec. 12.
80.78	The 1/4 sec. cor. of secs. 11 and 12.
	<hr/> <p style="text-align: center;"><b>Subdivision of Section 14, T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> From the 1/4 sec. cor. of secs. 14 and 23.  N. 0°01' E., on the N. and S. center line of sec. 14.
40.25	Point accepted for the center 1/4 sec. cor. of sec. 14, occupied with an iron reinforcement rod, 5/8 in. diam., firmly set, projecting 3 ins. above the ground. This rod was set in the course of an unrecorded 2001 survey under the direction of Gerald K. Wood, Professional Land Surveyor, RLS No. 22290. This position is accepted as a careful and faithful determination of the cor. position.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">             T 23 N R 20 E              C 1/4 S 14               2005           </div> Deposit a magnet in a white plastic case at the base, and the 24 ins. long reinforcement rod inside of the stainless steel post.  Cor. is located 3 lks. E. of a cor. of fences under construction, extending N. and E.
	<hr/> N. 0°01' E., beginning new measurement.

**Subdivision of Section 14,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.25	<p>The 1/4 sec. cor. of secs. 11 and 14.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 14.</p> <p>S. 89°54' W., on the E. and W. center line of sec. 14.</p>
40.12	<p>The center 1/4 sec. cor. of sec. 14.</p> <hr/> <p>S. 89°54' W., beginning new measurement.</p>
40.18	<p>The 1/4 sec. cor. of secs. 14 and 15.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 18, T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 18 and 19.</p> <p>N. 0°07' E., on the N. and S. center line of sec. 18.</p>
40.14	<p>Point for the center 1/4 sec. cor. of sec. 18, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E C 1/4 S 18</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p>
80.28	<p>The 1/4 sec. cor. of secs. 7 and 18.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 17 and 18.</p> <p>S. 89°50' W., on the E. and W. center line of sec. 18.</p>
39.97	<p>The center 1/4 sec. cor. of sec. 18.</p>

**Subdivision of Section 18,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
76.76	<p>The 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set flush in a mound of stone, 5 ft. base, 1 ft. high, with brass cap mkd. T23N R19E R20E 1/4 S13 S18 2004.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 20, T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 20 and 29.</p> <p>N. 1°40' E., on the N. and S. center line of sec. 20.</p>
40.16	<p>Point for the center 1/4 sec. cor. of sec. 20, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E C 1/4 S 20</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p>
80.32	<p>The 1/4 sec. cor. of secs. 17 and 20.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 20 and 21.</p> <p>N. 88°06' W., on the E. and W. center line of sec. 20.</p>
39.91	<p>The center 1/4 sec. cor. of sec. 20.</p>
79.82	<p>The 1/4 sec. cor. of secs. 19 and 20.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 22, T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 22 and 27.</p> <p>N. 1°26' W., on the N. and S. center line of sec. 22.</p>
40.41	<p>Point for the center 1/4 sec. cor. of sec. 22, at intersection with the E. and W. center line.</p>

**Subdivision of Section 22,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E C 1/4 S 22</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p>
41.14	Center line of Navajo Route 15, asphalt surfaced, 30 ft. wide, bears N. 87° E. and S. 87° W.
80.75	The 1/4 sec. cor. of secs. 15 and 22.
	<hr/> <p>From the 1/4 sec. cor. of secs. 22 and 23.</p> <p>N. 89°46' W., on the E. and W. center line of sec. 22.</p>
40.90	The center 1/4 sec. cor. of sec. 22.
80.16	The 1/4 sec. cor. of secs. 21 and 22.
	<hr/> <p style="text-align: center;"><b>Subdivision of Section 24, T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 24 and 25.</p> <p>N. 0°01' E., on the N. and S. center line of sec. 24.</p>
40.05	Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E. and W. center line.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E C 1/4 S 24</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p>

**Subdivision of Section 24,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.07	<p>The 1/4 sec. cor. of secs. 13 and 24.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T23N 1/4 R20E R21E S24 S19 2004.</p> <p>S. 88°56' W., on the E. and W. center line of sec. 24.</p>
40.38	The center 1/4 sec. cor. of sec. 24.
80.75	The 1/4 sec. cor. of secs. 23 and 24.
	<p><b>Subdivision of Section 26, T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 26 and 35.</p> <p>N. 0°40' E., on the N. and S. center line of sec. 26.</p>
40.10	<p>Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E C 1/4 S 26</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p>
79.58	The 1/4 sec. cor. of secs. 23 and 26.
	<hr/> <p>From the 1/4 sec. cor. of secs. 25 and 26.</p> <p>N. 89°26' W., on the E. and W. center line of sec. 26.</p>
39.50	The center 1/4 sec. cor. of sec. 26.

**Subdivision of Section 26,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
78.51	<p>The 1/4 sec. cor. of secs. 26 and 27.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 28, T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 28 and 33.</p> <p>N. 0°24' E., on the N. and S. center line of sec. 28.</p>
39.44	<p>Point for the center 1/4 sec. cor. of sec. 28, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 20 E C 1/4 S 28</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post northerly of the cor.</p>
79.48	<p>The 1/4 sec. cor. of secs. 21 and 28.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 27 and 28.</p> <p>N. 88°01' W., on the E. and W. center line of sec. 28.</p>
40.22	<p>The center 1/4 sec. cor. of sec. 28.</p>
79.72	<p>The 1/4 sec. cor. of secs. 28 and 29.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 30, T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 30 and 31.</p> <p>N. 0°20' W., on the N. and S. center line of sec. 30.</p>
40.01	<p>Point for the center 1/4 sec. cor. of sec. 30, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Subdivision of Section 30,  
T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 20 E C 1/4 S 30  2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Set a steel fence post northerly of the cor.
80.18	The 1/4 sec. cor. of secs. 19 and 30. <hr/> From the 1/4 sec. cor. of secs. 29 and 30.  N. 89°08' W., on the E. and W. center line of sec. 30.
40.94	The center 1/4 sec. cor. of sec. 30.
77.85	The 1/4 sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. T23N R19E R20E 1/4 S25 S30 2004. <hr/>

**T. 23 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS

---

 GENERAL DESCRIPTION
 

---

This survey is located on the Navajo Indian reservation, almost equidistant from either Winslow or Holbrook, being 45 miles Northeast of Winslow and 47 miles Northwest of Holbrook. Primary access to the township is provided by Navajo Route 15 which runs E. and W., essentially bisecting the N. half of the township from the S. A multitude of dirt roads, both graded and two track, provide entry to virtually all of the project area.

Many small housing clusters and single dwellings occupy the project, there are no housing developments within the project area. The El Paso Gas Company maintains a pipeline that diagonally crosses the NW of the township. A former ENRON pipeline roughly parallels the El Paso line. The primary agricultural use is the grazing of sheep, goats, cattle, and horses. There are remains of cultivated fields along the Gleshbito Wash plain.

The eastern portion of the township is severely broken by the many tributaries to the Gleshbito Wash, which cuts through the township from the Northeast to the Southeast. Above the wash basin in the western portion of the project, the ground is nearly level with several buttes rising out of the central area. Elevation ranges from 5200 ft. at the lowest point in the Gleshbito Wash, to 6550 ft. on top of the buttes.

Vegetation on the valley floor is of various grasses, sages and cacti typical to the Great Basin Desertscrub biotic community, while the slopes of the buttes are dotted with juniper, scrub oak, and mahogany. Many of the larger junipers have been harvested for fire wood and fence posts. Mule deer were present in the broken terrain along the Gleshbito Wash.

The mean magnetic declination of 11 1/4° E., was derived from the National Geophysical Data Center's magnetic declination calculator, GEOMAG v4.0, utilizing the International Geomagnetic Reference Field model for years 2000 through 2005, for the dates of survey.

---





