

**ORIGINAL**

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE  
DEPENDENT RESURVEY OF  
A PORTION OF THE SUBDIVISIONAL LINES  
AND THE  
SURVEY OF  
A PORTION OF THE SUBDIVISIONAL LINES  
TOWNSHIP 40 NORTH, RANGE 5 WEST

OF THE GILA AND SALT RIVER MERIDIAN,  
IN THE STATE OF ARIZONA.

**EXECUTED BY**

**Joe R. Salazar, Cadastral Surveyor**

Under Special Instructions dated June 14, 2005, approved June 14, 2005, which provided for the surveys included under Group No. 964, and assignment instructions dated July 21, 2005.

**Survey commenced July 25, 2005**

**Survey completed August 24, 2005**

**INDEX DIAGRAM**

TOWNSHIP 40 NORTH                      RANGE 5 WEST  
 GILA AND SALT RIVER MERIDIAN, ARIZONA

6	5	4 11	24 3 22	23 2 17	18 1
7	8	9 10	25 10 21	22 11 16	17 12
18	17	16 9	24 15 20 6	20 14 15	15 13
19	20	21 8	9 22 5	19 23 13	14 24
30	29	28 7	8 27 5	19 26 12	13 25
31	32	33	6 34	5 35	4 36

**T. 40 N., R. 5 W., Gila and Salt River Meridian, Arizona**

## CHAINS

The following field notes describe the dependent resurvey of a portion of the subdivisional lines and the survey of a portion of the subdivisional lines, Township 40 North, Range 5 West, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Jos. C. Thoma surveyed the Tenth Standard Parallel North (north boundary), the First Guide Meridian West (east boundary), and a portion of the subdivisional lines in 1913-14.

William E. Hiester and Willis W. Bandy resurveyed a portion of the Tenth Standard Parallel North (north boundary) in 1925.

Walter H. Good resurveyed a portion of the Tenth Standard Parallel North (north boundary) and a portion of the subdivisional lines in 1933.

Harry S. Pierce correctively resurveyed a portion of the Tenth Standard Parallel North (north boundary) in 1979.

W. William Foster resurveyed a portion of the Tenth Standard Parallel North (north boundary) and a portion of the First Guide Meridian West (east boundary) in 2003.

W. William Foster resurveyed a portion of the Tenth Standard Parallel North (north boundary) in 2005.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated June 14, 2005, for Group No. 964, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 3700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from a tie to first order United States Coast and Geological Survey triangulation station PIPE, 1953 as published by the National Geodetic Survey, NAD 83 (1992). The geographic position of the corner of sections 25, 30, 31 and 36 on the east boundary of township, is as follows:

Latitude: 36°49'55.22" N.

Longitude: 112°46'23.62" W.

**T. 40 N., R. 5 W., Gila and Salt River Meridian, Arizona**

CHAINS

The mean magnetic declination is 12 1/4° E.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 40 N., R. 5 W., Gila and Salt River Meridian, Arizona**

---

Restoring the survey executed by  
Jos. C. Thoma, in 1914

---

Beginning at the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 15 ins. above the ground, with brass cap mkd. T40N S25 S30 R5W S36 S31 R4W 1914 2003.

From this cor. point, U. S. Coast and Geodetic Survey triangulation station "PIPE, 1953", with published latitude of 36°51'44.0015" N. and longitude of 112°43'57.0426" W., NAD 83(1992), bears N. 47°16' E. (forward bearing), 245.77 chs. dist., monumented with a standard disk, 3 ins. diam., encased in a concrete form, 10 ins. sq., projecting 7 ins. above the ground, with top of disk mkd. PIPE 1953 and a triangle.

Cor. is located in an intersection of fences, extending E., S. and W.

S. 89°59' W., bet. secs. 25 and 36, along a fence on the Kaibab Paiute Indian Reservation Bdy.

Over nearly level terrain, through scattered sage, Mormon Tea and native grasses.

40.02 The 1/4 sec. cor. of secs. 25 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. T40N R5W 1/4 S25 S36 1914.

Cor. is located in a fence, bears E. and W.

Add the marks 2005 to the brass cap.

---

S. 89°59' W., beginning new measurement.

40.03 The cor. of secs. 25, 26, 35 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. T40N R5W S26 S25 S35 S36 1914.

Cor. is located in an intersection of fences, extending E., S. and W.

Add the marks 2005 to the brass cap.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 40 N., R. 5 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<hr/> <p>S. 89°59' W., bet. secs. 26 and 35, along a fence on the Kaibab Paiute Indian Reservation Bdy.</p>
	<p>Over nearly level terrain, through scattered sage, Mormon Tea and native grasses.</p>
40.02	<p>The 1/4 sec. cor. of secs. 26 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. 1/4 S26 S35 1914.</p>
	<p>Cor. is located in a fence, extending E. and W.</p>
	<p>Add the marks T40N R5W 2005 to the brass cap.</p>
	<hr/> <p>S. 89°59' W., beginning new measurement.</p>
40.03	<p>The cor. of secs. 26, 27, 34 and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. T40N R5W S27 S26 S34 S35 1914.</p>
	<p>Cor. is located in a fence, extending E. and W.</p>
	<p>Add the marks 2005 to the brass cap.</p>
	<hr/> <p>N. 0°01' W., bet. secs. 26 and 27.</p>
	<p>Over nearly level terrain, through scattered sage, Mormon Tea and native grasses.</p>
40.02	<p>The 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. 1/4 S27 S26 1914.</p>
	<p>Add the marks T40N R5W 2005 to the brass cap.</p>
	<hr/> <p>N. 0°01' E., beginning new measurement.</p>
40.02	<p>The cor. of secs. 22, 23, 26 and 27, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. T40N R5W S22 S23 S27 S26 1914.</p>
	<p>Add the marks 2005 to the brass cap.</p>
	<hr/> <p>North, bet. secs. 22 and 23.</p>
14.90	<p>Graded road, 16 ft. wide, bears N. 80° E. and S. 80° W.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 40 N., R. 5 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over nearly level terrain, through scattered sage, Mormon Tea and native grasses.
40.02	<p>The 1/4 sec. cor. of secs. 22 and 23, monumented with an iron post, 1 in. diam., firmly set, flush with ground, with brass cap mkd. 1/4 S22 S23 1914.</p> <p>Add the marks T40N R5W 2005 to the brass cap.</p> <hr/>
	North, beginning new measurement.
26.50	Southerly right-of-way fence of Arizona State Highway No. 389, bears N. 80° E. and S. 80° W.
28.00	Center of pavement of Arizona State Highway No. 389, 36 ft. wide, bears N. 80° E. and S. 80° W.
29.50	Northerly right-of-way fence of Arizona State Highway No. 389, bears N. 80° E. and S. 80° W.
40.03	<p>The cor. of secs. 14, 15, 22 and 23, monumented with an iron post, 2 ins. diam., firmly set, projecting 16 ins. above the ground, with brass cap mkd. T40N R5W S15 S14 S22 S23 1914.</p> <p>Add the marks 2005 to the brass cap.</p> <hr/>
	<p>North, bet. secs. 14 and 15.</p> <p>Over nearly level land, through scattered sage, Mormon Tea and native grasses.</p>
40.19	<p>The 1/4 sec. cor. of secs. 14 and 15, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. 1/4 S15 S14 1914.</p> <p>Add the marks T40N R5W 2005 to the brass cap.</p> <hr/>
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°58' W., bet. secs. 27 and 34, along a fence on the Kaibab Paiute Indian Reservation Bdy.</p> <p>Over nearly level terrain, through scattered sage, Mormon Tea and native grasses.</p>
40.02	<p>The 1/4 sec. cor. of secs. 27 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. 1/4 S27 S34 1914.</p> <p>Cor. is located in a fence, extending E. and W.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 40 N., R. 5 W., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Add the marks T40N R5W 2005 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°59' W., beginning new measurement.</p>						
40.03	<p>The cor. of secs. 27, 28, 33 and 34, monumented with an iron post, 2 ins. diam., firmly set, projecting 13 ins. above the ground, with brass cap mkd. T40N R5W S28 S27 S33 S34 1914.</p> <p>Cor. is located in an intersection of fences, extending N., E. and S., and beneath a power line, bears N. and S.</p> <p>Add the marks 2005 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°02' W., bet. secs. 27 and 28, along a fence and beneath a power line, on the Kaibab Paiute Indian Reservation Bdy.</p> <p>Over nearly level terrain, through scattered sage, Mormon Tea and native grasses.</p>						
40.02	<p>The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd. 1/4 S28 S27 1914.</p> <p>Add the marks T40N R5W 2005 to the brass cap.</p> <p>Cor. is located in a fence, extending N. and S., and beneath a power line, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°06' W., beginning new measurement.</p>						
40.03	<p>Point for the cor. of secs. 21, 22, 27 and 28, determined latitudinally by proportionate measurement and longitudinally by a fence, extending N. and S., there is no remaining evidence of the original cor. position.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: 0 auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 40 N</td> <td style="padding: 0 10px;">R 5 W</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 21</td> <td style="padding: 0 10px;">S 22</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 28</td> <td style="padding: 0 10px;">S 27</td> </tr> </table> <p style="margin: 5px 0;">2005</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located beneath a power line, bears N. and S.</p>	T 40 N	R 5 W	S 21	S 22	S 28	S 27
T 40 N	R 5 W						
S 21	S 22						
S 28	S 27						

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 40 N., R. 5 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 89°59' W., bet. secs. 22 and 27.</p> <p>Over nearly level terrain, through scattered sage, Mormon Tea and native grasses.</p>
40.06	<p>The 1/4 sec. cor. of secs. 22 and 27, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. 1/4 S22 S27 1914.</p> <p>Add the marks T40N R5W 2005 to the brass cap.</p>
	<hr/> <p>West, beginning new measurement.</p>
40.08	<p>The cor. of secs. 21, 22, 27 and 28.</p> <hr/> <p>N. 0°01' E., bet. secs. 21 and 22, along a fence and beneath a power line, on the Kaibab Paiute Indian Reservation Bdy.</p> <p>Over nearly level terrain, through scattered sage, Mormon Tea and native grasses.</p>
0.20	<p>Graded road, 16 ft. wide, bears N. 80° E. and W.</p>
40.01	<p>The 1/4 sec. cor. of secs. 21 and 22, monumented with an iron post, 1 in. diam., firmly set, flush with the ground, with brass cap mkd. 1/4 S21 S22 1914.</p> <p>Add the marks T40N R5W 2005 to the brass cap.</p> <p>Cor. is located in a fence and beneath a power line, extending N. and S.</p> <hr/> <p>N. 0°02' W., beginning new measurement.</p>
40.03	<p>The cor. of secs. 15, 16, 21 and 22, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. T40N R5W S16 S15 S21 S22 1914.</p> <p>Cor. is located in a fence and beneath a power line, extending N. and S.</p> <p>Add the marks 2005 to the brass cap.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 40 N., R. 5 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>West, bet. secs. 15 and 22.</p> <p>Over nearly level terrain, through scattered sage, Mormon Tea and native grasses.</p>
37.85	<p>Easterly right-of-way fence of Arizona State Highway No. 389, bears S. 72° E. and N. 72° W.</p>
40.06	<p>The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 1 in. diam., firmly set, flush with the ground, with brass cap mkd. 1/4 S15 S22 1914.</p> <p>Add the marks T40N R5W 2005 to the brass cap.</p> <hr/>
	<p>West, beginning new measurement.</p>
2.60	<p>Center of pavement of Arizona State Highway No. 389, 36 ft. wide, bears S. 72° E. and N. 72° W.</p>
7.40	<p>Westerly right-of-way fence of Arizona State Highway No. 389, bears S. 72° E. and N. 72° W.</p>
40.07	<p>The cor. of secs. 15, 16, 21 and 22.</p> <hr/>
	<p>N. 0°04' W., bet. secs. 15 and 16, along a fence on the Kaibab Paiute Indian Reservation Bdy.</p> <p>Over nearly level terrain, through scattered sage, Mormon Tea and native grasses.</p>
10.75	<p>Southerly right-of-way fence of Arizona State Highway No. 389, bears S. 72° E. and N. 72° W.</p>
12.30	<p>Center of pavement of Arizona State Highway No. 389, 36 ft. wide, bears S. 72° E. and N. 72° W.</p>
13.90	<p>Northerly right-of-way fence of Arizona State Highway No. 389, bears S. 72° E. and N. 72° W.</p>
40.02	<p>The 1/4 sec. cor. of secs. 15 and 16, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. 1/4 S16 S15 1914.</p> <p>Add the marks T40N R5W 2005 to the brass cap.</p>
	<p>Cor. is located in a fence, extending N. and S.</p> <hr/>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 40 N., R. 5 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Restoring the survey executed by Walter H. Good, in 1933</p> <hr/>
	N. 0°08' W., beginning new measurement.
16.00	Steep bluff, thence along very rugged, mountainous terrain.
39.80	Wash, 4 ft. wide, 2 ft. deep, drains N. 75° W.
39.98	The cor. of secs. 9, 10, 15 and 16, monumented with an iron post, 2 ins. diam., firmly set, projecting 20 ins. above the ground, in a mound of stone, 2 ft. base, 1 ft. high, with brass cap mkd. T40N R5W S9 S10 S16 S15 1933.
	Add the marks 2005 to the brass cap.
	<hr/>
	N. 0°01' W., bet. secs. 9 and 10, along the Kaibab Paiute Indian Reservation Bdy.
	Over rugged, mountainous terrain, through scattered sage, Mormon Tea, juniper trees and native grasses.
39.99	The 1/4 sec. cor. of secs. 9 and 10, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd. 1/4 S9 S10 1933.
	Add the marks T40N R5W 2005 to the brass cap.
	<hr/>
	N. 0°07' W., beginning new measurement.
39.91	Point for the cor. of secs. 3, 4, 9 and 10, at proportionate dist., by the method of three point control, there is no remaining evidence of the original cor. position. Cor. falls on large, unstable boulder in wash, 15 ft. wide, 15 ft. deep, drains West, where it is impracticable to establish a permanent monument.
	from which
	An "X" chiseled on a sandstone, 8 X 6 X 2 ft., bears S. 88°16' E., 29 lks. dist.
	An "X" chiseled on a sandstone, 6 X 4 X 2 ft., bears S. 16°54' E., 35 lks. dist.
	Note: Find an iron post, 2 ins. diam., 36 ins. long, lying nearby, upended and under a boulder in the wash, with brass cap mkd. T40N R5W S4 S3 S9 S10 1933. Remove the iron post from the area.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 40 N., R. 5 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this cor. point, the 1/4 sec. cor. of secs. 4 and 9, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above the ground, in a supporting mound of stone, 2 1/2 ft. base, 1 ft. high, with brass cap mkd. 1/4 S4 S9 1933, bears N. 89°58' W., 39.91 chs. dist. Add the marks T40N R5W 2005 to the brass cap and rebuild the supporting mound of stone, 3 ft. base, to top.</p>
	<hr/> <p>N. 0°04' E., bet. secs. 3 and 4.</p>
	<p>Over rugged, mountainous terrain, through scattered sage, Mormon Tea, juniper trees and native grasses.</p>
39.91	<p>The 1/4 sec. cor. of secs. 3 and 4, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. 1/4 S4 S3 1933, witnessed with a mound of stone, 4 ft. base, 3 ft. high, W. of cor.</p> <p>Add the marks T40N R5W 2005 to the brass cap.</p>
	<hr/> <p>N. 0°07' W., beginning new measurement.</p>
31.96	<p>The witness cor. to the closing cor. of secs. 3 and 4, monumented with an iron post, 1 in. diam., firmly set, projecting 17 ins. above the ground, with brass cap mkd. T41N R5W S34 CC S4 S3 T40N R5W WC 1933.</p> <p>Add the marks 2005 to the brass cap.</p>
	<p>Build a supporting mound of stone, 3 ft. base, to top of brass cap.</p>
33.82	<p>True point for the closing cor. of secs. 3 and 4, at intersection with the Tenth Stan. Par. N., falls on steep sandstone side hill, where it is impracticable to establish a permanent monument.</p> <p>From the true point for the closing cor. of secs. 3 and 4, the true point for the stan. cor. of secs. 33 and 34, T. 41 N., R. 5 W., bears West, 8.90 chs. dist. From this true point, the witness cor. to the stan. cor. of secs. 33 and 34, bears West, 7.82 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 36 ins. above the ground, in a supporting mound of stone, 4 1/2 ft. base, 2 1/2 ft. high, with brass cap mkd. SC T41N R5W S33 S34 WC 1925 2005.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 40 N., R. 5 W., Gila and Salt River Meridian, Arizona**

CHAINS	<p>From this same true point for the closing cor. of secs. 3 and 4, the true point for the stan. 1/4 sec. cor. of sec. 34, T. 41 N., R. 5 W., bears East, 31.22 chs. dist. From this true point, the witness cor. to the stan. 1/4 sec. cor. of sec. 34, bears N. 58°15' E., 3.92 chs. dist., monumented with a brass tablet, 3 1/2 ins. diam, mkd. WC SC T41N R5W 1/4 S34 2005 and an arrow pointing to the true point.</p> <hr/> <p style="text-align: center;"><b>Survey of a Portion of the Subdivisional Lines, T. 40 N., R. 5 W., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36, hereinbefore described.</p> <p>N. 0°02' E., bet. secs. 25 and 26.</p> <p>Over nearly level terrain, through scattered sage, Mormon Tea and native grasses.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 5 W 1/4 S 26   S 25  2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>80.00 Point for the cor. of secs. 23, 24, 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 5 W S 23   S 24 S 26   S 25  2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>
--------	--

**Survey of a Portion of the Subdivisional Lines,  
T. 40 N., R. 5 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. T40N R5W R4W S24 S19 S25 S30 1914 2003.</p> <p>S. 89°58' W., bet. secs. 24 and 25.</p> <p>Over nearly level terrain, through scattered sage, Mormon Tea and native grasses.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 5 W S 24 1/4 ——— S 25</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.04	<p>The cor. of secs. 23, 24, 25 and 26.</p> <hr/> <p>N. 0°02' E., bet. secs. 23 and 24.</p> <p>Over rolling terrain, through scattered sage, Mormon Tea and native grasses.</p>
30.20	<p>Graded road, 16 ft. wide, bears N. 80° E. and S. 80° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 5 W 1/4 S 23   S 24</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
63.35	<p>Southerly right-of-way fence of Arizona State Highway No. 389, bears N. 80° E. and S. 80° W.</p>

**Survey of a Portion of the Subdivisional Lines,  
T. 40 N., R. 5 W., Gila and Salt River Meridian, Arizona**

CHAINS									
64.85	Center of pavement of Arizona State Highway No. 389, 36 ft. wide, bears N. 80° E. and S. 80° W.								
66.35	Northerly right-of-way fence of Arizona State Highway No. 389, bears N. 80° E. and S. 80° W.								
80.00	<p>Point for the cor. of secs. 13, 14, 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="810 684 1024 785"> <tr> <td align="center" colspan="2">T 40 N R 5 W</td> </tr> <tr> <td align="center">S 14</td> <td align="center">S 13</td> </tr> <tr> <td align="center">S 23</td> <td align="center">S 24</td> </tr> </table> <p align="center">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 15 ins. above the ground, with brass cap mkd. T40N S13 S18 R5W S24 S19 R4W 1914 2003.</p> <p>S. 89°56' W., bet. secs. 13 and 24.</p> <p>Over rolling terrain, through scattered sage, Mormon Tea and native grasses.</p>	T 40 N R 5 W		S 14	S 13	S 23	S 24		
T 40 N R 5 W									
S 14	S 13								
S 23	S 24								
40.02	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="810 1503 1024 1619"> <tr> <td align="center" colspan="2">T 40 N R 5 W</td> </tr> <tr> <td align="center" colspan="2">S 13</td> </tr> <tr> <td align="center">1/4</td> <td align="center">_____</td> </tr> <tr> <td align="center" colspan="2">S 24</td> </tr> </table> <p align="center">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 40 N R 5 W		S 13		1/4	_____	S 24	
T 40 N R 5 W									
S 13									
1/4	_____								
S 24									
80.04	<p>The cor. of secs. 13, 14, 23 and 24.</p> <hr/>								

**Survey of a Portion of the Subdivisional Lines,  
T. 40 N., R. 5 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 0°02' E., bet. secs. 13 and 14.
	Over rolling terrain, through scattered sage, Mormon Tea, native grasses and juniper.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 N R 5 W 1/4 S 14   S 13  2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
68.50	Enter very rugged terrain.
80.00	Point for the cor. of secs. 11, 12, 13 and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.
	T 40 N R 5 W S 11   S 12 S 14   S 13  2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
<hr/>	
	From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. T40N R5W S12 S7 S13 S18 R4W 1914 2003.
	S. 89°53' W., bet. secs. 12 and 13.
	Over broken terrain, through scattered sage, Mormon Tea and native grasses.
40.02	Point for the 1/4 sec. cor. of secs. 12 and 13.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of a Portion of the Subdivisional Lines,  
T. 40 N., R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 40 N R 5 W S 12 1/4 ——— S 13</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.04	<p>The cor. of secs. 11, 12, 13 and 14.</p> <hr/> <p>N. 0°02' E., bet. secs. 11 and 12.</p> <p>Over rugged terrain, through scattered sage, Mormon Tea and native grasses.</p>
40.00	<p>True point for the 1/4 sec. cor. of secs. 11 and 12, falls on steep E. slope of ridge, where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 11 and 12, bears S. 26°36' E., 1.07 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">WC T 40 N R 5 W 1/4 S 11   S 12</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, cemented in a drill hole, 4 1/2 ins. deep, in solid sandstone, with top mkd.</p> <p style="text-align: center;">T 40 N R 5 W S 2   S 1 S 11   S 12</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in drill hole, at the base of the brass tablet.</p>

**Survey of a Portion of the Subdivisional Lines,  
T. 40 N., R. 5 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Cor. is located on a sandstone ledge, on E. side of ravine, 200 ft. deep, drains S. 10° W.</p> <hr/> <p>From the true point for the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp.</p> <p>From this true point, the witness cor. to the cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above a supporting mound of stone, 3 ft. base, with brass cap mkd. T40N R5W R4W S1 S6 WC S7 S12 1914 2003, bears N. 0°09' E., 80 lks. dist.</p> <p>S. 89°55' W., bet. secs. 1 and 12.</p> <p>Over rugged terrain, through scattered sage, Mormon Tea and native grasses.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p align="center">T 40 N R 5 W S 1 1/4 _____ S 12</p> <p align="center">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located on steep and rocky, south slope of ridge, bears E. and W.</p>
79.98	<p>The cor. of secs. 1, 2, 11 and 12.</p> <hr/> <p>N. 0°02' E., bet. secs. 1 and 2.</p> <p>Over rugged terrain, through scattered sage, Mormon Tea and native grasses.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, cemented in a drill hole, 4 1/2 ins. deep, in solid sandstone, with top mkd.</p>

**Survey of a Portion of the Subdivisional Lines,  
T. 40 N., R. 5 W., Gila and Salt River Meridian, Arizona**

CHAINS	<p align="center">T 40 N R 5 W 1/4 S 2   S 1 2005</p> <p>Deposit a magnet in drill hole, at the base of the brass tablet.</p> <p>Cor. is located on W. face of a steep slope of a ridge, bears N. and S.</p> <p>73.70 Point for the closing cor. of secs. 1 and 2, at intersection with the Tenth Stan. Par. N.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 41 N R 5 W S 36 ----- S 2   S 1 T 40 N R 5 W CC 2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the stan. cor. of secs. 35 and 36, T. 41 N., R. 5 W., bears West, 8.96 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. SC T41N R5W S35 S36 2005.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 41 N., R. 5 W., bears East, 31.16 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. SC T41N R5W 1/4 S36 2005.</p> <hr/> <p>The true point for the 1/4 sec. cor. of sec. 1, is at midpoint on the N. bdy. of sec. 1, falls on a steep slope where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for a witness cor. to the 1/4 sec. cor. of sec. 1, bears N. 80°56' E., 90 lks. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
--------	---

Survey of a Portion of the Subdivisional Lines,  
T. 40 N., R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">WC T 41 N R 5 W ← ————— 1/4 S 1 T 40 N R 5 W</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this same true point, the stan. 1/4 sec. cor. of sec. 36, bears West, 8.87 chs. dist.</p> <p>From this same true point, the stan. cor. of Tps. 41 N., Rs. 4 and 5 W. bears East, 31.25 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. SC T41N S36 S31 R5W R4W 2003 1979 1975 1914 2005.</p> <hr/>
	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>West, bet. secs. 23 and 26.</p> <p>Over nearly level terrain, through scattered sage, Mormon Tea and native grasses.</p>
40.04	<p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 5 W S 23 1/4 ————— S 26</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.08	<p>The cor. of secs. 22, 23, 26 and 27, hereinbefore described.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 89°58' W., bet. secs. 14 and 23.</p> <p>Over nearly level terrain, through scattered sage, Mormon Tea and native grasses.</p>

**Survey of a Portion of the Subdivisional Lines,  
T. 40 N., R. 5 W., Gila and Salt River Meridian, Arizona**

CHAINS	
40.06	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p align="center">T 40 N R 5 W S 14 1/4 ——— S 23</p> <p align="center">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.12	<p>The cor. of secs. 14, 15, 22 and 23, hereinbefore described.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 14 and 15, hereinbefore described.</p> <p>N. 0°01' E., bet. secs. 14 and 15.</p> <p>Over rugged, mountainous terrain, through scattered sage, Mormon Tea and native grasses.</p>
40.00	<p>Point for the cor. of secs. 10, 11, 14 and 15.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, cemented in a drill hole, 4 1/2 ins. deep, in solid sandstone, with top mkd.</p> <p align="center">T 40 N R 5 W S 10   S 11 S 15   S 14</p> <p align="center">2005</p> <p>Deposit a magnet in drill hole, at the base of the brass tablet.</p> <p>Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.</p> <p>Cor. is located on a sandstone ledge of an E. facing moderate slope.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 89°49' W., bet. secs. 11 and 14.</p> <p>Over rugged, mountainous terrain, through scattered sage, Mormon Tea and native grasses.</p>

**Survey of a Portion of the Subdivisional Lines,  
T. 40 N., R. 5 W., Gila and Salt River Meridian, Arizona**

CHAINS	
40.07	<p>Point for the 1/4 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, 1 1/2 ft. base, to top, with brass cap mkd.</p> <p align="center">T 40 N R 5 W S 11 1/4 ——— S 14</p> <p align="center">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.14	<p>The cor. of secs. 10, 11, 14 and 15.</p> <hr/> <p>N. 0°01' E., bet. secs. 10 and 11.</p> <p>Over rugged, mountainous terrain, through scattered sage, scattered pine and juniper trees.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 40 N R 5 W 1/4 S 10   S 11</p> <p align="center">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 2, 3, 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p align="center">T 40 N R 5 W S 3   S 2 ————— S 10   S 11</p> <p align="center">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>

**Survey of a Portion of the Subdivisional Lines,  
T. 40 N., R. 5 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°50' W., bet. secs. 2 and 11.</p> <p>Over rugged, mountainous terrain, through scattered sage, scattered pine and juniper trees.</p>
40.07	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, cemented in a drill hole, 4 1/2 ins. deep, in solid sandstone, with top mkd.</p> <p align="center">T 40 N R 5 W S 2 1/4 ——— S 11</p> <p align="center">2005</p> <p>Deposit a magnet in drill hole, at the base of the brass tablet.</p>
80.14	<p>The cor. of secs. 2, 3, 10 and 11.</p> <hr/> <p>N. 0°01' E., bet. secs. 2 and 3.</p> <p>Over rugged, mountainous terrain, through scattered sage, scattered pine and juniper trees.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 40 N R 5 W 1/4 S 3   S 2</p> <p align="center">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
73.44	<p>Point for the closing cor. of secs. 2 and 3, at intersection with the Tenth Stan. Par. N.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Survey of a Portion of the Subdivisional Lines,  
T. 40 N., R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS

T 41 N R 5 W  
S 35

S 3	S 2
T 40 N	
CC	

2005

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the stan. cor. of secs. 34 and 35, T. 41 N., R. 5 W., bears West, 9.07 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. SC T41N R5W S34 S35 2005.

From this same cor. point, the true point for the stan. 1/4 sec. cor. of sec. 35, T. 41 N., R. 5 W., bears East, 31.05 chs. dist. From this true point, the witness cor. to the stan. 1/4 sec. cor. of sec. 35, bears N. 50°55' E., 2.81 chs. dist., monumented with brass tablet, set flush in a sandstone ledge, with top mkd. WC SC T41N R5W 1/4 S35 2005 and an arrow pointing to the true point.

The true point for the 1/4 sec. cor. of sec. 2, is at midpoint on the N. bdy. of sec. 2, falls on a near vertical cliff, 400 ft. high, where it is impracticable to establish a permanent monument.

From this true point, the point selected for a witness cor. to the 1/4 sec. cor. of sec. 2, bears N. 28°41' W., 3.98 chs. dist.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, cemented in a drill hole, 4 1/2 ins. deep, in sandstone, with top mkd.

WC	
T 41 N R 5 W	
-----	
1/4 S 2	
T 40 N R 5 W	

2005

Deposit a magnet in the drill hole at the base of the brass tablet.

Cor. is located on the top of a sandstone exposed spur, 20 ft. wide, bears N. and S.

**Survey of a Portion of the Subdivisional Lines,  
T. 40 N., R. 5 W., Gila and Salt River Meridian, Arizona**

CHAINS

From this same true point, the true point for the stan. 1/4 sec. cor. of sec. 35, bears West, 9.015 chs. dist.

From this same true point, the stan. cor. of sec. 35 and 36, Tp. 41 N., Rg. 5 W. bears East, 31.105 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. SC T41N S35 S36 R5W 2005.

---

The point for the 1/4 sec. cor. of sec. 3, is at midpoint on the N. bdy. of sec. 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 41 N R 5 W

1/4 S 3

T 40 N R 5 W

2005

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the true point for the stan. 1/4 sec. cor. of sec. 34, T. 41 N. R. 5 W., bears West, 8.985 chs. dist.

From this same cor. point, the stan. cor. of secs. 34 and 35, bears East, 31.135 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. SC T41N R5W S34 S35 2005.

---

From the cor. of secs. 10, 11, 14 and 15.

S. 89°52' W., bet. secs. 10 and 15.

Over rugged, mountainous terrain, through scattered sage, scattered pine and juniper trees.

40.13

Point for the 1/4 sec. cor. of secs. 10 and 15.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, cemented in a drill hole, 4 1/2 ins. deep, in solid sandstone, with top mkd.

**Survey of a Portion of the Subdivisional Lines,  
T. 40 N., R. 5 W., Gila and Salt River Meridian, Arizona**

CHAINS	
80.26	<p align="center">T 40 N R 5 W S 10 1/4 ——— S 15</p> <p align="center">2005</p> <p>Deposit a magnet in drill hole, at the base of the brass tablet. Cor. is located on edge of sheer sandstone rock face.</p> <p>The cor. of secs. 9, 10, 15 and 16.</p> <hr/>
40.19	<p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. 89°47' W., bet. secs. 3 and 10.</p> <p>Over rugged, mountainous terrain, through scattered sage, scattered pine and juniper trees.</p> <p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
80.38	<p align="center">T 40 N R 5 W S 3 1/4 ——— S 10</p> <p align="center">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 3, 4, 9 and 10, hereinbefore described.</p> <hr/>
	<p align="center">GENERAL DESCRIPTION</p> <hr/> <p>The area surveyed is located within the Kaibab Paiute Indian Reservation. The terrain is nearly level to mountainous.</p> <p>The elevation ranges from 4900 to 6500 feet above sea level. The soil is mostly sandy with some sandstone outcrops. The vegetation consists of native grasses, Mormon Tea, sage, pine and juniper.</p>

**T. 40 N., R. 5 W., Gila and Salt River Meridian, Arizona**

CHAINS

Arizona State Highway No. 389 traverses the township. There are some trail roads throughout the area. The township is used primarily for grazing. There is no evidence of mining activity in the area.

The mean magnetic declination of  $12 \frac{1}{4}^{\circ}$  E., was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2005 for the date of survey.

---

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

**FIELD ASSISTANTS**

NAMES	CAPACITY
Lonnie Bitsoi	Land Surveyor
W. William Foster	Land Surveyor
Michelle M. Meece	Land Surveyor-in-Training
Nathan F. Allen	Surveying Technician
Chad E. Buescher	Surveying Technician
Nelson Kinsel	Surveying Technician
Robert J. Lyle	Surveying Technician
Gene L. Staples	Surveying Technician
Leon F. Stroman	Surveying Technician
Charles E. Wright	Surveying Technician

CERTIFICATE OF SURVEY

I, Joe R. Salazar, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 14th day of June, 2005, I have dependently resurveyed a portion of the subdivisional lines and surveyed a portion of the subdivisional lines, T. 40 N., R. 5 W., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

5/15/2006  
(Date)

Joe R. Salazar  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines and a survey of a portion of the subdivisional lines, T. 40 N., R. 5 W., Gila and Salt River Meridian, in the State of Arizona, executed by Joe R. Salazar, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

7-5-06  
(Date)

Daniel L. Mosby  
Acting (Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 40 N., R. 5 W., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~