

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF
THE SEVENTH AUXILIARY GUIDE MERIDIAN EAST (WEST BOUNDARY),

THE SOUTH AND EAST BOUNDARIES,

A PORTION OF THE SUBDIVISIONAL LINES,

THE SUBDIVISION OF CERTAIN SECTIONS,

AND

METES-AND-BOUNDS SURVEYS,

TOWNSHIP 22 NORTH, RANGE 29 EAST,

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA.

EXECUTED BY

ADRIEN J. RODRIGUEZ, Cadastral Surveyor

Under Special Instructions dated January 16, 2004, approved January 16, 2004, and Supplemental Special Instructions dated February 8, 2005, approved February 8, 2005, which provided for the surveys included under Group No. 921, and assignment instructions dated January 16, 2004.

Survey commenced January 26, 2004

Survey completed March 28, 2005

INDEX DIAGRAM

TOWNSHIP 22 NORTH RANGE 29 EAST
 GILA AND SALT RIVER MERIDIAN, ARIZONA

8 6 72	5 64	4 55	3 46	2 35	1 21
72	71	64	54	45	34
7 7 70	8 63	9 54	10 44	11 33	12 20
18	70	62	53	44	33
	17 62	16 52	15 43	14 32	13 19
6 19 69	69	61	52	42	31
	20 60	21 51	22 41	23 30	24 18
68	68	59	50	40	27
5 30 67	29 58	28 49	27 38	26 25	25 16
66	65	57	48	37	23
4 31 65	32 55	33 47	34 35	35 22	36 16
15	14	13	11	10	9

Subdivision of Certain Sections Pages 73-115
 M. & B. Survey of Right of Way of Interstate 40 .. Pages 115-142
 M. & B. Survey of Right of Way of Burlington Northern
 Santa Fe Railroad..... Pages 142-175
 M. & B. Survey of Proposed Lease Tract, Sec. 25 .. Pages 175-180

T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the Seventh Auxiliary Guide Meridian East (West Boundary), the south and east boundaries, a portion of the subdivisional lines, the subdivision of certain sections and metes-and-bounds surveys, Township 22 North, Range 29 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

W.R. Fitzgerald surveyed the Seventh Auxiliary Guide Meridian East (West Boundary), the south, east and north boundaries and the subdivisional lines in 1882. Sidney E. Blout dependently resurveyed the north boundary in 1920. Stephen J. Malloy dependently resurveyed a portion of the east boundary in 1987-1993. William P. Carpender, Stephen J. Malloy and Kenneth W. Bays reestablished certain corners in 1987-1993. Joe R. Salazar dependently resurveyed a portion of the Seventh Auxiliary Guide Meridian East (West Boundary) and a portion of the subdivisional lines and reestablished certain corners in 1993.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated January 16, 2004, for Group No. 921, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5800 and 5700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) FLAGSTAFF 1 CORS ARP, AZTEC CORS ARP and ALBUQUERQUE 1 CORS ARP. The NAD 83 (CORS96) (EPOCH: 2002), geographic position of the southeast corner of the township, is as follows:

Latitude: 35°15'17.84" N. Longitude: 109°12'38.58" W.

The mean magnetic declination is 11° E.

**Dependant Resurvey of a Portion of the
Seventh Auxiliary Guide Meridian East (West Boundary),
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

Restoring the survey executed by
W.R. Fitzgerald, in 1882

Beginning at the cor. of Tps. 21 and 22 N., Rs. 28 and 29 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with an accessory mound of stone, 3 ft. base, 2 ft. high, to the S., with brass cap mkd. T22N R28E R29E S36 S31 S1 S6 T21N 1991, from which the 1991 bearing trees

A juniper, 22 ins. diam., bears N. 58 1/2° E., 1.305 chs. dist., with scribe marks T22N R29E S31 BT visible on partially open blaze.

A multiple stemmed juniper stump, 40 ins. diam., bears S. 77 3/4° E., 2.10 chs. dist., with no marks visible. (Record: S. 77 1/2° E., 2.05 chs. dist.)

A juniper, 6 ins. diam., bears S. 38 1/2° W., 1.445 chs. dist., with scribe marks T21N R28E S1 BT visible on partially open blaze.

A steel fence post is set alongside the cor.

Add the marks 2004 to the brass cap.

N. 0°03' E., bet. secs. 31 and 36, on the W. bdy. of the Tp..

Over sandy land covered with juniper, pine and sage.

38.94

Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N
R 28 E R 29 E
1/4
S 36 | S 31

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located 30 lks. S. of a trail road, bears S. 70° E. and N. 70° W.

Dependant Resurvey of a Portion of the
Seventh Auxiliary Guide Meridian East (West Boundary),
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

77.88

Point accepted for the cor. of secs. 25, 30, 31 and 36, at the intersection of barbed wire fences, extending N. and E. This position is locally recognized as the cor. and is accepted as the best available evidence of the orig. cor. position.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T 22 N	
R 28 E	R 29 E
S 25	S 30
S 36	S 31

2004

Set a steel fence post alongside the stainless steel post.

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

N. 0°02' W., bet. secs. 25 and 30.

Over rolling land covered with juniper, pine and sage.

41.04

Point accepted for the 1/4 sec. cor. of secs. 25 and 30, at the intersection of barbed wire fences extending N., E. and S. This position is locally recognized as the cor. and is accepted as the best available evidence of the orig. cor. position.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N	
R 28 E	R 29 E
1/4	
S 25	S 30

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

N. 0°01' W., beginning new measurement.

**Dependant Resurvey of a Portion of the
Seventh Auxiliary Guide Meridian East (West Boundary),
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.09	<p>The cor. of secs. 19, 24, 25 and 30, monumented with a stainless steel post, firmly set, projecting 4 ins. above ground, with brass cap mkd. T22N R28E R29E S24 S19 S25 S30 1992, from which the 1992 bearing trees</p> <p>A forked juniper, 12 ins. diam., bears N. 36° E., 2.14 chs. dist., with scribe marks T22N R29E S19 BT visible on partially open blaze.</p> <p>A juniper, 7 ins. diam., bears S. 47 1/4° E., 1.70 chs. dist., with scribe marks T22N R29E S30 BT visible on partially open blaze.</p> <p>A juniper, 10 ins. diam., bears S. 4 1/2° W., 2.38 chs. dist., with scribe marks T22N R28E S25 BT visible on partially open blaze.</p> <p>A partially sawed forked juniper, 8 ins. diam., bears N. 60 1/4° W., 1.115 chs. dist., with partial scribe marks 2N R28E S24 BT visible on partially open blaze.</p> <p>Add the marks 2004 to the brass cap.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located at intersection of barbed wire fences, extending N., E. and S.</p> <hr/> <p>N. 1°31' W., bet. secs. 19 and 24.</p> <p>Over rolling land covered with juniper, pine and sage.</p>
40.28	<p>Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 28 E R 29 E 1/4 S 24 S 19</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.56	<p>The cor. of secs. 13, 18, 19 and 24, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. T22N R28E R29E S13 S18 S24 S19 1993, from which the 1993 bearing tree</p>

**Dependant Resurvey of a Portion of the
Seventh Auxiliary Guide Meridian East (West Boundary),
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

A juniper, 12 ins. diam., bears N. 24 1/4° W., 62 lks. dist., with scribe marks T22N R28E S13 BT visible on partially open blaze.

Add the marks 2004 to the brass cap.

A steel fence post is set alongside the cor.

Cor. is located 3 lks. W. of the intersetion of barbed wire fences extending N. and E.

From the cor. of secs. 7, 12, 13 and 18, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T22N R28E R29E S12 S7 S13 S18 1993, from which the 1993 bearing tree

A forked juniper, 9 ins. diam., bears N. 0 1/2° E., 45.5 lks. dist., with scribe marks T22N R29E S7 BT visible on partially open blaze.

Add the marks 2004 to the brass cap.

N. 0°07' E., bet. secs. 7 and 12.

Over rolling land covered with juniper, pine and sage.

39.71 Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 22 N
R 28 E R 29 E
1/4
S 12 | S 7

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

79.42 Point for the cor. of secs. 1, 6, 7 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependant Resurvey of a Portion of the
Seventh Auxiliary Guide Meridian East (West Boundary),
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 22 N	
R 28 E	R 29 E
S 1	S 6
S 12	S 7

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

N. 0°07' E., bet. secs. 1 and 6.

Over rolling land covered with juniper, pine and sage.

39.71 Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N	
R 28 E	R 29 E
1/4	
S 1	S 6

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

79.42 The cor. of Tps. 22 and 23 N., Rs. 28 and 29 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above ground, in a collar of stone, with brass cap mkd. T23N R28E R29E S36 S31 S1 S6 T22N 1993 2002 1920. Add the marks 2004 to the brass cap.

**Dependent Resurvey of the South Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

Restoring the survey executed by
W.R. Fitzgerald, in 1882

From the cor. of Tps. 21 and 22 N., Rs. 29 and 30 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set projecting 5 ins. above ground, with brass cap mkd. T22N R29E R30E S36 S31 S1 S6 T21N 1993. Add the marks 2004 to the brass cap.

**Dependant Resurvey of the South Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS					
37.39	<p>Cor. is located at the intersection of barbed wire fences, extending E. and S.</p> <p>S. 86°59' W., bet. secs. 1 and 36, on the S. bdy. of the Tp.</p> <p>Over rolling sandy land covered with juniper and sage.</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 29 E</p> <p>S 36</p> <p>1/4 ———</p> <p>S 1</p> <p>T 21 N</p> <p>2004</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>				
74.78	<p>Point accepted for the cor. of secs. 1, 2, 35 and 36, at the intersection of barbed wire fences, extending N. and W. This position is locally recognized as the cor. and is accepted as the best available evidence of the orig. cor. position, from which bearing trees of unknown origin</p> <ul style="list-style-type: none"> A juniper, 36 ins. diam., bears N. 47 3/4° E., 32 lks. dist., with a healed blaze. A forked juniper, 14 ins. diam., bears S. 78 1/4° E., 90 lks. dist., with a healed blaze. A forked juniper, 36 ins. diam., bears N. 65 3/4° W., 69 lks. dist., with a healed blaze. <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 29 E</p> <table border="1" style="margin: auto;"> <tr> <td>S 35</td> <td>S 36</td> </tr> <tr> <td>S 2</td> <td>S 1</td> </tr> </table> <p>T 21 N</p> <p>2004</p> </div>	S 35	S 36	S 2	S 1
S 35	S 36				
S 2	S 1				

**Dependant Resurvey of the South Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>N. 89°56' W., bet. secs. 2 and 35.</p> <p>Over rolling sandy land covered with sage.</p> <p>40.05 The 1/4 sec. cor. of secs. 2 and 35, monumented with a wood post, 14 x 6 x 2 ins., loosely set, projecting 12 ins. above ground, alongside an ancient barbed wire fence, extending E. and W. This position is locally recognized as the cor. and is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 35 1/4 ——— S 2 T 21 N</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the wood post alongside the stainless steel post.</p> <hr/> <p>N. 89°52' W., beginning new measurement.</p>
<p>40.73</p>	<p>Point accepted for the cor. of secs. 2, 3, 34 and 35, at the intersection of barbed wire fences, extending N. and E. This position is locally recognized as the cor. and is accepted as the best available evidence of the orig. cor. position, from which a bearing tree of unknown origin</p> <p style="padding-left: 40px;">A forked juniper, 12 ins. diam., bears S. 10 3/4° E., 62 lks. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependant Resurvey of the South Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

T 22 N R 29 E
S 34 | S 35
S 3 | S 2
T 21 N

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

N. 89°57' W., bet. secs. 3 and 34.

Over rolling sandy land covered with juniper and sage.

19.64 Point for the E. 1/16 sec. cor. of secs. 3 and 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
S 34
E 1/16 ———
S 3
T 21 N

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

39.28 The 1/4 sec. cor. of secs. 3 and 34, monumented with a wood post, 7 ft. long, 6 ins. sq., firmly set, projecting 4 1/2 ft. above ground. This position is locally recognized as the cor. and is accepted as the best available evidence of the orig. cor. position.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

**Dependant Resurvey of the South Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 22 N R 29 E
S 34
1/4 ———
S 3
T 21 N

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Bury the wood post alongside the stainless steel post.

Set steel fence post alongside the stainless steel post.

N. 89°57' W., beginning new measurement.

40.02

The cor. of secs. 3, 4, 33 and 34, monumented with a wood post, 3 ft. long, 3 ins. sq., firmly set, projecting 18 ins. above ground. This position is locally recognized as the cor. and is accepted as the best available evidence of the orig. cor. position, from which bearing trees of unknown origin

A forked juniper, 21 ins. diam., bears S. 33° E., 48 lks. dist., with a healed blaze.

A forked juniper, 24 ins. diam., bears S. 79 1/4° W., 1.07 chs. dist., with a healed blaze.

A forked juniper, 16 ins. diam., bears N. 19 1/4° W., 19 lks. dist., with a healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
S 33 | S 34
S 4 | S 3
T 21 N

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Bury the wood post alongside the stainless steel post.

Dependant Resurvey of the South Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>S. 89°34' W., bet. secs. 4 and 33.</p> <p>Over rolling sandy land covered with juniper and sage.</p>
40.10	<p>True point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor. True point falls on an eroding sandy slope, where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for the witness cor. to the 1/4 sec. cor. of secs. 4 and 33, bears N. 45°00' E., 2 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC</p> <p>T 22 N R 29 E</p> <p>S 33</p> <p>1/4 ———</p> <p>S 4</p> <p>↙ T 21 N</p> <p>2004</p> </div>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
60.07	<p>Point for AP16, sec. 33, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.</p>
80.20	<p>The cor. of secs. 4, 5, 32 and 33, monumented with a wood post, 24 ins. long, 5 ins. sq., firmly set, projecting 10 ins. above ground. This position is locally recognized as the cor. and is accepted as the best available evidence of the orig. cor. position. Two iron pipes, 1 in. diam., 19 ins. long, are firmly set alongside the wood post, projecting 1 in. above ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>

**Dependant Resurvey of the South Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p style="text-align: center;">T 22 N R 29 E S 32 S 33 S 5 S 4 T 21 N</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the wood post and the iron pipes alongside the stainless steel post.</p> <hr/> <p>S. 89°22' W., bet. secs. 5 and 32.</p> <p>Over rolling sandy land covered with juniper, pine and sage</p>
7.02	Point for AP10, sec. 32, at intersection with the right-of-way of Interstate 40, hereinafter described.
17.52	Point for AP9, sec. 32, at intersection with the right-of-way of Interstate 40, hereinafter described.
39.98	Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 32 1/4 ——— S 5 T 21 N</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.96	<p>The cor. of secs. 5, 6, 31 and 32, monumented with a sandstone, 26 x 10 x 6 ins., firmly set, projecting 11 ins. above ground, mkd. with 5 notches on E. face and 1 notch on the W.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependant Resurvey of the South Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 22 N R 29 E
S 31 | S 32

S 6 | S 5
T 21 N

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Bury the orig. sandstone alongside the stainless steel post.

N. 89°03' W., bet. secs. 6 and 31.

Over rolling sandy land covered with juniper, pine and sage.

38.50 Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
S 31
1/4 ———
S 6
T 21 N

2004

Raise a mound of stone, 2 ft. base, 1 ft. high, N. of cor.

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

76.04 The cor. of Tps. 21 and 22 N., Rs. 28 and 29 E., hereinbefore described.

**Dependent Resurvey of the East Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

Restoring the surveys executed by
W.R. Fitzgerald, in 1882 and
Stephen J. Malloy, in 1987-1993

From the cor. of Tps. 21 and 22 N., Rs. 29 and 30 E., hereinbefore described.

**Dependant Resurvey of the East Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>N. 0°02' W., bet. secs. 31 and 36, on the E. bdy. of the Tp.</p> <p>Over sandy land covered with juniper, pine and sage.</p>								
40.15	<p>The 1/4 sec. cor. of secs. 31 and 36, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T22N R29E R30E 1/4 S36 S31 1993.</p> <p>Add the marks 2004 to the brass cap.</p> <p>A steel fence post is located alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/>								
40.19	<p>N. 0°01' W., beginning new measurement.</p> <p>The cor. of secs. 25, 30, 31 and 36, monumented with a wood post, 3 ft. long, 4 ins. sq., firmly set, projecting 28 ins. above ground, with illegible marks. This position is locally recognized as the cor. and is accepted as the best available evidence of the orig. cor. position. A rebar, 1/2 in. diam., 18 ins. long, is firmly set alongside the wood post, projecting 5 ins. above ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="border: none;">T 22 N</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">R 29 E</td> <td style="padding: 2px 5px;">R 30 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 25</td> <td style="padding: 2px 5px;">S 30</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 36</td> <td style="padding: 2px 5px;">S 31</td> </tr> </table> </div> <p style="text-align: center; margin: 5px 0;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar inside the stainless steel post.</p> <p>Bury the wood post alongside the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°17' E., bet. secs. 25 and 30.</p> <p>Over rolling land covered with juniper, pine and sage.</p>	T 22 N		R 29 E	R 30 E	S 25	S 30	S 36	S 31
T 22 N									
R 29 E	R 30 E								
S 25	S 30								
S 36	S 31								

**Dependant Resurvey of the East Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS											
21.78	Point for AP42, sec. 25, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.										
27.88	Point for AP27, sec. 25, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.										
39.96	Point accepted for the 1/4 sec. cor. of secs. 25 and 30, at the intersection of barbed wire fences extending E., S. an N. This position is locally recognized as the cor. and is accepted as the best available evidence of the orig. cor. position.										
	At the corner point										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table border="0"> <tr><td colspan="2">T 22 N</td></tr> <tr><td>R 29 E</td><td>R 30 E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td>S 25</td><td>S 30</td></tr> </table>	T 22 N		R 29 E	R 30 E	1/4		S 25	S 30		
T 22 N											
R 29 E	R 30 E										
1/4											
S 25	S 30										
	2004										
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.										
	N. 1°26' E., beginning new measurement.										
24.84	Point for AP26, sec. 25, at intersection with the right-of-way of Interstate 40, hereinafter described.										
38.71	Point for the cor. of secs. 19, 24, 25 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.										
	<table border="0"> <tr><td colspan="2">T 22 N</td></tr> <tr><td>R 29 E</td><td>R 30 E</td></tr> <tr><td>S 24</td><td>S 19</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td>S 25</td><td>S 30</td></tr> </table>	T 22 N		R 29 E	R 30 E	S 24	S 19	-----		S 25	S 30
T 22 N											
R 29 E	R 30 E										
S 24	S 19										

S 25	S 30										
	2004										
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.										
	Set a steel fence post alongside the stainless steel post.										

**Dependant Resurvey of the East Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Cor. is located 40 lks. S. of paved road, 30 ft. wide, bears S. 50° E. and N. 50° W., and 45 lks. N. of Interstate 40 west bound exit lane, 20 ft. wide, bears S. 50° E. and N. 50° W.</p>
	<p>From this cor. point, a local monument of unknown origin, bears S. 13°45' W., 4.39 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set flush with ground.</p>
	<p>N. 1°26' E., bet. secs. 19 and 24.</p>
	<p>Over rolling land covered with juniper, pine and sage.</p>
<p>1.79</p>	<p>Point for AP1, sec. 24, at intersection with the right-of-way of Interstate 40, hereinafter described.</p>
<p>19.355</p>	<p>Point for the S. 1/16 sec. cor. of secs. 19 and 24.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 29 E R 30 E S 1/16 S 24 S 19</p>
	<p style="text-align: center;">2004</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
<p>38.71</p>	<p>Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 29 E R 30 E 1/4 S 24 S 19</p>
	<p style="text-align: center;">2004</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
<p>77.42</p>	<p>Point for the cor. of secs. 13, 18, 19 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>

Dependant Resurvey of the East Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

T 22 N	
R 29 E	R 30 E
S 13	S 18
S 24	S 19

2004

from which

A sandstone boulder, 7 x 5 x 2 ft., 5 ft. above ground,
bears N. 50 3/4° W., 96 lks. dist., mkd. B + O.

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Cor. is located on N. edge of a dry wash, 20 ft. wide, 10 ft.
deep, drains S. 60° W.

N. 1°26' E., bet. secs. 13 and 18.

Over rolling land covered with juniper, pine and sage.

38.71 Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate
dist.; there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 22 N	
R 29 E	R 30 E
1/4	
S 13	S 18

2004

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Set a steel fence post alongside the stainless steel post.

Cor. is located in the middle of a corn field.

77.42 The cor. of secs. 7, 12, 13 and 18, monumented with a sandstone,
16 x 10 x 6 ins., loosely set on its side, mkd. with 4 notches
on the S. face, from which an orig. bearing tree

A rotted juniper stump, 15 ins. diam., bears
N. 57 3/4° W., 96 lks. dist., no marks visible.
(Record: N. 55° W., 94 lks. dist.)

from which a bearing tree of unknown origin

**Dependant Resurvey of the East Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

A forked juniper, 15 ins. diam., bears S. 37 1/4° W.,
45 lks. dist., with a healed blaze on SW face.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T 22 N	
R 29 E	R 30 E
S 12	S 7
S 13	S 18

2004

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Bury orig. stone alongside the stainless steel post.

N. 0°02' W., bet. secs. 7 and 12.

Over rolling land covered with juniper, pine and sage.

40.46

The 1/4 sec. cor. of secs. 7 and 12, monumented with a
sandstone, 18 x 8 x 4 ins., loosely set, lying on its side, mkd.
1/4 on top.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
28 ins. in the ground, with brass cap mkd.

T 22 N	
R 29 E	R 30 E
1/4	
S 12	S 7

2004

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Bury the orig. stone alongside the stainless steel post.

Cor. is located 30 lks. W. of a drain, 10 ft. wide, 10 ft. deep,
drains S. 50° W.

N. 0°45' W., beginning new measurement.

Dependant Resurvey of the East Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

40.77

The cor. of secs. 1, 6, 7 and 12, monumented with a sandstone, 22 x 12 x 4 ins., loosely set lying on its side, mkd. with 5 notches on S. face and 1 notch on N. face.

At the corner point

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in solid rock, with top mkd.

T 22 N	
R 29 E	R 30 E
S 1	S 6
S 12	S 7

2004

Deposit a magnet at the base of the brass tablet.

Remove orig. sandstone from area, impracticable to bury.

Cor. is located on sandstone rock face, 20 x 20 x 10 ft. high.

N. 0°53' E., bet. secs. 1 and 6.

Over mountainous land covered with juniper, pine and sage.

39.51

The 1/4 sec. cor. of secs. 1 and 6, monumented with a sandstone, 24 x 11 x 6 ins., loosely set, lying on its side, mkd. 1/4 on top.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to bedrock, supported in a mound of stone, 6 ft. base, to top, with brass cap mkd.

T 22 N	
R 29 E	R 30 E
1/4	
S 1	S 6

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Deposit orig. stone in mound of stone.

N. 0°19' W., beginning new measurement.

**Dependant Resurvey of the East Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

39.70

The cor. of Tps. 22 and 23 N., Rs. 29 and 30 E., monumented with a sandstone, firmly set, 24 x 10 x 8 ins., projecting 10 ins. above ground, mkd. T23N R30E on top, with 6 notches on N., E., S. and W. faces.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 23 N	
R 29 E	R 30 E
S 36	S 31
S 1	S 6
T 22 N	

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Deposit orig. stone in mound of stone.

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 W., Gila and Salt River Meridian, Arizona**

Restoring the survey executed by W. R. Fitzgerald, in 1882
and the resurvey by Joe R. Salazar, in 1993

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.

N. 0°04' W., bet. secs. 35 and 36.

Over rolling land covered with juniper, pine and sage.

39.82

Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 22 N R 29 E	
1/4	
S 35	S 36

2004

Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p style="text-align: center;">T 22 N R 29 E S 25 E 1/16 ——— S 36</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar inside stainless steel post.</p> <p>Bury the wood post alongside the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
<p>39.98</p>	<p>The 1/4 sec. cor. of secs. 25 and 36, monumented with a wood post, 36 x 5 x 4 ins., firmly set, 24 ins. above ground, with illegible marks. A rebar, 5/8 in. diam., 18 ins. long, firmly set, flush with the ground, is set alongside the wood post. This position is locally recognized as the cor. and is accepted as the best available evidence of the orig. cor. position</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 25 1/4 ——— S 36</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar inside the stainless steel post.</p> <p>Bury the wood post alongside the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
<p>8.765</p>	<p style="text-align: center;">—————</p> <p>S. 82°15' W., beginning new measurement.</p> <p>Point for the E-W 1/64 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p style="text-align: center;">T 22 N R 29 E S 25 E-W 1/64 S 36</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
17.53	<p>Point for the W. 1/16 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 29 E S 25 W 1/16 ——— S 36</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
35.06	<p>The cor. of secs. 25, 26, 35 and 36.</p> <hr/>
	<p>N. 0°08' W., bet. secs. 25 and 26.</p> <p>Over rolling land covered with juniper, pine and sage.</p>
17.73	<p>Point for AP35, sec. 25, identical with AP30, sec. 26, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.</p>
19.885	<p>True point for the S. 1/16 sec. cor. of secs. 25 and 26, falls in the center of the Burlington Northern Santa Fe railroad tracks, where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for the witness cor. to the S. 1/16 sec. cor. of secs. 25 and 26, bears N. 63°16' W., 4.68 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	WC T 22 N R 29 E S 1/16 S 26 S 25  2004
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post alongside the stainless steel post.
	Cor. is located 35 lks. N. of a barbed wire fence, bears E. and W.
20.80	Point for AP15, sec. 26, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.
23.87	Point for AP34, sec. 25, identical with AP14, sec. 26, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.
39.77	The 1/4 sec. cor. of secs. 25 and 26, monumented with a sandstone, 20 x 11 x 4 ins., firmly set, projecting 8 ins. above ground, mkd. IA on E. face and 1/4 on W. face. A rebar with a red plastic cap, 5/8 in. diam., 20 ins. long, is firmly set alongside the stone, flush with the ground. This position is locally recognized as the cor. and is accepted as the best available evidence of the orig. cor. position.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 22 N R 29 E 1/4 S 26 S 25 2004
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Deposit the rebar inside the stainless steel post.
	Bury the stone alongside the stainless steel post.
	Set a steel fence post alongside the stainless steel post.
	<hr style="width: 20%; margin: 10px auto;"/> N. 3°21' W., beginning new measurement.

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
19.98	<p>Point for the N. 1/16 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E N 1/16 S 26 S 25</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
36.28	<p>Point for AP8, sec. 25, identical with AP13, sec. 26, at intersection with the right-of-way of Interstate 40, hereinafter described.</p>
39.96	<p>Point for the cor. of secs. 23, 24, 25 and 26, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 23 S 24 ----- S 26 S 25</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located 30 lks. N. of the N. edge of pavement of the W. bound lane of Interstate 40, bears E. and W.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 87°20' W., bet. secs. 24 and 25.</p> <p>Over level land covered with sage.</p>

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
10.83	Point for AP13, sec. 24, identical with AP1, sec. 25, at intersection with the right-of-way of Interstate 40, hereinafter described.
19.60	<p>Point for the E. 1/16 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 29 E S 24 E 1/16 ——— S 25</p>
	<p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
29.40	<p>Point for the W-E 1/64 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 29 E S 24 W-E 1/64 S 25</p>
	<p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
39.20	<p>Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 29 E S 24 1/4 ——— S 25</p>
	<p style="text-align: center;">2004</p>

Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p> <p>40.29</p> <p>49.00</p> <p>58.80</p>	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located 60 lks. N. of paved road, 20 ft. wide, bears E. and W.</p> <p>Point for AP14, sec. 24, identical with AP7, sec. 25, at intersection with the right-of-way of Interstate 40, hereinafter described.</p> <p>Point for the E-W 1/64 sec. cor. of secs. 24 and 25, falls in the center line of an asphalt-surfaced road, 25 ft. wide, bears E. and W.</p> <p>Set a railroad spike, flush with the surface of asphalt.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 45°00' E., 66 ft. dist., with brass cap mkd. T22N R29E 1/64 S24 RM 66 FT. TO COR. 2004 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post alongside the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 45°00' W., 66 ft. dist., with brass cap mkd. T22N R29E 1/64 S24 RM 66 FT. TO COR. 2004 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post alongside the stainless steel post.</p> <p>Point for the W. 1/16 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 29 E</p> <p style="padding-left: 40px;">S 24</p> <p style="padding-left: 40px;">W 1/16 ———</p> <p style="padding-left: 40px;">S 25</p> <p>2004</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
--	---

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located 40 lks. S. of a paved road, 25 ft. wide, bears E. and W.</p>
78.40	<p>The cor. of secs. 23, 24, 25 and 26.</p> <hr/> <p>N. 1°20' E., bet. secs. 23 and 24.</p> <p>Over rolling land covered with juniper, pine and sage.</p>
1.81	<p>Point for AP17, sec. 24, identical with AP1, sec. 23, at intersection with the right-of-way of Interstate 40, hereinafter described.</p>
19.95	<p>Point for the S. 1/16 sec. cor. of secs. 23 and 24.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 29 E S 1/16 S 23 S 24</p>
	<p style="text-align: center;">2004</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Set a steel fence post alongside the stainless steel post.</p>
39.90	<p>Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 29 E 1/4 S 23 S 24</p>
	<p style="text-align: center;">2004</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
59.85	<p>Cor. is located 40 lks. N. of a dirt road, 10 ft. wide, bears N. 70° E. and S. 70° W.</p> <p>Point for the N. 1/16 sec. cor. of secs. 23 and 24.</p>

Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
N 1/16
S 23 | S 24

2004

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Set a steel fence post alongside the stainless steel post.

79.80

Point for the cor. of secs. 13, 14, 23 and 24, at proportionate
dist.; there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
S 14 | S 13
S 23 | S 24

2004

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the
Tp., hereinbefore described.

S. 89°05' W., bet. secs. 13 and 24.

Over rolling land covered with juniper, pine and sage.

39.18

Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate
dist.; there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
S 13
1/4 ———
S 24

2004

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
58.77	<p>Point for the W. 1/16 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 13 W 1/16 ——— S 24</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
78.36	<p>The cor. of secs. 13, 14, 23 and 24.</p> <hr/> <p>N. 0°23' E., bet. secs. 13 and 14.</p> <p>Over mountainous land covered with juniper, pine and sage.</p>
39.89	<p>Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E 1/4 S 14 S 13</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.78	<p>Point accepted for the cor. of secs. 11, 12, 13 and 14, at the intersection of barbed wire fences, extending N. and W. This position is locally recognized as the cor. and is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>

Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

T 22 N	R 29 E
S 11	S 12
S 14	S 13

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

Cor. is located 2 lks. N. of a trail road, bears S. 80° E. and S. 80° W.

From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.

N. 89°12' W., bet. secs. 12 and 13.

Over mountainous land covered with juniper, pine and sage.

39.87 Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T 22 N	R 29 E
S 12	
1/4	_____
S 13	

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

79.74 The cor. of secs. 11, 12, 13 and 14.

N. 0°07' E., bet. secs. 11 and 12.

Over rolling and mountainous land covered with juniper, pine and sage.

39.77 Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor. position.

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E 1/4 S 11 S 12</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 15 lks. E. of a barbed wire fence, bears N. and S.</p>
79.54	<p>Point for the cor. of secs. 1, 2, 11 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 2 S 1 S 11 S 12</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
39.52	<hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°35' W., bet. secs. 1 and 12.</p> <p>Over mountainous land covered with juniper, pine and sage.</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 1 1/4 ——— S 12</p> <p style="text-align: center;">2004</p>

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.03	<p>The cor. of secs. 1, 2, 11 and 12.</p> <hr/>
	<p>N. 0°13' W., bet. secs. 1 and 2.</p> <p>Over rolling and mountainous land covered with juniper, pine and sage.</p>
39.77	<p>Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 22 N R 29 E 1/4 S 2 S 1 2004</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.70	<p>The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 26 ins. above ground, in a mound of stone, 3 ft. base, 20 ins. high, mkd. T23N R29E S35 S36 S2 S1 T22N 1920, from which the 1920 bearing trees</p> <p>A forked juniper, 12 ins. diam., bears N. 55 1/4° E., 1.38 chs. dist., with scribe marks T23N R29E S36 BT visible on partially open blaze.</p> <p>A forked juniper, 10 ins. diam., bears S. 30° W., 68 lks. dist., with a healed blaze.</p> <p>A forked juniper, 12 ins. diam., bears N. 39 3/4° W., 59 lks. dist., with a healed blaze.</p> <p>Add the marks 2004 to the brass cap.</p> <hr/>
	<p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°36' E., bet. secs. 34 and 35.</p> <p>Over rolling land covered with juniper, pine and sage.</p>

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.03	<p>Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E 1/4 S 34 S 35 2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
60.045	<p>Point for the N. 1/16 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E N 1/16 S 34 S 35 2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
77.16	<p>Point for AP15, sec. 34, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.</p>
80.06	<p>True point for the cor. of secs. 26, 27, 34 and 35, at proportionate dist.; there is no remaining evidence of the orig. cor. True point falls on the eroding N. bank of a railroad grade, where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for the witness cor. to the cor. of secs. 26, 27, 34 and 35, bears N. 45°00' W., 2.00 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

WC
T 22 N R 29 E
S 27 | S 26
S 34 | S 35

2004



Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

From the cor. of secs. 25, 26, 35 and 36.

N. 89°36' W., bet. secs. 26 and 35.

Over rolling land covered with juniper, pine and sage.

19.965

True point for the E. 1/16 sec. cor. of secs. 26 and 35, falls on the left bank of the Rio Puerco River, 200 ft. wide, drains N. 70° W., where it is impracticable to establish a permanent monument.

From this true point, the point selected for the witness cor. to the E. 1/16 sec. cor. of secs. 26 and 35, bears S. 45°00' W., 3 chs. dist.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

WC
T 22 N R 29 E
S 26
E 1/16 ———
S 35

2004



Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

39.93

Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in solid rock, with top mkd.

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>T 22 N R 29 E S 26 1/4 ——— S 35</p> <p>2004</p> <p>Deposit a magnet at the base of the brass tablet.</p>
59.895	<p>Point for the W. 1/16 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p>T 22 N R 29 E S 26 W 1/16 ——— S 35</p> <p>2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
73.81	<p>Point for AP23, sec. 26, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.</p>
79.86	<p>The cor. of secs. 26, 27, 34 and 35.</p> <hr/> <p>N. 0°13' W., bet. secs. 26 and 27.</p> <p>Over rolling land covered with juniper, pine and sage.</p>
2.14	<p>Point for AP22, sec. 26, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.</p>
5.10	<p>Point for AP20, sec. 26, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.</p>
8.17	<p>Point for AP19, sec. 26, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.</p>
20.01	<p>Point for the S. 1/16 sec. cor. of secs. 26 and 27, occupied with a sandstone, 10 x 4 ins., firmly set, projecting 12 ins. above ground, in a collar of stone.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, in a supporting mound of stone, 8 ft. base, to top, with brass cap mkd.

T 22 N R 29 E	
S 22	S 23
S 27	S 26

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Deposit rebar inside the stainless steel post.

Set a steel fence post alongside the stainless steel post.

From the cor. of secs. 23, 24, 25 and 26.

S. 89°53' W., bet. secs. 23 and 26.

Over level land covered with scattered juniper, pine and sage.

19.42

Point for the E. 1/16 sec. cor. of secs. 23 and 26.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 50 ins. in the ground, with brass cap mkd.

T 22 N R 29 E	
S 23	
E 1/16	_____
S 26	

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located 40 lks. N. of the center line of the W. bound lane of Interstate 40, 30 ft. wide, bears E. and W.

38.84

Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.

Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p style="text-align: center;">T 22 N R 29 E S 23 1/4 ——— S 26</p> <p style="text-align: center;">2004</p> <p>from which</p> <p style="padding-left: 40px;">An Arizona Department of Transportation bench mark, bears N. 40°57' W., 16 lks. dist., monumented with a brass tablet, 3 ins. diam., set in a concrete retaining wall, 12 x 3 x 1 ft., 3 ft. high, with brass cap mkd. ELEV 6001.75 + STA 2196+13 2-17-1931.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located 60 lks. N. of west bound lane of Interstate 40 and 60 lks. S. of the center line of a paved frontage road, 20 ft. wide, bears E. and W. A fence parallels the frontage road on the S. side.</p> <p>47.74 Point for AP5, sec. 23, at intersection with the right-of-way of Interstate 40, hereinafter described.</p> <p>58.26 Point for the W. 1/16 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 23 W 1/16 ——— S 26</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>77.68 The cor. of secs. 22, 23, 26 and 27.</p> <hr/> <p>N. 0°10' E., bet. secs. 22 and 23.</p> <p>Over rolling and mountainous land covered with juniper, pine and sage.</p>
---------------	--

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
20.59	<p>Point for the S. 1/16 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 1/16 S 22 S 23</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
41.18	<p>The 1/4 sec. cor. of secs. 22 and 23, monumented with a sandstone, 20 x 14 x 4 ins., loosely set, lying on top of the ground, in a scattered mound of stone, mkd. 1/4 on top.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E 1/4 S 22 S 23</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
40.18	<p>Bury orig. stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>N. 1°55' E., beginning new measurement.</p> <p>The cor. of secs. 14, 15, 22 and 23, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T22N R29E S15 S14 S22 S23 1993.</p> <p>Add the marks 2004 to the brass cap.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 88°59' W., bet. secs. 14 and 23.</p>

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.03	<p>Over mountainous land covered with juniper, pine and sage.</p> <p>Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 14 1/4 ——— S 23</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
78.06	<p>The cor. of secs. 14, 15, 22 and 23.</p> <hr/> <p>N. 0°41' W., bet. secs. 14 and 15.</p>
39.27	<p>Over rolling land covered with juniper, pine and sage.</p> <p>Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate dist.; occupied with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 6 ins. above ground; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E 1/4 S 15 S 14</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit rebar inside the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
78.54	<p>The cor. of secs. 10, 11, 14 and 15, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush with the ground, with brass cap mkd. T22N R29E S10 S11 S15 S14 1993.</p> <p>Add the marks 2004 to the brass cap.</p>

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Cor. is located at intersection of barbed wire fences, extending N., E. and W.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 89°50' W., bet. secs. 11 and 14.</p> <p>Over rolling land covered with juniper, pine and sage.</p> <p>39.76 The 1/4 sec. cor. of secs. 11 and 14, monumented with a wood post, 23 ins. long, 5 ins. sq., at intersection of barbed wire fences, extending N., E. and W., mkd. 1/4 on its side. A rebar, 1/2 in. diam., 18 ins. long, firmly set, flush with the ground, is set alongside the wood post. This position is locally recognized as the cor. and is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 11 1/4 ——— S 14</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar inside the stainless steel post.</p> <p>Bury the wood post alongside the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 89°58' W., beginning new measurement.</p>
39.75	<p>The cor. of secs. 10, 11, 14 and 15.</p> <hr/> <p>N. 0°04' W., bet. secs. 10 and 11.</p> <p>Over rolling land covered with juniper, pine and sage.</p>
40.94	<p>Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
1/4
S 10 | S 11

2004

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Set a steel fence post alongside the stainless steel post.

Cor. is located 3 lks. E. of a five strand barbed wire fence,
bears N. and S.

81.88

Point accepted for the cor. of secs. 2, 3, 10 and 11, at the
intersection of barbed wire fences, extending E., S. and W.
This position is locally recognized as the cor. and is accepted
as the best available evidence of the orig. cor. position.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
25 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
S 3 | S 2
S 10 | S 11

2004

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Set a steel fence post alongside the stainless steel post..

From the cor. of secs. 1, 2, 11 and 12.

N. 88°13' W., bet. secs. 2 and 11.

Over mountainous and rolling land covered with juniper, pine and
sage.

39.88

Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate
dist.; there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
25 ins. in the ground, with brass cap mkd.

Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 22 N R 29 E S 2 1/4 ——— S 11 2004
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
79.77	The cor. of secs. 2, 3, 10 and 11. <hr/> N. 0°18' W., bet. secs. 2 and 3. Over rolling land covered with juniper, pine and sage.
38.34	Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 29 E 1/4 S 3 S 2 2004
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
77.04	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 20 ins. above ground, badly rusted, with brass cap mkd. T23N R29E S34 S35 S3 S2 T22N 1920. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T 23 N R 29 E S 34 S 35 S 3 S 2 T 22 N 2004
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.


**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Bury orig. iron post alongside the stainless steel post.</p> <hr/>
	<p>From the cor. of secs. 3, 4, and 33 and 34, on the S. bdy. of the Tp.</p>
	<p>North, bet. secs. 33 and 34.</p>
	<p>Over rolling land covered with juniper, pine and sage.</p>
34.37	<p>Point for AP9, sec. 33, identical with AP22, sec. 34, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.</p>
40.05	<p>Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 29 E 1/4 S 33 S 34 2004</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Set a steel fence post alongside the stainless steel post.</p>
49.45	<p>Point for AP8, sec. 33, identical with AP6, sec. 34, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.</p>
60.075	<p>Point for the N. 1/16 sec. cor. of secs. 33 and 34.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 29 E N 1/16 S 33 S 34 2004</p>
	<p>Raise a mound of stone, 3 ft. base, 1 ft. high, W. of cor.</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Set a steel fence post alongside the stainless steel post.</p>

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS							
80.10	<p>The cor. of secs. 27, 28, 33 and 34, monumented with a sandstone, 24 x 19 x 2 ins., firmly set, projecting 18 ins. above ground, in a mound of stone, 2 ft. base, 1 ft. high, mkd. with 2 notches and AI on the E. face and 1 notch on the S. face. This position is locally recognized as the cor. and is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="803 724 1031 840"> <tr> <td colspan="2" style="text-align: center;">T 22 N R 29 E</td> </tr> <tr> <td style="text-align: center;">S 28</td> <td style="text-align: center;">S 27</td> </tr> <tr> <td style="text-align: center;">S 33</td> <td style="text-align: center;">S 34</td> </tr> </table> <p style="text-align: center;">2004</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>	T 22 N R 29 E		S 28	S 27	S 33	S 34
T 22 N R 29 E							
S 28	S 27						
S 33	S 34						
	<hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°55' W., bet. secs. 27 and 34.</p> <p>Over rolling land covered with juniper, pine and sage.</p>						
4.57	<p>Point for AP14, sec. 34, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.</p>						
20.03	<p>True point for the E. 1/16 sec. cor. of secs. 27 and 34, falls on the edge of the left bank of the Rio Puerco River, 200 ft. wide, drains S. 25° W., where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for the witness cor. to the E. 1/16 sec. cor. of secs. 27 and 34, bears S. 32°19' E., 3.96 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>						

Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<div style="text-align: center;">  <p>WC T 22 N R 29 E S 27 E 1/16 S 34</p> <p>2004</p> </div>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Set a steel fence post alongside the stainless steel post.</p>
30.68	<p>Point for AP1, sec. 34, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.</p>
40.06	<p>Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T 22 N R 29 E S 27 1/4 S 34</p> <p>2004</p> </div>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Set a steel fence post alongside the stainless steel post.</p>
45.29	<p>Point for AP5, sec. 34, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.</p>
80.12	<p>The cor. of secs. 27, 28, 33 and 34.</p> <hr/>
	<p>N. 0°13' W., bet. secs. 27 and 28. Over mountainous land covered with juniper, pine and sage.</p>
39.78	<p>Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.56	<p style="text-align: center;">T 22 N R 29 E 1/4 S 28 S 27</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Point for the cor. of secs. 21, 22, 27 and 28, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 21 S 22 S 28 S 27</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
40.01	<hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 88°07' W., bet. secs. 22 and 27.</p> <p>Over rolling land covered with juniper, pine and sage.</p> <p>The 1/4 sec. cor. of secs. 22 and 27, monumented with a sandstone, 24 x 10 x 4 ins., loosely set, projecting 20 ins. above ground, in a scattered mound of stone, mkd. 1/4 on N. face and IA on S. face. This position is locally recognized as the cor. and is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.</p>

Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 22 N R 29 E S 22 1/4 ——— S 27</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury orig. stone alongside the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°11' W., beginning new measurement.</p>
40.16	<p>The cor. of secs. 21, 22, 27 and 28.</p> <hr style="width: 60%; margin: 10px auto;"/>
	<p>N. 0°25' E., bet. secs. 21 and 22.</p> <p>Over rolling land covered with juniper, pine and scattered sage.</p>
39.78	<p>Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 29 E 1/4 S 21 S 22</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located 75 lks. N. of a trail road, bears S. 60° E. and N. 60° W.</p>
79.56	<p>Point for the cor. of secs. 15, 16, 21 and 22, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 22 N	R 29 E
S 16	S 15
S 21	S 22

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

From the cor. of secs. 14, 15, 22 and 23.

S. 89°59' W., bet. secs. 15 and 22.

Over rolling land covered with juniper, pine and sage.

40.72

The 1/4 sec. cor. of secs. 15 and 22, monumented with a wood post, 48 ins. long, 6 ins. sq., firmly set, projecting 27 ins. above ground, mkd. 1/4 on N. face and IA on S. face. This position is locally recognized as the cor. and is accepted as the best available evidence of the orig. cor. position.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 22 N	R 29 E
	S 15
1/4	—
	S 22

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

S. 88°32' W., beginning new measurement

40.30

The cor. of secs. 15, 16, 21 and 22.

N. 0°06' W., bet. secs. 15 and 16.

Over rolling land covered with juniper, pine and sage.

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.78	Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 22 N R 29 E 1/4 S 16 S 15</p>
	2004
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
79.56	Point for the cor. of secs. 9, 10, 15 and 16, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 22 N R 29 E S 9 S 10 S 16 S 15</p>
	2004
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	<hr/> From the cor. of secs. 10, 11, 14 and 15.
	S. 89°53' W., bet. secs. 10 and 15.
40.21	The 1/4 sec. cor. of secs. 10 and 15, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush with the ground, with brass cap mkd. T22N R29E 1/4 S10 S15 1993.
	Add the marks 2004 to the brass cap.
	Cor. is located at intersection of barbed wire fences, extending N. and E.
	A steel fence post is set alongside the cor.
	<hr/> N. 89°53' W., beginning new measurement.
39.99	The cor. of secs. 9, 10, 15 and 16.

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.78	<p>N. 0°10' E., bet. secs. 9 and 10.</p> <p>Over rolling land covered with juniper, pine and sage.</p> <p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 29 E 1/4 S 9 S 10</p>
	<p style="text-align: center;">2004</p>
79.56	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 3, 4, 9 and 10, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 29 E S 4 S 3 ----- S 9 S 10</p>
	<p style="text-align: center;">2004</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
40.15	<hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 89°59' W., bet. secs. 3 and 10.</p> <p>Over rolling land covered with juniper, pine and sage.</p> <p>Point accepted for the 1/4 sec. cor. of secs. 3 and 10, at the intersection of barbed wire fences, extending E. and S. This position is locally recognized as the cor. and is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p style="text-align: center;">T 22 N R 29 E S 3 1/4 ——— S 10</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 86°38' W., beginning new measurement.</p>
39.78	<p>The cor. of secs. 3, 4, 9 and 10.</p> <hr/>
39.78	<p>N. 0°04' W., bet. secs. 3 and 4.</p> <p>Over rolling land covered with juniper, pine and sage.</p>
	<p>Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
79.43	<p style="text-align: center;">T 22 N R 29 E 1/4 S 4 S 3</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T23N R29E S33 S34 S4 S3 T22N 1920.</p> <p>Add the marks 2004 to the brass cap.</p> <hr/>
	<p>From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 32 and 33.</p> <p>Over rolling land covered with scattered juniper, pine and sage.</p>

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
7.37	Point for AP11, sec. 32, at intersection with the right-of-way of Interstate 40, hereinafter described.
23.36	Point for AP7, sec. 32, at intersection with the right-of-way of Interstate 40, hereinafter described.
31.82	Point for AP6, sec. 32, at intersection with the right-of-way of Interstate 40, hereinafter described.
33.43	Point for AP1, sec. 32, at intersection with the right-of-way of Interstate 40, hereinafter described.
40.03	<p>Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E 1/4 S 32 S 33</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
60.045	<p>Point for the N. 1/16 sec. cor. of secs. 32 and 33, occupied with a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E N 1/16 S 32 S 33</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the rebar alongside the stainless steel post.</p> <p>Cor. is located 21 lks., N. 85° W., from the intersection of barbed wire fences, bearing N. and E.</p>

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

80.06

The cor. of secs. 28, 29, 32 and 33, monumented with a wood post, 36 ins. long, 4 ins. sq., firmly set, projecting 24 ins. above ground. A rebar, 1/2 in. diam., 18 ins. long, firmly set, projecting 3 ins. above ground and an iron post, 3 1/2 ins. diam., firmly set, projecting 4 ft. above ground, are set alongside the wood post. This position is locally recognized as the cor. and is accepted as the best available evidence of the orig. cor. position.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

T 22 N	R 29 E
S 29	S 28
S 32	S 33

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Deposit rebar inside the stainless steel post.

Set a steel fence post alongside the stainless steel post.

Cor. is located 20 lks. E. of a trail road, bears N. 10° E. and S. 10° W.

From the cor. of secs. 27, 28, 33 and 34.

S. 89°32' W., bet. secs. 28 and 33.

Over rolling land covered with juniper, pine and sage.

11.20

Point for AP1, sec. 33, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.

40.12

The 1/4 sec. cor. of secs. 28 and 33, monumented with a sandstone, 22 x 11 x 4 ins., loosely set, lying on the ground, with an accessory mound of stone, 2 ft. base, 1 ft. high, to the E., mkd. 1/4 IA on top. This position is locally recognized as the cor. and is accepted as the best available evidence of the orig. cor. position.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 22 N R 29 E S 28 1/4 ——— S 33</p> <p style="text-align: center;">2004</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury orig. sandstone alongside the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°34' W., beginning new measurement.</p>
20.05	<p>Point for the W. 1/16 sec. cor. of secs. 28 and 33, occupied with a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S 28 W 1/16 ——— S 33</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the rebar alongside the stainless steel post.</p>
40.10	<p>The cor. of secs. 28, 29, 32 and 33.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>North, bet. secs. 28 and 29.</p> <p>Over rolling land covered with scattered juniper, pine and sage.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate dist., occupied with a sandstone, 22 x 14 x 2 ins., loosely set on top of the ground, mkd. 1/4 SET 9-19-29 FREIJAG 1' EAST OF TRUE COR on top; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 21 1/4 ——— S 28</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury wood post alongside the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located 25 lks. S. of a trail road, bears N. 70° E. and S. 70° W. A four wire power line parallels the N. side of the trail road.</p> <hr/> <p>S. 89°47' W., beginning new measurement.</p>
39.86	<p>The cor. of secs. 20, 21, 28 and 29.</p> <hr/> <p>N. 0°25' W., bet. secs. 20 and 21.</p> <p>Over rolling land covered with juniper, pine and sage.</p>
40.01	<p>The 1/4 sec. cor. of secs. 20 and 21, monumented with an wood post, 3 ft. long, 4 ins. sq., firmly set, projecting 14 ins. above ground, mkd. IA on E. and W. faces. A rebar, 1/4 in. diam., 22 ins. long, firmly set, projecting 8 ins. above ground, is set alongside the wood post. This position is locally recognized as the cor. and is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E 1/4 S 20 S 21</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a steel fence post alongside the stainless steel post.

Bury wood post and rebar alongside the stainless steel post.

Cor. is located at the intersection of barbed wire fences, extending N., S. and W.

N. 0°11' W., beginning new measurement.

40.15 The cor. of secs. 16, 17, 20 and 21, monumented with a wood post, 30 ins. long, 4 ins. sq., firmly set, projecting 24 ins. above ground, mkd. with 4 notches on E. face, 3 notches on S. face and IA on W. face. This position is locally recognized as the cor. and is accepted as the best available evidence of the orig. cor. position.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, in mound of stone, 3 ft. base, to top, with brass cap mkd.

T 22 N	R 29 E
S 17	S 16
S 20	S 21

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Remove the wood post from the area, impracticable to bury.

Set a steel fence post alongside the stainless steel post.

From the cor. of secs. 15, 16, 21 and 22.

N. 89°42' W., bet. secs. 16 and 21.

Over rolling land covered juniper, pine and sage.

40.45 Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p style="text-align: center;">T 22 N R 29 E S 16 1/4 ——— S 21</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.90	<p>The cor. of secs. 16, 17, 20 and 21.</p> <hr/> <p>N. 0°46' E., bet. secs. 16 and 17.</p> <p>Over rolling land covered with juniper, pine and sage.</p>
39.71	<p>Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E 1/4 S 17 S 16</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.42	<p>Point for the cor. of secs. 8, 9, 16 and 17, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 8 S 9 S 17 S 16</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 89°48' W., bet. secs. 9 and 16.</p>

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.84	<p>Over rolling land covered with juniper, pine and sage.</p> <p>Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 9 1/4 ——— S 16</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.68	<p>The cor. of secs. 8, 9, 16 and 17.</p> <hr/> <p>N. 0°23' E., bet. secs. 8 and 9.</p>
39.70	<p>Over rolling land covered with juniper, pine and sage.</p> <p>Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E 1/4 S 8 S 9</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.40	<p>Point for the cor. of secs. 4, 5, 8 and 9, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 5 S 4 S 8 S 9</p> <p style="text-align: center;">2004</p>

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From the cor. of secs. 3, 4, 9 and 10.

N. 89°54' W., bet. secs. 4 and 9.

Over rolling land covered with juniper, pine and sage.

39.68 Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
S 4
1/4 ———
S 9

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

79.36 The cor. of secs. 4, 5, 8 and 9.

N. 0°15' W., bet. secs. 4 and 5.

Over rolling land covered with juniper, pine and sage.

39.70 Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
1/4
S 5 | S 4

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.12	<p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. T23N R29E S32 S33 S5 S4 T22N 1920. All the 1920 bearing trees were found, dead and down nearby, with no discernable root holes.</p> <p>Add the marks 2004 to the brass cap.</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°09' W., bet. secs. 31 and 32.</p> <p>Over rolling land covered with juniper, pine and sage.</p>
40.10	<p>Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E 1/4 S 31 S 32</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 35 lks. N. of a trail road, bears N. 80° E. and S. 80° W.</p>
80.20	<p>The cor. of secs. 29, 30, 31 and 32, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T22N R29E S30 S29 S31 S32-1993.</p> <p>Add the marks 2004 to the brass cap.</p> <p>An iron fence post, 3 1/2 ins. diam., firmly set, projecting 4 ft. above ground, is set alongside the cor.</p> <p>Cor. is located 10 lks. E. of a trail road, bears N. 30° E. and S. 30° W.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>S. 89°28' W., bet. secs. 29 and 32.</p>

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

<p>CHAINS</p> <p>40.07</p> <p>80.14</p> <p>40.18</p>	<p>Over rolling land covered with juniper, pine and sage.</p> <p>Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 29 1/4 ——— S 32</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located 1.05 chs. N. of a graded dirt road, 25 ft. wide, bears S. 40° E. and N. 70° W.</p> <p>The cor. of secs. 29, 30, 31 and 32.</p> <hr/> <p>S. 89°21' W., bet. secs. 30 and 31.</p> <p>Over rolling land covered with juniper, pine and sage.</p> <p>The 1/4 sec. cor. of secs. 30 and 31, monumented with a wood fence cor. post, 6 ins. sq., firmly set, projecting 4 1/2 ft. above ground. This position is locally recognized as the cor. and is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 30 1/4 ——— S 31</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/>
--	--

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
35.56	<p>S. 89°00' W., beginning new measurement.</p> <p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/>
	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°15' W., bet. secs. 29 and 30.</p> <p>Over rolling land covered with juniper, pine and sage.</p>
39.87	<p>Point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E 1/4 S 30 S 29</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.74	<p>Point accepted for the cor. of secs. 19, 20, 29 and 30, at the intersection of fences, no wire strands, extending N. and E. This position is locally recognized as the cor. and is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 19 S 20 S 30 S 29</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located 30 lks. E. of a trail road, bears S. 10° E. and N. 10° W.</p> <hr/>

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89°29' W., bet. secs. 20 and 29.</p> <p>Over rolling land covered with juniper, pine and sage.</p> <p>40.16 The 1/4 sec. cor. of secs. 20 and 29, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set in a rotting wood post, 24 ins. long, 6 ins. sq., flush with the ground. This position is locally recognized as the cor. and is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 20 1/4 ——— S 29</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury wood post and rebar alongside the stainless steel post.</p> <p>A steel fence post is set alongside the stainless steel post.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>S. 89°04' W., beginning new measurement.</p>
40.31	<p>The cor. of secs. 19, 20, 29 and 30.</p> <hr style="width: 80%; margin: 0 auto;"/> <p>N. 89°29' W., bet. secs. 19 and 30.</p> <p>Over rolling land covered with juniper, pine and sage.</p>
39.80	<p>Point accepted for the 1/4 sec. cor. of secs. 19 and 30, at the intersection of barbed wire fences extending N., S. and W. This position is locally recognized as the cor. and is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 22 N R 29 E
S 19
1/4 —
S 30

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

S. 89°55' W., beginning new measurement.

35.61 The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.

From the cor. of secs. 19, 20, 29 and 30.

N. 0°14' E., bet. secs. 19 and 20.

Over rolling land covered with juniper, pine and sage.

41.74 The 1/4 sec. cor. of secs. 19 and 20, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T22N R29E 1/4 S19 S20 1993.

Add the marks 2004 to the brass cap.

A steel fence post and wood fence post are set alongside the cor.

From the cor. of secs. 16, 17, 20 and 21.

S. 89°37' W., bet. secs. 17 and 20.

Over rolling land covered with juniper, pine and sage.

39.81 The 1/4 sec. cor. of secs. 17 and 20, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T22N R29E 1/4 S17 S20 1993, from which the orig. bearing trees

A juniper, 36 ins. diam., bears S. 14° W., 49 lks. dist., with scribe marks 1/4 S20 BT visible on partially open blaze. (Record: 44 lks. dist.)

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.67	<p>Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E 1/4 S 7 S 8</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.34	<p>Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 6 S 5 S 7 S 8</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
39.93	<hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>N. 89°56' W., bet. secs. 5 and 8.</p> <p>Over rolling land covered with juniper, pine and sage.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 5 1/4 ——— S 8</p> <p style="text-align: center;">2004</p>

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.86	<p>The cor. of secs. 5, 6, 7 and 8.</p> <hr/>
	<p>S. 89°43' W., bet. secs. 6 and 7.</p> <p>Over rolling land covered with juniper, pine and sage.</p>
39.83	<p>Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 29 E S 6 1/4 ——— S 7</p> <p style="text-align: center;">2004</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
78.91	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/>
	<p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°02' W., bet. secs. 5 and 6.</p> <p>Over rolling land covered with juniper, pine and sage.</p>
39.67	<p>Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 29 E 1/4 S 6 S 5</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.22	<p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T23N R29E S31 S32 S6 S5 T22N R29E 1993. Add the marks 2004 to the brass cap. A steel fence post is set alongside the cor.</p>
	<p style="text-align: center;">Subdivision of Section 10, T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona</p>
	<p>From the 1/4 sec. cor. of secs. 10 and 15. N. 0°01' W., on the N. and S. center line of sec. 10. Over rolling land covered with juniper, pine and sage.</p>
40.44	<p>Point for the center 1/4 sec. cor. of sec. 10, at intersection with the E. and W. center line of sec. 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 29 E C 1/4 S 10 2004</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post alongside the stainless steel post. Cor. is located 3 lks. E. of a barbed wire fence, bears N. and S.</p>
81.98	<p>The 1/4 sec. cor. of secs. 3 and 10.</p>
	<p>From the 1/4 sec. cor. of secs. 10 and 11. S. 89°10' W., on the E. and W. center line of sec. 10. Over rolling land covered with juniper, pine and sage.</p>
40.18	<p>The center 1/4 sec. cor. of sec. 10.</p>

Subdivision of Section 10,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.03	<p>The 1/4 sec. cor. of secs. 9 and 10.</p> <hr/> <p style="text-align: center;">Subdivision of Section 14, T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 14 and 23.</p> <p>N. 0°09' W., on the N. and S. center line of sec. 14.</p> <p>Over mountainous land covered with juniper, pine and sage.</p>
39.58	<p>Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E. and W. center line of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a supporting mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E C 1/4 S 14</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>From this cor. point, a local monument, bears N. 27°53' W., 39 lks. dist., monumented with a sandstone, 14 x 12 x 3 ins., firmly set, projecting 14 ins. above ground, mkd. C 1/4 on W. face.</p>
79.20	<p>The 1/4 sec. cor. of secs. 11 and 14.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 14.</p> <p>N. 89°27' W., on the E. and W. center line of sec. 14.</p> <p>Over rolling land covered with juniper, pine and sage.</p>
39.39	<p>The center 1/4 sec. cor. of sec. 14.</p>

**Subdivision of Section 14,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
78.78	<p>The 1/4 sec. cor. of secs. 14 and 15.</p> <hr/> <p style="text-align: center;">Subdivision of Section 20, T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 20 and 29.</p> <p>N. 0°04' W., on the N. and S. center line of sec. 20.</p> <p>Over rolling land covered with juniper, pine and sage.</p>
40.72	<p>Point for the center 1/4 sec. cor. of sec. 20, at intersection with the E. and W. center line of sec. 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E C 1/4 S 20</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>From this cor. point, a local monument, bears S. 15°40' W., 63 lks. dist., monumented with a wood post, 4 ins. sq., firmly set, 16 ins. above ground, mkd. IA on S. face and illegible marks on N. face. A sandstone, 5 x 2 ins., firmly set, projecting 12 ins. above ground, is set alongside the wood post. A steel fence post is also set alongside the wood post.</p>
80.25	<p>The 1/4 sec. cor. of secs. 17 and 20.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 20 and 21.</p> <p>N. 89°30' W., on the E. and W. center line of sec. 20.</p> <p>Over rolling land covered with juniper, pine and sage.</p>
39.91	<p>The center 1/4 sec. cor. of sec. 20.</p>

Subdivision of Section 20,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The 1/4 sec. cor. of secs. 19 and 20.</p> <hr/> <p style="text-align: center;">Subdivision of Section 22, T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 22 and 27.</p> <p>N. 0°31' E., on the N. and S. center line of sec. 22.</p> <p>Over rolling and mountainous land covered with juniper, pine and sage.</p>
19.77	<p>Point for the center S. 1/16 sec. cor. of sec. 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 22 N R 29 E</p> <p style="margin-left: 100px;">C</p> <p>S 1/16 S 22</p> <p style="margin-left: 100px;">C</p> <p>2004</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 20 lks. E. of a barbed wire fence, bears N. and S.</p>
39.54	<p>Point for the center 1/4 sec. cor. of sec. 22, at intersection with the E. and W. center line of sec. 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 22 N R 29 E</p> <p style="margin-left: 100px;">C 1/4 S 22</p> <p>2004</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
80.02	<p>The 1/4 sec. cor. of secs. 15 and 22.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 22 and 23.</p>

**Subdivision of Section 22,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

S. 89°32' W., on the E. and W. center line of sec. 22.

Over rolling and mountainous land covered with juniper, pine and sage.

39.75 The center 1/4 sec. cor. of sec. 22.

79.96 The 1/4 sec. cor. of secs. 21 and 22.

SE 1/4 Section 22

From the S. 1/16 sec. cor. of secs. 22 and 23.

N. 89°18' W., on the E. and W. center line of the SE 1/4 of sec. 22.

39.87 The center S. 1/16 sec. cor. of sec. 22.

**Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

From the 1/4 sec. cor. of secs. 24 and 25.

N. 1°23' E., on the N. and S. center line of sec. 24.

Over rolling land covered with scattered juniper, pine and sage.

4.915 Point for the center S-S-S 1/256 sec. cor. of sec. 24.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
S 24
C-S-S-S
1/256

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

9.83 Point for the center S-S 1/64 sec. cor. of sec. 24.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
14.745	<p style="text-align: center;">T 22 N R 29 E S 24 C-S-S 1/64 2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Point for the center N-S-S 1/256 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
19.66	<p style="text-align: center;">T 22 N R 29 E S 24 C-N-S-S 1/256 2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Point for the center S. 1/16 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>
24.575	<p style="text-align: center;">T 22 N R 29 E C S 1/16 S 24 C 2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Point for the center S-N-S 1/256 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
29.49	<p style="text-align: center;">T 22 N R 29 E S 24 C-S-N-S 1/256</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Point for the center N-S 1/64 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
34.405	<p style="text-align: center;">T 22 N R 29 E S 24 C-N-S 1/64</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Point for the center N-N-S 1/256 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>
39.32	<p style="text-align: center;">T 22 N R 29 E S 24 C-N-N-S 1/256</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E. and W. center line of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
58.965	<p style="text-align: center;">T 22 N R 29 E C 1/4 S 24</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Point for the center N. 1/16 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
78.61	<p style="text-align: center;">T 22 N R 29 E C N 1/16 S 24 C 2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>The 1/4 sec. cor. of secs. 13 and 24.</p> <hr style="width: 60%; margin-left: 0;"/> <p>From the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp.</p> <p>S. 88°12' W., on the E. and W. center line of sec. 24.</p> <p>Over rolling land covered with juniper, pine and sage.</p>
19.59	<p>Point for the center E. 1/16 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
29.385	<p style="text-align: center;">T 22 N R 29 E E 1/16 C — C S 24</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the center W-E 1/64 sec. cor. of sec. 24.</p>

**Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 24 C-W-E 1/64 2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
39.18	The center 1/4 sec. cor. of sec. 24.
48.975	<p>Point for the center E-W 1/64 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 24 C-E-W 1/64 2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
58.77	<p>Point for the center W. 1/16 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E W 1/16 C—C S 24 2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located 50 lks. W. of a graded dirt road, 20 ft. wide, bears N. and S.</p>

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
78.36	The 1/4 sec. cor. of secs. 23 and 24.
	<hr/> <p style="text-align: center;">SE 1/4 Section 24</p> <hr/>
	From the E. 1/16 sec. cor. of secs. 24 and 25.
	N. 1°25' E., on the N. and S. center line of the SE 1/4 of sec. 24.
4.875	Point for the center S-S-SE 1/256 sec. cor. of sec. 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 22 N R 29 E S 24 C-S-S-SE 1/256</p>
	<p style="text-align: center;">2004</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post alongside the stainless steel post.
9.75	Point for the center S-SE 1/64 sec. cor. of sec. 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 22 N R 29 E S 24 C-S-SE 1/64</p>
	<p style="text-align: center;">2004</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post alongside the stainless steel post.
14.625	True point for the center N-S-SE 1/256 sec. cor. of sec. 24, falls in the middle of a chicken coop, 24 x 11 ft., where it is impracticable to establish a permanent monument.
	From this true point, the point selected for the witness cor. to the center N-S-SE 1/256 sec. cor. of sec. 24, bears N. 45°00' E., 1 ch. dist.

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">WC T 22 N R 29 E S 24 ↙ C-N-S-SE 1/256 2004</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Set a steel fence post alongside the stainless steel post.</p>
19.50	<p>Point for the SE 1/16 sec. cor. of sec. 24, at intersection with the E. and W. center line of the SE 1/4 of sec. 24.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 29 E SE 1/16 S 24 2004</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
29.25	<p>Point for the center N-SE 1/64 sec. cor. of sec. 24.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 29 E S 24 C-N-SE 1/64 2004</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
39.00	<p>The center E. 1/16 sec. cor. of sec. 24.</p> <hr/>


Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the S. 1/16 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp.</p>
	<p>S. 87°46' W., on the E. and W. center line of the SE 1/4 of sec. 24.</p>
19.59	<p>The SE 1/16 sec. cor. of sec. 24.</p>
29.385	<p>True point for the center W-SE 1/64 sec. cor. of sec. 24, falls in the middle of Black Wash, 100 ft. wide, 10 ft. deep, drains S. 30° W., where it is impracticable to establish a permanent monument.</p>
	<p>From this true point, the point selected for the witness cor. to the center W-SE 1/64 sec. cor. of sec. 24, bears S. 45°00' E., 1 ch. dist.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>WC  T 22 N R 29 E S 24 C-W-SE 1/64 2004</p> </div>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Set a steel fence post alongside the stainless steel post.</p>
39.18	<p>The center S. 1/16 sec. cor. of sec. 24.</p> <hr/>
	<p>From the W-E 1/64 sec. cor. of secs. 24 and 25.</p>
	<p>N. 1°24' E., on the N. and S. center line of the SW 1/4 of the SE 1/4 of sec. 24.</p>
4.895	<p>Point for the center S-SW-SE 1/256 sec. cor. of sec. 24, not monumented.</p>
9.79	<p>Point for the SW-SE 1/64 sec. cor. of sec. 24, at intersection with the E. and W. center line of the SW 1/4 of the SE 1/4 of sec. 24.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 22 N R 29 E S 24 SW-SE 1/64 2004</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Set a steel fence post alongside the stainless steel post.</p>
14.685	<p>Point for the center N-SW-SE 1/256 sec. cor. of sec. 24.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 29 E S 24 C-N-SW-SE 1/256 2004</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Set a steel fence post alongside the stainless steel post.</p>
19.58	<p>The center W-SE 1/64 sec. cor. of sec. 24.</p> <hr/>
	<p>From the center S-SE 1/64 sec. cor. of sec. 24.</p>
	<p>S. 87°33' W., on the E. and W. center line of the SW 1/4 of the SE 1/4 of sec. 24.</p>
9.80	<p>The SW-SE 1/64 sec. cor. of sec. 24.</p>
19.60	<p>The center S-S 1/64 sec. cor. of sec. 24.</p> <hr/>
	<p>From the center N-S-SE 1/256 sec. cor. of sec. 24.</p>
	<p>S. 87°40' W., on the E. and W. center line of the NE 1/4 of the SW 1/4 of the SE 1/4 of sec. 24.</p>
9.80	<p>The center N-SW-SE 1/256 sec. cor. of sec. 24.</p> <hr/>

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the center S-S-SE 1/256 sec. cor. of sec. 24.</p> <p>S. 87°27' W., on the E. and W. center line of the SE 1/4 of the SW 1/4 of the SE 1/4 of sec. 24.</p>
9.80	<p>The point for the center S-SW-SE 1/256 sec. cor. of sec. 24.</p> <hr/> <p>S. 87°27' W., on the E. and W. center line of the SW 1/4 of the SW 1/4 of the SE 1/4 of sec. 24.</p>
9.80	<p>The center S-S-S 1/256 sec. cor. of sec. 24.</p> <hr/> <p>From the center W-SE 1/64 sec. cor. of sec. 24.</p> <p>N. 1°24' E., on the N. and S. center line of the NW 1/4 of the SE 1/4 of sec. 24.</p>
4.895	<p>True point for the center S-NW-SE 1/256 sec. cor. of sec. 24, falls in the middle of Black Wash, 100 ft. wide, 10 ft. deep, drains S. 10° W., where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for the witness cor. to the center S-NW-SE 1/256 sec. cor. of sec. 24, bears N. 45°00' E., 3 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div data-bbox="760 1333 1031 1543" style="text-align: center;"> <p>WC T 22 N R 29 E S 24 C-S-NW-SE 1/256 2004</p>  </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
9.79	<p>Point for the NW-SE 1/64 sec. cor. of sec. 24, at intersection with the E. and W. center line of the NW 1/4 of the SE 1/4 of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>T 22 N R 29 E S 24 NW-SE 1/64 2004</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
14.685	<p>Point for the center N-NW-SE 1/256 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p>T 22 N R 29 E S 24 C-N-NW-SE 1/256 2004</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
19.58	<p>The center W-E 1/64 sec. cor. of sec. 24.</p> <hr/> <p>From center N-SE 1/64 sec. cor. of sec. 24.</p> <p>S. 87°59' W., on the E. and W. center line of the NW 1/4 of the SE 1/4 of sec. 24.</p>
9.795	<p>The NW-SE 1/64 sec. cor. of sec. 24.</p>
19.59	<p>The center N-S 1/64 sec. cor. of sec. 24.</p> <hr/> <p>From the true point for the center S-NW-SE 1/256 sec. cor. of sec. 24.</p> <p>S. 87°53' W., on the E. and W. center line of the SW 1/4 of the NW 1/4 of the SE 1/4 of sec. 24.</p>
9.795	<p>The center S-N-S 1/256 sec. cor. of sec. 24.</p> <hr/>

**Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
9.795	<p>From the center N-NW-SE 1/256 sec. cor. of sec. 24.</p> <p>S. 88°06' W., on the E. and W. center line of the NW 1/4 of the NW 1/4 of the SE 1/4 of sec. 24.</p> <p>The center N-N-S 1/256 sec. cor. of sec. 24</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">SW 1/4 Section 24</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the W. 1/16 sec. cor. of secs. 24 and 25.</p> <p>N. 1°22' E., on the N. and S. center line of the SW 1/4 of sec. 24.</p>
0.88	<p>Point for AP16, sec. 24, at intersection with the right-of-way of Interstate 40, hereinafter described.</p>
4.95	<p>Point for the center S-S-SW 1/256 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 24 C-S-S-SW 1/256 2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
9.90	<p>Point for the center S-SW 1/64 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 24 C-S-SW 1/64 2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>

**Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
14.85	<p>Point for the center N-S-SW 1/256 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 24 C-N-S-SW 1/256</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
19.80	<p>Point for the SW 1/16 sec. cor. of sec. 24, at intersection with the E. and W. center line of the SW 1/4 of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E SW 1/16 S 24</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
24.75	<p>Point for the center S-N-SW 1/256 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 24 C-S-N-SW 1/256</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>

**Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
29.70	<p>Point for the center N-SW 1/64 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 24 C-N-SW 1/64 2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located 65 lks. W. of a graded dirt road, 20 ft. wide, bears N. and S.</p>
34.65	<p>Point for the center N-N-SW 1/256 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 24 C-N-N-SW 1/256 2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located 50 lks. W. of a graded dirt road, 20 ft. wide, bears N. and S.</p>
39.60	<p>The center W. 1/16 sec. cor. of sec. 24.</p> <hr/> <p>From the center S. 1/16 sec. cor. of sec. 24.</p> <p>S. 87°46' W., on the E. and W. center line of the SW 1/4 of sec. 24.</p>
9.795	<p>Point for the center E-SW 1/64 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 22 N R 29 E S 24 C-E-SW 1/64 2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
19.59	The SW 1/16 sec. cor. of sec. 24.
39.18	The S. 1/16 sec. cor. of secs. 23 and 24.
	<hr/> <p>From the center E-SW 1/64 sec. cor. of sec. 24.</p> <p>N. 1°22' E., on the N. and S. center line of the NE 1/4 of the SW 1/4 of sec. 24.</p>
4.93	<p>Point for the center S-NE-SW 1/256 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 29 E S 24 C-S-NE-SW 1/256 2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
9.86	<p>Point for the NE-SW 1/64 sec. cor. of sec. 24, at intersection with the E. and W. center line of the NE 1/4 of the SW 1/4 of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 29 E S 24 NE-SW 1/64 2004</p>

**Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
14.79	<p>Point for the center N-NE-SW 1/256 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 24 C-N-NE-SW 1/256 2004</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
19.72	<p>The center E-W 1/64 sec. cor. of sec. 24.</p> <hr/> <p>From the center N-S 1/64 sec. cor. of sec. 24.</p> <p>S. 87°59' W., on the E. and W. center line of the NE 1/4 of the SW 1/4 of sec. 24.</p>
9.795	<p>The NE-SW 1/64 sec. cor. of sec. 24.</p>
19.59	<p>The center N-SW 1/64 sec. cor. of sec. 24.</p> <hr/> <p>From the center N-N-S 1/256 sec. cor. of sec. 24.</p> <p>S. 88°06' W., on the E. and W. center line of the NE 1/4 of the NE 1/4 of the SW 1/4 of sec. 24.</p>
9.795	<p>The center N-NE-SW 1/256 sec. cor. of sec. 24.</p> <hr/> <p>From the center S-N-S 1/256 sec. cor. of sec. 24.</p> <p>S. 87°53' W., on the E. and W. center line of the SE 1/4 of the NE 1/4 of the SW 1/4 of sec. 24.</p>
9.795	<p>The center S-NE-SW 1/256 sec. cor. of sec. 24.</p> <hr/>

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
9.795	<p>S. 87°53' W., on the E. and W. center line of the SW 1/4 of the NE 1/4 of the SW 1/4 of sec. 24.</p> <p>The center S-N-SW 1/256 sec. cor. of sec. 24.</p> <hr/> <p>From the center N-NE-SW 1/256 sec. cor. of sec. 24.</p> <p>S. 88°06' W., on the E. and W. center line of the NW 1/4 of the NE 1/4 of the SW 1/4 of sec. 24.</p>
9.795	<p>The center N-N-SW 1/256 sec. cor. of sec. 24.</p> <hr/> <p>From the E-W 1/64 sec. cor. of secs. 24 and 25.</p> <p>N. 1°22' E., on the N. and S. center line of the SE 1/4 of the SW 1/4 of sec. 24.</p>
0.41	<p>Point for AP15, sec. 24, at intersection with the right-of-way of Interstate 40, hereinafter described.</p>
4.93	<p>Point for the center S-SE-SW 1/256 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 24 C-S-SE-SW 1/256 2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
9.86	<p>Point for the SE-SW 1/64 sec. cor. of sec. 24, at intersection with the E. and W. center line of the SE 1/4 of the SW 1/4 of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 24 SE-SW 1/64 2004</p>

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
14.79	<p>Point for the center N-SE-SW 1/256 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 24 C-N-SE-SW 1/256 2004</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
19.72	<p>The center E-SW 1/64 sec. cor. of sec. 24.</p> <hr/> <p>From the center S-S 1/64 sec. cor. of sec. 24.</p> <p>S. 87°33' W., on the E. and W. center line of the SE 1/4 of the SW 1/4 of sec. 24.</p>
9.80	<p>The SE-SW 1/64 sec. cor. of sec. 24.</p>
19.60	<p>The center S-SW 1/64 sec. cor. of sec. 24</p> <hr/> <p>From the center N-S-S 1/256 sec. cor. of sec. 24.</p> <p>S. 87°40' W., on the E. and W. center line of the NE 1/4 of the SE 1/4 of the SW 1/4 of sec. 24.</p>
9.80	<p>The center N-SE-SW 1/256 sec. cor. of sec. 24.</p> <hr/> <p>From the center S-S-S 1/256 sec. cor. of sec. 24.</p> <p>S. 87°27' W., on the E. and W. center line of the SE 1/4 of the SE 1/4 of the SW 1/4 of sec. 24.</p>
9.80	<p>The center S-SE-SW 1/256 sec. cor. of sec. 24.</p> <hr/>

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
9.80	<p>S. 87°27' W., on the E. and W. center line of the SW 1/4 of the SE 1/4 of the SW 1/4 of sec. 24.</p> <p>The center S-S-SW 1/256 sec. cor. of sec. 24.</p> <hr/> <p>From the center N-SE-SW 1/256 sec. cor. of sec. 24.</p> <p>S. 87°40' W., on the E. and W. center line of the NW 1/4 of the SE 1/4 of the SW 1/4 of sec. 24.</p>
9.80	<p>The center N-S-SW 1/256 sec. cor. of sec. 24.</p> <hr/> <p style="text-align: center;">NW 1/4 Section 24</p> <hr/> <p>From the center W. 1/16 sec. cor. of sec. 24.</p> <p>N. 1°22' E., on the N. and S. center line of the NW 1/4 of sec. 24.</p>
19.80	<p>Point for NW 1/16 sec. cor. of sec. 24, at intersection with the E. and W. center line of the NW 1/4 of sec. 24, falls in the center of a graded dirt road, 20 ft. wide, bears N. and S.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 47 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E NW 1/16 S 24</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>from which</p> <p style="margin-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 25°00' W., 198 ft. dist. with brass cap mkd. T22N R29E 1/16 S24 198 FT. TO COR. RM 2004 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post alongside the stainless steel post.</p>

**Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 25°00' W., 198 ft. dist. with brass cap mkd. T22N R29E 1/16 S24 198 FT. TO COR. RM 2004 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post alongside the stainless steel post.

39.60 The W. 1/16 sec. cor. of secs. 13 and 24.

From the center N. 1/16 sec. cor. of sec. 24.

S. 88°38' W., on the E. and W. center line of the NW 1/4 of sec. 24.

19.59 The NW 1/16 sec. cor. of sec. 24.

39.18 The N. 1/16 sec. cor. of secs. 23 and 24.

**Subdivision of Section 25,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

From the 1/4 sec. cor. of secs. 25 and 36.

N. 1°29' E., on the N. and S. center line of sec. 25.

Over rolling land covered with juniper, pine and sage.

17.76 Point for AP40, sec. 25, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.

23.87 Point for AP29, sec. 25, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.

32.58 Point for AP46, sec. 25, at intersection with the Proposed Lease Tract, hereinafter described.

37.37 Point for the center 1/4 sec. cor. of sec. 25, at intersection with the E. and W. center line of sec. 25.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
C 1/4 S 25

2004

**Subdivision of Section 25,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
57.08	<p>Point for the center N. 1/16 sec. cor. of sec. 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 22 N R 29 E C N 1/16 S 25 C</p> </div> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
66.935	<p>Point for the center N-N 1/64 sec. cor. of sec. 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 22 N R 29 E S 25 C-N-N 1/64</p> </div> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
71.25	<p>Point for AP11, sec. 25, at intersection with the right-of-way of Interstate 40, hereinafter described.</p>
76.73	<p>Point for AP6, sec. 25, at intersection with the right-of-way of Interstate 40, hereinafter described.</p>
76.79	<p>The 1/4 sec. cor. of secs. 24 and 25.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the 1/4 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp.</p> <p>S. 86°19' W., on the E. and W. center line of sec. 25.</p> <p>Over rolling land covered with juniper, pine and sage.</p>
19.645	<p>Point for the center E. 1/16 sec. cor. of sec. 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Subdivision of Section 25,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>T 22 N R 29 E E 1/16 C———C S 25 2004</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
39.29	The center 1/4 sec. cor. of sec. 25.
48.255	<p>Point for the center E-W 1/64 sec. cor. of sec. 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p>T 22 N R 29 E S 25 C-E-W 1/64 2004</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
57.22	<p>Point for the center W. 1/16 sec. cor. of sec. 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p>T 22 N R 29 E W 1/16 C———C S 25 2004</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
75.15	<p>The 1/4 sec. cor. of secs. 25 and 26.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">NE 1/4 Section 25</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the center E. 1/16 sec. cor. of sec. 25.</p> <p>N. 1°28' E., on the N. and S. center line of the NE 1/4 of sec. 25.</p>

Subdivision of Section 25,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
32.56	Point for AP16, sec. 25, at intersection with the right-of-way of Interstate 40, hereinafter described.
37.68	Point for AP4, sec. 25, at intersection with the right-of-way of Interstate 40, hereinafter described.
39.06	The E. 1/16 sec. cor. of secs. 24 and 25.
<hr/> SE 1/4 Section 25 <hr/>	
	From the E. 1/16 sec. cor. of secs. 25 and 36.
	N. 0°52' E., on the N. and S. center line of the SE 1/4 of sec. 25.
19.77	Point for AP41, sec. 25, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.
25.87	Point for AP28, sec. 25, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.
38.66	The center E. 1/16 sec. cor. of sec. 25.
<hr/> SW 1/4 Section 25 <hr/>	
	From the W. 1/16 sec. cor. of secs. 25 and 36.
	N. 0°39' E., on the N. and S. center line of the SW 1/4 of sec. 25.
18.19	True point for AP36, sec. 25, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.
24.34	True point for AP32, sec. 25, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.
32.34	Point for AP50, sec. 25, at intersection with the Proposed Lease Tract, hereinafter described.
38.57	The center W. 1/16 sec. cor. of sec. 25.
	From the E-W 1/64 sec. cor. of secs. 25 and 36.
	N. 1°04' E., on the N. and S. center line of the SE 1/4 of the SW 1/4 of sec. 25.

Subdivision of Section 25,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
18.06	Point for AP39, sec. 25, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.
18.98	Point for the center E-SW 1/64 sec. cor. of sec. 25, not monumented.
	<hr/> N. 1°04' E., on the N. and S. center line of the NE 1/4 of the SW 1/4 of sec. 25.
5.18	Point for AP30, sec. 25, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.
13.37	Point for AP48, sec. 25, at intersection with the Proposed Lease Tract, hereinafter described.
18.98	The center E-W 1/64 sec. cor. of sec. 25.
	<hr/> NW 1/4 Section 25 <hr/>
	From the center W. 1/16 sec. cor. of sec. 25.
	N. 0°57' W., on the N. and S. center line of the NW 1/4 of sec. 25.
19.83	Point for the NW 1/16 sec. cor. of sec. 25, at intersection with the E. and W. center line of the NW 1/4 of sec. 25.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 29 E NW 1/16 S 25
	2004
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
29.745	Point for the center N-NW 1/64 sec. cor. of sec. 25.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 29 E C-N-NW 1/64 S 25
	2004

**Subdivision of Section 25,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
35.05	Point for AP9, sec. 25, at intersection with the right-of-way of Interstate 40, hereinafter described.
39.66	The W. 1/16 sec. cor. of secs. 24 and 25.
	<hr/> <p>From the center N. 1/16 sec. cor. of sec. 25.</p> <p>S. 86°51' W., on the E. and W. center line of the NW 1/4 of sec. 25.</p>
9.38	Point for the center E-NW 1/64 sec. cor. of sec. 25.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 22 N R 29 E S 25 C-E-NW 1/64 2004</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
18.76	The NW 1/16 sec. cor. of sec. 25.
37.52	The N. 1/16 sec. cor. of secs. 25 and 26.
	<hr/> <p>From the center E-NW 1/64 sec. cor. of sec. 25.</p> <p>N. 0°16' E., on the N. and S. center line of the NE 1/4 of the NW 1/4 of sec. 25.</p>
9.88	Point for the NE-NW 1/64 sec. cor. of sec. 25, at intersection with the E. and W. center line of the NE 1/4 of the NW 1/4 of sec. 25.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Subdivision of Section 25,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>T 22 N R 29 E S 25 NE-NW 1/64</p> <p>2004</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
14.69	Point for AP10, sec. 25, at intersection with the right-of-way of Interstate 40, hereinafter described.
19.76	The E-W 1/64 sec. cor. of secs. 24 and 25.
	<hr/> <p>From the center N-N 1/64 sec. cor. of sec. 25.</p> <p>S. 87°06' W., on the E. and W center line of the NE 1/4 of the NW 1/4 of sec. 25.</p>
9.59	The NE-NW 1/64 sec. cor. of sec. 25.
19.18	The center N-NW 1/64 sec. cor. of sec. 25.
	<hr/> <p>From the center E-W 1/64 sec. cor. of sec. 25.</p> <p>N. 0°16' E., on the N. and S. center line of the SE 1/4 of the NW 1/4 of sec. 25.</p>
19.76	The center E-NW 1/64 sec. cor. of sec. 25.
	<hr/> <p>Subdivision of Section 26, T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona</p> <hr/>
	From the 1/4 sec. cor. of secs. 26 and 35.
	N. 0°58' W., on the N. and S. center line of sec. 26.
	Over rolling land covered with juniper, pine and sage.
10.415	Point at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.
14.995	Point at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.
17.95	Rio Puerco River, 200 ft. wide, course N. 20° W.

**Subdivision of Section 26,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
19.955	<p>Point for the center S. 1/16 sec. cor. of sec. 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E C S 1/16 S 26 C</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
39.80	Woven wire fence, bears E. and W.
39.91	<p>Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E. and W. center line of sec. 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E C 1/4 S 26</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
59.615	Point for the center N. 1/16 sec. cor. of sec. 26, not monumented.
79.32	The 1/4 sec. cor. of secs. 23 and 26.
	<hr/> <p>From the 1/4 sec. cor. of secs. 25 and 26.</p> <p>N. 89°25' W., on the E. and W. center line of sec. 26.</p> <p>Over rolling land covered with juniper, pine and sage.</p>
20.255	<p>Point for the center E. 1/16 sec. cor. of sec. 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 26,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 22 N R 29 E E 1/16 C——C S 26 2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>From this cor. point, a local monument, bears S. 82°17' E., 29 lks. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 5 ins. above the ground, with aluminum cap mkd. MARTINEZ LS5873.</p>
40.51	The center 1/4 sec. cor. of sec. 26.
60.21	Point for the center W. 1/16 sec. cor. of sec. 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 22 N R 29 E W 1/16 C——C S 26 2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located 5 lks. S. of a wire fence, bears E. and W.</p>
79.91	The 1/4 sec. cor. of secs. 26 and 27.
	<p style="text-align: center;">NE 1/4 Section 26</p> <hr/> <p>From the center E. 1/16 sec. cor. of sec. 26.</p> <p>N. 2°10' W., on the N. and S. center line of the NE 1/4 of sec. 26.</p>
19.835	Point for the NE 1/16 sec. cor. of sec. 26, at intersection with the E. and W. center line of the NE 1/4 of sec. 26.

Subdivision of Section 26,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E NE 1/16 S 26</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
35.80	Point for AP11, sec. 26, at intersection with the right-of-way of Interstate 40, hereinafter described.
39.67	The E. 1/16 sec. cor. of secs. 23 and 26.
<hr/>	
	<p>From the N. 1/16 sec. cor. of secs. 25 and 26.</p> <p>N. 89°45' W., on the E. and W. center line of the NE 1/4 of sec. 26.</p>
19.835	The NE 1/16 sec. cor. of sec. 26.
39.67	The center N. 1/16 sec. cor. of sec. 26.
<hr/>	
SE 1/4 Section 26	
<hr/>	
	<p>From the E. 1/16 sec. cor. of secs. 26 and 35.</p> <p>N. 0°33' W., on the N. and S. center line of the SE 1/4 of sec. 26.</p>
13.52	Point at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.
14.43	Point at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.
19.92	Point for the SE 1/16 sec. cor. of sec. 26, at intersection with the E. and W. center line of the SE 1/4 of sec. 26.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E SE 1/16 S 26</p> <p style="text-align: center;">2004</p>

Subdivision of Section 26,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
39.84	<p>The center E. 1/16 sec. cor. of sec. 26.</p> <hr/> <p>From the S. 1/16 sec. cor. of secs. 25 and 26.</p> <p>N. 89°30' W., on the E. and W. center line of the SE 1/4 of sec. 26.</p>
5.25	<p>Point for AP17, sec. 26, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.</p>
11.52	<p>True point for AP18, sec. 26, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.</p>
20.11	<p>The SE 1/16 sec. cor. of sec. 26.</p>
40.22	<p>The center S. 1/16 sec. cor. of sec. 26.</p> <hr/> <p style="text-align: center;">SW 1/4 Section 26</p> <hr/> <p>From the W. 1/16 sec. cor. of secs. 26 and 35.</p> <p>N. 0°36' W., on the N. and S. center line of the SW. 1/4 of sec. 26.</p>
6.15	<p>Point at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.</p>
11.59	<p>Point at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.</p>
19.98	<p>Point for the SW 1/16 sec. cor. of sec. 26, at intersection with the E. and W. center line of the SW 1/4 of sec. 26, occupied with a sandstone, 21 x 13 x 5 ins., projecting 7 ins. above ground.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p>T 22 N R 29 E SW 1/16 S 26</p> <p>2004</p>

**Subdivision of Section 26,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Bury the sandstone alongside the stainless steel post.

Set a steel fence post alongside the stainless steel post.

39.96 The center W. 1/16 sec. cor. of sec. 26.

From the center S. 1/16 sec. cor. of sec. 26.

N. 89°30' W., on the E. and W. center line of the SW 1/4 of sec. 26.

19.83 The SW 1/16 sec. cor. of sec. 26.

39.66 The S. 1/16 sec. cor. of secs. 26 and 27.

NW 1/4 Section 26

From the center W. 1/16 sec. cor. of sec. 26.

N. 0°34' W., on the N. and S. center line of the NW 1/4 of sec. 26.

25.32 Point for AP10, sec. 26, at intersection with the right-of-way of Interstate 40, hereinafter described.

38.50 Point for AP1, sec. 26, at intersection with the right of way of Interstate 40, hereinafter described.

39.16 The W. 1/16 sec. cor. of secs. 23 and 26.

**Subdivision of Section 28,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

From the 1/4 sec. cor. of secs. 28 and 33.

N. 0°10' W., on the N. and S. center line of sec. 28.

Over rolling land covered with juniper, pine and sage.

39.91 Point for the center 1/4 sec. cor. of sec. 28, at intersection with the E. and W. center line of sec. 28.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

**Subdivision of Section 28,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 22 N R 29 E
C 1/4 S 28

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

Cor. is located 50 lks. E. of a graded dirt road, 30 ft. wide, bears S. 20° E. and N. 20° W. A two-strand power line runs along the E. side of the road. Cor. is also located 50 lks. N. of dirt road, 15 ft. wide, bears E.

From this cor. point, a local monument, bears S. 25°44' E., 7 lks. dist., monumented with a wood post, 20 ins. sq., firmly set, projecting 6 ins. above ground.

79.86 The 1/4 sec. cor. of secs. 21 and 28.

From the 1/4 sec. cor. of secs. 27 and 28.

S. 89°43' W., on the E. and W. center line of sec. 28.

Over rolling land covered with juniper, pine and sage.

40.08 The center 1/4 sec. cor. of sec. 28.

80.05 The 1/4 sec. cor. of secs. 28 and 29.

**Subdivision of Section 30,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

From the 1/4 sec. cor. of secs. 30 and 31.

N. 0°01' E., on the N. and S. center line of sec. 30.

Over rolling land covered with juniper, pine and sage.

40.38 Point for the center 1/4 sec. cor. of sec. 30, at intersection with the E. and W. center line of sec. 30.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
C 1/4 S 30

2004

**Subdivision of Section 30,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

Cor. is located 10 lks. E. of a barbed wire fence, bears N. and S.

From this cor. point, a local monument, bears S. 4°58' W., 40 lks. dist., monumented with a wood post, 4 ins. sq., firmly set, projecting 6 ins. above ground.

80.56 The 1/4 sec. cor. of secs. 19 and 30.

From the 1/4 sec. cor. of secs. 29 and 30.

N. 89°56' W., on the E. and W. center line of sec. 30.

Over rolling land covered with juniper, pine and sage.

39.99 The center 1/4 sec. cor. of sec. 30.

75.58 The 1/4 sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp.

**Subdivision of Section 32,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

From the 1/4 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp.

N. 0°05' W., on the N. and S. center line of sec. 32.

Over rolling land covered with juniper, pine and sage.

40.07 Point for the center 1/4 sec. cor. of sec. 32, at intersection with the E. and W. center line of sec. 32, falls on the S. edge of a graded dirt road, 25 ft. wide, bears N. 20° E. and S. 20° W.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 54 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
C 1/4 S 32

2004

from which

**Subdivision of Section 32,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 23 ins. in the ground for a reference monument, bears N. 70°00' E., 99 ft. dist., with brass cap mkd. T22N R29E 1/4 S32 99 FT. TO COR. RM 2004 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post alongside the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 20°00' W., 99 ft. dist., with brass cap mkd. T22N R29E 1/4 S32 99 FT. TO COR. RM 2004 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post alongside the stainless steel post.</p>
80.13	<p>The 1/4 sec. cor. of secs. 29 and 32.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 32 and 33.</p> <p>S. 89°25' W., on the E. and W. center line of sec. 32.</p>
40.03	<p>The center 1/4 sec. cor. of sec. 32.</p>
80.06	<p>The 1/4 sec. cor. of secs. 31 and 32.</p> <hr/> <p style="text-align: center;">Subdivision of Section 33, T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp.</p> <p>N. 0°01' W., on the N. and S. center line of sec. 33.</p> <p>Over rolling land covered with juniper, pine and sage.</p>
13.16	<p>Point at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, not monumented.</p>
29.98	<p>Point at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, not monumented.</p>
39.43	<p>Point at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, not monumented.</p>
40.04	<p>Point for the center 1/4 sec. cor. of sec. 33, at intersection with the E. and W. center line of sec. 33, not monumented.</p>

Subdivision of Section 33,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
60.055	Point for the center N. 1/16 sec. cor. of sec. 33, not monumented.
80.07	The 1/4 sec. cor. of secs. 28 and 33.
<hr/>	
From the 1/4 sec. cor. of secs. 33 and 34.	
S. 89°33' W., on the E. and W. center line of sec. 33.	
Over rolling land covered with juniper, pine and sage.	
20.27	Point at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, not monumented.
39.86	Point at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, not monumented.
40.11	The center 1/4 sec. cor. of sec. 33.
60.16	Point for the center W. 1/16 sec. cor. of sec. 33, not monumented.
80.21	The 1/4 sec. cor. of secs. 32 and 33.
<hr/>	
NW 1/4 Section 33	
<hr/>	
From the center W. 1/16 sec. cor. of sec. 33.	
N. 0°01' W., on the N. and S. center line of the NW 1/4 of sec. 33.	
20.015	Point for the NW 1/16 sec. cor. of sec. 33, at intersection with the E. and W. center line of the NW 1/4 of sec. 33, occupied with a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground.
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.	
T 22 N R 29 E NW 1/16 S 33	
2005	
Deposit a magnet, in a white plastic case, at the base of the stainless steel post.	
Deposit the rebar inside the stainless steel post.	

**Subdivision of Section 33,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.03	<p>The W. 1/16 sec. cor. of secs. 28 and 33.</p> <hr/> <p>From the center N. 1/16 sec. cor. of sec. 33.</p> <p>S. 89°34' W., on the E. and W. center line of the NW 1/4 of sec. 33.</p>
20.05	<p>The NW 1/16 sec. cor. of sec. 33.</p>
40.10	<p>The N. 1/16 sec. cor. of secs. 32 and 33.</p> <hr/> <p style="text-align: center;">Subdivision of Section 34, T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp.</p> <p>N. 0°02' E., on the N. and S. center line of sec. 34.</p> <p>Over rolling land covered with juniper, pine and sage.</p>
40.04	<p>Point for the center 1/4 sec. cor. of sec. 34, at intersection with the E. and W. center line of sec. 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E C 1/4 S 34</p> <p style="text-align: center;">2004</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
53.28	<p>Point for AP20, sec. 34, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.</p>
60.06	<p>Point for the center N. 1/16 sec. cor. of sec. 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 34,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>T 22 N R 29 E C N 1/16 S 34 C</p> <p>2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
68.36	<p>True point for AP8, sec. 34, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.</p>
79.27	<p>Point for AP3, sec. 34, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.</p>
80.08	<p>The 1/4 sec. cor. of secs. 27 and 34.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 34 and 35.</p> <p>N. 89°56' W., on the E. and W. center line of sec. 34.</p> <p>Over rolling land covered with juniper, pine and sage.</p>
19.835	<p>Point for the center E. 1/16 sec. cor. of sec. 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 22 N R 29 E E 1/16 C ——— C S 34 </p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
39.67	<p>The center 1/4 sec. cor. of sec. 34.</p>
67.68	<p>Point for AP21, sec. 34, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.</p>
79.71	<p>The 1/4 sec. cor. of secs. 33 and 34.</p> <hr/>

Subdivision of Section 34,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

NE 1/4 Section 34

From the center E. 1/16 sec. cor. of sec. 34.

N. 0°19' E., on the N. and S. center line of the NE 1/4 of sec. 34.

20.015 Point for the NE 1/16 sec. cor. of sec. 34, at intersection with the E. and W. center line of the NE 1/4 of sec. 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
NE 1/16 S 34

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

27.68 Point for AP16, sec. 34, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.

35.25 True point for AP11, sec. 34, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.

40.03 The E. 1/16 sec. cor. of secs. 27 and 34.

From the N. 1/16 sec. cor. of secs. 34 and 35.

N. 89°55' W., on the E. and W. center line of the NE 1/4 of sec. 34.

19.93 The NE 1/16 sec. cor. of sec. 34.

35.43 Point for AP18, sec. 34, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.

39.86 The center N. 1/16 sec. cor. of sec. 34.

SE 1/4 Section 34

From the E. 1/16 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp.

**Subdivision of Section 34,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>N. 0°19' E., on the N. and S. center line of the SE 1/4 of sec. 34.</p>
40.03	<p>The center E. 1/16 sec. cor. of sec. 34.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">NW 1/4 Section 34</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the center N. 1/16 sec. cor. of sec. 34.</p> <p>N. 89°55' W., on the E. and W. center line of the NW 1/4 of sec. 34.</p>
17.56	<p>Point for AP7, sec. 34, at intersection with the right-of-way of Burlington Northern Santa Fe Railroad, hereinafter described.</p>
40.05	<p>The N. 1/16 sec. cor. of secs. 33 and 34.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">Metes-and-Bounds Survey of the Right-of-Way of Interstate 40 T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">In Section 23</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the point for AP1, sec. 23, identical with AP17, sec. 24, on the line bet. secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 22 N R 29 E</p> <p>AP1 AP17</p> <p>S23 ——— S24</p> </div> <p style="text-align: center; margin: 10px 0;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set steel fence post alongside the stainless steel post.</p> <p>Cor. is located 5 lks. N. of a barbed wire fence, bears S. 75° E. and N. 75° W.</p> <p>From this cor. point, the cor. of secs. 23, 24, 25 and 26, bears S. 1°20' W., 1.81 chs. dist., hereinbefore described.</p> <p>N. 89°56' W., on line 1-2.</p>

**Metes-and-Bounds Survey of the Right-of-Way of Interstate 40
T. 22 N., R. 29 E., Gila and Salt River Meridian**

CHAINS	
22.61	<p>AP2, monumented with an angle iron, 4 x 4 ins., firmly set, projecting 26 ins. above ground, mkd. 2101+09.7 HWY R of W.</p> <hr/> <p>N. 89°56' W., on line 2-3.</p>
1.91	<p>Point for AP3, sec. 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E AP3 S23</p> <hr/> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located alongside a barbed wire fence, bears S. 80° E. and N. 80° W.</p> <hr/> <p>S. 89°51' W., on line 3-4.</p>
3.44	<p>Point for AP4, sec. 23, at the Point of Curve.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E AP4 S23</p> <hr/> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 2 lks. N. of a barbed wire fence, bears S. 85° E. and N. 85° W.</p> <hr/> <p>Thence, on line 4-5, along a circular curve to the left, having a central angle of 9°40', a radius of 7789.44 ft., the chord of said arc bears S. 84°27' W., 19.908 chs. dist.</p>
19.932	<p>Point for AP5, sec. 23, on the line bet. secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>

Metas-and-Bounds Survey of the Right-of-Way of Interstate 40
 T. 22 N., R. 29 E., Gila and Salt River Meridian

CHAINS

T 22 N R 29 E
 AP5 S23



S26

2005


Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the cor. of secs. 22, 23, 26 and 27, bears S. 89°53' W., 29.94 chs. dist., hereinbefore described.

In Section 24

From the point for AP1, sec. 24, on the line bet. secs. 19 and 24, on the E. bdy. of the Tp.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.



2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located alongside a barbed wire fence, bears S. 55° E. and N. 55° W.

From this cor. point, an Arizona Department of Transportation right-of-way cor., bears S. 51°23' E., 6.70 chs. dist., monumented with a aluminum disk, 3 ins. diam., firmly set in concrete, with top mkd. ADOT HIGHWAY DIV. An angle iron, 4 X 4 ins., is set alongside, mkd. DOT 2276 + 85 on one side and HWY R OF W on the other.


From this same cor. point, the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., bears S. 1°26' W., 1.79 chs. dist., hereinbefore described.

N. 51°23' W., on line 1-2.


4.36

Point for AP2, sec. 24.

**Metes-and-Bounds Survey of the Right-of-Way of Interstate 40
T. 22 N., R. 29 E., Gila and Salt River Meridian**


CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 38 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 29 E AP2 S24</p>  <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in the middle of a dirt parking area.</p> <hr/> <p>N. 28°42' W., on line 2-3.</p>
3.60	<p>Point for AP3, sec. 24, monumented with a brass disk, 3 ins. diam., firmly set in concrete, with top mkd. ARIZONA HIGHWAY DEPT.</p> <p>An angle iron, 4 x 4 ins., is set alongside the cor. with illegible marks.</p> <hr/> <p>N. 32°59' W., on line 3-4.</p>
3.17	<p>Point for AP4, sec. 24, monumented with a brass disk, 3 ins. diam., firmly set in concrete, with top mkd. ARIZONA HIGHWAY DEPT ELEV + STA.</p> <p>An angle iron, 4 x 4 ins., is set alongside the cor. with illegible marks.</p> <hr/> <p>S. 56°58' W., on line 4-5.</p>
1.51	<p>Point for AP5, sec. 24, monumented with a brass disk, 3 ins. diam., firmly set in concrete, 5 ins. below ground, with top mkd. ARIZONA HIGHWAY DEPT.</p> <hr/> <p>S. 32°59' E., on line 5-6.</p>
2.27	<p>Point for AP6, sec. 24, determined by the remains of a cement collar.</p> <p>At the corner point</p>

Metes-and-Bounds Survey of the Right-of-Way of Interstate 40
T. 22 N., R. 29 E., Gila and Salt River Meridian

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E</p> <div style="text-align: center;">  </div> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury remains of cement collar alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 43°42' W., on line 6-7.</p>
<p>0.84</p>	<p>Point for AP7, sec. 24, determined by a collar of cement, with a depression, 6 ins. diam., in the middle.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E</p> <div style="text-align: center;">  </div> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury cement collar alongside the stainless steel post.</p> <p>An angle iron, 4 x 4 ins., is alongside the cor., mkd. POT 1+00.00 on a side and HWY R OF W on another.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 88°13' W., on line 7-8.</p>
<p>1.52</p>	<p>Point for AP8, sec. 24, determined by remnants of a cement collar.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 29 ins. in the ground, with brass cap mkd.</p>

Metes-and-Bounds Survey of the Right-of-Way of Interstate 40
 T. 22 N., R. 29 E., Gila and Salt River Meridian

CHAINS



Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Bury cement collar alongside the stainless steel post.

Cor. is located in parking area of Houck Chapter House.

S. 1°42' W., on line 8-9.

1.51 Point for AP9, sec. 24, monumented with a brass disk, 3 ins. diam., firmly set in concrete, with top mkd. ARIZONA HIGHWAY DEPT ELEV + STA.


An angle iron, 4 x 4 ins., is set alongside the cor., mkd. POT 0+00.00 on a side and HWY R OF W on another.

S. 88°18' E., on line 9-10.

3.03 Point for AP10, sec. 24, determined by a concrete form, 6 ins. diam., with no brass disk.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with top mkd.



Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Bury remains of concrete form alongside the stainless steel post.

An angle iron, 4 x 4 ins., is set alongside the cor., mkd. POT 2+00.00 on a side and HWY R OF W on another.

Metes-and-Bounds Survey of the Right-of-Way of Interstate 40
T. 22 N., R. 29 E., Gila and Salt River Meridian

CHAINS	
2.63	<p>S. 29°23' W., on line 10-11.</p> <p>Point for AP11, sec. 24, monumented with a brass disk, 3 ins. diam., firmly set in a concrete form, 6 ins. diam., projecting 8 ins. above ground, with top mkd. ARIZONA HIGHWAY DEPT ELEV + STA.</p> <p>An angle iron, 4 x 4 ins., is set alongside the cor., mkd. POC 2268+50.0 on a side and HWY R of W on another.</p>
4.49	<p>S. 42°13' W., on line 11-12.</p> <p>Point for AP12, sec. 24, monumented with a brass disk, 3 ins. diam., firmly set, in concrete form, 6 ins. diam., projecting 6 ins. above ground, with top mkd. ARIZONA HIGHWAY DEPT ELEV + STA.</p> <p>An angle iron, 4 x 4 ins., is set alongside the cor., mkd. POC 2266+60.00 on a side and HWY R OF W on another.</p>
0.64	<p>S. 60°46' W., on line 12-13.</p> <p>Point for AP13, sec. 24, identical with AP1, sec. 25, on the line bet. secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 29 E</p> <p>AP13 S24</p> <hr style="width: 100px; margin: 0 auto;"/> <p>AP1 S25</p> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located alongside a barbed wire fence, bears N. 60° E. and S. 60° W.</p> <p>From this cor. point, the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., bears N. 87°20' E., 10.83 chs. dist., hereinbefore described.</p> <hr style="width: 100%; margin-top: 20px;"/> <p>From the point for AP14, sec. 24, identical with AP7, sec. 25, on the line bet. secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Metes-and-Bounds Survey of the Right-of-Way of Interstate 40
T. 22 N., R. 29 E., Gila and Salt River Meridian

CHAINS

T 22 N R 29 E
S24 AP14

AP7
S25

2005

Cor. is located 8 lks. N. of a barbed wire fence, bears S. 75° E. and N. 75° W.

From this cor. point, the 1/4 sec. cor. of secs. 24 and 25, bears N. 87°20' E., 1.09 chs. dist., hereinbefore described.

N. 89°56' W., on line 14-15.

8.68

Point for AP15, sec. 24, at intersection with the N. and S. center line of the SE 1/4 of the SW 1/4 of sec. 24.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
AP15 S24



2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located 7 lks. N. of a new barbed wire fence and 5 lks. N. of an old barbed wire fence, bears S. 75° E. and N. 75° W.

From this cor. point, the E-W 1/64 sec. cor. of secs. 24 and 25, bears S. 1°22' W., 0.41 ch. dist., hereinbefore described.

N. 89°56' W., on line 15-16.

9.78

Point for AP16, sec. 24, at intersection with the N. and S. center line of the SW 1/4 of sec. 24.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

Metes-and-Bounds Survey of the Right-of-Way of Interstate 40
T. 22 N., R. 29 E., Gila and Salt River Meridian

CHAINS	
	<p style="text-align: center;">T 22 N R 29 E AP16 S24</p>  <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 6 lks. N. of a barbed wire fence, bears S. 75° E. and N. 75° W.</p> <p>From this cor. point, the W. 1/16 sec. cor. of secs. 24 and 25, bears S. 1°22' W., 0.88 ch. dist., hereinbefore described.</p> <hr/> <p>N. 89°56' W., on line 16-17.</p>
19.55	<p>AP17, sec. 24, identical with AP1, sec. 23, on the line bet. secs. 23 and 24.</p> <hr/> <p style="text-align: center;">In Section 25</p> <hr/> <p>From AP1, sec. 25, identical with AP13, sec. 24, on the line bet. secs. 24 and 25.</p> <p>S. 60°46' W., on line 1-2.</p>
2.19	<p>Point for AP2, sec. 25, monumented with a brass disk, firmly set, in a concrete form, 6 ins. diam., 6 ins. below ground, with top mkd. ARIZONA HIGHWAY DEPT ELEV + STA.</p> <p>An angle iron, 4 x 4 ins., is set alongside the cor., mkd. POC 2265+00.00 on a side and HWY R OF W on another.</p> <hr/> <p>S. 68°48' W., on line 2-3.</p>
3.28	<p>Point for AP3, sec. 25, falls in the N. edge of road, asphalt, 15 ft. wide, bears N. 80° E. and S. 80° W.</p> <p>Set a railroad spike, flush with the surface of asphalt.</p> <p>from which</p>

Metes-and-Bounds Survey of the Right-of-Way of Interstate 40
T. 22 N., R. 29 E., Gila and Salt River Meridian

CHAINS

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground for a reference monument, bears N. 45°36' E., 50 ft. dist. with brass cap mkd. T22N R29E AP3 S25 RM 50 FT. TO COR. and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 44°14' W., 50 ft. dist. with brass cap mkd. T22N R29E AP3 S25 RM 50 FT. TO COR. and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.


N. 83°09' W., on line 3-4.

3.85

Point for AP4, sec. 25, at intersection with the N. and S. center line of the NE 1/4 of sec. 25.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
AP4 S25



2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located 9 lks. S. of a barbed wire fence, bears S. 80° E. and N. 80° W.

From this cor. point, the E. 1/16 sec. cor. of secs. 24 and 25, bears N. 1°28' E., 1.38 chs. dist., hereinbefore described.

N. 83°09' W., on line 4-5.

3.43

Point for AP5, sec. 25.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Mates-and-Bounds Survey of the Right-of-Way of Interstate 40
 T. 22 N., R. 29 E., Gila and Salt River Meridian

CHAINS	
	<p style="text-align: center;">T 22 N R 29 E AP5 S25</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located 38 lks. E. of left bank of Black Creek, 25 ft. wide, drains S. 10° W.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89°56' W., on line 5-6.</p>
16.13	<p>Point for AP6, sec. 25, at intersection with the N. and S. center line of sec. 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 29 E AP6 S25</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located 6 lks. N. of a barbed wire fence bears S. 75° E. and N. 75° W.</p> <p>From this cor. point, the 1/4 sec. cor. of secs. 24 and 25, bears N. 1°29' E., 6 lks. dist.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89°56' W., on line 6-7.</p>
1.10	<p>AP7, sec. 25, identical with AP 14, sec. 24, on the line bet. secs. 24 and 25.</p> <hr style="width: 20%; margin: auto;"/> <p>From the point for AP8, sec. 25, identical with AP13, sec. 26, on the line bet. secs. 25 and 26.</p>

Metes-and-Bounds Survey of the Right-of-Way of Interstate 40
T. 22 N., R. 29 E., Gila and Salt River Meridian

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T 22 N R 29 E

2005

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Set a steel fence post alongside the stainless steel post.

Cor. is located alongside a barbed wire fence, bears E. and W.

From this cor. point, the cor. of secs. 23, 24, 25 and 26, bears
N. 3°21' W., 3.68 chs. dist., hereinbefore described.

S. 89°56' E., on line 8-9.

19.44

Point for AP9, sec. 25, at intersection with the N. and S.
center line of the NW 1/4 of sec. 25.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
28 ins. in the ground, with brass cap mkd.

T 22 N R 29 E

2005

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Set a steel fence post alongside the stainless steel post.

Cor. is located alongside a barbed wire fence, bears E. and W.

From this cor. point, the W. 1/16 sec. cor. of secs. 24 and 25,
bears N. 0°57' W., 4.61 chs. dist., hereinbefore described.

S. 89°56' E., on line 9-10.

9.69


Point for AP10, sec. 25, at intersection with the N. and S.
center line of the NE 1/4 of the NW 1/4 of sec. 25.

Metes-and-Bounds Survey of the Right-of-Way of Interstate 40
T. 22 N., R. 29 E., Gila and Salt River Meridian

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 22 N R 29 E



2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

Cor. is located alongside a barbed wire fence, bears E. and W.


From this cor. point, the NE-NW 1/64 sec. cor. of sec. 25, bears S. 0°16' W., 4.81 chs. dist., hereinbefore described.

S. 89°56' E., on line 10-11.

9.67 Point for AP11, sec. 25, at intersection with the N. and S. center line of sec. 25.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N R 29 E



2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

Cor. is located alongside a barbed wire fence, bears E. and W.

From this cor. point, the center N-N 1/64 sec. cor. of sec. 25, bears S. 1°29' W., 4.315 chs. dist., hereinbefore described.


S. 89°56' E., on line 11-12.

11.49 Point for AP12, sec. 25.

**Metes-and-Bounds Survey of the Right-of-Way of Interstate 40
T. 22 N., R. 29 E., Gila and Salt River Meridian**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E AP12 S25</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located alongside an angle iron, 4 x 4 ins., mkd. PC 2148+00.00 HWY R OF W.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 0°25' W., on line 12-13.</p>
<p>0.75</p>	<p>Point for AP13, sec. 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E AP13 S25</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 89°35' E., on line 13-14.</p>
<p>4.81</p>	<p>Point for AP14, sec. 25, monumented with a brass disk, firmly set in a concrete form, 6 ins. diam., flush with surface of the ground, with top mkd. ARIZONA HIGHWAY DEPT ELEV + STA.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 0°08' W., on line 14-15.</p>
<p>0.75</p>	<p>Point for AP15, sec. 25, monumented with a brass disk, firmly set in a concrete form, 6 ins. diam., projecting 1 in. above ground, with top mkd. ARIZONA HIGHWAY DEPT.</p>

Metes-and-Bounds Survey of the Right-of-Way of Interstate 40
T. 22 N., R. 29 E., Gila and Salt River Meridian

CHAINS	
	<p>An angle iron, 4 x 4 ins., is set alongside the cor., mkd. POT 1964+ FD BK HWY R OF W.</p> <hr/>
	<p>S. 89°49' E., on line 15-16.</p>
3.26	<p>Point for AP16, sec. 25, at intersection with the N. and S. center line of the NE 1/4 of sec. 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 29 E</p> <div style="text-align: center;">  </div> <p style="text-align: center;">2005</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>From this cor. point, the E. 1/16 sec. cor. of secs. 24 and 25, bears N. 1°28' E., 6.50 chs. dist., hereinbefore described.</p> <hr/>
	<p>S. 89°49' E., on line 16-17.</p>
1.18	<p>Point for AP17, sec. 25, monumented with a brass disk, 3 ins. diam., firmly set in a concrete form, 6 ins. diam., projecting 5 ins. above ground, with top mkd. ARIZONA HIGHWAY DEPT ELEV + STA.</p> <p>An angle iron, 4 x 4 ins., is set alongside the cor., mkd. POC 2261+20.00 HWY R OF W.</p> <hr/>
	<p>S. 65°27' E., on line 17-18.</p>
6.58	<p>Point for AP18, sec. 25, monumented with a brass disk, 3 ins. diam., firmly set in a concrete form, 6 ins. diam., projecting 2 ins. above ground, with top mkd. ARIZONA HIGHWAY DEPT ELEV + STA.</p> <p>An angle iron, 4 x 4 ins., is set alongside the cor., mkd. POC 2265+20.00 HWY R OF W.</p> <hr/>
	<p>S. 41°27' E., on line 18-19.</p>

Metes-and-Bounds Survey of the Right-of-Way of Interstate 40
T. 22 N., R. 29 E., Gila and Salt River Meridian

CHAINS	
6.97	<p>Point for AP19, sec. 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E</p> <p style="text-align: center;">AP19 S25</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 1 lk. W. of a barbed wire fence, bears S. 40° E. and N. 40° W.</p> <hr style="width: 20%; margin: 10px auto;"/>
2.41	<p>S. 1°53' W., on line 19-20.</p> <p>Point for AP20, sec. 25, monumented with a brass disk, 3 ins. diam., firmly set in a concrete form, 6 ins. diam., projecting 4 ins. above ground, with top mkd. ARIZONA HIGHWAY DEPT ELEV + STA.</p> <p>An angle iron, 4 x 4 ins., is set alongside the cor., mkd. PT 2461.78 HWY R OF W.</p> <hr style="width: 20%; margin: 10px auto;"/>
6.64	<p>S. 55°34' W., on line 20-21.</p> <p>Point for AP21, sec. 25, determined by a collar of cement, with a depression, 6 ins. diam., in the middle.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E</p> <p style="text-align: center;">AP21 S25</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the cement collar alongside the stainless steel post.</p>

Metes-and-Bounds Survey of the Right-of-Way of Interstate 40
T. 22 N., R. 29 E., Gila and Salt River Meridian

CHAINS	
	<p>An angle iron, 4 x 4 ins., is set alongside the cor., mkd. POT 26+00.00 HWY R OF W.</p> <hr/> <p>S. 34°23' E., on line 21-22.</p>
1.51	<p>Point for AP22, sec. 25, monumented with a brass disk, firmly set in a concrete form, 6 ins. diam., with top mkd. ARIZONA HIGHWAY DEPT.</p> <p>An angle iron, 4 x 4 ins., is set alongside the cor., mkd. POT 26+00.00 HWY R OF W.</p> <hr/> <p>N. 55°34' E., on line 22-23.</p>
6.64	<p>Point for AP23, sec. 25, identical with the Point of Tangency, monumented with a brass disk, 3 ins. diam., firmly set in a concrete form, 6 ins. diam., 6 ins. below ground, with top mkd. ARIZONA HIGHWAY DEPT ELEV + STA.</p> <p>An angle iron, 4 x 4 ins., is set alongside the cor., mkd. PT 21+61.78 HWY R OF W.</p> <hr/> <p>Thence, on line 23-24, along a circular curve to the left, having a central angle of 53°28', a radius of 368.31 ft., the chord of said arc bears N. 28°50' E., 5.021 chs. dist.</p>
5.208	<p>Point for AP24, sec. 25, identical with the Point of Curvature, monumented with a brass disk, 3 ins. diam., firmly set in a concrete form, 6 ins. diam., 3 ins. below ground, with top mkd. ARIZONA HIGHWAY DEPT.</p> <p>An angle iron, 4 x 4 ins., is set alongside the cor., mkd. PC 18+64.56 HWY R OF W.</p> <hr/> <p>S. 86°36' E., on line 24-25.</p>
2.95	<p>Point for AP25, sec. 25, monumented with a brass disk, 3 ins. diam., firmly set in a concrete form, 6 ins. diam., flush with the ground, with top mkd. ARIZONA HIGHWAY DEPT ELEV + STA.</p> <p>An angle iron, 4 x 4 ins., is set alongside the cor., mkd. POC 2272+50 HWY R OF W.</p> <hr/> <p>N. 57°02' E., on line 25-26.</p>
1.75	<p>Point for AP26, sec. 25, on the line bet. secs. 25 and 30, on the E. bdy. of the Tp.</p>

Metes-and-Bounds Survey of the Right-of-Way of Interstate 40
T. 22 N., R. 29 E., Gila and Salt River Meridian

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 22 N
 R 29 E R 30 E

 AP26 S30
 S25

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located alongside a barbed wire fence, bears S. 85° E. and N. 85° W.

From this cor. point, the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., bears N. 1°26' E., 13.87 chs. dist., hereinbefore described.

From this same cor. point, an Arizona Highway Department of Transportation right-of-way cor., bears N. 57°02' E., 4.33 chs. dist., monumented with a brass disk, 3 ins. diam., firmly set in a concrete form, 6 ins. diam., flush with the ground, with top mkd. ARIZONA HIGHWAY DEPT ELEV + STA. An angle iron, 4 x 4 ins., is set alongside the cor., mkd. POC 2275+80 HWY R OF W.

In Section 26

From the point for AP1, sec. 26, at intersection with the N. and S. center line of the NW 1/4 of sec. 26.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
 AP1
 S26 

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the W. 1/16 sec. cor. of secs. 23 and 26, bears N. 0°34' W., 66 lks. dist., hereinbefore described.

N. 88°37' W., on line 1-2.

**Metes-and-Bounds Survey of the Right-of-Way of Interstate 40
T. 22 N., R. 29 E., Gila and Salt River Meridian**

CHAINS	
0.63	<p>Point for AP2, sec. 26, monumented with a brass disk, 3 ins. diam., firmly set in a concrete form, 6 ins. diam., projecting 5 ins. above ground, with top mkd. ARIZONA HIGHWAY DEPT.</p>
	<p>An angle iron, 4 x 4 ins., is set alongside the cor., with illegible marks.</p>
	<hr/> <p>S. 9°56' E., on line 2-3.</p>
1.88	<p>Point for AP3, sec. 26, monumented with a brass disk, 3 ins. diam., firmly set in a concrete form, 6 ins. diam., projecting 4 ins. above ground, with top mkd. ARIZONA HIGHWAY DEPT.</p>
	<p>An angle iron, 4 x 4 ins., is set alongside the cor., mkd. POC 2083+50.00 HWY R OF W.</p>
	<hr/> <p>Thence, on line 3-4, along a circular curve to the left, having a central angle of 4°37', a radius of 7789.44 ft., the chord of said arc bears S. 71°55' W., 9.515 chs. dist.</p>
9.517	<p>Point for AP4, sec. 26.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 22 N R 29 E AP4 S26</p> <hr/> <p align="center">2005</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Set a steel fence post alongside the stainless steel post.</p>
	<p>Cor. is located alongside a barbed wire fence, bears N. 65° E. and S. 65° W.</p>
	<hr/> <p>S. 69°03' W., on line 4-5.</p>
3.44	<p>Point for AP5, sec. 26.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, in a supporting mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>

Metes-and-Bounds Survey of the Right-of-Way of Interstate 40
T. 22 N., R. 29 E., Gila and Salt River Meridian

CHAINS

T 22 N R 29 E
AP5 S26

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

S. 68°39' W., on line 5-6.

7.34

Point for AP6, sec. 26, on the line bet. secs. 26 and 27.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
AP6

S27 |
—| S26

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

From this cor. point, an Arizona Highway Department of Transportation right-of-way cor., bears S. 68°39' W., 25.18 chs. dist., monumented with a brass disk, 3 ins. diam., firmly set in a concrete form, 6 ins. diam., 6 ins. below ground, with top mkd. ARIZONA HIGHWAY DEPT. An angle iron, 4 x 4 ins., is set alongside the cor., mkd. POC 2050+00.00 HWY R OF WAY.

From this same cor. point, the cor. of secs. 22, 23, 26 and 27, bears N. 0°09' W., 9.30 chs. dist., hereinbefore described.

From the point for AP7, sec. 26, on the line bet. secs. 26 and 27.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Metes-and-Bounds Survey of the Right-of-Way of Interstate 40
T. 22 N., R. 29 E., Gila and Salt River Meridian

CHAINS

T 22 N R 29 E

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, a local monument, bears S. $71^{\circ}32'$ W., 10.13 chs. dist., monumented with a rebar, 1/2 in. diam., firmly set in concrete. An angle iron, 4 x 4 ins., is set alongside the cor., mkd. POT 2055+00.00 HWY R OF WAY.

From this same cor. point, the cor. of secs. 22, 23, 26 and 27, bears N. $0^{\circ}09'$ W., 18.51 chs. dist., hereinbefore described.

N. $71^{\circ}32'$ E., on line 7-8.

5.01 Point for AP8, sec. 26, monumented with a brass disk, 3 ins. diam., firmly set in a concrete form, 6 ins. diam., projecting 5 ins. above ground, with top mkd. ARIZONA HIGHWAY DEPT.

An angle iron, 4 x 4 ins., is set alongside the cor., mkd. POT 2065+00.00 HWY R OF W.

N. $76^{\circ}57'$ E., on line 8-9.

13.70 Point for AP9, sec. 26, monumented with a brass disk, 3 ins. diam., firmly set in a concrete form, 6 ins. diam., projecting 8 ins. above ground, with top mkd. ARIZONA HIGHWAY DEPT.

An angle iron, 4 x 4 ins., is set alongside the cor., mkd. POT 2074+00.00 HWY R OF W.

N. $88^{\circ}54'$ E., on line 9-10.

1.40 Point for AP10, sec. 26, at intersection with the N. and S. center line of the NW 1/4 of sec. 26.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Metes-and-Bounds Survey of the Right-of-Way of Interstate 40
T. 22 N., R. 29 E., Gila and Salt River Meridian

CHAINS

T 22 N R 29 E



AP10 | S26

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located alongside a barbed wire fence, bears N. 85° E. and S. 85° W.

From this cor. point, the W. 1/16 sec. cor. of secs. 23 and 26, bears N. 0°34' W., 13.84 chs. dist., hereinbefore described.

From this same cor. point, an Arizona Highway Department of Transportation right-of-way cor., bears N. 88°54' E., 4.945 chs. dist., monumented with a brass disk, 3 ins. diam., firmly set in concrete, 4 ins. diam., 6 ins. high, with top mkd. ARIZONA HIGHWAY DEPT. An angle iron, 4 x 4 ins., is set alongside the cor., mkd. POT 2078+00.00 HWY R OF W.

From the point for AP11, sec. 26, at intersection with the N. and S. center line of the NE 1/4 of sec. 26.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

T 22 N R 29 E



AP11 | S26

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, an Arizona Highway Department of Transportation right-of-way cor., bears S. 86°57' W., 7.84 chs. dist., monumented with a brass disk, 3 ins. diam., firmly set in concrete, 6 ins. diam., 4 ins. high, with top mkd. ARIZONA HIGHWAY DEPT. An angle iron, 4 x 4 ins., is set alongside the cor., mkd. 2096+65.54 HWY R OF W.

From this same cor. point, the E. 1/16 sec. cor. of secs. 23 and 26, bears N. 2°10' W., 3.87 chs. dist., hereinbefore described.

N. 86°57' E., on line 11-12.

Metes-and-Bounds Survey of the Right-of-Way of Interstate 40
T. 22 N., R. 29 E., Gila and Salt River Meridian

CHAINS					
4.63	<p>Point for AP12, sec. 26, monumented with a brass disk, 3 ins. diam., firmly set in a concrete form, 6 ins. diam., projecting 2 ins. above ground, with top mkd. ARIZONA HIGHWAY DEPT.</p> <p>An angle iron, 4 x 4 ins., is set alongside the cor., mkd. PT 2105+00.35 HWY R OF W.</p> <hr/> <p>S. 89°56' E., on line 12-13.</p>				
14.86	<p>Point for AP13, sec. 26, identical with AP8, sec. 25, on the line bet. secs. 25 and 26.</p> <hr/> <p style="text-align: center;">In Section 32</p> <hr/> <p>From the point for AP1, sec. 32, on the line bet. secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 29 E</p> <table border="0" style="margin: auto;"> <tr> <td style="padding: 0 5px;">AP1</td> <td style="border-left: 1px solid black; padding: 0 5px;">S33</td> </tr> <tr> <td style="padding: 0 5px;">S32</td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> </tr> </table> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of secs. 32 and 33, bears N. 0°01' W., 6.60 chs. dist., hereinbefore described.</p> <p>From this same cor. point, an Arizona Highway Department of Transportation right-of-way cor., along a circular curve to the right, having a central angle of 19°02', a radius of 1007.22, the chord of said arc bears S. 61°02' E., 5.048 chs. dist., is monumented with a brass disk, 3 ins. diam., firmly set in a concrete form, 6 ins. diam., flush with the ground, with top mkd. ARIZONA HIGHWAY DEPT ELEV + STA. An angle iron, 4 x 4 ins., is set alongside the cor. with illegible marks.</p> <p>Thence, on line 1-2, along a circular curve to the left, having a central angle of 15°52', a radius of 1007.22 ft., the chord of said arc bears N. 78°29' W., 4.212 chs. dist.</p>	AP1	S33	S32	
AP1	S33				
S32					
4.226	<p>Point for AP2, sec. 32, identical with the Point of Curvature, monumented with a brass disk, 3 ins. diam., firmly set in concrete form, 6 ins. diam., projecting 4 ins. above ground, with top mkd. ARIZONA HIGHWAY DEPT ELEV + STA.</p>				

Metes-and-Bounds Survey of the Right-of-Way of Interstate 40
T. 22 N., R. 29 E., Gila and Salt River Meridian

CHAINS	
	<p>An angle iron, 4 x 4 ins., is set alongside the cor., mkd. PC 566+67 HWY R OF W.</p> <hr/>
3.28	<p>N. 86°25' W., on line 2-3.</p> <p>Point for AP3, sec. 32, monumented with a brass disk, 3 ins. diam., firmly set in concrete form, 6 ins. diam., flush with ground, with top mkd. ARIZONA HIGHWAY DEPT ELEV + STA.</p>
	<p>An angle iron, 4 x 4 ins., is set alongside the cor., mkd. POT 350+00 HWY R OF W.</p> <hr/>
1.51	<p>S. 3°35' W., on line 3-4.</p> <p>Point for AP4, sec. 32, occupied with the remnants of a cement collar.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 29 E AP4 S32</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury remnants of cement collar alongside the stainless steel post.</p> <hr/>
	<p>S. 86°25' E., on line 4-5.</p>
3.28	<p>Point for AP5, sec. 32, identical with Point of Curvature.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 29 E AP5 S32</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Metes-and-Bounds Survey of the Right-of-Way of Interstate 40
T. 22 N., R. 29 E., Gila and Salt River Meridian

CHAINS

From this cor. point, an Arizona Highway Department of Transportation right-of-way cor., erroneously set, bears S. 3°11' W., 38 lks. dist., monumented with a brass disk, 3 ins. diam., firmly set in a concrete form, 6 ins. diam., 6 ins. above ground, with top mkd. ARIZONA HIGHWAY DEPT ELEV + STA. An angle iron, 4 x 4 ins., is set alongside the cor., mkd. PC 5+66.67 HWY R OF W.

Thence, on line 5-6, along a circular curve to the right, having a central angle of 18°07', a radius of 907.22 ft., the chord of said arc bears S. 77°22' E., 4.330 chs. dist.

4.348

Point for AP6, sec. 32, on the line bet. secs. 32 and 33.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N R 29 E

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, a local monument, bears S. 67°33' E., 13 lks. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with a aluminum cap on top mkd. GREER ENGR CO LS 5704.

From this same cor. point, an Arizona Highway Department of Transportation right-of-way cor., along a circular curve to the right, having a central angle of 16°47', a radius of 907.22, the chord of said arc bears S. 59°55' E., 4.014 chs. dist., is monumented with a brass disk, 3 ins. diam., firmly set in a concrete form, 6 ins. diam., projecting 4 ins. above ground, with top mkd. ARIZONA HIGHWAY DEPT ELEV + STA. An angle iron, 4 x 4, is lying loose on the ground alongside the cor., with illegible marks.


From this same cor. point, the 1/4 sec. cor. of secs. 32 and 33, bears N. 0°01' W., 8.21 chs. dist., hereinbefore described.

From the point for AP7, sec. 32, on the line bet. secs. 32 and 33.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Metes-and-Bounds Survey of the Right-of-Way of Interstate 40
T. 22 N., R. 29 E., Gila and Salt River Meridian

CHAINS



Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located alongside a barbed wire fence, bears N. 35° E. and S. 35° W.

From this cor. point, an Arizona Highway Department of Transportation right-of-way cor., bears N. 34°13' E., 7.23 chs. dist., monumented with a brass disk, 3 ins. diam., firmly set in a concrete form, 6 ins. diam., flush with the ground, with top mkd. ARIZONA HIGHWAY DEPT ELEV + STA. An angle iron, 4 x 4 ins., is set alongside the cor., mkd. POT 1933+25 HWY R OF W.


From this same cor. point, the 1/4 sec. cor. of secs. 32 and 33, bears N. 0°01' W., 16.67 chs. dist., hereinbefore described.

S. 34°13' W., on line 7-8.

12.93

Point for AP8, sec. 32.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.



Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located alongside a barbed wire fence, bears N. 35° E. and S. 35° W.

S. 38°32' W., on line 8-9.

16.44

Point for AP9, sec. 32, on the line bet. secs. 32 and 5, on the S. bdy. of the Tp.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

Metes-and-Bounds Survey of the Right-of-Way of Interstate 40
T. 22 N., R. 29 E., Gila and Salt River Meridian

CHAINS

T 22 N R 29 E
AP9 S32

S5
T21N

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located alongside a barbed wire fence, bears N. 40° E. and S. 40° W.

From this cor. point, the cor. of secs. 5, 4, 32 and 33, on the S. bdy. of the Tp., bears N. 89°22' E., 17.52 chs. dist., hereinbefore described.

From this same cor. point, an Arizona Highway Department of Transportation right-of-way cor., bears S. 38°32' W., 2.11 chs. dist., monumented with a brass disk, 3 ins. diam., firmly set in a concrete form, 6 ins. diam., projecting 2 ins. above ground, with top mkd. ARIZONA HIGHWAY DEPT ELEV + STA. An angle iron, 4 x 4 ins., is set alongside the cor., mkd. PT 1907+73.57 HWY R OF W.

From the point for AP10, sec. 32, on the line bet. secs. 32 and 5, on the S. bdy. of the Tp.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
S32 AP10

S5
T21N

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located alongside a barbed wire fence, bears N. 45° E. and S. 45° W.

From this cor. point, the cor. of secs. 5, 4, 32 and 33, on the S. bdy. of the Tp., bears N. 89°22' E., 7.02 chs. dist., hereinbefore described.

**Metes-and-Bounds Survey of the Right-of-Way of Interstate 40
T. 22 N., R. 29 E., Gila and Salt River Meridian**

CHAINS

10.23

From this same cor. point, an Arizona Highway Department of Transportation right-of-way cor., bears S. 43°17' W., 23.42 chs. dist., monumented with an angle iron, 4 x 4 ins., firmly set, projecting 24 ins. above ground, mkd. PT 1898+45.4 HWY RW.

N. 43°17' E., on line 10-11.

Point for AP11, sec. 32, on the line bet. secs. 32 and 33.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N R 29 E

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located 1 lk. S. of a barbed wire fence, bears N. 40° E. and S. 40° W.

From this cor. point, an Arizona Highway Department of Transportation right-of-way cor., bears N. 43°17' E., 53 lks. dist., monumented with a brass disk, 3 ins. diam., firmly set in a concrete form, 6 ins. diam., projecting 2 ins. above ground, with top mkd. ARIZONA HIGHWAY DEPT ELEV + STA. An angle iron, 4 x 4 ins., is set alongside the cor., mkd. POT 1921+00.00 HWY RW.

From this same cor. point, the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., bears S. 0°01' E., 7.37 chs. dist., hereinbefore described.

**Metes-and-Bounds Survey of the Right-of-Way of Burlington
Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**


In Section 25

From the point for AP27, sec. 25, on the line bet. secs. 25 and 30, on the E. bdy. of the Tp.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.

Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS



2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

Cor. is located 12 lks., N. 35° W., from the intersection of barbed wire fences, bearing N., E. and W.


From this cor. point, the 1/4 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp., bears N. 0°17' E., 12.08 chs. dist., hereinbefore described.

S. 84°19' W., on line 27-28.

19.84

Point for AP28, sec. 25, at intersection with the N. and S. center line of the SE 1/4 of sec. 25.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.



2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

Cor. is located 12 lks. N. of a woven wire fence, bears E. and W.

From this cor. point, the center E. 1/16 sec. cor. of sec. 25, bears N. 0°52' E., 12.79 chs. dist., hereinbefore described.

S. 84°19' W., on line 28-29.

14.43

Point for AP43, sec. 25, hereinafter described.

**Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**


CHAINS

19.86

Point for AP 29, sec. 25, at the intersection with the N. and S. center line of sec. 25.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 40 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
AP29 S25



2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located in a traffic area of the Arizona Silica Sand Company.

From this cor. point, the center 1/4 sec. cor. of sec. 25, bears N. 1°29' E., 13.50 chs. dist., hereinbefore described.

S. 84°19' W., on line 29-30.

8.90

Point for AP30, sec. 25, at the intersection with the N. and S. center line of the NE 1/4 of the SW 1/4 of sec. 25.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
AP30 S25



2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

Cor. is located alongside a waste water pond.

From this cor. point, the center E-W 1/64 sec. cor. of sec. 25, bears N. 1°04' E., 13.80 chs. dist., hereinbefore described.

S. 84°19' W., on line 30-31.

4.22

Point for AP31, sec. 25, identical with the Point of Curvature.

**Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
28 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
AP31 S25

2005

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Set a steel fence post alongside the stainless steel post.

Thence, on line 31-32, along a circular curve to the left,
having a central angle of 3°05', a radius of 5743.11 ft., the
chord of said arc bears S. 82°46' W., 4.688 chs. dist.

4.688

True point for AP32, sec. 25, at the intersection with the N.
and S. center line of the SW 1/4 of sec. 25, falls in a waste
water pond, where it is impracticable to establish a permanent
monument.

From this true point, the point selected for the witness cor. to
AP32, sec. 25, bears N. 45°56' E., 37 lks. dist.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
25 ins. in the ground, with brass cap mkd.

WC
T 22 N R 29 E
AP32 S25

2005

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Set a steel fence post alongside the stainless steel post.

Thence, on line 32-33, along a circular curve to the left,
having a central angle of 0°18', a radius of 5743.11 ft., the
chord of said arc bears S. 81°04' W., 0.455 chs. dist.

0.455


True point for AP33, sec. 25, identical with the Point of
Tangency, falls in a waste water pond, where it is impracticable
to establish a permanent monument.

Mates-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

From this true point, the point selected for the witness cor. to AP33, sec. 25, bears N. 43°38' W., 58 lks. dist.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.



Deposit a magnet, in a white plastic case, at the base of the stainless steel post.


Set a steel fence post alongside the stainless steel post.

S. 80°55' W., on line 33-34.

6.56 Point for AP53, sec. 25, hereinafter described.

17.47 Point for AP34, sec. 25, identical with AP14, sec. 26, on the line bet. secs. 25 and 26.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.



Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located 12 lks. N. of a barbed wire fence, bears N. 80° E. and S. 80° W.


From this cor. point, the 1/4 sec. cor. of secs. 25 and 26, bears N. 0°08' W., 15.90 chs. dist.

From the point for AP35, sec. 25, identical with AP30, sec. 26, on the line bet. secs. 25 and 26.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Metas-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS



2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located 13 lks. N. of a barbed wire fence, bears N. 80° E. and S. 80° W.

From this cor. point, the cor. of secs. 25, 26, 35 and 36, bears S. 0°08' E., 17.73 chs. dist.


N. 80°55' E., on line 35-36.

17.84

True point for AP36, sec. 25, at the intersection with the N. and S. center line of the SW 1/4 of sec. 25, falls in the Rio Puerco River, 100 ft. wide, drains N. 70° W., where it is impracticable to establish a permanent monument.

From this true point, the point selected for the witness cor. to AP36, sec. 25, bears N. 44°54' W., 1.32 chs. dist.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.



2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

From this cor. point, the W. 1/16 sec. cor. of secs. 25 and 36, bears S. 0°39' W., 18.19 chs. dist.

N. 80°55' E., on line 36-37.

0.58

True point for AP37, sec. 35, identical with the Point of Tangency, falls in the Rio Puerco River, 100 ft. wide, drains N. 70° W., where it is impracticable to establish a permanent monument.


**Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this true point, the point selected for the witness cor. to AP37, sec. 25, bears N. 55°40' E., 2.19 chs. dist.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

WC
T 22 N R 29 E



AP37 S25

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

Thence, on line 37-38, along a circular curve to the right, having a central angle of 3°23', a radius of 5343.11 ft., the chord of said arc bears N. 82°37' E., 4.784 chs. dist.

4.785 Point for AP38, sec. 25, identical with the Point of Curvature.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T 22 N R 29 E



AP38 S25

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

N. 84°19' E., on line 38-39.


3.51 Point for AP39, sec. 25, at the intersection with the N. and S. center line of the SE 1/4 of the SW 1/4 of sec. 25.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

T 22 N R 29 E



2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

Cor. is located 20 lks. S. of a line of riprap, bears N. 85° E. and S. 85° W.


From this cor. point, the E-W 1/64 sec. cor. of secs. 25 and 36, bears S. 1°04' W., 18.06 chs. dist.

N. 84°19' E., on line 39-40.

8.85 Point for AP40, sec. 25, at the intersection with the N. and S. center line of sec. 25.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 22 N R 29 E



2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

Cor. is located 14 lks. N. of a barbed wire fence, bears N. 85° E. and S. 85° W.

From this cor. point, the 1/4 sec. cor. of secs. 25 and 36, bears S. 1°29' W., 17.76 chs. dist.

N. 84°19' E., on line 40-41.


19.93 Point for AP41, sec. 25, at the intersection with the N. and S. center line of the SE 1/4 of sec. 25.

**Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
38 ins. in the ground, with brass cap mkd.

T 22 N R 29 E



2005

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Set a steel fence post alongside the stainless steel post.

Cor. is located on S. edge of a trail road, bears N. 85° E. and
S. 85° W. Cor. is also located 10 lks. N. of a barbed wire
fence, bears N. 85° E. and S. 85° W.

From this cor. point, the E. 1/16 sec. cor. of secs. 25 and 36,
bears S. 0°52' W., 19.77 chs. dist.


N. 84°19' E., on line 41-42.

19.90

Point for AP42, sec. 25, on the line bet. secs. 25 and 30, on
the E. bdy. of the Tp.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
37 ins. in the ground, with brass cap mkd.

T 22 N
R 29 E R 30 E



2005

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Set a steel fence post alongside the stainless steel post.

Cor. is located on S. edge of a trail road, bears N. 85° E. and
S. 85° W. Cor. is also located 10 lks. N. of a barbed wire
fence, bears N. 85° E. and S. 85° W.

From this cor. point, the cor. of secs. 25, 30, 31 and 36, on
the E. bdy. of the Tp., bears S. 0°17' W., 21.78 chs. dist.

**Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

In Section 26

From AP14, sec. 26, identical with AP34, sec. 25, on the line bet. secs. 25 and 26.

S. $0^{\circ}08'$ E., on line 14-15, along a portion of the line bet. secs. 25 and 26.

3.07 Point for AP15, sec. 26.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 36 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
AP15
—|
S26 | S25

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located in a gravel access road, 35 ft. wide, bears N. 65° E. and S. 65° W.

S. $80^{\circ}55'$ W., on line 15-16.

2.94 Point for AP16, sec. 26, identical with Beginning of Curvature.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 38 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
AP16 S26
—

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located in a gravel access road, 35 ft. wide, bears N. 65° E. and S. 65° W.

Thence, on line 16-17, along a circular curve to the left, having a central angle of $1^{\circ}32'$, a radius of 5829.58 ft., the chord of said arc bears S. $80^{\circ}14'$ W., 2.376 chs. dist.

2.376 Point for AP17, sec. 26, identical with End of Curvature.

**Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
36 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
AP17 S26

2005

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Cor. is located in a gravel access road, 35 ft. wide, bears
N. 65° E. and S. 65° W.

N. 89°30' W., on line 17-18, on a portion of the E. and W.
center line of the SE 1/4 of sec. 26.

6.27

True point for AP18, sec. 26, falls on an eroding bank of a
wash, 25 ft. wide, 15 ft. deep, drains S. 65° W., where it is
impracticable to establish a permanent monument.

From this true point, the point selected for the witness cor. to
AP18, sec. 26, bears N. 44°49' W., 0.27 chs. dist.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
26 ins. in the ground, with brass cap mkd.

WC
T 22 N R 29 E
AP18

S26

2005

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Set a steel fence post alongside the stainless steel post.

S. 80°39' W., on line 18-19.

8.68

Point at intersection with the N. and S. center line of the SE
1/4 of sec. 26, not monumented.

From this point, the SE 1/16 sec. cor. of sec. 26, bears
N. 0°33' W., 1.49 chs. dist.

Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
28.99	<p>Point at intersection with the N. and S. center line of sec. 26, not monumented.</p> <p>From this point, the center S. 1/16 sec. cor. of sec. 26, bears N. 0°58' W., 4.96 chs. dist.</p>
49.09	<p>Point at intersection with the N. and S. center line of the SW 1/4 of sec. 26, not monumented.</p> <p>From this point, the SW 1/16 sec. cor. of sec. 26, bears N. 0°36' W., 8.39 chs. dist.</p>
69.23	<p>Point for AP19, sec. 26, on the line bet. secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 29 E</p> <p>AP19</p> <p>S27 S26</p>  <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<hr/> <p>From the point for AP20, sec. 26, on the line bet. secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 29 E</p>  <p>S27 S26</p> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
9.88	<p>From this cor. point, the cor. of secs. 26, 27, 34 and 35, bears S. 0°13' E., 5.10 chs. dist.</p> <p>N. 80°39' E., on line 20-21.</p> <p>Point for AP21, sec. 26.</p>

Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
26 ins. in the ground, with brass cap mkd.

T 22 N R 29 E



AP21 / S26

2005

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.


S. 64°53' W., on line 21-22.

10.75

Point for AP22, sec. 26, on the line bet. secs. 26 and 27.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
27 ins. in the ground, with brass cap mkd.

T 22 N R 29 E



AP22
S27 | S26

2005

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

From this cor. point, the cor. of secs. 26, 27, 34 and 35, bears
S. 0°13' E., 2.14 chs. dist.

From the point for AP23, sec. 26, on the line bet. secs. 26 and
35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
25 ins. in the ground, with brass cap mkd.

T 22 N R 29 E




S26 AP23
S35

2005


Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

From this cor. point, the cor. of secs. 26, 27, 34 and 35, bears
N. 89°36' W., 6.05 chs. dist.

**Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
6.79	<hr/> <p>N. 64°51' E., on line 23-24.</p> <p>Point for AP24, sec. 26, identical with End of Curvature.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E</p> <div style="text-align: center;">  <p>AP24 S26</p> </div> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/>
8.335	<p>Thence, on line 24-25, along a circular curve to the right, having a central angle of 15°52', a radius of 5579.61 ft., the chord of said arc bears N. 72°45' E., 23.346 chs. dist.</p> <p>Point at intersection with the N. and S. center line of the SW 1/4 of sec. 26, not monumented.</p> <p>From this point, the W. 1/16 sec. cor. of secs. 26 and 35, bears S. 0°36' E., 6.15 chs. dist.</p>
23.420	<p>Point for AP25, sec. 26, identical with Beginning of Curvature.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E</p> <div style="text-align: center;">  <p>AP25 S26</p> </div> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/>
5.275	<p>N. 86°03' E., on line 25-26.</p> <p>Point at intersection with the N. and S. center line of sec. 26, not monumented.</p>

**Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this point, the 1/4 sec. cor. of secs. 26 and 35, bears S. 0°58' E., 10.415 chs. dist.</p>
11.26	<p>Point for AP26, sec. 26, identical with End of Curvature.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E</p> <p style="text-align: center;">  AP26 S26 </p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 5 lks. N. of a barbed wire fence, bears N. 85° E. and S. 85° W.</p> <hr style="width: 20%; margin: 10px auto;"/>
6.599	<p>Thence, on line 26-27, along a circular curve to the left, having a central angle of 8°25', a radius of 2964.79 ft., the chord of said arc bears N. 81°50' E., 6.593 chs. dist.</p> <p>Point for AP27, sec. 26, identical with Beginning of Curvature.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E</p> <p style="text-align: center;">  AP27 S26 </p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 5 lks. N. of a barbed wire fence, bears N. 80° E. and S. 80° W.</p> <hr style="width: 20%; margin: 10px auto;"/>
7.685	<p>N. 77°48' E., on line 27-28.</p> <p>Point at intersection with the N. and S. center line of the SE 1/4 of sec. 26, not monumented.</p> <p>From this point, the E. 1/16 sec. cor. of secs. 26 and 35, bears S. 0°33' E., 13.52 chs. dist.</p>

Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

20.91 Point for AP 28, sec. 26, identical with End of Curvature.
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
26 ins. in the ground, with brass cap mkd.

T 22 N R 29 E

AP28
S26

2005

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Cor. is located 14 lks. N. of a barbed wire fence, bears
N. 80° E. and S. 80° W.

Thence, on line 28-29, along a circular curve to the right,
having a central angle of 3°12', a radius of 5629.58 ft., the
chord of said arc bears N. 79°24' E., 4.764 chs. dist.

4.765 Point for AP29, sec. 26, identical with Beginning of Curvature.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
26 ins. in the ground, with brass cap mkd.

T 22 N R 29 E

AP29
S26

2005

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Cor. is located 15 lks. N. of a barbed wire fence, bears
N. 80° E. and S. 80° W.

N. 80°55' E., on line 29-30.

2.47 AP30, sec. 26, identical with AP35, sec. 25, on the line bet.
secs. 25 and 26.

In Section 33


**Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

From the true point for AP1, sec. 33, on the line bet. secs. 28 and 33, falls in the Rio Puerco River, 100 ft. wide, drains S. 20° W., where it is impracticable to establish a permanent monument.

From this true point, the point selected for the witness cor. to AP1, sec. 33, bears N. 64°53' W., 85 lks. dist.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 4 ft. base, 9 ins. high, with brass cap mkd.



2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

S. 37°55' W., on line 1-2.

19.47

Point for AP2, sec. 33, identical with Beginning of Curvature.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 22 N R 29 E



2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located 3 chs. N. of the right bank of the Rio Puerco River, drains S. 50° W.

Thence, on line 2-3, along a circular curve to the left, having a central angle of 9°28', a radius of 2009.86 ft., the chord of said arc bears S. 42°28' W., 5.027 chs. dist.

5.033

Point for AP3, sec. 33, identical with End of Curvature.

Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
26 ins. in the ground, with brass cap mkd.

T 22 N R 29 E

AP3
S33

2005

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Cor. is located 2.90 chs. N. of the right bank of the Rio Puerco
River, drains N. 80° W.

S. 47°12' W., on line 3-4.

7.52

True point for AP4, sec. 33, identical with Beginning of
Curvature, falls in the Rio Puerco River, 100 ft. wide, drains
S. 40° W., where it is impracticable to establish a permanent
monument.

From this true point, the point selected for the witness cor. to
AP4, sec. 33, bears N. 30°59' W., 1.84 chs. dist.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
25 ins. in the ground, with brass cap mkd.

WC
T 22 N R 29 E

AP4
S33

2005

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Thence, on line 4-5, along a circular curve to the left, having
a central angle of 25°57', a radius of 854.93 ft., the chord of
said arc bears S. 34°36' W., 5.818 chs. dist.

5.866

True point for AP5, sec. 33, identical with End of Curvature,
falls in the Rio Puerco River, 100 ft. wide, drains S. 55° W.,
where it is impracticable to establish a permanent monument.


From this true point, the point selected for the witness cor. to
AP5, sec. 33, bears N. 48°05' W., 3.70 chs. dist.

Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

WC
T 22 N R 29 E



2005

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

S. 21°38' W., on line 5-6.

12.15 Point at intersection with the E. and W. center line of sec. 33,
not monumented.

From this point, the center 1/4 sec. cor. of sec. 33, bears
S. 89°33' W., 25 lks. dist.


12.81 Point at intersection with the N. and S. center line of sec. 33,
not monumented.

From this point, the center 1/4 sec. cor. of sec. 33, bears
N. 0°01' W., 61 lks. dist.

26.81 Point for AP6, sec. 33, Beginning of Curvature.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T 22 N R 29 E



2005

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Cor. is located 1.75 chs. W. of the right bank of the Rio Puerco
River, drains S. 15° W.

Thence, on line 6-7, along a circular curve to the right, having
a central angle of 11°16', a radius of 6179.58 ft., the chord of
said arc bears N. 59°08' E., 18.383 chs. dist.

**Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
6.272	Point at intersection with the N. and S. center line of sec. 33, not monumented.
	From this point, the center 1/4 sec. cor. of sec. 33, bears N. 0°01' W., 10.06 chs. dist.
18.413	Point for AP7, sec. 33, identical with End of Curvature.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 22 N R 29 E AP7 S33 
	2005
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located 13 lks. N. of a barbed wire fence, bears N. 70° E. and S. 70° W.
	<hr style="width: 20%; margin: auto;"/> N. 64°46' E., on line 7-8.
10.19	Point at intersection with the E. and W. center line of sec. 33, not monumented.
	From this point, the center 1/4 sec. cor. of sec. 33, bears S. 89°33' W., 19.84 chs. dist.
32.60	Point for AP8, sec. 33, identical with AP6, sec. 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T 22 N R 29 E AP8 AP6 ———— S33 S34
	2005
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located 10 lks. N. of a barbed wire fence, bears N. 85° E. and S. 85° W.


**Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this cor. point, the 1/4 sec. cor. of secs. 33 and 34, bears South, 9.40 chs. dist.

From the point for AP9, sec. 33, identical with AP22, sec. 34, on the line bet. secs. 33 and 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.



2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.


Cor. is located 9 lks. N. of a barbed wire fence, bears N. 65° E. and S. 65° W.

From this cor. point, the 1/4 sec. cor. of secs. 33 and 34, bears North, 5.68 chs. dist.

S. 64°46' W., on line 9-10.

26.17 Point for AP10, sec. 33, identical with End of Curvature.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located 9 lks. N. of a barbed wire fence, bears N. 80° E. and S. 80° W.

Thence, on line 10-11, along a circular curve to the left, having a central angle of 13°58', a radius of 5279.58 ft., the chord of said arc bears S. 57°46' W., 19.467 chs. dist.

**Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
19.464	<p>Point at intersection with the N. and S. center line of sec. 33, not monumented.</p> <p>From this point, the 1/4 sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp., bears S. 0°01' E., 13.16 chs. dist.</p>
19.516	<p>Point for AP11, sec. 33, identical with Beginning of Curvature.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E</p> <div style="text-align: center;">  <p>AP11 S33</p> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 39°13' W., on line 11-12.</p>
3.79	<p>Point for AP12, sec. 33, identical with End of Curvature.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E</p> <div style="text-align: center;">  <p>AP12 S33</p> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 6.35 chs. S. of the left bank of the Rio Puerco River, bears N. 30° E. and S. 30° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence, on line 12-13, along a circular curve to the left, having a central angle of 4°00', a radius of 5529.65 ft., the chord of said arc bears S. 48°47' W., 5.852 chs. dist.</p>
5.853	<p>Point for AP13, sec. 33, identical with Beginning of Curvature.</p>

Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
26 ins. in the ground, with brass cap mkd.

T 22 N R 29 E



AP13
S33

2005

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Cor. is located 48 lks. W. of the right bank of the Rio Puerco
River.

N. 43°13' W., on line 13-14.

1.52 Point for AP14, sec. 33, identical with End of Curvature.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
26 ins. in the ground, with brass cap mkd.

T 22 N R 29 E



AP14
S33

2005

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Cor. is located 10 lks., N. 40° W., of a barbed wire fence,
bears N. 60° E. and S. 60° W.

Thence, on line 14-15, along a circular curve to the left,
having a central angle of 6°42', a radius of 5629.58 ft., the
chord of said arc bears S. 43°26' W., 9.983 chs. dist.

9.988 Point for AP15, sec. 33, identical with Beginning of Curvature.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
26 ins. in the ground, with brass cap mkd.

Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

T 22 N R 29 E

AP15
S33

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located 7 lks., N. 30° W., of a barbed wire fence, bears N. 40° E. and S. 40° W.

S. 40°04' W., on line 15-16.

8.12 Point for AP16, sec. 33, on the line bet. secs. 4 and 33, on the S. bdy. of the Tp.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
S33

AP16
S4
T21N

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located 10 lks., N. 55° E., of a barbed wire fence, bears N. 40° E. and S. 40° W.

From this cor. point, the 1/4 sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp., bears N. 89°34' E., 19.97 chs. dist.

In Section 34

From the point for AP1, sec. 34, on the line bet. secs. 27 and 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

**Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 22 N R 29 E
S27

 AP1 S34

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

From this cor. point, the 1/4 sec. cor. of secs. 27 and 34, bears N. 89°55' W., 9.38 chs. dist.

S. 80°38' W., on line 1-2.

0.96 Point for AP2, sec. 34, identical with Beginning of Curvature.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 22 N R 29 E

 AP2 S34

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

Thence, on line 2-3, along a circular curve to the right, having a central angle of 10°47', a radius of 2964.79 ft., the chord of said arc bears S. 85°40' W., 8.447 chs. dist.

8.459 Point for AP3, sec. 34, at intersection with the N. and S. center line of sec. 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, in a supporting mound of stone, 4 ft. base, 1 ft. high, with brass cap mkd.

T 22 N R 29 E

 AP3 | S34

2005

Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

Thence, on line 3-4, along a circular curve to the right, having a central angle of 1°01', a radius of 2964.79 ft., the chord of said arc bears N. 88°26' W., 0.794 chs. dist.

0.794 Point for AP4, sec. 34, identical with Point of Compound Curvature.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, in a mound of stone, 4 ft. base, 1 ft. high, with brass cap mkd.

T 22 N R 29 E

AP4 S34

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

Thence, on line 4-5, along a circular curve to the right, having a central angle of 16°12', a radius of 1054.93 ft., the chord of said arc bears N. 79°50' W., 4.507 chs. dist.

4.522 Point for AP5, sec. 34, on the line bet. secs. 27 and 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 22 N R 29 E

S27

AP5 S34

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point, the 1/4 sec. cor. of secs. 27 and 34, bears S. 89°55' E., 5.23 chs. dist.</p>
	<p>From AP6, sec. 34, identical with AP8, sec. 33, on line bet. secs. 33 and 34.</p>
	<p>N. 64°46' E., on line 6-7.</p>
24.86	<p>Point for AP7, sec. 34, at intersection with the E. and W. center line of the NW 1/4 of sec. 34.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p>T 22 N R 29 E</p>
	<p>AP7 S34</p>
	<p>2005</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Set a steel fence post alongside the stainless steel post.</p>
	<p>From this cor. point, the center N. 1/16 sec. cor. of sec. 34, bears S. 89°55' E., 17.56 chs. dist.</p>
	<p>N. 64°46' E., on line 7-8.</p>
19.42	<p>True point for AP8, sec. 34, at intersection with the N. and S. center line of sec. 34, falls in the Rio Puerco River, 250 ft. wide, drains N. 85° W., where it is impracticable to establish a permanent monument.</p>
	<p>From this true point, the point selected for the witness cor. to AP8, sec. 34, bears S. 20°00' W., 5.00 chs. dist.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p>WC</p>
	<p>T 22 N R 29 E</p>
	<p>AP8</p>
	<p>S34</p>
	<p>2005</p>

Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

Cor. is located 1.40 chs., S. 20° W., from the left bank of the Rio Puerco River.


From the true point, the center N. 1/16 sec. cor. of sec. 34, bears S. 0°02' W., 8.30 chs. dist.

N. 64°46' E., on line 8-9.

0.47 True point for AP9, sec. 34, falls in the Rio Puerco River, 250 ft. wide, drains N. 70° W., where it is impracticable to establish a permanent monument.

From this true point, the point selected for the witness cor. to AP9, sec. 34, bears N. 45°36' E., 3.23 chs. dist.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.



Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

S. 25°12' E., on line 9-10.

2.27 True point for AP10, sec. 34, falls in the Rio Puerco River, 250 ft. wide, drains N. 80° W., where it is impracticable to establish a permanent monument.

From this true point, the point selected for the witness cor. to AP10, sec. 34, bears S. 20°00' W., 2.95 chs. dist.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

WC
T 22 N R 29 E
AP10



S34

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

N. 64°48' E., on line 10-11.

20.57

True point for AP11, sec. 34, at intersection with the N. and S. center line of the NE 1/4 of sec. 34, falls in the Rio Puerco River, 350 ft. wide, drains S. 40° W., where it is impracticable to establish a permanent monument.

From this true point, the point selected for the witness cor. to AP11, sec. 34, bears S. 65°00' E., 2.62 chs. dist.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

WC
T 22 N R 29 E
AP11 S34



2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

From the true point, the E. 1/16 sec. cor. of secs. 27 and 34, bears N. 0°19' E., 4.78 chs. dist.

N. 64°48' E., on line 11-12.

5.19

Point for AP12, sec. 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

T 22 N R 29 E
AP12 S34



2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.



S. 25°12' E., on line 12-13.

2.27 Point for AP13, sec. 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
AP13 S34



2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.




N. 64°53' E., on line 13-14.

10.85 Point for AP14, sec. 34, on the line bet. secs. 27 and 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
S27



2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

**Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**


CHAINS

From this cor. point, the cor. of secs. 26, 27, 34 and 35, bears S. 89°55' E., 4.57 chs. dist.

From the point for AP15, sec. 34, on the line bet. secs. 34 and 35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 22 N R 29 E



2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

From this cor. point, the cor. of secs. 26, 27, 34 and 35, bears N. 0°36' E., 2.90 chs. dist.

S. 64°51' W., on line 15-16.

22.17

Point for AP16, sec. 34, at intersection with the N. and S. center line of the NE 1/4 of sec. 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 22 N R 29 E



2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

From this cor. point, the NE 1/16 sec. cor. of sec. 34, bears S. 0°19' W., 7.665 chs. dist.

S. 64°51' W., on line 16-17.

Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona


CHAINS

17.32

True point for AP17, sec. 34, falls on an eroding slope of an unnamed wash, 20 ft. deep, 30 ft. wide, drains N. 80° E., where it is impracticable to establish a permanent monument.

From this true point, the point selected for the witness cor. to AP17, sec. 34, bears S. 45°05' E., 1.03 chs. dist.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.



Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.


S. 25°12' E., on line 17-18.

0.31

True point for AP18, sec. 34, at intersection with the E. and W. center line of the NE 1/4 of sec. 34, falls on an eroding slope of an unnamed wash, 20 ft. deep, 30 ft. wide, drains N. 80° E., where it is impracticable to establish a permanent monument.

From this true point, the point selected for the witness cor. to AP18, sec. 34, bears S. 44°14' W., 0.50 chs. dist.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.



Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

From the true point, the center N. 1/16 sec. cor. of sec. 34, bears N. 89°55' W., 4.43 chs. dist.

Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
4.24	<p>S. 25°12' E., on line 18-19.</p> <p>Point for AP19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E</p> <div style="text-align: center;">  </div> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
6.90	<p>S. 64°46' W., on line 19-20.</p> <p>Point for AP20, sec. 34, at intersection with the N. and S. center line of sec. 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E</p> <div style="text-align: center;">  </div> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>From this cor. point, the center N. 1/16 sec. cor. of sec. 34, bears N. 0°02' E., 6.78 chs. dist.</p>
30.98	<p>S. 64°46' W., on line 20-21.</p> <p>Point for AP21, sec. 34, at intersection with the E. and W. center line of sec. 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

**Metes-and-Bounds Survey of the Right-of-Way,
of Burlington Northern Santa Fe Railroad,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 22 N R 29 E

~~AP21~~
S34

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

Cor. is located 10 lks. N. of a barbed wire fence, bears N. 60° E. and S. 60° W.

From this cor. point, the 1/4 sec. cor. of secs. 33 and 34, bears N. 89°56' W., 12.03 chs. dist.

S. 64°46' W., on line 21-22.

13.29 Point for AP22, sec. 34, identical with AP9, sec. 33.

**Metes-and-Bounds Survey of Proposed Lease Tract in Section 25,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

From the point for AP43, sec. 25, at intersection with the N. right-of-way of the Burlington Northern Santa Fe Railroad.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N R 29 E

~~S25~~ / AP43

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

Cor. is located alongside a barbed wire fence, bears S. 15° E. and N. 15° W.

From this cor. point, AP29, sec. 25, bears S. 84°19' W., 5.43 chs. dist.

Survey of Proposed Lease Tract in Section 25,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
5.88	<p>N. 4°41' E., on line 43-44.</p> <p>Point for AP44, sec. 25, occupied with a rebar, 5/8 in. diam., 20 ins. long, projecting 1 in. above ground.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 29 E</p> <p>S25 AP44</p>  <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit rebar inside stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/>
4.61	<p>N. 56°09' W., on line 44-45.</p> <p>Point for AP45, sec. 25, occupied with a rebar, 5/8 in. diam., 20 ins. long, projecting 1 in. above ground, with aluminum cap on top, mkd. AZ RLS 14667.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 29 E</p> <p>AP45 S25</p>  <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit rebar inside stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located alongside a barbed wire fence, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/>
1.85	<p>S. 81°59' W., on line 45-46.</p> <p>Point for AP46, sec. 25, at intersection with the N. and S. center line of sec. 25.</p>

Survey of Proposed Lease Tract in Section 25,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E AP46 S25</p> <p style="text-align: center;">+</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>From this cor. point, the center 1/4 sec. cor. of sec. 25, bears N. 1°29' E., 4.79 chs. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 81°59' W., on line 46-47.</p>
7.58	<p>Point for AP47, sec. 25, occupied with a rebar, 5/8 in. diam., 20 ins. long, flush with ground, with aluminum cap on top mkd. AZ RLS 14667.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E AP47 S25</p> <p style="text-align: center;">—</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit rebar inside stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located alongside a barbed wire fence, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 76°29' W., on line 47-48.</p>
1.46	<p>Point for AP48, sec. 25, at intersection with the N. and S. center line of the NE 1/4 of the SW 1/4 of sec. 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of Proposed Lease Tract in Section 25,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 22 N R 29 E
AP48 S25



2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

From this cor. point, the center E-W 1/64 sec. cor. of sec. 25, bears N. 1°04' E., 5.61 chs. dist.

S. 76°29' W., on line 48-49.

3.40

Point for AP49, sec. 25, occupied with a rebar, 5/8 in. diam., 20 ins. long, projecting 3 ins. above ground, with aluminum cap on top mkd. AZ RLS 14667.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
AP49 S25



2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Deposit rebar inside stainless steel post.

Set a steel fence post alongside the stainless steel post.

S. 85°57' W., on line 49-50.

5.62

Point for AP50, sec. 25, at intersection with the N. and S. center line of the SW 1/4 of sec. 25.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
AP50 S25



2005

Survey of Proposed Lease Tract in Section 25,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>From this cor. point, the center W. 1/16 sec. cor. of sec. 25, bears N. 0°39' E., 6.23 chs. dist.</p> <hr/> <p>S. 85°57' W., on line 50-51.</p>
<p>3.06</p>	<p>Point for AP51, sec. 25, occupied with a rebar, 5/8 in. diam., 20 ins. long, projecting 1 in. above ground, with plastic cap on top mkd. AZ RLS 14667.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E AP51 S25</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit rebar alongside stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located alongside a barbed wire fence, bears N. 55° E. and N. 75° W.</p> <hr/> <p>S. 84°39' W., on line 51-52.</p>
<p>4.41</p>	<p>Point for AP52, sec. 25, occupied with a rebar, 5/8 in. diam., 20 ins. long, set flush with ground, with aluminum cap on top mkd. AZ RLS 14667.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E AP52 S25</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Survey of Proposed Lease Tract in Section 25,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

8.49


Deposit rebar inside stainless steel post.
Set a steel fence post alongside the stainless steel post.

S. 2°49' E., on line 52-53.

Point for AP53, sec. 25, at intersection with the N. right-of-way of the Burlington Northern Santa Fe Railroad.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N R 29 E



2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside the stainless steel post.

Cor. is located 12 lks. N. of a barbed wire fence, bears N. 80° E. and S. 80° W.

From this cor. point, AP33, sec. 25, bears N. 80°55' E., 6.56 chs. dist.

GENERAL DESCRIPTION

The survey is located about 62 miles northwest of Holbrook, Arizona. The main access to the area is Interstate 40. Further access to the township is provided by numerous secondary and desert trail roads.

The terrain is mostly rolling throughout the township except in the NE where it is rolling and broken. The elevation varies from 4500 to 6000 feet above sea level.

The soil varies from mostly sandy to broken sandstone. No mineral deposits or activity was noted during the course of the survey.

The mean magnetic declination of 11° E. was derived from the computer program GEOMAGIX, utilizing the World Magnetic Model for Epoch WMM-2000 for the dates of survey.

CERTIFICATE OF SURVEY

I, Adrien J. Rodriguez, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 16th day of January, 2004, I have dependently resurveyed of a portion of the Seventh Auxiliary Guide Meridian East (West Boundary), the south and east boundaries, a portion of the subdivisional lines, subdivided certain sections, and metes-and-bounds surveys, T. 22 N., R. 29 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

Adrien J. Rodriguez, is no longer assigned to this office and is unavailable for Signature.

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the Seventh Auxiliary Guide Meridian East (West Boundary), the south and east boundaries, a portion of the subdivisional lines, subdivision of certain sections, and metes-and-bounds surveys, T. 22 N., R. 29 E., Gila and Salt River Meridian, in the State of Arizona, executed by Adrien J. Rodriguez, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

Oct. 2, 2006
(Date)

Stephen K. Hansen
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona, is a true copy of the orig. field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor of Arizona)~~