

ORIGINAL

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE  
DEPENDENT RESURVEY OF A  
PORTION OF THE WEST BOUNDARY  
AND  
A PORTION OF THE SUBDIVISIONAL LINES,  
**TOWNSHIP 16 SOUTH, RANGE 9 EAST,**  
OF THE GILA AND SALT RIVER MERIDIAN,  
IN THE STATE OF ARIZONA.

**EXECUTED BY**

**Gordon R. Bubel, Cadastral Surveyor**

Under Special Instructions dated January 13, 2006, approved January 13, 2006, which provided for the surveys included under Group No. 977, and assignment instructions dated January 13, 2006.

**Survey commenced January 18, 2006**

**Survey completed March 8, 2006**

**INDEX DIAGRAM**

TOWNSHIP 16 SOUTH

RANGE 9 EAST

	<b>6</b> 31	<b>5</b> 30	<b>4</b> 23	<b>3</b> 18	<b>2</b> 13	<b>1</b>
7	<b>7</b> 28 28	<b>8</b> 21 27	<b>9</b> 17 21	<b>10</b> 12 16	<b>11</b> 9 10	<b>12</b>
6	<b>18</b> 26 25	<b>17</b> 20 24	<b>16</b> 15 19	<b>15</b>	<b>14</b>	<b>13</b>
5 4	<b>19</b>	<b>20</b>	<b>21</b>	<b>22</b>	<b>23</b>	<b>24</b>
	<b>30</b>	<b>29</b>	<b>28</b>	<b>27</b>	<b>26</b>	<b>25</b>
	<b>31</b>	<b>32</b>	<b>33</b>	<b>34</b>	<b>35</b>	<b>36</b>

**T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona**

## CHAINS

The following field notes describe the dependent resurvey of a portion of the west boundary and a portion of the subdivisional lines, Township 16 South, Range 9 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

John C. Smith surveyed the west boundary in 1884. George J. Roskrige surveyed the subdivisional lines in 1886. Guy R. Veal, Karl L. Siebecker and Charles E. Hunter resurveyed a portion of the west boundary in 1920.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated January 13, 2006, for Group No. 977, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from horizontal order A, U. S. Coast and Geodetic Survey triangulation station "KING 1936", as published by the National Geodetic Survey, NAD 83 (1992). The geographic position of the corner of sections 11, 12, 13 and 14 is as follows:

Latitude: 32°02'40.96" N.                      Longitude: 111°23'06.97" W.

The mean magnetic declination is 11° E.

---

**Dependent Resurvey of a Portion of the West Boundary,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona**

---

Restoring the resurvey executed by  
Guy R. Veal, Karl L. Siebecker and Charles E. Hunter, in 1920

---

Beginning at the cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., loosely set in a scattered mound of stone, projecting 20 ins. above ground, with brass cap mkd. T16S R8E R9E S24 S19 S25 S30 1920.

**Dependent Resurvey of a Portion of the West Boundary,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Add the marks 2006 to the brass cap.</p> <p>from which the remains of the 1920 bearing trees</p> <p style="padding-left: 40px;">A mesquite stump, 8 ins. diam., 12 ins. high, bears S. 40° W., 1.89 chs. dist., with a portion of an unhealed blaze remaining.</p> <p style="padding-left: 40px;">A mesquite cluster, 24 ins. diam., at base, bears N. 74 1/2° W., 1.61 chs. dist., with illegible scribe marks visible on a dead 12 ins. diam. limb.</p> <p>Straighten iron post and rebuild supporting mound of stone, 3 ft. base, 1 ft. high.</p> <p>Cor. is located at intersection of barbed wire fences, bearing N., S. and W.</p> <p>N. 0°36' W., bet. secs. 19 and 24, on the W. bdy. of the Tp.</p> <p>Diverging westerly of barbed wire fence, through paloverde and mesquite timber.</p>
10.10	<p>The NW cor. of lot 87, as per Report of Survey executed by Gordon Walcott Ray, Arizona R.L.S. No. 9086 in 1975, on file at the Pima County Recorders Office in Book 1 of Record of Survey at page 55, monumented with a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground. The lots established in the 1975 Report of Survey are commonly known as the Hayhook Ranch subdivision.</p>
20.19	<p>The NW cor. of lot 88, as per Report of Survey executed by Gordon Walcott Ray, Arizona R.L.S. No. 9086 in 1975, on file at the Pima County Recorders Office in Book 1 of Record of Survey at page 55, monumented with a rebar, 1/2 in. diam., firmly set, projecting 3 ins. above ground, with attached aluminum wafer stamped ACCEPTED LS 26932.</p>
30.29	<p>The NW cor. of lot 89, as per Report of Survey executed by Gordon Walcott Ray, Arizona R.L.S. No. 9086 in 1975, on file at the Pima County Recorders Office in Book 1 of Record of Survey at page 55, monumented with a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, with attached aluminum wafer stamped ACCEPTED LS 26932.</p>
40.39	<p>The 1/4 sec. cor. of secs. 19 and 24 monumented with a limestone, 12 x 10 x 6 ins., firmly set, projecting 5 ins. above ground, mkd. 1/4 on W. face</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the West Boundary,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>T 16 S R 8 E    R 9 E       1/4 S 24   S 19               2006</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the orig. stone alongside the stainless steel post.</p> <p>Cor. is located 20.5 lks. W. of barbed wire fence, bears N. and S.</p> <hr/> <p align="center">Restoring the survey executed by John C. Smith, in 1884</p> <hr/> <p>N. 0°07' W., bet. secs. 19 and 24, on the W. bdy. of the Tp., beginning new measurement.</p>
10.01	<p>From this point, the NW cor. of lot 91, as per Report of Survey executed by Gordon Walcott Ray, Arizona R.L.S. No. 9086 in 1975, on file at the Pima County Recorders Office in Book 1 of Record of Survey at page 55, monumented with a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, bears East, 8 lks. dist.</p>
20.02	<p>From this point, the NW cor. of lot 92, as per ALTA/ACSM Survey executed by Taylor S. Hansen, Arizona R.L.S. No. 37512 in 2005, on file at the Pima County Recorders Office in Book 45 of Record of Survey at page 65, monumented with a rebar, 5/8 in. diam., firmly set, projecting 1 in. above ground, with affixed aluminum cap stamped HANSEN ENGINEERING RLS 37512, bears East, 15.5 lks. dist.</p>
30.03	<p>From this point, the NW cor. of lot 93, as per Report of Survey executed by Gordon Walcott Ray, Arizona R.L.S. No. 9086 in 1975, on file at the Pima County Recorders Office in Book 1 of Record of Survey at page 55, monumented with a rebar, 1/2 in. diam., firmly set, projecting 3 ins. above ground, bears East, 23.5 lks. dist.</p>
40.22	<p>Point for the cor. of secs. 13, 18, 19 and 24, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the West Boundary,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS

T 16 S	
R 8 E	R 9 E
S 13	S 18
S 24	S 19

2006

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, a rebar, 1/2 in. diam., firmly set, projecting 4 ins. above ground, bears S. 70°16' E., 33.5 lks. dist., established by Gordon Walcott Ray, Arizona R.L.S. No. 9086 in 1975, as per Report of Survey, on file at the Pima County Recorders Office in Book 1 of Record of Surveys at page 55. Cor. was established using improper control and is not utilized in the course of this resurvey. The rebar is located 1.5 lks. N. of a fence cor., with fences bearing S. and N. 88° E.

---

N. 0°07' W., bet. secs. 13 and 18, on the W. bdy. of the Tp.

Over gently rolling land.

40.22 Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate dist., there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T 16 S	
R 8 E	R 9 E
1/4	
S 13	S 18

2006

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

80.44 The cor. of secs. 7, 12, 13 and 18, determined on the E. side of the remains of the original accessory mound of stone, an embedded mound, 3 ft. diam.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd.

**Dependent Resurvey of a Portion of the West Boundary,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table border="1"> <tr><td colspan="2">T 16 S</td></tr> <tr><td>R 8 E</td><td>R 9 E</td></tr> <tr><td>S 12</td><td>S 7</td></tr> <tr><td>S 13</td><td>S 18</td></tr> </table>	T 16 S		R 8 E	R 9 E	S 12	S 7	S 13	S 18
T 16 S									
R 8 E	R 9 E								
S 12	S 7								
S 13	S 18								
	2006								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	This position was verified from a right-of-way map, obtained from Arizona Department of Transportation, entitled TUCSON-AJO HIGHWAY FEDERAL LANDS PROJECT 5A & 5B(2), accepted in 1944 and referenced by A.D.O.T. as 10-T 204.								
	<hr/>								
	N. 0°23' W., bet. secs. 7 and 12.								
	Slight ascent, over gently rolling land.								
0.67	Southerly right-of-way fence to State Hwy. No. 86, bears N. 87° E. and S. 87° W.								
1.99	Southerly edge of pavement, State Hwy. No. 86, bears N. 87° E. and S. 87° W.								
2.39	Northerly edge of pavement, State Hwy. No. 86, bears N. 87° E. and S. 87° W.								
3.70	Northerly right-of-way fence to State Hwy. No. 86, bears N. 87° E. and S. 87° W.								
3.80	Overhead power line, parallel with hwy.								
40.23	Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate dist., falls in a widely scattered mound of stone, with the original quartz stone, 14 x 5 x 5 ins., faintly mkd. 1/4 on a face, laying loose on the surface of the ground.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.								
	<table border="1"> <tr><td colspan="2">T 16 S</td></tr> <tr><td>R 8 E</td><td>R 9 E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S 12</td><td>S 7</td></tr> </table>	T 16 S		R 8 E	R 9 E	1/4		S 12	S 7
T 16 S									
R 8 E	R 9 E								
1/4									
S 12	S 7								
	2006								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								

**Dependent Resurvey of a Portion of the West Boundary,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS

80.46

Bury the original stone alongside the stainless steel post.

The cor. of secs. 1, 6, 7 and 12, monumented with a granite stone, 15 x 12 x 8 ins., loosely set, projecting 12 ins. above ground, in a mound of stone, 2 1/2 ft. base, 1 ft. high, mkd. with 1 faint groove on N. face and 5 faint grooves on S. face.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd.

T 16 S	
R 8 E	R 9 E
S 1	S 6
S 12	S 7

2006

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Incorporate the original stone, within the mound of stone.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona**

---

Restoring the survey executed by  
George J. Roskrige, in 1886

---

Beginning at the cor. of secs. 11, 12, 13 and 14, perpetuated by David M. Seese, Arizona R.L.S. No. 35545, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap, 3 ins. diam., mkd. T16S R9E S11 S12 S14 S13 2004 RLS 35545. With the orig. basalt stone, 18 x 8 x 7 ins., mkd. with 4 grooves on a face and 1 groove on an adjacent face, laying loose nearby. This is accepted as a careful and faithful perpetuation of the orig. cor. position.

from which reference monuments established by R.L.S. No. 35545

A rebar, 5/8 in. diam., bears N. 45°19' E., 1.604 chs. dist., with affixed brass wafer mkd., STANTEC RM CONTROL.

A rebar, 5/8 in. diam., bears S. 44°42' E., 1.606 chs. dist., with affixed brass wafer mkd., STANTEC RM CONTROL.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A rebar, 5/8 in. diam., bears S. 45°16' W., 1.607 chs. dist., with affixed brass wafer mkd., STANTEC RM CONTROL.</p> <p>A rebar, 5/8 in. diam., bears N. 44°47' W., 1.605 chs. dist., with affixed brass wafer mkd., STANTEC RM CONTROL.</p> <p>Bury the orig. stone alongside the stainless steel post.</p> <p>Cor. is located at intersection of barbed wire fences, with intact fences bearing N., S. and W, and downed fence bearing E.</p> <p>From this cor. point, U.S.C. &amp; G.S. horizontal order "A", triangulation station "KING 1936," bears S. 9°08' E., (forward bearing), 345.37 chs. dist., monumented with a 3 1/2 ins. diam., brass disk, seated in a concrete monument, 12 ins. sq., projecting 7 ins. above ground, with top mkd. KING 1936 and a triangle.</p> <p>N. 0°12' W., bet. secs. 11 and 12.</p> <p>Slight ascent, over gently rolling land, through mesquite and paloverde timber.</p>
40.25	<p>The 1/4 sec. cor. of secs. 11 and 12, monumented with a basalt stone, 16 x 12 x 10 ins., firmly set, projecting 5 ins. above ground, mkd. 1/4 on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 9 E 1/4 S 11   S 12</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the orig. stone alongside the stainless steel post.</p> <p>Cor. is located in a barbed wire fence, bears N. and S.</p>
40.73	<p>N. 0°14' W., beginning new measurement.</p> <p>The cor. of secs. 1, 2, 11 and 12, monumented with a granite stone, 23 x 15 x 6 ins., firmly set, projecting 12 ins. above ground, mkd. with 5 grooves on S. face and 1 groove on E. face.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground to bedrock, in a supporting mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 16 S</td> <td style="border-left: 1px solid black; padding: 0 10px;">R 9 E</td> </tr> <tr> <td style="padding: 0 10px;">S 2</td> <td style="border-left: 1px solid black; padding: 0 10px;">S 1</td> </tr> <tr> <td style="padding: 0 10px;">S 11</td> <td style="border-left: 1px solid black; padding: 0 10px;">S 12</td> </tr> </table> </div> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Incorporate the orig. stone, within the mound of stone.</p> <p>Cor. is located in a barbed wire fence, bears S. and S. 85° W.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 85°56' W., bet. secs. 11 and 14.</p> <p>Over bottom lands, through paloverde and mesquite timber.</p> <p>39.93 Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 16 S</td> <td style="padding: 0 10px;">R 9 E</td> </tr> <tr> <td style="padding: 0 10px;">S 11</td> <td style="padding: 0 10px;">—</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="padding: 0 10px;">—</td> </tr> <tr> <td style="padding: 0 10px;">S 14</td> <td style="padding: 0 10px;">—</td> </tr> </table> </div> <p style="text-align: center;">2006</p> <p>from which reference monuments established by David M. Seese, Arizona R.L.S. No. 35545</p> <p style="padding-left: 40px;">A rebar, 5/8 in. diam., bears N. 1°50' E., 1.708 chs. dist., with affixed brass wafer mkd., STANTEC RM CONTROL.</p> <p style="padding-left: 40px;">A rebar, 5/8 in. diam., bears S. 1°28' E., 1.505 chs. dist., with affixed brass wafer mkd., STANTEC RM CONTROL.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 16 S	R 9 E	S 2	S 1	S 11	S 12	T 16 S	R 9 E	S 11	—	1/4	—	S 14	—
T 16 S	R 9 E														
S 2	S 1														
S 11	S 12														
T 16 S	R 9 E														
S 11	—														
1/4	—														
S 14	—														

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona**

<p>CHAINS</p> <p>79.86</p>	<p>Cor. is located 1 lk. S. of barbed wire fence, bears N. 85° E. and S. 85° W.</p> <p>From this cor. point, a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T16S R9E 1/4 S11 S14 2004 RLS 35545, established by David M. Seese, Arizona R.L.S. No. 35545, in 2004, bears N. 24°48' E., 11 lks. dist. Cor. was established using improper control and is not utilized in the course of this resurvey.</p> <p>The cor. of secs. 10, 11, 14 and 15, determined from the remains of the orig. bearing trees</p> <p style="padding-left: 40px;">A mesquite snag, 15 in. diam., 60 ins. high, bears N. 20° E., 1.93 chs. dist., with rotted blaze.</p> <p style="padding-left: 40px;">A dead 11 ins. diam. limb, of a forked mesquite, bears N. 53° W., 1.37 chs. dist., no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 16 S</td> <td>R 9 E</td> </tr> <tr> <td>S 10</td> <td>S 11</td> </tr> <tr> <td>S 15</td> <td>S 14</td> </tr> </table> <p style="text-align: center;">2006</p> <p>from which reference monuments established by David M. Seese, Arizona R.L.S. No. 35545</p> <p style="padding-left: 40px;">A rebar, 5/8 in. diam., projecting 2 in. above the ground, bears N. 42°54' E., 1.816 chs. dist., with affixed brass wafer mkd., STANTEC RM CONTROL.</p> <p style="padding-left: 40px;">A rebar, 5/8 in. diam., projecting 1 in. above the ground, bears S. 52°27' E., 1.544 chs. dist., with affixed brass wafer mkd., STANTEC RM CONTROL.</p> <p style="padding-left: 40px;">A rebar, 5/8 in. diam., projecting 1 in. above the ground, bears S. 48°29' W., 1.400 chs. dist., with affixed brass wafer mkd., STANTEC RM CONTROL.</p> <p style="padding-left: 40px;">A rebar, 5/8 in. diam., projecting 1 in. above the ground, bears N. 37°40' W., 1.695 chs. dist., with affixed brass wafer mkd., STANTEC RM CONTROL.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 16 S	R 9 E	S 10	S 11	S 15	S 14
T 16 S	R 9 E						
S 10	S 11						
S 15	S 14						

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Cor. is located 1 lk. N. of barbed wire fence, bears N. 85° E. and S. 85° W.</p> <p>From this cor., a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T16S R9E S10 S11 S15 S14 2004 RLS 35545, established by David M. Seese, Arizona R.L.S. No. 35545, in 2004, bears N. 24°14' E., 22.5 lks. dist. The orig. bearing trees were not recovered in 2004, this position was established incorrectly by proportionate dist., and is not utilized in the course of this resurvey.</p> <hr/>
	<p>N. 0°46' W., bet. secs. 10 and 11.</p> <p>Over bottom lands, through mesquite and paloverde timber.</p> <p>40.47 The 1/4 sec. cor. of secs. 10 and 11, determined from the remains of the orig. bearing trees</p> <p style="padding-left: 40px;">A mesquite stump, 10 in. diam., 16 ins. high, bears S. 47° W., 33 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A mesquite snag, 16 ins. diam., 60 ins. high, bears N. 34° W., 72 lks. dist., no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 9 E 1/4 S 10   S 11  2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/>
	<p>N. 0°16' W., beginning new measurement.</p>
34.18	<p>Southerly right-of-way fence to State Hwy. No. 86, bears N. 65° E. and S. 65° W.</p>
35.65	<p>Southerly edge of pavement, State Hwy. No. 86, bears N. 65° E. and S. 65° W.</p>
36.07	<p>Northerly edge of pavement, State Hwy. No. 86, bears N. 65° E. and S. 65° W.</p>
37.51	<p>Northerly right-of-way fence to State Hwy. No. 86, bears N. 65° E. and S. 65° W.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS									
40.31	<p>The cor. of secs. 2, 3, 10 and 11, monumented with a basalt stone, 18 x 12 x 10 ins., firmly set, projecting 8 ins. above ground, mkd. with 5 grooves on S. face and 2 groove on E. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T 16 S</td><td>R 9 E</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td>S 10</td><td>S 11</td></tr> </table> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the orig. stone in the supporting mound of stone.</p> <p>Cor. is located in a barbed wire fence, bears N. 85° E., and S. 85° W.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 85°36' W., bet. secs. 2 and 11.</p> <p>Along a barbed wire fence.</p>	T 16 S	R 9 E	S 3	S 2	S 10	S 11		
T 16 S	R 9 E								
S 3	S 2								
S 10	S 11								
40.11	<p>The 1/4 sec. cor. of secs. 2 and 11, monumented with a basalt stone, 17 x 10 x 6 ins., firmly set, projecting 10 ins. above ground, with a scattered mound of stone, to the N., mkd. 1/4 on N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T 16 S</td><td>R 9 E</td></tr> <tr><td>S 2</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 11</td><td></td></tr> </table> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 16 S	R 9 E	S 2		1/4	—	S 11	
T 16 S	R 9 E								
S 2									
1/4	—								
S 11									

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Incorporate the orig. stone and the accessory mound of stone within the supporting mound of stone.</p> <p>Cor. is located 3 lks. S. of barbed wire fence, bears N. 85° E., and S. 85° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 86°01' W., beginning new measurement.</p> <p>24.45 Southerly right-of-way fence to State Hwy. No. 86, bears N. 65° E. and S. 65° W.</p> <p>28.18 Southerly edge of pavement, State Hwy. No. 86, bears N. 65° E. and S. 65° W.</p> <p>29.27 Northerly edge of pavement, State Hwy. No. 86, bears N. 65° E. and S. 65° W.</p> <p>32.96 Northerly right-of-way fence to State Hwy. No. 86, bears N. 65° E. and S. 65° W.</p> <p>40.16 The cor. of secs. 2, 3, 10 and 11.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of secs. 15, 16, 21 and 22, occupied with a granite stone, 16 x 12 x 8 ins., origin unknown, firmly set, projecting 6 ins. above ground, mkd. X on the top, (Record: wood post), with a rebar, 1/2 in. diam., firmly set, projecting 5 ins. above the ground, set alongside and to the W. This position is harmoniously related to existing orig. cors., and is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T 16 S R 9 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 16</td> <td style="padding: 0 5px;">S 15</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 21</td> <td style="padding: 0 5px;">S 22</td> </tr> </table> </div> <p style="text-align: center; margin: 10px 0;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar, 18 ins. long, inside the stainless steel post, and bury the stone alongside.</p> <p>From this cor., the intersection of barbed wire fences, extending S. and N. 45° W., bears S. 0°30' W., 45 lks. dist.</p>	T 16 S R 9 E		S 16	S 15	S 21	S 22
T 16 S R 9 E							
S 16	S 15						
S 21	S 22						

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this same cor., the intersection of barbed wire fences, extending S. 45° E. and S. 86° W., bears S. 87°30' W., 44 lks. dist.</p> <p>From this same cor., the 1/4 sec. cor. of secs. 21 and 22, bears S. 0°06' E., 40.46 chs. dist., monumented with a granite stone, 12 x 8 ins., firmly set, projecting 12 ins. above ground, mkd. 1/4 on W. face. (Record: wood post)</p> <p>N. 0°03' W., bet. secs. 15 and 16.</p> <p>Over bottom lands, through mesquite timber.</p>
40.41	<p>Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 9 E 1/4 S 16   S 15</p> <p style="text-align: center;">2006</p> <p>from which reference monuments established by David M. Seese, Arizona R.L.S. No. 35545</p> <p style="padding-left: 40px;">A rebar, 5/8 in. diam., bears S. 89°45' E., 1.981 chs. dist., with affixed brass wafer mkd., STANTEC RM CONTROL.</p> <p style="padding-left: 40px;">A rebar, 5/8 in. diam., bears N. 89°46' W., 1.232 chs. dist., with affixed brass wafer mkd., STANTEC RM CONTROL.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 50 lks. E. of barbed wire fence, bears N. and S.</p> <p>From this cor. point, a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. T16S R9E 1/4 S16 S15 2004 RLS 35545, established by David M. Seese, Arizona R.L.S. No. 35545, in 2004, bears S. 89°40' E., 37.5 lks. dist. Cor. was established using improper control and is not utilized in the course of this resurvey.</p>
80.82	<p>Point for the cor. of secs. 9, 10, 15 and 16, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	<div style="text-align: center;"> <table border="0"> <tr> <td>T 16 S</td> <td>R 9 E</td> </tr> <tr> <td>S 9</td> <td>S 10</td> </tr> <tr> <td>S 16</td> <td>S 15</td> </tr> </table> <p>2006</p> <p>from which reference monuments established by David M. Seese, Arizona R.L.S. No. 35545</p> <p>A rebar, 5/8 in. diam., bears N. 59°17' E., 2.205 chs. dist., with affixed brass wafer mkd., STANTEC RM CONTROL.</p> <p>A rebar, 5/8 in. diam., bears S. 58°40' E., 2.204 chs. dist., with affixed brass wafer mkd., STANTEC RM CONTROL.</p> <p>A rebar, 5/8 in. diam., bears S. 18°54' W., 1.200 chs. dist., with affixed brass wafer mkd., STANTEC RM CONTROL.</p> <p>A rebar, 5/8 in. diam., bears N. 18°24' W., 1.199 chs. dist., no wafer found.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the intersection of barbed wire fences, extending S. and N. 85° E., bears S. 55°16' W., 64.5 lks. dist.</p> <p>From this same cor. point, a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T16S R9E S9 S10 S16 S15 2004 RLS 35545, established by David M. Seese, Arizona R.L.S. No. 35545, in 2004, bears S. 89°41' E., 75 lks. dist. Cor. was established using improper control and is not utilized in the course of this resurvey.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 85°28' W., bet. secs. 10 and 15.</p> <p>Over bottom lands, through mesquite timber.</p> <p>40.25 Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> </div>	T 16 S	R 9 E	S 9	S 10	S 16	S 15
T 16 S	R 9 E						
S 9	S 10						
S 16	S 15						

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 16 S R 9 E S 10 1/4 ——— S 15</p> <p style="text-align: center;">2006</p> <p>from which reference monuments established by David M. Seese, Arizona R.L.S. No. 35545</p> <p style="padding-left: 40px;">A rebar, 5/8 in. diam., bears N. 14°11' E., 1.760 chs. dist., with affixed brass wafer mkd., STANTEC RM CONTROL.</p> <p style="padding-left: 40px;">A rebar, 5/8 in. diam., bears S. 15°27' E., 1.564 chs. dist., with affixed brass wafer mkd., STANTEC RM CONTROL.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 17 lks. N. of barbed wire fence, bears N. 85° E. and S. 85° W.</p> <p>From this cor. point, a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T16S R9E 1/4 S10 S15 2004 RLS 35545, established by David M. Seese, Arizona R.L.S. No. 35545, in 2004, bears N. 76°42' E., 43.5 lks. dist. Cor. was established using improper control and is not utilized in the course of this resurvey.</p>
80.50	<p>The cor. of secs. 9, 10, 15 and 16.</p> <hr/>
	<p>N. 0°28' W., bet. secs. 9 and 10.</p> <p>Over bottom lands, through mesquite timber.</p>
40.41	<p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 9 E 1/4 S 9   S 10</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS							
44.22	Southerly right-of-way fence to State Hwy. No. 86, bears N. 65° E. and S. 65° W.						
45.66	Southerly edge of pavement, State Hwy. No. 86, bears N. 65° E. and S. 65° W.						
46.09	Northerly edge of pavement, State Hwy. No. 86, bears N. 65° E. and S. 65° W.						
47.55	Northerly right-of-way fence to State Hwy. No. 86, bears N. 65° E. and S. 65° W.						
48.20	Power line, bears N. 65° E. and S. 65° W.						
80.82	<p>The cor. of secs. 3, 4, 9 and 10, monumented with a basalt stone, 28 x 11 x 8 ins., firmly set, projecting 11 ins. above ground, mkd. with 5 grooves on S. face and 3 groove on E. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <table border="1" data-bbox="794 989 1003 1087" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 16 S</td> <td>R 9 E</td> </tr> <tr> <td>S 4</td> <td>S 5</td> </tr> <tr> <td>S 9</td> <td>S 10</td> </tr> </table> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in a barbed wire fence, bears N. 85° E. and S. 85° W.</p>	T 16 S	R 9 E	S 4	S 5	S 9	S 10
T 16 S	R 9 E						
S 4	S 5						
S 9	S 10						
	<p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. 85°30' W., bet. secs. 3 and 10.</p> <p>Slight ascent, over rolling land, in and along barbed wire fence.</p>						
40.20	<p>Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>						

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 16 S R 9 E S 3 1/4 ——— S 10  2006</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 2 lks. N. of a barbed wire fence, bears N. 85° E. and S. 85° W.</p>
80.40	<p>The cor. of secs. 3, 4, 9 and 10.</p> <hr/>
	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 85°49' W., bet. secs. 16 and 21.</p> <p>Over bottom lands, through mesquite timber, along barbed wire fence.</p>
20.21	<p>A rebar, 1/2 in. diam., firmly set, projecting 3 ins. above ground.</p>
40.41	<p>The 1/4 sec. cor. of secs. 16 and 21, monumented with a granite stone, 12 x 11 x 10 ins., firmly set, projecting 2 ins. above ground, mkd. 1/4 on N. face, (Record: wood post), with a rebar, 1/2 in. diam., firmly set, projecting 1 ins. above ground, set alongside and to the S.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 16 S R 9 E S 16 1/4 ——— S 21  2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar, (22 ins. long) inside the stainless steel post, and bury the orig. stone alongside.</p> <p>Cor. is located 1 lk. S. of barbed wire fence, bears N. 85° E. and S. 85° W.</p> <hr/>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>S. 86°11' W., beginning new measurement.</p> <p>20.21 A rebar, 1/2 in. diam., firmly set, projecting 1 ins. above ground.</p> <p>40.41 The cor. of secs. 16, 17, 20 and 21, monumented with a granite stone, 16 x 10 x 8 ins., firmly set, projecting 7 ins. above ground, mkd. with 3 grooves on S. face and 4 groove on E. face, with a 1/2 in. diam. rebar, firmly set, projecting 33 ins. above ground set alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="803 779 1015 884"> <tr><td>T 16 S</td><td>R 9 E</td></tr> <tr><td>S 17</td><td>S 16</td></tr> <tr><td>S 20</td><td>S 21</td></tr> </table> <p>2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the orig. stone alongside the stainless steel post, and reset the rebar, (46 ins. long) 36 ins. in the ground, W. of the stainless steel post.</p> <p>Cor. is located at intersection of barbed wire fences, extending N. 85° E., S. and S. 85° W.</p> <hr/> <p>N. 0°08' W., bet. secs. 16 and 17.</p> <p>Over bottom lands, through mesquite timber.</p> <p>40.96 The 1/4 sec. cor. of secs. 16 and 17, monumented with a granite stone, 20 x 8 x 6 ins., firmly set, projecting 5 ins. above ground, mkd. 1/4 on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="803 1692 1015 1797"> <tr><td>T 16 S</td><td>R 9 E</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S 17</td><td>S 16</td></tr> </table> <p>2006</p>	T 16 S	R 9 E	S 17	S 16	S 20	S 21	T 16 S	R 9 E	1/4		S 17	S 16
T 16 S	R 9 E												
S 17	S 16												
S 20	S 21												
T 16 S	R 9 E												
1/4													
S 17	S 16												

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the orig. stone alongside the stainless steel post.</p> <hr/> <p>N. 0°30' E., beginning new measurement.</p>								
40.24	<p>Point for the cor. of secs. 8, 9, 16 and 17, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T 16 S</td><td>R 9 E</td></tr> <tr><td>S 8</td><td>S 9</td></tr> <tr><td>S 17</td><td>S 16</td></tr> </table> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>S. 86°15' W., bet. secs. 9 and 16.</p>	T 16 S	R 9 E	S 8	S 9	S 17	S 16		
T 16 S	R 9 E								
S 8	S 9								
S 17	S 16								
40.23	<p>Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T 16 S</td><td>R 9 E</td></tr> <tr><td>S 9</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 16</td><td></td></tr> </table> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 16 S	R 9 E	S 9		1/4	—	S 16	
T 16 S	R 9 E								
S 9									
1/4	—								
S 16									
80.46	<p>The cor. of secs. 8, 9, 16 and 17.</p> <hr/> <p>N. 0°43' W., bet. secs. 8 and 9.</p> <p>Ascending, over rolling land.</p>								

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
12.60	Southerly right-of-way fence to State Hwy. No. 86, bears N. 65° E. and S. 65° W.
14.03	Southerly edge of pavement, State Hwy. No. 86, bears N. 65° E. and S. 65° W.
14.45	Northerly edge of pavement, State Hwy. No. 86, bears N. 65° E. and S. 65° W.
15.92	Northerly right-of-way fence to State Hwy. No. 86, bears N. 65° E. and S. 65° W.
16.55	Power line, bears N. 65° E. and S. 65° W.
40.24	The 1/4 sec. cor. of secs. 8 and 9, monumented with a basalt stone, 22 x 13 x 6 ins., firmly set, projecting 13 ins. above ground, mkd. 1/4 on W. face, with a mound of stone, 5 ft. base, 2 ft. high, to the W.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, 1 ft. high, with brass cap mkd.  T 16 S R 9 E 1/4 S 8   S 9  2006  Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Incorporate the orig. stone, within the mound of stone.  N. 0°02' W., beginning new measurement.
40.10	The cor. of secs. 4, 5, 8 and 9, monumented with a basalt stone, 26 x 13 x 4 ins., firmly set, projecting 12 ins. above ground, mkd. with 4 grooves on E. face and 5 grooves on S. face.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, in a supporting mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS															
	<div style="text-align: center;"> <table border="1"> <tr><td>T 16 S</td><td>R 9 E</td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td>S 8</td><td>S 9</td></tr> </table> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Incorporate the orig. stone, within the supporting mound of stone.</p> <p>Cor. is located 2.5 lks. S. of barbed wire fence, bears N. 85° E. and S. 85° W., on the SE slope of Martina Mountain.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 86°12' W., bet. secs. 4 and 9.</p> <p>Ascending, in and along a barbed wire fence.</p> <p>40.12 The 1/4 sec. cor. of secs. 4 and 9, monumented with a basalt stone, 24 x 12 x 6 ins., firmly set, projecting 12 ins. above ground, mkd. 1/4 on N. face.</p> <p>From which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A stump hole, 16 ins. diam., bears N. 25° W., 1.12 chs. dist., with a dead and down, paloverde alongside, no marks found.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, in a supporting mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T 16 S</td><td>R 9 E</td></tr> <tr><td>S 4</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 9</td><td></td></tr> </table> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Incorporate the orig. stone, within the supporting mound of stone.</p>	T 16 S	R 9 E	S 5	S 4	S 8	S 9	T 16 S	R 9 E	S 4		1/4	—	S 9	
T 16 S	R 9 E														
S 5	S 4														
S 8	S 9														
T 16 S	R 9 E														
S 4															
1/4	—														
S 9															

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located in a barbed wire fence, bears N. 85° E. and S. 85° W.</p>
	<p style="text-align: center;">_____</p> <p>S. 85°35' W., bet. secs. 4 and 9, beginning new measurement.</p>
40.23	<p>The cor. of secs. 4, 5, 8 and 9.</p>
	<p style="text-align: center;">_____</p> <p>From the cor. of secs. 16, 17, 20 and 21.</p>
	<p>S. 86°15' W., bet. secs. 17 and 20.</p> <p>Over bottom lands, along barbed wire fence.</p>
6.69	<p>A rebar, 1/2 in. diam., firmly set, projecting 1 in. above ground, with affixed brass tag stamped LS 10046.</p>
13.38	<p>A rebar, 1/2 in. diam., firmly set, projecting 2 in. above ground, with affixed brass tag stamped LS 10046.</p>
20.07	<p>A rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground.</p>
26.76	<p>A rebar, 1/2 in. diam., firmly set, projecting 1 in. above ground, with affixed brass tag stamped LS 10046.</p>
33.45	<p>A rebar, 1/2 in. diam., firmly set, projecting 3 in. above ground, with affixed brass tag stamped LS 10046.</p>
40.14	<p>The 1/4 sec. cor. of secs. 17 and 20, monumented with a granite stone, 14 x 10 x 5 ins., firmly set, projecting 6 ins. above ground, mkd. 1/4 on N. face.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 16 S R 9 E</p>
	<p style="text-align: center;">S 17</p>
	<p style="text-align: center;">1/4 _____</p>
	<p style="text-align: center;">S 20</p>
	<p style="text-align: center;">2006</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Bury the orig. stone alongside the stainless steel post.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS							
	<p>Cor. is located in a woven wire fence, bears N. 86° E. and S. 86° W.</p>						
	<hr/> <p>S. 85°45' W., beginning new measurement.</p>						
20.02	<p>A rebar, 1/2 in. diam., firmly set, projecting 4 ins. above ground, with affixed, damaged and unreadable plastic cap.</p>						
24.90	<p>A rebar, 1/2 in. diam., firmly set, projecting 1 ins. above ground, with affixed, damaged and unreadable plastic cap.</p>						
29.78	<p>A rebar, 1/2 in. diam., firmly set, projecting 1 ins. above ground, with affixed, damaged and unreadable plastic cap.</p>						
34.67	<p>A rebar, 1/2 in. diam., firmly set, projecting 1 ins. above ground, with affixed, damaged and unreadable plastic cap.</p>						
39.80	<p>Coleman Road, graded, 25 ft. wide, bears irregularly N. and S.</p>						
40.04	<p>The cor. of secs. 17, 18, 19 and 20, perpetuated by Taylor S. Hansen, Arizona R.L.S. No. 37512, monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with affixed aluminum cap mkd. HANSEN ENGINEERING RLS 37512. This accepted as a careful and faithful perpetuation of the orig. cor. position</p>						
	<p>At the corner point</p>						
	<p>Drive a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over the rebar, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>						
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 16 S</td> <td>R 9 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 18</td> <td>S 17</td> </tr> <tr> <td style="border-right: 1px solid black;">S 19</td> <td>S 20</td> </tr> </table>	T 16 S	R 9 E	S 18	S 17	S 19	S 20
T 16 S	R 9 E						
S 18	S 17						
S 19	S 20						
	<p align="center">2006</p>						
	<p>Set a steel fence post N. of the stainless steel post.</p>						
	<p>Cor. is located 4 lks. N. of woven wire fence, bears N. 85° E. and S. 85° W.</p>						
	<p>From this cor., the 1/4 sec. cor. of secs. 19 and 20, bears S. 0°07' W., 40.17 chs. dist., monumented with a rebar, 5/8 in. diam., set flush with the surface of Coleman Road. Perpetuated by Gordon Walcott Ray, Arizona R.L.S. No. 9086 in 1975, as per Report of Survey, on file at the Pima County Recorders Office in Book 1 of Record of Survey at page 55.</p>						
	<hr/> <p>S. 87°53' W., bet. secs. 18 and 19.</p>						

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.10	<p>In and along a woven and barbed wire fence.</p> <p>Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 9 E S 18 1/4 ——— S 19</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 4 lks. N. of a barbed wire fence, bears N. 85° E. and S. 85° W. and 24 lks. N. of graded road, same bearing.</p> <p>From this cor. the NW cor. of lot 110, as per Report of Survey executed by Gordon Walcott Ray, Arizona R.L.S. No. 9086 in 1975, on file at the Pima County Recorders Office in Book 1 of Record of Survey at page 55, monumented with a rebar, 1/2 in. diam., firmly set, projecting 1 ins. above ground, bears S. 58°43' E., 12 lks. dist.</p>
79.99	<p>The NW cor. of lot 95, as per Report of Survey executed by Gordon Walcott Ray, Arizona R.L.S. No. 9086 in 1975, on file at the Pima County Recorders Office in Book 1 of Record of Survey at page 55, monumented with a rebar, 1/2 in. diam., firmly set, 3 ins. below the surface of ground, bears S., 14 lks. dist.</p>
118.74	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°22' E., bet. secs. 17 and 18.</p> <p>Over nearly level land, W. of Coleman Road.</p>
40.17	<p>Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 16 S R 9 E 1/4 S 18   S 17</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 60 lks. W. of the W. edge of Coleman Road.</p> <p>80.34 The cor. of secs., 7, 8, 17 and 18, reestablished, at record, from a right-of-way map, obtained from Arizona Department of Transportation, entitled TUCSON-AJO HIGHWAY FEDERAL LANDS PROJECT 5A &amp; 5B(2), accepted in 1944 and referenced by A.D.O.T. as 10-T 204.</p> <p>Drive a steel chisel, 9 ins. long, 3/4 in. wide, 7 ins. below the surface of Coleman Road.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears S. 44°29' E., 65.3 ft. dist. with brass cap mkd. RM T16S R9E S17 65.3 FT TO COR. 2006 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 23 ins. in the ground for a reference monument, bears S. 45°34' W., 66.6 ft. dist. with brass cap mkd. RM T16S R9E S18 66.6 FT TO COR. 2006 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 9 lks. E. of the W. edge of Coleman Road, graded, 20 ft. wide, bears irregularly N. and S.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>S. 85°10' W., bet. secs. 8 and 17.</p> <p>Over bottom lands, through mesquite and creosote.</p>
40.36	<p>The 1/4 sec. cor. of secs. 8 and 17, monumented with a granite stone, 19 x 8 x 8 ins., firmly set, projecting 8 ins. above ground, mkd. 1/4 on N. face (Record: wood post), with a scattered mound of stone to the N.</p> <p>At the corner point</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 9 E S 8 1/4 ——— S 17</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the mkd. stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 85°34' W., beginning new measurement.</p>
39.62	<p>The cor. of secs. 7, 8, 17 and 18.</p> <hr style="width: 80%; margin: auto;"/>
	<p>S. 87°57' W., bet. secs. 7 and 18.</p>
40.24	<p>Point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 9 E S 7 1/4 ——— S 18</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 2.15 chs. S. of southerly right-of-way fence, State Hwy. No. 86, bears N. 87° E. and S. 87° W.</p>
119.41	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <hr style="width: 80%; margin: auto;"/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°42' E., bet. secs. 7 and 8.</p> <p>Along Coleman Road.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
2.91	Southerly right-of-way fence, State Hwy. No. 86, bears N. 87° E. and S. 87° W.
4.24	Southerly edge of pavement, State Hwy. No. 86, bears N. 87° E. and S. 87° W.
4.44	<p>The center line of State Hwy No. 86, identical with station 178 + 82.70, as per a right-of-way map, obtained from Arizona Department of Transportation, entitled TUCSON-AJO HIGHWAY FEDERAL LANDS PROJECT 5A &amp; 5B(2), accepted in 1944 and referenced by A.D.O.T. as 10-T 204, not monumented.</p> <p>From this point, the computed center line at station 202 + 00, bears S. 86°52' W., 35.11 chs. dist., not monumented.</p> <p>from which</p> <p style="padding-left: 40px;">A galvanized iron pipe, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, bears S. 3°08' E., 0.758 chs. (50.0 ft) dist., with brass cap mkd. U.S. DEPARTMENT OF AGRICULTURE ELEVATION 202 + 00 2790.04 FEET 1938 BUREAU OF PUBLIC ROADS</p> <p style="padding-left: 40px;">A galvanized iron pipe, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, bears N. 3°08' W., 0.758 chs. (50.0 ft) dist., with brass cap mkd. U.S. DEPARTMENT OF AGRICULTURE ELEVATION 202 + 00 2790.49 FEET 1938 BUREAU OF PUBLIC ROADS</p>
4.63	Northerly edge of pavement, State Hwy. No. 86, bears N. 87° E. and S. 87° W.
5.95	Northerly right-of-way fence, State Hwy. No. 86, bears N. 85° E. and S. 87° W.
6.02	Power line, bears N. 87° E. and S. 87° W.
40.14	<p>The 1/4 sec. cor. of secs. 7 and 8, monumented with a granite stone, 20 x 12 x 7 ins., firmly set, projecting 11 ins. above ground, mkd. 1/4 on W. face, with a mound of stone, 3 1/2 ft. base, 1 ft. high to the W.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
<p>T 16 S R 9 E 1/4 S 7   S 8 2006</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS							
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the mkd. stone alongside the stainless steel post and scatter the accessory mound of stone.</p> <hr/> <p>N. 0°01' E., beginning new measurement.</p> <p>Ascend over SW slopes of Martina Mountain.</p>						
44.31	<p>The cor. of secs. 5, 6, 7 and 8, monumented with a granite stone, 18 x 10 x 10 ins., firmly set, projecting 9 ins. above ground, mkd. with 5 grooves on E. face and 5 grooves on S. face, with a scattered mound of stone to the N.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 16 S</td> <td>R 9 E</td> </tr> <tr> <td>S 6</td> <td>S 5</td> </tr> <tr> <td>S 7</td> <td>S 8</td> </tr> </table> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Incorporate the orig. stone within the supporting mound of stone.</p> <p>Rebuild the accessory mound of stone, 5 1/2 ft. base, 3 ft. high, N. of cor.</p> <p>Cor. is located on bench on the SW slope of Martina Mountain.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>S. 88°17' W., bet. secs. 5 and 8.</p> <p>Across steep southerly slopes of Martina Mountain.</p>	T 16 S	R 9 E	S 6	S 5	S 7	S 8
T 16 S	R 9 E						
S 6	S 5						
S 7	S 8						
39.36	<p>Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, in a supporting mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p>						

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 16 S R 9 E S 5 1/4 ——— S 8</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on steep S. slope of Martina Mountain.</p>
78.72	<p>The cor. of secs. 5, 6, 7 and 8.</p> <hr/> <p>S. 85°56' W., bet. secs. 6 and 7.</p> <p>Descending over the W. slope of Martina Mountain.</p>
40.13	<p>The 1/4 sec. cor. of secs. 6 and 7, monumented with a granite stone, 20 x 11 x 6 ins., firmly set, projecting 11 ins. above ground, mkd. 1/4 on N. face, with an embedded mound of stone to the N.</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A stump hole, 16 ins. diam., bears N. 45 1/2° W., 1.08 chs. dist., with a dead and down paloverde alongside. (Record: N. 43° W., 107 lks.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 9 E S 6 1/4 ——— S 7</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the mkd. stone alongside the stainless steel post.</p> <hr/> <p>S. 86°08' W., beginning new measurement.</p> <p>Descending over rolling land.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona**

<p>CHAINS 80.51</p>	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p>The resurvey is located about 30 miles WSW of Tucson, Arizona. Access is by way of Arizona Highway Number 86, Coleman Road and a few trail roads.</p> <p>The terrain is predominately bottom lands, with the exception of parts of sections 7, 8 and 9, being occupied with the south slopes of Martina Mountain. The timber consists of scattered paloverde and mesquite, with undergrowth of creosote and grasses. The mean elevation is 2800 feet above sea level.</p> <p>Mendoza wash, roughly parallels Arizona Highway Number 86, entering the area surveyed on the line between sections 10 and 11, and exiting between sections 17 and 20.</p> <p>The soil is generally second rate. Cattle grazing is the predominate use, with stock tanks located in sections 7, 8 and 11.</p> <p>No mineral deposits or activity was noted during the course of the resurvey.</p> <p>The mean magnetic declination of 11° E. was derived from the computer program GEOMAGIX, utilizing the World Magnetic Model for Epoch WMM-2005 for the dates of survey.</p> <hr/>
-------------------------	---



CERTIFICATE OF SURVEY

I, Gordon R. Bubel, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 13th day of January, 2006, have dependently resurveyed a portion of the West boundary and a portion of the subdivisional lines, T. 16 S., R. 9 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

SEPTEMBER 25, 2006  
(Date)

Gordon R. Bubel  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey a portion of the West boundary and a portion of the subdivisional lines, T. 16 S., R. 9 E., Gila and Salt River Meridian, in the State of Arizona, executed by Gordon R. Bubel, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

Mar. 20, 2007  
(Date)

Stephen H. Hansen  
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 16 S., R. 9 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~\_\_\_\_\_  
(Date)~~

~~\_\_\_\_\_  
(Chief Cadastral Surveyor of Arizona)~~