

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY
OF A PORTION OF
THE SUBDIVISIONAL LINES
AND THE SUBDIVISION
OF SECTION 28

TOWNSHIP 20 NORTH, RANGE 7 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

Geoffrey A. Graham, Cadastral Surveyor

Under Special Instructions dated April 5, 2007, approved April 5, 2007, which provided for the surveys included under Group No. 1016, and assignment instructions dated April 5, 2007.

Survey commenced April 10, 2007

Survey completed June 7, 2007

INDEX DIAGRAM

TOWNSHIP 20 NORTH RANGE 7 EAST
 GILA AND SALT RIVER MERIDIAN, ARIZONA

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29 8	16 28 4	27	26	25
31	32	5 33	34	35	36

Subdivision of Section 28 Pages 17-24

T. 20 N., R. 7 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the subdivisional lines and the subdivision of section 28, Township 20 North, Range 7 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

In 1878, John L. Harris surveyed the exterior boundaries and the subdivisional lines of the township. In 1966, Wallace R. Ott remonumented a portion of the subdivisional corners throughout the township.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated April 5, 2007, for Group Number 1016, Arizona.

The true meridian direction and length of all lines were determined by angle and distance measurements with a Topcon GTS3B total station and by real time kinematic and fast static global positioning system observations using Trimble Navigation 5700 and 5800 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) AI8820 FERNO MESA CORS ARP, DH3751 ASHLER HILLS CORS ARP, and AI7443 FLAGSTAFF 1 CORS ARP. The NAD 83 (CORS96)(EPOCH:2002), geographic position of the corner of sections 27, 28, 33 and 34, is as follows:

Latitude: 35°04'44.94" N. Longitude: 111°39'02.28" W.

The mean magnetic declination is 11 1/2° E.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 7 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Restoring the survey executed by John L. Harris, in 1878</p> <hr/>
	<p>Beginning at the cor. of secs. 27, 28, 33 and 34, monumented with a Bureau of Land Management iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. T20NR7E S28 S27 S33 S34 1966, from which the remains of the orig. bearing trees</p>
	<p>A ponderosa pine, 33 ins. diam., bears S. 18 1/4° E., 1.27 chs. dist., with scribe marks NRVIIE X visible on partially healed blaze, with Forest Service standard sign 54-3 attached. (1966 Record: S. 19° E., 1.25 chs.)</p>
	<p>A significantly decayed ponderosa pine stump, 18 ins. diam., bears S. 78 3/4° W., 1.02 chs. dist., with no remains of blaze. (1966 Record: S. 80° W., 1.00 chs.)</p>
	<p>and new bearing trees</p>
	<p>A ponderosa pine, 31 ins. diam., bears N. 62 1/2° E., 1.86 chs. dist., mkd. T20NR7ES27BT, with Forest Service standard sign 54-3 attached.</p>
	<p>A ponderosa pine, 23 ins. diam., bears S. 76 1/2° W., 1.57 chs. dist., mkd. T20NR7ES33BT, with Forest Service standard sign 54-3 attached.</p>
	<p>Add the marks 2007 to the brass cap. This monument is oriented to be read from the east.</p>
	<p>Set a steel sign post with attached Forest Service standard signs 54-2 and 54-9 nearby.</p>
	<p>N. 0°13' W., bet. secs. 27 and 28.</p>
0.04	<p>The base of a damaged telephone utility box, 6 1/2 X 6 1/2 ins., bears East, 1 lk. dist.</p>
9.88	<p>A telephone utility box, 6 1/2 X 6 1/2 ins., projecting 3 ft. above the ground, bears East, 4 lks. dist.</p>
9.96	<p>A rebar, 1/2 in. diam., firmly set, projecting 2 ins. above the ground, with a yellow plastic cap mkd. R. SCHILKE RLS 28230, bears East, 3 lks. dist., located 1 1/2 lks. W. of fence bearing N. and S.</p>
10.07	<p>A fire hydrant, 7 ins. diam., projecting 2.8 ft. above the ground, painted yellow, bears East, 3 lks. dist.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 7 E., Gila and Salt River Meridian, Arizona**

CHAINS	
10.09	A water valve box, 9 ins. diam., projecting 4 ins. above the ground, bears East, 3 lks. dist.
19.92	A rebar, 1/2 in. diam., firmly set, 3 ins. below the ground, with a faded red plastic shiner mkd. WERHAN, FOLKERS & MONIHAN RLS 18215, located at cor. of fences extending N., S. and W.
19.97	A telephone utility box, 6 1/2 X 6 1/2 ins., projecting 2.9 ft. above the ground, bears East, 1 lk. dist.
31.20	A rebar, 1/2 in. diam., firmly set, projecting 3 ins. above the ground, with no marks, bears East, 1 lk. dist., located 1 lk. E. of a fence bearing N. and S.
33.99	A rebar, 1/2 in. diam., firmly set flush with the ground, with a yellow plastic cap mkd. EXTREME MEASURERS RLS 26406.
35.12	East Comanche, unpaved, 31 ft. wide, bears E. and W.
35.55	A rebar, 1/2 in. diam., firmly set, 2 ins. below the ground, with no marks.
36.44	A rebar, 1/2 in. diam., firmly set, projecting 1 1/2 ins. above the ground, with a yellow plastic shiner mkd. EEC. INC. RLS 18215 928-779-4505.
40.09	<p>The 1/4 sec. cor. of secs. 27 and 28, monumented with a Bureau of Land Management iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T20NR7E 1/4 S28 S27 1966, from which the remaining 1966 bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 31 ins. diam., bears S. 41 1/4° E., 40 lks. dist., with a healed blaze, with Forest Service standard sign 54-3 attached.</p> <p>Add the marks 2007 to the brass cap.</p> <p>A steel sign post with attached Forest Service standard sign 54-2 is set nearby.</p> <p>Cor. is located 1 lk. N. of the terminus of a fence extending W. and S. 50° W., 2 1/2 lks. from the terminus of fence extending S., also located 93 lks. W. of intersection of dirt roads, one bears S. 40° E. and N. 40° W., 30 ft. wide, and the other bears S. 10° W., 15 ft. wide.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>S. 89°35' W., bet. secs. 28 and 33.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 7 E., Gila and Salt River Meridian, Arizona**

CHAINS	
10.11	A rebar, 1/2 in. diam., firmly set, projecting 2 ins. above the ground, with yellow plastic cap mkd. R. SCHILKE RLS 28230.
17.46	Dirt road, 12 ft. wide, bears N. 25° E. and S. 25° W.
20.22	A rebar, 1/2 in. diam., firmly set flush with the ground, with a red plastic shiner mkd. WERHAN, FOLKERS & MONIHAN RLS 18215, located at cor. of fences extending N. and E.
24.70	Cor. of fences extending S. 86° E. and N. 60° W., bears South, 25 lks. dist.
25.11	Fence, bears S. 60° E. and N. 60° W.
29.95	Fence, bears N. 4° E. and S. 4° W.
30.00	Cor. of fences extending N. 4° E. and N. 85° W., bears South, 81 lks. dist.
38.88	Fence, bears S. 85° E. and N. 85° W.
39.66	<p>The 1/4 sec. cor. of secs. 28 and 33, monumented with a Forest Service alum. post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, in a collar of stone, with alum. cap mkd. T20NR7E S28 1/4 S33 RLS 18215 1994. This cor. was reestablished by James A. Folkers, Arizona Registered Land Surveyor No. 18215, in the course of a survey recorded in Docket 1666, Page 407, and Book 12 of maps, Page 3, Coconino County Recorder's Office. This is accepted as a careful and faithful reestablishment of the orig. cor. position.</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears S. 72 3/4° W., 54 lks. dist., mkd. X BT, with Forest Service standard sign 54-3 attached.</p>
	<p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears N. 11 1/4° W., 69 lks. dist., mkd. X BT, with Forest Service standard sign 54-3 attached.</p>
	<p>Set a steel sign post with attached Forest Service standard signs 54-2 and 54-9 nearby.</p>
	<p>From this cor. point, a cor. of fences extending S. 85° E. and N. 3° W., bears N. 42° E., 9 lks. dist.</p>
	<hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>S. 89°35' W., beginning new measurement.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 7 E., Gila and Salt River Meridian, Arizona**

CHAINS	
19.83	Point for the W. 1/16 sec. cor. of secs. 28 and 33, not monumented.
39.66	<p>The cor. of secs. 28, 29, 32 and 33, monumented with a Bureau of Land Management iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with an accessory mound of stone, 3 ft. base, 1 ft. high, W. of the cor., with brass cap mkd. T20NR7E S29 S28 S32 S33 1966, from which the remains of the orig. bearing trees</p> <p style="padding-left: 40px;">A rotted fallen ponderosa pine, 16 ins. diam., with no identifiable stump hole, is located at the approximate record bearing and dist., N. 60° E., 2.25 chs., with no marks remaining.</p> <p style="padding-left: 40px;">A rotted ponderosa pine stump, 28 ins. diam., bears S. 86° W., 4.22 chs. dist., with no marks visible. (1966 Record: S. 85° W., 4.18 chs.)</p> <p style="padding-left: 40px;">A rotted ponderosa pine stump, 36 ins. diam., bears N. 54° W., 1.14 chs. dist., with no marks visible. (1966 Record: N. 50° W., 1.12 chs.)</p> <p>and the 1966 bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 22 ins. diam., bears N. 50° W., 13 lks. dist., with a healed blaze, with Forest Service standard sign 54-3 attached.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 20 ins. diam., bears N. 5° E., 98 lks. dist., mkd. T20NR7ES28BT, with Forest Service standard sign 54-3 attached.</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears S. 79 3/4° E., 2.29 chs. dist., mkd. T20NR7ES33BT, with Forest Service standard sign 54-3 attached.</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears S. 46 1/4° W., 3.87 chs. dist., mkd. T20NR7ES32BT, with Forest Service standard sign 54-3 attached.</p> <p>Add the marks 2007 to the brass cap.</p> <p>Set a steel sign post with attached Forest Service standard signs 54-2 and 54-9 nearby.</p> <p>From this cor. point, an embedded mound of stone, 3 ft. diam., 1/2 ft. high, with no monument recovered, bears N. 89°06' W., 81 lks. dist. This is the apparent position used to control the layout of the Mountaineer subdivisions.</p> <hr/>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 7 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 0°25' W., bet. secs. 28 and 29.
1.79	Track road, 12 ft. wide, curves S. 55° E., from N. 70° W.
18.88	Track road, 21 ft. wide, curves N. 60° E., from S. 55° W.
19.65	Cor. of rail fence extending N. 75 1/2° E. and N. 70 1/2° W., bears East, 11 lks. dist.
19.69	Rail fence, bears S. 70 1/2° E. and N. 70 1/2° W.
20.18	Point for the S. 1/16 sec. cor. of secs. 28 and 29. Set an alum. post, 30 ins. long, 2 1/2 ins. diam., flush with the grade, with alum. cap mkd.
	T 20 N R 7 E S 1/16 S 29 S 28 2007
	Deposit a magnet in a white plastic case at the base of the alum. post.
	Set a steel sign post with attached Forest Service standard signs 54-2 and 54-9 nearby.
	Cor. is located in the parking area for a house in lot 47, Mountaineer Unit One.
20.31	An open end iron pipe, 1/2 in. inside diam., firmly set, 1 in. below ground, with no marks, bears West, 67 lks. dist. This is the SW cor. of the Mountaineer Unit One subdivision.
20.62	Roofline of house, 26 lks., E. of cor. of porch rooflines extending N. 3/4° E. and E.
20.90	The SE cor. of roofline for shed, 10 X 11.3 ft., bears West, 50 lks. dist., long side of roofline bears N. 1/2° E.
21.24	Roofline of same house, 42 lks., E. of cor. of rooflines extending E. and S. 3/4° W.
21.77	Roofline of house, 50 lks., E. of cor. of rooflines extending E. and N. 1 1/2° W.
21.94	SE cor. of roofline for shed, 11.3 X 16.9 ft., bears West, 84 lks. dist., long side of roofline bears S. 88° W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 7 E., Gila and Salt River Meridian, Arizona**

CHAINS	
22.22	Roofline of same house, 51 lks., E. of cor. of rooflines extending E. and S. $1\ 1/2^\circ$ E.
22.35	SE cor. of roofline for shed, 6.8 X 10 ft., bears West, 90 lks. dist., long side of roofline bears N. $5\ 3/4^\circ$ E.
22.44	Roofline of house, 35 lks., S. $89\ 3/4^\circ$ E., of cor. of rooflines extending N. 1° E. and S. $89\ 3/4^\circ$ E.
22.69	Roofline of same house, 4 lks., S. $89\ 3/4^\circ$ E., of cor. of roofline and deck bearing N. 1° E. and N. $89\ 3/4^\circ$ W.
22.82	Edge of deck, 4 lks., S. $89\ 3/4^\circ$ E., of cor. of deck bearing S. $89\ 3/4^\circ$ E. and S. 1° W.
24.49	Southern edge of pavement of North Tonowanda, 24 ft. wide, bears S. $74\ 1/4^\circ$ E. and N. $74\ 1/4^\circ$ W.
24.89	Northern edge of pavement of North Tonowanda, 24 ft. wide, bears S. $72\ 1/4^\circ$ E. and N. $72\ 1/4^\circ$ W.
25.21	Roofline of house, 9 lks., N. $89\ 1/2^\circ$ E., of cor. of rooflines extending N. $89\ 1/2^\circ$ E. and N. 2° W.
25.93	Roofline of same house, 26 lks., N. $89\ 1/2^\circ$ E., of cor. of rooflines extending N. $89\ 1/2^\circ$ E. and S. 2° E.
26.08	SE cor. of rooflines for shed, 11 X 12.6 ft., bears West, 2 lks. dist., long side of roofline bears N. $2\ 1/4^\circ$ W.
26.35	East edge of pavement of North Ute, asphalt paved, 23 ft. wide, bears West, 27 lks. dist. Road bears N. $2\ 3/4^\circ$ E. and S. $2\ 3/4^\circ$ W.
27.88	East edge of pavement of North Ute, asphalt paved, 23 ft. wide, bears West, 19 lks. dist. Road bears S. $2\ 3/4^\circ$ W., the northerly extension becomes the driveway and parking area for a house.
27.96	Cor. of fences extending N. $84\ 1/2^\circ$ E. and N. $3/4^\circ$ W., bears West, 89 lks. dist.
27.99	Cor. of fences extending N. 36° E. and S. $84\ 1/2^\circ$ W., bears West, 48 lks. dist.
28.28	Cor. of fences extending S. 36° W. and N. 32° W., bears West, 27 lks. dist.
28.39	Terminus of fence extending S. 32° E., at cor. of rooflines for house, extending N. $80\ 1/2^\circ$ E. and N. $9\ 3/4^\circ$ W., bears West, 34 lks. dist.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 7 E., Gila and Salt River Meridian, Arizona**

CHAINS	
28.44	Roofline of same house, 8 lks., N. 80 1/2° E., of cor. of rooflines extending N. 80 1/2° E. and N. 9 3/4° W.
29.01	Roofline of same house, 56 lks., S. 9 1/2° E., of cor. of rooflines extending S. 9 1/2° E. and S. 80 1/2° W.
29.28	Cor. of fences extending N. 1 1/2° E., N. 77 3/4° E. terminating at house, and S. 3/4° E., bears West, 90 lks. dist.
29.57	Fence, bears N. 83 1/4° E. and S. 83 1/4° W.
30.44	SE cor. of rooflines for shed, 7.4 X 8.2 ft., bears West, 72 lks. dist., long side of roofline bears N. 1° E.
30.74	Fence, bears S. 18 3/4° E. and N. 18 3/4° W.
30.98	Cor. of fences extending N. 1° E., N. 87 3/4° E. and S. 1 1/2° W., bears West, 84 lks. dist.
31.01	Cor. of fences extending S. 18 3/4° E., S. 87 3/4° W. and N. 20 1/2° W., bears West, 9 lks. dist.
31.49	Fence, bears S. 23 1/4° E. and N. 23 1/4° W.
31.71	Cor. of fences extending N. 63 1/4° E. and S. 23 1/4° E., bears West, 9 lks. dist.
31.75	Fence, bears N. 63 1/4° E. and S. 63 1/4° W.
32.35	Cor. of fences extending N. 81 1/4° E. and S. 1° W., bears West, 81 lks. dist.
32.38	Cor. of fences extending S. 20 1/2° E. and S. 81 1/4° W., bears West, 59 lks. dist.
32.59	An open end iron pipe, 1/2 in. inside diam., loosely set, projecting 8 ins. above the ground, with no marks, bears West, 62 lks. dist., located at cor. of fences extending N. 5° E. and S. 31° E. A stone retaining wall, 2 ft. high, 46 ft. long, extends N. 2 1/2° W.
33.52	Fence, bears S. 55 1/4° E. and N. 55 1/4° W.
33.63	A water valve box, 8 ins. diam., set flush with ground, bears West, 25 lks. dist.
33.73	An open end iron pipe, 1/2 in. inside diam., firmly set, 3 ins. below the ground, with no marks, bears West, 61 lks. dist.
33.93	Cor. of fences extending S. 55 1/4° E. and N. 2 1/2° W., bears West, 58 lks. dist.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 7 E., Gila and Salt River Meridian, Arizona**

CHAINS	
34.06	Fence, 59 lks. E. of cor. of fences extending E. and S. $2\ 1/2^\circ$ E.
34.18	A rebar, 1/2 in. diam., firmly set, projecting 3 ins. above the ground, with an alum. cap mkd. MARTIN RLS 18548, bears West, 61 lks. dist.
34.19	SE cor. of rooflines for shed, 5.9 X 8.2 ft., bears West, 15 lks. dist., long side of roofline bears S. $89\ 3/4^\circ$ W.
34.22	Cor. of fences extending N. $89\ 1/4^\circ$ E. and N. $1/2^\circ$ W. bears West, 59 lks. dist.
34.23	Fence, bears N. $89\ 1/4^\circ$ E. and S. $89\ 1/4^\circ$ W.
34.60	Roofline of house, 16 lks., N. $61\ 1/2^\circ$ E., of cor. of rooflines extending N. $61\ 1/2^\circ$ E. and N. $29\ 1/4^\circ$ W.
35.19	Roofline of same house, 51 lks., N. $61\ 1/2^\circ$ E., of cor. of rooflines extending N. $61\ 1/2^\circ$ E. and S. $29\ 1/4^\circ$ E.
36.46	Fence, bears S. $69\ 1/2^\circ$ E. and N. $69\ 1/2^\circ$ W.
36.61	Long side of roofline of garage, 26.3 X 28.9 ft., 4 lks., N. $26\ 1/4^\circ$ E., of SE cor. of rooflines.
36.68	Cor. of fences extending S. $69\ 1/2^\circ$ E., S. $1/2^\circ$ E. and N. $1/4^\circ$ W., bears West, 59 lks. dist.
37.30	Long side of deck on house, 10.0 X 19.5 ft., 18 lks., S. 8° E., of the NW cor. of the deck.
37.48	Short side of same deck, 3 lks., N. 82° E., of the NW cor. of the deck.
37.97	Cor. of fences extending N. 88° E. and S. $1/4^\circ$ E., bears West, 59 lks. dist.
37.99	Fence, bears N. 88° E. and S. 88° W.
39.48	An open end iron pipe, 1/2 in. inside diam., firmly set 7 ins. below ground, with no marks, bears West, 58 lks. dist.
39.51	A rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with no marks, bears West, 61 lks. dist.
39.73	South edge of unpaved portion of West Osage, 24 ft. wide, bears S. $82\ 1/4^\circ$ E. and N. $82\ 1/4^\circ$ W.
40.10	A trail, 6 ft. wide, extending N. 73° W., from the end of West Osage, bears West, 11 lks. dist.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 7 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.24	An open end iron pipe, 1/2 in. inside diam., firmly set, 8 ins. below the ground, with no marks, bears West, 58 lks. dist., located on the southern edge of trail bearing S. 73° E. and N. 73° W.
40.25	A rebar, 1/2 in. diam., firmly set, projecting 2 ins. above the ground, with a red plastic shiner mkd. WERHAN, FOLKERS & MONIHAN RLS 18215.
40.34	Fence, 1 lk., S. 88 1/2° E., of cor. of fences extending S. 88 1/2° E. and N. 5 1/2° W.
40.36	<p>The 1/4 sec. cor. of secs. 28 and 29, monumented with a rebar, 1/2 in. diam., firmly set flush, with an alum. cap mkd. WFM 1/4 RLS 18215. This cor. was reestablished by James A. Folkers, Arizona Registered Land Surveyor No. 18215, in the course of a survey recorded in Docket 2018, Page 236, and Book 11 of maps, Page 70, Coconino County Recorder's Office. This is accepted as a careful and faithful reestablishment of the orig. cor. position.</p> <p>At the corner point</p> <p>Set an alum. post, 30 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with alum. cap mkd.</p> <p align="center">T 20 N R 7 E 1/4 S 29 S 28</p> <p align="center">2007</p> <p>Deposit a magnet in a white plastic case at the base, and the 18 ins. long rebar inside of the alum. post.</p> <p>From this cor. point, a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above the ground, with no marks, bears N. 54°25' W., 71 lks. dist. This is the apparent position used to control the layout of the Mountaineer subdivisions.</p> <hr/> <p>N. 0°25' W., beginning new measurement.</p>
2.20	Cor. of fences extending S. 5 1/2° E. and N. 82 3/4° W., bears West, 21 lks. dist.
2.24	Cor. of fences extending N. 6 1/4° E. and S. 82 3/4° E., bears West, 49 lks. dist.
3.71	Fence, bears S. 82 1/2° E. and N. 82 1/2° W.
3.73	Cor. of fences extending N. 21° E. and S. 82 1/2° E., bears West, 16 lks. dist.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 7 E., Gila and Salt River Meridian, Arizona**

CHAINS	
3.75	Terminus of fence extending S. 6 1/4° W., bears West, 31 lks. dist.
4.13	Fence, bears N. 21° E. and S. 21° W.
7.57	A rebar, 1/2 in. diam., firmly set flush with the ground, with a red plastic shiner mkd. WERHAN, FOLKERS & MONIHAN RLS 18215, located 1 lk. S. of a ponderosa pine, 20 ins. diam.
7.95	Fence, bears S. 89 3/4° E. and N. 89 3/4° W.
8.61	Cor. of fences extending N. 19 3/4° E. and S. 39 1/4° E., bears West, 90 lks. dist.
10.00	Cor. of fences extending N. 8 1/2° E. and S. 19 3/4° W., bears West, 39 lks. dist.
11.01	Cor. of fences extending N. 1/4° E. and S. 8 1/2° W., bears West, 23 lks. dist.
13.03	A rebar, 1/2 in. diam., firmly set, projecting 4 ins. above the ground, with an alum. cap mkd. MARTIN LS 18548, located at the N. base of a ponderosa pine, 20 ins. diam.
13.79	Fence, bears S. 86 1/2° E. and N. 86 1/2° W.
13.80	Cor. of fences extending N. 1/4° E., S. 86 1/2° E. and S. 1/4° W., bears West, 20 lks. dist.
14.54	Fence, bears S. 85 3/4° E. and N. 85 3/4° W.
14.55	Cor. of fences extending N. 1 3/4° E., S. 85 3/4° E. and S. 1/4° W., bears West, 19 lks. dist.
15.15	A rebar, 1/2 in. diam., firmly set, projecting 1 in. above the ground, with a red plastic shiner mkd. WERHAN, FOLKERS & MONIHAN RLS 18215. A rebar, 1/2 in. diam., firmly set, projecting 13 ins. above the ground, with no marks, is set alongside.
15.50	An open end iron pipe, 1/2 in. inside diam., firmly set, projecting 5 ins. above the ground, with no marks, bears West, 15 lks. dist., located in dilapidated portion of fence, bearing N. 5 1/4° E. and S. 1 3/4° W.
16.28	Fence, bears S. 81° E. and N. 81° W.
16.29	Cor. of fences extending S. 81° E., S. 5 1/4° W. and N. 1/4° W., bears West, 8 lks. dist.
18.87	Fence, bears S. 89 1/2° E. and N. 89 1/2° W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 7 E., Gila and Salt River Meridian, Arizona**

CHAINS	
18.89	A pair of rebar, a 3/8 in. diam., firmly set flush, and a 1/2 in. diam., firmly set, projecting 4 ins. above the ground, side by side, bears West, 7 lks. dist.
18.98	A rebar, 1/2 in. diam., firmly set, projecting 1 in. above the ground, in a collar of stone, with a red plastic shiner mkd. WERHAN, FOLKERS & MONIHAN RLS 18215.
25.42	A rebar, 1/2 in. diam., firmly set, 5 ins. below the ground, with a red plastic shiner mkd. WERHAN, FOLKERS & MONIHAN RLS 18215, located 3 lks. E. of a cor. of fences extending E. and N. 2 3/4° W.
28.37	Cor. of steel rail fences extending N. 1/4° E. and S. 2 3/4° E., bears West, 15 lks. dist.
28.65	The SW cor. of roofline for shed, 12.3 X 24.5 ft., bears West, 8 lks. dist., the long side of shed bears N. 3/4° E.
29.06	The SW cor. of concrete slab, 12 X 12 ft., enclosed by a fence, bears West, 7 lks. dist., slab extends N. 3/4° E. and S. 89 1/4° E.
32.15	A rebar, 1/2 in. diam., firmly set 1 in. below the ground, with a faded red plastic cap mkd. EXTREME MEASURERS RLS 26406.
32.18	Fence, bears E. and W.
32.67	Mountaineer Road, asphalt surfaced, 24 ft. wide, bears E. and W.
34.21	A fire hydrant, 7 ins. diam., projecting 2.1 ft. above the ground, painted yellow, with tag mkd. MFD 7, bears West, 30 lks. dist.
35.19	Cor. of fences extending N. 1 3/4° E. and N. 79 3/4° E., bears West, 39 lks. dist.
35.26	Fence, bears N. 79 3/4° E. and S. 79 3/4° W.
37.06	Cor. of fences extending N. 1 3/4° E., N. 84 1/2° E. and S. 1 3/4° W., bears West, 32 lks. dist.
37.09	Fence, bears N. 84 1/2° E. and S. 84 1/2° W.
38.11	Cor. of fences extending N. 82 3/4° E. and S. 1 3/4° W., bears West, 28 lks. dist.
38.14	Southerly stone and concrete gate pillar, 4 ft. base, 4.3 ft. high, 2 lks. E. of it's SW cor.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 7 E., Gila and Salt River Meridian, Arizona**

CHAINS	
38.28	Cattle guard, 7 X 18 ft., in line with center line of gravel driveway, 18 ft. wide, bears N. 87 3/4° E. and S. 87 3/4° W. Driveway is accessed off Forest Road No. 762.
38.46	Post with electric gate control, bears West, 28 lks. dist.
38.47	Northerly stone and concrete gate pillar, 4 ft. base, 4.3 ft. high, 2 lks. E. of it's SW cor.
38.52	Cor. of fences extending N. 1 3/4° E. and N. 87 1/4° E., bears West, 28 lks. dist.
40.36	<p>The cor. of secs. 20, 21, 28 and 29, monumented with a Bureau of Land Management iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. T20NR7E S20 S21 S29 S28 1966, from which an orig. bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 26 ins. diam., bears N. 60° E., 1.07 chs. dist., with faint scribe marks visible on a weathered blaze, with Forest Service standard sign 54-3 attached.</p> <p>and the 1966 bearing objects</p> <p style="padding-left: 40px;">The NW cor. of a stone fireplace, bears S. 51°43' E., 71 lks. dist. (Record: S. 50° E.)</p> <p style="padding-left: 40px;">A fence cor., bears N. 67° W., 23 lks. dist., with fences extending E. and S. 1 3/4° W.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears S. 41 3/4° W., 2.05 chs. dist., mkd. T20NR7ES29BT, with Forest Service standard sign 54-3 attached.</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears N. 14 3/4° W., 45 lks. dist., mkd. X BT, with Forest Service standard sign 54-3 attached.</p> <p>Add the marks 2007 to the brass cap.</p> <p>Set a steel sign post with attached Forest Service standard signs 54-2 and 54-9 nearby.</p> <hr/>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 7 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 21 and 28, monumented with a Bureau of Land Management iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with an accessory mound of stone, 2 ft. base, 1 ft. high, N. of the cor., with brass cap mkd. T20NR7E S21 1/4 S28 1966, from which the remains of an orig. bearing tree</p> <p>A ponderosa pine stump, 35 ins. diam., bears S. 45 1/2° E., 25 lks. dist., with Forest Service standard sign 54-3 attached.</p> <p>and the 1966 bearing tree</p> <p>A ponderosa pine, 13 ins. diam., bears N. 56° W., 36 lks. dist., with a healed blaze, with Forest Service standard sign 54-3 attached.</p> <p>and a new bearing tree</p> <p>A ponderosa pine, 14 ins. diam., bears S. 19 1/2° E., 59 lks. dist., mkd. 1/4S28BT, with Forest Service standard sign 54-3 attached.</p> <p>Add the marks 2007 to the brass cap.</p> <p>A steel sign post with attached Forest Service standard signs 54-2 and 54-9 is set nearby.</p> <p>S. 89°12' W., bet. secs. 21 and 28.</p>
19.895	<p>Point for the W. 1/16 sec. cor. of secs. 21 and 28.</p> <p>Set an alum. post, 30 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with alum. cap mkd.</p> <div style="text-align: center;"> <p>T 20 N R 7 E</p> <p>S 21</p> <p>W 1/16 ———</p> <p>S 28</p> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the alum. post.</p> <p>Set a steel sign post with attached Forest Service standard signs 54-2 and 54-9 nearby.</p> <p>Cor. is located at cor. of fences extending S. 1/4° W. and S. 87 1/2° W.</p>
34.95	<p>Fence, bears E. and W.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 7 E., Gila and Salt River Meridian, Arizona**

CHAINS	
37.36	The NE cor. of shed, 8.8 X 9.9 ft.
37.51	The NW cor. of same shed.
39.79	The cor. of secs. 20, 21, 28 and 29.
<hr/> <p>Subdivision of Section 28, T. 20 N., R. 7 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the 1/4 sec. cor. of secs. 28 and 33.
	N. 0°19' W., on the N. and S. center line of sec. 28.
0.07	Cor. of fences extending S. 85° E. and N. 3° W., bears East, 6 lks. dist.
1.28	Range fence, bears S. 3° E. and N. 3° W.
9.08	Cor. of range fences extending N., S. 1° W. and W., bears West, 4 lks. dist.
20.115	Point for the center S. 1/16 sec. cor. of sec. 28.
	Set an alum. post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with alum. cap mkd.
	T 20 N R 7 E C S 1/16 S 28 C 2007
	Deposit a magnet in a white plastic case at the base of the alum. post.
	Set a steel sign post with attached Forest Service standard signs 54-2 and 54-9 nearby.
	From this cor. point, an open end iron pipe, 1/2 in. inside diam., firmly set, projecting 1 in. above the ground, with no marks, bears N. 23°26' W., 19 lks. dist.
	Cor. is located on E. edge of foot trail, 6 ft. wide, bears N. and S., and 2 lks. W. of a range fence bears N. and S.
	Enter and pass through residential area.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 7 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.23	<p>Point for the center 1/4 sec. cor. of sec. 28, at intersection with the E. and W. center line.</p> <p>Set an alum. post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with alum. cap mkd.</p> <p align="center">T 20 N R 7 E C 1/4 S 28</p> <p align="center">2007</p> <p>Deposit a magnet in a white plastic case at the base of the alum. post.</p> <p>Set a steel sign post with attached Forest Service standard signs 54-2 and 54-9 nearby.</p>
80.98	<p>The 1/4 sec. cor. of secs. 21 and 28.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 27 and 28.</p> <p>S. 89°47' W., on the E. and W. center line of sec. 28.</p>
12.73	Fence, bears S. 6 3/4° E. and N. 6 3/4° W.
13.34	The NE cor. of roofline for shed, 5 X 10.6 ft., bears North, 3 lks. dist., the long side of the roofline bears S. 85° W.
13.49	An open end iron pipe, 3/8 in. inside diam., firmly set, projecting 2 ins. above the ground, with no marks, bears South, 6 lks. dist., located at SW cor. of roofline for shed, and at cor. of fences extending S. and S. 88° W.
14.24	An open end iron pipe, 3/8 in. inside diam., firmly set, projecting 3 ins. above the ground, with no marks, bears South, 8 lks. dist., located at cor. of fences extending N. 88° E., S. and S. 88° W.
15.13	Fence, 3 lks., S. 2 1/2° E. of cor. of fences extending S. 2 1/2° E. and S. 89 3/4° W.
15.76	Fence, 3 lks., S. 1/4° W. of cor. of fences extending S. 1/4° W. and W.
16.39	Roofline for shed, 8.2 X 9.4 ft., 3 lks., S. 1 1/2° W., of NE cor. of roofline. Long side of roofline bears S. 87 1/2° W. The NW cor. of roofline is identical with a cor. of fences extending S. 1 1/2° W. and W.
17.27	Fence, 3 lks. S. of cor. of fences extending E. and S.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 7 E., Gila and Salt River Meridian, Arizona**

CHAINS	
19.86	<p>Point for the center E. 1/16 sec. cor. of sec. 28.</p> <p>Set an alum. post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with alum. cap mkd.</p> <p align="center">T 20 N R 7 E E 1/16 C-----C S 28</p> <p align="center">2007</p> <p>Deposit a magnet in a white plastic case at the base of the alum. post.</p> <p>Set a steel sign post with attached Forest Service standard signs 54-2 and 54-9 nearby.</p>
39.72	The center 1/4 sec. cor. of sec. 28.
45.04	An open end iron pipe, 7/8 in. inside diam., firmly set, projecting 7 ins. above the ground, with no marks, bears South, 3 lks. dist., located at cor. of fences extending S. and N. 87 1/2° W.
46.27	Fence, 3 lks., S. 1° W., of cor. of fences extending S. 87 1/2° E. and S. 1° W.
47.79	An open end iron pipe, 3/4 in. inside diam., firmly set, projecting 8 ins. above the ground, with no marks, bears North, 8 lks. dist., located at cor. of fences extending S. 88 1/2° E. and S. 1 1/2° E.
50.41	A rebar, 1/2 in. diam., firmly set, projecting 1 in. above the ground, with a yellow plastic cap mkd. FOUR WINDS LS 27254, bears North, 8 lks. dist., located at cor. of fences extending S. 19 1/2° E., S. 31 1/4° W. and N. 19 1/2° W.
50.44	An open end iron pipe, 1/2 in. inside diam., firmly set, 2 ins. below the ground, with no marks, bears North, 17 lks. dist., located at cor. of fences extending S. 19 1/2° E. and N. 88° W.
52.60	An open end iron pipe, 1/2 in. inside diam., firmly set, 1 in. below the ground, with no marks, bears North, 25 lks. dist., located at cor. of fences extending S. 88° E., S. 7 3/4° W. and N. 88° W.
53.24	Gated footpath, 4 ft. wide, extending N. 60° E., bears North, 26 lks. dist.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 7 E., Gila and Salt River Meridian, Arizona**

CHAINS	
53.45	An open end iron pipe, 1/2 in. inside diam., firmly set, 1 in. below the ground, with no marks, bears North, 28 lks. dist., located at cor. of fences extending S. 88° E., S. 3 1/4° W. and N. 88 1/4° W.
53.74	Roofline of pump house, extending S. 84 3/4° E. and N. 84 3/4° W.
53.85	Roofline of same pump house, 1 lk. S. 5° W., of cor. of rooflines extending S. 84 3/4° E. and S. 5° W.
54.27	An open end iron pipe, 1/2 in. inside diam., firmly set, 1 in. below the ground, with no marks, bears North, 31 lks. dist., located at cor. of fences extending S. 88 1/4° E. and S. 2 1/2° E.
54.32	Footpath, 4 ft. wide, bears N. and S.
55.10	An open end iron pipe, firmly set, flush with the ground, with no marks, bears North, 34 lks. dist.
55.65	Stone retaining wall, 3 ft. high, bears S. 13° E. and N. 13° W.
55.84	Roofline of house, 8 lks., S. 4° W., of cor. of rooflines extending S. 4° W. and N. 86 3/4° W.
56.39	A willow tree, 9 ins. diam., bears North, 63 lks. dist.
56.63	Roofline of same house, 10 lks., S. 4° W., of cor. of roofline and deck.
56.68	The NW cor. of deck, 12.5 X 30.5 ft., bears North, 30 lks. dist., the long side of deck bears S. 86 3/4° E. A stone retaining wall, 1 ft. high, extends N. 2° E., from the same deck cor.
58.06	NE cor. of stone retaining wall, 2 ft. high, 31 ft. long, bears North, 91 lks. dist. Wall extends S. 37° W.
58.16	Fence, bears S. 32 1/4° E. and N. 32 1/4° W.
58.28	Cor. of fences extending S. 32 1/4° E. and N. 79° W., bears North, 18 lks. dist.
58.54	Long side of shed roofline, 12.1 X 20 ft., 12 lks., S. 1/4° E., of NE cor. of the roofline.
58.55	Wood retaining wall, 1 ft. high, 13 ft. long, extending N., bears North, 24 lks. dist.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 7 E., Gila and Salt River Meridian, Arizona**

CHAINS	
58.72	Roofline of same shed, 12 lks., S. 1/4° E., of NW cor. of roofline, common with the SW cor. of roofline for adjacent smaller shed, 8.8 X 11.2 ft., the long side of which bears N. 10 1/2° E.
58.76	Cor. of stone and wood retaining walls extending N. 89 3/4° E., 2 ft. high, 14 ft. long, and S. 8 3/4° W., 2 ft. high, 12 ft. long.
59.13	Fence, bears S. 15 1/2° E. and N. 15 1/2° W.
59.25	Cor. of fences extending S. 15 1/2° E. and S. 58° W., bears North, 42 lks. dist.
59.58	<p>Point for the center W. 1/16 sec. cor. of sec. 28.</p> <p>Set an alum. post, 30 ins. long, 2 1/2 ins. diam., flush with the ground, with alum. cap mkd.</p>
	<p align="center">T 20 N R 7 E W 1/16 C ——— C S 28 2007</p> <p>Deposit a magnet in a white plastic case at the base of the alum. post.</p> <p>Set a steel sign post with attached Forest Service standard signs 54-2 and 54-9 nearby.</p> <p>Enter and pass through residential area.</p>
79.44	The 1/4 sec. cor. of secs. 28 and 29.
	<hr/> <p>From the point for the W. 1/16 sec. cor. of secs. 28 and 33.</p> <p>N. 0°22' W., on the N. and S. center line of the SW 1/4 of sec. 28.</p>
20.145	<p>Point for the SW 1/16 sec. cor. of sec. 28, at intersection with the E. and W. center line of the SW 1/4 of sec. 28.</p> <p>Set an alum. post, 30 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, with alum. cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 7 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 20 N R 7 E SW 1/16 S 28 2007
	Deposit a magnet in a white plastic case at the base of the alum. post. Set a steel sign post with attached Forest Service standard signs 54-2 and 54-9 nearby. Cor. is located on lower right bank of drainage, 9 ft. wide, 3 ft. deep, drains N. 25° W. From this cor. point, an open end iron pipe, 5/8 in. inside diam., firmly set, projecting 3 ins. above the ground, with no marks, bears N. 20°33' E., 10 lks. dist.
40.29	The center W. 1/16 sec. cor. of sec. 28. <hr/> From the center S. 1/16 sec. cor. of sec. 28. S. 89°41' W., on the E. and W. center line of the SW 1/4 of sec. 28.
1.00	Track road transitioning into ATV trail, 5 ft. wide, bears N. and S.
1.14	The NE cor. of roofline for shed, 9.5 X 9.8 ft., bears South, 6 lks. dist., long side of roofline bears S. 3 1/2° E.
1.63	The NE cor. of roofline for shed, 9.4 X 14.2 ft., bears South, 8 lks. dist., long side of roofline bears S. 3 1/4° E.
2.26	ATV trail, 5 ft. wide, bears N. and S.
2.66	The NE cor. of roofline for small shed, 2 X 3 ft., bears South, 35 lks. dist., long side of roofline bears N. 87° W.
2.82	Fence for dog run, 35 lks., N. 1° W. of cor. of fences extending S. 89 1/2° W. and N. 1° W.
3.15	Fence for same dog run, 35 lks., N. 1° W. of cor. of fences extending N. 89 1/2° E. and N. 1° W.
3.51	A rebar, 1/2 in. diam., firmly set flush with the ground, with yellow plastic cap mkd. LS 31695, bears North, 17 lks. dist., located at base of S. side of utility pole.
8.21	Stone wall bordering unfinished patio, 16 lks., N. 39° E., of SE end of wall.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 7 E., Gila and Salt River Meridian, Arizona**

CHAINS	
8.51	Stone wall bordering same unfinished patio, 14 lks., N. 12° W. of the SW end of wall.
15.13	An open end iron pipe, 1/2 in. inside diam., firmly set, projecting 1 in. above the ground, with no marks, bears North, 11 lks. dist.
18.21	Approximate location of septic leach line, as indicated by land owner, bears N. 53 1/2° E. and S. 53 1/2° W.
18.26	The long side of a concrete step for entry to house, 5.5 X 5.7 ft. The southern most cor. of step bears S. 46° W., 2 lks. dist.
19.85	The SW 1/16 sec. cor. of sec. 28.
20.29	Terminus of low rail fence, extends S. 84 1/2° W.
22.16	Cor. of same low rail fence, bears South, 17 lks. dist. Fence extends N. 84 1/2° E. and N. 20° W.
22.34	North Celilo, asphalt surfaced, 24 ft. wide, bears S. 36° E. and N. 36° W.
22.51	Cor. of fences extending N. 88° W. and N. 20° W., bears South, 15 lks. dist.
24.78	The terminus of a fence extending S. 88° E., bears South, 6 lks. dist.
28.09	Long side of roofline for shed, 11.9 X 13.6 ft., 9 lks., N. 2° W. of the SE cor. of the roofline.
28.24	An open end, iron pipe, 1/2 in. inside diam., firmly set, projecting 1 in. above the ground, with no marks, bears North, 11 lks. dist.
30.54	Cor. of fences extending N. and N. 88° W., bears South, 37 lks. dist.
31.22	The NE cor. of roofline for shed, 12 X 12.3 ft., bears South, 3 lks. dist., long side of roofline bears S. 7 1/2° W.
31.26	Cor. of fences extending N. 9° E. and S. 88° E., bears South, 35 lks. dist.
32.82	ATV trail, 8 ft. wide, bears S. 25° W., extending from the SW end of N. Shoshone.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 7 E., Gila and Salt River Meridian, Arizona**

CHAINS	
35.23	Abandoned railroad grade, 10 ft. wide, bears N. and S.
38.79	North Iroquois, asphalt paved, 21 ft. wide, 15 lks. N. of end of pavement, bears N. and S.
39.70	The S. 1/16 sec. cor. of secs. 28 and 29.
	<hr/> <p>From the center W. 1/16 sec. cor. of sec. 28.</p> <p>N. 0°22' W., on the N. and S. center line of the NW 1/4 of sec. 28.</p>
0.22	Fence, bears N. 58° E. and S. 58° W.
0.42	A rebar, 1/2 in. diam., firmly set, 2 ins. below the ground, with a red plastic shiner mkd. WERHAN, FOLKERS & MONIHAN RLS 18215.
4.44	A rebar, 1/2 in. diam., firmly set, projecting 2 ins. above the ground, with a yellow plastic cap mkd. RLS 22258, located at cor. of fences extending W. and N. 1/4° W.
10.34	Cor. of fences extending S. 1/4° E. and W.
15.36	A rebar, 1/2 in. diam., firmly set, projecting 1 in. above the ground, with a red plastic shiner mkd. WERHAN, FOLKERS & MONIHAN RLS 18215, located 1/2 lk. NW of tree used as cor. of fences extending W. and N. 1/4° W.
24.92	A rebar, 1/2 in. diam., firmly set, projecting 1 in. above a mound of stone, 3 ft. base, 1/2 ft. high, with a faded red plastic shiner mkd. WERHAN, FOLKERS & MONIHAN RLS 18215, located 1 lk. E. of fence bearing S. 1/4° E. and N. 1/4° W.
33.34	Terminus of fence extending S. 1/4° E.
33.35	A rebar, 1/2 in. diam., firmly set, projecting 2 ins. above the ground, with an alum. cap mkd. 2007, bears West, 8 lks. dist., located at cor. of fences extending N. 1/4° E. and W.
40.55	The W. 1/16 sec. cor. of secs. 21 and 28.
	<hr/>

T. 20 N., R. 7 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

This survey is the identification of lands managed by the Coconino National Forest, and the trespasses created by the location of the Mountaineire subdivisions. Primary access is by Mountaineire Road, off of Interstate 17, approximately 6 miles South of Flagstaff. Subdivision streets and Forest Service roads providing the balance.

The elevation of the project ranges from 6750 ft. in the valley floor to 6930 ft. at the top of the hills. The flora and fauna of the area is typical to the Rocky Mountain montane conifer forest biotic community, consisting of moderately dense ponderosa pine forest with scattered oak, broken by relatively open grassland. Few elk were seen in comparison to the amount of sign observed. A large number of squirrels inhabit the area.

The mean magnetic declination of 11 1/2° E. was derived from the National Geophysical Data Center's magnetic declination calculator, GEOMAG v6.0, utilizing the International Geomagnetic Reference Field model for years 2005 through 2010, for the dates of survey.
