

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF THE SIXTH GUIDE MERIDIAN EAST (EAST BOUNDARY)

AND

THE SURVEY OF THE SUBDIVISIONAL LINES,

TOWNSHIP 26 NORTH, RANGE 24 EAST,

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA

EXECUTED BY

Jones Curtiss, Cadastral Surveyor

Under Special Instructions dated July 31, 2006, approved July 31, 2006, which provided for the surveys included under Group No. 987, and assignment instructions dated July 31, 2006.

Survey commenced August 1, 2006

Survey completed October 5, 2006

INDEX DIAGRAM

TOWNSHIP 26 NORTH RANGE 24 EAST
 GILA AND SALT RIVER MERIDIAN, ARIZONA

6 59 58	5 48 58	4 40 47	3 31 39	2 23 31	1 14 23
7 57 56	8 46 55	9 38 46	10 30 37	11 22 29	12 14 21
18 55 54	17 45 53	16 37 44	15 29 36	14 20 28	13 13 20
19 52 52	20 43 51	21 35 43	22 27 34	23 19 27	24 10 18
30 50 50	29 42 49	28 34 41	27 26 33	26 17 25	25 6 16
31 48	32 40	33 32	34 24	35 15	36 4

T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of the Sixth Guide Meridian East (east boundary) and the survey of the subdivisional lines, Township 26 North, Range 24 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

The south boundary of the Navajo Indian Reservation (abandoned) was surveyed by John G. Evans in 1884-85. The Sixth Guide Meridian East (west boundary) of Township 26 North, Range 25 East and a portion of the north boundary of Township 25 North, Range 24 East was surveyed by Frederick C. Miller in 1915. The south boundary of Township 27 North, Range 25 East was dependently resurveyed by William F. Olver, Leonard R. Sandoval and Olian T. Shockley in 1989-90. The east boundary of Township 25 North, Range 23 East was surveyed by Jones Curtiss in 2001-02. The Sixth Guide Meridian East (east boundary) and a portion of the north boundary was dependently resurveyed and a portion of the north boundary of Township 25 North, Range 24 East was surveyed by Jones Curtiss in 2001-02. The east boundary of Township 26 North, Range 23 East was surveyed by Leonard R. Sandoval in 2002. The south boundary, Township 27 North, Range 24 East was surveyed by Jones Curtiss in 2004.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated July 31, 2006, for Group Number 987, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation Model 5700 receivers.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Surveys Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (COR) DUECECLUBSAZ2005 CORS ARP, GRANTS NMDOT CORS ARP, and CHACOCNHP_NM2005 CORS ARP. The NAD83 (CORS96) (EPOCH:2002) geographic position of the southeast corner of the township is as follows:

Latitude: 35°36'17.10" N. Longitude: 109°43'12.06" W.

The mean declination is 11° E.

**Dependent Resurvey of the Sixth Guide Meridian (East Boundary),
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p style="text-align: center;">Restoring the survey executed by Frederick C. Miller, in 1915</p> <hr/> <p>Beginning at the cor. of Tps. 25 and 26 N., Rs. 24 and 25 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T26N R24E R25E S36 S31 S1 S6 T25N 2002 1915.</p> <p>Add the marks 2006 to the brass cap.</p> <p>N. 0°03' E., bet. secs. 31 and 36.</p> <p>Over rolling land.</p>
39.93	<p>The 1/4 sec. cor. of secs. 31 and 36, monumented with an iron post, 1 in. diam., badly bent, firmly set, projecting 2 ins. above ground, with brass cap mkd. 1/4 S36 S31 1915.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N 1/4 R 24 E R 25 E S 36 S 31</p> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the iron post, 36 ins. long, alongside the stainless steel post.</p> <p>Cor. is located 1.51 chs. S. of Apache County Road C414, a graded road, 30 ft. wide, bears N. 40° E. and S. 40° W.</p> <hr/> <p>N. 0°01' W., beginning new measurement.</p> <p>Over rolling land.</p>
10.00	<p>Point for the S-N 1/64 sec. cor. of secs. 31 and 36, at proportionate dist., there is no remaining evidence of the orig. cor.</p>

Dependent Resurvey of the Sixth Guide Meridian (East Boundary),
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N S-N 1/64 R 24 E R 25 E S 36 S 31</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
20.00	<p>Point for the N. 1/16 sec. cor. of secs. 31 and 36, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N N 1/16 R 24 E R 25 E S 36 S 31</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
25.60	<p>S. bank of Pueblo Colorado Wash, 5 ft. high, bears S. 85° E. and N. 85° W.</p>
28.15	<p>Pueblo Colorado Wash, 30 ft. wide, 4 ft. deep, drains S. 60° W.</p>
30.00	<p>Point for the N-N 1/64 sec. cor. of secs. 31 and 36, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N N-N 1/64 R 24 E R 25 E S 36 S 31</p> <p style="text-align: center;">2006</p>

**Dependent Resurvey of the Sixth Guide Meridian (East Boundary),
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS													
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.												
31.00	N. bank of Pueblo Colorado Wash, 6 ft. high, bears N. 50° E. and S. 50° W.												
33.00	Apache County Road C414, a graded road, 30 ft. wide, bears S. 70° E. and N. 70° W.												
40.00	The cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 3 ins. diam., firmly set, flush with surface of the ground, with brass cap partial destroyed and mkd. T26N R24E R25E S25 S30 S36 S31 1915.												
	At the corner point												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.												
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td></td><td align="center">T 26 N</td><td></td></tr> <tr><td align="center">R 24 E</td><td align="center"> </td><td align="center">R 25 E</td></tr> <tr><td align="center">S 25</td><td align="center"> </td><td align="center">S 30</td></tr> <tr><td align="center">S 36</td><td align="center"> </td><td align="center">S 31</td></tr> </table>		T 26 N		R 24 E		R 25 E	S 25		S 30	S 36		S 31
	T 26 N												
R 24 E		R 25 E											
S 25		S 30											
S 36		S 31											
	2006												
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.												
	Bury the iron post, 36 ins. long, alongside the stainless steel post.												
	<hr/>												
	N. 0°08' E., bet. secs. 25 and 30.												
	Over rolling land.												
10.03	The S-S 1/64 sec. cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., badly bent, firmly set, projecting 12 ins. above ground, with brass cap erroneously mkd. S1/64 S19 S30 1915.												
	At the corner point												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.												

Dependent Resurvey of the Sixth Guide Meridian (East Boundary),
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 26 N S-S 1/64 R 24 E R 25 E S 25 S 30</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the iron post, 36 ins. long, alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°01' E., beginning new measurement.</p> <p>Over rolling land.</p>
10.00	<p>Point for the S. 1/16 sec. cor. of secs. 25 and 30, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 26 N S 1/16 R 24 E R 25 E S 25 S 30</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
12.30	<p>Point for the meander cor. of secs. 25 and 30 originally set on the left bank of Pueblo Colorado Wash, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">MC ----- S 25 S 30 R 24 E R 25 E T 26 N 2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>

**Dependent Resurvey of the Sixth Guide Meridian (East Boundary),
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS																
13.80	<p>Point for the meander cor. of secs. 25 and 30 originally set on the right bank of Pueblo Colorado Wash, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td></td><td>T 26 N</td><td></td></tr> <tr><td>R 24 E</td><td> </td><td>R 25 E</td></tr> <tr><td>S 25</td><td> </td><td>S 30</td></tr> <tr><td colspan="3"><hr/></td></tr> <tr><td></td><td>MC</td><td></td></tr> </table> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>		T 26 N		R 24 E		R 25 E	S 25		S 30	<hr/>				MC	
	T 26 N															
R 24 E		R 25 E														
S 25		S 30														
<hr/>																
	MC															
20.00	<p>The N-S 1/64 sec. cor. of secs. 25 and 30, monumented with a badly decayed iron post, 1 in. diam., firmly set, 14 ins. below the surface of the ground, with the brass cap erroneously mkd. S 1/64 S19 S30 1915.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td></td><td>T 26 N</td><td></td></tr> <tr><td></td><td>N-S</td><td></td></tr> <tr><td></td><td>1/64</td><td></td></tr> <tr><td>R 24 E</td><td> </td><td>R 25 E</td></tr> <tr><td>S 25</td><td> </td><td>S 30</td></tr> </table> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the iron post, 36 ins. long, alongside the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>North, beginning new measurement.</p> <p>Over rolling land.</p>		T 26 N			N-S			1/64		R 24 E		R 25 E	S 25		S 30
	T 26 N															
	N-S															
	1/64															
R 24 E		R 25 E														
S 25		S 30														
10.01	<p>The 1/4 sec. cor. of secs. 25 and 30, monumented with a badly decayed iron post, 1 in. diam., firmly set, 18 ins. below the surface of the ground, with brass cap mkd. 1/4 S25 S30 1915.</p> <p>At the corner point</p>															

**Dependent Resurvey of the Sixth Guide Meridian (East Boundary),
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N 1/4 R 24 E R 25 E S 25 S 30</p> <p align="center">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the iron post, 36 ins. long, alongside the stainless steel post.</p> <hr/> <p>N. 0°01' E., beginning new measurement.</p> <p>Over rolling land.</p>
10.00	<p>The S-N 1/64 sec. cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., firmly set, 16 ins. below the surface of the ground, with brass cap mkd. 1/64 S25 S30 1915.</p> <p>Reset the iron post, 32 ins. in the ground and remark the brass cap to read</p> <p align="center">T 26 N S-N 1/64 R 24 E R 25 E S 25 S 30</p> <p align="center">2006 1915</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>North, beginning new measurement.</p> <p>Over rolling land.</p>
10.005	<p>Point for the N. 1/16 sec. cor. of secs. 25 and 30, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Sixth Guide Meridian (East Boundary),
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.01	<p style="text-align: center;">T 26 N R 24 E R 25 E N 1/16 S 25 S 30</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the N-N 1/64 sec. cor. of secs. 25 and 30, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
30.015	<p style="text-align: center;">T 26 N N-N 1/64 R 24 E R 25 E S 25 S 30</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 19, 24, 25, and 30, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
10.005	<p style="text-align: center;">T 26 N R 24 E R 25 E S 24 S 19 S 25 S 30</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>North, bet. secs. 19 and 24.</p> <p>Over rolling land.</p> <p>The S-S 1/64 sec. cor. of secs. 19 and 24, monumented with an iron post, 1 in. diam., badly bent, firmly set, flush with surface of the ground, with brass cap mkd. 1/64 S24 S19 1915.</p>

Dependent Resurvey of the Sixth Guide Meridian (East Boundary),
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 26 N S-S 1/64 R 24 E R 25 E S 24 S 19</p>
	2006
	Deposit a magnet, in a white plastic case, at the base of the
	stainless steel post.
	Bury the iron post, 36 ins. long, alongside the stainless steel
	post.
	<hr style="width: 30%; margin: auto;"/> <p style="text-align: center;">N. 0°02' W., beginning new measurement.</p>
7.20	Power line, bears N. 40° E. and S. 40° W.
10.02	The S. 1/16 sec. cor. of secs. 19 and 24, monumented with an
	iron post, 1 in. diam., firmly set, 2 ins. below surface of the
	ground, with brass cap mkd. S 1/16 S24 S19 1915.
	Remark the brass cap to read
	<p style="text-align: center;">T 26 N S 1/16 R 24 E R 25 E S 24 S 19</p>
	2006
	1915
	<hr style="width: 30%; margin: auto;"/> <p style="text-align: center;">North, beginning new measurement.</p>
	Over rolling land.
10.00	The N-S 1/64 sec. cor. of secs. 19 and 24, monumented with an
	iron post, 1 in. diam., badly bent, firmly set, 3 ins. below the
	surface of the ground, with brass cap mkd. 1/64 S24 S19 1915.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the Sixth Guide Meridian (East Boundary),
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 26 N N-S 1/64 R 24 E R 25 E S 24 S 19 2006
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Bury the iron post, 36 ins. long, alongside the stainless steel post. <hr/> N. 0°02' E., beginning new measurement. Over rolling land.
4.68	Navajo Route 15, asphalt pavement, 25 ft. wide, bears N. 20° E. and S. 20° W.
8.33	A brass tablet, 3 ins. diam., set flush in a concrete post, 6 ins. diam., firmly set, projecting 8 ins. above ground, bears East, 9 lks. dist., with top mkd. B I A ROAD 19, witnessed by a 4 in. angle iron to the S., firmly set, projecting 24 ins. above ground, mkd. STA. PT 504+80.28 on the side.
8.37	Barbed wire fence, 3 strands, parallels highway.
10.01	The 1/4 sec. cor. of secs. 19 and 24, monumented with an iron post, 1 in. diam., firmly set, 7 ins. below surface of the ground, with brass cap mkd. 1/4 S24 S19 1915. Remark the brass cap to read T 26 N 1/4 R 24 E R 25 E S 24 S 19 2006 1915
	<hr/> N. 0°02' E., beginning new measurement. Over rugged and broken land, ascend S. slope of a mesa.
1.92	Barbed wire fence, 3 strands, bears S. 70° E. and N. 70° W.
40.06	Point for the cor. of secs. 13, 18, 19 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.

Dependent Resurvey of the Sixth Guide Meridian (East Boundary),
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T 26 N</td></tr> <tr><td style="text-align: center;">R 24 E</td><td style="text-align: center;">R 25 E</td></tr> <tr><td style="text-align: center;">S 13</td><td style="text-align: center;">S 18</td></tr> <tr><td style="text-align: center;">S 24</td><td style="text-align: center;">S 19</td></tr> </table> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/>	T 26 N		R 24 E	R 25 E	S 13	S 18	S 24	S 19
T 26 N									
R 24 E	R 25 E								
S 13	S 18								
S 24	S 19								
	<p>N. 0°02' E., bet. secs. 13 and 18.</p> <p>Over rugged and broken land.</p>								
40.06	<p>The 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 1 in. diam., badly bent, firmly set, projecting 3 ins. above ground, with brass cap mkd. 1/4 S13 S18 1915.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T 26 N</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">R 24 E</td><td style="text-align: center;">R 25 E</td></tr> <tr><td style="text-align: center;">S 13</td><td style="text-align: center;">S 18</td></tr> </table> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the iron post, 36 ins. long, alongside the stainless steel post.</p> <hr/>	T 26 N		1/4		R 24 E	R 25 E	S 13	S 18
T 26 N									
1/4									
R 24 E	R 25 E								
S 13	S 18								
38.75	<p>N. 0°01' E., beginning new measurement.</p> <p>Over rolling and broken land.</p>								
40.00	<p>Rim, edge of mesa, bears S. 50° E. and N. 50° W.</p> <p>The cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 3 ins. diam., firmly set, projecting 13 ins. above ground, with brass cap erroneously mkd. T26N R25E S1 S6 S12 S7 R24E 1915.</p> <p>At the corner point</p>								

**Dependent Resurvey of the Sixth Guide Meridian (East Boundary),
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> <table border="0"> <tr><td colspan="2">T 26 N</td></tr> <tr><td>R 24 E</td><td>R 25 E</td></tr> <tr><td>S 12</td><td>S 7</td></tr> <tr><td>S 13</td><td>S 18</td></tr> </table> </p> <p align="center">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the iron post, 36 ins. long, alongside the stainless steel post.</p> <hr/> <p>N. 0°04' E., bet. secs. 7 and 12.</p> <p>Over rugged and broken land.</p>	T 26 N		R 24 E	R 25 E	S 12	S 7	S 13	S 18
T 26 N									
R 24 E	R 25 E								
S 12	S 7								
S 13	S 18								
39.995	<p>Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> <table border="0"> <tr><td colspan="2">T 26 N</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>R 24 E</td><td>R 25 E</td></tr> <tr><td>S 12</td><td>S 7</td></tr> </table> </p> <p align="center">2006</p> <p>from which a bearing tree irreconcilable with record</p> <p align="center">A forked piñon, 24 ins. diam. at base, bears S. 72° E., 1.05 chs. dist., mkd. 1/4 S7 on partially healed blaze.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 26 N		1/4		R 24 E	R 25 E	S 12	S 7
T 26 N									
1/4									
R 24 E	R 25 E								
S 12	S 7								
79.99	<p>The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. T26N R25E S1 S6 S12 S7 R24E 1915.</p> <p>Add the marks 2006 to the brass cap.</p> <hr/> <p>N. 0°04' E., bet. secs. 1 and 6.</p> <p>Over rolling land.</p>								

**Dependent Resurvey of the Sixth Guide Meridian (East Boundary),
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.02	<p>Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N 1/4 R 24 E R 25 E S 1 S 6</p> <p align="center">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.04	<p>The cor. of Tps. 26 and 27 N., Rs. 24 and 25 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T27N R24E R25E S36 S31 S1 S6 T26N 1990 2004 1915.</p> <p>Add the marks 2006 to the brass cap.</p> <hr/> <p align="center">Survey of the Subdivisional Lines, T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T26N R24E S35 S36 S2 S1 T25N 2002.</p> <p>Add the marks 2006 to the brass cap.</p> <p>Cor. is located 20 lks. S. of the S. flood bank of Pueblo Colorado Wash, 5 ft. high, bears N. 60° E. and S. 60° W.</p> <p>N. 0°01' E., bet. secs. 35 and 36.</p> <p>Over rolling land.</p>
8.80	Pueblo Colorado Wash, 100 ft. wide, 3 ft. deep, drains S. 80° W.
17.60	N. flood bank of Pueblo Colorado Wash, 15 ft. high, bears N. 80° E. and S. 80° W.
30.04	Power line, bears N. 45° E. and S. 45° W.
31.60	Underground water line, bears N. 45° E. and S. 45° W.
36.36	Navajo Route 15, asphalt pavement, 25 ft. wide, bears N. 62° E. and S. 62° W.

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 24 E 1/4 S 35 S 36</p> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
41.50	Rim, edge of mesa, bears S. 75° E. and N. 75° W.
65.00	Rim, edge of mesa, bears S. 70° E. and N. 70° W.
80.00	<p>Point for the cor. of secs. 25, 26, 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 24 E S 26 S 25 S 35 S 36</p> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, greasewood, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°57' W., bet. secs. 25 and 36.</p> <p>Over rolling and broken land.</p>
12.50	Apache County Road C414, a graded road, 30 ft. wide, bears S. 60° E. and N. 60° W.
39.00	Power line, bears N. 20° E. and S. 20° W.
40.02	Point for the 1/4 sec. cor. of secs. 25 and 36.

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. below the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 24 E S 25 1/4 ——— S 36</p> <p style="text-align: center;">2006</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 60°00' W., 215.0 ft. dist., with brass cap mkd. RM T26N R24E 1/4 S36 215.0 FT. TO COR. 2006 and an arrow pointing to the corner. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 40°00' W., 174.0 ft. dist., with brass cap mkd. RM T26N R24E 1/4 S25 174.0 FT. TO COR. 2006 and an arrow pointing to the corner. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post at the 1/4 sec. cor.</p>
40.43	Navajo Route 15, asphalt pavement, 25 ft. wide, bears N. 20° E. and S. 20° W.
46.50	Rim, edge of mesa, bears N. 25° E. and S. 25° W.
59.40	Rim, edge of mesa, bears N. 15° E. and S. 15° W.
80.04	The cor. of secs. 25, 26, 35 and 36.
	<p>Land, rolling and broken. Soil, sandy and sandy clay. Timber, scattered juniper; undergrowth, sagebrush, and native grasses.</p> <hr/> <p>N. 0°01' E., bet. secs. 25 and 26.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 26 N R 24 E 1/4 S 26 S 25 2006
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 23, 24, 25 and 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 24 E S 23 S 24 ----- S 26 S 25 2006
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rugged and broken. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, sagebrush, cacti and native grasses.
	From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.
	West, bet. secs. 24 and 25.
	Over rolling and broken land.
12.26	Navajo Route 15, asphalt pavement, 25 ft. wide, bears N. 20° E. and S. 20° W.
18.45	Rim, edge of mesa, bears N. 20° E. and S. 20° W.
36.00	Rim, edge of mesa, bears S. 75° E. and N. 75° W.
39.80	Wash, 10 ft. wide, 6 ft. deep, drains S. 15° E.
40.02	Point for the 1/4 sec. cor. of secs. 24 and 25.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 26 N R 24 E S 24 1/4 <u> </u> S 25</p> <p style="text-align: center;">2006</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
44.20	<p>Rim, edge of mesa, bears S. 80° E. and N. 80° W.</p>
64.50	<p>Rim, edge of mesa, bears S. 30° E. and N. 30° W.</p>
80.04	<p>The cor. of secs. 23, 24, 25 and 26.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/>
	<p>N. 0°01' E., bet. secs. 23 and 24.</p> <p>Over rugged and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 26 N R 24 E 1/4 S 23 S 24</p> <p style="text-align: center;">2006</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 13, 14, 23 and 24.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 26 N R 24 E S 14 S 13 <u> </u> S 23 S 24</p> <p style="text-align: center;">2006</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rugged and broken land. Soil, sandy and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°56' W., bet. secs. 13 and 24.</p> <p>Over rugged and broken land.</p>
34.05	Rim, edge of mesa, bears N. 20° E. and S. 20° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 24 E S 13 1/4 ——— S 24</p> <p>2006</p> </div>
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, Scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>N. 0°01' E., bet. secs. 13 and 14.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 24 E 1/4 S 14 S 13</p> <p>2006</p> </div>

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>								
80.00	<p>Point for the cor. of secs. 11, 12, 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 26 N</td> <td style="padding: 0 10px;">R 24 E</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 11</td> <td style="padding: 0 10px;">S 12</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 14</td> <td style="padding: 0 10px;">S 13</td> </tr> </table> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°53' W., bet. secs. 12 and 13.</p> <p>Over rolling and broken land.</p>	T 26 N	R 24 E	S 11	S 12	S 14	S 13		
T 26 N	R 24 E								
S 11	S 12								
S 14	S 13								
1.70	<p>Rim, edge of mesa, bears S. 50° E. and N. 50° W.</p>								
25.20	<p>Rim, edge of mesa, bears North and South.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 26 N</td> <td style="padding: 0 10px;">R 24 E</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">S 12</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">1/4 ———</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">S 13</td> </tr> </table> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 26 N	R 24 E		S 12		1/4 ———		S 13
T 26 N	R 24 E								
	S 12								
	1/4 ———								
	S 13								
80.00	<p>The cor. of secs. 11, 12, 13 and 14.</p>								

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>N. 0°01' E., bet. secs. 11 and 12.</p> <p>Over rolling land.</p>
6.00	Navajo Route 9057, a graded road, 20 ft. wide, bears N. 40° E. and S. 40° W.
39.35	Rim, edge of mesa, bears S. 40° E. and N. 40° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 24 E 1/4 S 11 S 12</p> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
62.70	Trail road, bears N. 60° E. and S. 60° W.
80.00	<p>Point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 24 E S 2 S 1 S 11 S 12</p> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°54' W., bet. secs. 1 and 12.</p> <p>Over rolling land.</p>
22.57	Navajo Route 9057, a graded road, 20 ft. wide, bears N. 30° E. and S. 30° W.
40.02	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 24 E S 1 1/4 ——— S 12</p> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
59.90	Trail road, bears N. 45° E. and S. 45° W.
80.04	<p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>N. 0°05' E., bet. secs. 1 and 2.</p> <p>Over rolling and broken land.</p>
38.85	S. bank of a wash, 25 ft. high, bears S. 40° E. and N. 40° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a magnet, in a white plastic case, 24 ins. below the surface of the ground.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45°00' E., 50.0 ft. dist., with brass cap mkd. RM T26N R24E 1/4 S1 50.0 FT. TO COR. 2006 and an arrow pointing to the corner. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 45°00' W., 50.0 ft. dist., with brass cap mkd. RM T26N R24E 1/4 S2 50.0 FT. TO COR. 2006 and an arrow pointing to the corner. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in a wash, 50 ft. wide, 25 ft. deep, drains N. 35° W.</p>
80.29	<p>The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R24E S35 S36 S2 S1 T26N 2004.</p> <p>Add the marks 2006 to the brass cap.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, and native grasses.</p> <hr/> <p>From the cor. of secs. 34 and 35 only, on the S. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T26N R24E S34 S35 T25N R24E S2 2002 1915.</p> <p>Add the marks 2006 to the brass cap.</p> <p>N. 0°01' E., bet. secs. 34 and 35.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 24 E 1/4 S 34 S 35 2006</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
42.30	Trail road, bears N. 55° E. and S. 55° W.								
80.00	Point for the cor. of secs. 26, 27, 34 and 35.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 26 N</td> <td>R 24 E</td> </tr> <tr> <td>S 27</td> <td>S 26</td> </tr> <tr> <td>S 34</td> <td>S 35</td> </tr> </table>	T 26 N	R 24 E	S 27	S 26	S 34	S 35		
T 26 N	R 24 E								
S 27	S 26								
S 34	S 35								
	2006								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Land, rolling.								
	Soil, sand and sandy clay.								
	Timber, scattered piñon and juniper; undergrowth, sagebrush, native grasses.								
	<hr/>								
	From the cor. of secs. 25, 26, 35 and 36.								
	N. 89°59' W., bet. secs. 26 and 35.								
	Over rolling and broken land.								
9.90	Rim, edge of mesa, bears N. 15° E. and S. 15° W.								
21.30	Navajo Route 9031, a graded road, 20 ft. wide, bears S. 65° E. and N. 65° W.								
40.04	Point for the 1/4 sec. cor. of secs. 26 and 35.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 26 N</td> <td>R 24 E</td> </tr> <tr> <td></td> <td>S 26</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 35</td> </tr> </table>	T 26 N	R 24 E		S 26	1/4	—		S 35
T 26 N	R 24 E								
	S 26								
1/4	—								
	S 35								
	2006								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Set a steel fence post nearby.								

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Cor. is located 8 lks. S. of the S. edge of Navajo Route 9031, a graded road, 20 ft. wide, bears S. 65° E. and N. 65° W.
80.08	The cor. of secs. 26, 27, 34 and 35. Land, rolling and broken. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.
	N. 0°01' E., bet. secs. 26 and 27. Over rolling and broken land.
4.45	Navajo Route 9031, a graded road, 20 ft. wide, bears S. 70° E. and N. 70° W.
28.90	Apache County Road C429, a graded road, 20 ft. wide, bears S. 25° E. and N. 25° W.
40.00	Point for the 1/4 sec. cor of secs. 26 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 24 E 1/4 S 27 S 26 2006
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 22, 23, 26 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 24 E S 22 S 23 S 27 S 26 2006
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper, undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26. N. 89°59' W., bet. secs. 23 and 26. Over rugged and broken land.</p>
38.00	Rim, edge of mesa, bears S. 10° E. and N. 10° W.
40.04	<p>Point for the 1/4 sec. cor. of secs. 23 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 24 E S 23 1/4 ——— S 26</p> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
52.65	Navajo Route 9057, a graded road, 20 ft. wide, bears N. 10° E., S. 10° W.
80.08	<p>The cor. of secs. 22, 23, 26 and 27. Land, rolling and broken. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 0°01' E., bet. secs. 22 and 23. Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 26 N R 24 E 1/4 S 22 S 23 2006
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 14, 15, 22 and 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 24 E S 15 S 14 S 22 S 23 2006
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, sagebrush and native grasses.
	<hr/> From the cor. of secs. 13, 14, 23 and 24. N. 89°59' W., bet. secs. 14 and 23. Over rolling and broken land.
33.45	Navajo Route 9057, a graded road, 20 ft. wide, bears N. 35° E. and S. 35° W.
35.70	Trail road, bears N. 70° E. and S. 70° W.
40.04	Point for the 1/4 sec. cor. of secs. 14 and 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 24 E S 14 1/4 ——— S 23 2006

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.08	The cor. of secs. 14, 15, 22 and 23. Land, rolling and broken land. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.
	<hr/>
	N. 0°01' E., bet. secs. 14 and 15. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 24 E 1/4 S 15 S 14 2006 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 10, 11, 14 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 24 E S 10 S 11 --- --- S 15 S 14 2006 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper, undergrowth, sagebrush and native grasses.
	<hr/>
	From the cor. of secs. 11, 12, 13 and 14. N. 89°59' W., bet. secs. 11 and 14.

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling and broken land.
1.55	Navajo Route 9057, a graded road, 20 ft. wide, bears N. 5° E. and S. 5° W.
40.04	Point for the 1/4 sec. cor. of secs. 11 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 24 E S 11 1/4 ——— S 14 2006 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.08	The cor. of secs. 10, 11, 14 and 15. Land, rolling and broken. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.
	<hr/> N. 0°01' E., bet. secs. 10 and 11. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 24 E 1/4 S 10 S 11 2006 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 2, 3, 10 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS					
	<p align="center">T 26 N R 24 E <table border="1" style="margin: auto;"> <tr> <td style="padding: 2px;">S 3</td> <td style="padding: 2px;">S 2</td> </tr> <tr> <td style="padding: 2px;">S 10</td> <td style="padding: 2px;">S 11</td> </tr> </table> 2006</p>	S 3	S 2	S 10	S 11
S 3	S 2				
S 10	S 11				
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/>				
	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°59' W., bet. secs. 2 and 11.</p> <p>Over rolling land.</p>				
<p>40.04</p>	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>				
	<p align="center">T 26 N R 24 E <table style="margin: auto;"> <tr> <td style="padding: 2px;">S 2</td> <td style="padding: 2px;">1/4 ———</td> </tr> <tr> <td style="padding: 2px;">S 11</td> <td></td> </tr> </table> 2006</p>	S 2	1/4 ———	S 11	
S 2	1/4 ———				
S 11					
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>				
<p>80.08</p>	<p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/>				
	<p>N. 0°08' E., bet. secs. 2 and 3.</p> <p>Over rolling and broken land.</p>				
<p>9.50</p>	<p>Trail road, bears N. 45° E. and S. 45° W.</p>				
<p>40.00</p>	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p>				

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a magnet, in a white plastic case, 24 ins. below the surface of the ground.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 10°00' E., 50.0 ft. dist., with brass cap mkd. RM T26N R24E 1/4 S2 50.0 FT. TO COR. 2006 and an arrow pointing to the corner. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 10°00' W., 50.0 ft. dist., with brass cap mkd. RM T26N R24E 1/4 S3 50.0 FT. TO COR. 2006 and an arrow pointing to the corner. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in a wash, 16 ft. wide, 8 ft. deep, drains N. 20° W.</p>
80.36	<p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R24E S34 S35 S3 S2 T26N 2004.</p> <p>Add the marks 2006 to the brass cap.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 33 and 34 only, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T26N R24E S33 S34 T25N R24E S3 2002.</p> <p>Add the marks 2006 to the brass cap.</p> <p>North, bet. secs. 33 and 34.</p> <p>Over rolling and broken land.</p>
16.20	Trail road, bears N. 75° E. and S. 75° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 26 N R 24 E 1/4 S 33 S 34 2006
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
43.10	Trail road, bears S. 85° E. and N. 85° W.
80.00	Point for the cor. of secs. 27, 28, 33 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 24 E S 28 S 27 S 33 S 34 2006
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling and broken. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.
	From the cor. of secs. 26, 27, 34 and 35.
	N. 89°52' W., bet. secs. 27 and 34.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 24 E S 27 1/4 ——— S 34 2006
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 27, 28, 33 and 34.

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper, undergrowth, sagebrush and native grasses.</p> <hr/> <p>North, bet. secs. 27 and 28.</p> <p>Over rolling and broken land.</p>
14.60	Navajo Route 9031, a graded road, 20 ft. wide, bears S. 45° E. and N. 45° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 24 E 1/4 S 28 S 27</p> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 21, 22, 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 24 E S 21 S 22 S 28 S 27</p> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs 22, 23, 26 and 27.</p> <p>N. 89°52' W., bet. secs. 22 and 27.</p> <p>Over rolling and broken land.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
13.35	Apache County Road C429, a graded road, 20 ft. wide, bears North and South.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 24 E S 22 1/4 ——— S 27 2006 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 21, 22, 27 and 28. Land, rolling and broken. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses. <hr/>
	North, bet. secs. 21 and 22. Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 22. Set a magnet, in a white plastic case, 24 ins. below the surface of the ground. from which <div style="margin-left: 40px;"> A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45°00' E., 60.0 ft. dist., with brass cap mkd. RM T26N R24E 1/4 S22 60.0 FT. TO COR. 2006 and an arrow pointing to the corner. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 45°00' W., 60.0 ft. dist., with brass cap mkd. RM T26N R24E 1/4 S21 60.0 FT. TO COR. 2006 and an arrow pointing to the corner. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. </div> Cor. is located in a wash, 6 ft. wide, 2 ft. deep, drains S. 40° E.

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
55.40	Trail road, bears N. 75° E. and S. 75° W.
80.00	<p>Point for the cor. of secs. 15, 16, 21 and 22.</p> <p>Set a magnet, in a white plastic case, 24 ins. below the surface of the ground.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 25°00' E., 30.0 ft. dist., with brass cap mkd. RM T26N R24E S22 30.0 FT. TO COR. 2006 and an arrow pointing to the corner. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 25°00' W., 30.0 ft. dist., with brass cap mkd. RM T26N R24E S16 30.0 FT. TO COR. 2006 and an arrow pointing to the corner. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on the S. bank of a wash, 20 ft. wide, 10 ft. deep, drains S. 65° W.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr style="width: 60%; margin-left: 0;"/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 89°52' W., bet. secs. 15 and 22.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T 26 N R 24 E</p> <p> S 15</p> <p> 1/4 ———</p> <p> S 22</p> <p> 2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
48.90	Apache County Road C429, a graded road, 20 ft. wide, bears N. 5° E. and S. 5° W.
80.00	The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and cacti and native grasses.
	<hr/>
	North, bet. secs. 15 and 16. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 24 E 1/4 S 16 S 15 2006 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
61.75	Apache County Road C429, a graded road, 20 ft. wide, bears S. 45° E. and N. 45° W.
80.00	Point for the cor. of secs. 9, 10, 15 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 24 E S 9 S 10 <hr style="width: 50%; margin: 0 auto;"/> S 16 S 15 2006 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.
	<hr/>
	From the cor. of secs. 10, 11, 14 and 15.

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>N. 89°52' W., bet. secs. 10 and 15.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 24 E</p> <p>S 10</p> <p>1/4 ———</p> <p>S 15</p> </div> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 10 lks. E. of the E. bank of a wash, 20 ft. deep, bears N. 20° E. and S. 20° W.</p>
40.90	<p>Wash, 10 ft. wide, 2 ft. deep, drains S. 25° W.</p>
80.00	<p>The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, rolling.</p> <p>Soil, sand and sandy clay.</p> <p>Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>North, bet. secs. 9 and 10.</p> <p>Over rolling land.</p>
31.05	<p>Sand Dunes Wash, 40 ft. wide, 2 ft. deep, drains S. 35° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 24 E</p> <p>1/4</p> <p>S 9 S 10</p> </div> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS									
73.15	Apache County Road C429, a graded road, 20 ft. wide, bears N. 80° E. and S. 80° W.								
80.00	<p>Point for the cor. of secs. 3, 4, 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 26 N</td> <td>R 24 E</td> </tr> <tr> <td>S 4</td> <td>S 3</td> </tr> <tr> <td>S 9</td> <td>S 10</td> </tr> </table> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11. N. 89°52' W., bet. secs. 3 and 10. Over rolling land.</p>	T 26 N	R 24 E	S 4	S 3	S 9	S 10		
T 26 N	R 24 E								
S 4	S 3								
S 9	S 10								
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 26 N</td> <td>R 24 E</td> </tr> <tr> <td>S 3</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 10</td> <td></td> </tr> </table> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 26 N	R 24 E	S 3		1/4	—	S 10	
T 26 N	R 24 E								
S 3									
1/4	—								
S 10									
73.35	Apache County Road C429, a graded road, 20 ft. wide, bears N. 15° E. and S. 15° W.								
80.00	The cor. of secs. 3, 4, 9 and 10.								

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>N. 0°07' E., bet. secs. 3 and 4.</p> <p>Over rolling land.</p>
10.05	Apache County Road C429, a graded road, 20 ft. wide, bears S. 60° E. and N. 60° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 24 E 1/4 S 4 S 3 2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.26	<p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R24E S33 S34 S4 S3 T26N 2004.</p> <p>Adds the marks 2006 to the brass cap.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 32 and 33 only, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T26N R24E S32 S33 T25N R24E S4 2002.</p> <p>Add the marks 2006 to the brass cap.</p> <p>North, bet. secs. 32 and 33.</p> <p>Over rolling and land.</p>
40.00	Point for the 1/4 sec. cor. of secs. 32 and 33.

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 24 E 1/4 S 32 S 33</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
78.45	S. bank of Sand Dunes Wash, 1 ft. high, bears N. 35° E. and S. 35° W.
80.00	<p>Point for the cor. of secs. 28, 29, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 24 E S 29 S 28 S 32 S 33</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 90 lks. S. of Navajo Route 9031, a graded road, 20 ft. wide, bears S. 25° E. and N. 25° W.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 89°52' W., bet. secs. 28 and 33.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 26 N R 24 E S 28 1/4 ——— S 33 2006
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
52.60	Navajo Route 9031, a graded road, 20 ft. wide, bears N. 65° E. and S. 65° W.
70.05	Trail road, bears N. 35° E. and S. 35° W.
78.90	S. bank of Sand Dunes Wash, 1 ft. high, bears N. 35° E. and S. 35° W.
79.55	Navajo Route 9031, a graded road, 20 ft. wide, bears S. 25° E. and N. 25° W.
80.00	The cor of secs. 28, 29, 32 and 33. Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.
	North, bet. secs. 28 and 29. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 24 E 1/4 S 29 S 28 2006
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
43.10	S. bank of Sand Dunes Wash, 1 ft. high, bears N. 20° E. and S. 20° W.
54.25	N. bank of Sand Dunes Wash, 1 ft. high, bears N. 45° E. and S. 45° W.

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS									
80.00	<p>Point for the cor. of secs. 20, 21, 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 26 N</td> <td>R 24 E</td> </tr> <tr> <td>S 20</td> <td>S 21</td> </tr> <tr> <td>S 29</td> <td>S 28</td> </tr> </table> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; sagebrush and native grasses.</p> <hr/>	T 26 N	R 24 E	S 20	S 21	S 29	S 28		
T 26 N	R 24 E								
S 20	S 21								
S 29	S 28								
	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N. 89°52' W., bet. secs. 21 and 28.</p> <p>Over rolling land.</p>								
27.15	<p>Trail road, bears N. 15° E. and S. 15° W.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 26 N</td> <td>R 24 E</td> </tr> <tr> <td></td> <td>S 21</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 28</td> </tr> </table> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 26 N	R 24 E		S 21	1/4	—		S 28
T 26 N	R 24 E								
	S 21								
1/4	—								
	S 28								
73.35	<p>Sand Dunes Wash, 100 ft. wide, 6 ft. deep, drains S. 25° W.</p>								
80.00	<p>The cor. of secs. 20, 21, 28 and 29.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>North, bet. secs. 20 and 21.</p>								

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
4.30	Trail road, bears N. 5° E. and S. 5° W.
13.36	The SW cor. of a sandstone masonry house, 25 x 16 ft., bears East, 1.06 chs. dist., long side bears N. 5° E.
14.23	The SW cor. of a frame house, 24 x 16 ft., bears East, 9 lks. dist., long side bears N. 15° E.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 24 E 1/4 S 20 S 21 2006 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 16, 17, 20 and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 24 E S 17 S 16 S 20 S 21 2006 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.
	From the cor. of secs. 15, 16, 21 and 22. N. 89°52' W., bet. secs. 16 and 21. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 21.

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 24 E S 16 1/4 ——— S 21</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
46.30	Sand Dunes Wash, 40 ft. wide, 10 ft. deep, drains S. 5° E.
80.00	<p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>North, bet. secs. 16 and 17.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 24 E 1/4 S 17 S 16</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 8, 9, 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 24 E S 8 S 9 S 17 S 16</p> <p style="text-align: center;">2006</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 89°52' W., bet. secs. 9 and 16.</p> <p>Over rolling land.</p>
11.05	Apache County Road C429, a graded road, 20 ft. wide, bears S. 5° E. and N. 5° W.
26.70	Sand Dunes Wash, 40 ft. wide, 10 ft. deep, drains S. 15° W.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 16.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 24 E S 9 1/4 ——— S 16</p> <p style="text-align: center;">2006</p>
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>North, bet. sec. 8 and 9.</p> <p>Over rolling land.</p>
23.40	Trail road, bears S. 80° E. and N. 80° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 26 N R 24 E 1/4 S 8 S 9 2006
80.00	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Point for the cor. of secs. 4, 5, 8 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 24 E S 5 S 4 S 8 S 9 2006
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.
40.00	<hr/> From the cor. of secs. 3, 4, 9 and 10. N. 89°52' W., bet. secs. 4 and 9. Over rolling land. Point for the 1/4 sec. cor. of secs. 4 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 24 E S 4 1/4 ——— S 9 2006
80.00	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. The cor. of secs. 4, 5, 8 and 9.

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 0°07' E., bet. secs. 4 and 5.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 26 N R 24 E 1/4 S 5 S 4 2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
69.70	<p>Apache County Road C429, a graded road, 20 ft. wide, bears S. 50° E. and N. 50° W.</p>
80.18	<p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R24E S32 S33 S5 S4 T26N 2004.</p> <p>Add the marks 2006 to the brass cap.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 31 and 32 only, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T26N R24E S31 S32 T25N R24E S5 2002.</p> <p>Add the marks 2006 to the brass cap.</p> <p>N. 0°01' W., bet. secs. 31 and 32.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 24 E 1/4 S 31 S 32</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 29, 30, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 24 E S 30 S 29 S 31 S 32</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 89°52' W., bet. secs. 29 and 32.</p> <p>Over rolling and broken land.</p>
3.95	<p>N. bank of Sand Dunes Wash, 1 ft. high, bears N. 45° E. and S. 45° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 24 E S 29 1/4 ——— S 32</p> <p style="text-align: center;">2006</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 29, 30, 31 and 32. Land, rolling and broken. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.
	<hr/>
	N. 89°52' W., bet. secs. 30 and 31. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 24 E S 30 1/4 ——— S 31 2006
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
81.67	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. T26N R23E R24E S25 S30 S36 S31 2002. Add the marks 2006 to the brass cap. Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.
	<hr/>
	From the cor. of secs. 29, 30, 31 and 32. N. 0°01' W., bet. secs. 29 and 30. Over rolling land.
38.85	Trail road, bears N. 45° E. and S. 45° W.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 30.

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 24 E 1/4 S 30 S 29</p> <p style="text-align: center;">2006</p> <p>from which</p> <p style="text-align: center;">The NW cor. of a stucco house, 32 x 29 ft., bears N. 86 1/4° E., 2.08 chs. dist., long side bears S. 15° W.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
52.85	Navajo Route 9031, a graded road, 20 ft. wide, bears S. 85° E. and N. 85° W.
80.00	<p>Point for the cor. of secs. 19, 20, 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 24 E S 19 S 20 S 30 S 29</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>N. 89°52' W., bet. secs. 20 and 29.</p> <p>Over rolling land.</p>
1.20	Trail road, bears N. 15° E. and S. 15° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 26 N R 24 E S 20 1/4 ——— S 29 2006
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor of secs. 19, 20, 29 and 30. Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper, undergrowth, sagebrush and native grasses.
	<hr/> N. 89°52' W., bet. secs. 19 and 30. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 24 E S 19 1/4 ——— S 30 2006
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
81.63	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T26N R23E R24E S24 S19 S25 S30 2002. Add the marks 2006 to the brass cap. Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper, undergrowth, sagebrush and native grasses.
	<hr/> From the cor. of secs. 19, 20, 29 and 30. N. 0°01' W., bet. secs. 19 and 20.

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
9.10	Trail road, bears S. 80° E. and N. 80° W.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 24 E 1/4 S 19 S 20 2006 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
58.40	Trail road, bears S. 60° E. and N. 60° W.
80.00	Point for the cor. of secs. 17, 18, 19 and 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 24 E S 18 S 17 S 19 S 20 2006 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, sagebrush and native grasses.
	From the cor. of secs. 16, 17, 20 and 21. N. 89°52' W., bet. secs. 17 and 20. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 26 N R 24 E S 17 1/4 ——— S 20 2006
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
47.80	Trail road, bears North and South.
65.25	Trail road, bears N. 5° E. and S. 5° W.
80.00	The cor. of secs. 17, 18, 19 and 20. Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, sagebrush and native grasses.
	N. 89°52' W., bet. secs. 18 and 19. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 18 and 19. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 24 E S 18 1/4 ——— S 19 2006
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
81.59	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T26N R23E R24E S13 S18 S24 S19 2002. Add the marks 2006 to the brass cap.

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20. N. 0°01' W., bet. sec. 17 and 18. Over rolling land.</p>
24.45	Trail road, bears S. 80° E. and N. 80° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 24 E 1/4 S 18 S 17</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
51.55	Trail road, bears N. 65° E. and S. 65° W.
80.00	<p>Point for the cor. of secs. 7, 8, 17 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 24 E S 7 S 8 S 18 S 17</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17. N. 89°52' W., bet. secs. 8 and 17.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
38.50	Trail road, bears N. 45° E. and S. 45° W.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 24 E S 8 1/4 ——— S 17 2006 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 7, 8, 17 and 18. Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, sagebrush and native grasses.
	<hr/> N. 89°52' W., bet. secs. 7 and 18. Over rolling land.
20.90	Trail road, bears N. 10° E. and S. 10° W.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 24 E S 7 1/4 ——— S 18 2006 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
65.55	Trail road, bears N. 20° E. and S. 20° W.

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
81.55	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T26N R23E R24E S12 S7 S13 S18 2002.</p> <p>Add the marks 2006 to the brass cap.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18. N. 0°01' W., bet. secs. 7 and 8. Over rolling land.</p>
28.75	Trail road, bears N. 40° E. and S. 40° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 24 E 1/4 S 7 S 8</p> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
58.20	Trail road, bears S. 20° E. and N. 20° W.
80.00	<p>Point for the cor. of secs. 5, 6, 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 24 E S 6 S 5 S 7 S 8</p> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9. N. 89°52' W., bet. secs. 5 and 8. Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 24 E S 5 1/4 ——— S 8</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 5, 6, 7 and 8. Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 89°52' W., bet. secs. 6 and 7. Over rolling land.</p>
11.95	Trail road, bears N. 35° E. and S. 35° W.
22.35	Trail road, bears N. 85° E. and S. 85° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 7. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 26 N R 24 E S 6 1/4 ——— S 7 2006
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
47.40	Trail road, bears S. 5° E. and N. 5° W.
81.51	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T26N R23E R24E S1 S6 S12 S7 2002.
	Add the marks 2006 to the brass cap.
	Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, sagebrush and native grasses.
	From the cor. of secs. 5, 6, 7 and 8.
	N. 0°06' E., bet. secs. 5 and 6.
	Over rolling land.
16.65	Trail road, bears N. 35° E. and S. 35° W.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 6.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 24 E 1/4 S 6 S 5 2006
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
58.30	Trail road, bears N. 75° E. and S. 75° W.
80.09	The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R24E S31 S32 S6 S5 T26N 2004.

**Survey of the Subdivisional Lines,
T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Add the marks 2006 to the brass cap.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p>The area surveyed is within the Navajo Indian Reservation and approximately 10 miles southwest of Ganado, Arizona. The terrain is mostly rolling with broken land in the southern and southeast portion of the township. The drainage is southwesterly through the central portion of the township with Sand Dune Wash being the main drainage. Pueblo Colorado Wash drains southwest through the southeastern portion of the township.</p> <p>The elevation varies from 6100 to 6700 feet above sea level. The soil is sand and sandy clay, with sandstone outcrops and ledges along the slopes of the mesas and canyons. The timber consists of piñon and juniper in the northerly portion of the township where it is mostly rolling hills. Undergrowth consists of greasewood and rabbit brush in the valleys and cacti and dense areas of sagebrush at the higher elevations.</p> <p>Principal access to the township is provided by Navajo Route 15. The highway enters the township in section 24 and extends southwesterly, exiting in section 35. From this main highway Navajo Routes 9057, 9031 and Apache County Road C429 extend northwesterly into the township. Much of this area is used for grazing of livestock. There are numerous permanent residences throughout the township. There is no mining activity in the township.</p> <p>The mean magnetic declination of 11° E. was derived from the computer program GEOMAGIX, utilizing the World Magnetic Model for Epoch 2005 for the dates of survey.</p> <hr/>
--------	---

CERTIFICATE OF SURVEY

I, Jones Curtiss, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 31st day of July, 2006, I have dependently resurveyed the Sixth Guide Meridian East (east boundary) and surveyed the subdivisional lines, T. 26 N., R. 24 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

November 08, 2007
(Date)

Jones Curtiss
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the Sixth Guide Meridian East (East Boundary) and the survey of the subdivisional lines, T. 26 N., R. 24 E., Gila and Salt River Meridian, in the State of Arizona, executed by Jones Curtiss, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

Jan 11, 2009
(Date)

Stephen K. Ham
(Chief Cadastral Surveyor of Arizona)

 CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 26 N., R. 24 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.

(Date)

(Chief Cadastral Surveyor of Arizona)
