

ORIGINAL

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE  
DEPENDENT RESURVEY OF  
THE SOUTH AND WEST BOUNDARIES,  
THE SUBDIVISIONAL LINES,  
AND  
THE SUBDIVISION OF SECTIONS 6, 24, 32 and 34,  
**TOWNSHIP 22 NORTH, RANGE 19 EAST,**  
OF THE GILA AND SALT RIVER MERIDIAN,  
IN THE STATE OF ARIZONA

**EXECUTED BY**

**Leonard R. Sandoval, Cadastral Surveyor**

Under Special Instructions dated and approved September 24, 2007, which provided for the surveys included under Group No. 1024, and assignment instructions dated September 24, 2007.

**Survey commenced October 1, 2007**

**Survey completed December 20, 2007**

## INDEX DIAGRAM

TOWNSHIP 22 NORTH                      RANGE 19 EAST  
GILA AND SALT RIVER MERIDIAN, ARIIZONA

15	6	61	5	49	4	41	3	32	2	24	1
	61		60		49		40		32		23
14	7	59	8	48	9	39	10	31	11	23	12
	59		58		47		39		30		22
13	18	57	17	46	16	38	15	29	14	20	13
	56		55		46		37		28		20
12	19	54	20	45	21	36	22	28	23	19	24
	53		53		44		36		27		18
11	30	52	29	43	28	35	27	26	26	17	25
	51		51		42		34		25		16
10	31	50	32	41	33	33	34	25	35	15	36
	9		8		7		6		5		4

Subdivision Sec. 6  
Subdivision Sec. 24  
Subdivision Sec. 32  
Subdivision Sec. 34

Pg. 62  
Pg. 63  
Pg. 64  
Pg. 65

## T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes describe the dependent resurvey of the south and west boundaries, the subdivisional lines, and the subdivision of sections 6, 24, 32 and 34, Township 22 North, Range 19 East, Gila and Salt River Meridian, Arizona.

A. P. Johnson surveyed the north boundary, Township 21 North, Range 18 East, in 1883 and surveyed the south, east, west and north boundaries, and the subdivisional lines, Township 22 North, Range 19 East, in 1883. Ty White dependently resurveyed the Fifth Standard Parallel North (south boundary), Township 21 North, Range 18 East, in 1947. Geoffrey A. Graham dependently resurveyed the south boundary, Townships 23 North, Ranges 19 and 20 East, in 2004-05. Jones Curtiss dependently resurveyed the south and west boundaries, Township 22 North, Range 20 East, in 2006. Gordon R. Bubel and Joel A. Emert dependently resurveyed the south boundary, Township 23 North, Range 18 East, in 2006-07.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated September 24, 2007, for Group Number 1024, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Some of the recovered evidence of the 1883 survey included stones, marked and unmarked, set in the ground, at the east edge of mounds of stone. If only a mound of stone was recovered, a position at the east edge of the mound of stone is accepted as the best available evidence of the orig. cor. position.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) Ashler Hills, Ferno Mesa, and SpiderrockAZ2005. The NAD 83 (CORS96)(Epoch 2002)(Epoch:2007.7144), geographic position of the southeast corner of the township is as follows:

Latitude: 35°15'26.85" N.                      Longitude: 110°16'01.52" W.

The mean magnetic declination is 11° E.

**Dependent Resurvey of the South Boundary,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS

Restoring the survey executed by  
A. P. Johnson, in 1883

---

Beginning at the cor. of the Tps. 21 and 22 N., Rs. 19 and 20 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T22N R19E R20E S36 S31 S1 S6 T21N 2006, with a mound of stone, 3 ft. base, 1 ft. high, S. of cor.

Add the marks 2007 to the brass cap.

S. 89°43' W., bet. secs. 1 and 36.

Over rolling and broken land.

39.67

Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate dist., there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N R 19 E  
S 36  
1/4 ———  
S 1  
T 21 N  
  
2007

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

79.34

The cor. of secs. 1, 2, 35 and 36, monumented with a basalt stone, 16 x 10 x 6 ins., firmly set, 5 ins. in the ground, at the E. edge of a scattered mound of stone, faintly mkd. 4 grooves on W. face.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N R 19 E  
S 35 | S 36  
S 2 | S 1  
T 21 N  
  
2007

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Dependent Resurvey of the South Boundary,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS							
	<p>Bury the basalt stone alongside the stainless steel post.</p> <p>Rebuild the mound of stone, 3 ft. base, 1 ft. high, W. of cor.</p> <hr/> <p>S. 89°49' W., bet. secs. 2 and 35.</p> <p>Over rolling and broken land.</p>						
2.30	Wash, 30 ft. wide, 8 ft. deep, drains S. 30° E., with a trail road in the bed.						
27.20	Wash, 30 ft. wide, 6 ft. deep, drains S. 30° E.						
40.11	<p>Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 19 E</p> <p>S 35</p> <p>1/4 ———</p> <p>S 2</p> <p>T 21 N</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>						
79.10	Wash, 40 ft. wide, 6 ft. deep, drains S. 65° W.						
80.22	<p>The cor. of secs. 2, 3, 34 and 35, determined at the E. edge of an embedded mound of stone, 3 ft. base, 8 ins. high, and is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 19 E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 34</td> <td style="padding: 0 5px;">S 35</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 3</td> <td style="padding: 0 5px;">S 2</td> </tr> <tr> <td colspan="2" style="text-align: center;">T 21 N</td> </tr> </table> <p>2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> </div>	S 34	S 35	S 3	S 2	T 21 N	
S 34	S 35						
S 3	S 2						
T 21 N							

**Dependent Resurvey of the South Boundary,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Rebuild the mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 15 lks. W. of a trail road, bears S. 45° E. and N. 45° W.</p> <hr/> <p>S. 89°44' W., bet. secs. 3 and 34.</p> <p>Over rolling and broken land.</p>
39.00	Trail road, bears S. 10° E. and N. 10° W.
39.65	Trail road, bears S. 35° E. and N. 35° W.
40.145	<p>Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 19 E</p> <p>S 34</p> <p>1/4 ———</p> <p>S 3</p> <p>T 21 N</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
70.95	Trail road, bears N. 40° E. and S. 40° W.
77.60	Wash, 20 ft. wide, 2 ft. deep, drains S. 10° E.
80.29	<p>The cor. of secs. 3, 4, 33 and 34, determined at the E. edge of an embedded mound of stone, 2 ft. base, 6 ins. high, and is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the South Boundary,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS											
	<table style="margin: auto;"> <tr><td>T 22 N</td><td>R 19 E</td></tr> <tr><td>S 33</td><td>S 34</td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td colspan="2">T 21 N</td></tr> </table> <p style="text-align: center;">2007</p>	T 22 N	R 19 E	S 33	S 34	S 4	S 3	T 21 N			
T 22 N	R 19 E										
S 33	S 34										
S 4	S 3										
T 21 N											
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Retain the orig. mound of stone W. of cor.</p> <p>Set a steel fence post nearby.</p> <hr/> <p>S. 88°03' W., bet. secs. 4 and 33.</p> <p>Over rolling and broken land.</p>										
37.67	<p>Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										
	<table style="margin: auto;"> <tr><td>T 22 N</td><td>R 19 E</td></tr> <tr><td>S 33</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 4</td><td></td></tr> <tr><td colspan="2">T 21 N</td></tr> </table> <p style="text-align: center;">2007</p>	T 22 N	R 19 E	S 33		1/4	—	S 4		T 21 N	
T 22 N	R 19 E										
S 33											
1/4	—										
S 4											
T 21 N											
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>										
69.70	<p>Trail road, bears S. 55° E. and N. 55° W.</p>										
75.34	<p>The cor. of secs. 4, 5, 32 and 33, monumented with the decayed remains of a juniper post, set flush with the surface of the ground and 8 ins. deep, with a rebar, 20 ins. long, 1/2 in. diam., of unknown origin, firmly set, projecting 2 ins. above ground, alongside, with the top portion of the juniper post, 34 ins. long, 4 ins. diam., lying loose nearby, mkd. with faint scribe marks on a side.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										

**Dependent Resurvey of the South Boundary,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 22 N R 19 E	
S 32	S 33
S 5	S 4
T 21 N	

2007

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Bury the juniper post alongside, and deposit the rebar, inside, the stainless steel post

Set a steel fence post nearby.

---

N. 88°40' W., bet. secs. 5 and 32.

Over rolling land.

41.16

Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate dist., there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N R 19 E	
S 32	
1/4 ———	
S 5	
T 21 N	

2007

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

82.32

Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist., there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N R 19 E	
S 31	S 32
S 6	S 5
T 21 N	

2007

**Dependent Resurvey of the South Boundary,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 68 lks. N. of Navajo Route 9857, a graded road, 20 ft. wide, bears S. 80° E. and N. 80° W.</p> <hr/> <p>N. 88°40' W., bet. secs. 6 and 31.</p> <p>Over rolling land.</p>								
5.00	Navajo Route 9857, a graded road, 20 ft. wide, bears S. 80° E. and N. 80° W.								
41.16	<p>Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 19 E</p> <p>S 31</p> <p>1/4 ———</p> <p>S 6</p> <p>T 21 N</p> <p>2007</p> </div>								
80.08	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the cor. of Tps. 21 and 22 N., Rs. 18 and 19 E., at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R 18 E</td> <td style="padding: 0 5px;">R 19 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 36</td> <td style="padding: 0 5px;">S 31</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 1</td> <td style="padding: 0 5px;">S 6</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">T 21 N</td> </tr> </table> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	R 18 E	R 19 E	S 36	S 31	S 1	S 6	T 21 N	
R 18 E	R 19 E								
S 36	S 31								
S 1	S 6								
T 21 N									

**Dependent Resurvey of the South Boundary,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this cor. point, the stan. cor. of Tps. 21 N., Rs. 18 and 19 E., bears S. 0°09' E., 482.42 chs. dist., monumented with an iron post, 3 ins. diam., set 12 ins. below the surface of ground, with brass cap mkd. SC T21N R18E R19E S36 S31 1947, with a wood fence post nearby. Add the marks 2007 to the brass cap. Cor is located in a barbed wire fence, 5 strand, bears East and West.

The control line was fully retraced, and no evidence of the intervening cors. was found.

From this same cor. point, the 1/4 sec. cor. of secs. 1 and 36, T. 22 N., R. 18 E., bears N. 88°47' W., 41.15 chs. dist., determined at record bearing and dist. from the orig. accessory post

A juniper post, 3 ins. diam., firmly set, projecting 10 ins. above ground, bears East, 5 1/2 ft. dist., mkd. 1/4 on N. side.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N   R 18 E  
          S 36  
1/4 ———  
          S 1  
          T 21 N

2007

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Retain the orig. accessory post in place.

---

Dependent Resurvey of the West Boundary,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona

---

Restoring the survey executed by  
A. P. Johnson, in 1883

---

From the cor. of Tps. 21 and 22 N., Rs. 18 and 19 E., hereinbefore described.

N. 0°25' W., bet. secs. 31 and 36.

Over rolling and broken land.

**Dependent Resurvey of the West Boundary,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS									
16.13	Power line, bears East and West.								
25.10	Navajo Route 9857, a graded road, 20 ft. wide, bears S. 65° E. and N. 65° W.								
40.20	Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 22 N</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>R 18 E</td><td>R 19 E</td></tr> <tr><td>S 36</td><td>S 31</td></tr> </table> <p>2007</p> </div>	T 22 N		1/4		R 18 E	R 19 E	S 36	S 31
T 22 N									
1/4									
R 18 E	R 19 E								
S 36	S 31								
80.40	Point for the cor. of secs. 25, 30, 31 and 36, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 22 N</td></tr> <tr><td>R 18 E</td><td>R 19 E</td></tr> <tr><td>S 25</td><td>S 30</td></tr> <tr><td>S 36</td><td>S 31</td></tr> </table> <p>2007</p> </div>	T 22 N		R 18 E	R 19 E	S 25	S 30	S 36	S 31
T 22 N									
R 18 E	R 19 E								
S 25	S 30								
S 36	S 31								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	<hr/> <p>N. 0°25' W., bet. secs. 25 and 30.</p> <p>Over rolling land.</p>								
34.85	Trail road, bears S. 55° E. and N. 55° W.								
37.00	Power line, bears N. 50° E. and S. 50° W.								
40.20	Point for the 1/4 sec. cor. of secs. 25 and 30, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								

**Dependent Resurvey of the West Boundary,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N 1/4 R 18 E   R 19 E S 25   S 30  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
42.80	Underground water pipeline, bears N. 50° E. and S. 50° W.
57.18	Navajo Route 60, asphalt pavement, 25 ft. wide, bears N. 50° E. and S. 50° W.
80.40	The cor. of secs. 19, 24, 25 and 30, monumented with a juniper post, 42 ins. long, 3 ins. diam., firmly set, projecting 24 ins. above ground, mkd. with illegible scribe marks on blazed E. side.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 18 E   R 19 E S 24   S 19 S 25   S 30  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Bury the juniper post alongside the stainless steel post.
	<hr/>
	N. 0°05' W., bet. secs. 19 and 24.
	Over rolling land.
40.20	The 1/4 sec. cor. of secs. 19 and 24, monumented with a broken sandstone, 20 x 12 x 2 ins., reassembled size, with bottom portion, firmly set, 3 ins. in the ground, top portion mkd. 1/4 on W. face.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the West Boundary,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N 1/4 R 18 E   R 19 E S 24   S 19  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Bury the sandstone pieces alongside the stainless steel post. <hr/> N. 0°03' W., beginning new measurement.  Over rolling land.
31.15	Trail road, bears S. 75° E. and N. 75° W.
37.85	Power line, bears S. 80° E. and N. 80° W.
40.24	The cor. of secs. 13, 18, 19 and 24, determined at the E. edge of an embedded mound of stone, 3 ft. base, flush with the surface of the ground, and is accepted as the best available evidence of the orig. cor. position.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, utilize the orig. mound of stone in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T 22 N R 18 E   R 19 E S 13   S 18 <hr/> S 24   S 19  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. <hr/> N. 1°56' E., bet. secs. 13 and 18.  Over rolling and broken land.
39.70	Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the West Boundary,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N 1/4 R 18 E   R 19 E S 13   S 18  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
79.40	Point for the cor. of secs. 7, 12, 13 and 18, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 18 E   R 19 E S 12   S 7 S 13   S 18  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	<hr/> N. 1°56' E., bet. secs. 7 and 12.  Over rolling land.
39.70	Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N 1/4 R 18 E   R 19 E S 12   S 7  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
75.95	Power line, bears S. 70° E. and N. 70° W.
79.40	Point for the cor. of secs. 1, 6, 7 and 12, at proportionate dist., there is no remaining evidence of the orig. cor.

**Dependent Resurvey of the West Boundary,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with brass cap mkd.

T 22 N	
R 18 E	R 19 E
S 1	S 6
S 12	S 7

2007

Deposit a magnet, in a white plastic case, at the base of the  
stainless steel post.

---

N. 1°56' E., bet. secs. 1 and 6.

Over rolling land.

39.70 Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate  
dist., there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with brass cap mkd.

T 22 N	
1/4	
R 18 E	R 19 E
S 1	S 6

2007

Deposit a magnet, in a white plastic case, at the base of the  
stainless steel post.

40.50 Wash, 13 ft. wide, 4 ft. deep, drains N. 30° W.

79.40 The cor. of Tps. 22 and 23 N., Rs. 18 and 19 E., monumented with  
a stainless steel post, 2 1/2 ins. diam., firmly set, projecting  
3 ins. above ground, in an embedded mound of stone, 4 ft. base,  
to top, with brass cap mkd. T23N R18E R19E S36 S31 S1 S6 T22N  
2004, with a steel fence post nearby.

Add the marks 2007 to the brass cap.

---

Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona

---

Restoring the survey executed by  
A. P. Johnson, in 1883

---

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°38' W., bet. secs. 35 and 36.</p> <p>Over rugged and broken land.</p>
1.85	Trail road, bears East and West.
37.57	<p>Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 19 E 1/4 S 35   S 36</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
75.14	<p>The cor. of secs. 25, 26, 35 and 36, monumented with a broken basalt stone, 12 x 6 x 4 ins., reassembled size, bottom portion, set flush with the surface of the ground, at the E. edge of an embedded mound of stone, top portion mkd. 1 groove and S26 on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 19 E S 26   S 25 S 35   S 36</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the basalt stone pieces alongside the stainless steel post.</p> <p>Retain the orig. mound of stone W. of cor.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T22N R19E R20E S25 S30 S36 S31 2006.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Add the marks 2007 to the brass cap.</p> <p>S. 86°13' W., bet. secs. 25 and 36.</p> <p>Over rolling and broken land.</p>
40.68	<p>Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 19 E</p> <p>S 25</p> <p>1/4 ———</p> <p>S 36</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
81.36	<p>The cor. of secs. 25, 26, 35 and 36.</p> <hr/> <p>N. 0°57' E., bet. secs. 25 and 26.</p> <p>Over rugged and broken land.</p>
39.83	<p>The 1/4 sec. cor. of secs. 25 and 26, monumented with a basalt stone, 11 x 9 x 7 ins., loosely set, 3 ins. in the ground, at the E. edge of a mound of stone, 3 ft. base, 1 ft. high, mkd. 1/4 on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, utilize the orig. mound of stone in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 19 E</p> <p>1/4</p> <p>S 26   S 25</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS

Bury the basalt stone alongside the stainless steel post.

---

N. 0°16' E., beginning new measurement.

Over rugged and broken land.

39.91

The cor. of secs. 23, 24, 25 and 26, monumented with basalt stone, 20 x 13 x 6 ins., loosely set, 3 ins. in the ground, at the E. edge of an embedded mound of stone, 3 ft. base, flush with the surface of the ground, with no visible marks.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, utilize the orig. mound of stone in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 22 N	R 19 E
S 23	S 24
S 26	S 25

2007

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Bury the basalt stone alongside stainless steel post.

---

From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., set flush with the surface of the ground, with brass cap mkd. T22N R19E R20E S24 S19 S25 S30 2006.

Add the marks 2007 to the brass cap.

S. 85°57' W., bet. secs. 24 and 25.

Over rolling land.

27.40

From this point, the SE cor. of an octagonal wood framed hogan, 24 ft. diam., bears North, 1.06 chs. dist., with 10 ft. sides.

40.78

Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate dist., there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p style="text-align: center;">T 22 N R 19 E S 24 1/4 ——— S 25</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
81.55	<p>The cor. of secs. 23, 24, 25 and 26.</p> <hr/>
	<p>N. 0°22' W., bet. secs. 23 and 24.</p> <p>Over rolling land.</p>
24.40	<p>Trail road, bears S. 70° E. and N. 70° W.</p>
27.15	<p>Power line, bears S. 25° E. and N. 25° W.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 19 E 1/4 S 23   S 24</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.04	<p>The cor. of secs. 13, 14, 23 and 24, determined at the E. edge of an embedded mound of stone, 2 ft. base, flush with the surface of the ground, and is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, utilize the orig. mound of stone in a collar of stone, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table style="margin: auto;"> <tr><td>T 22 N</td><td>R 19 E</td></tr> <tr><td>S 14</td><td>S 13</td></tr> <tr><td>S 23</td><td>S 24</td></tr> </table>	T 22 N	R 19 E	S 14	S 13	S 23	S 24		
T 22 N	R 19 E								
S 14	S 13								
S 23	S 24								
	2007								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Set a steel fence post nearby.								
	<hr/>								
	From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T22N R19E R20E S13 S18 S24 S19 2006, with a steel fence set nearby.								
	Add the marks 2007 to the brass cap.								
	S. 85°59' W., bet. secs. 13 and 24.								
	Over rolling land.								
41.52	Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate dist., there is no remaining evidence of the orig. cor.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto;"> <tr><td>T 22 N</td><td>R 19 E</td></tr> <tr><td></td><td>S 13</td></tr> <tr><td>1/4</td><td>———</td></tr> <tr><td></td><td>S 24</td></tr> </table>	T 22 N	R 19 E		S 13	1/4	———		S 24
T 22 N	R 19 E								
	S 13								
1/4	———								
	S 24								
	2007								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Set a steel fence post nearby.								
42.75	Trail road, bears N. 55° E. and S. 55° W.								
43.95	Trail road, bears N. 20° E. and S. 20° W.								
83.05	The cor. of secs. 13, 14, 23 and 24.								
	<hr/>								
	N. 1°15' E., bet. secs. 13 and 14.								
	Over rolling land.								

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
27.45	Navajo Route 9860, a graded road, 20 ft. wide, bears S. 75° E. and N. 75° W.
28.00	Power line, bears N. 40° E. and S. 40° W.
32.35	Underground water pipeline, bears S. 75° E. and N. 75° W.
32.60	Power line, bears S. 75° E. and N. 75° W.
40.50	Sunflower Butte Wash, 80 ft. wide, 5 ft. deep, drains N. 60° E., thence ascend S. slope of a mesa.
46.42	The 1/4 sec. cor. of secs. 13 and 14, determined at the E. edge of an embedded mound of stone, 4 ft. base, 1 ft. high, and is accepted as the best available evidence of the orig. cor. position.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 19 E 1/4 S 14   S 13  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Retain the orig. mound of stone W. of cor.
	_____
	N. 0°11' W., beginning new measurement.
	Over rugged and broken S. slope of a mesa.
29.60	S. rim of mesa, bears S. 80° E. and N. 80° W., thence over rolling land atop the mesa.
38.51	The cor. of secs. 11, 12, 13 and 14, monumented with a deteriorated basalt stone, 13 x 13 x 4 ins., loosely set, 6 ins. in the ground, at the E. edge of a mound of stone, 2 ft. base, 1 ft high, with no visible marks.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 19 E S 11   S 12 S 14   S 13  2007  Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Bury the basalt stone alongside the stainless steel post.  Retain the orig. mound of stone W. of cor.  <hr/> From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, encircled with a collar of stone, with brass cap mkd. T22N R19E R20E S12 S7 S13 S18 2006.  Add the marks 2007 to the brass cap.  S. 89°14' W., bet. secs. 12 and 13.  Over rolling and broken land.
16.70	Wash, 20 ft. wide, 6 ft. deep, drains South, thence ascend the E. slope of a mesa.
18.70	Trail road, bears S. 25° E. and N. 25° W.
41.29	Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 19 E S 12 1/4 ——— S 13  2007  Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
63.30	E. rim of a mesa, bears N. 20° E. and S. 20° W.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
82.58	<p>The cor. of secs. 11, 12, 13 and 14.</p> <hr/> <p>N. 2°05' E., bet. secs. 11 and 12.</p> <p>Over rolling land, atop a mesa.</p>
20.80	<p>N. rim of a mesa, bears N. 30° E. and S. 30° W., thence descend over rugged and broken N. slope.</p>
40.125	<p>Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 19 E 1/4 S 11   S 12</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.25	<p>Point for the cor. of secs. 1, 2, 11 and 12, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 19 E S 2   S 1 S 11   S 12</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T22N R19E R20E S1 S6 S12 S7 2006.</p> <p>Add the marks 2007 to the brass cap.</p> <p>S. 89°38' W., bet. secs. 1 and 12.</p> <p>Over rolling and broken land.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.69	<p>Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 19 E</p> <p>S 1</p> <p>1/4 ———</p> <p>S 12</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
51.75	Trail road, bears North and South.
77.20	Trail road, bears N. 5° E. and S. 5° W.
81.39	The cor. of secs. 1, 2, 11 and 12.
	<hr/> <p>N. 1°51' E., bet. secs. 1 and 2.</p> <p>Over rolling land.</p>
10.65	Trail road, bears S. 65° E. and N. 65° W.
11.35	Trail road, bears East and West.
40.12	<p>Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 19 E</p> <p>1/4</p> <p>S 2   S 1</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
47.35	Trail road, bears N. 40° E. and S. 40° W.
79.88	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T23N R19E S35 S36 S2 S1 T22N 2004.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Add the marks 2007 to the brass cap.</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°44' E., bet. secs. 34 and 35.</p> <p>Over rolling land.</p>
23.40	Trail road, bears S. 85° E. and N. 85° W.
37.825	<p>Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 19 E 1/4 S 34   S 35</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
75.65	<p>The cor. of secs. 26, 27, 34 and 35, monumented with a juniper post, 36 ins. long, 3 ins. diam., firmly set, 6 ins. in the ground, in the center of a mound of stone, 3 ft. base, 1 ft. high, mkd. S26 on E. side.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, utilize the orig. mound of stone in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 19 E S 27   S 26 S 34   S 35</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the juniper post alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 89°48' W., bet. secs. 26 and 35.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling and broken land.
39.215	Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 22 N   R 19 E                      S 26                  1/4 ———                      S 35             2007         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
78.43	The cor. of secs. 26, 27, 34 and 35. <hr/>
	N. 0°08' W., bet. secs. 26 and 27.
	Over rugged and broken land, ascend the S. slope of Echo Spring Mountain.
5.35	Trail road, bears N. 20° E. and S. 20° W.
27.20	From this point, a spring, bears West, 4.60 chs. dist.
37.40	S. rim of Echo Spring Mountain, bears N. 60° E. and S. 60° W., thence over rolling land.
39.45	The 1/4 sec. cor. of secs. 26 and 27, monumented with a basalt stone, 18 x 10 x 7 ins., firmly set, projecting 9 ins. above ground, at the E. edge of a mound of stone, 2 ft. base, 1 ft high, mkd. 1/4 on E. face.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in basalt stone bedrock, utilize the orig. mound of stone in a mound of stone, 2 ft. base, to top, with brass cap mkd.  <div style="text-align: center;">           T 22 N   R 19 E                      1/4                  S 27   S 26             2007         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS							
	<p>Bury the basalt stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°08' W., beginning new measurement.</p> <p>Over rolling land.</p>						
39.91	<p>The cor. of secs. 22, 23, 26 and 27, monumented with a juniper post, 42 ins. long, 3 ins. diam., loosely set, 4 ins. in the ground, in the center of a mound of stone, 3 ft. base, 1 1/2 ft. high, with illegible scribe marks on E. side.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in sandstone bedrock, utilize the orig. mound of stone in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T 22 N</td> <td style="padding: 0 5px;">R 19 E</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 22</td> <td style="padding: 0 5px;">S 23</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 27</td> <td style="padding: 0 5px;">S 26</td> </tr> </table> </div> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the juniper post alongside the stainless steel post.</p> <p>From this cor. point, an aluminum rod, 1 in. diam., the remains of third order National Geodetic Survey triangulation station "DRIVE 1966", bears S. 24°05' E., 7.945 chs. dist., cemented flush in a basalt stone outcrop.</p> <hr style="width: 20%; margin: auto;"/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89°56' W., bet. secs. 23 and 26.</p> <p>Over rugged and broken land, ascend the E. slope of Echo Spring Mountain.</p>	T 22 N	R 19 E	S 22	S 23	S 27	S 26
T 22 N	R 19 E						
S 22	S 23						
S 27	S 26						
39.72	<p>Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in basalt stone bedrock, with top mkd.</p>						

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 19 E S 23 1/4 ——— S 26  2007
	Deposit a magnet, in a white plastic case, in the drill hole, at the base of the brass tablet.
48.40	E. rim of Echo Spring Mountain, bears N. 10° E. and S. 10° W., thence over rolling land.
79.44	The cor. of secs. 22, 23, 26 and 27.
	<hr/> N. 0°03' E., bet. secs. 22 and 23.  Over rolling land.
42.125	Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in basalt stone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T 22 N R 19 E 1/4 S 22   S 23  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
84.25	Point for the cor. of secs. 14, 15, 22 and 23, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 19 E S 15   S 14 ——— S 22   S 23  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	<hr/> From the cor. of secs. 13, 14, 23 and 24.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 80°53' W., bet. secs. 14 and 23.
	Over rolling and broken land, ascend the E. slope of Echo Spring Mountain.
13.55	Trail road, bears S. 30° E. and N. 30° W.
18.65	Trail road, bears N. 40° E. and S. 40° W.
19.00	Power line, bears N. 40° E. and S. 40° W.
39.76	The 1/4 sec. cor. of secs. 14 and 23, monumented with a basalt stone, 12 x 8 x 5 ins., loosely set, 4 ins. in the ground, at the E. edge of an embedded mound of stone, 2 ft. base, 1 ft. high, mkd. 1 on N. face.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, utilize the orig. mound of stone in a collar of stone, with brass cap mkd.
	T 22 N R 19 E S 14 1/4 ——— S 23  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Bury the basalt stone alongside the stainless steel post.
	—————
	S. 86°49' W., beginning new measurement.
	Over rugged and broken land, ascend the E. slope of Echo Spring Mountain.
16.20	E. rim of Echo Spring Mountain, bears N. 20° E. and S. 20° W., thence over rolling land.
39.65	The cor. of secs. 14, 15, 22 and 23.
	—————
	N. 0°23' W., bet. secs. 14 and 15.
	Over rolling land.
3.70	N. rim of Echo Spring Mountain, bears East and West, thence descend into rolling land.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
42.12	<p>The 1/4 sec. cor. of secs. 14 and 15, monumented with a basalt stone, 22 x 10 x 6 ins., loosely set, 4 ins. in the ground, at the E. edge of an embedded mound of stone, 3 ft. base, 1 ft. high, faintly mkd. 1/ on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 19 E 1/4 S 15   S 14</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the basalt stone alongside the stainless steel post.</p> <p>Rebuild the mound of stone, 3 ft. high, 1 ft. high, W. of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1°26' E., beginning new measurement.</p> <p>Over rolling land.</p>
9.35	Navajo Route 9860, a graded road, 20 ft. wide, bears S. 70° E. and N. 70° W.
11.90	Underground water pipeline, bears S. 65° E. and N. 65° W.
12.13	Power line, bears S. 65° E. and N. 65° W.
39.64	<p>Point for the cor. of secs. 10, 11, 14 and 15, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 19 E S 10   S 11 S 15   S 14</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of secs. 11, 12, 13 and 14.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 89°19' W., bet. secs. 11 and 14.  Over rolling land, atop a mesa.
10.00	W. rim of a mesa, bears S. 5° E. and N. 5° W., thence descend over rolling land.
39.51	Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, encircled with a collar of stone, with brass cap mkd.  <div style="text-align: center;">           T 22 N R 19 E                  S 11              1/4 ———                  S 14             2007         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
43.70	Barbed wire fence, 5 strand, bears S. 30° E. and N. 30° W.
67.79	Barbed wire fence, 5 strand, bears S. 5° E. and N. 5° W.
68.00	Trail road, bears S. 5° E. and N. 5° W.
79.02	The cor. of secs. 10, 11, 14 and 15. <hr/>
	N. 0°40' E., bet. secs. 10 and 11.  Over rolling land.
7.65	Trail road, bears N. 20° E. and S. 20° W.
24.10	Trail road, bears S. 45° E. and N. 45° W.
39.63	Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 22 N R 19 E                  1/4              S 10   S 11             2007         </div>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
79.26	Point for the cor. of secs. 2, 3, 10 and 11, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T 22 N</td><td>R 19 E</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td>S 10</td><td>S 11</td></tr> </table> <p>2007</p> </div>	T 22 N	R 19 E	S 3	S 2	S 10	S 11		
T 22 N	R 19 E								
S 3	S 2								
S 10	S 11								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	From the cor. of secs. 1, 2, 11 and 12.  West, bet. secs. 2 and 11.  Over rolling land.								
40.50	Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T 22 N</td><td>R 19 E</td></tr> <tr><td>S 2</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 11</td><td></td></tr> </table> <p>2007</p> </div>	T 22 N	R 19 E	S 2		1/4	—	S 11	
T 22 N	R 19 E								
S 2									
1/4	—								
S 11									
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
51.80	Trail road, bears N. 25° E. and S. 25° W.								
81.00	The cor. of secs. 2, 3, 10 and 11.  N. 2°20' E., bet. secs. 2 and 3.  Over rolling land.								
5.55	Trail road, bears N. 80° E. and S. 80° W.								

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.66	<p>Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 19 E 1/4 S 3   S 2</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Thence ascend the S. slope of Wide Butte.</p>
79.18	<p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R19E S34 S35 S2 S3 T22N 2004, with a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Add the marks 2007 to the brass cap.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 1°12' E., bet. secs. 33 and 34.</p> <p>Over rolling and broken land.</p>
37.96	<p>Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 19 E 1/4 S 33   S 34</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS									
75.92	<p>The cor. of secs. 27, 28, 33 and 34, monumented with a basalt stone, 16 x 7 x 6 ins., loosely set, 4 ins. in the ground, at the E. edge of an embedded mound of stone, 3 ft. base, 1 ft. high, mkd. 1 groove on S. face and 3 grooves on E. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, utilize the orig. mound of stone in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T 22 N</td><td>R 19 E</td></tr> <tr><td>S 28</td><td>S 27</td></tr> <tr><td>S 33</td><td>S 34</td></tr> </table> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the basalt stone alongside stainless steel post.</p> <p>Set a steel fence post nearby.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S. 89°55' W., bet. secs. 27 and 34.</p> <p>Over rugged and broken land, along the S. slope of Echo Spring Mountain.</p>	T 22 N	R 19 E	S 28	S 27	S 33	S 34		
T 22 N	R 19 E								
S 28	S 27								
S 33	S 34								
2.80	Trail road, bears S. 25° E. and N. 25° W.								
39.82	<p>Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in basalt stone bedrock, with top mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T 22 N</td><td>R 19 E</td></tr> <tr><td>S 27</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 34</td><td></td></tr> </table> <p>2007</p> </div> <p>Deposit a magnet, in the drill hole, at the base of the brass tablet.</p>	T 22 N	R 19 E	S 27		1/4	—	S 34	
T 22 N	R 19 E								
S 27									
1/4	—								
S 34									

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.65	<p>The cor. of secs. 27, 28, 33 and 34.</p> <hr/> <p>N. 0°34' W., bet. secs. 27 and 28.</p> <p>Over rugged and broken land, ascend the S. slope of Echo Spring Mountain.</p>
39.55	<p>The 1/4 sec. cor. of secs. 27 and 28, monumented with a basalt stone, 10 x 10 x 5 ins., loosely set, 3 ins. in the ground, mkd. 1/4 on W. face.</p> <p>from which</p> <p style="padding-left: 40px;">A multi-trunk juniper, 30 ins. diam. at base, bears S. 65 1/2° W., 29 lks. dist., with N. branch, 6 ins. diam., cut and lying loose nearby, mkd. 1/4 BT on open blaze. (Record: S. 44° W.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 19 E 1/4 S 28   S 27</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the basalt stone alongside the stainless steel post.</p> <hr/> <p>N. 0°07' E., beginning new measurement.</p> <p>Over rugged and broken land, ascend the S. slope of Echo Spring Mountain.</p>
2.40	<p>S. rim of Echo Spring Mountain, bears N. 80° E. and S. 80° W., thence over rolling land.</p>
39.24	<p>The cor. of secs. 21, 22, 27 and 28, monumented with a basalt stone, 10 x 9 x 6 ins., loosely set, 4 ins. in the ground, at the E. edge of an embedded mound of stone, 2 ft. base, 10 ins. high, mkd. 2 grooves on S. face.</p> <p>At the corner point</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in basalt stone bedrock, utilize the orig. mound of stone in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 22 N</td> <td>R 19 E</td> </tr> <tr> <td>S 21</td> <td>S 22</td> </tr> <tr> <td>S 28</td> <td>S 27</td> </tr> </table>	T 22 N	R 19 E	S 21	S 22	S 28	S 27		
T 22 N	R 19 E								
S 21	S 22								
S 28	S 27								
	2007								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Bury the basalt stone alongside the stainless steel post.								
	<hr/>								
	From the cor. of secs. 22, 23, 26 and 27.								
	S. 89°30' W., bet. secs. 22 and 27.								
	Over rolling land.								
39.89	Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate dist., there is no remaining evidence of the orig. cor.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 22 N</td> <td>R 19 E</td> </tr> <tr> <td></td> <td>S 22</td> </tr> <tr> <td></td> <td>1/4 ———</td> </tr> <tr> <td></td> <td>S 27</td> </tr> </table>	T 22 N	R 19 E		S 22		1/4 ———		S 27
T 22 N	R 19 E								
	S 22								
	1/4 ———								
	S 27								
	2007								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
79.78	The cor. of secs. 21, 22, 27 and 28.								
	<hr/>								
	N. 0°59' E., bet. secs. 21 and 22.								
	Over rolling land.								
41.33	Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate dist., there is no remaining evidence of the orig. cor.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in basalt stone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.								

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 19 E 1/4 S 21   S 22  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
56.60	N. rim of Echo Spring Mountain, bears S. 65° E. and N. 65° W., thence descend over rugged and broken N. slope.
82.66	Point for the cor. of secs. 15, 16, 21 and 22, at proportionate dist., there is no remaining evidence of the orig. cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled with a collar of stone, with brass cap mkd.
	T 22 N R 19 E S 16   S 15 S 21   S 22  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	From the cor. of secs. 14, 15, 22 and 23.
	S. 88°20' W., bet. secs. 15 and 22.
	Over rugged and broken land, descend the NW slope of Echo Spring Mountain.
33.60	Wash, 20 ft. wide, 3 ft. deep, drains N. 35° E.
34.00	Trail road, bears N. 15° E. and S. 15° W.
39.22	Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate dist., there is no remaining evidence of the orig. cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 19 E S 15 1/4 ——— S 22  2007

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
78.44	The cor. of secs. 15, 16, 21 and 22. <hr/>
	N. 0°09' W., bet. secs. 15 and 16.
	Over rugged and broken land, descend the N. slope of Echo Spring Mountain.
41.325	Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. below the surface of the ground, with brass cap mkd.
	T 22 N R 19 E 1/4 S 16   S 15  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located on the E. edge of a trail road, bears S. 10° E. and N. 10° W.
	Thence over rolling land.
68.55	Underground water pipeline, bears S. 85° E. and N. 85° W.
72.80	Navajo Route 9860, a graded road, 20 ft. wide, bears S. 80° E. and N. 80° W.
82.65	The cor. of secs. 9, 10, 15 and 16, monumented with remains of a juniper post, 26 ins. long, 3 ins. diam., firmly set, 18 ins. in the ground, with no visible marks.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 19 E S 9   S 10 S 16   S 15  2007

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the juniper post alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 89°00' W., bet. secs. 10 and 15.</p> <p>Over rolling land.</p>
2.45	Trail road, bears N. 20° E. and S. 20° W.
39.66	<p>Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 19 E</p> <p>S 10</p> <p>1/4 ———</p> <p>S 15</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.33	<p>The cor. of secs. 9, 10, 15 and 16.</p> <hr/> <p>N. 1°02' W., bet. secs. 9 and 10.</p> <p>Over rugged and broken land, ascend a rocky butte.</p>
39.86	<p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 19 E</p> <p>1/4</p> <p>S 9   S 10</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on the rocky SW slope of a rocky butte.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS									
79.72	<p>The cor. of secs. 3, 4, 9 and 10, determined at the E. edge of an embedded mound of stone, 3 ft. base, 1 ft. high, and is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 22 N</td><td>R 19 E</td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td>S 9</td><td>S 10</td></tr> </table> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Retain the orig. mound of stone W. of cor.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. 89°20' W., bet. secs. 3 and 10.</p> <p>Over rolling land.</p>	T 22 N	R 19 E	S 4	S 3	S 9	S 10		
T 22 N	R 19 E								
S 4	S 3								
S 9	S 10								
27.30	Trail road, bears S. 15° E. and N. 15° W.								
29.00	Trail road, bears S. 5° E. and N. 5° W.								
40.835	<p>Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 22 N</td><td>R 19 E</td></tr> <tr><td>S 3</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 10</td><td></td></tr> </table> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Thence ascend the E. slope of a rocky butte.</p>	T 22 N	R 19 E	S 3		1/4	—	S 10	
T 22 N	R 19 E								
S 3									
1/4	—								
S 10									

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
81.67	<p>The cor. of secs. 3, 4, 9 and 10.</p> <hr/> <p>N. 3°58' E., bet. secs. 3 and 4.</p> <p>Over rugged and broken land.</p>
40.44	<p>Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 19 E 1/4 S 4   S 3</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
45.15	Trail road, bears S. 55° E. and N. 55° W.
80.85	<p>The cor. of secs. 3, 4, 33 and 34, at the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, encircled with a collar of stone, with brass cap mkd. T23N R19E S33 S34 S4 S3 T22N 2004.</p> <p>Add the marks 2007 to the brass cap.</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°34' W., bet. secs. 32 and 33.</p> <p>Over rolling land.</p>
40.33	<p>The 1/4 sec. cor. of secs. 32 and 33, determined at record bearing and dist. from the orig. accessory post</p> <p style="text-align: center;">A juniper post, 3 ins. diam., firmly set, projecting 22 ins. above ground, encircled with a collar of stone, 2 1/2 ft. base, bears North, 5 1/2 ft. dist., faintly mkd. 1/4 on W. side.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 19 E 1/4 S 32   S 33  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Retain the orig. accessory post in place.  Set a steel fence post nearby.  <hr style="width: 20%; margin: 10px auto;"/> N. 0°21' W., beginning new measurement.  Over rolling land.
39.51	The cor. of secs. 28, 29, 32 and 33, monumented with a basalt stone, 12 x 9 x 8 ins., loosely set, 2 ins. in the ground, at the E. edge of a mound of stone, 2 1/2 ft. base, 1 ft. high, mkd. 1 groove on S. face and 4 grooves on E. face.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 19 E S 29   S 28 <hr style="width: 20%; margin: 0 auto;"/> S 32   S 33  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Bury the basalt stone alongside the stainless steel post.  Retain the orig. mound of stone W. of cor.  Set a steel fence post nearby.  <hr style="width: 80%; margin: 10px auto;"/> From the cor. of secs. 27, 28, 33 and 34.  N. 88°56' W., bet. secs. 28 and 33.  Over rolling and broken land.
39.56	The 1/4 sec. cor. of secs. 28 and 33, determined at record bearing and dist. from the orig. bearing tree

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>A juniper, 14 ins. diam., bears N. 65°00' W., 20 lks. dist., with a scribe marks 1/4 S2 BT visible on open blaze.</p> <p>The orig. cor., a juniper post, 3 ft. long, 3 ins. diam., was found lying loose nearby, mkd. 1/4 S on a blazed side.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 22 N R 19 E S 28 1/4 ——— S 33</p> <p align="center">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the juniper post alongside the stainless steel post.</p> <hr/> <p>N. 89°04' W., beginning new measurement.</p> <p>Over rolling land.</p>
27.70	W. rim of Echo Spring Mountain, bears N. 30° E. and S. 30° W., thence descend into rugged badlands.
37.96	The cor. of secs. 28, 29, 32 and 33.
	<hr/> <p>N. 2°30' W., bet. secs. 28 and 29.</p> <p>Over rolling and broken land.</p>
40.08	<p>Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 22 N R 19 E 1/4 S 29   S 28</p> <p align="center">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

## CHAINS

80.16

Point for the cor. of secs. 20, 21, 28 and 29, at proportionate dist., there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N	R 19 E
S 20	S 21
S 29	S 28

2007

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

---

From the cor. of secs. 21, 22, 27 and 28.

N. 88°07' W., bet. secs. 21 and 28.

Over rolling land.

13.30

W. rim of Echo Spring Mountain, bears N. 30° E. and S. 30° W., thence descend abruptly over rugged broken rocky slope.

40.36

Point for 1/4 sec. cor. of secs. 21 and 28, at proportionate dist., there is no remaining evidence of the orig. cor.

Chisel an X on basalt stone bedrock, 8 ins. below the surface of ground.

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 20°00' E., 85.0 ft. dist., with brass cap mkd. RM T22N R19E 1/4 S21 85.0 FT TO COR. 2007 and an arrow pointing to the cor. Deposit a magnet in white plastic case at the base of the stainless steel post.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 20°00' W., 150.0 ft. dist., with brass cap mkd. RM T22N R19E 1/4 S28 150.0 FT TO COR. 2007 and an arrow pointing to the cor. Deposit a magnet in white plastic case at the base of the stainless steel post.

The NW cor. of the concrete casing of Echo Spring Well, bears S. 24°23' E., 2.25 chs. dist., 7 ft. square, projecting 5.5 ft. above ground.

Cor. is located in a wash, 15 ft. wide, 3 ft. deep, drains S. 85° W.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.73	<p>The cor. of secs. 20, 21, 28 and 29.</p> <hr/> <p>N. 2°05' E., bet. secs. 20 and 21.</p> <p>Over rolling land.</p>
40.07	<p>Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 19 E 1/4 S 20   S 21</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.14	<p>The cor. of secs. 16, 17, 20 and 21, monumented with a basalt stone, 19 x 12 x 6 ins., firmly set, 5 ins. in the ground, at the E. edge of an embedded mound of stone, 3 ft. base, 1 ft. high, mkd. 3 grooves on S. face and 4 grooves on E. face.</p> <p>At the corner point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 19 E S 17   S 16 S 20   S 21</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the basalt stone alongside the stainless steel post.</p> <p>Retain the orig. mound of stone W. of cor.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this cor. point, a juniper post, 4 ins. diam., of unknown origin, bears N. 24°21' W., 5.93 chs. dist., loosely set in center of mound of stone, 3 ft. base, 1 ft. high, mkd. VO on a side.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 89°56' W., bet. secs. 16 and 21.</p> <p>Over rugged and broken land, ascend the N. slope of Echo Spring Mountain.</p>
39.60	<p>Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 19 E S 16 1/4 ——— S 21</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
57.90	<p>W. rim of Echo Spring Mountain, bears North and South, thence descend abruptly over rugged and broken rocky slope.</p>
79.20	<p>The cor. of secs. 16, 17, 20 and 21.</p> <hr/> <p>N. 1°22' W., bet. secs. 16 and 17.</p> <p>Over rugged and broken land, along the W. slope of Echo Spring Mountain.</p>
40.54	<p>Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 19 E 1/4 S 17   S 16</p> <p>2007</p> </div>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
76.85	Navajo Route 9860, a graded road, 20 ft. wide, bears N. 60° E. and S. 60° W.								
81.08	Point for the cor. of secs. 8, 9, 16 and 17, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 22 N</td><td>R 19 E</td></tr> <tr><td>S 8</td><td>S 9</td></tr> <tr><td>S 17</td><td>S 16</td></tr> </table> <p>2007</p> </div>	T 22 N	R 19 E	S 8	S 9	S 17	S 16		
T 22 N	R 19 E								
S 8	S 9								
S 17	S 16								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	From the cor. of secs. 9, 10, 15 and 16.  S. 88°56' W., bet. secs. 9 and 16.  Over rolling land.								
35.20	Navajo Route 9860, a graded road, 30 ft. wide, bears S. 85° E. and N. 85° W.								
39.30	Wash, 20 ft. wide, 10 ft. deep, drains S. 60° W.								
40.45	Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 22 N</td><td>R 19 E</td></tr> <tr><td>S 9</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 16</td><td></td></tr> </table> <p>2007</p> </div>	T 22 N	R 19 E	S 9		1/4	—	S 16	
T 22 N	R 19 E								
S 9									
1/4	—								
S 16									
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
72.50	Navajo Route 9860, a graded road, 30 ft. wide, bears N. 60° E. and S. 60° W.								

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.91	<p>The cor. of secs. 8, 9, 16 and 17.</p> <hr/> <p>N. 1°06' W., bet. secs. 8 and 9.</p> <p>Over rolling land.</p>
2.00	Underground water pipeline, bears N. 50° E. and S. 50° W.
17.64	Power line, bears S. 75° E. and N. 75° W.
35.80	Wash, 14 ft. wide, 2 ft. deep, drains S. 20° W.
40.53	<p>Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 19 E 1/4 S 8   S 9</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
60.60	Underground water pipeline, adjacent to a trail road, bears S. 20° E. and N. 20° W.
70.76	From this point, the NE cor. of a wood framed house, 48 x 24 ft., bears West, 49.5 lks. dist., long side bears S. 16° W.
76.75	Trail road, bears N. 75° E. and S. 75° W.
81.06	<p>Point for the cor. of secs. 4, 5, 8 and 9, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 19 E S 5   S 4 S 8   S 9</p> <p style="text-align: center;">2007</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 89°53' W., bet. secs. 4 and 9.</p> <p>Over rugged and broken land.</p>
23.25	From this point, the hand-pump of Tode Baho Tsiquini Well, bears South, 19.13 chs. dist., in the center of metal well casing, 32 ins. square, set flush with surface of the ground.
40.49	<p>Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 19 E</p> <p>S 4</p> <p>1/4 ———</p> <p>S 9</p> <p>2007</p> </div>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
73.50	Underground water pipeline, bears N. 30° E. and S. 30° W.
80.99	The cor. of secs. 4, 5, 8 and 9.
	<hr/> <p>N. 4°49' E., bet. secs. 4 and 5.</p> <p>Over rolling land.</p>
7.25	Navajo Route 60, asphalt pavement, 20 ft. wide, bears N. 35° E. and S. 35° W.
9.64	Power line, bears N. 35° E. and S. 35° W.
40.40	Trail road, bears S. 75° E. and N. 75° W.
40.67	<p>Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 19 E 1/4 S 5   S 4  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
81.58	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R19E S32 S33 S5 S4 T22N 2004.  Add the marks 2007 to the brass cap.
	<hr/> From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described.  N. 1°18' E., bet. secs. 31 and 32.  Over rolling land.
38.75	Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T 22 N R 19 E 1/4 S 31   S 32  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.
77.50	The cor. of secs. 29, 30, 31 and 32, determined at the E. edge of an embedded mound of stone, 2 ft. base, 6 ins. high, and is accepted as the best available evidence of the orig. cor. position.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table style="margin: auto;"> <tr><td>T 22 N</td><td>R 19 E</td></tr> <tr><td>S 30</td><td>S 29</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 31</td><td>S 32</td></tr> </table> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Rebuild the mound of stone, 3 ft. base, 1 ft. high, W. of cor.</p> <p>Set a steel fence post nearby.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>S. 89°41' W., bet. secs. 29 and 32.</p> <p>Over rolling land.</p>	T 22 N	R 19 E	S 30	S 29			S 31	S 32
T 22 N	R 19 E								
S 30	S 29								
S 31	S 32								
39.94	<p>Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 22 N</td><td>R 19 E</td></tr> <tr><td></td><td>S 29</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S 32</td></tr> </table> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> </p>	T 22 N	R 19 E		S 29	1/4	—		S 32
T 22 N	R 19 E								
	S 29								
1/4	—								
	S 32								
79.88	<p>The cor. of secs. 29, 30, 31 and 32.</p> <hr/> <p>N. 86°40' W., bet. secs. 30 and 31.</p> <p>Over rolling land.</p>								
42.55	<p>Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 19 E S 30 1/4 ——— S 31  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
82.55	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.  <hr/> From the cor. of secs. 29, 30, 31 and 32.  N. 0°19' E., bet. secs. 29 and 30.  Over rugged and broken land, ascend the S. slope of French Butte.
39.21	The 1/4 sec. cor. of secs. 29 and 30, monumented with a basalt stone, 19 x 12 x 3 ins., loosely set, 4 ins. in the ground, at the E. edge of a mound of stone, 2 ft. base, 1 ft. high, mkd. 1/4 on W. face.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, utilize the orig. mound of stone in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T 22 N R 19 E 1/4 S 30   S 29  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Bury the basalt stone alongside the stainless steel post.  <hr/> N. 6°10' W., beginning new measurement.  Over rugged and broken land, along the E. slope of French Butte.
1.40	Spur ridge, bears East and West, thence descend over NE slope of French Butte.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS									
38.40	Power line, bears S. 70° E. and N. 70° W., at base of descent, thence over rolling land.								
41.47	Point for the cor. of secs. 19, 20, 29 and 30, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 22 N</td><td>R 19 E</td></tr> <tr><td>S 19</td><td>S 20</td></tr> <tr><td>S 30</td><td>S 29</td></tr> </table> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89°56' W., bet. secs. 20 and 29.</p> <p>Over nearly level land.</p>	T 22 N	R 19 E	S 19	S 20	S 30	S 29		
T 22 N	R 19 E								
S 19	S 20								
S 30	S 29								
40.29	Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 22 N</td><td>R 19 E</td></tr> <tr><td>S 20</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 29</td><td></td></tr> </table> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 22 N	R 19 E	S 20		1/4	—	S 29	
T 22 N	R 19 E								
S 20									
1/4	—								
S 29									
80.59	The cor. of secs. 19, 20, 29 and 30.  <hr/> <p>N. 86°32' W., bet. secs. 19 and 30.</p> <p>Over rolling land.</p>								
33.00	Power line, bears N. 50° E. and S. 50° W.								
35.95	Underground water pipeline, bears N. 30° E. and S. 30° W.								

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.48	<p>Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 19 E S 19 1/4 ——— S 30</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
50.74	<p>From this point, a brass tablet, 3 ins. diam., set in a concrete post, 3 ins. diam., bears North, 34 lks. dist., firmly set, projecting 2 ins. above ground, with top mkd. B.I.A ROADS 19, with an angle iron, firmly set, projecting 24 ins. above ground, nearby, mkd. HWRW 987+00.00 on the side.</p>
52.24	<p>Navajo Route 60, asphalt pavement, 25 ft. wide, bears N. 50° E. and S. 50° W.</p>
78.89	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 1°32' E., bet. secs. 19 and 20.</p> <p>Over nearly level land.</p>
41.24	<p>Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 19 E 1/4 S 19   S 20</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
46.88	<p>Navajo Route 60, asphalt pavement, 25 ft. wide, bears N. 50° E. and S. 50° W.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS									
81.75	Underground water pipeline, bears N. 60° E. and S. 60° W.								
82.48	<p>Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 22 N</td> <td>R 19 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 18</td> <td>S 17</td> </tr> <tr> <td style="border-right: 1px solid black;">S 19</td> <td>S 20</td> </tr> </table> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 82°52' W., bet. secs. 17 and 20.</p> <p>Over rolling and broken land.</p>	T 22 N	R 19 E	S 18	S 17	S 19	S 20		
T 22 N	R 19 E								
S 18	S 17								
S 19	S 20								
42.90	<p>The 1/4 sec. cor. of secs. 17 and 20, determined at record bearing and dist. from the orig. accessory post. The orig. accessory post, was recovered, found mkd. 1/4 and tied to by Theodore F McNabb, Arizona R.L.S. No. 1651, as shown on his plat of the survey of the Castle Butte Trading Post, dated July 2, 1955.</p> <p style="padding-left: 40px;">A weathered juniper post, 3 ins. diam., firmly set, projecting 7 ins. above ground, bears East, 5 1/2 ft. dist., with no marks.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 22 N</td> <td>R 19 E</td> </tr> <tr> <td></td> <td>S 17</td> </tr> <tr> <td></td> <td>1/4 ———</td> </tr> <tr> <td></td> <td>S 20</td> </tr> </table> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Retain the orig. accessory post in place.</p>	T 22 N	R 19 E		S 17		1/4 ———		S 20
T 22 N	R 19 E								
	S 17								
	1/4 ———								
	S 20								

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this cor. point, a rebar, 5/8 ins. diam., Cor. C, the northerly cor., of Castle Butte Trading Post property, bears N. 26°28' W., 25.20 chs. dist., firmly set, projecting 2 ins. above ground, with no cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 85°30' W., beginning new measurement.</p> <p>Over rolling land.</p>
8.26	Navajo Route 60, asphalt pavement, 25 ft. wide, bears N. 15° E. and S. 15° W.
37.50	Underground water pipeline, bears N. 60° E. and S. 60° W.
38.83	The cor. of secs. 17, 18, 19 and 20.
	<hr style="width: 60%; margin: 10px auto;"/> <p>S. 87°47' W., bet. secs. 18 and 19.</p> <p>Over rolling land.</p>
3.30	Graded road, 15 ft. wide, bears N. 55° E. and S. 55° W.
7.55	Power line, bears N. 60° E. and S. 60° W.
38.67	<p>The 1/4 sec. cor. of secs. 18 and 19, determined at record bearing and dist. from the remains of orig. accessory post</p> <p style="padding-left: 40px;">The decayed remains of a juniper post, 4 ins. diam., set flush with the surface of the ground and 10 ins. deep, bears West, 5 1/2 ft. dist., in the center of embedded mound of stone, 3 ft. base, flush with surface of ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T 22 N R 19 E</p> <p>S 18</p> <p>1/4 ———</p> <p>S 19</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Bury the remains of the juniper post in the center of the orig. mound of stone.
	_____
	N. 84°15' W., beginning new measurement.
	Over rolling land.
42.60	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described.
	_____
	From the cor. of secs. 17, 18, 19 and 20.
	N. 0°58' W., bet. secs. 17 and 18.
	Over rolling and broken land.
2.20	Graded road, 15 ft. wide, bears N. 55° E. and S. 55° W.
4.68	Power line, bears N. 60° E. and S. 60° W.
41.23	Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate dist., there is no remaining evidence of the orig. cor,
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled with a collar of stone, with brass cap mkd.
	T 22 N R 19 E 1/4 S 18   S 17  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Thence ascend the rugged and broken S. slope of Chezhin Chotah Butte.
78.50	S. rim of Chezhin Chotah Butte, bears N. 60° E. and S. 60° W., thence over rolling land.
82.46	The cor. of secs. 7, 8, 17 and 18, determined at the E. edge of an embedded mound of stone, 3 ft. base, 6 ins. high, and is accepted as the best available evidence of the orig. cor. position.
	At the corner point

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p>								
	<table border="1"> <tr> <td>T 22 N</td> <td>R 19 E</td> </tr> <tr> <td>S 7</td> <td>S 8</td> </tr> <tr> <td>S 18</td> <td>S 17</td> </tr> </table>	T 22 N	R 19 E	S 7	S 8	S 18	S 17		
T 22 N	R 19 E								
S 7	S 8								
S 18	S 17								
	2007								
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>								
	<p>Retain the orig. mound of stone W. of cor.</p> <hr/>								
	<p>From the cor. of secs. 8, 9, 16 and 17.</p>								
	<p>N. 87°23' W., bet. secs. 8 and 17.</p>								
	<p>Over rolling land.</p>								
14.30	<p>Wash, 15 ft. wide, 3 ft. deep, drains S. 30° W.</p>								
29.43	<p>Power line, bears N. 15° E. and S. 15° W.</p>								
30.65	<p>Navajo Route 60, asphalt pavement, 25 ft. wide, bears N. 15° E. and S. 15° W., thence over rugged and broken land, ascend the E. slope of Chazhin Chotah Butte.</p>								
40.41	<p>Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate dist., there is no remaining evidence of the orig. cor.</p>								
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p>								
	<table border="1"> <tr> <td>T 22 N</td> <td>R 19 E</td> </tr> <tr> <td>S 8</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 17</td> <td></td> </tr> </table>	T 22 N	R 19 E	S 8		1/4	—	S 17	
T 22 N	R 19 E								
S 8									
1/4	—								
S 17									
	2007								
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>								
76.60	<p>E. rim of Chazhin Chotah Butte, bears N. 10° E. and S. 10° W.</p>								

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.81	<p>The cor. of secs. 7, 8, 17 and 18.</p> <hr/> <p>N. 89°59' W., bet. secs. 7 and 18.</p> <p>Over rolling land, atop Chazhin Chotah Butte.</p>
8.40	<p>W. rim of Chazhin Chotah Butte, bears S. 60° E. and N. 60° W., thence descend over rugged and broken W. slope.</p>
39.65	<p>The 1/4 sec. cor. of secs. 7 and 18, determined at the E. edge of an embedded mound of stone, 3 ft. base, 1 ft. high, and is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 19 E</p> <p>S 7</p> <p>1/4 ———</p> <p>S 18</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Retain the orig. mound of stone W. of cor.</p> <hr/> <p>S. 89°29' W., beginning new measurement.</p> <p>Over rolling land.</p>
37.30	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 1°13' W., bet. secs. 7 and 8.</p> <p>Over rolling land.</p>
4.80	<p>Top of basalt stone ridge, bears N. 75° E. and S. 75° W., thence descend over rugged and broken rocky N. slope of Chazhin Chotah Butte.</p>
36.45	<p>Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate dist., there is no remaining evidence of the orig. cor.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 19 E 1/4 S 7   S 8</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located at the base of a descent, thence over rolling land.</p>
72.90	<p>The cor. of secs. 5, 6, 7 and 8, monumented with a basalt stone, 12 x 10 x 6 ins., firmly set, 6 ins. in the ground, mkd. 5 grooves on S. face and 5 grooves on E. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 19 E S 6   S 5 S 7   S 8</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the basalt stone alongside the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>S. 86°49' W., bet. secs. 5 and 8.</p> <p>Over rolling land.</p>
4.80	<p>Navajo Route 60, asphalt pavement, 25 ft. wide, bears N. 35° E. and S. 35° W.</p>
6.40	<p>Power line, bears N. 35° E. and S. 35° W.</p>
40.41	<p>Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate dist., there is no remaining evidence of the orig. cor.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 19 E S 5 1/4 ——— S 8</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 60 lks. S. of a trail road, bears East and West.</p>
80.82	<p>The cor. of secs. 5, 6, 7 and 8.</p> <hr/> <p>N. 85°10' W., bet. secs. 6 and 7.</p> <p>Over rolling land.</p>
34.20	<p>Power line, bears East and West.</p>
37.16	<p>Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 19 E S 6 1/4 ——— S 7</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 28 lks. N. of power line, bears East and West.</p>
72.97	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 5°18' E., bet. secs. 5 and 6.</p> <p>Over rolling land.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
3.21	Power line, bears East and West.
42.79	<p>Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 19 E 1/4 S 6   S 5</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
86.08	<p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T23N R19E S31 S32 S6 S5 T22N 2004.</p> <p>Add the marks 2007 to the brass cap.</p> <hr/> <p style="text-align: center;">Subdivision of Section 6, T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 6 and 7.</p> <p>N. 3°35' E., on the N. and S. center line of sec. 6.</p> <p>Over rolling land.</p>
41.20	<p>Point for the center 1/4 sec. cor. of sec. 6, at intersection with the E. and W. center line of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 19 E C 1/4 S 6</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>

**Subdivision of Section 6,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
82.71	<p>The 1/4 sec. cor. of secs. 6 and 31, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T23N R19E 1/4 S31 S6 T22N 2004, with a mound of stone, 3 ft. base, 1 1/2 ft. high, N. of cor., with a steel fence post nearby.</p> <p>Add the marks 2007 to the brass cap.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 5 and 6.</p> <p>N. 87°33' W., on the E. and W. center line of sec. 6.</p> <p>Over rolling land.</p>
38.43	The center 1/4 sec. cor. of sec. 6.
75.38	The 1/4 sec. cor. of secs. 1 and 6, on the W. bdy. of the Tp.
<hr/> <p>Subdivision of Section 24, T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 24 and 25.</p> <p>N. 0°12' E., on the N. and S. center line of sec. 24.</p> <p>Over rolling land.</p>
5.85	Power line, bears S. 65° E. and N. 65° W.
6.35	Trail road, bears S. 65° E. and N. 65° W.
39.10	Wash, 20 ft. wide, 5 ft. deep, drains N. 60° E.
40.04	<p>Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E. and W. center line of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 19 E C 1/4 S 24</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>

**Subdivision of Section 24,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.08	<p>The 1/4 sec. cor. of secs. 13 and 24.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T22N R19E R20E 1/4 S24 S19 2006.</p> <p>Add the marks 2007 to the brass cap.</p> <p>S. 85°58' W., on the E. and W. center line of sec. 24.</p> <p>Over rolling land.</p>
39.30	Wash, 20 ft. wide, 5 ft. deep, drains N. 60° E.
41.15	The center 1/4 sec. cor. of sec. 24.
60.55	Trail road, bears S. 15° E. and N. 15° W.
82.30	The 1/4 sec. cor. of secs. 23 and 24.
	<hr/> <p>Subdivision of Section 32, T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona</p> <hr/>
39.535	<p>From the 1/4 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp.</p> <p>N. 0°24' E., on the N. and S. center line of sec. 32.</p> <p>Over rolling land.</p> <p>Point for the center 1/4 sec. cor. of sec. 32, at intersection with the E. and W. center line of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 19 E C 1/4 S 32</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located on the SW edge of a trail road, bears S. 45° E. and N. 45° W.</p>

**Subdivision of Section 32,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
78.665	<p>The 1/4 sec. cor. of secs. 29 and 32.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 32 and 33. N. 89°45' W., on the E. and W. center line of sec. 32. Over rolling land.</p>
40.465	The center 1/4 sec. cor. of sec. 32.
81.015	<p>The 1/4 sec. cor. of secs. 31 and 32.</p> <hr/> <p style="text-align: center;">Subdivision of Section 34, T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp. N. 0°58' E., on the N. and S. center line of sec. 34. Over rolling land.</p>
11.60	Trail road, bears East and West.
20.90	Trail road, bears S. 50° E. and N. 50° W.
35.10	Trail road, bears N. 50° E. and S. 50° W.
37.89	<p>Point for the center 1/4 sec. cor. of sec. 34, at intersection with the E. and W. center line of sec. 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 19 E C 1/4 S 34</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
75.785	<p>The 1/4 sec. cor. of secs. 27 and 34.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 34 and 35. S. 89°49' W., on the E. and W. center line of sec. 34.</p>

**Subdivision of Section 34,  
T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
24.50	Trail road, bears N. 15° E. and S. 15° W.
36.15	Trail road, bears N. 60° E. and S. 60° W.
39.99	The center 1/4 sec. cor. of sec. 34.
63.30	Trail road, bears N. 10° E. and S. 10° W.
79.975	The 1/4 sec. cor. of secs. 33 and 34.
	<hr/>

## T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS

## GENERAL DESCRIPTION

The area surveyed is located approximately three miles south of Dilkon, Arizona, within the Navajo Indian Reservation. The terrain is mostly basalt stone mesas. Echo Spring Mountain is located in the center of the township. The drainage is to the east, south and west, with sand washes.

The elevation varies from 5600 to 5700 feet above sea level. The soil is mostly sandy and sandy clay with areas of basalt stone outcrops, ledges and cliffs. The timber is juniper, scattered throughout the township. Undergrowth consists of cacti, greasewood, and native grasses.

Principal access to the area is by Navajo Route 60, while Navajo Routes 9860 and 9857 serve as main access routes for permanent residents of the township. There are several livestock grazing areas. There is no mining activity in the township.

The mean magnetic declination of 11° E. was derived from the computer program GEOMAGIX, utilizing the World Magnetic Model for Epoch 2005 for the dates of survey.



## CERTIFICATE OF SURVEY

I, Leonard R. Sandoval, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 24th day of September, 2007, I have dependently resurveyed the south and west boundaries, the subdivisional lines, and subdivided sections 6, 24, 32 and 34, T. 22 N., R. 19 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

August 27, 2008  
(Date)

Leonard R. Sandoval  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the south and west boundaries, the subdivisional lines, and the subdivision of sections 6, 24, 32 and 34, T. 22 N., R. 19 E., Gila and Salt River Meridian, in the State of Arizona, executed by Leonard R. Sandoval, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

Sept 2, 2008  
(Date)

Stephen K. Hansen  
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 22 N., R. 19 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~\_\_\_\_\_~~  
~~(Date)~~

~~\_\_\_\_\_~~  
~~(Chief Cadastral Surveyor of Arizona)~~