

ORIGINAL

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF A PORTION
OF THE NORTH BOUNDARY
OF THE
SALT RIVER PIMA-MARICOPA INDIAN COMMUNITY
TOWNSHIP 3 NORTH, RANGE 5 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

Gordon R. Bubel, Cadastral Surveyor

Under Special Instructions dated June 12, 2008, approved June 12, 2008, which provided for the surveys included under Group No. 1050, and assignment instructions dated June 12, 2008.

Survey commenced July 10, 2008

Survey completed July 31, 2008

INDEX DIAGRAM

TOWNSHIP 3 NORTH RANGE 5 EAST
 GILA AND SALT RIVER MERIDIAN, ARIZONA

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
20	17	14	11	6	4
31	32	33	34	35	36

T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the north boundary of the Salt River Pima-Maricopa Indian Community in Township 3 North, Range 5 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

In 1888, L.D. Chillson surveyed the north boundary of the Salt River Indian Reservation. In 1911, Robert A. Farmer, resurveyed the north boundary of the Salt River Indian Reservation, disregarding Chillson's survey and destroying all evidence of it. In 1950, Ty White and Claude F. Warner resurveyed portions of the north boundary of the Salt River Indian Reservation.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated June 12, 2008, for Group Number 1050, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) CNTR FOR ARTS CORS ARP, ASHLER HILLS CORS ARP AND SCOTTSDALE CORS ARP. The NAD 83 (CORS96) (EPOCH: 2002), geographic position of the 1/4 section corner of sections 25 and 36, is as follows:

Latitude: 33°34'04.45" N. Longitude: 111°47'45.70" W.

The mean magnetic declination is 11 1/4° E.

**Dependent Resurvey of a Portion of the North Boundary
of the Salt River Pima-Maricopa Indian Community,
T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p style="text-align: center;">Restoring the survey executed by Robert A. Farmer, in 1911 and the resurvey executed by Ty White and Claude F. Warner in 1950</p> <hr style="width: 20%; margin: auto;"/> <p>Beginning at the 1/4 sec. cor. of secs. 25 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with a mound of stone, 2 ft. base, 1 ft. high to the N., with brass cap mkd. S25 1/4 S36 SRIR 1911.</p> <p>Add the marks T3N R5E 2008 to the brass cap.</p> <p>Cor. is located 46 lks. N. of a barbed wire fence, extends E. and W.</p> <p>N. 89°58' W., bet. secs. 25 and 36.</p> <p>On the north boundary of the Salt River Pima-Maricopa Indian Community (hereinafter SRPMIC), over nearly level land, through mesquite, ironwood and palo verde timber.</p> <p>13.42 Point for a witness point, occupied with a rebar, 16 ins. long, 5/8 in. diam., firmly set, flush with the ground, origin unknown.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>WP T 3 N R 5 E S 25 ----- S 36 SRPMIC 2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p>Deposit the rebar inside the aluminum post.</p> <p>Cor. is located 45 lks. N. of a barbed wire fence, extends E. and W.</p> <p>This cor. represents a monument identified by Greiner Inc., and depicted on unrecorded result of survey, entitled "RESULT OF SURVEY SADDLEBACK MOUNTAIN PT SEC 25 T3N R5E & PT SEC 30 T3N R6E." The survey was executed to satisfy Public Law 104-102, which conveyed lands acquired by the Resolution Trust Corporation, to the City of Scottsdale and SRPMIC.</p>

**Dependent Resurvey of a Portion of the North Boundary
of the Salt River Pima-Maricopa Indian Community,
T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS											
20.00	<p>The W. 1/16 sec. cor. of secs. 25 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 17 ins. above ground, encircled with a collar of stone, with brass cap mkd. NO 2 S25 1/16 SRIR S36 1911.</p> <p>Add the marks T3N R5E 2008.</p> <p>Cor. is located 44 lks. N. of a barbed wire fence, extends E. and W.</p> <hr/> <p>N. 89°58' W., beginning new measurement.</p>										
2.68	<p>A brass disk, 4 ins. diam., set in concrete, flush with ground, with top mkd. ROW 306+97.61 175 FT LT R-12, thence across Central Arizona Project, irrigation canal, bears S. 40° E. and N. 40° W.</p>										
8.72	<p>A rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, no identifying marks.</p>										
20.03	<p>The cor. of secs. 25, 26, 35 and 36, perpetuated by Scott A. Nelson, Arizona R.L.S. No. 21782, in 2005, as recorded in the Maricopa County Recorder's Office in book 752, page 33, monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, flush with the ground, with attached 2 ins. diam., aluminum cap, mkd. MARICOPA COUNTY T3N R5E S26 S25 S35 S36 2005 RLS 21782. This is accepted as a careful and faithful perpetuation of the position of the orig. cor.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with aluminum cap mkd.</p> <table border="1" data-bbox="812 1354 1023 1533" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 3 N</td> <td>R 5 E</td> </tr> <tr> <td>S 26</td> <td>S 25</td> </tr> <tr> <td>S 35</td> <td>S 36</td> </tr> <tr> <td colspan="2" style="text-align: center;">SRPMIC</td> </tr> <tr> <td colspan="2" style="text-align: center;">2008</td> </tr> </table> <p>from which</p> <p>An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground for a reference monument, bears S. 45°00' E., 50.0 ft. dist. with aluminum cap mkd. RM T3N R5E 50.0 FT. TO COR. S 36 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p>	T 3 N	R 5 E	S 26	S 25	S 35	S 36	SRPMIC		2008	
T 3 N	R 5 E										
S 26	S 25										
S 35	S 36										
SRPMIC											
2008											

**Dependent Resurvey of a Portion of the North Boundary
of the Salt River Pima-Maricopa Indian Community,
T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°00' W., 41.0 ft. dist. with aluminum cap mkd. RM T3N R5E 41.0 FT. TO COR. S 35 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p>Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p>Deposit the rebar inside the aluminum post.</p> <p>Cor. is located on the easterly edge of N. 128th St., City of Scottsdale (paved, bears N. and S.), and 42 lks. N. of a barbed wire fence, extends E. and W.</p> <hr/> <p>N. 89°56' W., bet. secs. 26 and 35.</p> <p>On the north boundary of the SRPMIC, over nearly level land, through mesquite, ironwood and palo verde timber.</p>
16.15	A rebar, 1/2 in. diam., firmly set, projecting 3 ins. above ground, no identifying marks.
19.96	Point accepted for the E. 1/16 sec. cor. of secs. 26 and 35, occupied with a rebar, 18 ins. long, 1/2 in. diam., firmly set, projecting 5 ins. above ground. This is accepted as the best available evidence of the position of the orig. cor.
	<p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, in a mound of stone, 4 1/2 ft. base, to top, with aluminum cap mkd.</p> <p style="text-align: center;">T 3 N R 5 E S 26 E 1/16 — S 35 SRPMIC 2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p>Deposit the rebar inside the aluminum post.</p> <p>Cor. is located 48 lks. N. of a barbed wire fence, extends E. and W.</p> <hr/> <p>N. 89°50' W., beginning new measurement.</p>

**Dependent Resurvey of a Portion of the North Boundary
of the Salt River Pima-Maricopa Indian Community,
T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
3.82	A rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, no identifying marks.
3.83	Intersect a block and iron fence, bears N. and bears S., for 10 lks. to fence cor., extending W.
7.58	Intersect same fence, bears N. and bears S., for 1 lk. to fence cor., extending E.
11.40	A rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, no identifying marks, located 1 lk. W. of a fence cor., with block fences bearing N. and E.
12.82	Intersect the easterly side of a 8 ins. wide, 16 ins. high concrete structure, the NE cor. bears N. 2°25' E., 20.5 lks. dist., the SE cor. bears S. 2°25' W., 10.5 lks. dist., the long side bears N. 87°35' W.
13.28	Intersect the westerly side of same concrete structure, the NW cor. bears N. 2°25' E., 22 lks. dist., the SW cor. bears S. 2°25' W., 9 lks. dist., the long side bears S. 87°35' E.
15.62	Center of three, 1/2 in. diam. rebars, set in a triangle cluster, all projecting 1 in. above ground, no identifying marks.
16.37	Intersect the SE cor. of an iron fence, bears N. and N. 89°22' W.
17.83	From this point, the SW cor. of same fence, bears N., 1.5 lks. dist., fence bears N. and S. 89°22' E.
19.73	From this point, the SE cor. of an iron fence bears S., 4.5 lks. dist., fence bears N. and N. 84°43' W.
20.04	The calculated 1/4 sec. cor. of secs. 26 and 35, perpetuated by Scott A. Nelson, Arizona R.L.S. No. 21782, in 2005, as recorded in the Maricopa County Recorder's Office in book 752, page 33. Determined at record distances from reference monuments established by Nelson. This is accepted as a careful and faithful perpetuation of the position of the orig. cor. from which reference monuments established by R.L.S. Nelson A rebar, 1/2 in. diam., firmly set, flush with the ground, bears S. 34°07' E., 39.39 ft. dist. with attached 2 ins. diam., aluminum cap mkd. MARICOPA COUNTY T3N R5E 1/4 S26 RM2 2005 LS 21782, and an arrow pointing to the cor. A rebar, 1/2 in. diam., firmly set, flush with the ground, bears S. 52°46' W., 50.36 ft. dist. with attached 2 ins. diam., aluminum cap mkd. MARICOPA COUNTY T3N R5E 1/4 S26 RM1 2005 LS 21782, and an arrow pointing to the cor.

**Dependent Resurvey of a Portion of the North Boundary
of the Salt River Pima-Maricopa Indian Community,
T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>At the corner point</p> <p>Set a rebar, 18 ins. long, 1/2 in. diam., 18 ins. in the ground.</p> <p>from which</p> <p style="padding-left: 40px;">An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 21 ins. in the ground for a reference monument, bears S. 45°00' E., 66.0 ft. dist. with aluminum cap mkd. RM T3N R5E 66.0 FT. TO COR. S 35 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p style="padding-left: 40px;">An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground for a reference monument, bears S. 45°00' W., 66.0 ft. dist. with aluminum cap mkd. RM T3N R5E 66.0 FT. TO COR. S 35 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p>Cor. is located 1.5 lks. N. of an iron fence, bears S. 84°43' E. and N. 84°43' W., and 43 lks. N. of a barbed wire fence, extends E. and W.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 89°56' W., beginning new measurement.</p>
0.91	From this point, the SW cor. of an iron fence bears N., 7 lks. dist., fence bears N. and S. 84°43' E.
3.36	From this point, the SE cor. of an iron and block fence bears N., 1 lk. dist., fence bears N. and N. 40° E.
4.45	From this point, the SW cor. of same fence, bears N., 2 lks. dist., fence bears N. and E.
6.05	A rebar, 1/2 in. diam., firmly set, projecting 20 ins. above ground, no identifying marks.
7.48	A rebar, 1/2 in. diam., firmly set, projecting 3 ins. above ground, no identifying marks.
9.98	From this point, a rebar, 1/2 in. diam., firmly set, projecting 3 ins. above ground, bears S., 1 lk. dist., no identifying marks.
10.00	An open end, iron pipe, 1 in. diam., firmly set, projecting 12 ins. above ground, no identifying marks.
11.48	From this point, the cor. of fences extending N. and S. 55° W., bears N., 5 lks. dist.

**Dependent Resurvey of a Portion of the North Boundary
of the Salt River Pima-Maricopa Indian Community,
T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
11.55	Cor. of fences, extending N. 55° E. and W.
12.48	From this point, a rebar, 1/2 in. diam., firmly set, projecting 3 ins. above ground, bears S., 1 lk. dist., no identifying marks, located at intersection of fences, with block fence extending N., iron fence extending E. and woven wire fence extending W.
14.96	Point selected for a witness point on the N. bdy. of the SRPMIC. Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 27 ins. in the ground, with aluminum cap mkd. <div style="text-align: center;"> W P T 3 N R 5 E S 26 <hr style="width: 20%; margin: 0 auto;"/> S 35 SRPMIC 2008 </div>
14.97	Intersect an iron and block fence, bears N. and bears S., for 45 lks., to intersection with barbed wire fence bearing E. and barbed wire/electric fence bearing W.; thence across developed back yard of residence.
17.43	Intersect a block fence, bears N. and bears S., for 45 lks., to intersection with barbed wire/electric fence bearing E. and barbed wire bearing W; thence exit developed back yard of residence.
17.48	A rebar, 1/2 in. diam., firmly set, projecting 3 ins. above ground, with affixed 1 in. diam., plastic cap, stamped RLS 28719.
18.90	Most easterly of a series of high voltage transmission lines, bears S. 30° E. and N. 30° W.
20.00	The W. 1/16 sec. cor. of secs. 26 and 35, reestablished by Jeffery Ronnie Cook, Arizona R.L.S. No. 28719, monumented with a rebar, 18 ins. long, 1/2 in. diam., set 20 ins. in the ground, with affixed 1 in. diam., plastic cap, stamped RLS 28719. This is accepted as careful and faithful reestablishment of the orig. cor. position. At the corner point Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with aluminum cap mkd.

**Dependent Resurvey of a Portion of the North Boundary
of the Salt River Pima-Maricopa Indian Community,
T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p style="text-align: center;">T 3 N R 5 E S 26 W 1/16 ——— S 35 SRPMIC 2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p>Deposit the rebar inside the aluminum post.</p> <p>Cor. is located 45 lks. N. of a barbed wire fence, extends E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°56' W., beginning new measurement.</p> <p>3.60 Most westerly of a series of high voltage transmission lines, bears S. 30° E. and N. 30° W.</p> <p>5.24 From this point, a cor. of fences bears N., 21 lks. dist., with iron fence extending S. 30° E., iron and block fence extending W. and block fence extending N. 30° W.</p> <p>9.98 From this point, an open end iron pipe, 1 in. diam., firmly set, bent over 12 ins. to the east, bears S., 5 lks. dist., no identifying marks.</p> <p>19.99 Point accepted for the cor. of secs. 26, 27, 34 and 35, occupied with a smooth iron rod, 3/4 diam., set 20 ins. below the surface of ground. This is accepted as the best available evidence of the orig. cor. position. A rebar, 12 ins. long, 1/2 in. diam., firmly set, flush with the ground, with attached 2 ins. diam., aluminum cap, mkd. MARICOPA COUNTY T3N R5E S27 S26 S34 S35 2005 RLS 21782, is set over the iron rod.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over the iron rod, with aluminum cap mkd.</p> <p style="text-align: center;">T 3 N R 5 E S 27 S 26 S 34 S 35 SRPMIC 2008</p> <p>from which</p>
--------	--

**Dependent Resurvey of a Portion of the North Boundary
of the Salt River Pima-Maricopa Indian Community,
T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°00' E., 50.0 ft. dist. with aluminum cap mkd. RM T3N R5E 50.0 FT. TO COR. S 35 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p>An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground for a reference monument, bears S. 45°00' W., 50.0 ft. dist. with aluminum cap mkd. RM T3N R5E 50.0 FT. TO COR. S 34 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p>Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p>Bury the rebar alongside the aluminum post.</p> <p>Cor. is located 42 lks. N. of a barbed wire fence, extends E. and W., and 24 lks. S. of an iron and block fence, extending E. and W.</p> <hr/> <p>N. 89°25' W., bet. secs. 27 and 34.</p> <p>On the north boundary of SRPMIC, within an equestrian and walking trail.</p>
9.975	<p>Point for the E-E 1/64 sec. cor. of secs. 27 and 34, at proportionate dist., there is no remaining evidence of the 1950 wooden post.</p> <p>Not monumented.</p>
19.95	<p>The E. 1/16 sec. cor. of secs. 27 and 34, monumented with an iron post, 1 in. diam., set flush with the surface of ground, with brass cap mkd. NO. 1 1/16 S27 S34 SRIR 1911.</p> <p>from which</p> <p>An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground for a reference monument, bears S. 45°00' E., 66.0 ft. dist. with aluminum cap mkd. RM T3N R5E 66.0 FT. TO COR. S 34 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p>

**Dependent Resurvey of a Portion of the North Boundary
of the Salt River Pima-Maricopa Indian Community,
T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, for a reference monument, bears S. 35°00' W., 75.0 ft. dist. with aluminum cap mkd. RM T3N R5E 75.0 FT. TO COR. S 34 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p>Add the marks T3N R5E 2008 to the brass cap.</p> <p>Cor. is located 41 lks. N. of a barbed wire fence, extends E. and W., and 24 lks. S. of an iron and block fence, extending E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°55' W., beginning new measurement.</p>
10.035	<p>Point for the W-E 1/64 sec. cor. of secs. 27 and 34, at proportionate dist., there is no remaining evidence of the 1950 wooden post.</p> <p>Not monumented.</p>
20.07	<p>The 1/4 sec. cor. of secs. 27 and 34, perpetuated by Scott A. Nelson, Arizona R.L.S. No. 21782, in 2005, as recorded in the Maricopa County Recorder's Office in book 752, page 33, monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, projecting 1 in. above ground, with attached 2 ins. diam., aluminum cap, mkd. MARICOPA COUNTY T3N R5E 1/4 S27 S34 2005 RLS 21782. This is accepted as a careful and faithful perpetuation of the position of the orig. cor.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 3 N R 5 E</p> <p>S 27</p> <p>1/4 ———</p> <p>S 34</p> <p>SRPMIC</p> <p>2008</p> </div> <p>from which</p> <p>An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 21 ins. in the ground for a reference monument, bears S. 45°00' E., 66.0 ft. dist. with aluminum cap mkd. RM T3N R5E 66.0 FT. TO COR. S 34 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p>

**Dependent Resurvey of a Portion of the North Boundary
of the Salt River Pima-Maricopa Indian Community,
T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground for a reference monument, bears S. 45°00' W., 66.0 ft. dist. with aluminum cap mkd. RM T3N R5E 66.0 FT. TO COR. S 34 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Remove the rebar from the area.</p> <p>Cor. is located 42 lks. N. of a barbed wire fence, extends E. and W., and 24 lks. S. of an iron and block fence, extending E. and W.</p> <hr/> <p>N. 89°56' W., beginning new measurement.</p> <p>20.01 Point accepted for the W. 1/16 sec. cor. of secs. 27 and 34, occupied with a rebar, 18 ins. long, 1/2 in. diam., firmly set, projecting 4 ins. above ground. This accepted as the best available evidence of the orig. cor. position.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 3 N R 5 E S 27 W 1/16 ——— S 34 SRPMIC 2008</p> <p>from which</p> <p>An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground for a reference monument, bears S. 45°00' E., 66.0 ft. dist. with aluminum cap mkd. RM T3N R5E 66.0 FT. TO COR. S 34 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p>An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground for a reference monument, bears S. 45°00' W., 66.0 ft. dist. with aluminum cap mkd. RM T3N R5E 66.0 FT. TO COR. S 34 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p>Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p>
--------	---

**Dependent Resurvey of a Portion of the North Boundary
of the Salt River Pima-Maricopa Indian Community,
T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit the rebar inside the aluminum post.</p> <p>Cor. is located 42 lks. N. of a barbed wire fence, extends E. and W., and 24 lks. S. of an iron and block fence, extending E. and W.</p> <hr/> <p>S. 89°58' W., beginning new measurement.</p>
10.00	<p>Point for the W-W 1/64 sec. cor. of secs. 27 and 34, at proportionate dist., there is no remaining evidence of the 1950 wooden post.</p> <p>Not monumented.</p>
20.00	<p>The cor. of secs. 27, 28, 33 and 34, monumented with an iron post, 2 ins. diam., set 3 ins. below the surface of ground, with brass cap mkd. S28 S27 R5E T3N S33 S34 SRIR 1911.</p> <p>from which</p> <p style="padding-left: 40px;">An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°00' E., 66.0 ft. dist. with aluminum cap mkd. RM T3N R5E 66.0 FT. TO COR. S 34 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p style="padding-left: 40px;">An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground for a reference monument, bears S. 55°00' W., 66.0 ft. dist. with aluminum cap mkd. RM T3N R5E 66.0 FT. TO COR. S 33 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p>Add the marks 2008 to the brass cap.</p> <p>Two, 1/2 in. diam. rebars are set alongside the iron post, no identifying marks.</p> <p>Cor. is located in an iron rail fence, bears N. and S., 42 lks. N. of intersection with a barbed wire fence, extends E. and W., and 22 lks. S. of a fence cor., with block fence extending N., and iron and block fence extending W.</p> <hr/> <p>S. 89°49' W., bet. secs. 28 and 33.</p> <p>On the north boundary of SRPMIC, within an equestrian and walking trail.</p>

**Dependent Resurvey of a Portion of the North Boundary
of the Salt River Pima-Maricopa Indian Community,
T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona**

<p>CHAINS</p> <p>20.00</p>	<p>Point for the E. 1/16 sec. cor. of secs. 28 and 33, at proportionate dist., by the method of irregular boundary adjustment, based on the survey executed by Thomas Wayne Ballard, Arizona R.L.S. No. 21754 in 1988, recorded in the Maricopa County Recorder's Office in book 324, page 30.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 3 N R 5 E S 28 E 1/16 ——— S 33 SRPMIC 2008</p> <p>from which</p> <p style="padding-left: 40px;">An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground for a reference monument, bears S. 45°00' E., 66.0 ft. dist. with aluminum cap mkd. RM T3N R5E 66.0 FT. TO COR. S 33 2008 and an arrow pointing to the cor. Deposit a railroad spike, at the base of the aluminum post.</p> <p style="padding-left: 40px;">An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°00' W., 66.0 ft. dist. with aluminum cap mkd. RM T3N R5E 66.0 FT. TO COR. S 33 2008 and an arrow pointing to the cor. Deposit a railroad spike, at the base of the aluminum post.</p> <p>Deposit a railroad spike, at the base of the aluminum post.</p> <p>The orig. iron pipe, 36 ins. long, 1 in. diam., sans brass cap was found lying loose nearby, remove from area, impracticable to bury.</p> <p>Cor. is located 42 lks. N. of a barbed wire fence, extends E. and W., and 24 lks. S. of a block fence, extending E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°25' W., beginning new measurement.</p>
<p>19.86</p>	<p>The 1/4 sec. cor. of secs. 28 and 33, perpetuated by Scott A. Nelson, Arizona R.L.S. No. 21782, in 2005, as recorded in the Maricopa County Recorder's Office in book 752, page 33, monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, 18 ins. in the ground, with attached 2 ins. diam., aluminum cap, mkd. MARICOPA COUNTY T3N R5E 1/4 S28 S33 2005 RLS 21782. This is accepted as a careful and faithful perpetuation of the position of the orig. cor.</p>

**Dependent Resurvey of a Portion of the North Boundary
of the Salt River Pima-Maricopa Indian Community,
T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona**

<p>CHAINS</p>	<p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 3 N R 5 E S 28 1/4 ——— S 33 SRPMIC 2008</p> <p>from which</p> <p style="padding-left: 40px;">An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 25°00' E., 33.0 ft. dist. with aluminum cap mkd. RM T3N R5E 33.0 FT. TO COR. S 33 2008 and an arrow pointing to the cor. Deposit a rebar, 18 ins. long, 1/2 in. diam., inside the aluminum post.</p> <p style="padding-left: 40px;">An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 65°00' W., 66.0 ft. dist. with aluminum cap mkd. RM T3N R5E 66.0 FT. TO COR. S 33 2008 and an arrow pointing to the cor. Deposit a rebar, 18 ins. long, 1/2 in. diam., inside the aluminum post.</p> <p>Deposit the rebar, inside the aluminum post.</p> <p>Cor. is located 43 lks. N. of a barbed wire fence, extends E. and W., and 22 lks. S. of an iron and block fence, extending E. and W.</p> <p style="text-align: center;">—————</p> <p>West, beginning new measurement.</p> <p>19.98 Point for the W. 1/16 sec. cor. of secs. 28 and 33, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 3 N R 5 E S 28 W 1/16 ——— S 33 SRPMIC 2008</p> <p>from which</p>
---------------	--

**Dependent Resurvey of a Portion of the North Boundary
of the Salt River Pima-Maricopa Indian Community,
T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears S. 45°00' E., 66.0 ft. dist. with aluminum cap mkd. RM T3N R5E 66.0 FT. TO COR. S 33 2008 and an arrow pointing to the cor. Deposit a rebar., 18 ins. long, 1/2 in. diam., inside the aluminum post.</p> <p>An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears S. 45°00' W., 66.0 ft. dist. with aluminum cap mkd. RM T3N R5E 66.0 FT. TO COR. S 33 2008 and an arrow pointing to the cor. Deposit a rebar, 18 ins. long, 1/2 in. diam., inside the aluminum post.</p> <p>Deposit a rebar, 18 ins. long, 1/2 in. diam., inside the aluminum post.</p> <p>Cor. is located 42 lks. N. of a barbed wire fence, extends E. and W., and 25 lks. S. of an iron and block fence, extending E. and W.</p>
39.96	<p>The cor. of secs. 28, 29, 32 and 33, occupied with a brass disk, 3 ins. diam., set in a 8 ins. diam. concrete cylinder, projecting 3 ins. above ground, with top mkd. CITY OF SCOTTSDALE 19. This is accepted as the best available evidence of the position of the orig. cor.</p> <p>Not remonumented.</p> <p>from which</p> <p>An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground for a reference monument, bears S. 45°00' E., 100.0 ft. dist. with aluminum cap mkd. RM T3N R5E 100.0 FT. TO COR. S 33 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p>An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground for a reference monument, bears S. 35°00' W., 100.0 ft. dist. with aluminum cap mkd. RM T3N R5E 100.0 FT. TO COR. S 32 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p>Cor. is located 41 lks. N. of a barbed wire fence, extends E. and W.</p> <hr/> <p>N. 89°26' W., bet. secs. 29 and 32.</p> <p>On the north boundary of the SRPMIC, within an equestrian and walking trail.</p>

**Dependent Resurvey of a Portion of the North Boundary
of the Salt River Pima-Maricopa Indian Community,
T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
20.15	<p>The E. 1/16 sec. cor. of secs. 29 and 32, monumented with an iron post, 1 in. diam., set in concrete, 6 ins. below surface of ground, sans brass cap.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over the iron post, with aluminum cap mkd.</p> <p style="text-align: center;">T 3 N R 5 E S 29 E 1/16 ——— S 32 SRPMIC 2008</p> <p>from which</p> <p style="padding-left: 40px;">An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground for a reference monument, bears S. 45°00' E., 66.0 ft. dist. with aluminum cap mkd. RM T3N R5E 66.0 FT. TO COR. S 32 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p style="padding-left: 40px;">An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground for a reference monument, bears S. 45°00' W., 60.0 ft. dist. with aluminum cap mkd. RM T3N R5E 60.0 FT. TO COR. S 32 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p>Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p>Cor. is located 43 lks. N. of a barbed wire fence, extends E. and W., and 24 lks. S. of an iron and block fence, extending E. and W.</p> <p style="text-align: center;">—————</p> <p>S. 89°48' W., beginning new measurement.</p>
20.01	<p>The 1/4 sec. cor. of secs. 29 and 32, perpetuated by Blair C. Meggitt, Arizona R.L.S. No. 18436, monumented with a brass disk, 3 ins. diam., set in concrete, 3 ins. below the surface of ground, with top mkd. SRPMIC 18436 S29 S32 T3N R5E 1992. This is accepted as a careful and faithful perpetuation of the position of the orig. cor.</p> <p>Not remonumented.</p> <p>from which</p>

**Dependent Resurvey of a Portion of the North Boundary
of the Salt River Pima-Maricopa Indian Community,
T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°00' E., 70.0 ft. dist. with aluminum cap mkd. RM T3N R5E 70.0 FT. TO COR. S 32 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p>An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°00' W., 75.0 ft. dist. with aluminum cap mkd. RM T3N R5E 75.0 FT. TO COR. S 32 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p>Cor. is located 41 lks. N. of a barbed wire fence, extends E. and W., and 24 lks. S. of a block fence, extending E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°54' W., beginning new measurement.</p>
19.945	<p>Point for the W. 1/16 sec. cor. of secs. 29 and 32, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 3 N R 5 E S 29 W 1/16 ——— S 32 SRPMIC 2008</p> </div> <p>from which</p> <p>An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°00' E., 66.0 ft. dist. with aluminum cap mkd. RM T3N R5E 66.0 FT. TO COR. S 32 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p>An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°00' W., 55.0 ft. dist. with aluminum cap mkd. RM T3N R5E 55.0 FT. TO COR. S 32 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p>

**Dependent Resurvey of a Portion of the North Boundary
of the Salt River Pima-Maricopa Indian Community,
T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p>Cor. is located 40 lks. N. of a barbed wire fence, extends E. and W., and 23 lks. S. of an iron and block fence, extending E. and W.</p> <p>39.89 The cor. of secs. 29, 30, 31 and 32, perpetuated by Scott A. Nelson, Arizona R.L.S. No. 21782, in 2005, as recorded in the Maricopa County Recorder's Office in book 752, page 33, monumented with a rebar, 1/2 in. diam., firmly set, 15 ins. below the surface of ground, with attached 2 ins. diam., aluminum cap, mkd. MARICOPA COUNTY T3N R5E S30 S29 S31 S32 2005 RLS 21782. This is accepted as a careful and faithful perpetuation of the position of the orig. cor.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over the rebar, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td>T 3 N</td><td>R 5 E</td></tr> <tr><td>S 30</td><td> S 29</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 31</td><td> S 32</td></tr> <tr><td colspan="2" style="text-align: center;">SRPMIC</td></tr> <tr><td colspan="2" style="text-align: center;">2008</td></tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°00' E., 66.0 ft. dist. with aluminum cap mkd. RM T3N R5E 66.0 FT. TO COR. S 32 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p style="padding-left: 40px;">An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground for a reference monument, bears S. 45°00' W., 66.0 ft. dist. with aluminum cap mkd. RM T3N R5E 66.0 FT. TO COR. S 31 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p>Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p>Cor. is located 44 lks. N. of a barbed wire fence, extends E. and W.</p> <hr style="width: 60%; margin-left: 0;"/> <p>N. 89°56' W., bet. secs. 30 and 31.</p>	T 3 N	R 5 E	S 30	S 29			S 31	S 32	SRPMIC		2008	
T 3 N	R 5 E												
S 30	S 29												
S 31	S 32												
SRPMIC													
2008													

**Dependent Resurvey of a Portion of the North Boundary
of the Salt River Pima-Maricopa Indian Community,
T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°00' E., 75.0 ft. dist. with aluminum cap mkd. RM T3N R5E 75.0 FT. TO COR. S 31 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p>An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°00' W., 33.0 ft. dist. with aluminum cap mkd. RM T3N R5E 33.0 FT. TO COR. S 31 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p>Cor. is located 42 lks. N. of a barbed wire fence, extends E. and W., and 27 lks. S. of a block fence, extending E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°44' W., beginning new measurement.</p>
1.05	Center of rock lined drainage channel, 32 ft. wide, 4 ft. deep, drains S. 20° E.
11.85	A rebar, 1/2 in. diam., firmly set, flush with the surface of ground, with affixed 1 in. diam. plastic cap, mkd. RLS 33315.
16.11	A rebar, 1/2 in. diam., firmly set, flush with the surface of ground, with affixed 1 in. diam. plastic cap, mkd. RLS 33315.
18.48	Point selected for a witness point.
	<p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">W P T 3 N R 5 E S 30 <hr style="width: 10%; margin: 0 auto;"/> S 31 SRPMIC 2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p> <p>Cor. is located 42 lks. N. of a barbed wire fence, extends E. and W.</p>
19.17	A brass disk, 3 ins. diam., seated in concrete, flush with the surface of ground, with top mkd. A.D.O.T. HIGHWAY DIV. 19.

**Dependent Resurvey of a Portion of the North Boundary
of the Salt River Pima-Maricopa Indian Community,
T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
19.995	<p>Point for the W. 1/16 sec. cor. of secs. 30 and 31, at proportionate dist., falls in the pavement of 90th St., City of Scottsdale, asphalt, bears N. and S., there is no remaining evidence of the orig. cor.</p> <p>Not monumented.</p>
20.68	<p>A rebar, 1/2 in. diam., firmly set and bent over 4 ins. to the S., no identifying marks.</p>
21.51	<p>Point selected for a witness point.</p> <p>Set an aluminum drive rod, 10 ins. long, 3/4 ins. diam., 10 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;"> W P T 3 N R 5 E S 30 <hr style="width: 10%; margin: 0 auto;"/> S 31 SRPMIC 2008 </p> <p>Cor. is located 14 lks. N. of the N. edge of pavement, of an unnamed road in the SRPMIC, 25 ft. wide, bears E. and W.</p>
22.75	<p>A PK nail, set flush with the pavement, with attached 1 1/2 ins. diam., aluminum disk stamped AJW 37936.</p>
35.445	<p>Point selected for a witness point.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;"> W P T 3 N R 5 E S 30 <hr style="width: 10%; margin: 0 auto;"/> S 31 SRPMIC 2008 </p> <p>Deposit a magnet, in a white plastic case, at the base of the aluminum post.</p>
35.47	<p>Easterly right-of-way fence to State Route No. 101 (Pima Freeway), woven wire, 6 ft. high, bears S. 5° E. and N. 5° W.</p>
36.10	<p>A brass disk, 3 ins. diam., seated in concrete, flush with the surface of ground, with top mkd. A.D.O.T. HIGHWAY DIV. 4 + 08.329 19; located within the right-of-way of State Route No. 101.</p>

**Dependent Resurvey of a Portion of the North Boundary
of the Salt River Pima-Maricopa Indian Community,
T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>39.99 The closing cor. of secs. 30 and 31, identical with the NW cor. of the SRPMIC, perpetuated by the Arizona Department of Transportation, monumented with a brass disk, 3 ins. diam., seated in concrete, flush with the pavement of State Route No. 101, with top mkd. A.D.O.T. HIGHWAY DIV. 19. This is accepted as careful and faithful reestablishment of the orig. cor. position.</p> <p>from which, the reference monuments established in 2005, by Scott A. Nelson, Arizona R.L.S. No. 21782.</p> <p style="padding-left: 40px;">A rebar, 1/2 in. diam., firmly set, projecting 1 in. above ground, bears S. 55°44' W., 133.00 ft. dist., the 2 ins. diameter brass cap is missing.</p> <p style="padding-left: 40px;">A rebar, 1/2 in. diam., firmly set, projecting 1 in. above ground, bears N. 68°24' W., 113.86 ft. dist., the 2 ins. diameter brass cap is missing.</p> <p>The origin of the rebars, is recorded in the Maricopa County Recorder's Office, in book 763, page 38.</p> <p>Cor. is located in the shoulder of the S. bound lanes of, State Route No. 101, 9 lks. E. of retaining/sound wall.</p> <p>From this cor. point, the cor. of secs. 25 and 36 only, T. 3 N., R. 4 E., bears S. 0°16' W., 3.10 chs. dist., monumented with a 3 ins. diam. aluminum cap, seated in concrete and set in a 10 ins. diam. iron survey well, with top mkd. A.D.O.T. HIGHWAY DIV. 19. This is accepted as a careful and faithful reestablishment of the orig. cor.</p> <p>From this same cor. point, the 1/4 sec. cor. of sec. 24 only, T. 3 N., R. 4 E., bears N. 0°16' E., 116.93 chs. dist., monumented with a rebar, 1/2 in. diam., firmly set, flush with the surface of ground, with affixed 2 ins. diam., aluminum cap mkd. MARICOPA COUNTY T3N R4E R5E 1/4 S24 2005 RLS 21782. Reestablished by Scott A. Nelson, Arizona R.L.S. and recorded in Maricopa County Recorder's Office, in book 763, page 38. This is accepted as a careful and faithful reestablishment of the orig. cor.</p> <p>This control line was fully retraced and careful search was made for evidence of intervening cors., none of which was recovered.</p> <hr style="width: 60%; margin-left: 0;"/>
--------	--

T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

This survey is located at the foot of the McDowell Mountains. The terrain is generally flat, with numerous south draining washes. The mean elevation is 1400 ft. above sea level. The timber is composed of palo verde, ironwood and mesquite. Residential housing within the city of Scottsdale, is north of the area surveyed.

The mean magnetic declination of $11\ 1/4^\circ$ E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2005 for the dates of survey.
