

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,

TOWNSHIP 26 NORTH, RANGE 28 EAST,

AND THE

DEPENDENT RESURVEY OF THE EAST BOUNDARY,

AND THE

SURVEY OF THE SUBDIVISIONAL LINES,

TOWNSHIP 25 NORTH, RANGE 27 EAST,

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA

EXECUTED BY

Leonard R. Sandoval, Cadastral Surveyor

Under Special Instructions dated and approved April 14, 2008, which provided for the surveys included under Group No. 1048, and assignment instructions dated April 14, 2008.

Survey commenced April 21, 2008

Survey completed July 16, 2008

INDEX DIAGRAM

TOWNSHIP 26 NORTH RANGE 28 EAST
 TOWNSHIP 25 NORTH RANGE 27 EAST

Gila and Salt River Meridian, Arizona

4

63 6 61	62 5 47	49 4 38	40 3 29	30 2 20	21 1 10
60 7 59	59 8 46	46 9 37	37 10 27	28 11 18	19 12 10
57 18 56	57 17 44	45 16 35	36 15 26	27 14 17	18 13 9
55 19 54	55 20 43	44 21 34	35 22 25	25 23 15	16 24 7
53 30 51	52 29 41	42 28 32	33 27 23	24 26 14	15 25 6
51 31 49	50 32 40	41 33 31	32 34 22	23 35 12	13 36 5

**T. 26 N., R. 28 E. and T. 25 N., R. 27 E.,
Gila and Salt River Meridian, Arizona**

CHAINS

The following field notes describe the dependent resurvey of a portion of the south boundary, Township 26 North, Range 28 East, and the dependent resurvey of the east boundary and the survey of the subdivisional lines, Township 25 North, Range 27 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Frank Follman surveyed the Sixth Standard Parallel North (south boundary), Township 25 North, Range 27 East, and the south boundary, Township 26 North, Range 28 East, in 1883. Frederick C. Miller surveyed the east boundary, Township 25 North, Range 26 East, in 1915. Loyd E. Sechrist and Sidney E. Blout resurveyed the Sixth Standard Parallel North (south boundary), Township 25 North, Range 27 East, and the south boundary, Township 26 North, Range 28 East and surveyed the west boundary, Township 25 North, Range 28 East, in 1920-27. Jones Curtiss dependently resurveyed the Sixth Standard Parallel North (south boundaries), Township 25 North, Ranges 26 and 27 East, and dependently resurveyed the east boundary, Township 25 North, Range 26 East, in 2002-03. Jones Curtiss surveyed the east boundary and the subdivisional lines, Township 24 North, Range 27 East, in 2003. Leonard R. Sandoval surveyed the south boundary, Township 26 North, Range 27 East, in 2004.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, the Assignment Instructions dated April 14, 2008 and the Special Instructions dated April 14, 2008, for Group 1048, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Preliminary to the survey, the lines of the prior surveys were retraced and search was made for all corners and other calls of the record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) SPIDERROCKAZ2005, GRANTS, AND CHACOCNHP_NM2005. The NAD83(COR96)(EPOCH:2002) geographic position of the southeast corner of the township is as follows:

Latitude: 35°31'03.38" N. Longitude: 109°24'02.88" W.

The mean magnetic declination is 10 3/4° E.

**Dependent Resurvey of a Portion of the South Boundary,
T. 26 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS

Restoring the resurvey executed by
Loyd E. Sechrist and Sidney E. Blout, in 1920-27

Beginning at the 1/4 sec. cor. of sec. 31 only, T. 26 N.,
R. 28 E., monumented with a sandstone, 18 x 14 x 3 ins., firmly
set flush with surface of the ground, mkd. 1/4 on W. face, with
an iron post, 1 in. diam., firmly set alongside, projecting
14 ins. above ground, with brass cap mkd. 1/4 S31 1920.

from which the remains of a 1883 bearing tree

A piñon stump, 12 ins. diam., bears N. 56° W., 68 lks.
dist., mkd. 1/4 S BT on partially healed blaze.

from which the remains of the 1920 bearing trees

A root hole, bears N. 40° E., 1.02 chs. dist., with the
badly decayed remains of a piñon trunk, 12 ins. diam.,
lying alongside, with no mks.

A piñon, 16 ins. diam., bears N. 22 1/2° W., 1.48 chs.
dist., mkd. 1/4 S31 BT on open blaze.

At the corner point

Reset the iron post, 36 ins. long, 30 ins. in the ground, with
brass cap mkd.

T 26 N R 28 E
1/4 S 31

T 25 N R 28 E
2008
1920

Bury the original sandstone alongside the iron post.

N. 89°58' W., on the S. bdy. of sec. 31.

Over rolling and broken land.

39.50

The cor. of Tps. 26 N., Rs. 27 and 28 E., monumented with a
stainless steel post, 2 1/2 ins. diam., firmly set, projecting
3 ins. above a mound of stone, 5 ft. base, 1/2 ft. high, with
brass cap mkd. T26N R27E R28E S36 S31 T25N R27E 2002 2004.

from which the 1883 bearing tree

A piñon, 14 ins. diam., bears N. 5 3/4° E., 64 lks. dist.,
with healed blaze.

**Dependent Resurvey of a Portion of the South Boundary,
T. 26 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>from which the 1920 bearing trees</p> <p>A forked piñon, 14 ins. diam., at base, bears N. 29° E., 1.74 chs. dist., with illegible scribe mks. on open blaze, on a branch, 9 ins. diam.</p> <p>A piñon, 15 ins. diam., bears N. 76 1/2° E., 1.78 chs. dist., with illegible scribe mks. on open blaze.</p> <p>A forked piñon, 12 ins. diam., at base, bears N. 82° W., 40 lks. dist., with illegible scribe mks. on open blaze, on a branch, 8 ins. diam.</p> <p>Add the marks S1 2008 to the brass cap.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of the East Boundary, T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;">Restoring the survey executed by Loyd E. Sechrist and Sidney E. Blout, in 1920-27</p> <hr/> <p>From the stan. cor. of Tps. 25 N., Rs. 27 and 28 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. SC T25N R27E R28E S36 S31 2003 1920, with a mound of stone, 4 ft. base, 2 ft. high, N. of cor.</p> <p>from which the remains of the 1920 bearing trees</p> <p>A piñon, 23 ins. diam., bears N. 48 1/2° E., 88 lks. dist., mkd. T25N R28E S31 SC BT, on partially healed blaze.</p> <p>A piñon stump, 24 ins. diam., at base, 12 ins. high, bears N. 35 1/4° W., 78 lks. dist.</p> <p>Add the marks 2008 to the brass cap.</p> <p>From this cor. point, the 1920 line tree, a piñon, 12 ins. diam., bears East, 43 lks. dist., with hack mks. on E. and W. sides.</p> <p>N. 0°02' E., bet. secs. 31 and 36.</p> <p>Over rolling and broken land.</p> <p>7.40 Trail road, bears S. 55° E. and N. 55° W.</p> <p>40.04 The 1/4 sec. cor. of secs. 31 and 36, determined at record distances from the remains of the 1920 bearing trees</p>
--------	--

**Dependent Resurvey of the East Boundary,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>A dead, dry, badly burned and charred piñon, 14 ins. diam., bears S. 56 3/4° E., 6 lks. dist., with illegible scribe mks. on open blaze.</p> <p>A root hole, with the remains of piñon tree roots, bears S. 78 3/4° W., 71 lks. dist.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled by a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N 1/4 R 27 E R 28 E S 36 S 31</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°01' E., beginning new measurement.</p> <p>Over rolling and broken land.</p>
2.90	Navajo Route 28, a graded road, 25 ft. wide, bears N. 30° E. and S. 30° W.
40.02	<p>The cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. T25N R27E R28E S25 S30 S36 S31 1920.</p> <p>from which the remains of the 1920 bearing trees</p> <p style="padding-left: 40px;">A dead, dry, badly burned and charred piñon, 10 ins diam., bears S. 32 1/4° W., 13 lks. dist., with illegible scribe mks. on open blaze.</p> <p style="padding-left: 40px;">A root hole, 14 ins. diam., bears N. 46 1/2° W., 27 lks dist., with a dead, dry, badly burned and charred piñon, 12 ins. diam., with illegible scribe mks. on open blaze, lying alongside.</p> <p>Add the marks 2008 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°03' E., bet. secs. 25 and 30.</p> <p>Over rolling and broken land.</p>

**Dependent Resurvey of the East Boundary,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS

40.06

The 1/4 sec. cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, in a scattered mound of stone, with brass cap mkd. 1/4 S25 S30 1920.

from which the remaining 1920 bearing tree

A dead, dry, badly burned and charred piñon, 6 ins. diam., bears N. 13 1/2° E., 14 lks. dist., with illegible scribe mks. on open blaze.

Add the marks T25N R27E R28E 2008 to the brass cap.

N. 0°01' E., beginning new measurement.

Over rolling and broken land.

40.01

The cor. of secs. 19, 24, 25 and 30, determined at record distances from the 1920 bearing trees

A piñon, 14 ins. diam., bears N. 73° E., 1.06 chs. dist., mkd. T25N R 8E S19 BT on partially healed blaze.

A dead, dry piñon, 12 ins. diam., bears S. 18° E., 1.48 chs. dist., mkd. T25N R28E S30 BT on open blaze.

A dead, dry piñon, 10 ins. diam., bears S. 42° W., 85 lks. dist., mkd. T25N R27E S25 BT on open blaze.

A piñon, 11 ins. diam., bears N. 58 1/2° W., 22 lks. dist., mkd. T25N R27E S2 BT on partially healed blaze.
(Record: N. 63° W.)

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 N	
R 27 E	R 28 E
S 24	S 19
S 25	S 30

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

N. 0°03' E., bet. secs. 19 and 24.

Over rolling and broken land.

**Dependent Resurvey of the East Boundary,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
40.03	<p>The 1/4 sec. cor. of secs. 19 and 24, determined in the center of a mound of stone, 4 ft. base, 1 ft. high. This is accepted as the best available evidence of the position of the orig. cor. from which the 1920 bearing trees</p> <p style="padding-left: 40px;">A piñon, 9 ins. diam., bears S. 79 1/4° E., 38 lks. dist., mkd. 4 S19 BT on partially healed blaze.</p> <p style="padding-left: 40px;">A dead, dry piñon, 10 ins. diam., bears S. 86 3/4° W., 1.54 chs. dist., mkd. 1/4 S24 BT on open blaze. (Record: 1.51 chs.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, rebuild the mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <table style="margin: auto;"> <tr><td colspan="2">T 25 N</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>R 27 E</td><td> R 28 E</td></tr> <tr><td>S 24</td><td> S 19</td></tr> </table> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 0°03' E., beginning new measurement.</p> <p>Over rolling and broken land.</p>	T 25 N		1/4		R 27 E	R 28 E	S 24	S 19
T 25 N									
1/4									
R 27 E	R 28 E								
S 24	S 19								
40.05	<p>The cor. of secs. 13, 18, 19 and 24, determined at record distances from the remaining 1920 bearing trees</p> <p style="padding-left: 40px;">A piñon stump, 15 diam., 36 ins. high, bears N. 51 3/4° E., 60 lks. dist., mkd. T25N R28E S1 BT on open blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 36 ins. diam., bears S. 17° W., 1.13 chs. dist., mkd. 27E 24 BT on partially healed blaze.</p> <p style="padding-left: 40px;">A dead, dry piñon, 15 ins. diam., bears N. 29 1/2° W., 1.70 chs. dist., mkd. T25N R27E S13 BT on open blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>								

**Dependent Resurvey of the East Boundary,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS											
	<table style="margin: auto;"> <tr><td colspan="2">T 25 N</td></tr> <tr><td>R 27 E</td><td>R 28 E</td></tr> <tr><td>S 13</td><td>S 18</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 24</td><td>S 19</td></tr> </table>	T 25 N		R 27 E	R 28 E	S 13	S 18	<hr/>		S 24	S 19
T 25 N											
R 27 E	R 28 E										
S 13	S 18										
<hr/>											
S 24	S 19										
	2008										
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.										
	<hr/>										
	N. 0°02' E., bet. secs. 13 and 18.										
	Over rolling and broken land.										
15.20	Underground gas pipeline, bears N. 70° E. and S. 70° W.										
19.45	Asphalt paved road, 16 ft. wide, bears N. 75° E. and S. 75° W.										
40.00	The 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 21 ins. above ground, with brass cap mkd. 1/4 S13 S18 1920.										
	from which the 1920 bearing trees										
	A piñon, 12 ins. diam., bears N. 58 1/4° E., 11 lks. dist., mkd. 1/4 S18 B on partially healed blaze.										
	A piñon, 17 ins. diam., bears S. 64° W., 90 lks. dist., mkd. 1/4 S13 BT on partially healed blaze.										
	Add the marks T25N R27E R28E 2008 to the brass cap.										
	<hr/>										
	N. 0°04' E., beginning new measurement.										
	Over rolling land.										
40.05	The cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. T25N R27E R28E S12 S7 S13 S18 1920.										
	from which the remains of the 1920 bearing trees										
	A dead, dry piñon, 12 ins. diam., bears N. 86 1/2° E., 54 lks. dist., mkd. T25N R28E S7 BT on partially healed blaze.										
	A forked juniper, 9 ins. diam. at the base, bears S. 50 1/2° E., 25 lks. dist., mkd. T25N R28E S18 BT on partially healed blaze. (Record: S. 49° E.)										

**Dependent Resurvey of the East Boundary,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>A root hole, bears S. 72 1/4° W., 41 lks. dist., with piñon stump, 9 ins. diam., lying loose nearby, mkd. T25N R27E S13 BT on partially healed blaze.</p> <p>A dead, dry piñon, 8 ins. diam., bears N. 49° W., 37 lks. dist., mkd. T2 R27 S12 BT on partially healed blaze.</p> <p>Add the marks 2008 to the brass cap.</p> <hr/> <p>N. 0°01' W., bet. secs. 7 and 12.</p> <p>Over rolling land.</p>
40.04	<p>The 1/4 sec. cor. of secs. 7 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. 1/4 S12 S7 1920.</p> <p>from which the 1920 bearing trees</p> <p style="padding-left: 40px;">A piñon, 14 ins. diam., bears N. 57° E., 45 lks. dist., mkd. 1/4 S7 BT on open blaze.</p> <p style="padding-left: 40px;">A dead, dry forked juniper, 10 ins. diam. at the base, bears S. 43° W., 30 lks. dist., mkd. 1/4 S12 BT on open blaze. (Record: S. 47 1/2° W.)</p> <p>Add the marks T25N R27E R28E 2008 to the brass cap.</p> <hr/> <p>North, beginning new measurement.</p> <p>Over rolling land.</p>
6.15	Trail road, bears S. 15° E. and N. 15° W.
6.40	Power line, bears S. 20° E. and N. 20° W.
40.03	<p>The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. T25N R27E R28E S1 S6 S12 S7 1920.</p> <p>from which the 1920 bearing tree</p> <p style="padding-left: 40px;">A piñon, 20 ins. diam., bears S. 34° W., 4.27 chs. dist., mkd. BT on mostly healed blaze. (Record: S. 34 1/2° W.)</p> <p>Add the marks 2008 to the brass cap.</p> <hr/> <p>North, bet. secs. 1 and 6.</p> <p>Over rolling land.</p>

**Dependent Resurvey of the East Boundary,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
13.20	Trail road, bears S. 65° E. and N. 65° W.
40.04	<p>The 1/4 sec. cor. of secs. 1 and 6, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above ground, in a scattered mound of stone, with brass cap mkd. 1/4 S1 S6 1920.</p> <p>from which the 1920 bearing trees</p> <p style="padding-left: 40px;">A piñon, 17 ins. diam., bears N. 29 1/2° E., 70 lks., mkd. 1/4 S6 BT on open blaze.</p> <p style="padding-left: 40px;">A piñon, 14 ins. diam., bears S. 15 3/4° W., 61 lks. dist., mkd. 1/4 S1 BT on open blaze.</p> <p>Add the marks T25N R27E R28E 2008 to the brass cap.</p> <p>Rebuild the mound of stone around the iron post, 3 ft. base, to top.</p> <hr style="width: 30%; margin: 20px auto;"/> <p>N. 0°01' W., beginning new measurement.</p> <p>Over rolling land.</p>
42.90	<p>The closing cor. of Tps. 25 N., Rs. 27 and 28 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 14 ins. above ground, in an embedded mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. T26N R28E S31 S1 S6 R27E R28E CC T25N 1920 2004.</p> <p>from which the remaining 1920 bearing tree</p> <p style="padding-left: 40px;">A dead piñon, 25 ins. diam., bears S. 35 1/2° W., 1.80 chs. dist., mkd. T25N R27E S1 BT on open blaze. Deface the marks.</p> <p>Add the marks AM and 2008 to the brass cap, bury the iron post, 36 ins. long, in place, and destroy the mound of stone.</p>
42.92	<p>Point for the closing cor. of Tps. 25 N., Rs. 27 and 28 E., at intersection with the S. bdy. of sec. 31, T. 26 N., R. 28 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the East Boundary,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS					
	T 26 N R 28 E S 31 <hr style="width: 10%; margin: auto;"/> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 1</td> <td style="padding: 0 5px;">S 6</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R 27 E</td> <td style="padding: 0 5px;">R 28 E</td> </tr> </table> T 25 N CC 2008	S 1	S 6	R 27 E	R 28 E
S 1	S 6				
R 27 E	R 28 E				
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.				
	From this cor. point, the 1/4 sec. cor. of sec. 31 only, T. 26 N., R. 28 E., bears S. 89°58' E., 33.45 chs. dist., hereinbefore described.				
	From this same cor. point, the cor. of Tps. 26 N., Rs. 27 and 28 E., bears N. 89°58' W., 6.05 chs. dist., hereinbefore described.				
	<hr/> Survey of the Subdivisional Lines, T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona <hr/>				
	From the stan. cor. of secs. 35 and 36, on the Sixth Standard Parallel North, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T25N R27E S35 S36 2003, with a mound of stone, 3 ft. base, 1 ft. high, N. of cor.				
	from which the 1920 bearing trees				
	A dead, dry piñon, 9 ins. diam., bears N. 88 1/2° E., 47 lks. dist., mkd. T25N R27E S36 SC BT on partially healed blaze.				
	A piñon, 10 ins. diam., bears N. 73 1/4° W., 11 lks. dist., mkd. T25N R27E S35 SC BT on partially healed blaze.				
	Add the marks 2008 to the brass cap.				
	N. 0°01' E., bet. secs. 35 and 36.				
	Over rolling and broken land.				
3.95	Navajo Route 28, a graded road, 25 ft. wide, bears N. 80° E. and S. 80° W.				
40.00	Point for the 1/4 sec. cor. of secs. 35 and 36.				

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E 1/4 S 35 S 36</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 25, 26, 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E S 26 S 25 S 35 S 36</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy, gravelly clay. Timber, scattered ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 25 and 36.</p> <p>Over rolling and broken land.</p>
40.03	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E S 25 1/4 ——— S 36</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
55.15	Trail road, bears S. 50° E. and N. 50° W.
80.06	The cor. of secs. 25, 26, 35 and 36. Land, rolling and broken. Soil, sandy, gravelly clay. Timber, scattered ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.
	N. 0°01' E., bet. secs. 25 and 26. Over rolling and broken land.
4.80	Trail road, bears East and West.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 27 E 1/4 S 26 S 25 2008 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 27 E S 23 S 24 S 26 S 25 2008 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located 1.20 chs. S. and 75 lks. E. of a trail road, bears N. 30° E. and S. 30° W.

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, scattered ponderosa pine, piñon juniper and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°57' W., bet. secs. 24 and 25.</p> <p>Over rolling and broken land.</p>
40.04	<p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 27 E S 24 1/4 ——— S 25</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.08	<p>The cor. of secs. 23, 24, 25 and 26.</p> <p>Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°01' E., bet. secs. 23 and 24.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in sandstone bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 27 E 1/4 S 23 S 24</p> <p>2008</p> </div>

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>76.20 Underground gas pipeline, bears N. 80° E. and S. 80° W.</p> <p>78.40 Asphalt paved road, 16 ft. wide, bears N. 75° E. and S. 75° W.</p> <p>80.00 Point for the cor. of secs. 13, 14, 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 25 N</td> <td style="padding: 0 10px;">R 27 E</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 14</td> <td style="padding: 0 10px;">S 13</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 23</td> <td style="padding: 0 10px;">S 24</td> </tr> </table> <p>2008</p> </div> <p>from which</p> <p style="margin-left: 40px;">The SE cor. of a log cabin with a concrete foundation, 24 x 18 ft., bears N. 18 1/2° E., 1.115 chs. dist., the long side bears N. 12° E.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.</p> <hr style="width: 60%; margin: 20px auto;"/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°53' W., bet. secs. 13 and 24.</p> <p>Over rolling and broken land.</p> <p>28.80 Trail road, bears S. 10° E. and N. 10° W.</p> <p>40.06 Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 25 N</td> <td style="padding: 0 10px;">R 27 E</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">S 13</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="padding: 0 10px; border-top: 1px solid black;">S 24</td> </tr> </table> <p>2008</p> </div>	T 25 N	R 27 E	S 14	S 13	S 23	S 24	T 25 N	R 27 E		S 13	1/4	S 24
T 25 N	R 27 E												
S 14	S 13												
S 23	S 24												
T 25 N	R 27 E												
	S 13												
1/4	S 24												

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
63.80	Underground gas pipeline, bears N. 80° E. and S. 80° W.
72.90	Asphalt paved road, 16 ft. wide, bears N. 75° E. and S. 75° W.
80.12	The cor. of secs. 13, 14, 23 and 24.
	Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.
	N. 0°01' E., bet. secs. 13 and 14.
	Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 27 E 1/4 S 14 S 13 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 11, 12, 13 and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 27 E S 11 S 12 S 14 S 13 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°51' W., bet. secs. 12 and 13.</p> <p>Over rolling land.</p>
40.07	<p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 27 E S 12 1/4 ——— S 13</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.14	<p>The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, rolling. Soil, sandy, gravelly clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°01' E., bet. secs. 11 and 12.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 27 E 1/4 S 11 S 12</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
78.30	Trail road, bears S. 60° E. and N. 60° W.								
80.00	Point for the cor. of secs. 1, 2, 11 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 25 N</td><td>R 27 E</td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td>S 11</td><td>S 12</td></tr> </table> <p>2008</p> </div>	T 25 N	R 27 E	S 2	S 1	S 11	S 12		
T 25 N	R 27 E								
S 2	S 1								
S 11	S 12								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling. Soil, sandy, gravelly clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.								
	From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described. S. 89°49' W., bet. secs. 1 and 12. Over rolling land.								
10.55	Trail road, bears S. 20° E. and N. 20° W.								
10.68	Power line, bears S. 20° E. and N. 20° W.								
40.05	Point for the 1/4 sec. cor. of secs. 1 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 25 N</td><td>R 27 E</td></tr> <tr><td>S 1</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 12</td><td></td></tr> </table> <p>2008</p> </div>	T 25 N	R 27 E	S 1		1/4	—	S 12	
T 25 N	R 27 E								
S 1									
1/4	—								
S 12									
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
48.49	Woven wire fence with one strand of barbed wire, bears N. 50° E. and S. 50° W.								
63.95	Trail road, paralleled on the E. side, by a barbed wire fence, 5 strand, bears S. 15° E. and N. 15° W.								

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.10	<p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°01' E., bet. secs. 1 and 2.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E 1/4 S 2 S 1</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
54.45	Trail road, bears S. 25° E. and N. 25° W.
63.90	Trail road, bears S. 55° E. and N. 55° W.
83.23	<p>Point for the closing cor. of secs. 1 and 2, at intersection with the S. bdy. of sec. 36, T. 26 N., R. 27 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E S 36 ----- S 2 S 1 T 25 N R 27 E CC</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of secs. 1 and 36, Tps. 25 and 26 N., R. 27 E., bears East, 34.00 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set flush with surface of the ground, with brass cap mkd. T26N R27E 1/4 S36 S1 T25N 2004.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS

This cor. now functions as the 1/4 sec. cor. of sec. 36 only,
T. 26 N., R. 27 E., remark the brass cap to read

T 26 N R 27 E
1/4 S 36

T 25 N R 27 E
2008
2004

From this same cor. point, the cor. of secs. 1, 2, 35 and 36,
Tps. 25 and 26 N., R. 27 E., bears West, 6.00 chs. dist.,
monumented with a stainless steel post, 2 1/2 ins. diam., firmly
set, projecting 4 ins. above ground, with brass cap mkd. T26N
R27E S35 S36 S2 S1 T25N 2004.

This cor. now functions as the cor. of secs. 35 and 36 only,
T. 26 N., R. 27 E., remark the brass cap to read

T 26 N R 27 E
S 35 | S 36

S 2
T 25 N R 27 E
2008
2004

Land, rolling.

Soil, sandy, gravelly clay with sandstone outcrops.

Timber, scattered ponderosa pine, piñon, juniper and Gambel oak;
undergrowth, brush and native grasses.

Point for the 1/4 sec. cor of sec. 1 only, at midpoint on the N.
bdy. of sec. 1.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
20 ins. in the ground, in a supporting mound of stone, 3 ft.
base, to top, with brass cap mkd.

T 26 N R 27 E

1/4 S 1
T 25 N R 27 E

2008

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

From this cor. point, the cor. of Tp. 26 N., Rs. 27 and 28 E.,
bears East, 33.975 chs. dist., hereinbefore described.

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this same cor. point, the 1/4 sec. cor. of sec. 36 only, T. 26 N., R. 27 E., bears West, 6.025 chs. dist.

From the stan. cor. of secs. 34 and 35, on the Sixth Standard Parallel North (south boundary), monumented with a stainless steel post, 2 1/2 ins. diam., firmly set flush with the surface of the ground, with brass cap mkd. SC T25N R27E S34 S35 2003.

from which the 2003 accessories

The SW cor. of a wood frame house, 32 x 24 ft., bears N. 62 1/2° E., 2.80 chs. dist., the long side bears North.

The NE cor. of a wood frame barn, 24 x 17 ft., bears N. 80° W., 1.83 chs. dist., the long side bears South.

Add the marks 2008 to the brass cap.

North, bet. secs. 34 and 35.

Over rolling land.

40.00 Point for the 1/4 sec. cor. of secs. 34 and 35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 N R 27 E
1/4
S 34 | S 35

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

66.95 Trail road, bears S. 80° E. and N. 80° W.

80.00 Point for the cor. of secs. 26, 27, 34 and 35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 N R 27 E
S 27 | S 26
S 34 | S 35

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36. N. 89°59' W., bet. secs. 26 and 35. Over rolling land.</p>
32.90	Trail road, bears N. 50° E. and S. 50° W.
40.02	<p>Point for the 1/4 sec. cor. of secs. 26 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 27 E S 26 1/4 ——— S 35</p> <p>2008</p> </div>
80.04	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 26, 27, 34 and 35. Land, rolling. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>North, bet. secs. 26 and 27. Over rolling and broken land.</p>
2.50	Trail road, bears N. 85° E. and S. 85° W.
18.75	Trail road, bears N. 55° E. and S. 55° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 25 N R 27 E 1/4 S 27 S 26 2008 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 22, 23, 26 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 27 E S 22 S 23 S 27 S 26 2008 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses.
	<hr/> From the cor. of secs. 23, 24, 25 and 26. N. 89°59' W., bet. secs. 23 and 26. Over rolling land.
40.02	Point for the 1/4 sec. cor. of secs. 23 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 27 E S 23 1/4 ——— S 26 2008 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.04	The cor. of secs. 22, 23, 26 and 27.

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>North, bet. secs. 22 and 23.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 27 E 1/4 S 22 S 23</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
58.35	Underground gas pipeline, bears N. 75° E. and S. 75° W.
60.40	Asphalt paved road, 16 ft. wide, bears N. 75° E. and S. 75° W.
80.00	<p>Point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 27 E S 15 S 14 S 22 S 23</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 89°59' W., bet. secs. 14 and 23.</p> <p>Over rolling and broken land.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.02	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 27 E</p> <p>S 14</p> <p>1/4 ———</p> <p>S 23</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.04	<p>The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, rolling and broken.</p> <p>Soil, sandy, gravelly clay with sandstone outcrops.</p> <p>Timber, scattered ponderosa pine, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>North, bet. secs. 14 and 15.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 27 E</p> <p>1/4</p> <p>S 15 S 14</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 10, 11, 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 27 E</p> <p>S 10 S 11</p> <p>S 15 S 14</p> <p>2008</p> </div>

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.02	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, scattered ponderosa pine, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 89°59' W., bet. secs. 11 and 14.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E S 11 1/4 ——— S 14</p> <p style="text-align: center;">2008</p>
80.04	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, scattered ponderosa pine, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>North, bet. secs. 10 and 11.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to sandstone bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E 1/4 S 10 S 11</p> <p style="text-align: center;">2008</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>								
80.00	<p>Point for the cor. of secs. 2, 3, 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 25 N</td><td>R 27 E</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td>S 10</td><td>S 11</td></tr> </table> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, scattered ponderosa pine, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°59' W., bet. secs. 2 and 11.</p> <p>Over rolling land.</p>	T 25 N	R 27 E	S 3	S 2	S 10	S 11		
T 25 N	R 27 E								
S 3	S 2								
S 10	S 11								
40.02	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 25 N</td><td>R 27 E</td></tr> <tr><td>S 2</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 11</td><td></td></tr> </table> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 25 N	R 27 E	S 2		1/4	—	S 11	
T 25 N	R 27 E								
S 2									
1/4	—								
S 11									
80.04	<p>The cor. of secs. 2, 3, 10 and 11.</p>								

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>North, bet. secs. 2 and 3.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E 1/4 S 3 S 2 2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
43.80	<p>Trail road, bears S. 65° E. and N. 65° W.</p>
63.95	<p>S. rim of Wide Ruin Wash canyon, 25 ft. high, bears S. 45° E. and N. 45° W., thence across the canyon.</p>
69.00	<p>N. rim of Wide Ruin Wash canyon, 100 ft. high, bears S. 55° E. and N. 55° W.</p>
83.21	<p>Point for the closing cor. of secs. 2 and 3, at intersection with the S. bdy. of sec. 35, T. 26 N., R. 27 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 27 E S 35 ----- S 3 S 2 T 25 N R 27 E CC 2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this cor. point, the 1/4 sec. cor. of secs. 2 and 35, Tps. 25 and 26 N., R. 27 E., bears East, 34.05 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T26N R27E 1/4 S35 S2 T25N 2004.

This cor. now functions as the 1/4 sec. cor. of sec. 35 only, T. 26 N., R. 27 E., remark the brass cap to read

T 26 N R 27 E
1/4 S 35

T 25 N R 27 E
2008
2004

From this same cor. point, the cor. of secs. 2, 3, 34 and 35, Tps. 25 and 26 N., R. 27 E., bears West 5.95 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T26N R27E S34 S35 S3 S2 T25N 2004.

This cor. now functions as the cor. of secs. 34 and 35 only, T. 26 N., R. 27 E., remark the brass cap to read

T 26 N R 27 E
S 34 S 35

S 3
T 25 N R 27 E
2008
2004

Land, rolling.
Soil, sandy, gravelly clay with sandstone outcrops.
Timber, scattered ponderosa pine, piñon, juniper and Gambel oak;
undergrowth, brush and native grasses.

Point for the 1/4 sec. cor of sec. 2 only, at midpoint on the N. bdy. of sec. 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 N R 27 E

1/4 S 2
T 25 N R 27 E
2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this cor. point, the cor. of secs. 35 and 36 only,
T. 26 N., R. 27 E., bears East, 34.025 chs. dist.

From this same cor. point, the 1/4 sec. cor. of sec. 35 only,
T. 26 N., R. 27 E., bears West, 5.975 chs. dist.

From the stan. cor. of secs. 33 and 34, on the Sixth Standard
Parallel North (south boundary), monumented with an iron post,
2 ins. diam., firmly set, projecting 10 ins. above ground, with
brass cap mkd. SC T25N R27E S33 S34 2003 1920.

Add the marks 2008 to the brass cap.

Cor. is located 50 lks. S. of a trail road, bears N. 45° E. and
S. 45° W.

North, bet. secs. 33 and 34.

Over rolling land.

2.25 Graded road, 15 ft. wide, bears N. 50° E. and S. 50° W.

40.00 Point for the 1/4 sec. cor. of secs. 33 and 34.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented
in a drill hole in sandstone bedrock, with top mkd.

T 25 N R 27 E
1/4
S 33 | S 34

2008

Deposit a magnet, in a white plastic case, in the drill hole,
beneath the brass tablet.

60.15 Trail road, bears N. 55° E. and S. 55° W.

80.00 Point for the cor. of secs. 27, 28, 33 and 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T 25 N R 27 E
S 28 | S 27

S 33 | S 34

2008

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy, gravelly clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35. N. 89°59' W., bet. secs. 27 and 34. Over rolling land.</p>
15.20	Trail road, bears S. 15° E. and N. 15° W.
24.20	Trail road, bears S. 20° E. and N. 20° W.
27.50	Graded road, 15 ft. wide, bears N. 45° E. and S. 45° W.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 25 N R 27 E S 27 1/4 ——— S 34 2008</p>
	<p>from which</p> <p style="padding-left: 40px;">The SW cor. of a stucco house, 20 x 17 ft., bears N. 77 1/2° E., 1.46 chs. dist., the long side bears N. 20° E.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
49.70	Trail road, bears N. 70° E. and S. 70° W.
80.00	The cor. of secs. 27, 28, 33 and 34. Land, rolling. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.
	<hr/> <p>North, bet. secs. 27 and 28. Over rolling and broken land.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E 1/4 S 28 S 27</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 21, 22, 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E S 21 S 22 S 28 S 27</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27. N. 89°59' W., bet. secs. 22 and 27. Over rolling and broken land.</p>
22.90	Trail road, bears N. 20° E. and S. 20° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E S 22 1/4 ——— S 27</p> <p style="text-align: center;">2008</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 21, 22, 27 and 28. Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.
	North, bet. secs. 21 and 22. Over rolling land.
33.50	Underground gas pipeline, bears N. 60° E. and S. 60° W.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in sandstone bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.
	T 25 N R 27 E 1/4 S 21 S 22 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
42.60	Asphalt paved road, 16 ft. wide, bears N. 85° E. and S. 85° W.
80.00	Point for the cor. of secs. 15, 16, 21 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to sandstone bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.
	T 25 N R 27 E S 16 S 15 S 21 S 22 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23. N. 89°59' W., bet. secs. 15 and 22. Over rolling and broken land.</p>
33.10	Trail road, bears N. 25° E. and S. 25° W.
35.05	Trail road, bears S. 35° E. and N. 35° W.
40.01	Point for the 1/4 sec. cor. of secs. 15 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in sandstone bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.
	<p>T 25 N R 27 E S 15 1/4 ——— S 22 2008</p>
80.02	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 15, 16, 21 and 22. Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>North, bet. secs. 15 and 16. Over rolling and broken land.</p>
23.95	Trail road, bears N. 80° E. and S. 80° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 25 N R 27 E 1/4 S 16 S 15 2008 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 9, 10, 15 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 27 E S 9 S 10 S 16 S 15 2008 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.
	<hr/> From the cor. of secs. 10, 11, 14 and 15. N. 89°59' W., bet. secs. 10 and 15. Over rolling and broken land.
40.01	Point for the 1/4 sec. cor. of secs. 10 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 27 E S 10 1/4 ——— S 15 2008 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.02	The cor. of secs. 9, 10, 15 and 16.

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>North, bet. secs. 9 and 10.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E 1/4 S 9 S 10</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 3, 4, 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E S 4 S 3 S 9 S 10</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, scattered ponderosa pine, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 89°59' W., bet. secs. 3 and 10.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E S 3 1/4 ——— S 10</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, scattered ponderosa pine, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>North, bet. secs. 3 and 4.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E 1/4 S 4 S 3</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located at the base of the upper most sandstone ledge, 5 ft. high, bears N. 10° E. and S. 10° W, on the S. rim of Wide Ruin Wash canyon.</p> <p>Thence across the canyon.</p>
57.40	<p>N. rim of Wide Ruin Wash canyon, top of sandstone ledge, bears N. 20° E. and S. 20° W.</p>
71.60	<p>From this point, the center of the concrete casing of Tudecoz Spring Well, No. 17-2-11, bears West, 1.78 chs. dist., 7 ft. square, projecting 12 ins. above ground, mkd. 8-21-62 PHS Co.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS

83.18

Point for the closing cor. of secs. 3 and 4, at intersection with the S. bdy. of sec. 34, T. 26 N., R. 27 E.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.

$$\begin{array}{r} T\ 26\ N\ R\ 27\ E \\ \quad S\ 34 \\ \hline S\ 4\ | \ S\ 3 \\ T\ 25\ N\ R\ 27\ E \\ \quad CC \end{array}$$

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located in a bladed trail road to a residential area, 15 ft. wide, bears S. 45° E. and N. 45° W.

From this cor. point, the 1/4 sec. cor. of secs. 3 and 34, Tps. 25 and 26 N., R. 27 E., bears East, 34.06 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. T26N R27E 1/4 S34 S3 T25N 2004.

This cor. now functions as the 1/4 sec. cor. of sec. 34 only, T. 26 N., R. 27 E., remark the brass cap to read

$$\begin{array}{r} T\ 26\ N\ R\ 27\ E \\ \quad 1/4\ S\ 34 \\ \hline T\ 25\ N\ R\ 27\ E \\ \quad 2008 \\ \quad 2004 \end{array}$$

From this same cor. point, the cor. of secs. 3, 4, 33 and 34, Tps. 25 and 26 N., R. 27 E., bears West 5.94 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T26N R27E S33 S34 S4 S3 T25N 2004.

This cor. now functions as the cor. of secs. 33 and 34 only, T. 26 N., R. 27 E., remark the brass cap to read

$$\begin{array}{r} T\ 26\ N\ R\ 27\ E \\ \quad S\ 33\ | \ S\ 34 \\ \hline \quad S\ 4 \\ T\ 25\ N\ R\ 27\ E \\ \quad 2008 \\ \quad 2004 \end{array}$$

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS

Land, rolling and broken.
Soil, sandy, gravelly clay with sandstone outcrops.
Timber, scattered ponderosa pine, piñon, juniper and Gambel oak;
undergrowth, brush and native grasses.

Point for the 1/4 sec. cor of sec. 3 only, at midpoint on the N.
bdy. of sec. 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T 26 N R 27 E

1/4 S 3

T 25 N R 27 E

2008

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

From this cor. point, the cor. of secs. 34 and 35 only,
T. 26 N., R. 27 E., bears East, 34.055 chs. dist.

From this same cor. point, the 1/4 sec. cor. of sec. 34 only,
T. 26 N., R. 27 E., bears West, 5.945 chs. dist.

From the stan. cor. of secs. 32 and 33, on the Sixth Standard
Parallel North (south boundary), monumented with an iron post,
2 ins. diam., firmly set, projecting 8 ins. above ground, with
brass cap mkd. SC T25N R27E S32 S33 1920 2003.

Add the marks 2008 to the brass cap.

N. 0°01' W., bet. secs. 32 and 33.

Over rolling land.

40.00

Point for the 1/4 sec. cor. of secs. 32 and 33.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T 25 N R 27 E

1/4

S 32 | S 33

2008

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
80.00	<p>Point for the cor. of secs. 28, 29, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 25 N</td> <td>R 27 E</td> </tr> <tr> <td>S 29</td> <td>S 28</td> </tr> <tr> <td>S 32</td> <td>S 33</td> </tr> </table> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 89°59' W., bet. secs. 28 and 33.</p> <p>Over rolling land.</p>	T 25 N	R 27 E	S 29	S 28	S 32	S 33		
T 25 N	R 27 E								
S 29	S 28								
S 32	S 33								
40.05	<p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 25 N</td> <td>R 27 E</td> </tr> <tr> <td></td> <td>S 28</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 33</td> </tr> </table> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 25 N	R 27 E		S 28	1/4	—		S 33
T 25 N	R 27 E								
	S 28								
1/4	—								
	S 33								
80.10	<p>The cor. of secs. 28, 29, 32 and 33.</p> <p>Land, rolling. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 28 and 29.</p> <p>Over rolling and broken land.</p>								

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E 1/4 S 29 S 28</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 20, 21, 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E S 20 S 21 S 29 S 28</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28. N. 89°59' W., bet. secs. 21 and 28. Over rolling and broken land.</p>
40.05	<p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E S 21 1/4 ——— S 28</p> <p style="text-align: center;">2008</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.10	The cor. of secs. 20, 21, 28 and 29. Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses.

	N. 0°01' W., bet. secs. 20 and 21. Over rolling and broken land.
1.60	Underground gas pipeline, bears N. 70° E. and S. 70° W.
9.75	Asphalt paved road, 16 ft. wide, bears N. 60° E. and S. 60° W.
14.24	From this point, the SE cor. of a wood frame house, 38 x 24 ft., bears West, 15 lks. dist., the long side bears N. 2° E.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 27 E 1/4 S 20 S 21 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
79.20	Wash, 15 ft. wide, 4 ft. deep, drains S. 30° W.
80.00	Point for the cor. of secs. 16, 17, 20 and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 27 E S 17 S 16 S 20 S 21 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22. N. 89°59' W., bet. secs. 16 and 21. Over rolling and broken land.</p>
40.05	<p>Point for the 1/4 sec. cor. of secs. 16 and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to sandstone bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E S 16 1/4 ——— S 21 2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.10	<p>The cor. of secs. 16, 17, 20 and 21. Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, scattered ponderosa pine, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 16 and 17. Over rolling and broken land.</p>
18.80	<p>Trail road, bears N. 50° E. and S. 50° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to sandstone bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E 1/4 S 17 S 16 2008</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 8, 9, 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 25 N</td> <td>R 27 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 8</td> <td>S 9</td> </tr> <tr> <td style="border-right: 1px solid black;">S 17</td> <td>S 16</td> </tr> </table> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, scattered ponderosa pine, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 89°59' W., bet. secs. 9 and 16.</p> <p>Over rolling and broken land.</p>	T 25 N	R 27 E	S 8	S 9	S 17	S 16		
T 25 N	R 27 E								
S 8	S 9								
S 17	S 16								
40.05	<p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in sandstone bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 25 N</td> <td>R 27 E</td> </tr> <tr> <td></td> <td>S 9</td> </tr> <tr> <td>1/4</td> <td style="border-top: 1px solid black;">———</td> </tr> <tr> <td></td> <td>S 16</td> </tr> </table> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 25 N	R 27 E		S 9	1/4	———		S 16
T 25 N	R 27 E								
	S 9								
1/4	———								
	S 16								
80.10	<p>The cor. of secs. 8, 9, 16 and 17.</p>								

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, scattered ponderosa pine, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 8 and 9.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 27 E 1/4 S 8 S 9</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 4, 5, 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 27 E S 5 S 4 S 8 S 9</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 89°59' W., bet. secs. 4 and 9.</p> <p>Over rolling land.</p>
40.05	<p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E S 4 1/4 ——— S 9</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.10	<p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Land, rolling. Soil, sandy, gravelly clay with sandstone outcrops. Timber, scattered ponderosa pine, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 4 and 5.</p> <p>Over rolling and broken land.</p>
4.70	<p>S. rim of Wide Ruin Wash canyon, top of a sandstone ledge, bears N. 50° E. and S. 50° W., thence across the canyon.</p>
12.40	<p>N. rim of Wide Ruin Wash canyon, top of a sandstone ledge, bears N. 65° E. and S. 65° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E 1/4 S 5 S 4</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
51.90	<p>Navajo Route 203, a graded road, 25 ft. wide, bears N. 55° E. and S. 55° W.</p>
55.85	<p>Trail road, bears N. 85° E. and S. 85° W.</p>
83.16	<p>Point for the closing cor. of secs. 4 and 5, at intersection with the S. bdy. of sec. 33, T. 26 N., R. 27 E.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.

T 26 N R 27 E
S 33

S 5 | S 4
T 25 N R 27 E
CC

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the 1/4 sec. cor. of secs. 4 and 33, Tps. 25 and 26 N., R. 27 E., bears East, 34.17 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T26N R27E 1/4 S33 S4 T25N 2004.

This cor. now functions as the 1/4 sec. cor. of sec. 33 only, T. 26 N., R. 27 E., remark the brass cap to read

T 26 N R 27 E
1/4 S 33

T 25 N R 27 E
2008
2004

From this same cor. point, the cor. of secs. 4, 5, 32 and 33, Tps. 25 and 26 N., R. 27 E., bears West 5.83 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T26N R27E S32 S33 S5 S4 T25N 2004.

This cor. now functions as the cor. of secs. 32 and 33 only, T. 26 N., R. 27 E., remark the brass cap to read

T 26 N R 27 E
S 32 | S 33

S 5
T 25 N R 27 E
2008
2004

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS

Land, rolling and broken.
Soil, sandy, gravelly clay with sandstone outcrops.
Timber, scattered ponderosa pine, piñon, juniper and Gambel oak;
undergrowth, brush and native grasses.

Point for the 1/4 sec. cor of sec. 4 only, at midpoint on the N.
bdy. of sec. 4.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T 26 N R 27 E

1/4 S 4

T 25 N R 27 E

2008

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

From this cor. point, the cor. of secs. 33 and 34 only,
T. 26 N., R. 27 E., bears East, 34.155 chs. dist.

From this same cor. point, the 1/4 sec. cor. of sec. 33 only,
T. 26 N., R. 27 E., bears West, 5.885 chs. dist.

From the stan. cor. of secs. 31 and 32, on the Sixth Standard
Parallel North (south boundary), monumented with an iron post,
2 ins. diam., firmly set, projecting 10 ins. above ground, with
brass cap mkd. SC T25N R27E S31 S32 1920 2003.

from which the remaining 1920 bearing tree

A forked juniper, 17 ins. diam., at base, bears
N. 45 1/4° E., 39 lks. dist., mkd. T25N SC R27E BT on
partially healed blaze.

Add the marks 2008 to the brass cap.

N. 0°02' W., bet. secs. 31 and 32.

Over rolling and broken land.

40.00

Point for the 1/4 sec. cor. of secs. 31 and 32.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
18 ins. in sandstone bedrock, in a supporting mound of stone,
3 ft. base, to top, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 25 N R 27 E 1/4 S 31 S 32 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 29, 30, 31 and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 27 E S 30 S 29 S 31 S 32 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses.
	From the cor. of secs. 28, 29, 32 and 33.
	N. 89°59' W., bet. secs. 29 and 32.
	Over rolling land.
1.40	Trail road, bears N. 10° E. and S. 10° W.
10.90	Trail road, bears S. 55° E. and N. 55° W.
12.95	Trail road, bears N. 20° E. and S. 20° W.
39.99	Point for the 1/4 sec. cor. of secs. 29 and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 27 E S 29 1/4 ——— S 32 2008

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
79.98	The cor. of secs. 29, 30, 31 and 32. Land, rolling. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses.
	<hr/>
	S. 89°59' W., bet. secs. 30 and 31. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 27 E S 30 1/4 ——— S 31 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
68.60	Power line, bears N. 55° E. and S. 55° W.
76.00	Trail road, bears N. 70° E. and S. 70° W.
79.70	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T25N R26E R27E S25 S30 S36 S31 2002. Add the marks 2008 to the brass cap. Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses.
	<hr/>
	From the cor. of secs. 29, 30, 31 and 32. N. 0°02' W., bet. secs. 29 and 30. Over rolling and broken land.

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
15.65	Trail road, bears S. 75° E. and N. 75° W.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 27 E 1/4 S 30 S 29 2008 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
57.50	Underground gas pipeline, bears N. 75° E. and S. 75° W.
60.40	Asphalt paved road, 16 ft. wide, bears N. 75° E. and S. 75° W.
68.95	Graded road, 15 ft. wide, bears N. 60° E. and S. 60° W.
80.00	Point for the cor. of secs. 19, 20, 29 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 27 E S 19 S 20 S 30 S 29 2008 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling. Soil, sandy, gravelly clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.
	From the cor. of secs. 20, 21, 28 and 29. N. 89°59' W., bet. secs. 20 and 29. Over rolling land.
5.30	Underground gas pipeline, bears N. 75° E. and S. 75° W.
17.55	Asphalt paved road, 16 ft. wide, bears N. 60° E. and S. 60° W.
39.99	Point for the 1/4 sec. cor of secs. 20 and 29.

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E S 20 1/4 ——— S 29</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
67.20	Graded road, 15 ft. wide, bears N. 25° E. and S. 25° W.
79.98	The cor. of secs. 19, 20, 29 and 30.
	<p>Land, rolling. Soil, sandy, gravelly clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>S. 89°57' W., bet. secs. 19 and 30.</p> <p>Over rolling and broken land.</p>
17.20	Trail road, bears North and South.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in sandstone bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E S 19 1/4 ——— S 30</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
47.80	E. rim of Wide Ruin Wash canyon, top of a sandstone ledge, bears N. 25° E. and S. 25° W, thence across the canyon.
58.30	W. rim of Wide Ruin Wash canyon, top of a sandstone ledge, bears N. 45° E. and S. 45° W.

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.52	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T25N R26E R27E S24 S19 S25 S30 2002.</p> <p>Add the marks 2008 to the brass cap.</p> <p>Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30. N. 0°02' W., bet. secs. 19 and 20. Over rolling land.</p>
3.85	Trail road, bears East and West.
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 27 E 1/4 S 19 S 20</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
57.70	S. rim of Wide Ruin Wash canyon, top of a sandstone ledge, bears N. 85° E. and S. 85° W., thence across the canyon.
65.60	N. rim of Wide Ruin Wash canyon, top of a sandstone ledge, bears N. 75° E. and S. 75° W.
80.00	<p>Point for the cor. of secs. 17, 18, 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 27 E S 18 S 17 S 19 S 20</p> <p>2008</p> </div>

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89°59' W., bet. secs. 17 and 20.</p> <p>Over rolling land.</p>
14.50	Trail road, bears N. 40° E. and S. 40° W.
39.99	Point for the 1/4 sec. cor. of secs. 17 and 20.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E S 17 1/4 ——— S 20</p> <p style="text-align: center;">2008</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
44.00	E. rim of Wide Ruin Wash canyon, top of a sandstone ledge, bears N. 45° E. and S. 45° W., thence across the canyon.
61.80	W. rim of Wide Ruin Wash canyon, top of a sandstone ledge, bears N. 20° E. and S. 20° W.
79.98	The cor. of secs. 17, 18, 19 and 20.
	<p>Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>S. 89°59' W., bet. secs. 18 and 19.</p> <p>Over rolling land.</p>
40.00	Point for the 1/4 sec. cor. of secs. 18 and 19.

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E S 18 1/4 ——— S 19</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.41	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T25N R26E R27E S13 S18 S24 S19 2002.</p> <p>Add the marks 2008 to the brass cap.</p> <p>Land, rolling. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20. N. 0°02' W., bet. secs. 17 and 18. Over rolling land.</p>
36.70	Trail road, bears N. 60° E. and S. 60° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E 1/4 S 18 S 17</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 7, 8, 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 25 N R 27 E S 7 S 8 S 18 S 17 2008 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.
	<hr/> From the cor. of secs. 8, 9, 16 and 17. N. 89°59' W., bet. secs. 8 and 17. Over rolling and broken land.
15.00	E. rim of Wide Ruin Wash canyon, top of a sandstone ledge, bears N. 60° E. and S. 60° W., thence across the canyon.
26.20	W. rim of Wide Ruin Wash canyon, top of a sandstone ledge, bears N. 15° E. and S. 15° W.
39.99	Point for the 1/4 sec. cor. of secs. 8 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 27 E S 8 1/4 ——— S 17 2008 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
79.98	The cor. of secs. 7, 8, 17 and 18. Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.
	<hr/> S. 89°59' W., bet. secs. 7 and 18.

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
36.90	Underground water pipeline, bears N. 20° E. and S. 20° W.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. below the surface of the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 27 E S 7 1/4 ——— S 18 2008 </div> from which A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 76°00' E., 100.0 ft. dist., with brass cap mkd. RM T25N R27E 1/4 S7 100.0 FT TO COR. 2008 and an arrow pointing to the cor. Deposit a magnet in white plastic case beneath the stainless steel post. Set a steel fence post nearby. A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 76°00' W., 125.0 ft. dist., with brass cap mkd. RM T25N R27E 1/4 S18 125.0 FT TO COR. 2008 and an arrow pointing to the cor. Deposit a magnet in white plastic case beneath the stainless steel post. Set a steel fence post nearby. Deposit a magnet, in a white plastic case, at the base of the stainless steel post at the 1/4 sec. cor. Cor. is located on the E. edge of Navajo Route 203, a graded road, 20 ft. wide, bears N. 20° E. and S. 20° W.
79.26	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T25N R26E R27E S12 S7 S13 S18 2002. Add the marks 2008 to the brass cap.

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18. N. 0°02' W., bet. secs. 7 and 8. Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E 1/4 S 7 S 8 2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
55.50	<p>Navajo Route 203, a graded road, 20 ft. wide, bears N. 45° E. and S. 45° W.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 7 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E S 6 S 5 S 7 S 8 2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9. N. 89°59' W., bet. secs. 5 and 8.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling and broken land.
1.70	E. rim of Wide Ruin Wash canyon, top of a sandstone ledge, bears N. 5° E. and S. 5° W., thence across the canyon.
8.60	W. rim of Wide Ruin Wash canyon, top of a sandstone ledge, bears N. 20° E. and S. 20° W.
39.99	Point for the 1/4 sec. cor. of secs. 5 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> T 25 N R 27 E S 5 1/4 ——— S 8 2008 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
58.00	Navajo Route 203, a graded road, 20 ft. wide, bears N. 40° E. and S. 40° W.
79.98	The cor. of secs. 5, 6, 7 and 8. Land, rolling and broken. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.
	————— S. 89°53' W., bet. secs. 6 and 7.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 7. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 27 E S 6 1/4 ——— S 7 2008 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
48.75	Trail road, bears N. 50° E. and S. 50° W.
79.14	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T25N R26E R27E S1 S6 S12 S7 2002.</p> <p>Add the marks 2008 to the brass cap.</p> <p>Land, rolling. Soil, sandy, gravelly clay with sandstone outcrops. Timber, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°02' W., bet. secs. 5 and 6.</p> <p>Over rolling land.</p>
24.40	Trail road, bears S. 80° E. and N. 80° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E 1/4 S 6 S 5</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
78.60	Trail road, bears S. 55° E. and N. 55° W.
79.90	Trail road, bears N. 75° E. and S. 75° W.
83.14	<p>Point for the closing cor. of secs. 5 and 6, at intersection with the S. bdy. of sec. 32, T. 26 N., R. 27 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 26 N R 27 E
S 32
 S 6 | S 5
 T 25 N R 27 E
 CC

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the 1/4 sec. cor. of secs. 5 and 32, Tps. 25 and 26 N., R. 27 E., bears East, 34.16 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T26N R27E 1/4 S32 S5 T25N 2004.

This cor. now functions as the 1/4 sec. cor. of sec. 32 only, T. 26 N., R. 27 E., remark the brass cap to read

T 26 N R 27 E
1/4 S 32
 T 25 N R 27 E
 2008
 2004

From this same cor. point, the cor. of secs. 5, 6, 31 and 32, Tps. 25 and 26 N., R. 27 E., bears West, 5.84 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T26N R27E S31 S32 S6 S5 T25N 2004.

This cor. now functions as the cor. of secs. 31 and 32 only, T. 26 N., R. 27 E., remark the brass cap to read

T 26 N R 27 E
S 31 | S 32
 S 6
 T 25 N R 27 E
 2008
 2004

Land, rolling.
 Soil, sandy, gravelly clay with sandstone outcrops.
 Timber, piñon, juniper and Gambel oak; undergrowth, brush and native grasses.

Point for the 1/4 sec. cor of sec. 5 only, at midpoint on the N. bdy. of sec. 5.

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T 26 N R 27 E

1/4 S 5

T 25 N R 27 E

2008

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

From this cor. point, the cor. of secs. 32 and 33 only,
T. 26 N., R. 27 E., bears East, 34.165 chs. dist.

From this same cor. point, the 1/4 sec. cor. of sec. 32 only,
T. 26 N., R. 27 E., bears West, 5.835 chs. dist.

Point for the 1/4 sec. cor of sec. 6 only, at 40.00 chs. in
westing from the closing cor. of secs. 5 and 6, on the N. bdy.
of sec. 6.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T 26 N R 27 E

1/4 S 6

T 25 N R 27 E

2008

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

From this cor. point, the cor. of secs. 31 and 32 only,
T. 26 N., R. 27 E., bears East, 34.16 chs. dist.

From this same cor. point, the 1/4 sec. cor. of secs. 6 and 31,
Tps. 25 and 26 N., R. 27 E., bears West, 5.84 chs. dist.,
monumented with a stainless steel post, 2 1/2 ins. diam., firmly
set, projecting 4 ins. above ground, with brass cap mkd. T26N
R27E 1/4 S31 S6 T25N 2004.

This cor. now functions as the 1/4 sec. cor. of sec. 31 only,
T. 26 N., R. 27 E., remark the brass cap to read

**Survey of the Subdivisional Lines,
T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 26 N R 27 E
1/4 S 31

T 25 N R 27 E
2008
2004

GENERAL DESCRIPTION

The area surveyed is within the Navajo Indian Reservation, approximately 4 miles northeast of Klagetoh, Arizona. The terrain is rolling and broken. The drainage is southwesterly with Wide Ruin Wash as the main drainage.

The elevation varies from 6500 to 7400 feet above sea level. The soil is mostly sandy, gravelly clay with sandstone outcrops throughout the township. The timber consist of ponderosa pine, piñon, juniper and Gambel oak with an undergrowth of various brush and native grasses.

The main access to the area is provided by Navajo Routes 203 and 28, graded roads, and an asphalt paved road paralleling a pipeline entering the township in the southwest portion from U. S. Highway 191. There are several permanent residents along these roads with livestock pastures scattered throughout the township. There is no evidence of any current mining activity.

The mean magnetic declination of 10 3/4° E. was derived from the computer program GEOMAGIX utilizing the World Magnetic Model for Epoch 2005 for the dates of survey.

CERTIFICATE OF SURVEY

I, Leonard R. Sandoval, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing the date of the 14th day of April, 2008, I have dependently resurveyed a portion of the south boundary, T. 26 N., R. 28 E., and dependently resurveyed the east boundary and surveyed the subdivisional lines, T. 25 N., R. 27 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in the specific manner described in the foregoing field notes.

April 30, 2009
(Date)

Leonard R. Sandoval
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the south boundary, T. 26 N., R. 28 E., and the dependent resurvey of the east boundary and the survey of the subdivisional lines, T. 25 N., R. 27 E., Gila and Salt River Meridian, in the State of Arizona, executed by Leonard R. Sandoval, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

6/3/2009
(Date)

Stephen K. Hansen
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 26 N., R. 28 E. and T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____~~
~~(Date)~~

~~_____~~
~~(Chief Cadastral Surveyor of Arizona)~~