

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF A PORTION
OF THE GILA AND SALT RIVER BASE LINE
THROUGH RANGES 16 AND 17 EAST (NORTH BOUNDARY)
AND
THE SURVEY OF THE SOUTH AND EAST BOUNDARIES
AND THE SUBDIVISIONAL LINES
TOWNSHIP 1 SOUTH, RANGE 17 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

Joe R. Salazar, Cadastral Surveyor

Under Special Instructions dated May 21, 2001, approved May 21, 2001, which provided for the surveys included under Group No. 873, and assignment instructions dated May 21, 2001 and February 26, 2009.

Survey commenced July 25, 2001

Survey completed March 12, 2009

INDEX DIAGRAM

TOWNSHIP 1 SOUTH RANGE 17 EAST
 GILA AND SALT RIVER MERIDIAN, ARIZONA

7	6	6	5	5	4
67 6 65	66 5 53	53 4 44	45 3 35	36 2 26	27 1 17
64 7 63	64 8 51	52 9 42	44 10 33	34 11 24	25 12 16
62 18 60	61 17 50	50 16 41	42 15 32	33 14 23	24 13 16
60 19 58	59 20 48	49 21 39	40 22 31	31 23 21	22 24 15
57 30 56	57 29 47	48 28 38	39 27 29	30 26 20	21 25 14
55 31 54 12	55 32 46 12	46 33 37 11	38 34 28 10	28 35 19 9	20 36 13 8

T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the Gila and Salt River Base Line through Ranges 16 and 17 East (north boundary) and the survey of the south and east boundaries and the subdivisional lines, Township 1 South, Range 17 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

H. L. Baldwin, Topographer, surveyed the Gila and Salt River Base Line through Ranges 16, 17, and 18 East, within the White Mountain Indian Reservation (San Carlos Indian Reservation), in 1915.

W. William Foster surveyed the west boundary, concurrently under this same group, in 2001.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated May 21, 2001, for Group Number 873, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5800 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from first order United States Coast and Geodetic Survey triangulation station CUTTER RESET 1973, as published by the National Geodetic Survey, NAD 83 (1992). The geographic position of the Corner of Townships 1 and 2 South, Ranges 17 and 18 East, is as follows:

Latitude: 33°17'42.47" N. Longitude: 110°33'08.71" W.

The mean magnetic declination is 11 1/2° E.

**Dependent Resurvey of a Portion of the Gila and Salt River
Base Line through Ranges 16 and 17 East (North Boundary),
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

Restoring the survey executed by
H. L. Baldwin, in 1915

**Dependent Resurvey of a Portion of the Gila and Salt River
Base Line through Ranges 16 and 17 East (North Boundary),
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Beginning at the stan. cor. of secs. 34 and 35, T. 1 N., R. 17 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd. SC T1N R17E S34 S35 1915, witnessed with a mound of stone, 4 ft. base, 2 ft. high, N. of cor.</p>
	<p>Add the marks 2001 to the brass cap.</p>
	<p>S. 89°58' W., along the S. bdy. of sec. 34.</p>
	<p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
2.20	<p>Fence line, 9 strand barbed wire, bears S. 45° E. and N. 45° W.</p>
16.00	<p>Point for the closing cor. of Tps. 1 S., Rgs. 17 and 18 E., hereinafter described.</p>
40.02	<p>The stan. 1/4 sec. cor. of sec. 34, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above the ground, with brass cap mkd. SC 1/4 S34 1915.</p>
	<p>Add the marks T1N R17E 2001 to the brass cap.</p>
	<p>Raise a supporting mound of stone, 3 ft. base, to top of brass cap.</p>
	<p>Cor. is located on the W. slope of a ridge, bears N. and S.</p>
	<p>_____</p> <p>West, beginning new measurement.</p>
15.975	<p>Point for the 1/4 sec. cor. of sec. 1 only, T. 1 S., R. 17 E., hereinafter described.</p>
39.99	<p>The stan. cor. of secs. 33 and 34, monumented with the remains of the supporting mound of stone, 4 ft. base, 18 ins. high.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">SC</p>
	<p style="text-align: center;">T 1 N R 17 E</p>
	<p style="text-align: center;">S 33 S 34</p>
	<p style="text-align: center;">2001</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Cor. is located on the N. slope of a ridge, bears E. and W.</p>

**Dependent Resurvey of a Portion of the Gila and Salt River
Base Line through Ranges 16 and 17 East (North Boundary),
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<hr/> <p>West, along the S. bdy. of sec. 33.</p>
	<p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
15.98	<p>Point for the closing cor. of secs. 1 and 2, T. 1 S., R. 17 E., hereinafter described.</p>
40.02	<p>The stan. 1/4 sec. cor. of sec. 33, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. SC 1/4 S33 1915, witnessed with a scattered mound of stone, N. of cor.</p>
	<p>Add the marks T1N R17E 2001 to the brass cap.</p>
	<p>Rebuild mound of stone 3 ft. base, 2 ft. high, N. of cor.</p> <hr/>
	<p>S. 89°58' W., beginning new measurement.</p>
15.96	<p>Point for the 1/4 sec. cor. of sec. 2 only, T. 1 S., R. 17 E., hereinafter described.</p>
40.10	<p>The stan. cor. of secs. 32 and 33, monumented with an iron post, 3 ins. diam., firmly set, projecting 17 ins. above the ground, with brass cap mkd. SC T1N R17E S32 S33 1915, witnessed with a scattered mound of stone, 3 ft. base, 1 ft. high, N. of cor.</p>
	<p>Add the marks 2001 to the brass cap.</p>
	<p>Rebuild mound of stone 3 ft. base, 2 ft. high, N. of cor.</p>
	<p>Cor. is located on the E. slope of a ridge, bears N. and S.</p> <hr/>
	<p>S. 89°58' W., along the S. bdy. of sec. 32.</p>
	<p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
15.86	<p>Point for the closing cor. of secs. 2 and 3, T. 1 S., R. 17 E., hereinafter described.</p>
39.70	<p>Wash, drains S. 10° W.</p>
40.00	<p>The stan. 1/4 sec. cor. of sec. 32, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. SC 1/4 S32 1915.</p>
	<p>Add the marks T1N R17E 2001 to the brass cap.</p>
	<p>Raise a supporting mound of stone, 3 ft. base to top of brass cap.</p>

**Dependent Resurvey of a Portion of the Gila and Salt River
Base Line through Ranges 16 and 17 East (North Boundary),
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<hr/> <p>S. 89°59' W., beginning new measurement.</p>
0.10	Wash, drains S. 10° W.
15.865	Point for the 1/4 sec. cor. of sec. 3 only, T. 1 S., R. 17 E., hereinafter described.
40.01	<p>The stan. cor. of secs. 31 and 32, monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above the ground, in a mound of stone, 2 1/2 ft. base to top, with brass cap mkd. SC T1N R17E S31 S32 1915.</p> <p>Add the marks 2009 to the brass cap.</p> <hr/>
	S. 89°57' W., along the S. bdy. of sec. 31.
	Over rocky, rolling terrain, through scrub oak and mesquite.
15.86	Point for the closing cor. of secs. 3 and 4, T. 1 S., R. 17 E., hereinafter described.
39.97	<p>The stan. 1/4 sec. cor. of sec. 31, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. SC 1/4 S31 1915.</p> <p>Add the marks T1N R17E 2009 to the brass cap.</p> <hr/>
	S. 89°57' W., beginning new measurement.
15.89	Point for the 1/4 sec. cor. of sec. 4 only, T. 1 S., R. 17 E., hereinafter described.
40.06	<p>The stan. cor. of Tps. 1 N., Rgs. 16 and 17 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 16 ins. above the ground, with brass cap mkd. SC T1N R16E R17E S36 S31 1915.</p> <p>Add the marks 2001 to the brass cap.</p> <p>Cor. is located on the SW slope of a ridge, bears NE and SW.</p> <hr/>
	S. 89°59' W., along the S. bdy. of sec. 36.
	Over rocky, rolling terrain, through scrub oak and mesquite.
15.83	Point for the closing cor. of secs. 4 and 5, T. 1 S., R. 17 E., hereinafter described.

**Dependent Resurvey of a Portion of the Gila and Salt River
Base Line through Ranges 16 and 17 East (North Boundary),
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.04	<p>The stan. 1/4 sec. cor. of sec. 36, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. SC 1/4 S36 1915.</p> <p>Add the marks T1N R16E 2001 to the brass cap.</p> <hr/>
	<p>S. 89°57' W., beginning new measurement.</p>
15.79	<p>Point for the 1/4 sec. cor. of sec. 5 only, T. 1 S., R. 17 E., hereinafter described.</p>
40.04	<p>The stan. cor. of secs. 35 and 36, monumented with an iron post, 3 ins. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd. SC T1N R16E S35 S36 1915, witnessed with a mound of stone 3 ft. base 1 ft. high N. of cor.</p> <p>Add the marks 2001 to the brass cap.</p> <hr/>
	<p>S. 89°58' W., along the S. bdy. of sec. 35.</p>
	<p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
15.75	<p>Point for the closing cor. of secs. 5 and 6, T. 1 S., R. 17 E., hereinafter described.</p>
40.00	<p>The stan. 1/4 sec. cor. of sec. 35, monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd. SC 1/4 S35 1915, witnessed with a scattered mound of stone, N. of cor.</p> <p>Add the marks T1N R16E 2001 to the brass cap.</p> <p>Rebuild mound of stone, 2 1/2 ft. base, 2 ft. high, N. of cor.</p> <hr/>
	<p>S. 89°58' W., beginning new measurement.</p>
15.75	<p>Point for the 1/4 sec. cor. of sec. 6 only, T. 1 S., R. 17 E., hereinafter described.</p>
40.02	<p>The stan. cor. of secs. 34 and 35, monumented with an iron post, 3 ins. diam., firmly set, projecting 16 ins. above the ground with brass cap marked and witnessed as described in the field notes of the Dependent Resurvey of a portion of the Gila and Salt River Base Line through Range 16 East, executed concurrently under this same group.</p> <hr/>
	<p style="text-align: center;">Survey of the South Boundary, T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona</p> <hr/>

**Survey of the South Boundary,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS

From the point for the cor. of Tps. 1 and 2 S., Rgs. 17 and 18 E., determined at 478.49 chs., North of the cor. of Tps. 2 and 3 S., Rgs. 17 and 18 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. T2S R17E R18E S36 S31 S1 S6 T3S 1915. Add the marks 2001 to the brass cap.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bed rock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.

	T 1 S	
R 17 E		R 18 E
S 36		S 31
S 1		S 6
	T 2 S	

2001

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 32°19' E., 339.5 ft. dist. with brass cap mkd. RM T1S R18E 339.5 FT TO COR S31 2009 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

S. 89°55' W., bet. secs. 1 and 36.

Over rocky, rolling terrain, through scrub oak and mesquite.

40.00

Point for the 1/4 sec. cor. of secs. 1 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 1 S	R 17 E
	S 36
1/4	—
	S 1
	T 2 S

2001

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

78.00

Graded road, 12 ft. wide, bears N. and S.

**Survey of the South Boundary,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS											
80.00	<p>Point for the cor. of secs. 1, 2, 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 1 S</td><td>R 17 E</td></tr> <tr><td>S 35</td><td>S 36</td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td>T 2 S</td><td></td></tr> </table> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>S. 89°55' W., bet. secs. 2 and 35.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>	T 1 S	R 17 E	S 35	S 36	S 2	S 1	T 2 S			
T 1 S	R 17 E										
S 35	S 36										
S 2	S 1										
T 2 S											
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 1 S</td><td>R 17 E</td></tr> <tr><td>S 35</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 2</td><td></td></tr> <tr><td>T 2 S</td><td>R 17 E</td></tr> </table> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>	T 1 S	R 17 E	S 35		1/4	—	S 2		T 2 S	R 17 E
T 1 S	R 17 E										
S 35											
1/4	—										
S 2											
T 2 S	R 17 E										
80.00	<p>Point for the cor. of secs. 2, 3, 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>										

**Survey of the South Boundary,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">T 1 S R 17 E S 34 S 35 <hr/>S 3 S 2 T 2 S R 17 E</p> <p align="center">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on the NNE slope of a ridge, bears SE and NW.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>S. 89°55' W., bet. secs. 3 and 34.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p> <p align="center">T 1 S R 17 E S 34 1/4 <hr/>S 3 T 2 S R 17 E</p> <p align="center">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 3, 4, 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p align="center">T 1 S R 17 E S 33 S 34 <hr/>S 4 S 3 T 2 S R 17 E</p> <p align="center">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the South Boundary,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>S. 89°55' W., bet. secs. 4 and 33.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
27.95	Center of Coolidge Dam road, a dilapidated paved road, 20 ft. wide, bears S. 45° E. and N. 45° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a supporting mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 17 E S 33 1/4 ——— S 4 T 2 S R 17 E</p> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on the N. slope of a ridge, bears E. and W.</p>
80.00	<p>Point for the cor. of secs. 4, 5, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 17 E S 32 S 33 S 5 S 4 T 2 S R 17 E</p> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>S. 89°55' W., bet. secs. 5 and 32.</p>

**Survey of the South Boundary,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p align="center"> T 1 S R 17 E S 32 1/4 ——— S 5 T 2 S R 17 E </p> <p align="center">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p align="center"> T 1 S R 17 E S 31 S 32 S 6 S 5 T 2 S R 17 E </p> <p align="center">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on the SW slope of a ridge, bears SSE and NNW.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>S. 89°55' W., bet. secs. 6 and 31.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a supporting mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>

**Survey of the South Boundary,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p align="center">T 1 S R 17 E S 31 1/4 ——— S 6 T 2 S R 17 E</p> <p align="center">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
78.70	<p>The cor. of Tps. 1 and 2 S., Rgs. 16 and 17 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, in a mound of stone, 3 ft. base, to top, marked and witnessed as described in the field notes of the survey of T. 1 S., R. 16 E., executed concurrently under this same group.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p align="center">Survey of the East Boundary, T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of Tps. 1 and 2 S., Rgs. 17 and 18 E., hereinbefore described.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
26.55	<p>Graded road, 12 ft. wide, bears SSE and NNW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p align="center">T 1 S 1/4 R 17 E R 18 E S 36 S 31</p> <p align="center">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 25, 30, 31 and 36.</p>

Survey of the East Boundary,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS																
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td></td><td style="text-align: center;">T 1 S</td><td></td></tr> <tr><td style="text-align: center;">R 17 E</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">R 18 E</td></tr> <tr><td style="text-align: center;">S 25</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">S 30</td></tr> <tr><td style="text-align: center;">S 36</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">S 31</td></tr> </table> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p>		T 1 S		R 17 E		R 18 E	S 25		S 30	S 36		S 31			
	T 1 S															
R 17 E		R 18 E														
S 25		S 30														
S 36		S 31														
40.00	<p>North, bet. secs. 25 and 30.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p> <p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td></td><td style="text-align: center;">T 1 S</td><td></td></tr> <tr><td style="text-align: center;">R 17 E</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">R 18 E</td></tr> <tr><td></td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td></td></tr> <tr><td></td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;">1/4</td><td></td></tr> <tr><td style="text-align: center;">S 25</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">S 30</td></tr> </table> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>		T 1 S		R 17 E		R 18 E					1/4		S 25		S 30
	T 1 S															
R 17 E		R 18 E														
	1/4															
S 25		S 30														
80.00	<p>Point for the cor. of secs. 19, 24, 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td></td><td style="text-align: center;">T 1 S</td><td></td></tr> <tr><td style="text-align: center;">R 17 E</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">R 18 E</td></tr> <tr><td style="text-align: center;">S 24</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">S 19</td></tr> <tr><td style="text-align: center;">S 25</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">S 30</td></tr> </table> <p style="text-align: center;">2001</p>		T 1 S		R 17 E		R 18 E	S 24		S 19	S 25		S 30			
	T 1 S															
R 17 E		R 18 E														
S 24		S 19														
S 25		S 30														

**Survey of the East Boundary,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr style="border: 0.5px solid black;"/> <p>North, bet. secs. 19 and 24.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>								
5.40	Southerly right-of-way fence, bears S. 70° E. and N. 70° W.								
7.00	Center of U. S. Highway No. 70, 37 ft. wide, bears S. 70° E. and N. 70° W.								
8.60	Northerly right-of-way fence, bears S. 70° E. and N. 70° W.								
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 1 S</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R 17 E</td><td style="padding: 0 5px;">R 18 E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 24</td><td style="padding: 0 5px;">S 19</td></tr> </table> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 1 S		1/4		R 17 E	R 18 E	S 24	S 19
T 1 S									
1/4									
R 17 E	R 18 E								
S 24	S 19								
80.00	<p>Point for the cor. of secs. 13, 18, 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 1 S</td></tr> <tr><td colspan="2">R 17 E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 13</td><td style="padding: 0 5px;">S 18</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 24</td><td style="padding: 0 5px;">S 19</td></tr> </table> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr style="border: 0.5px solid black;"/>	T 1 S		R 17 E		S 13	S 18	S 24	S 19
T 1 S									
R 17 E									
S 13	S 18								
S 24	S 19								

**Survey of the East Boundary,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS											
	North, bet. secs. 13 and 18.										
	Over rocky, rolling terrain, through scrub oak and mesquite.										
7.80	Graded road, 20 ft. wide, along high pressure gas pipeline, bears SE and NW.										
40.00	Point for the 1/4 sec. cor. of secs. 13 and 18.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table style="margin: auto;"> <tr><td colspan="2">T 1 S</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>R 17 E</td><td> R 18 E</td></tr> <tr><td>S 13</td><td> S 18</td></tr> </table>	T 1 S		1/4		R 17 E	R 18 E	S 13	S 18		
T 1 S											
1/4											
R 17 E	R 18 E										
S 13	S 18										
	2001										
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.										
79.90	Wash, drains NW.										
80.00	Point for the cor. of secs. 7, 12, 13 and 18.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table style="margin: auto;"> <tr><td colspan="2">T 1 S</td></tr> <tr><td>R 17 E</td><td> R 18 E</td></tr> <tr><td>S 12</td><td> S 7</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 13</td><td> S 18</td></tr> </table>	T 1 S		R 17 E	R 18 E	S 12	S 7	<hr/>		S 13	S 18
T 1 S											
R 17 E	R 18 E										
S 12	S 7										
<hr/>											
S 13	S 18										
	2001										
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.										
	Land, rolling.										
	Soil, sandy loam.										
	Undergrowth, scrub oak and mesquite.										
	<hr/>										
	North, bet. secs. 7 and 12.										
	Over rocky, rolling terrain, through scrub oak and mesquite.										
3.30	Graded road, 16 ft. wide, bears N. 75° E. and S. 75° W..										
40.00	Point for the 1/4 sec. cor. of secs. 7 and 12.										

**Survey of the East Boundary,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS											
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 1 S</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>R 17 E</td><td style="border-left: 1px solid black;">R 18 E</td></tr> <tr><td>S 12</td><td style="border-left: 1px solid black;">S 7</td></tr> </table> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 1 S		1/4		R 17 E	R 18 E	S 12	S 7		
T 1 S											
1/4											
R 17 E	R 18 E										
S 12	S 7										
62.60	Center of Southern Pacific rail road tracks, bears S. 85° E. and N. 70° W., on curve.										
65.00	Center of main channel of Gilson Wash, 50 ft. wide, drains S. 75° E.										
67.95	Southerly right-of-way fence, bears N. 80° E. and N. 65° W., on curve.										
68.45	Center of Apache road No. 6, bears N. 80° E. and N. 65° W., on curve.										
69.80	Northerly right-of-way fence, bears N. 80° E. and N. 65° W., on curve.										
77.90	Power lines, bears N. 80° E. and S. 80° W.										
80.00	Point for the cor. of secs. 1, 6, 7 and 12.										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 1 S</td></tr> <tr><td colspan="2">R 17 E</td></tr> <tr><td>S 1</td><td style="border-left: 1px solid black;">R 18 E</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">S 12</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">S 7</td></tr> </table> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr style="width: 60%; margin-left: 0;"/> <p>North, bet. secs. 1 and 6.</p>	T 1 S		R 17 E		S 1	R 18 E	S 12		S 7	
T 1 S											
R 17 E											
S 1	R 18 E										
S 12											
S 7											

**Survey of the East Boundary,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rocky, rolling terrain, through scrub oak and mesquite.
38.55	Fence line, 5 strand barbed wire, bears N. 35° E. and S. 35° W.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 6. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 1 S R 17 E R 18 E 1/4 S 1 S 6 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
62.03	Point for the closing cor. of Tps. 1 S., Rgs. 17 and 18 E., at intersection with the Gila and Salt River Base Line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 1 N R 17 E S 34 ----- S 1 S 6 R 17 E R 18 E CC T1S 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located on the E. slope of a ridge, bears N. and S. from which A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground for a reference monument, bears S. 15°18' E., 782.1 ft. dist. with brass cap mkd. RM T1S R18E S6 782.1 FT TO COR 2009 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	From this cor. point, the stan. cor. of secs. 34 and 35, T. 1 N., R. 17 E., bears N. 89°58' E., 16.00 chs. dist., hereinbefore described.

**Survey of the East Boundary,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS							
	<p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 1 N., R. 17 E., bears S. 89°58' W., 24.02 chs. dist., hereinbefore described.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p style="text-align: center;">Survey of the Subdivisional Lines, T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>						
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 1 S</td> <td style="padding: 0 10px;">R 17 E</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">1/4</td> </tr> <tr> <td style="padding: 0 10px;">S 35</td> <td style="padding: 0 10px;"> S 36</td> </tr> </table> <p style="margin: 5px 0;">2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 1 S	R 17 E		1/4	S 35	S 36
T 1 S	R 17 E						
	1/4						
S 35	S 36						
80.00	<p>Point for the cor. of secs. 25, 26, 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 1 S</td> <td style="padding: 0 10px;">R 17 E</td> </tr> <tr> <td style="padding: 0 10px;">S 26</td> <td style="padding: 0 10px;"> S 25</td> </tr> <tr> <td style="padding: 0 10px;">S 35</td> <td style="padding: 0 10px;"> S 36</td> </tr> </table> <p style="margin: 5px 0;">2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/>	T 1 S	R 17 E	S 26	S 25	S 35	S 36
T 1 S	R 17 E						
S 26	S 25						
S 35	S 36						

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°55' W., bet. secs. 25 and 36.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p> <p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 1 S R 17 E</p> <p>S 25</p> <p>1/4 ———</p> <p>S 36</p> </div> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, rolling.</p> <p>Soil, sandy loam.</p> <p>Undergrowth, scrub oak and mesquite.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 1 S R 17 E</p> <p>1/4</p> <p>S 26 S 25</p> </div> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Cor. is located on the W. face of Bucket mountain.</p> <p>Point for the cor. of secs. 23, 24, 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 1 S</td><td>R 17 E</td></tr> <tr><td>S 23</td><td>S 24</td></tr> <tr><td>S 26</td><td>S 25</td></tr> </table>	T 1 S	R 17 E	S 23	S 24	S 26	S 25		
T 1 S	R 17 E								
S 23	S 24								
S 26	S 25								
	2001								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.								
	<hr/>								
	From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.								
	S. 89°55' W., bet. secs. 24 and 25.								
	Over rocky, rolling terrain, through scrub oak and mesquite.								
40.00	Point for the 1/4 sec. cor. of secs. 24 and 25.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 1 S</td><td>R 17 E</td></tr> <tr><td>S 24</td><td></td></tr> <tr><td>1/4</td><td><hr/></td></tr> <tr><td>S 25</td><td></td></tr> </table>	T 1 S	R 17 E	S 24		1/4	<hr/>	S 25	
T 1 S	R 17 E								
S 24									
1/4	<hr/>								
S 25									
	2001								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
80.00	The cor. of secs. 23, 24, 25 and 26.								
	Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.								
	<hr/>								
	N. 0°01' W., bet. secs. 23 and 24.								
	Over rocky, rolling terrain, through scrub oak and mesquite.								
35.40	Southerly right-of-way fence, bears S. 70° E. and N. 70° W.								
36.95	Center of U. S. Highway No. 70, 37 ft. wide, bears S. 70° E. and N. 70° W.								

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
38.60	Northerly right-of-way fence, bears S. 70° E. and N. 70° W.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 1 S R 17 E 1/4 S 23 S 24 2001 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
57.45	Graded road, 12 ft. wide, bears NE and SW.
80.00	Point for the cor. of secs. 13, 14, 23 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 1 S R 17 E S 14 S 13 S 23 S 24 2001 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.
40.00	From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp. S. 89°55' W., bet. secs. 13 and 24. Over rocky, rolling terrain, through scrub oak and mesquite. Point for the 1/4 sec. cor. of secs. 13 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 1 S R 17 E S 13 1/4 ——— S 24 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
41.10	Wash, 30 ft. wide, 1 ft. deep, drains NE.
55.10	Graded road, 12 ft. wide, bears N. and S.
80.00	The cor. of secs. 13, 14, 23 and 24. Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.
	N. 0°01' W., bet. secs. 13 and 14. Over rocky, rolling terrain, through scrub oak and mesquite.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 1 S R 17 E 1/4 S 14 S 13 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs 11, 12, 13 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 1 S R 17 E S 11 S 12 ——— S 14 S 13 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°55' W., bet. secs. 12 and 13.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
0.15	Wash, drains NW.
34.90	Graded road, 12 ft. wide, bears N. 35° E. and S. 40° W.
40.00	Point for the 1/4 sec. cor. of secs. 12 and 13.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 1 S R 17 E S 12 1/4 ——— S 13</p> <p align="center">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
77.50	Graded road along high pressure gas pipeline, bears S. 65° E. and N. 65° W.
79.65	Fence, 5 strand barbed wire, bears S. 55° E. and N. 55° W.
80.00	The cor. of secs. 11, 12, 13 and 14.
	<p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
0.24	Fence, 5 strand barbed wire, bears S. 55° E. and N. 55° W.
1.05	Graded road along high pressure gas pipeline, bears S. 65° E. and N. 65° W.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 12.

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 17 E 1/4 S 11 S 12</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
63.25	Fence, 4 strand barbed wire, extending S. 85° E. and N. 85° W.
64.00	Center of Southern Pacific rail road tracks, bears S. 85° E. and N. 85° W.
67.30	Fence, 5 strand barbed wire, extending S. 85° E. and N. 85° W.
69.50	Right bank of Gilson Wash, bears N. 75° E. and S. 75° W.
73.10	Left bank of Gilson Wash, bears N. 75° E. and S. 75° W.
80.00	Point for the cor. of secs. 1, 2, 11 and 12.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 17 E S 2 S 1 S 11 S 12</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°55' W., bet. secs. 1 and 12.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
40.00	Point for the 1/4 sec. cor. of secs. 1 and 12.

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p align="center">T 1 S R 17 E S 1 1/4 ——— S 12</p> <p align="center">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
74.60	Northeasterly right-of-way fence, bears S. 63° E. and N. 63° W.
76.20	Center of Apache road No. 6, bears S. 63° E. and N. 63° W.
77.85	Southwesterly right-of-way fence, bears S. 63° E. and N. 63° W.
80.00	The cor. of secs. 1, 2, 11 and 12.
	<p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>N. 0°01' W., bet. secs. 1 and 2.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
1.10	Southwesterly right-of-way fence, bears S. 63° E. and N. 63° W.
1.95	Center of Apache road No. 6, bears S. 63° E. and N. 63° W.
2.85	Northeasterly right-of-way fence, bears S. 63° E. and N. 63° W.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to bedrock, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p align="center">T 1 S R 17 E 1/4 S 2 S 1</p> <p align="center">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
62.12	Point for the closing cor. of secs. 1 and 2, at intersection with the Gila and Salt River Base Line.

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.

T 1 N R 17 E

 S 33

 S 2 | S 1
 T 1 S R 17 E
 CC

2009

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the stan. cor. of secs. 33 and 34, T. 1 N., R. 17 E., bears East, 15.98 chs. dist., hereinbefore described.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 33, T. 1 N., R. 17 E., bears West, 24.04 chs. dist., hereinbefore described.

Land, rolling.

Soil, sandy loam.

Undergrowth, scrub oak and mesquite.

Point for the 1/4 sec. cor. of sec. 1 only, T. 1 S., R. 17 E., is at midpoint on the N. bdy. of sec. 1.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.

T 1 N R 17 E

 1/4 S 1
 T 1 S R 17 E

2001

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 1 N., R. 17 E., bears East, 15.975 chs. dist., hereinbefore described.

From this same cor. point, the stan. cor. of secs. 33 and 34, T. 1 N., R. 17 E., bears West, 24.015 chs. dist., hereinbefore described.

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS									
40.00	<hr style="border: 0.5px solid black; margin-bottom: 10px;"/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td>T 1 S</td><td>R 17 E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td>S 34</td><td> S 35</td></tr> </table> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on the N. slope of a ridge, bears E. and W.</p>	T 1 S	R 17 E	1/4		S 34	S 35		
T 1 S	R 17 E								
1/4									
S 34	S 35								
47.05	<p>Graded road, 12 ft. wide, bears N. 65° E. and S. 80° W.</p>								
80.00	<p>Point for the cor. of secs. 26, 27, 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td>T 1 S</td><td>R 17 E</td></tr> <tr><td>S 27</td><td> S 26</td></tr> <tr><td colspan="2" style="border-top: 1px solid black; border-bottom: 1px solid black;"></td></tr> <tr><td>S 34</td><td> S 35</td></tr> </table> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr style="border: 0.5px solid black; margin-top: 10px;"/>	T 1 S	R 17 E	S 27	S 26			S 34	S 35
T 1 S	R 17 E								
S 27	S 26								
S 34	S 35								
40.00	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 89°55' W., bet. secs. 26 and 35.</p> <p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>								

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>T 1 S R 17 E S 26 1/4 ——— S 35</p> <p>2001</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in a wash, 70 ft. wide, drains NE.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 23 ins. in the ground for a reference monument, bears S. 72°11' W., 129.2 ft. dist. with brass cap mkd. RM T1S R17E S35 129.2 FT. TO COR 2001 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 23 ins. in the ground for a reference monument, bears N. 27°38' W., 132.7 ft. dist. with brass cap mkd. RM T1S R17E 132.7 FT TO COR S26 2001 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
53.70	Graded road, 8 ft. wide, bears N. 60° E. and S. 60° W., on curve.
80.00	<p>The cor. of secs. 26, 27, 34 and 35.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr style="width: 60%; margin-left: 0;"/> <p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 17 E 1/4 S 27 S 26</p> <p style="text-align: center;">2001</p>

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>								
80.00	<p>Point for the cor. of secs. 22, 23, 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 1 S</td> <td>R 17 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 22</td> <td>S 23</td> </tr> <tr> <td style="border-right: 1px solid black;">S 27</td> <td>S 26</td> </tr> </table> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on the E. edge of a wash, 15 ft. wide, 1 ft. deep, drains N.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89°55' W., bet. secs. 23 and 26.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>	T 1 S	R 17 E	S 22	S 23	S 27	S 26		
T 1 S	R 17 E								
S 22	S 23								
S 27	S 26								
3.80	<p>Graded road, 12 ft. wide, bears N. 45° E. and S. 45° W., on curve.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 1 S</td> <td>R 17 E</td> </tr> <tr> <td></td> <td>S 23</td> </tr> <tr> <td></td> <td style="border-top: 1px solid black;">1/4</td> </tr> <tr> <td></td> <td>S 26</td> </tr> </table> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 1 S	R 17 E		S 23		1/4		S 26
T 1 S	R 17 E								
	S 23								
	1/4								
	S 26								
80.00	<p>The cor. of secs. 22, 23, 26 and 27.</p>								

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 1 S R 17 E 1/4 S 22 S 23</p> <p align="center">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
65.35	<p>Southerly right-of-way fence, bears S. 69° E. and N. 69° W.</p>
66.95	<p>Center of U. S. Highway No. 70, 37 ft. wide, bears S. 69° E. and N. 69° W.</p>
68.55	<p>Northerly right-of-way fence, bears S. 69° E. and N. 69° W.</p>
80.00	<p>Point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 1 S R 17 E S 15 S 14 S 22 S 23</p> <p align="center">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89°55' W., bet. secs. 14 and 23.</p>

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rocky, rolling terrain, through scrub oak and mesquite.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 1 S R 17 E S 14 1/4 ——— S 23 2001 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
40.10	E. extent of braded wash, drains N.
40.50	W. extent of braded wash, drains N.
41.40	Right bank of wash, bears N. and S.
41.80	Left bank of wash, bears N. and S.
80.00	The cor. of secs. 14, 15, 22 and 23. Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.

	N. 0°01' W., bet. secs. 14 and 15.
	Over rocky, rolling terrain, through scrub oak and mesquite.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 1 S R 17 E 1/4 S 15 S 14 2001 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
80.00	Point for the cor. of secs. 10, 11, 14 and 15.

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 17 E S 10 S 11 S 15 S 14</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 89°55' W., bet. secs. 11 and 14.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 17 E S 11 1/4 ——— S 14</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 10 lks. N. of a wash, 3 ft. wide, 1/2 ft. deep, drains E.</p>
80.00	<p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>N. 0°01' W., bet. secs. 10 and 11.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
29.00	Fence, 5 strand barbed wire, bears S. 75° E. and N. 85° W.
30.15	Graded road along high pressure gas pipeline, 8 ft. wide, bears S. 75° E. and N. 75° W.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 1 S R 17 E 1/4 S 10 S 11 2001 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
58.50	Center of Southern Pacific rail road tracks, bears N. 60° E. and S. 60° W.
65.95	Right bank of Gilson Wash, bears N. 70° E. and S. 70° W.
73.35	Left bank of Gilson Wash, bears N. 80° E. and S. 80° W.
80.00	Point for the cor. of secs. 2, 3, 10 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 1 S R 17 E S 3 S 2 S 10 S 11 2001 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite. <hr/> From the cor. of secs. 1, 2, 11 and 12. S. 89°55' W., bet. secs. 2 and 11. Over rocky, rolling terrain, through scrub oak and mesquite.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 11.

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 17 E S 2 1/4 ——— S 11</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
1.55	Fence, 5 strand barbed wire, bears N. 70° E. and S. 70° W.
4.60	Southerly right-of-way fence, bears N. 65° E. and S. 65° W.
5.45	Center of Apache road No. 6, bears N. 65° E. and S. 65° W.
6.20	Northerly right-of-way fence, bears N. 65° E. and S. 65° W.
8.21	From this point, a brass tablet, 3 ins. diam., firmly set flush with ground, incased in concrete, 15 ins. diam., bears West, 1.05 chs. dist., mkd. B.I.A. ROADS PT. STA. R.P. 75 DO NOT DISTURB.
9.65	Fence, chain link, 6 ft. high, bears S. 85° E. and N. 85° W., enter San Carlos Job Corp Conservation Center.
22.30	Fence, chain link, 6 ft. high, bears E. and W., leave San Carlos Job Corp Conservation Center.
22.50	Paved road, 20 ft. wide, bears E. and W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
62.21	<p style="text-align: center;">T 1 S R 17 E 1/4 S 3 S 2 2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the closing cor. of secs. 2 and 3, at intersection with the Gila and Salt River Base Line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 N R 17 E S 32 ----- S 3 S 2 T 1 S R 17 E CC 2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the stan. cor. of secs. 32 and 33, T. 1 N., R. 17 E., bears N. 89°58' E., 15.86 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 32, T. 1 N., R. 17 E., bears S. 89°58' W., 24.14 chs. dist., hereinbefore described.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 2 only, T. 1 S., R. 17 E., is at midpoint on the N. bdy. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 1 N R 17 E ----- 1/4 S 2 T 1 S R 17 E 2009</p>

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 33, T. 1 N., R. 17 E., bears N. 89°58' E., 15.96 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the stan. cor. of secs. 32 and 33, T. 1 N., R. 17 E., bears S. 89°58' W., 24.14 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
39.60	Graded road, 12 ft. wide, bears N. 45° E. and S. 80° W., on curve.
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 1 S R 17 E 1/4 S 33 S 34</p> <p align="center">2001</p>
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 27, 28, 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p align="center">T 1 S R 17 E S 28 S 27 ----- S 33 S 34</p> <p align="center">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35. S. 89°55' W., bet. secs. 27 and 34. Over rocky, rolling terrain, through scrub oak and mesquite.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 17 E S 27 1/4 ——— S 34</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
40.20	<p>Wash, 8 ft. wide, 2 ft. deep, drains N. 50° E.</p>
80.00	<p>The cor. of secs. 27, 28, 33 and 34. Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>N. 0°02' W., bet. secs. 27 and 28. Over rocky, rolling terrain, through scrub oak and mesquite.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 28. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 17 E 1/4 S 28 S 27</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS									
80.00	<p>Point for the cor. of secs. 21, 22, 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 1 S</td> <td>R 17 E</td> </tr> <tr> <td>S 21</td> <td>S 22</td> </tr> <tr> <td>S 28</td> <td>S 27</td> </tr> </table> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/>	T 1 S	R 17 E	S 21	S 22	S 28	S 27		
T 1 S	R 17 E								
S 21	S 22								
S 28	S 27								
40.00	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S. 89°55' W., bet. secs. 22 and 27.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p> <p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 1 S</td> <td>R 17 E</td> </tr> <tr> <td></td> <td>S 22</td> </tr> <tr> <td>1/4</td> <td>——</td> </tr> <tr> <td></td> <td>S 27</td> </tr> </table> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 1 S	R 17 E		S 22	1/4	——		S 27
T 1 S	R 17 E								
	S 22								
1/4	——								
	S 27								
80.00	<p>The cor. of secs. 21, 22, 27 and 28.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/>								
40.00	<p>N. 0°02' W., bet. secs. 21 and 22.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p> <p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p>								

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 17 E 1/4 S 21 S 22</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.50	Wash, 6 ft. wide, 1 ft. deep, drains N. 55° E.
80.00	<p>Point for the cor. of secs. 15, 16, 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 17 E S 16 S 15 S 21 S 22</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 89°55' W., bet. secs. 15 and 22.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
30.55	Northerly right-of-way fence, bears S. 69° E. and N. 69° W.
34.80	Center of U. S. Highway No. 70, 37 ft. wide, bears S. 69° E. and N. 69° W.
39.15	Southerly right-of-way fence, bears S. 69° E. and N. 69° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 1 S R 17 E S 15 1/4 ——— S 22 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
79.80	Wash, 5 ft. wide, 1 ft. deep, drains N. 20° W.
80.00	The cor. of secs. 15, 16, 21 and 22.
	Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.

	N. 0°02' W., bet. secs. 15 and 16.
	Over rocky, rolling terrain, through scrub oak and mesquite.
0.90	Wash, 5 ft. wide, 1 ft. deep, drains N. 35° W.
15.30	Southerly right-of-way fence, bears S. 69° E. and N. 69° W.
16.90	Center of U. S. Highway No. 70, 37 ft. wide, bears S. 69° E. and N. 69° W.
18.55	Northerly right-of-way fence, bears S. 69° E. and N. 69° W.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 1 S R 17 E 1/4 S 16 S 15 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 9, 10, 15 and 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>T 1 S R 17 E S 9 S 10 S 16 S 15</p> <p>2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 89°55' W., bet. secs. 10 and 15.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 17 E S 10 1/4 ——— S 15</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
40.70	Right bank of wash, 2 ft. deep, bears N. and S.
41.40	Left bank of same wash, bears N. and S.
80.00	<p>The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
25.75	Graded road along high pressure gas pipeline, 8 ft. wide, bears N. 85° E. and S. 85° W.

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS							
27.40	Center of Southern Pacific rail road tracks, bears N. 70° E. and S. 70° W.						
39.00	Right bank of wash, 2 ft. deep, bears E. and W.						
40.00	Point for the 1/4 sec. cor. of secs. 9 and 10. Set a magnet, in a white plastic case, 22 ins. below the surface of the ground, cor. is located in wash, impracticable to set a permanent monument. from which A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears S. 71°32' W., 323.0 ft. dist. with brass cap mkd. RM T1S R17E 323.0 FT TO COR 1/4 S9 2001 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears N. 8°19' W., 175.0 ft. dist. with brass cap mkd. RM T1S R17E 175.0 FT TO COR 1/4 S9 2001 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.						
40.40	Left bank of wash, 2 ft. deep, bears E. and W.						
63.90	Southerly right-of-way fence, bears N. 80° E. and S. 80° W.						
64.65	Center of Apache road No. 6, bears N. 80° E. and S. 80° W.						
65.40	Northerly right-of-way fence, bears N. 80° E. and S. 80° W.						
80.00	Point for the cor. of secs. 3, 4, 9 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T 1 S R 17 E</td> </tr> <tr> <td style="text-align: center; border-right: 1px solid black;">S 4</td> <td style="text-align: center;">S 3</td> </tr> <tr> <td style="text-align: center; border-right: 1px solid black;">S 9</td> <td style="text-align: center;">S 10</td> </tr> </table> <p style="text-align: center; margin-top: 10px;">2001</p> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.	T 1 S R 17 E		S 4	S 3	S 9	S 10
T 1 S R 17 E							
S 4	S 3						
S 9	S 10						

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	From the cor. of secs. 2, 3, 10 and 11. S. 89°55' W., bet. secs. 3 and 10.
13.40	Southerly right-of-way fence, bears N. 70° E. and S. 75° W., on curve.
16.60	Center of Apache road No. 6, bears N. 70° E. and S. 75° W., on curve.
24.55	Northerly right-of-way fence, bears N. 70° E. and S. 75° W., on curve.
39.70	Paved drive way, bears N. and S.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 1 S R 17 E S 3 1/4 ——— S 10 2001 </div>
80.00	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. The cor. of secs. 3, 4, 9 and 10. Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite. <hr/>
	N. 0°02' W., bet. secs. 3 and 4. Over rocky, rolling terrain, through scrub oak and mesquite.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 1 S R 17 E 1/4 S 4 S 3 2009 </div>

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
62.29	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the closing cor. of secs. 3 and 4, at intersection with the Gila and Salt River Base Line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 N R 17 E</p> <p style="margin-left: 100px;">S 31</p> <hr style="width: 100px; margin: 0 auto;"/> <p style="margin-left: 50px;">S 4 S 3</p> <p>T 1 S R 17 E</p> <p style="margin-left: 100px;">CC</p> <p>2009</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the stan. cor. of secs. 31 and 32, T. 1 N., R. 17 E., bears N. 89°57' E., 15.86 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 1 N., R. 17 E., bears S. 89°57' W., 24.11 chs. dist., hereinbefore described.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 3 only, T. 1 S., R. 17 E., is at midpoint on the N. bdy. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 N R 17 E</p> <hr style="width: 100px; margin: 0 auto;"/> <p style="margin-left: 100px;">1/4 S 3</p> <p>T 1 S R 17 E</p> <p>2009</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 32, T. 1 N., R. 17 E., bears N. 89°59' E., 15.865 chs. dist., hereinbefore described.</p>

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this same cor. point, the stan. cor. of secs. 31 and 32, T. 1 N., R. 17 E., bears S. 89°59' W., 24.145 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 32 and 33.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 17 E 1/4 S 32 S 33 2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
71.45	<p>Center of Coolidge Dam road, a dilapidated paved road, 20 ft. wide, bears S. 70° E. and N. 70° W.</p>
80.00	<p>Point for the cor. of secs. 28, 29, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 17 E S 29 S 28 S 32 S 33 2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>S. 89°55' W., bet. secs. 28 and 33.</p>

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rocky, rolling terrain, through scrub oak and mesquite.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 1 S R 17 E S 28 1/4 ——— S 33 2001 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 28, 29, 32 and 33. Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.
	————— N. 0°02' W., bet. secs. 28 and 29.
	Over rocky, rolling terrain, through scrub oak and mesquite.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 1 S R 17 E 1/4 S 29 S 28 2001 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 20, 21, 28 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 1 S R 17 E S 20 S 21 S 29 S 28 2001 </div>

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on S. slope of a ridge, bears SSE and NNW.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/>
40.00	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. 89°55' W., bet. secs. 21 and 28.</p> <p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 17 E S 21 1/4 ——— S 28</p> <p>2001</p> </div>
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, N. of cor.</p> <p>The cor. of secs. 20, 21, 28 and 29.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/>
40.00	<p>N. 0°02' W., bet. secs. 20 and 21.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p> <p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 17 E 1/4 S 20 S 21</p> <p>2001</p> </div>

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>								
80.00	<p>Point for the cor. of secs. 16, 17, 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 1 S</td><td>R 17 E</td></tr> <tr><td>S 17</td><td>S 16</td></tr> <tr><td>S 20</td><td>S 21</td></tr> </table> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on E. slope of a ridge, bears N. and S.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 89°55' W., bet. secs. 16 and 21.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>	T 1 S	R 17 E	S 17	S 16	S 20	S 21		
T 1 S	R 17 E								
S 17	S 16								
S 20	S 21								
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 1 S</td><td>R 17 E</td></tr> <tr><td></td><td>S 16</td></tr> <tr><td>1/4</td><td>_____</td></tr> <tr><td></td><td>S 21</td></tr> </table> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 1 S	R 17 E		S 16	1/4	_____		S 21
T 1 S	R 17 E								
	S 16								
1/4	_____								
	S 21								
80.00	<p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/>								

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 0°02' W., bet. secs. 16 and 17. Over rocky, rolling terrain, through scrub oak and mesquite.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 1 S R 17 E 1/4 S 17 S 16 2001 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
40.35	Southerly right-of-way fence, bears S. 72° E. and N. 72° W.
41.95	Center of U. S. Highway No. 70, 37 ft. wide, bears S. 72° E. and N. 72° W.
43.55	Northerly right-of-way fence, bears S. 72° E. and N. 72° W.
80.00	Point for the cor. of secs. 8, 9, 16 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 1 S R 17 E S 8 S 9 S 17 S 16 2001 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located on NW slope of a ridge, bears N. 60° E. and S. 60° W. Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite. <hr/> From the cor. of secs. 9, 10, 15 and 16. S. 89°55' W., bet. secs. 9 and 16. Over rocky, rolling terrain, through scrub oak and mesquite.

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
1.45	Fence, barbed wire, bears S. 10° E. and N. 10° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T 1 S R 17 E S 9 1/4 ——— S 16 </div> <div style="text-align: center; margin: 10px 0;">2001</div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 0°02' W., bet. secs. 8 and 9.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
26.30	Graded road along high pressure gas pipeline, 8 ft. wide, bears S. 85° E. and N. 85° W.
26.90	Right bank of Gilson Wash, 2 ft. high, bears N. 60° E. and S. 60° W.
28.50	Left bank of Gilson Wash, 4 ft. high, bears N. 50° E. and S. 45° W.
34.00	Center of Southern Pacific rail road tracks, bears S. 70° E., curving southerly and N. 70° W., curving westerly.
39.95	Utility line, bears N. 80° E. and S. 80° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T 1 S R 17 E 1/4 S 8 S 9 </div> <div style="text-align: center; margin: 10px 0;">2001</div>

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS									
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 1 S</td><td>R 17 E</td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td>S 8</td><td>S 9</td></tr> </table> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on N. face of steep slope of a ridge, bears E. and W.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/>	T 1 S	R 17 E	S 5	S 4	S 8	S 9		
T 1 S	R 17 E								
S 5	S 4								
S 8	S 9								
40.00	<p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 89°55' W., bet. secs. 4 and 9.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 1 S</td><td>R 17 E</td></tr> <tr><td>S 4</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 9</td><td></td></tr> </table> <p>2001</p> </div>	T 1 S	R 17 E	S 4		1/4	—	S 9	
T 1 S	R 17 E								
S 4									
1/4	—								
S 9									
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/>								

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 0°02' W., bet. secs. 4 and 5. Over rocky, rolling terrain, through scrub oak and mesquite.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 1 S R 17 E 1/4 S 5 S 4 2001 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
62.35	Point for the closing cor. of secs. 4 and 5, at intersection with the Gila and Salt River Base Line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground,, with brass cap mkd. <div style="text-align: center;"> T 1 N R 16 E S 36 S 5 S 4 T 1 S R 17 E CC 2001 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	From this cor. point, the stan. cor. of Tps. 1 N., Rgs. 16 and 17 E., bears N. 89°59' E., 15.83 chs. dist., hereinbefore described.
	From this same cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 1 N., R. 16 E., bears S. 89°59' W., 24.21 chs. dist., hereinbefore described.
	Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.
	Point for the 1/4 sec. cor. of sec. 4 only, T. 1 S., R. 17 E., is at midpoint on the N. bdy. of sec. 4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>T 1 N R 17 E</p> <hr style="width: 10%; margin: auto;"/> <p>1/4 S 4</p> <p>T 1 S R 17 E</p> <p>2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 1 N., R. 17 E., bears N. 89°57' E., 15.89 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the stan. cor. of Tps. 1 N., Rgs. 16 and 17 E., bears S. 89°57' W., 24.17 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;"> T 1 S R 17 E 1/4 S 31 S 32 </p> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone 2 1/2 ft. base, 2 ft. high, W. of cor.</p> <p>Cor. is located on W. slope of a ridge, bears NNE and SSW.</p>
80.00	<p>Point for the cor. of secs. 29, 30, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table border="0"> <tr> <td>T 1 S</td> <td>R 17 E</td> </tr> <tr> <td>S 30</td> <td>S 29</td> </tr> <tr> <td>S 31</td> <td>S 32</td> </tr> </table>	T 1 S	R 17 E	S 30	S 29	S 31	S 32		
T 1 S	R 17 E								
S 30	S 29								
S 31	S 32								
	2001								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.								
	<hr/>								
	From the cor. of secs. 28, 29, 32 and 33.								
	S. 89°55' W., bet. secs. 29 and 32.								
	Over rocky, rolling terrain, through scrub oak and mesquite.								
9.40	Center of Coolidge Dam road, a dilapidated paved road, 20 ft. wide, bears S. 35° E. and N. 35° W.								
40.00	Point for the 1/4 sec. cor. of secs. 29 and 32.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="0"> <tr> <td>T 1 S</td> <td>R 17 E</td> </tr> <tr> <td></td> <td>S 29</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 32</td> </tr> </table>	T 1 S	R 17 E		S 29	1/4	—		S 32
T 1 S	R 17 E								
	S 29								
1/4	—								
	S 32								
	2001								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Cor. is located on SW slope of a ridge, bears ENE and WSW.								
80.00	The cor. of secs. 29, 30, 31 and 32.								
	Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.								
	<hr/>								
	S. 89°55' W., bet. secs. 30 and 31.								
	Over rocky, rolling terrain, through scrub oak and mesquite.								
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31.								

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 17 E S 30 1/4 ——— S 31</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.</p> <p>Cor. is located on the S. slope of a ridge, bears E. and W.</p>
78.62	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, marked and witnessed as described in the field notes of the survey of T. 1 S., R. 16 E., executed concurrently under this same group.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 17 E 1/4 S 30 S 29</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on SE slope of a ridge, bears ENE and WSW.</p>
80.00	<p>Point for the cor. of secs. 19, 20, 29 and 30.</p>

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T 1 S	R 17 E
S 19	S 20
S 30	S 29

2001

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Cor. is located on the N. slope of a ridge, bears E. and W.

Land, rolling.

Soil, sandy loam.

Undergrowth, scrub oak and mesquite.

From the cor. of secs. 20, 21, 28 and 29.

S. 89°55' W., bet. secs. 20 and 29.

Over rocky, rolling terrain, through scrub oak and mesquite.

40.00

Point for the 1/4 sec. cor. of secs. 20 and 29.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T 1 S	R 17 E
	S 20
1/4	———
	S 29

2009

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Cor. is located on the W. slope of a ridge, bears N. and S.

69.40

Center of Coolidge Dam road, a dilapidated paved road, 20 ft.
wide, bears S. 45° E. and N. 45° W.

80.00

The cor. of secs. 19, 20, 29 and 30.

Land, rolling.

Soil, sandy loam.

Undergrowth, scrub oak and mesquite.

S. 89°55' W., bet. secs. 19 and 30.

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Over rocky, rolling terrain, through scrub oak and mesquite.</p> <p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 17 E S 19 1/4 ——— S 30</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on S. slope of a ridge, bears NE and SW.</p>
78.54	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, marked and witnessed as described in the field notes of the survey of T. 1 S., R. 16 E., executed concurrently under this same group.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
20.95	<p>Center of Coolidge Dam road, a dilapidated paved road, 20 ft. wide, bears S. 40° E. and N. 50° W., on curve.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 17 E 1/4 S 19 S 20</p> <p style="text-align: center;">2009</p>

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>								
80.00	<p>Point for the cor. of secs. 17, 18, 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 1 S</td><td>R 17 E</td></tr> <tr><td>S 18</td><td>S 17</td></tr> <tr><td>S 19</td><td>S 20</td></tr> </table> <p>2009</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on E. slope of a ridge, bears N. and S.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>S. 89°55' W., bet. secs. 17 and 20.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>	T 1 S	R 17 E	S 18	S 17	S 19	S 20		
T 1 S	R 17 E								
S 18	S 17								
S 19	S 20								
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 1 S</td><td>R 17 E</td></tr> <tr><td></td><td>S 17</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S 20</td></tr> </table> <p>2009</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on the W. slope of a ridge, bears N. and S.</p>	T 1 S	R 17 E		S 17	1/4	—		S 20
T 1 S	R 17 E								
	S 17								
1/4	—								
	S 20								
80.00	<p>The cor. of secs. 17, 18, 19 and 20.</p>								

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>S. 89°55' W., bet. secs. 18 and 19.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
34.05	Center of Coolidge Dam road, a dilapidated paved road, 20 ft. wide, bears S. 30° E. and N. 30° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 17 E S 18 1/4 ——— S 19</p> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on SW slope of a ridge, bears NE and SW.</p>
78.46	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, marked and witnessed as described in the field notes of the survey of T. 1 S., R. 16 E., executed concurrently under this same group.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°03' W., bet. secs. 17 and 18.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 1 S R 17 E 1/4 S 18 S 17 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
61.00	Southerly right-of-way fence, bears S. 75° E. and N. 75° W.
62.55	Center of U. S. Highway No. 70, 37 ft. wide, bears S. 75° E. and N. 75° W.
64.10	Northerly right-of-way fence, bears S. 75° E. and N. 75° W.
80.00	Point for the cor. of secs. 7, 8, 17 and 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 1 S R 17 E S 7 S 8 S 18 S 17 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.
	From the cor. of secs. 8, 9, 16 and 17.
	S. 89°55' W., bet. secs. 8 and 17.
	Over rocky, rolling terrain, through scrub oak and mesquite.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 1 S R 17 E S 8 1/4 ——— S 17 2001

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 7, 8, 17 and 18. Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.

	S. 89°55' W., bet. secs. 7 and 18. Over rocky, rolling terrain, through scrub oak and mesquite.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18. Set a magnet, in a white plastic case, 12 ins. below the surface of the ground, cor. is located in wash, 300 ft. wide, drains E., impracticable to set a permanent monument. from which A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 39°47' E., 85.2 ft. dist. with brass cap mkd. RM T1S R17E 85.2 FT TO COR 1/4 S7 2001 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 17°59' W., 86.0 ft. dist. with brass cap mkd. RM T1S R17E 1/4 S7 86.0 FT TO COR 2001 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. From this cor. point, U.S.C. and G.S. triangulation station CUTTER RESET 1973, bears S. 86°08' W., 34.00 chs. dist., monumented with a concrete monument, 12 ins. sq., firmly set flush with ground, with brass tablet, 3 ins. diam., mkd. CUTTER 1945 1973.
50.95	Easterly right-of-way fence, bears N. 10° E. and S. 10° W.
51.75	Center of Apache road No. 6, bears N. 10° E. and S. 10° W.
52.50	Westerly right-of-way fence, bears N. 10° E. and S. 10° W., enter saw mill area.
60.80	Graded road along high pressure gas pipeline, bears N. 65° E., and S. 65° W.

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
69.65	Northerly right-of-way fence, bears S. 80° E. and N. 80° W., leave saw mill area.
76.25	Center of U. S. Highway No. 70, 37 ft. wide, bears S. 80° E. and N. 80° W.
78.38	The cor. of secs. 7, 12, 13 and 18. on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 2 ins. below the ground, marked and witnessed as described in the field notes of the survey of T. 1 S., R. 16 E., executed concurrently under this same group. Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.

	From the cor. of secs. 7, 8, 17 and 18. N. 0°03' W., bet. secs. 7 and 8. Over rocky, rolling terrain, through scrub oak and mesquite.
15.75	Graded road along high pressure gas pipeline, bears N. 60° E. and S. 60° W.
17.75	Center of Southern Pacific rail road tracks, bears N. 75° E. and S. 75° W.
21.30	Southerly right-of-way fence, bears N. 50° E. and S. 40° W., on curve.
21.90	Center of Apache road No. 6, bears N. 50° E. and S. 40° W., on curve.
22.70	Northerly right-of-way fence, bears N. 50° E. and S. 40° W., on curve.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 1 S R 17 E 1/4 S 7 S 8 2009
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 5, 6, 7 and 8.

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;"> T 1 S R 17 E S 6 S 5 S 7 S 8 2009 </p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on the S. slope of a ridge, bears NNE and SSW.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>S. 89°55' W., bet. secs. 5 and 8.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 1 S R 17 E S 5 1/4 ——— S 8 2009 </p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 5, 6, 7 and 8.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>S. 89°55' W., bet. secs. 6 and 7.</p> <p>Over rocky, rolling terrain, through scrub oak and mesquite.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p>

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 17 E S 6 1/4 ——— S 7</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
78.30	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, in a mound of stone, 3 ft. base, to top, marked and witnessed as described in the field notes of the survey of T. 1 S., R. 16 E., executed concurrently under this same group.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°03' W., bet. secs. 5 and 6.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 17 E 1/4 S 6 S 5</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
62.41	<p>Point for the closing cor. of secs. 5 and 6, at intersection with the Gila and Salt River Base Line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 1 N R 16 E
 S 35
 S 6 | S 5
 T 1 S R 17 E
 CC

2009

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the stan. cor. of secs. 35 and 36, T. 1 N., R. 16 E., bears N. 89°58' E., 15.75 chs. dist., hereinbefore described.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 35, T. 1 N., R. 16 E., bears S. 89°58' W., 24.25 chs. dist., hereinbefore described.

Land, rolling.
 Soil, sandy loam.
 Undergrowth, scrub oak and mesquite.

Point for the 1/4 sec. cor. of sec. 5 only, T. 1 S., R. 17 E., is at midpoint on the N. bdy. of sec. 5.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 1 N R 16 E
 1/4 S 5
 T 1 S R 17 E

2001

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, S. of cor.

From this cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 1 N., R. 16 E., bears N. 89°57' E., 15.79 chs. dist., hereinbefore described.

From this same cor. point, the stan. cor. of secs. 35 and 36, T. 1 N., R. 16 E., bears S. 89°57' W., 24.25 chs. dist., hereinbefore described.

**Survey of the Subdivisional Lines,
T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS

Point for the 1/4 sec. cor. of sec. 6 only, T. 1 S., R. 17 E., at 40.00 chs. dist. from the closing cor. of secs. 5 and 6, on the N. bdy. of sec. 6.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, to top, with brass cap mkd.

T 1 N R 16 E

1/4 S 6

T 1 S R 17 E

2009

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 35, T. 1 N., R. 16 E., bears N. 89°58' E., 15.75 chs. dist., hereinbefore described.

From this same cor. point, the stan. cor. of secs. 34 and 35, T. 1 N., R. 16 E., bears S. 89°58' W., 24.27 chs. dist., hereinbefore described.

GENERAL DESCRIPTION

This survey is located approximately 10 miles east of the town of Globe, Arizona, on the San Carlos Indian Reservation. Access is provided by U. S. Highway No. 70 and Apache Road No. 6.

The elevation ranges from 2900 to 4800 ft. above sea level. The terrain consists of low broken ridges, with a moderate to dense growth of scrub oak and mesquite. The soil is mostly sandy loam.

The mean magnetic declination of 11 1/2 ° E. was derived from National Geophysical Data Center's (NGDC) on-line declination calculator, utilizing the latest International Geomagnetic Reference Field (IGRF) model for the dates of survey.

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD ASSISTANTS

NAMES	CAPACITY
William A. Olver	Land Surveyor
Gordon R. Bubel	Land Surveyor
W. William Foster	Land Surveyor
Geoff A. Graham	Surveyor in Training
Rudy Keedah	Surveyor in Training
Robert J. Lyle	Surveying Technician
Mark R. Searles	Surveying Technician
Robert C. Tessely	Surveying Technician
Blas J. Urena	Surveying Technician

CERTIFICATE OF SURVEY

I, Joe R. Salazar, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 21st day of May, 2001, I have dependently resurveyed a portion of the Gila and Salt River Base Line, through Ranges 16 and 17 East (north boundary), surveyed the south and east boundaries and the subdivisional lines, T. 1 S., R. 17 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

9/8/2009
(Date)

Joe R. Salazar
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the Gila and Salt River Base Line, through Ranges 16 and 17 East (north boundary), and the survey of the south and east boundaries and the subdivisional lines, T. 1 S., R. 17 E., Gila and Salt River Meridian, in the State of Arizona, executed by Joe R. Salazar, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

10/28/2009
(Date)

Paul J. Moss
Acting (Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 1 S., R. 17 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor of Arizona)~~