

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF THE WEST BOUNDARY,
THE SURVEY OF THE SOUTH AND NORTH BOUNDARIES
AND THE
SUBDIVISIONAL LINES
AND THE SUBDIVISION OF CERTAIN SECTIONS

TOWNSHIP 22 NORTH, RANGE 12 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

Joe R. Salazar, Cadastral Surveyor

Under Special Instructions dated May 6, 2009, approved May 6, 2009, which provided for the surveys included under Group No. 1067, and assignment instructions dated May 6, 2009.

Survey commenced May 13, 2009

Survey completed July 30, 2009

INDEX DIAGRAM

TOWNSHIP 22 NORTH RANGE 12 EAST
 GILA AND SALT RIVER MERIDIAN, ARIZONA

7	17 6 62	17 5 51	16 4 43	15 3 35	14 2 26	13 1
6	61 7 59	60 8 49	50 9 41	42 10 32	34 11 24	25 12
6	59 18 57	58 17 47	48 16 39	40 15 30	31 14 23	24 13
5	57 19 55	56 20 46	47 21 38	39 22 29	30 23 21	22 24
4	55 30 53	54 29 45	45 28 37	38 27 28	29 26 20	21 25
4	53 31 51 12	52 32 43 12	44 33 35 11	36 34 26 10	27 35 18 9	19 36 8

Subdivision of Sections 7-11, 13 & 14 Pages 62-70

T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of the west boundary, the survey of the south and north boundaries and the subdivisional lines and the subdivision of certain sections, Township 22 North, Range 12 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Benjamin J. Kinsey surveyed the east boundary and a portion of the north boundary of Township 21 North, Range 11 East, in 1932. Benjamin J. Kinsey surveyed the east boundary and a portion of the north boundary of Township 22 North, Range 11 East, in 1932. Joe R. Salazar surveyed the south and west boundary of Township 22 North, Range 12 1/2 East, in 2007.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated May 6, 2009, for Group Number 1067, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) FERN FERNO MESA CORS ARP, FST1 FLAGSTAFF 1 CORS ARP and P015 DUECECLUBSAZ2005 CORS ARP. The NAD 83 (CORS96)(EPOCH 2002) geographic position of the corner of Townships 21 and 22 North, Ranges 12 and 12 1/2 East, is as follows:

Latitude: 35°14'37.00" N. Longitude: 111°03'38.58" W.

The mean magnetic declination is 11 1/4° E.

**Dependent Resurvey of the West Boundary,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Restoring the survey executed by Benjamin J. Kinsey, in 1932</p> <hr/>								
	<p>Beginning at the cor. of Tps. 21 and 22 N., Rgs. 11 and 12 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above the ground, in a supporting mound of stone, 2 ft. base to top, with brass cap mkd. T22N R11E R12E S36 S31 S1 S6 T21N 1932 and witnessed with a scattered mound of stone, S. of cor.</p>								
	<p>Add the marks 2009 to the brass cap.</p>								
	<p>Rebuild mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p>								
	<p>N. 0°04' E., bet. secs. 31 and 36.</p>								
	<p>Over nearly level, desert terrain, through scattered native grasses.</p>								
40.00	<p>The 1/4 sec. cor. of secs. 31 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above the ground, in a supporting mound of stone, 3 ft. base to top, with brass cap mkd. 1/4 S36 S31 1932.</p>								
	<p>Add the marks T22N R11E R12E 2009 to the brass cap.</p> <hr/>								
	<p>N. 0°03' E., beginning new measurement.</p>								
39.99	<p>The cor. of secs. 25, 30, 31 and 36, monumented with a mound of stone, 4 ft. base, 1 ft. high.</p>								
	<p>At the center of the mound of stone</p>								
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								
	<table style="margin: auto;"> <tr> <td colspan="2">T 22 N</td> </tr> <tr> <td style="border-right: 1px solid black;">R 11 E</td> <td>R 12 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 25</td> <td>S 30</td> </tr> <tr> <td style="border-right: 1px solid black;">S 36</td> <td>S 31</td> </tr> </table>	T 22 N		R 11 E	R 12 E	S 25	S 30	S 36	S 31
T 22 N									
R 11 E	R 12 E								
S 25	S 30								
S 36	S 31								
	<p>2009</p>								
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>								
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/>								
	<p>N. 0°01' E., bet. secs. 25 and 30.</p>								

**Dependent Resurvey of the West Boundary,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.
39.98	The 1/4 sec. cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. 1/4 S25 S30 1932. Add the marks T22N R11E R12E 2009 to the brass cap. <hr/>
	N. 0°03' E., beginning new measurement.
40.00	The cor. of secs. 19, 24, 25 and 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above the ground, witnessed with a mound of stone, 4 ft. base, 2 1/2 ft. high, W. of cor., with brass cap mkd. T22N R11E R12E S24 S19 S25 S30 1932. Add the marks 2009 to the brass cap. <hr/>
	N. 0°01' E., bet. secs. 19 and 24.
	Over nearly level, desert terrain, through scattered native grasses and Mormon tea.
39.99	The 1/4 sec. cor. of secs. 19 and 24, monumented with a mound of stone, 3 ft. base, 2 ft. high. At a point 1 ft. E. of the mound of stone Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 22 N 1/4 R 11 E R 12 E S 24 S 19 2009 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. <hr/>
	N. 0°01' E., beginning new measurement.
39.99	The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, witnessed with a mound of stone, 3 ft. base, 2 ft. high, W. of cor., with brass cap mkd. T22N R11E R12E S13 S18 S24 S19 1932.

**Dependent Resurvey of the West Boundary,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Add the marks 2009 to the brass cap.</p> <hr/> <p>N. 0°02' E., bet. secs. 13 and 18.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>								
40.02	<p>The 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above the ground in a supporting mound of stone, 3 ft. base to top, with brass cap mkd. S13 S18 1932.</p> <p>Add the marks T22N R11E R12E 1/4 2009 to the brass cap.</p> <p>Cor. is located in disturbed area of Trans Western pipelines.</p> <hr/> <p>N. 0°02' E., beginning new measurement.</p>								
0.10	<p>Center of Trans Western pipelines, bears S. 89° E. and N. 89° W.</p>								
40.00	<p>The cor. of secs. 7, 12, 13 and 18, monumented with a mound of stone, 3 ft. base, 2 ft. high.</p> <p>At the center of the mound of stone</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td colspan="2" style="padding: 0 10px;">T 22 N</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R 11 E</td> <td style="padding: 0 5px;">R 12 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 12</td> <td style="padding: 0 5px;">S 7</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 13</td> <td style="padding: 0 5px;">S 18</td> </tr> </table> <p style="margin: 5px 0;">2009</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on a basalt ridge, bears E. and W., 10 lks. E. of a utility pole line, bears E. and W.</p> <hr/> <p>N. 0°02' E., bet. secs. 7 and 12.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>	T 22 N		R 11 E	R 12 E	S 12	S 7	S 13	S 18
T 22 N									
R 11 E	R 12 E								
S 12	S 7								
S 13	S 18								
9.10	<p>Southerly right-of-way fence of Navajo Route 15, bears N. 68°30' E. and S. 68°30' W.</p>								

**Dependent Resurvey of the West Boundary,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
10.30	Center of pavement of Navajo Route 15, 38 ft. wide, bears N. 68°30' E. and S. 68°30' W.
11.50	Northerly right-of-way fence of Navajo Route 15, bears N. 68°30' E. and S. 68°30' W.
20.00	High voltage transmission lines, bears S. 87° E. and N. 87° W.
40.01	Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 22 N 1/4 R 11 E R 12 E S 12 S 7 2009 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Cor. is located in disturbed area of El Paso Natural Gas pipelines.
40.71	Center of El Paso Natural Gas pipelines, bears S. 86° E. and N. 86° W.
80.02	The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, witnessed with a scattered mound of stone, W. of cor., with brass cap mkd. T22N R11E R12E S1 S6 S12 S7 1932. Add the marks 2009 to the brass cap. Rebuild mound of stone, 3 ft. base, 2 ft. high, W. of cor. <hr/> N. 0°01' E., bet. secs. 1 and 6. Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.
40.00	The 1/4 sec. cor. of secs. 1 and 6, monumented with a mound of stone, 4 ft. base, 1 1/2 ft. high. At a point 1 ft. E. of the mound of stone

**Dependent Resurvey of the West Boundary,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 22 N 1/4 R 11 E R 12 E S 1 S 6</p>
	<p align="center">2009</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Rebuild mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/>
	<p>N. 0°02' E., beginning new measurement.</p>
39.99	<p>The cor. of Tps. 22 and 23 N., Rgs. 11 and 12 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 5 ins. above the ground, witnessed with a scattered mound of stone, S. of cor., with brass cap mkd. T23N R11E R12E S36 S31 S1 S6 T22N 1932.</p>
	<p>Add the marks 2009 to the brass cap.</p>
	<p>Rebuild the mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p> <hr/>
	<p align="center">Survey of the South Boundary, T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona</p> <hr/>
	<p>From the cor. of Tps. 21 and 22 N., Rgs. 12 and 12 1/2 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T22N R12E R121/2E S36 S34 S1 S3 T21N 2007.</p>
	<p>Add the marks 2009 to the brass cap.</p>
	<p>N. 89°59' W., bet. secs. 1 and 36, on the S. bdy. of the Tp.</p>
	<p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p>
	<p>Set a stainless steel post, 2 1/2 ins. diam., 16 ins. long, in a concrete form, 12 ins. diam., 14 ins. long, 8 ins. in the ground, to limestone bedrock, with brass cap mkd.</p>

**Survey of the South Boundary,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 12 E S 36 1/4 ——— S 1 T 21 N 2009 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 1, 2, 35 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to limestone bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> T 22 N R 12 E S 35 S 36 ——— ——— S 2 S 1 T 21 N </div> 2009 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.
40.00	<hr/> N. 89°59' W., bet. secs. 2 and 35. Over nearly level, desert terrain, through scattered native grasses and Mormon Tea. Point for the 1/4 sec. cor. of secs. 2 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to limestone bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> T 22 N R 12 E S 35 1/4 ——— S 2 T 21 N 2009 </div>

**Survey of the South Boundary,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>										
80.00	<p>Point for the cor. of secs. 2, 3, 34 and 35.</p> <p>Set a stainless steel post, 2 1/2 ins. diam., 16 ins. long, in a concrete form, 11 ins. diam., 14 ins. long, 8 ins. in the ground, to limestone bedrock, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T 22 N</td> <td style="padding: 0 5px;">R 12 E</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 34</td> <td style="padding: 0 5px;">S 35</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 3</td> <td style="padding: 0 5px;">S 2</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">T 21 N</td> </tr> </table> <p>2009</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>N. 89°59' W., bet. secs. 3 and 34.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>	T 22 N	R 12 E	S 34	S 35	S 3	S 2	T 21 N			
T 22 N	R 12 E										
S 34	S 35										
S 3	S 2										
T 21 N											
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 2 1/2 ins. diam., 16 ins. long, in a concrete form, 12 ins. diam., 14 ins. long, 8 ins. in the ground, to limestone bedrock, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T 22 N</td> <td style="padding: 0 5px;">R 12 E</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S 34</td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="padding: 0 5px; border-top: 1px solid black;"></td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S 3</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">T 21 N</td> </tr> </table> <p>2009</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 22 N	R 12 E		S 34	1/4			S 3	T 21 N	
T 22 N	R 12 E										
	S 34										
1/4											
	S 3										
T 21 N											
80.00	<p>Point for the cor. of secs. 3, 4, 33 and 34.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, on limestone bedrock, 3 ins. below the surface of the ground, with top mkd.</p>										

Survey of the South Boundary,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 22 N R 12 E S 33 S 34 ----- S 4 S 3 T 21 N</p> <p style="text-align: center;">2009</p> <p>Deposit a cylindrical magnet, 3/4 X 1 in., in drill hole, beneath the brass tablet.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>N. 89°59' W., bet. secs. 4 and 33.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to limestone bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 12 E S 33 1/4 ----- S 4 T 21 N</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 4, 5, 32 and 33.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, flush with limestone bedrock, with top mkd.</p> <p style="text-align: center;">T 22 N R 12 E S 32 S 33 ----- S 5 S 4 T 21 N</p> <p style="text-align: center;">2009</p>

**Survey of the South Boundary,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a cylindrical magnet, 3/4 X 1 in., in drill hole, beneath the brass tablet.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>N. 89°59' W., bet. secs. 5 and 32.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, flush with ground, in a concrete form, 12 ins. diam., 6 ins. in ground, to limestone bedrock, with top mkd.</p> <div style="text-align: center;"> <p>T 22 N R 12 E S 32 1/4 ——— S 5 T 21 N</p> <p>2009</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the concrete form.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
67.00	<p>Center of Navajo Route 6910, a graveled road, 35 ft. wide, bears S. 12° E. and N. 12° W.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 12 E S 31 S 32 S 6 S 5 T 21 N</p> <p>2009</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>N. 89°59' W., bet. secs. 6 and 31.</p>

**Survey of the South Boundary,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p> <p>Point for the 1/4 sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 12 E S 31 1/4 ——— S 6 T 21 N</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.75	<p>The cor. of Tps. 21 and 22 N., Rgs. 11 and 12 E., on W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p style="text-align: center;">Survey of the North Boundary, T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of Tps. 22 and 23 N., Rgs. 12 and 12 1/2 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd. T23N R12E R12 1/2E S36 S34 S1 S3 T22N 2007.</p> <p>Add the marks 2009 to the brass cap.</p> <p>N. 89°59' W., bet. secs. 1 and 36, on the N. bdy. of the Tp.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the North Boundary,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p style="text-align: center;">T 23 N R 12 E S 36 1/4 ——— S 1 T 22 N</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>80.00 Point for the cor. of secs. 1, 2, 35 and 36.</p> <p>Set a stainless steel post, 2 1/2 ins. diam., 16 ins. long, in a concrete form, 10 ins. diam., 14 ins. long, 8 ins. in the ground, to limestone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 12 E S 35 S 36 ——— ——— S 2 S 1 T 22 N</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the concrete form.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>N. 89°59' W., bet. secs. 2 and 35.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 2 1/2 ins. diam., 16 ins. long, in a concrete form, 14 ins. diam., 13 ins. long, 8 ins. in the ground, to limestone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 12 E S 35 1/4 ——— S 2 T 22 N</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
---------------	--

**Survey of the North Boundary,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS											
80.00	<p>Point for the cor. of secs. 2, 3, 34 and 35.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, flush with ground, in a concrete form, 12 ins. diam., 6 ins. in the ground, to limestone bedrock, with top mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T 23 N</td> <td style="padding: 0 5px;">R 12 E</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 34</td> <td style="padding: 0 5px;">S 35</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 3</td> <td style="padding: 0 5px;">S 2</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">T 22 N</td> </tr> </table> <p>2009</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the concrete form.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, N. of cor.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>N. 89°59' W., bet. secs. 3 and 34.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>	T 23 N	R 12 E	S 34	S 35	S 3	S 2	T 22 N			
T 23 N	R 12 E										
S 34	S 35										
S 3	S 2										
T 22 N											
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T 23 N</td> <td style="padding: 0 5px;">R 12 E</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S 34</td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="padding: 0 5px; border-top: 1px solid black;">—</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S 3</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">T 22 N</td> </tr> </table> <p>2009</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 23 N	R 12 E		S 34	1/4	—		S 3	T 22 N	
T 23 N	R 12 E										
	S 34										
1/4	—										
	S 3										
T 22 N											
80.00	<p>Point for the cor. of secs. 3, 4, 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										

**Survey of the North Boundary,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS											
	<table style="margin: auto; border-collapse: collapse;"> <tr><td style="padding: 0 5px;">T 23 N</td><td style="padding: 0 5px;">R 12 E</td></tr> <tr><td style="padding: 0 5px;">S 33</td><td style="padding: 0 5px;">S 34</td></tr> <tr><td style="padding: 0 5px;">S 4</td><td style="padding: 0 5px;">S 3</td></tr> <tr><td colspan="2" style="padding: 0 5px;">T 22 N</td></tr> </table>	T 23 N	R 12 E	S 33	S 34	S 4	S 3	T 22 N			
T 23 N	R 12 E										
S 33	S 34										
S 4	S 3										
T 22 N											
	2009										
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>N. 89°59' W., bet. secs. 4 and 33.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, to limestone bedrock, with brass cap mkd.</p>										
	<table style="margin: auto; border-collapse: collapse;"> <tr><td style="padding: 0 5px;">T 23 N</td><td style="padding: 0 5px;">R 12 E</td></tr> <tr><td style="padding: 0 5px;">S 33</td><td></td></tr> <tr><td style="padding: 0 5px;">1/4</td><td style="padding: 0 5px;">—</td></tr> <tr><td style="padding: 0 5px;">S 4</td><td></td></tr> <tr><td colspan="2" style="padding: 0 5px;">T 22 N</td></tr> </table>	T 23 N	R 12 E	S 33		1/4	—	S 4		T 22 N	
T 23 N	R 12 E										
S 33											
1/4	—										
S 4											
T 22 N											
	2009										
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>										
80.00	<p>Point for the cor. of secs. 4, 5, 32 and 33.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, on limestone bedrock, with top mkd.</p>										
	<table style="margin: auto; border-collapse: collapse;"> <tr><td style="padding: 0 5px;">T 23 N</td><td style="padding: 0 5px;">R 12 E</td></tr> <tr><td style="padding: 0 5px;">S 32</td><td style="padding: 0 5px;">S 33</td></tr> <tr><td style="padding: 0 5px;">S 5</td><td style="padding: 0 5px;">S 4</td></tr> <tr><td colspan="2" style="padding: 0 5px;">T 22 N</td></tr> </table>	T 23 N	R 12 E	S 32	S 33	S 5	S 4	T 22 N			
T 23 N	R 12 E										
S 32	S 33										
S 5	S 4										
T 22 N											
	2009										
	<p>Deposit a cylindrical magnet, 3/4 X 1 in., in drill hole, beneath the brass tablet.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>										

**Survey of the North Boundary,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>N. 89°59' W., bet. secs. 5 and 32.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 2 1/2 ins. diam., 16 ins. long, in a concrete form, 14 ins. diam., 15 ins. long, 9 ins. in the ground, to limestone bedrock, with brass cap mkd.</p> <p align="center"> T 23 N R 12 E S 32 1/4 ——— S 5 T 22 N 2009 </p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, N. of cor.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> T 23 N R 12 E S 31 S 32 S 6 S 5 T 22 N 2009 </p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>N. 89°59' W., bet. secs. 6 and 31.</p>

**Survey of the North Boundary,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.
16.30	Center of Navajo Route 6910, a graveled road, 35 ft. wide, bears N. 6° E. and S. 6° W.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 31. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, to limestone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> T 23 N R 12 E S 31 1/4 ——— S 6 T 22 N 2009 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
78.95	The cor. of Tps. 22 and 23 N., Rgs. 11 and 12 E., hereinbefore described. Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.
<hr/> <p>Survey of the Subdivisional Lines, T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described. N. 0°01' W., bet. secs. 35 and 36. Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.
40.00	Point for the 1/4 sec. cor. of secs. 35 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to limestone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 12 E 1/4 S 35 S 36 2009
80.00	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Point for the cor. of secs. 25, 26, 35 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, to limestone bedrock, in a collar of stone, with brass cap mkd. <div style="text-align: center;"> T 22 N R 12 E S 26 S 25 --- --- S 35 S 36 </div> 2009 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.
28.55	<hr/> From the cor. of secs. 25, 27, 34 and 36, on the E. bdy. of the Tp., monumented with a brass tablet, 3 1/4 ins. diam., flush with limestone bedrock, witnessed with a mound of stone, 2 ft. base, 1 ft. high, W. of cor., with top mkd. T22N R12E R12 1/2E S25 S27 S36 S34 2007. Add the marks 2009 to the brass tablet. N. 89°59' W., bet. secs. 25 and 36. Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.
40.00	From this point, a windmill atop of a 9 ft. square, 4 ins. thick concrete slab, with a 31,000 gallon storage tank alongside, bears S., 4.80 chs. dist. Point for the 1/4 sec. cor. of secs. 25 and 36. Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, on limestone bedrock, with top mkd.

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 12 E S 25 1/4 ——— S 36 2009
	Deposit a cylindrical magnet, 3/4 X 1 in., in drill hole, beneath the brass tablet.
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
80.00	The cor. of secs. 25, 26, 35 and 36. Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.
	N. 0°01' W., bet. secs. 25 and 26.
	Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 26. Set a stainless steel post, 2 1/2 ins. diam., 16 ins. long, in a concrete form, 13 ins. diam., 13 ins. long, 13 ins. in the ground, to limestone bedrock, with brass cap mkd.
	T 22 N R 12 E 1/4 S 26 S 25 2009
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to limestone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T 22 N R 12 E S 23 S 24 S 26 S 25 2009
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>From the cor. of secs. 22, 24, 25 and 27, on the E. bdy. of the Tp., monumented with a brass tablet, 3 1/4 ins. diam., flush with limestone bedrock, with top mkd. T22N R12E R12 1/2E S24 S22 S25 S27 2007.</p> <p>Add the marks 2009 to the brass tablet.</p> <p>N. 89°59' W., bet. secs. 24 and 25.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, on limestone bedrock, with top mkd.</p> <p style="text-align: center;">T 22 N R 12 E S 24 1/4 ——— S 25</p> <p style="text-align: center;">2009</p> <p>Deposit a cylindrical magnet, 3/4 X 1 in., in drill hole, beneath the brass tablet.</p> <p>80.00 The cor. of secs. 23, 24, 25 and 26.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>N. 0°01' W., bet. secs. 23 and 24.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, on limestone bedrock, with top mkd.</p>
--------	--

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p style="text-align: center;">T 22 N R 12 E 1/4 S 23 S 24</p> <p style="text-align: center;">2009</p> <p>Deposit a cylindrical magnet, 3/4 X 1 in., in drill hole, beneath the brass tablet.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Point for the cor. of secs. 13, 14, 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 12 E S 14 S 13 S 23 S 24</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>From the cor. of secs. 13, 15, 22 and 24, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T22N R12E R12 1/2E S13 S15 S24 S22 2007.</p> <p>Add the marks 2009 to the brass cap.</p> <p>N. 89°59' W., bet. secs. 13 and 24.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 12 E S 13 1/4 ——— S 24</p> <p style="text-align: center;">2009</p>

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 13, 14, 23 and 24. Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.
	N. 0°01' W., bet. secs. 13 and 14.
	Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.
31.20	Center of Trans Western pipelines, bears S. 86° E. and N. 86° W.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14. Set a stainless steel post, 2 1/2 ins. diam., 16 ins. long, in a concrete form, 11 ins. diam., 15 ins. long, 11 ins. in the ground, to limestone bedrock, with brass cap mkd.
	T 22 N R 12 E 1/4 S 14 S 13 2009
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
75.05	Southerly right-of-way fence of Navajo Route 15, bears S. 78°25' E. and N. 78°25' W.
76.20	Center of pavement of Navajo Route 15, 38 ft. wide, bears S. 78°25' E. and N. 78°25' W.
77.35	Northerly right-of-way fence of Navajo Route 15, bears S. 78°25' E. and N. 78°25' W.
80.00	Point for the cor. of secs. 11, 12, 13 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 12 E S 11 S 12 S 14 S 13 2009

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/>
	<p>From the cor. of secs. 10, 12, 13 and 15, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T22N R12E R12 1/2E S12 S10 S13 S15 2007.</p>
	<p>Add the marks 2009 to the brass cap.</p>
	<p>N. 89°59' W., bet. secs. 12 and 13.</p>
	<p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
24.57	<p>High voltage transmission lines, bears S. 61° E. and N. 61° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 22 N R 12 E S 12 1/4 ——— S 13</p>
	<p align="center">2009</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 11, 12, 13 and 14.</p>
	<p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 11 and 12.</p>
	<p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
5.10	<p>High voltage transmission lines, bears S. 89° E. and N. 89° W.</p>
13.60	<p>Center of El Paso Natural Gas pipelines, bears S. 86° E. and N. 86° W.</p>

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
20.90	From this point, the center of fenced enclosed area of water well and storage tanks, bears W., 15.80 chs.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 22 N R 12 E 1/4 S 11 S 12 2009 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 1, 2, 11 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 22 N R 12 E S 2 S 1 --- S 11 S 12 2009 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.
40.00	From the cor. of secs. 1, 3, 10 and 12, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 14 ins. above the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd. T22N R12E R12 1/2E S1 S3 S12 S10 2007. Add the marks 2009 to the brass cap. N. 89°59' W., bet. secs. 1 and 12. Point for the 1/4 sec. cor. of secs. 1 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 12 E S 1 1/4 ——— S 12 2009 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 1, 2, 11 and 12. Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.
	<hr/> N. 0°01' W., bet. secs. 1 and 2.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, to limestone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T 22 N R 12 E 1/4 S 2 S 1 2009 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., hereinbefore described. Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.
	<hr/> From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°01' W., bet. secs. 34 and 35. Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.
40.00	Point for the 1/4 sec. cor. of secs. 34 and 35.

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, flush with the ground, in a concrete form, 15 ins. diam., 6 ins. in the ground, to limestone bedrock, with top mkd.</p> <p style="text-align: center;">T 22 N R 12 E 1/4 S 34 S 35</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the concrete form.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.</p> <p>Point for the cor. of secs. 26, 27, 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 12 E S 27 S 26 ----- S 34 S 35</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 89°59' W., bet. secs. 26 and 35.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, on limestone bedrock, 2 ins. below the surface of the ground, with top mkd.</p> <p style="text-align: center;">T 22 N R 12 E S 26 1/4 ----- S 35</p> <p style="text-align: center;">2009</p>

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>Deposit a cylindrical magnet, 3/4 X 1 in., in drill hole, beneath the brass tablet.</p> <p>The cor. of secs. 26, 27, 34 and 35.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, flush with the ground, in a concrete form, 16 ins. diam., 8 ins. in the ground, to limestone bedrock, with top mkd.</p> <div style="text-align: center;"> <p>T 22 N R 12 E 1/4 S 27 S 26</p> <p>2009</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the concrete form.</p>
80.00	<p>Point for the cor. of secs. 22, 23, 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to limestone bedrock, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 12 E S 22 S 23 S 27 S 26</p> <p>2009</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p>

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>N. 89°59' W., bet. secs. 23 and 26.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 2 1/2 ins. diam., 16 ins. long, in a concrete form, 15 ins. diam., 14 ins. long, 8 ins. in the ground, to limestone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 12 E S 23 1/4 ——— S 26</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 2 1/2 ins. diam., 16 ins. long, in a concrete form, 14 ins. diam., 14 ins. long, 13 ins. in the ground, to limestone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 12 E 1/4 S 22 S 23</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.</p>
80.00	<p>Point for the cor. of secs. 14, 15, 22 and 23.</p>

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 2 1/2 ins. diam., 16 ins. long, in a concrete form, 12 ins. diam., 13 ins. long, 11 ins. in the ground, to limestone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 12 E S 15 S 14 S 22 S 23</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 89°59' W., bet. secs. 14 and 23.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, 2 ins. below the surface of the ground, on limestone bedrock, with top mkd.</p> <p style="text-align: center;">T 22 N R 12 E S 14 1/4 ——— S 23</p> <p style="text-align: center;">2009</p> <p>Deposit a cylindrical magnet, 3/4 X 1 in., in drill hole, beneath the brass tablet.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
80.00	<p>The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>N. 0°01' W., bet. secs. 14 and 15.</p>

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.
35.95	Center of Trans Western pipelines, bears S. 86° E. and N. 86° W.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 15. Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, flush with ground, in a concrete form, 12 ins. diam., 8 ins. in the ground, to limestone bedrock, with top mkd. <div style="text-align: center;"> T 22 N R 12 E 1/4 S 15 S 14 2009 </div>
	Deposit a magnet, in a white plastic case, at the base of the concrete form. Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
80.00	Point for the cor. of secs. 10, 11, 14 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, to limestone bedrock, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> T 22 N R 12 E S 10 S 11 S 15 S 14 2009 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.
	From the cor. of secs. 11, 12, 13 and 14. N. 89°59' W., bet. secs. 11 and 14. Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.
13.05	Northerly right-of-way fence of Navajo Route 15, bears S. 78°30' E. and N. 78°30' W.

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
18.65	Center of pavement of Navajo Route 15, 40 ft. wide, bears S. 78°30' E. and N. 78°30' W.
24.30	Southerly right-of-way fence of Navajo Route 15, bears S. 78°30' E. and N. 78°30' W. From this point, a right-of-way marker, bears N. 79°19' W., 1.30 chs. dist., monumented with a 3 in. diam. brass cap, encased in concrete, 6 ins. diam., projecting 3 ins. above the ground, mkd. BIA ROADS 19, with a 4 in. angle iron alongside, mkd. HWY. R. OF W. PT. STA. 499+40.26.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 22 N R 12 E S 11 1/4 ——— S 14 2009 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
58.74	From this point, a corner of fences, 5 strand barbed wire, enclosing El Paso Natural Gas Compressor Station, bearing N. 1°30' E., S. 1°25' W. and N. 88°45' W., bears N., 6.12 chs. dist.
80.00	The cor. of secs. 10, 11, 14 and 15. Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea. <hr/>
	N. 0°01' W., bet. secs. 10 and 11. Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.
2.61	Southerly right-of-way fence of Navajo Route 15, bears S. 88°10' E. and N. 88°10' W.
3.75	Center of pavement of Navajo Route 15, 40 ft. wide, bears S. 88°10' E. and N. 88°10' W.
4.85	Extension of right-of-way fences, bears S. 88°10' E. and N. 88°10' W.

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	From this point, a corner of a right-of-way fence, bearing N. 88°10' W. and a 5 strand barbed wire fence, bearing N. 1°15' E., bears N. 88°10' W., 1.48 chs. dist.
6.60	Barbed wire fence, enclosing El Paso Natural Gas Compressor Station, bears N. 88°45' W. and S. 88°45' E. From this point, a corner of fences, 5 strand barbed wire, enclosing El Paso Natural Gas Compressor Station, bearing N. 1°15' E., S. 88°45' E. and S. 1°15' W., bears N. 88°45' W., 1.43 chs. dist.
6.90	High voltage transmission lines, bears S. 89° E. and N. 89° W.
17.42	From this point, a corner of a chain link fence, 9 ft. high, enclosing El Paso Natural Gas Compressor Station buildings, bearing N. 50°17' E. and S. 43°47' E., bears E., 2.34 chs. dist.
17.80	Center of El Paso Natural Gas pipelines, bears S. 88° E. and N. 88° W.
18.75	From this point, a corner of fences, 5 strand barbed wire, enclosing El Paso Natural Gas Compressor Station, bearing S. 1°15' W. and N. 88°40' W., bears W., 1.17 chs. dist.
18.86	From this point, a 2 in. diam. aluminum cap, flush with the ground, bears W., 1.10 chs. dist., mkd. LEUPP.
23.59	Chain link fence, 9 ft. high, enclosing El Paso Natural Gas Compressor Station buildings, bears S. 43°39' E. and N. 43°39' W.
24.37	Chain link fence, 9 ft. high, enclosing El Paso Natural Gas Compressor Station buildings, bears N. 46°20' E. and S. 46°20' W.
28.82	From this point, a corner of fences, enclosing El Paso Natural Gas Compressor Station, 5 strand barbed wire, bearing N. 1°25' E. and N. 88°40' W., bears W., 5.75 chs. dist.
38.67	Barbed wire fence, enclosing El Paso Natural Gas Compressor Station, bears S. 88°45' E. and N. 88°45' W.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T 22 N R 12 E 1/4 S 10 S 11 2009

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS									
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.</p> <p>True point for the cor. of secs. 1, 2, 10 and 11.</p> <p>Cor. falls on easterly face of sandstone outcrop, 10 ft. high, impracticable to set a permanent monument.</p> <p>From this true point, the point selected for a witness cor. for the cor. of secs. 2, 3, 10 and 11, bears S. 40°00' E., 15 lks. dist.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, on limestone bedrock, with top mkd.</p> <div style="text-align: center;"> <p>WC</p> <table style="margin: auto;"> <tr> <td>T 22 N</td> <td>R 12 E</td> </tr> <tr> <td>S 3</td> <td>S 2</td> </tr> <tr> <td>S 10</td> <td>S 11</td> </tr> </table> <p>2009</p> </div> <p>Deposit a cylindrical magnet, 3/4 X 1 in., in drill hole, beneath the brass tablet.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°59' W., bet. secs. 2 and 11.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>	T 22 N	R 12 E	S 3	S 2	S 10	S 11		
T 22 N	R 12 E								
S 3	S 2								
S 10	S 11								
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. below the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 22 N</td> <td>R 12 E</td> </tr> <tr> <td></td> <td>S 2</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td></td> <td>S 11</td> </tr> </table> <p>2009</p> </div>	T 22 N	R 12 E		S 2	1/4	_____		S 11
T 22 N	R 12 E								
	S 2								
1/4	_____								
	S 11								

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in a Team Roping arena, 4 lks. S. of the observation tower.</p>
80.00	<p>True point for the cor. of secs. 2, 3, 10 and 11.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to limestone bedrock, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 12 E 1/4 S 3 S 2 2009</p>
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p>

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to limestone bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 12 E 1/4 S 33 S 34</p> <p style="text-align: center;">2009</p>
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 27, 28, 33 and 34.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, on limestone bedrock, with top mkd.</p> <p style="text-align: center;">T 22 N R 12 E S 28 S 27 ----- S 33 S 34</p> <p style="text-align: center;">2009</p> <p>Deposit a cylindrical magnet, 3/4 X 1 in., in drill hole, beneath the brass tablet.</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°59' W., bet. secs. 27 and 34.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, to limestone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 12 E S 27 1/4 ----- S 34</p> <p style="text-align: center;">2009</p>

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 27, 28, 33 and 34.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, 2 ins. below the surface of the ground, on limestone bedrock, with top mkd.</p> <p style="text-align: center;">T 22 N R 12 E 1/4 S 28 S 27</p> <p style="text-align: center;">2009</p> <p>Deposit a cylindrical magnet, 3/4 X 1 in., in drill hole, beneath the brass tablet.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
80.00	<p>Point for the cor. of secs. 21, 22, 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to limestone bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 12 E S 21 S 22 S 28 S 27</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/>

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 89°59' W., bet. secs. 22 and 27.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to limestone bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p align="center">T 22 N R 12 E S 22 1/4 ——— S 27</p> <p align="center">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 21, 22, 27 and 28.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>N. 0°02' W., bet. secs. 21 and 22.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, 2 ins. below the surface of the ground, on limestone bedrock, with top mkd.</p> <p align="center">T 22 N R 12 E 1/4 S 21 S 22</p> <p align="center">2009</p> <p>Deposit a cylindrical magnet, 3/4 x 1 in., in the drill hole, at the base of the brass tablet.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.</p>
80.00	<p>Point for the cor. of secs. 15, 16, 21 and 22.</p>

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 2 1/2 ins. diam., 15 ins. long, in a concrete form, 12 ins. diam., 12 ins. long, 8 ins. in the ground, to limestone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 12 E S 16 S 15 S 21 S 22</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 89°59' W., bet. secs. 15 and 22.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 12 E S 15 1/4 ——— S 22</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
37.55	Center of Trans Western pipelines, bears S. 87° E. and N. 87° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, flush with the ground, in a concrete form, 12 ins. diam., 6 ins. in the ground, to limestone bedrock, with top mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 22 N R 12 E 1/4 S 16 S 15</p> <p>2009</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the concrete form.</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.</p>
80.00	<p>Point for the cor. of secs. 9, 10, 15 and 16.</p> <p>Set a stainless steel post, 2 1/2 ins. diam., 16 ins. long, in a concrete form, 16 ins. diam., 13 ins. long, 13 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 22 N R 12 E S 9 S 10 ----- S 16 S 15</p> <p>2009</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 89°59' W., bet. secs. 10 and 15.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
24.80	From this point, a wind mill atop of a 9 ft. square, 1 ft. thick concrete slab, with a 50,000 gallon and 30,000 gallon storage tanks alongside, bears South, 2.37 chs. dist.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 15.

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 2 1/2 ins. diam., 16 ins. long, in a concrete form, 11 ins. diam., 14 ins. long, 14 ins. in the ground, to limestone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 12 E S 10 1/4 ——— S 15</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.</p>
80.00	<p>The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
4.68	<p>Southerly right-of-way fence of Navajo Route 15, bears S. 88°40' E. and N. 88°40' W.</p>
5.80	<p>Center of pavement of Navajo Route 15, 38 ft. wide, bears S. 88°40' E. and N. 88°40' W.</p>
6.92	<p>Northerly right-of-way fence of Navajo Route 15, bears S. 88°40' E. and N. 88°40' W.</p>
9.00	<p>High voltage transmission lines, bears S. 89° E. and N. 87° W.</p>
22.20	<p>Center of El Paso Natural Gas pipelines, bears S. 86° E. and N. 86° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, flush with the surface of the ground, on limestone bedrock, with top mkd.</p> <p style="text-align: center;">T 22 N R 12 E 1/4 S 9 S 10</p> <p style="text-align: center;">2009</p>

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a cylindrical magnet, 3/4 X 1 in., in drill hole, beneath the brass tablet.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>						
80.00	<p>Point for the cor. of secs. 3, 4, 9 and 10.</p> <p>Set a stainless steel post, 15 ins. long, 2 1/2 ins. diam., 6 ins. below the surface of the ground, to limestone bedrock, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 22 N</td> <td style="padding: 0 10px;">R 12 E</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 4</td> <td style="padding: 0 5px;">S 3</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 9</td> <td style="padding: 0 5px;">S 10</td> </tr> </table> <p>2009</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on W. edge of graded road, bears N. and S.</p> <p>From this cor. point, an iron pipe, 1 1/2 ins. diam., firmly set in concrete form, 1 1/2 ft. diam., projecting 9 ins. above the ground, bears S. 88°39' E., 1.04 chs. dist., with welded iron top mkd. 4 3 9 10.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the true point for the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 89°59' W., bet. secs. 3 and 10.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>	T 22 N	R 12 E	S 4	S 3	S 9	S 10
T 22 N	R 12 E						
S 4	S 3						
S 9	S 10						
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to limestone bedrock, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 22 N</td> <td style="padding: 0 10px;">R 12 E</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S 3</td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="padding: 0 5px; border-top: 1px solid black;">S 10</td> </tr> </table> <p>2009</p> </div>	T 22 N	R 12 E		S 3	1/4	S 10
T 22 N	R 12 E						
	S 3						
1/4	S 10						

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>N. 0°02' W., bet. secs. 3 and 4.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 12 E 1/4 S 4 S 3 2009</p>
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on the N. bank of a wash, drains E.</p> <p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 32 and 33.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p style="text-align: center;">T 22 N R 12 E 1/4 S 32 S 33</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 28, 29, 32 and 33.</p> <p>Set a stainless steel rod, 5/8 in. diam., 12 ins. long, flush with the ground, in a concrete form, 9 ins. diam., 12 ins. in the ground, to limestone bedrock, with brass cap mkd.</p>
40.00	<p style="text-align: center;">T 22 N R 12 E S 29 S 28 S 32 S 33</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel rod.</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 89°59' W., bet. secs. 28 and 33.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p> <p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to limestone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 12 E S 28 1/4 ——— S 33</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>The cor. of secs. 28, 29, 32 and 33.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>N. 0°02' W., bet. secs. 28 and 29.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, flush with the ground, in a concrete form, 14 ins. diam., 8 ins. in the ground, to limestone bedrock, with top mkd.</p> <p style="text-align: center;">T 22 N R 12 E 1/4 S 29 S 28</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the concrete form.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.</p>
80.00	<p>Point for the cor. of secs. 20, 21, 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 12 E S 20 S 21 S 29 S 28</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N. 89°59' W., bet. secs. 21 and 28.</p>

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 28. Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, 2 ins. below the surface of the ground, on limestone bedrock, with top mkd. <div style="text-align: center;"> T 22 N R 12 E S 21 1/4 ——— S 28 2009 </div>
	Deposit a cylindrical magnet, 3/4 X 1 in., in drill hole, beneath the brass tablet.
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
80.00	The cor. of secs. 20, 21, 28 and 29. Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.
	----- N. 0°02' W., bet. secs. 20 and 21.
	Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 21. Set a stainless steel rod, 5/8 in. diam., 12 ins. long, flush with the ground, in a concrete form, 12 ins. diam., 13 ins. in the ground, to limestone bedrock, with brass cap mkd. <div style="text-align: center;"> T 22 N R 12 E 1/4 S 20 S 21 2009 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel rod.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
80.00	Point for the cor. of secs. 16, 17, 20 and 21.

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, flush with ground, in a concrete form, 10 ins. diam., 8 ins. in the ground, to limestone bedrock, with top mkd.</p> <p style="text-align: center;">T 22 N R 12 E S 17 S 16 S 20 S 21</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the concrete form.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 89°59' W., bet. secs. 16 and 21.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 15 ins. long, 2 1/2 ins. diam., in a concrete form, 14 ins. diam., 6 ins. long, 14 ins. in the ground, to limestone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 12 E S 16 1/4 ——— S 21</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>N. 0°02' W., bet. secs. 16 and 17.</p>

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.
39.25	Center of Trans Western pipelines, bears S. 89° E. and N. 89° W.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 17. Set a stainless steel post, 2 1/2 ins. diam., 15 ins. long, in a concrete form, 12 ins. diam., 12 ins. long, 7 ins. in the ground, to limestone bedrock, with brass cap mkd. <div style="text-align: center;"> T 22 N R 12 E 1/4 S 17 S 16 2009 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor. Cor. is located on the N. edge of a disturbed area of Trans Western pipelines.
80.00	Point for the cor. of secs. 8, 9, 16 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 22 N R 12 E S 8 S 9 S 17 S 16 2009 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.
	From the cor. of secs. 9, 10, 15 and 16. N. 89°59' W., bet. secs. 9 and 16. Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 16.

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel rod, 5/8 in. diam., 12 ins. long, flush with the ground, in concrete form, 10 ins. diam., 12 ins. deep, to limestone bedrock, with brass cap mkd.</p> <p align="center">T 22 N R 12 E S 9 1/4 ——— S 16</p> <p align="center">2009</p>
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel rod.</p> <p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>N. 0°02' W., bet. secs. 8 and 9.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
12.70	High voltage transmission lines, bears S. 87° E. and N. 87° W.
25.65	Southerly right-of-way fence of Navajo Route 15, bears S. 73° E. and N. 84° W., on a curve.
26.80	Center of pavement of Navajo Route 15, 38 ft. wide, bears S. 73° E. and N. 84° W., on a curve.
27.95	Northerly right-of-way fence of Navajo Route 15, bears S. 73° E. and N. 84° W., on a curve.
29.30	Center of El Paso Natural Gas pipelines, bears S. 84° E. and N. 84° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, flush with ground, in a concrete form, 11 ins. diam., 8 ins. in the ground, to limestone bedrock, with top mkd.</p> <p align="center">T 22 N R 12 E 1/4 S 8 S 9</p> <p align="center">2009</p>

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	Deposit a magnet, in a white plastic case, at the base of the concrete form.								
80.00	Point for the cor. of secs. 4, 5, 8 and 9. Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, on limestone bedrock, with top mkd. <div style="text-align: center;"> <table border="0"> <tr><td>T 22 N</td><td>R 12 E</td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 8</td><td>S 9</td></tr> </table> <p>2009</p> </div>	T 22 N	R 12 E	S 5	S 4	<hr/>		S 8	S 9
T 22 N	R 12 E								
S 5	S 4								
<hr/>									
S 8	S 9								
	Deposit a cylindrical magnet, 3/4 X 1 in., in drill hole, beneath the brass tablet.								
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.								
	Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.								
	<hr/>								
	From the cor. of secs. 3, 4, 9 and 10.								
	N. 89°59' W., bet. secs. 4 and 9.								
	Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.								
40.00	Point for the 1/4 sec. cor. of secs. 4 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table border="0"> <tr><td>T 22 N</td><td>R 12 E</td></tr> <tr><td>S 4</td><td></td></tr> <tr><td>1/4</td><td><hr/></td></tr> <tr><td>S 9</td><td></td></tr> </table> <p>2009</p> </div>	T 22 N	R 12 E	S 4		1/4	<hr/>	S 9	
T 22 N	R 12 E								
S 4									
1/4	<hr/>								
S 9									
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
80.00	The cor. of secs. 4, 5, 8 and 9. Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.								
	<hr/>								

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>N. 0°02' W., bet. secs. 4 and 5.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 2 1/2 ins. diam., 16 ins. long, in a concrete form, 11 ins. diam., 14 ins. long, 14 ins. in the ground, to limestone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 12 E 1/4 S 5 S 4</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.</p>
80.00	<p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 12 E 1/4 S 31 S 32</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in track road, bears E. and W.</p>

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS									
47.40	Center of Navajo Route 6910, a graveled road, 35 ft. wide, bears S. 25° E. and N. 28° W., on a curve.								
80.00	<p>Point for the cor. of secs. 29, 30, 31 and 32.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, on limestone bedrock, with top mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 22 N</td><td>R 12 E</td></tr> <tr><td>S 30</td><td>S 29</td></tr> <tr><td>S 31</td><td>S 32</td></tr> </table> <p>2009</p> </div> <p>Deposit a cylindrical magnet, 3/4 X 1 in., in drill hole, beneath the brass tablet.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 89°59' W., bet. secs. 29 and 32.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>	T 22 N	R 12 E	S 30	S 29	S 31	S 32		
T 22 N	R 12 E								
S 30	S 29								
S 31	S 32								
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 2 1/2 ins. diam., 15 ins. long, in a concrete form, 12 ins. diam., 12 ins. long, 12 ins. in the ground, to limestone bedrock, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 22 N</td><td>R 12 E</td></tr> <tr><td>S 29</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 32</td><td></td></tr> </table> <p>2009</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.</p>	T 22 N	R 12 E	S 29		1/4	—	S 32	
T 22 N	R 12 E								
S 29									
1/4	—								
S 32									
80.00	The cor. of secs. 29, 30, 31 and 32.								

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>N. 89°59' W., bet. secs. 30 and 31.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
17.40	Center of Navajo Route 6910, a graveled road, 35 ft. wide, bears S. 30° E. and N. 30° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 12 E S 30 1/4 ——— S 31</p> <p>2009</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on the E. edge of a dry lake bed.</p> <p>Thence along dry lake bed.</p>
79.58	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p style="text-align: center;">T 22 N R 12 E 1/4 S 30 S 29</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 19, 20, 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
40.00	<p style="text-align: center;">T 22 N R 12 E S 19 S 20 S 30 S 29</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>N. 89°59' W., bet. secs. 20 and 29.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p> <p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to limestone bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
80.00	<p style="text-align: center;">T 22 N R 12 E S 20 1/4 ——— S 29</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 19, 20, 29 and 30.</p>

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>West, bet. secs. 19 and 30.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p> <p>37.05 Center of Navajo Route 6910, a graveled road, 35 ft. wide, bears N. 5° E. and S. 5° W.</p> <p>37.50 Enter lava flow.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, to limestone bedrock, with brass cap mkd.</p> <p align="center">T 22 N R 12 E S 19 1/4 ——— S 30</p> <p align="center">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.</p> <p>79.44 The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, on limestone bedrock, with top mkd.</p>
--------	--

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p style="text-align: center;">T 22 N R 12 E 1/4 S 19 S 20</p> <p style="text-align: center;">2009</p> <p>Deposit a cylindrical magnet, 3/4 X 1 in., in drill hole, beneath the brass tablet.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Point for. the cor. of secs. 17, 18, 19 and 20.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a crack in the limestone bedrock, 6 ins. wide, 8 ins. deep, with top mkd.</p>
40.00	<p style="text-align: center;">T 22 N R 12 E S 18 S 17 S 19 S 20</p> <p style="text-align: center;">2009</p> <p>Deposit a cylindrical magnet, 3/4 X 1 in., in crack, beneath the brass tablet.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89°59' W., bet. secs. 17 and 20.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p> <p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 2 1/2 ins. diam., 16 ins. long, in a concrete form, 14 ins. diam., 13 ins. long, 13 ins. in the ground, to limestone bedrock, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 12 E S 17 1/4 ——— S 20</p> <p style="text-align: center;">2009</p>

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 17, 18, 19 and 20. Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.

	S. 89°59' W., bet. secs. 18 and 19.
29.25	Center of Navajo Route 6910, a graveled road, 35 ft. wide, bears N. 5° E. and S. 5° W.
40.00	Point for the 1/4 sec. cor. of secs. 18 and 19. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to limestone bedrock, in a collar of stone, with brass cap mkd.
	T 22 N R 12 E S 18 1/4 ——— S 19 2009
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
79.33	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described. Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.

	From the cor. of secs. 17, 18, 19 and 20. N. 0°03' W., bet. secs. 17 and 18. Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 18. Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, on limestone bedrock, with top mkd.

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 12 E 1/4 S 18 S 17 2009
	Deposit a cylindrical magnet, 3/4 X 1 in., in drill hole, beneath the brass tablet.
	Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.
40.60	Center of Trans Western pipelines, bears S. 89° E. and N. 89° W.
80.00	Point for the cor. of secs. 7, 8, 17 and 18.
	Set a stainless steel rod, 5/8 in. diam., 12 ins. long, flush with the ground, in concrete form, 12 ins. diam., 13 ins. deep, with brass cap mkd.
	T 22 N R 12 E S 7 S 8 S 18 S 17 2009
	Deposit a magnet, in a white plastic case, at the base of the stainless steel rod.
	Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.
	Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.
	<hr/> From the cor. of secs. 8, 9, 16 and 17.
	N. 89°59' W., bet. secs. 8 and 17.
	Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 17.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, on limestone bedrock, with top mkd.
	T 22 N R 12 E S 8 1/4 ——— S 17 2009

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a cylindrical magnet, 3/4 X 1 in., in drill hole, beneath the brass tablet.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
80.00	<p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>West, bet. secs. 7 and 18.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
28.65	<p>Center of Navajo Route 6910, a graveled road, 35 ft. wide, bears N. and S.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, flush with ground, in a concrete form, 10 ins. diam., 8 ins. deep, to limestone bedrock, with top mkd.</p> <div style="text-align: center;"> <p>T 22 N R 12 E S 7 1/4 ——— S 18</p> <p>2009</p> </div>
79.20	<p>Deposit a magnet, in a white plastic case, at the base of the concrete form.</p> <p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°03' W., bet. secs. 7 and 8.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
16.35	High voltage transmission lines, bears S. 87° E. and N. 87° W.
29.05	Southerly right-of-way fence of Navajo Route 15, bears E. and W.
30.15	Center of pavement of Navajo Route 15, 38 ft. wide, bears E. and W.
31.25	Northerly right-of-way fence of Navajo Route 15, bears E. and W.
35.35	Center of El Paso Natural Gas pipelines, bears S. 86° E. and N. 86° W.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 8. Set a stainless steel post, 2 1/2 ins. diam., 16 ins. long, in a concrete form, 12 ins. diam., 11 ins. long, 14 ins. in the ground, to limestone bedrock, with brass cap mkd. <div style="text-align: center;"> T 22 N R 12 E 1/4 S 7 S 8 2009 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.
80.00	Point for the cor. of secs. 5, 6, 7 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, to limestone bedrock, with brass cap mkd. <div style="text-align: center;"> T 22 N R 12 E S 6 S 5 S 7 S 8 2009 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea.
	<hr/> From the cor. of secs. 4, 5, 8 and 9, N. 89°59' W., bet. secs. 5 and 8.

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, to limestone bedrock, with brass cap mkd. <div style="text-align: center;"> T 22 N R 12 E S 5 1/4 ——— S 8 2009 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 5, 6, 7 and 8. Land, rolling. Soil, sandy loam. Undergrowth, native grasses and Mormon Tea. <hr/>
	N. 89°59' W., bet. secs. 6 and 7.
	Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.
19.00	Center of Navajo Route 6910, a graveled road, 35 ft. wide, bears N. 25° E. and S. 25° W.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 7. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 22 N R 12 E S 6 1/4 ——— S 7 2009 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
79.07	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.

**Survey of the Subdivisional Lines,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy loam. Undergrowth, scrub oak and mesquite.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8. N. 0°03' W., bet. secs. 5 and 6. Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 12 E 1/4 S 6 S 5 2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/> <p style="text-align: center;">Subdivision of Section 7, T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 7 and 18. N. 0°03' W., on the N. and S. center line of sec. 7. Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
18.20	<p>High voltage transmission lines, bears S. 87° E. and N. 87° W.</p>
24.40	<p>Southerly right-of-way fence of Navajo Route 15, bears N. 70° E. and S. 68° W., on a curve.</p>
25.60	<p>Center of pavement of Navajo Route 15, 38 ft. wide, bears N. 70° E. and S. 68° W., on a curve.</p>
26.80	<p>Northerly right-of-way fence of Navajo Route 15, bears N. 70° E. and S. 68° W., on a curve.</p>

**Subdivision of Section 7,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
38.05	Center of El Paso Natural Gas pipelines, bears S. 86° E. and N. 86° W.
40.00	Point for the center 1/4 sec. cor. of sec. 7, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T 22 N R 12 E C 1/4 S 7 2009 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The 1/4 sec. cor. of secs. 6 and 7. <hr/> From the 1/4 sec. cor. of secs. 7 and 8. N. 89°59' W., on the E. and W. center line of sec. 7. Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.
30.40	Center of Navajo Route 6910, a graveled road, 35 ft. wide, bears S. 12° E. and N. 7° W., on a curve.
40.00	The center 1/4 sec. cor. of sec. 7.
68.85	Center of El Paso Natural Gas pipelines, bears S. 86° E. and N. 86° W.
79.14	The 1/4 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp., hereinbefore described. <hr/>
Subdivision of Section 8, T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona	
	<hr/> From the 1/4 sec. cor. of secs. 8 and 17. N. 0°03' W., on the N. and S. center line of sec. 8. Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.
14.50	High voltage transmission lines, bears S. 87° E. and N. 87° W.

**Subdivision of Section 8,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
29.00	<p>Southerly right-of-way fence of Navajo Route 15, bears S. 86° E. and N. 89° W., on a curve.</p> <p>From this point, a right-of-way marker, bears S. 78°47' E., 15 lks. dist., monumented with a 3 in. brass cap, encased in concrete, 6 ins. diam., projecting 2 ins. above the ground, mkd. BIA ROADS 19, with a 4 in. angle iron alongside, mkd. HWY. R. OF W. PT. STA. 323+84.91.</p>
30.10	Center of pavement of Navajo Route 15, 38 ft. wide, bears S. 86° E. and N. 89° W., on a curve.
31.25	<p>Northerly right-of-way fence of Navajo Route 15, bears S. 86° E. and N. 89° W., on a curve.</p> <p>From this point, a right-of-way marker, bears S. 88°42' E., 33 lks. dist., monumented with a 3 in. brass cap, encased in concrete, 6 ins. diam., projecting 1 in. above the ground, mkd. BIA ROADS 19, with a 4 in. angle iron alongside, mkd. HWY. R. OF W. PT. STA. 323+84.91.</p>
32.65	Center of El Paso Natural Gas pipelines, bears S. 86° E. and N. 86° W.
40.00	<p>Point for the center 1/4 sec. cor. of sec. 8, at intersection with the E. and W. center line.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, flush with ground, in a concrete form, 14 ins. diam., 7 ins. deep, to limestone bedrock, with top mkd.</p> <p style="text-align: center;">T 22 N R 12 E C 1/4 S 8</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the concrete form.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
80.00	<p>The 1/4 sec. cor. of secs. 5 and 8.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 8 and 9.</p> <p>N. 89°59' W., on the E. and W. center line of sec. 8.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
40.00	The center 1/4 sec. cor. of sec. 8.

**Subdivision of Section 8,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>The 1/4 sec. cor. of secs. 7 and 8.</p> <hr/> <p style="text-align: center;">Subdivision of Section 9, T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 9 and 16.</p> <p>N. 0°02' W., on the N. and S. center line of sec. 9.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
7.70	<p>Southerly right-of-way fence of Navajo Route 15, bears S. 74° E. and N. 65° W., on a curve.</p> <p>From this point, a right-of-way marker, bears N. 66°30' W., 1.53 chs. dist., monumented with a 3 in. brass cap, encased in concrete, 6 ins. diam., projecting 2 ins. above the ground, mkd. BIA ROADS 19, with a 4 in. angle iron alongside, mkd. HWY. R. OF W. PC. STA. 378+50.26.</p>
8.90	<p>Center of pavement of Navajo Route 15, 38 ft. wide, bears S. 74° E. and N. 65° W., on a curve</p>
10.15	<p>Northerly right-of-way fence of Navajo Route 15, bears S. 74° E. and N. 65° W., on a curve.</p> <p>From this point, a right-of-way marker, bears N. 62°51' E., 46 lks. dist., monumented with a 3 in. brass cap, encased in concrete, 6 ins. diam., projecting 2 ins. above the ground, mkd. BIA ROADS 19, with a 4 in. angle iron alongside, mkd. HWY. R. OF W. PC. STA. 378+50.26.</p>
10.85	<p>High voltage transmission lines, bears S. 87° E. and N. 87° W.</p>
25.40	<p>Center of El Paso Natural Gas pipelines, bears S. 84° E. and N. 84° W.</p>
40.00	<p>Point for the center 1/4 sec. cor. of sec. 9, at intersection with the E. and W. center line.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, on limestone bedrock, 1 in. below the surface of the ground, with top mkd.</p>
	<p>T 22 N R 12 E C 1/4 S 9</p> <p>2009</p>

**Subdivision of Section 9,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a cylindrical magnet, 3/4 X 1 in., in drill hole, beneath the brass tablet.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
80.00	The 1/4 sec. cor. of secs. 4 and 9.
	<hr/>
	From the 1/4 sec. cor. of secs. 9 and 10.
	N. 89°59' W., on the E. and W. center line of sec. 9.
	Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.
40.00	The center 1/4 sec. cor. of sec. 9.
80.00	The 1/4 sec. cor. of secs. 8 and 9.
	<hr/>
	Subdivision of Section 10, T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona
	<hr/>
	From the 1/4 sec. cor. of secs. 10 and 15.
	N. 0°02' W., on the N. and S. center line of sec. 10.
	Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.
3.75	Southerly right-of-way fence of Navajo Route 15, bears S. 88°41' E. and N. 88°41' W.
4.85	Center of pavement of Navajo Route 15, 38 ft. wide, bears S. 88°41' E. and N. 88°41' W.
6.00	Northerly right-of-way fence of Navajo Route 15, bears S. 88°41' E. and N. 88°41' W.
7.85	High voltage transmission lines, bears S. 89° E. and N. 89° W.
19.34	From this point, a corner of fences enclosing El Paso Natural Gas Compressor Station, 5 strand barbed wire, bearing N. 1°25' E. and S. 88°40' E., bears E., 14.03 chs. dist.
19.60	Center of El Paso Natural Gas pipelines, bears S. 86° E. and N. 86° W.
29.25	From this point, a corner of fences, enclosing El Paso Natural Gas Compressor Station, 5 strand barbed wire, bearing S. 88°40' E. and S. 1°25' W., bears E., 14.28 chs. dist.

**Subdivision of Section 10,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the center 1/4 sec. cor. of sec. 10, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 12 E C 1/4 S 10</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The 1/4 sec. cor. of secs. 3 and 10.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 10 and 11.</p> <p>N. 89°59' W., on the E. and W. center line of sec. 10.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
5.50	<p>From this point, a corner of fences, enclosing El Paso Natural Gas Compressor Station, 5 strand barbed wire, bearing S. 88°45' E. and S. 1°25' W., bears S., 1.20 chs. dist.</p>
40.00	<p>The center 1/4 sec. cor. of sec. 10.</p>
80.00	<p>The 1/4 sec. cor. of secs. 9 and 10.</p> <hr/> <p style="text-align: center;">Subdivision of Section 11, T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 11 and 14.</p> <p>N. 0°01' W., on the N. and S. center line of sec. 11.</p> <p>Over nearly level, desert terrain, through scattered native grasses.</p>
1.30	<p>Southerly right-of-way fence of Navajo Route 15, bears S. 88°08' E. and N. 88°08' W.</p>
2.45	<p>Center of pavement of Navajo Route 15, 38 ft. wide, bears S. 88°08' E. and N. 88°08' W.</p>
3.55	<p>Northerly right-of-way fence of Navajo Route 15, bears S. 88°08' E. and N. 88°08' W.</p>

**Subdivision of Section 11,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
6.00	High voltage transmission lines, bears S. 89° E. and N. 89° W.
16.25	Center of El Paso Natural Gas pipelines, bears S. 86° E. and N. 86° W.
40.00	Point for the center 1/4 sec. cor. of sec. 11, at intersection with the E. and W. center line. Set a stainless steel post, 2 1/2 ins. diam., 16 ins. long, in a concrete form, 12 ins. diam., 13 ins. long, 13 ins. in the ground, to limestone bedrock, with brass cap mkd.
	T 22 N R 12 E C 1/4 S 11 2009
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The 1/4 sec. cor. of secs. 2 and 11. <hr/>
	From the 1/4 sec. cor. of secs. 11 and 12. N. 89°59' W., on the E. and W. center line of sec. 11. Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.
40.00	The center 1/4 sec. cor. of sec. 11.
57.86	From this point, a corner of fences enclosing El Paso Natural Gas Compressor Station, 5 strand barbed wire, bearing S. 1°30' W. and N. 88°45' W., bears S., 1.81 chs. dist.
80.00	The 1/4 sec. cor. of secs. 10 and 11. <hr/>
	Subdivision of Section 13, T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 13 and 24. North, on the N. and S. center line of sec. 13. Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.
28.65	Center of Trans Western pipelines, bears S. 86° E. and N. 86° W.

**Subdivision of Section 13,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the center 1/4 sec. cor. of sec. 13, at intersection with the E. and W. center line.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, flush with ground, in a concrete form, 15 ins. diam., 10 ins. deep, to limestone bedrock, with top mkd.</p> <p style="text-align: center;">T 22 N R 12 E C 1/4 S 13</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the concrete form.</p>
67.35	<p>Southerly right-of-way fence of Navajo Route 15, bears S. 82° E. and N. 82° W.</p> <p>From this point, a right-of-way marker, bears S. 85°35' W., 8.5 lks. dist., monumented with a 3 in. diam. brass cap, encased in concrete, 6 ins. diam., projecting 1 in. above the ground, mkd. BIA ROADS 19, with a 4 in. angle iron alongside, mkd. HWY. R. OF W. PT. STA. 543+39.26.</p>
68.45	<p>Center of pavement of Navajo Route 15, 38 ft. wide, bears S. 82° E. and N. 82° W.</p>
69.60	<p>Northerly right-of-way fence of Navajo Route 15, bears S. 82° E. and N. 82° W.</p> <p>From this point, a right-of-way marker, bears S. 87°23' E., 21 lks. dist., monumented with a 3 in. diam. brass cap, encased in concrete, 6 ins. diam., projecting 2 ins. above the ground, mkd. BIA ROADS 19, with a 4 in. angle iron alongside, mkd. HWY. R. OF W. PT. STA. 543+39.26.</p>
80.00	<p>The 1/4 sec. cor. of secs. 12 and 13.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 15, on the E. bdy. of the Tp., monumented with a brass tablet, 3 1/4 ins. diam., 4 ins. below the ground, on limestone bedrock, with top mkd. T22N 1/4 R11E R12 1/2E S13 S15 2007.</p> <p>Add the marks 2009 to the brass tablet.</p> <p>N. 89°59' W., on the E. and W. center line of sec. 13.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
40.00	<p>The center 1/4 sec. cor. of sec. 13.</p>

**Subdivision of Section 13,
T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>The 1/4 sec. cor. of secs. 13 and 14.</p> <hr/> <p style="text-align: center;">Subdivision of Section 14, T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 14 and 23.</p> <p>N. 0°01' W., on the N. and S. center line of sec. 14.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
33.80	Center of Trans Western pipelines, bears S. 86° E. and N. 86° W.
40.00	<p>Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 2 1/2 ins. diam., 16 ins. long, in a concrete form, 12 ins. diam., 15 ins. long, 9 ins. in the ground, to limestone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 12 E C 1/4 S 14</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the concrete form.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
80.00	<p>The 1/4 sec. cor. of secs. 11 and 14.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 14.</p> <p>N. 89°59' W., on the E. and W. center line of sec. 14.</p> <p>Over nearly level, desert terrain, through scattered native grasses and Mormon Tea.</p>
40.00	The center 1/4 sec. cor. of sec. 14.
80.00	<p>The 1/4 sec. cor. of secs. 14 and 15.</p> <hr/>

T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

This survey is located on the Navajo Indian Reservation, about 6 miles W. of the village of Leupp, Arizona.

Most of the township consists of nearly level to gently rolling terrain. The area is extremely rocky, with vegetation consisting of native grasses and Mormon tea. The area is used primarily for grazing of sheep, cattle and horses.

Navajo Route 15 traverses the township in an easterly and westerly direction.

The mean magnetic declination of $11 \frac{1}{4}^{\circ}$ E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2005 for the dates of survey.

CERTIFICATE OF SURVEY

I, Joe R. Salazar, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 6th day of May, 2009, I have dependently resurveyed the west boundary, surveyed the south and north boundaries, the subdivisional lines and the subdivision of certain sections, T. 22 N., R. 12 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

11/22/2009
(Date)

Joe R. Salazar
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the west boundary, the survey of the south and north boundaries, the subdivisional lines and the subdivision of certain sections, T. 22 N., R. 12 E., Gila and Salt River Meridian, in the State of Arizona, executed by Joe R. Salazar, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

12/7/2009
(Date)

Paul F. Moss
Acting (Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 22 N., R. 12 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor of Arizona)~~