

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE SURVEY
OF A PORTION OF
THE TENTH STANDARD PARALLEL NORTH (NORTH BOUNDARY),
THE SOUTH AND WEST BOUNDARIES
AND THE SUBDIVISIONAL LINES,
AND
THE SUBDIVISION OF CERTAIN SECTIONS
TOWNSHIP 40 NORTH, RANGE 19 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

Alvina A. Begaye, Cadastral Surveyor

Under Special Instructions dated and approved January 25, 2010, which provided for the surveys included under Group No. 1077 and assignment instructions dated January 25.

Survey commenced January 25, 2010

Survey completed May 20, 2010

INDEX DIAGRAM

TOWNSHIP 40 NORTH, RANGE 19 EAST

GILA AND SALT RIVER MERIDIAN, ARIZONA

R18E		TENTH STANDARD PARALLEL NORTH										R19E											
36		31		32		33		34		35		36											
8		7		6		5		4		4													
		71		70		58		49		40		30											
21		6		69		5		57		4		48		3		39		2		29		1	
		69		68		56		47		38		29											
19		7		67		8		55		9		46		10		37		11		28		12	
		66		66		54		46		37		27											
19		18		65		17		54		16		45		15		36		14		26		13	
		64		63		53		44		35		25											
18		19		63		20		52		21		44		22		34		23		24		24	
		62		61		52		43		33		24											
17		30		60		29		51		28		42		27		33		26		23		25	
		60		59		50		41		32		22											
16		31		58		32		49		33		41		34		31		35		22		36	
		15		14		13		12		11		9											

- Subdivision of section 1.....71-72
- Subdivision of Section 12.....72-73
- Subdivision of Section 13.....73-74
- Subdivision of Section 14.....74-75
- Subdivision of Section 23.....75-76
- Subdivision of Section 26.....76-78
- Subdivision of Section 35.....78-78
- Subdivision of Section 36.....79-80

T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the survey of a portion of the Tenth Standard Parallel North (north boundary), the south and west boundaries and the subdivisional lines, and the subdivision of certain sections, Township 40 North, Range 19 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

The west and north boundaries, Township 38 North, Range 19 East, and the west and north boundaries, Township 39 North, Range 20 East, were surveyed by Leonard R. Sandoval in 1997-98 and 1998. The Tenth Standard Parallel North (south boundary), and the west boundary, Township 41 North, Range 20 East, were surveyed by Joe R. Salazar in 2006. A portion of Tenth Standard Parallel North (south boundary), Township 41 North, Range 19 East, and the west boundary, Township 40 North, Range 20 East, was surveyed by Jones Curtiss in 2008.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated January 25, 2010, for Group Number 1077, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) CITY OF PAGE, SPIDERROCKAZ2005, and MONTICELLOUT2006. The NAD 83 (CORS96) (EPOCH: 2002) (EPOCH: 2010), geographic position of the southeast corner of the township is as follows:

Latitude: 36°49'28.34" N. Longitude: 110°14'09.18" W.

The mean magnetic declination is 11° E.

Survey of a Portion of the Tenth Standard Parallel North (N. Bdy.),
T. 40 N., R 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Beginning at the stan. cor. of secs. 35 and 36, Tp. 41 N., R. 19 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. SC T41N R19E S35 S36 2008.</p>
	<p>Add the marks 2010 to the brass cap.</p>
	<p>West, on the S. bdy. of sec. 35, T. 41 N., R. 19 E.</p>
	<p>Over rolling sandy terrain.</p>
9.90	<p>BIA route 6430 a graded road, 20 ft. wide, bears S. 65° E. and N. 65° W.</p>
40.00	<p>Point for the stan. 1/4 sec. cor. of sec. 35.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T 41 N R 19 E 1/4 S 35 <hr style="width: 10%; margin: auto;"/></p>
	<p style="text-align: center;">2010</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Cor. is located 62 lks. E. of a trail road, bears N. 25° E. and S. 25° W.</p>
80.00	<p>Point for the stan. cor. of secs. 34 and 35.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T 41 N R 19 E S 34 S 35 <hr style="width: 10%; margin: auto;"/></p>
	<p style="text-align: center;">2010</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Land, rolling.</p>
	<p>Soil, sand and sandy clay.</p>
	<p>Timber, scattered juniper; undergrowth, rabbit brush, Mormon Tea, yucca and native grasses.</p>
	<hr style="width: 80%; margin-left: 0;"/> <p>West, on the S. bdy. of sec. 34, T. 41 N., R. 19 E.</p>

**Survey of a Portion of the Tenth Standard Parallel North (N. Bdy.),
T. 40 N., R 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
4.75	Trail road, bears N. 56° E. and S. 56° W.
40.00	Point for the stan. 1/4 sec. cor. of sec. 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">SC T 41 N R 19 E 1/4 S 34</p> <hr/>
	<p align="center">2010</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
43.20	E. bank of El Capitan wash, 150 ft. wide, 3 ft. deep, drains N. 40° W.
52.20	W. bank of El Capitan wash, 150 ft. wide, 3 ft. deep, drains N. 40° W.
53.75	Trail road, bears S. 25° E. and N. 25° W.
62.55	Trail road, bears N. 15° E. and S. 15° W.
80.00	Point for the stan. cor. of secs. 33 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">SC T 41 N R 19 E S 33 S 34</p> <hr/>
	<p align="center">2010</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling.
	Soil, sand and sandy clay.
	Timber, scattered juniper; undergrowth, rabbit brush, Mormon Tea, yucca and native grasses.
	<hr/> West, on the S. bdy. of sec. 33, T. 41 N., R. 19 E.
	Over rolling land.

**Survey of a Portion of the Tenth Standard Parallel North (N. Bdy.),
T. 40 N., R 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
4.65	Trail road, bears S. 10° E. and N. 10° W.
40.00	Point for the stan. 1/4 sec. cor. of sec. 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, in a collar of stone, with brass cap mkd.
	SC T 41 N R 19 E <u>1/4 S 33</u>
	2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the stan. cor. of secs. 32 and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	SC T 41 N R 19 E <u>S 32 S 33</u>
	2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, rabbit brush, Mormon Tea, yucca and native grasses.
	<hr/> West, on the S. bdy. of sec. 32, T. 41 N., R. 19 E.
	Over rolling land.
27.50	Trail road, bears S. 40° E. and N. 40° W.
40.00	Point for the stan. 1/4 sec. cor. of sec. 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of a Portion of the Tenth Standard Parallel North (N. Bdy.),
T. 40 N., R 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	SC T 41 N R 19 E <u>1/4 S 32</u>
	2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
55.70	Wash, 10 ft. wide, 2 ft. deep, drains N. 20° W.
80.00	Point for the stan. cor. of secs. 31 and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	SC T 41 N R 19 E <u>S 31 S 32</u>
	2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, rabbit brush, Mormon Tea, yucca and native grasses.
	West, on the S. bdy. of sec. 31, T. 41 N., R. 19 E.
	Over rolling land.
4.35	BIA route 6420 a graded road, 20 ft. wide, bears N. 35° E. and S. 35° W.
15.15	Levee, 3 ft. wide, 5 ft. high, 10 ft. base, bears N. 40° E. and S. 40° W.
20.65	Trail road, bears S. 5° E. and N. 5° W.
33.15	Power line, bears N. 20° E. and S. 20° W.
40.00	Point for the stan. 1/4 sec. cor. of sec. 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of a Portion of the Tenth Standard Parallel North (N. Bdy.),
T. 40 N., R 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	SC T 41 N R 19 E <u>1/4 S 31</u>
	2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
42.90	Oljeto Wash, 50 ft. wide, 5 ft. deep, drains N. 15° W.
50.25	Trail road, bears N. 15° E. and S. 15° W.
51.30	Barbed wire fence, bears N. 15° E. and S. 15° W.
61.95	Barbed wire fence, bears N. 45° E. and S. 45° W.
75.45	Barbed wire fence, bears S. 60° E. and N. 60° W.
78.25	Barbed wire fence, bears N. 45° E. and S. 45° W.
80.00	Point for the stan. cor. of Tps. 41 N., Rs. 18 and 19 E.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	SC T 41 N R 18 E R 19 E <u>S 36 S 31</u>
	2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling.
	Soil, sand and sandy clay.
	Timber, scattered juniper; undergrowth, rabbit brush, Mormon Tea, yucca and native grasses.
	<hr/>
	West, on the S. bdy. of sec. 36, T. 41 N., R. 18 E.
	Over rolling land.
40.00	Point for the stan. 1/4 sec. cor. of sec. 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of a Portion of the Tenth Standard Parallel North (N. Bdy.),
T. 40 N., R 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	SC T 41 N R 18 E <u>1/4 S 36</u>
	2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
67.25	Oljeto Wash, 90 ft. wide, 8 ft. deep, drains N. 20° E.
74.70	Trail road, bears N. 5° E. and S. 5° W.
80.00	Point for the stan. cor. of secs. 35 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	SC T 41 N R 18 E <u>S 35 S 36</u>
	2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling.
	Soil, sand and sandy clay.
	Timber, scattered juniper; undergrowth, rabbit brush, Mormon Tea, yucca and native grasses.
	<hr/> Survey of the South Boundary, T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona <hr/>
	From the cor. of Tps. 39 and 40 N., Rs. 19 and 20 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, encircled with collar of stone, with brass cap mkd. T40N R19E R20E S36 S31 S1 S6 T39N 2008 1998.
	Add the marks 2010 to the brass cap.
	West, bet. secs. 1 and 36.
	Over broken land.
6.50	E. right-of-way fence of U. S. Highway 163, 5 strand barbed wire, parallels highway.

Survey of the South Boundary,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
7.70	U. S. Highway 163, asphalt surface, 30 ft. wide, bears S. 25° E., and N. 25° W.
9.20	W. right-of-way fence of U. S. Highway 163, 5 strand barbed wire, parallels highway.
11.50	Power line, bears S. 45° E. and N. 45° W.
13.40	El Capitan wash, 30 ft. wide, 3 ft. deep, drains N. 20° W.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>T 40 N R 19 E S 36 1/4 ——— S 1 T 39 N</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Ascend Tyende Mesa.</p>
80.00	True point for the sec. cor. of secs. 1, 2, 35 and 36, falls on a steep slope, where it is impracticable to establish a monument. From this true point, the point selected for a witness cor. to the cor. of secs. 1, 2, 35 and 36, bears South, 3.00 chs. dist. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>WC ↑ T 40 N R 19 E S 35 S 36 S 2 S 1 T 39 N</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 0.40 lks. S. of N. rim of Tyende Mesa, bears S. 60° E. and N. 60° W.</p>

Survey of the South Boundary,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, broken. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.</p> <hr/> <p>West, bet. secs. 2 and 35.</p> <p>Over broken land.</p>
5.10	Northeasterly rim of Tyende Mesa, bears S. 35° E. and N. 35° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 40 N R 19 E S 35 1/4 ——— S 2 T 39 N</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
45.30	Base of mesa, bears S. 10° E. and N. 10° W., thence ascend 150 ft. over E. slope of mesa.
80.00	<p>True point for the cor. of secs. 2, 3, 34 and 35, falls on the W. face of a sandstone cliff, impracticable to establish a monument.</p> <p>From this point, the point selected for a witness cor. to the cor. of secs. 2, 3, 34 and 35, bears S. 31°07' W., 1.31 chs. dist.</p> <p>Set a brass tablet, 3 1/2 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, flush with the surface of a sandstone bedrock, with top mkd.</p> <div style="text-align: center;"> <p>WC </p> <p>T 40 N R 19 E S 34 S 35 —+— S 3 S 2 T 39 N</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the brass tablet.</p>

Survey of the South Boundary,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the true point for the cor. of secs. 2, 3, 34 and 35, second order National Geodetic Survey, triangulation station "Owl", bears N. 36°50' W., 39.50 chs. dist., monumented with a 3 1/2 ins. diam. brass cap, firmly set, flush with a 10 ins. diam., concrete cylinder, projecting 1 in. above ground, with brass cap mkd. US DEPT OF INTERIOR ELEV FT TRI + STA OWL 1970 GEOLOGICAL SURVEY.</p> <p>Land, broken. Soil, sand, sandy clay and sandstone outcrops. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.</p> <hr/> <p>West, bet. secs. 3 and 34.</p> <p>Over broken land.</p>
3.80	W. bank of wash, 100 ft. wide, 50 ft. deep, drains N. 12° W.
19.30	Ridge, bears S. 15° E. and N. 15° W.
40.00	<p>True point for the 1/4 sec. cor. of secs. 3 and 34, falls at the base of a steep canyon, where it is impracticable to establish a monument.</p> <p>From this true point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 3 and 34, bears N. 40°00' W., 0.50 chs. dist.</p> <p>Set a brass tablet, 3 1/2 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, flush with the surface of a sandstone bedrock, with top mkd.</p> <div style="text-align: center;"> <p>WC T 40 N R 19 E S 34 1/4 ——— S 3 T 39 N ↘ 2010</p> </div>
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the brass tablet.</p> <p>Point for the cor. of secs. 3, 4, 33 and 34.</p> <p>Set a brass tablet, 3 1/2 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, flush with the surface of a sandstone outcrop, with top mkd.</p>

**Survey of the South Boundary,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 40 N R 19 E S 33 S 34 S 4 S 3 T 39 N 2010
	Deposit a magnet, in a white plastic case, at the base of the brass tablet. Land, broken. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.
	West, bet. secs. 4 and 33. Over rolling to broken land.
23.75	Trail road, bears N. 55° E. and S. 55° W.
33.90	Trail road, bears S. 70° E. and N. 70° W.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 N R 19 E S 33 1/4 ——— S 4 T 39 N 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
58.05	Trail road, bears N. 70° E. and S. 70° W.
71.05	Trail road, bears N. 10° E. and S. 10° W.
80.00	Point for the cor. of secs. 4, 5, 32 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the South Boundary,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 40 N R 19 E S 32 S 33 S 5 S 4 T 39 N 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling and broken. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.
	West, bet. secs. 5 and 32. Over rolling to broken land.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 N R 19 E S 32 1/4 ——— S 5 T 39 N 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located 65 lks. E. of W. edge of a ridge, bears S. 20° E. and N. 20° W.
67.25	Trail road, bears S. 10° E. and N. 10° W.
80.00	Point of the cor. of secs. 5, 6, 31 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the South Boundary,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<table style="margin: auto;"> <tr><td>T 40 N</td><td>R 19 E</td></tr> <tr><td>S 31</td><td>S 32</td></tr> <tr><td>S 6</td><td>S 5</td></tr> <tr><td colspan="2">T 39 N</td></tr> </table>	T 40 N	R 19 E	S 31	S 32	S 6	S 5	T 39 N			
T 40 N	R 19 E										
S 31	S 32										
S 6	S 5										
T 39 N											
	2010										
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.										
	Land, rolling and broken. Soil, sandy and sandy clay. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.										
	West, bet. secs. 6 and 31.										
	Over rolling land.										
40.00	Point for the 1/4 sec. cor. of secs. 6 and 31.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table style="margin: auto;"> <tr><td>T 40 N</td><td>R 19 E</td></tr> <tr><td>S 31</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 6</td><td></td></tr> <tr><td colspan="2">T 39 N</td></tr> </table>	T 40 N	R 19 E	S 31		1/4	—	S 6		T 39 N	
T 40 N	R 19 E										
S 31											
1/4	—										
S 6											
T 39 N											
	2010										
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.										
78.36	The cor. of Tps. 39 and 40 N., Rs. 18 and 19 E.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table style="margin: auto;"> <tr><td colspan="2">T 40 N</td></tr> <tr><td>R 18 E</td><td>R 19 E</td></tr> <tr><td>S 36</td><td>S 31</td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td colspan="2">T 39 N</td></tr> </table>	T 40 N		R 18 E	R 19 E	S 36	S 31	S 1	S 6	T 39 N	
T 40 N											
R 18 E	R 19 E										
S 36	S 31										
S 1	S 6										
T 39 N											
	2010										
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.										

**Survey of the South Boundary,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this point, the cor. of Tps. 38 and 39 N., Rs. 18 and 19 E., bears South, 480 chs. dist., monumented with a brass tablet, 3 1/4 ins. diam., firmly set, flush with sandstone bedrock, with top mkd. T39N R18E R19E S36 S31 S1 S6 T38N 1998.

Add the marks 2010 to the brass tablet.

Land, rolling.

Soil, sand and sandy clay.

Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.

**Survey of the West Boundary,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

From the cor. of Tps. 39 and 40 N., Rs. 18 and 19 E., hereinbefore described.

North, bet. secs. 31 and 36.

Over rolling land.

40.00 Point for the 1/4 sec. cor. of secs. 31 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 40 N
R 18 E R 19 E
 1/4
 S 36 | S 31

2010

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

62.60 N. rim of Tyende Mesa, bears S. 45° E. and N. 45° W., thence descend N. rim of Tyende Mesa.

78.10 Rim of Tyende Mesa, bears S. 35° E., and N. 35° W., thence descend Tyende Mesa.

80.00 Point for the cor. of secs. 25, 30, 31 and 36.

Set a brass tablet, 3 1/2 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, flush with the surface of a sandstone bedrock, with top mkd.

**Survey of the West Boundary,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table style="margin: auto;"> <tr><td colspan="2">T 40 N</td></tr> <tr><td>R 18 E</td><td>R 19 E</td></tr> <tr><td>S 25</td><td>S 30</td></tr> <tr><td>S 36</td><td>S 31</td></tr> </table>	T 40 N		R 18 E	R 19 E	S 25	S 30	S 36	S 31
T 40 N									
R 18 E	R 19 E								
S 25	S 30								
S 36	S 31								
	2010								
	Deposit a magnet, in a white plastic case, at the base of the brass tablet.								
	Land, rolling and broken. Soil, sand and sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.								
	North bet. secs. 25 and 30.								
	Over extremely rugged and broken land.								
5.00	Rim of Tyende Mesa, bears S. 80° E. and N. 80° W., thence descend Teyende Mesa.								
40.00	True point for the 1/4 sec. cor. of secs. 25 and 30, falls in the steep canyons of Adahchijiyahi canyon, where it is impracticable to establish a permanent monument.								
57.00	Point selected for a witness point, at the base of Tyende Mesa. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto;"> <tr><td colspan="2">WP</td></tr> <tr><td colspan="2">T 40 N</td></tr> <tr><td>R 18 E</td><td>R 19 E</td></tr> <tr><td>S 25</td><td>S 30</td></tr> </table>	WP		T 40 N		R 18 E	R 19 E	S 25	S 30
WP									
T 40 N									
R 18 E	R 19 E								
S 25	S 30								
	2010								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
80.00	Point for the cor. secs. 19, 24, 25 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								

Survey of the West Boundary,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<table style="margin: auto;"> <tr><td colspan="2">T 40 N</td></tr> <tr><td>R 18 E</td><td>R 19 E</td></tr> <tr><td>S 24</td><td>S 19</td></tr> <tr><td>S 25</td><td>S 30</td></tr> </table>	T 40 N		R 18 E	R 19 E	S 24	S 19	S 25	S 30
T 40 N									
R 18 E	R 19 E								
S 24	S 19								
S 25	S 30								
	2010								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Land, rugged and broken. Soil, sandy and sandy clay with sandstone outcrops. Timber, scattered juniper and Russian Olive along wash, undergrowth, rabbit brush and native grasses.								
	North bet. secs. 19 and 24.								
	Over rugged and broken land.								
3.10	Oljeto Wash, 50 ft. wide, 4 ft. deep, drains N. 50° E.								
6.55	Trail road, bears N. 55° E. and S. 55° W.								
16.20	Point selected for a witness point, at the base of Azansosi Mesa, thence ascend Azansosi Mesa.								
	Set a brass tablet, 3 1/2 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, flush with the surface of a sandstone outcrop, with top mkd.								
	<table style="margin: auto;"> <tr><td colspan="2">WP</td></tr> <tr><td colspan="2">T 40 N</td></tr> <tr><td>R 18 E</td><td>R 19 E</td></tr> <tr><td>S 24</td><td>S 19</td></tr> </table>	WP		T 40 N		R 18 E	R 19 E	S 24	S 19
WP									
T 40 N									
R 18 E	R 19 E								
S 24	S 19								
	2010								
	Deposit a magnet, in a white plastic case, at the base of the brass tablet.								
40.00	True point 1/4 sec. cor. of secs. 19 and 24.								
	Cor. is located on top of inaccessible Azansosi Mesa, not monumented.								
80.00	Point for the secs. of 13, 18, 19 and 24.								
	Set a brass tablet, with 16 ins. long aluminum rod, 2 1/2 ins. diam., 16 ins. in the ground, with brass cap mkd.								

**Survey of the West Boundary,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">T 40 N</td></tr> <tr><td style="text-align: center;">R 18 E</td><td style="text-align: center;">R 19 E</td></tr> <tr><td style="text-align: center;">S 13</td><td style="text-align: center;">S 18</td></tr> <tr style="border-top: 1px solid black;"><td style="text-align: center;">S 24</td><td style="text-align: center;">S 19</td></tr> </table> <p style="text-align: center;">2010</p> <p>Cor. falls on the N. slope of a limestone rock ridge.</p> <p>Land, rugged and broken. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.</p> <hr/> <p>North, bet. secs. 13 and 18.</p> <p>Over rugged and broken land.</p>	T 40 N		R 18 E	R 19 E	S 13	S 18	S 24	S 19
T 40 N									
R 18 E	R 19 E								
S 13	S 18								
S 24	S 19								
22.60	<p>Point selected for a witness point, at the base of Azansosi Mesa, bears S. 5° E., and N. 5° W.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">WP</td></tr> <tr><td colspan="2" style="text-align: center;">T 40 N</td></tr> <tr><td style="text-align: center;">R 18 E</td><td style="text-align: center;">R 19 E</td></tr> <tr><td style="text-align: center;">S 13</td><td style="text-align: center;">S 18</td></tr> </table> <p style="text-align: center;">2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	WP		T 40 N		R 18 E	R 19 E	S 13	S 18
WP									
T 40 N									
R 18 E	R 19 E								
S 13	S 18								
40.00	<p>True point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Cor. is located on top of inaccessible Azansosi Mesa, not monumented.</p>								
80.00	<p>True point for the cor. of secs. 7, 12, 13 and 18.</p> <p>Cor. is located on top of an inaccessible mesa, not monumented.</p> <p>Land, rugged and broken. Soil, Sandy and sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.</p> <hr/> <p>North, bet. secs. 7 and 12.</p>								

**Survey of the West Boundary,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rugged to broken land.
3.95	<p>Point for the online witness cor. of secs. 7, 12, 13 and 18.</p> <p>Set a brass tablet, 3 1/2 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, flush with the surface of sandstone bedrock, with top mkd.</p> <div style="text-align: center;"> <pre> WC T 40 N R 18 E R 19 E S 12 S 7 ----- S 13 S 18 v 2010 </pre> </div> <p>Deposit a magnet, in a white plastic case, at the base of the brass tablet.</p>
19.20	Base of Azansosi Mesa, 1000 ft. high, bears S. 60° E., and N. 60° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <pre> T 40 N R 18 E R 19 E 1/4 S 12 S 7 </pre> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 1, 6, 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <pre> T 40 N R 18 E R 19 E S 1 S 6 ----- S 12 S 7 </pre> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the West Boundary,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rugged and broken. Soil, sandy and sandy clay. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.</p> <hr/> <p>North, bet. secs. 1 and 6. Over rolling land.</p>
32.30	Graded road, 25 ft. wide, bears S. 30° E. and N. 30° W.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 6. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 40 N R18 E R19E 1/4 S 1 S 6 2010</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
42.40	Power line, 2 lines, bears N. 85° E. and S. 85° W.
48.30	Graded road, 20 ft. wide, bears N. 85° E. and S. 85° W.
80.02	Point for the closing cor. of Tps. 40 N., Rs. 18 and 19 E., at the intersection with the Tenth Standard Parallel North, on the N. bdy of the Tp. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 41 N R 18 E S 36 ----- S 1 S 6 R 18 E R 19 E T 40 N CC 2010</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	From this cor. point, the stan. cor. of Tps. 41 N., Rs. 18 and 19 E., bears East, 12.99 chs. dist., hereinbefore described.

**Survey of the West Boundary,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 41 N., R. 18 E., bears West, 27.01 chs. dist., hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca, and native grasses.</p> <hr/> <p style="text-align: center;">Survey of the Subdivisional Lines, T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the true point for the cor. of secs. 1, 2, 35 and 36. on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over rugged and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 40 N R 19 E 1/4 S 35 S 36</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
66.80	<p>S. right-of-way fence of U. S. Highway 163, 5 strand barbed wire, parallels highway.</p>
68.10	<p>U. S. Highway 163, asphalt surface, 30 ft. wide, bears S. 57° E., and N. 57° W.</p>
69.45	<p>N. right-of-way fence of U. S. Highway 163, 5 strand barbed wire, parallels highway.</p>
80.00	<p>Point for the cor. of secs. 25, 26, 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 40 N R 19 E S 26 S 25 S 35 S 36
	2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rugged and broken. Soil, sand and sandy clay. No timber; rabbit brush, sagebrush, Mormon Tea, yucca and native grasses.
	<hr/>
	From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 11 ins. above ground, with a mound of stone 3 ft. base to top, with brass cap mkd. T40N R19E R20E S25 S30 S36 S31 2008.
	Add the marks 2010 to the brass cap.
	West, bet. secs. 25 and 36.
	Over rugged and broken land.
2.05	Graded road, 25 ft. wide, bears N. 10° E. and S. 10° W.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 N R 19 E S 25 1/4 ——— S 36
	2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
46.70	Easterly branch of El Capitan Wash, 15 ft. wide, 2 ft. deep, drains N. 35° W.
47.60	Trail road, bears S. 35° E. and N. 35° W.
80.00	The cor. of secs. 25, 26, 35 and 36.

Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rugged and broken. Soil, sand and sandy clay. No timber; rabbit brush, sagebrush, Mormon Tea, yucca and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over rolling land.</p>
3.50	El Capitan Wash, 10 ft. wide, 20 ft. deep, drains N. 85° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 40 N R 19 E 1/4 S 26 S 25</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 40 N R 19 E S 23 S 24 S 26 S 25</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 0.50 chs. N. of a trail road, bears S. 75° E. and N. 75° W.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper. Undergrowth, rabbit brush, sagebrush, Mormon Tea, yucca and native grasses.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 in diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T40N R19E R20E S24 S19 S25 S30 2008.</p> <p>Add the marks 2010 to the brass cap.</p>

Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	West, bet. secs. 24 and 25.
	Over rolling land.
33.70	Trail road, bears S. 25° E. and N. 25° W.
40.00	Point for the 1/4 sec. cor. of secs. 24 and 25.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 N R 19 E S 24 1/4 ——— S 25 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located S. 35° E., 1.65 chs. dist., from the southwest cor. fence post of a private cemetery, 85 ft. X 75 ft., long side bears N. 15° E.
80.00	The cor. of secs. 23, 24, 25 and 26.
	Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper. Undergrowth, rabbit brush, sagebrush, yucca and native grasses.

	N. 0°01' W., bet. secs. 23 and 24.
	Over rugged and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.
	T 40 N R 19 E 1/4 S 23 S 24 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 13, 14, 23 and 24.

**Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 19 E S 14 S 13 S 23 S 24</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 0.46 chs. dist., S. of a trail road, bears S. 30° E. and N. 30° W.</p> <p>Land, rugged and broken. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. dim., firmly set, projecting 16 ins. above ground, with a mound of stone 3 ft. base to top, with brass cap mkd. T40N R19E R20E S13 S18 S24 S19 2008.</p> <p>Add the marks 2010 to the brass cap.</p> <p>West, bet. secs. 13 and 24.</p> <p>Over rugged and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 19 E S 13 1/4 ——— S 24</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located W. of the easterly bank of a dry pond.</p>
42.25	<p>W. bank of a dry pond.</p>
80.00	<p>The cor. of secs. 13, 14, 23 and 24.</p>

**Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Land, rugged and broken. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, Mormon Tea, yucca and native grasses.
	N. 0°01' W., bet. secs. 13 and 14. Over rolling land.
6.15	Underground water line, bears S. 50° E. and N. 50° W.
12.20	Trail road, bears E. and W.
13.80	Trail road, bears N. 20° E. and S. 20° W.
17.80	Front door to Hogan, bears West, 44 lks. dist.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 N R 19 E 1/4 S 14 S 13 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
62.50	S. right-of-way fence of U. S. Highway 163, 5 strand barbed wire, parallels highway.
65.00	U. S. Highway 163, asphalt surface, 30 ft. wide, bears N. 30° E. and S. 30° W.
67.35	N. right-of-way fence of U. S. Highway 163, 5 strand barbed wire, parallels highway.
69.55	Power line, 4 lines, bears N. 30° E. and S. 30° W.
77.40	Trail road, bears S. 80° E. and N. 80° W.
79.70	Trail road, bears S. 60° E. and N. 60° W.
80.00	Point for the cor. of secs. 11, 12, 13 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<table style="margin: auto;"> <tr><td>T 40 N</td><td>R 19 E</td></tr> <tr><td>S 11</td><td>S 12</td></tr> <tr><td>S 14</td><td>S 13</td></tr> </table>	T 40 N	R 19 E	S 11	S 12	S 14	S 13		
T 40 N	R 19 E								
S 11	S 12								
S 14	S 13								
	2010								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Land rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.								
	<hr/>								
	From the true point for the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp.								
	West, bet. secs. 12 and 13.								
	Over rugged and broken land.								
40.00	Point for the 1/4 sec. cor. of secs. 12 and 13.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in sandstone bedrock, with brass cap mkd.								
	<table style="margin: auto;"> <tr><td>T 40 N</td><td>R 19 E</td></tr> <tr><td></td><td>S 12</td></tr> <tr><td>1/4</td><td>———</td></tr> <tr><td></td><td>S 13</td></tr> </table>	T 40 N	R 19 E		S 12	1/4	———		S 13
T 40 N	R 19 E								
	S 12								
1/4	———								
	S 13								
	2010								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
46.20	Base of mesa, bears S. 20° E. and N. 20° W.								
70.65	E. right-of-way fence of U. S. Highway 163, 5 strand barbed wire, parallels highway.								
71.90	U. S Highway 163, asphalt surface, 30 ft. wide, bears N. 30° E. and S. 30° W.								
73.20	W. right-of-way fence of U. S. Highway 163, 5 strand barbed wire, parallels highway.								
74.45	Power line, 4 lines, bears S. 30° W. and S. 30° W.								
80.00	The cor. of secs. 11, 12, 13 and 14.								

Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rugged and broken. Soil, sand and sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 19 E 1/4 S 11 S 12</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
74.50	<p>Trail road, bears S. 80° E. and N. 80° W.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 19 E S 2 S 1 ----- S 11 S 12</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. dim., firmly set, projecting 5 ins. above ground, with brass cap mkd. T40N R19E R20E S1 S6 S12 S7 2008.</p> <p>Add the marks 2010 to the brass cap.</p>

**Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	West, bet. secs. 1 and 12.
	Over rolling land.
28.85	E. right-of-way fence of U. S. Highway 163, 5 strand barbed wire, parallels highway.
30.10	U. S Highway 163, asphalt surface, 30 ft. wide, bears N. 25° E. and S. 25° W.
31.40	W. right-of-way fence of U. S. Highway 163, 5 strand barbed wire, parallels highway.
32.65	Power line, 4 lines, bears N. 25° E. and S. 25° W.
37.40	Trail road, bears N. 20° E. and S. 20° W.
39.90	Trail road, bears N. 5° E. and S. 5° W.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 N R 19 E S 1 1/4 ——— S 12 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 1, 2, 11 and 12.
	Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, Mormon Tea, yucca and native grasses.

	N. 0°01' W., bet. secs. 1 and 2.
	Over rolling land.
22.20	Trail road, bears E. and W.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 40 N R 19 E
1/4
S 2 | S 1

2010

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

80.01

Point for the closing cor. of secs. 1 and 2 , at intersection with the Tenth Standard Parallel North, on the N. bdy. of the Tp.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 41 N R 19 E
S 35

S 2 | S 1
T 40 N R 19 E
CC

2010

From this cor. point, the stan. cor. of secs. 35 and 36, T. 41 N., R. 19 E., bears East, 15.19 chs. dist., hereinbefore described.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 35, T. 41 N., R. 19 E., bears West, 24.81 chs. dist., hereinbefore described.

Land, rolling.

Soil, sand and sandy clay.

Timber, scattered juniper; undergrowth, rabbit brush, cacti, Mormon Tea, yucca and native grasses.

Point for the 1/4 sec. cor. of sec. 1 only, at the midpoint on the N. bdy. of sec. 1.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 41 N R 19 E

1/4 S 1
T 40 N R 19 E

2010

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this cor. point, the stan. 1/4 sec. cor. of sec. 36, bears East, 15.195 chs. dist., monumented with a stainless steel post, 2 1/2 ins diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. SC T41N R19E S36 2008.</p> <p>From this same cor. point, the stan. cor. of secs. 35 and 36, T. 41 N., R. 19 E., bears West, 24.805 chs. dist., hereinbefore described.</p> <hr/> <p>From the true point for the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp. hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over extremely rugged land.</p>
3.82	W. bank of a wash, 100 ft. wide, 50 ft. deep, bears N. 5° E. and S. 5° W.
39.00	N. rim of Tyende Mesa, bears S. 80° E. and N. 80° W.
40.00	<p>True point for the 1/4 sec. cor. of secs. 34 and 35, falls on the N. face of steep mesa, where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 35 and 36, bears S. 15° E., 1.33 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 40 N R 19 E</p> <p>↙ 1/4</p> <p>S 34 S 35</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.25	Wash, 10 ft. wide, 5 ft. deep, drains N. 10° E.
80.00	<p>Point for the cor. of secs. 26, 27, 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<table style="margin: auto;"> <tr> <td>T 40 N</td> <td>R 19 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 27</td> <td>S 26</td> </tr> <tr> <td style="border-right: 1px solid black;">S 34</td> <td>S 35</td> </tr> </table>	T 40 N	R 19 E	S 27	S 26	S 34	S 35		
T 40 N	R 19 E								
S 27	S 26								
S 34	S 35								
	2010								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Land, rugged.								
	Soil, sand and sandy clay with sandstone outcrops.								
	Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.								
	<hr/>								
	From the cor. of secs. 25, 26, 35 and 36.								
	West, bet. secs. 26 and 35.								
	Over broken to rolling land.								
17.50	E. right-of-way fence of U. S. Highway 163, 5 strand barbed wire, parallels highway.								
20.35	U. S. Highway 163, asphalt surface, 30 ft. wide, bears S. 65° E. and N. 65° W.								
24.45	W. right-of-way fence of U. S. Highway 163, 5 strand barbed wire, parallels highway.								
35.95	Power line, 4 lines, bears S. 65° E. and N. 65° W.								
40.00	Point for the 1/4 sec. cor. of secs. 26 and 35.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto;"> <tr> <td>T 40 N</td> <td>R 19 E</td> </tr> <tr> <td></td> <td>S 26</td> </tr> <tr> <td></td> <td>1/4 ———</td> </tr> <tr> <td></td> <td>S 35</td> </tr> </table>	T 40 N	R 19 E		S 26		1/4 ———		S 35
T 40 N	R 19 E								
	S 26								
	1/4 ———								
	S 35								
	2010								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
79.55	Wash, 10 ft. wide, 5 ft. deep, drains N. 10° W.								
80.00	The cor. of secs. 26, 27, 34 and 35.								

**Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, broken and rolling. Soil, sand and sandy clay. No timber; rabbit brush, sagebrush, yucca and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>Over rolling land.</p>
14.20	Trail road, bears N. 85° E. and S. 85° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 19 E 1/4 S 27 S 26</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the secs. 22, 23, 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 19 E S 22 S 23 S 27 S 26</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; rabbit brush, sagebrush, yucca, native grasses.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>West, bet. secs. 23 and 26.</p> <p>Over broken land.</p>
1.80	Trail road, bears S. 75° E. and N. 75° W.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 26.

**Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Set a brass tablet, 3 1/2 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, flush with the surface of a sandstone bedrock, with top mkd.
	T 40 N R 19 E S 23 1/4 ——— S 26 2010
	Deposit a magnet, in a white plastic case, at the base of the brass tablet.
47.10	E. rim of El Capitan Wash, 150 ft. wide, 200 ft. deep, bears S. 25° E. and N. 25° W.
52.00	W. rim of El Capitan Wash, 150 ft. wide, 200 ft. deep, bears S. 20° E. and N. 20° W.
63.50	Wash, 25 ft. wide, 10 ft. deep, drains N. 5° W.
74.00	E. right-of-way fence of U. S. Highway 163, 5 strand barbed wire, parallels highway.
75.25	U.S. Highway 163, asphalt surface, 30 ft. wide, N. 5° E. and S. 5° W.
76.35	W. right-of-way fence of U. S. Highway 163, 5 strand barbed wire, parallels highway.
76.55	Trail road, bears N. and S.
76.72	Power line, 4 lines, bears N. 5° E. and S. 5° W.
80.00	The cor. of secs. 22, 23, 26 and 27. Land, broken. Soil, sand and sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.

	N. 0°01' W., bet. secs. 22 and 23.
	Over rolling land.
1.45	Power line, 2 lines, bears S. 75° E. and N. 75° W.
1.70	Trail road, bears N. 70° E. and S. 70° W.
17.65	BIA route 6450 a graded road, 20 ft. wide, bears S. 30° E. and N. 30° W.

**Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
26.45	Wash, 13 ft. wide, 5 ft. deep, drains N. 70° E.
28.85	Power line, 2 lines, bears S. 75° E. and N. 75° W.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 40 N R 19 E 1/4 S 22 S 23 2010 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
44.15	Trail road, bears N. 55° E. and S. 55° W.
54.20	Trail road, bears N. 10° E. and S. 10° W.
55.66	Southeast cor. of a brick house, 40 ft. X 25 ft., bears West, 64 lks. dist., long side bears N. 10° E.
80.00	Point for the cor. of secs. 14, 15, 22 and 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 40 N R 19 E S 15 S 14 S 22 S 23 2010 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses. <hr/> From the cor. of secs. 13, 14, 23 and 24. West, bet. secs. 14 and 23. Over rolling land.
33.40	E. right-of-way fence of U. S. Highway 163, 5 strand barbed wire, parallels highway.

Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
34.65	U. S. Highway 163, asphalt surface, 30 ft. wide, bears N. 28° E., and S. 28° W.
35.95	W. right-of-way fence of U. S, Highway 163, 5 strand barbed wire, parallels highway.
36.90	Power line, 4 lines, bears N. 30° E. and S. 30° W.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 40 N R 19 E S 14 1/4 ——— S 23 2010 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
59.95	El Capitan Wash, 80 ft. wide, 5 ft. deep, drains N. 20° E.
71.70	Trail road, bears N. and S.
80.00	The cor. of secs. 14, 15, 22 and 23. Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.
	<hr/> N. 0°01' W., bet. secs. 14 and 15. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 40 N R 19 E 1/4 S 15 S 14 2010 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS							
80.00	<p>Point for the cor. of secs. 10, 11, 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 10px;">T 40 N</td> <td style="padding: 0 10px;">R 19 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 10</td> <td style="padding: 0 5px;">S 11</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 15</td> <td style="padding: 0 5px;">S 14</td> </tr> </table> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>West, bet. secs. 11 and 14.</p>	T 40 N	R 19 E	S 10	S 11	S 15	S 14
T 40 N	R 19 E						
S 10	S 11						
S 15	S 14						
0.50	Trail road, bears S. 60° E. and N. 60° W.						
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 10px;">T 40 N</td> <td style="padding: 0 10px;">R 19 E</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S 11</td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="border-top: 1px solid black; padding: 0 5px;">S 14</td> </tr> </table> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 40 N	R 19 E		S 11	1/4	S 14
T 40 N	R 19 E						
	S 11						
1/4	S 14						
55.40	El Capitan Wash, 80 ft. wide, 5 ft. deep, drains N. 25° E.						
77.55	Wash, 25 ft. wide, 3 ft. deep, drains N. 20° E.						
80.00	<p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, rolling. Soil, sand and sandy clay, Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 10 and 11.</p>						

**Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
23.55	Levee, 4 ft. wide, 15 ft. high, 60 ft. base, bears S. 85° E. and N. 85° W.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 40 N R 19 E 1/4 S 10 S 11 2010 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 2, 3, 10 and 11. Set a magnet in a white plastic case, 24 ins. below the surface of the ground. from which <div style="margin-left: 40px;"> A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 50°02' E., 88.00 ft. dist. with brass cap mkd. RM T40N R19E 88.0 FT. TO COR S2 2010 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 50°00' W., 110.0 ft. dist. with brass cap mkd. RM T40N R19E 110.0 FT TO COR S10 2010 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. </div>
	Cor. is located in El Capitan wash, 80 ft. wide, 5 ft. deep, drains N. 40° E. Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, Mormon Tea, yucca and native grasses.
	From the cor. of secs. 1 , 2, 11 and 12. West, bet. secs. 2 and 11.

**Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
37.05	Trail road, bears N. 25° E. and S. 25° W.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 40 N R 19 E S 2 1/4 ——— S 11 2010 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located 1.70 chs. E. of a trail road, bears S. 80° E. and N. 80° W.
80.00	The cor. of secs. 2, 3, 10 and 11. Land, rolling. Soil, sand and sandy clay. No timber; rabbit brush, sagebrush, Mormon Tea, yucca and native grasses.
	————— N. 0°01' W., bet. secs. 2 and 3.
	Over rolling land.
5.10	Trail road, bears S. 80° E. and N. 80° W.
21.30	El Capitan Wash, 80 ft. wide, 5 ft. deep, drains N. 45° W.
28.60	El Capitan Wash, 80 ft. wide, 5 ft. deep, drains N. 55° W.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 3. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 40 N R 19 E 1/4 S 3 S 2 2010 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
75.00	Trail road, bears N. 55° E. and S. 55° W.
80.01	<p>Point for the closing cor. of secs. 2 and 3, at intersection with the Tenth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 41 N R 19 E S 34</p> <hr style="width: 10%; margin: auto;"/> <p>S 3 S 2 T 40 N R 19 E CC</p> </div> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the stan. cor. of secs. 34 and 35, T. 41 N., R. 19 E., bears East, 15.19 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 41 N., R. 19 E., bears West, 24.81 chs. dist., hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay. No Timber; rabbit brush, sagebrush, Mormon Tea, yucca and native grasses.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>Point for the 1/4 sec. cor. of sec. 2 only, at midpoint on the N. bdy. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 41 N R 19 E</p> <hr style="width: 10%; margin: auto;"/> <p>1/4 S 2 T 40 N R 19 E</p> </div> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 35, T. 41 N., R. 19 E., bears East, 15.19 chs. dist., hereinbefore described.</p>

Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this same cor. point, the stan. cor. of secs. 34 and 35, T. 41 N., R. 19 E., bears West, 24.81 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of Tp., hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over rolling and broken land.</p>
11.70	Trail road, bears N. 35° E. and S. 35° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 40 N R 19 E 1/4 S 33 S 34</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 27, 28, 33 and 34.</p> <p>Set a brass tablet, 3 1/2 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, flush with the surface of a sandstone bedrock, with top mkd.</p> <div style="text-align: center;"> <p>T 40 N R 19 E S 28 S 27 S 33 S 34</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the brass tablet.</p> <p>Land, rolling and broken. Soil, sand and sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>West, bet. secs. 27 and 34.</p>

**Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rugged broken land.
23.90	Base of Tyende Mesa, bears S. 10° E. and N. 10° W.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> T 40 N R 19 E S 27 1/4 ——— S 34 2010 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
51.80	E. edge of Tyende Mesa, bears S. 40° E. and N. 40° W.
68.20	W. edge of Tyende Mesa, bears N. 15° E. and S. 15° W.
80.00	The cor. of secs. 27, 28, 33 and 34. Land, rugged and broken. Soil, sand and sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.
	————— N. 0°02' W., bet. secs. 27 and 28.
	Over rugged and broken land.
40.00	True point for the 1/4 sec. cor. of secs. 27 and 28, falls on the N. face of a vertical cliff, where it is impracticable to establish a monument. From this cor. point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 27 and 28, bears N. 45°00' E., 50 lks. dist. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> WC T 40 N R 19 E 1/4 S 28 S 27 ↓ 2010 </div>

**Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS																	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.																
63.40	Base of Tyende Mesa bears S. 30° E. and N. 30° W.																
80.00	The Point for the cor. of secs. 21, 22, 27 and 28.																
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.																
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T 40 N</td> <td colspan="2">R 19 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 21</td> <td style="border-right: 1px solid black;"></td> <td style="border-right: 1px solid black;">S 22</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black;">S 28</td> <td style="border-right: 1px solid black;"></td> <td style="border-right: 1px solid black;">S 27</td> <td></td> </tr> </table>	T 40 N		R 19 E		S 21		S 22		S 28		S 27					
T 40 N		R 19 E															
S 21		S 22															
S 28		S 27															
	2010																
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rugged and broken. Soil, sand and sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.																
	From the cor. of secs. 22, 23, 26 and 27.																
	West, bet. secs. 22 and 27.																
	Over rolling land.																
16.95	Trail road, bears N. 15° E. and S. 15° W.																
37.35	Trail road, bears S. 50° E. and N. 50° W.																
40.00	Point for the 1/4 sec. cor. of secs. 22 and 27.																
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.																
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T 40 N</td> <td colspan="2">R 19 E</td> </tr> <tr> <td colspan="2"></td> <td colspan="2">S 22</td> </tr> <tr> <td colspan="2"></td> <td colspan="2">1/4 ———</td> </tr> <tr> <td colspan="2"></td> <td colspan="2">S 27</td> </tr> </table>	T 40 N		R 19 E				S 22				1/4 ———				S 27	
T 40 N		R 19 E															
		S 22															
		1/4 ———															
		S 27															
	2010																
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.																
	Cor. is located 30 lks. dist., W. of a wash, drains N. 40° W.																
80.00	The cor. of secs. 21, 22, 27 and 28.																

Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 21 and 22.</p> <p>Over rolling land.</p>
35.70	BIA Route 6450, a graded road, 25 ft. wide, bears S. 85° E. and N. 85° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 40 N R 19 E 1/4 S 21 S 22</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
49.05	Power line, 2 lines, bears S. 75° E. and N. 75° W.
50.65	Wash, 10 ft. wide, 1 ft. deep, drains S. 45° E.
80.00	<p>Point for the cor. of secs. 15, 16, 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 40 N R 19 E S 16 S 15 S 21 S 22</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; rabbit brush, sagebrush, yucca and native grasses.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>West, bet. secs. 15 and 22.</p>

Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over, rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 40 N R 19 E S 15 1/4 ——— S 22 2010 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
42.00	Wash, 15 ft. wide, 2 ft. deep, drains N. 30° E.
80.00	The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, sand and sandy clay. No timber; rabbit brush, sagebrush, yucca, and native grasses.
	<hr/> N. 0°02' W., bet. secs. 15 and 16. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 40 N R 19 E 1/4 S 16 S 15 2010 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
50.65	Trail road, bears S. 70° E. and N. 70° W.
77.00	Wash, 25 ft. wide, 1 ft. deep, drains N. 30° E.
80.00	Point for the cor. of secs. 9, 10, 15 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 40 N R 19 E S 9 S 10 S 16 S 15
	2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling. Soil, sand and sandy clay. No timber; rabbit brush, sagebrush, Mormon Tea, yucca and native grasses.
	<hr/>
	From the cor. of secs. 10, 11, 14 and 15.
	West, bet. secs. 10 and 15.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 15.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 N R 19 E S 10 1/4 ——— S 15
	2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
78.20	Wash, 25 ft. wide, 1 ft. deep, drains N. 15° E.
80.00	The cor. of secs. 9, 10, 15 and 16.
	Land, rolling. Soil, sand and sandy clay. No timber; rabbit brush, sagebrush, Mormon Tea, yucca and native grasses.
	<hr/>
	N. 0°02' W., bet. secs. 9 and 10.
	Over rolling land.
40.00	The point for the 1/4 sec. cor. of secs. 9 and 10.

**Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 19 E 1/4 S 9 S 10</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 3, 4, 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 19 E S 4 S 3 S 9 S 10</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; rabbit brush, sagebrush, Mormon Tea, yucca and native grasses.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>West, bet. secs. 3 and 10.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 19 E S 3 1/4 ——— S 10</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; rabbit brush, sagebrush, Mormon Tea, yucca and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 3 and 4.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 19 E 1/4 S 4 S 3 2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.01	<p>Point for the closing cor. of secs. 3 and 4, at intersection with the Tenth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 19 E S 33 <hr/>S 4 S 3 T 40 N R 19 E CC 2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the stan. cor. of secs. 33 and 34, T. 41 N., R. 19 E., bears East, 15.18 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 33, T. 41 N., R. 19 E., bears West, 24.82 chs. dist., hereinbefore described.</p>

**Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. No timber; rabbit brush, sagebrush, Mormon Tea, yucca and native grasses.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 3 only, at midpoint on the N. bdy. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 19 E ----- 1/4 S 3 T 40 N R 19 E</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 41 N., R. 19 E., bears East, 15.185 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the stan. sec. cor. of secs. 33 and 34, T. 41 N., R. 19 E., bears West, 24.815 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of Tp., hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 32 and 33.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 19 E 1/4 S 32 S 33</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS							
80.00	<p>True point for cor. of secs. 28, 29, 32 and 33, falls on the N. face of a vertical cliff, where it is impracticable to establish a monument.</p> <p>From this true point, the point selected for a witness cor. to the cor. of secs. 28, 29, 32 and 33, bears N. 43°00' W., 0.50 chs. dist.</p> <p>Set a brass tablet, 3 1/2 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, flush with the surface of a sandstone bedrock, with top mkd.</p> <div style="text-align: center;"> <p>WC</p> <table style="margin: auto;"> <tr> <td>T 40 N</td> <td>R 19 E</td> </tr> <tr> <td>S 29</td> <td>S 28</td> </tr> <tr> <td>S 32</td> <td>S 33</td> </tr> </table> <p style="text-align: right;">↘</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the of the brass tablet.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>West, bet. secs. 28 and 33.</p> <p>Over extremely rugged terrain.</p>	T 40 N	R 19 E	S 29	S 28	S 32	S 33
T 40 N	R 19 E						
S 29	S 28						
S 32	S 33						
5.60	Rim of Tyende Mesa, bears N. 65° E. and S. 65° W., thence descend Tyende Mesa.						
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Cor. is located on the E. face of an inaccessible mesa, not monumented.</p>						
56.70	<p>Point selected for a witness point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>						

**Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	WP T 40 N R 19 E S 28 1/4 ——— S 33 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The true point for the cor. of secs. 28, 29, 32 and 33. Land, rugged. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.
	<hr/> N. 0°03' W., bet. secs. 28 and 29. Over extremely rugged terrain.
36.10	N. rim of Tyende Mesa, bears S. 80° E. and N. 80° W, thence descend Tyende Mesa.
40.00	True point for the 1/4 sec. cor. of secs. 28 and 29, falls on a steep slope of a vertical cliff, where it is impracticable to establish a monument. From this true point, the point selected for the witness cor. to the 1/4 sec. cor. of secs. 28 and 29, bears S. 45°04' W., 4.88 chs. dist. Set a brass tablet, 3 1/2 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, flush with the surface of sandstone bedrock, with top mkd.
	WC T 40 N R 19 E → 1/4 S 29 S 28
	2010
	Deposit a magnet, in a white plastic case, at the base of the brass tablet.
80.00	Point for the cor. of secs. 20, 21, 28 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<table style="margin: auto;"> <tr> <td>T 40 N</td> <td>R 19 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 20</td> <td>S 21</td> </tr> <tr> <td style="border-right: 1px solid black;">S 29</td> <td>S 28</td> </tr> </table>	T 40 N	R 19 E	S 20	S 21	S 29	S 28		
T 40 N	R 19 E								
S 20	S 21								
S 29	S 28								
	2010								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Land, rugged.								
	Soil, sandy clay with sandstone outcrops.								
	Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.								
	<hr/>								
	From the cor. of secs. 21, 22, 27 and 28.								
	West, bet. secs. 21 and 28.								
	Over rolling and broken land.								
37.90	W. bank of wash, 30 ft. wide, 20 ft. deep, drains N. 25° E.								
40.00	Point for the 1/4 sec. cor. of secs. 21 and 28.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto;"> <tr> <td>T 40 N</td> <td>R 19 E</td> </tr> <tr> <td></td> <td style="text-align: center;">S 21</td> </tr> <tr> <td></td> <td style="text-align: center;">1/4 ———</td> </tr> <tr> <td></td> <td style="text-align: center;">S 28</td> </tr> </table>	T 40 N	R 19 E		S 21		1/4 ———		S 28
T 40 N	R 19 E								
	S 21								
	1/4 ———								
	S 28								
	2010								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
80.00	The cor. of secs. 20, 21, 28 and 29.								
	Land rolling and broken.								
	Soil, sand and sandy clay.								
	Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.								
	<hr/>								
	N. 0°03' W., bet. secs. 20 and 21.								
	Over rolling land.								
40.00	Point for the 1/4 sec. cor. of secs. 20 and 21.								

**Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 19 E 1/4 S 20 S 21</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
57.20	BIA route 6450 a graded road, 20 ft. wide, bears S. 70° E. and N. 70° W.
69.25	Power line, 2 lines, bears S. 75° E. and N. 75° W.
80.00	Point for the cor. of secs. 16, 17, 20 and 21.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 19 E S 17 S 16 S 20 S 21</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca, and native grasses.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>West, bet. secs. 16 and 21.</p> <p>Over rolling land.</p>
31.95	Trail road, bears N. 25° E. and S. 25° W.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 21.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 40 N R 19 E S 16 1/4 ——— S 21 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 16, 17, 20 and 21. Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca, and native grasses.
	<hr/> N. 0°03' W., bet. secs. 16 and 17. Over rolling to rugged land.
6.10	Trail road, bears N. 65° E. and S. 65° W.
40.00	Point of the 1/4 sec. cor. of secs. 16 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T 40 N R 19 E 1/4 S 17 S 16 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 8, 9, 16 and 17. Cor. is located on the top of inaccessible Boot Mesa, not monumented. Land, rolling and rugged. Soil, sand and sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.
	<hr/> From the cor. of secs. 9, 10, 15 and 16. West, bet. secs. 9 and 16.

Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over, rugged and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 40 N R 19 E S 9 1/4 ——— S 16 2010 </div>
65.04	Point selected for a witness point, at the base of Boot Mesa, an inaccessible mesa. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> WP T 40 N R 19 E S 9 ————— S 16 2010 </div>
80.00	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. True point for the cor. of secs. 8, 9, 16 and 17. Land, rugged and broken. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses. <hr/>
	N. 0°03' W., bet. secs. 8 and 9. Over extremely rugged terrain.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 9. Cor. is located at the top of inaccessible Boot Mesa, not monumented.
54.68	Point selected for a witness point, at the base of Boot Mesa, an inaccessible mesa.

**Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a brass tablet, 3 1/2 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, flush with the surface of a sandstone boulder, 40 x 30 x 11 ft. high, with top mkd.</p> <p style="text-align: center;">WP T 40 N R 19 E S 8 S 9 2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the brass tablet.</p>
80.00	<p>Point for the cor. of secs. 4, 5, 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 19 E S 5 S 4 S 8 S 9 2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rugged. Soil, sand and sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>West, bet. secs. 4 and 9.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 19 E S 4 1/4 ——— S 9 2010</p>

Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 4, 5, 8 and 9. Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.
	N. 0°03' W., bet. secs. 4 and 5.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 N R 19 E 1/4 S 5 S 4 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
54.88	Mine Shaft, a 7 1/2 ins. opened end iron pipe, projecting 5 ft. above ground, bears East, 3.98 chs. dist.
80.02	Point for the closing cor. of secs. 4 and 5, at the intersection with the Tenth Standard Parallel North, on the N. bdy. of Tp. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 19 E S 32 ----- S 5 S 4 T 40 N R 19 E CC 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	From this cor. point, the stan. cor. of secs. 32 and 33, T. 41 N., R. 19 E., bears East, 15.17 chs. dist., hereinbefore described.

**Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 32, T. 41 N., R. 19 E., bears West, 24.83 chs. dist., hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; rabbit brush, sagebrush, yucca and native grasses.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 4 only, at midpoint on the N. bdy. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 19 E ----- 1/4 S 4 T 40 N R 19 E</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 33, T. 41 N., R. 19 E., bears East, 15.175 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the stan. cor. of secs. 32 and 33, T. 41 N., R. 19 E., bears West, 24.825 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over rolling land.</p>
38.30	Trail road, bears S. 65° E. and N. 65° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 19 E 1/4 S 31 S 32</p> <p style="text-align: center;">2010</p>

**Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
79.30	N. rim of Tyende Mesa, bears N. 80° E. and S. 80° W.
80.00	True point for the cor. of secs. 29, 30, 31 and 32, falls at the base of an inaccessible mesa, where it is impracticable to establish a monument.
	From this true point, the point selected for a witness cor. to the cor. of secs. 29, 30, 31 and 32, bears S. 42°00' E., 1.105 chs. dist.
	Set a brass tablet, 3 1/2 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, flush with the surface of a sandstone bedrock, with top mkd.
	<p style="text-align: center;">WC T 40 N R 19 E S 30 S 29 S 31 S 32</p>
	2010
	Deposit a magnet, in a white plastic case, at the base of the brass tablet.
	Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.
	From the true point for the cor. of secs. 28, 29, 32 and 33.
	West, bet. secs. 29 and 32.
	Over rugged and broken land.
11.00	W. rim of Tyende Mesa, bears S. 35° E. and N. 35° W.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 40 N R 19 E S 29 1/4 ——— S 32</p>
	2010

**Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The true point for the cor. of secs. 29, 30, 31 and 32. Land, rugged and broken. Soil, sand and sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.

	West, bet. secs. 30 and 31. Over rugged and broken land.
34.70	E. rim of Tyende Mesa, bears S. 45° E. and N. 45° W.
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31. Set a brass tablet, 3 1/2 ins. diam., 2 1/2 ins. stem., cemented in place, in a drill hole, flush with the surface of sandstone bedrock, with top mkd.
	T 40 N R 19 E S 30 1/4 ——— S 31 2010
	Deposit a magnet, in a white plastic case, at the base of the brass tablet.
44.10	W. rim of Tyende Mesa, bears N. 60° E. and S. 60° W.
78.27	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.

	From the cor. of secs. 29, 30, 31 and 32. N. 0°03' W., bet. secs. 29 and 30. Over extremely rugged and broken land.
40.00	True point for 1/4 sec. cor. of secs. 29 and 30, falls at the base of Laughing Canyon, where it is impracticable to establish a monument. From this true point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 29 and 30, bears N. 59°00' E., 4.90 chs. dist.

**Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>Set a brass tablet, 3 1/2 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, flush with the surface of sandstone bedrock, with top mkd.</p> <div style="text-align: center;"> <p>WC</p> <p>T 40 N R 19 E</p> <p>1/4</p> <p>↙ S 30 S 29</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the brass tablet.</p> <p>Point for the cor. of secs. 19, 20, 29 and 30.</p> <p>Set a brass tablet, 3 1/2 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, flush with the surface of a sandstone bedrock, with top mkd.</p> <div style="text-align: center;"> <p>T 40 N R 19 E</p> <p>S 19 S 20</p> <hr style="width: 50%; margin: 0 auto;"/> <p>S 30 S 29</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the brass tablet.</p> <p>Land, rugged and broken. Soil, sand and sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>West, bet. secs. 20 and 29.</p> <p>Over rugged and broken land.</p>
40.00	<p>True point for the 1/4 sec. cor. of secs. 20 and 29, falls in an inaccessible canyon, where it is impracticable to establish a monument.</p> <p>From the true point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 20 and 29, bears S. 10°48' E., 4.47 chs. dist.</p> <p>Set a brass tablet, 3 1/2 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, flush with the surface of a sandstone bedrock, with top mkd.</p>

Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	WC T 40 N R 19 E ↑ S 20 1/4 ——— S 29 2010 Deposit a magnet, in a white plastic case, at the base of the brass tablet.
56.60	Rim of canyon, bears S. 70° E. and N. 70° W.
80.00	The cor. of secs. 19, 20, 29 and 30. Land, rugged and broken. Soil, sand and sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.
	—————
	West, bet. secs. 19 and 30. Over, rugged and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30. Cor. is located on top of an inaccessible mesa, not monumented.
49.02	Point selected for a witness point, at the base of mesa. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	WP T 40 N R 19 E S 19 ——— S 30 2010 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
78.18	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described. Land, rugged and broken. Soil, sand and sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.
	—————

**Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p> <p>Over, rugged and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 19 E 1/4 S 19 S 20</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
42.95	<p>N. rim of Tyende Mesa, bears S. 85° E. and N. 85° W.</p>
80.00	<p>Point for the cor. of secs. 17, 18, 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 19 E S 18 S 17 S 19 S 20</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rugged and broken. Soil, sand and sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>West, bet. secs. 17 and 20.</p> <p>Over rolling land.</p>
24.75	<p>Trail road, bears N. 20° E. and S. 20° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p>

Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 19 E S 17 1/4 ——— S 20</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
42.75	Power line, 2 lines, bears S. 75° E. and N. 75° W.
57.15	BIA route 6450 a graded road, 20 ft. wide, bears S. 70° E. and N. 70° W.
80.00	<p>The cor. of secs. 17, 18, 19 and 20.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.</p> <hr/> <p>West, bet. secs. 18 and 19.</p> <p>Over rolling and broken land.</p>
10.45	Trail road, bears N. 85° E. and S. 85° W.
27.95	Oljeto Wash, 10 ft. wide, 6 ft. deep, drains N. 15° E.
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 19 E S 18 1/4 ——— S 19</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 1.00 chs. dist., W. of a fence line, enclosing a cultivated field, 5 strand barbed wire, bears S. 70° E. and N. 70° W.</p>

**Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
43.70	W. fence line of a cultivated field, 5 strand barbed wire, bears N. 20° E. and S. 20° W.
51.45	Trail road, bears N. 40° E. and S. 40° W.
78.09	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described. Land, rolling and broken. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.
	From the cor. of secs. 17, 18, 19 and 20. N. 0°03' W., bet. secs. 17 and 18. Over, rolling and broken land.
4.35	Trail road, bears N. 75° E. and S. 75° W.
4.75	Trail road, bears S. 85° E. and N. 85° W.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 40 N R 19 E 1/4 S 18 S 17 2010 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
44.90	BIA route 6450 a graded road, 20 ft. wide, bears S. 10° E. and N. 10° W.
50.10	Power line, 2 lines, bears S. 15° E. and N. 15° W.
80.00	Point for the cor. of secs. 7, 8, 17 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 40 N R 19 E S 7 S 8 S 18 S 17 2010 </div>

**Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.</p> <hr/> <p>From the true point for the cor. of secs. 8, 9, 16 and 17.</p> <p>West, bet. secs. 8 and 17.</p> <p>Over extremely rugged land.</p>
33.35	Base of Boot Mesa, 800 ft. high, bears S. 30° E. and N. 30° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 40 N R 19 E</p> <p>S 8</p> <p>1/4 ———</p> <p>S 17</p> <p>2010</p> </div>
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, rugged and broken. Soil, sand and sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.</p> <hr/> <p>West, bet. secs. 7 and 18.</p> <p>Over rugged and broken land.</p>
7.90	Power line, 2 lines, bears S. 20° E. and N. 20° W.
9.10	BIA route 6450 a graded road, 20 ft. wide, bears S. 20° E. and N. 20° W.
35.30	Oljeto Wash, 25 ft. wide, 5 ft. deep, drains N. 35° W.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18.

Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 19 E S 7 1/4 ——— S 18</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
56.40	Base of Azansosi Mesa, 1000 ft. high, bears S. 40° E. and N. 40° W.
66.50	E. rim of Azansosi Mesa, 500 ft. high, bears N. and S.
78.01	The true point for the cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.
	<p>Land, rugged. Soil, sand and sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18. N. 0°03' W., bet. secs. 7 and 8. Over rolling and broken land.</p>
6.55	Trail road, bears S. 75° E. and N. 75° W.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 8.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 19 E 1/4 S 7 S 8</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	Point for the cor. of secs. 5, 6, 7 and 8.

Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>										
	<table border="1"> <tr> <td>T 40 N</td> <td>R 19 E</td> </tr> <tr> <td>S 6</td> <td>S 5</td> </tr> <tr> <td>S 7</td> <td>S 8</td> </tr> </table>	T 40 N	R 19 E	S 6	S 5	S 7	S 8				
T 40 N	R 19 E										
S 6	S 5										
S 7	S 8										
	2010										
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>										
	<p>Land, rugged and rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.</p>										
	<hr/>										
	<p>From the cor. of secs. 4, 5, 8 and 9.</p>										
	<p>West, bet. secs. 5 and 8.</p>										
	<p>Over rugged and broken land.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p>										
	<p>Cor. is located on top of Boot Mesa, an inaccessible mesa, not monumented.</p>										
50.00	<p>Point selected for a witness point, at the base of Boot Mesa.</p>										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										
	<table border="1"> <tr> <td colspan="2" style="text-align: center;">WP</td> </tr> <tr> <td>T 40 N</td> <td>R 19 E</td> </tr> <tr> <td>S 5</td> <td></td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td>S 8</td> <td></td> </tr> </table>	WP		T 40 N	R 19 E	S 5		-----		S 8	
WP											
T 40 N	R 19 E										
S 5											

S 8											
	2010										
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>										
80.00	<p>The cor. of secs. 5, 6, 7 and 8.</p>										
	<p>Land, rugged and broken. Soil, sand and sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, rabbit brush, sagebrush, yucca and native grasses.</p>										
	<hr/>										

**Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	West, bet. secs. 6 and 7.
	Over rolling and broken land.
24.95	Power line, 2 lines, bears N. and S.
28.25	Graded road, 20 ft. wide, bears N. 5° E. and S. 5° W.
35.60	Oljeto Wash, 35 ft. wide, 3 ft. deep, drains N. 10° E.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 7.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 N R 19 E S 6 1/4 ——— S 7 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located 2.5 lks. dist., W. of the fence line of an abandoned field, bears N. 10° E. and S. 10° W.
52.65	Fence line of an abandoned field, 4 strand barbed wire, bears N. and S.
56.55	Trail road, bears N. 50° E. and S. 50° W.
58.85	Graded road, 25 ft. wide, bears S. 30° E. and N. 30° W.
77.92	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.
	Land, rolling and broken. Soil, sand and sandy clay. No timber; rabbit brush, sagebrush, yucca and native grasses.
	From the cor. of secs. 5, 6, 7 and 8.
	N. 0°03' W., bet. secs. 5 and 6.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 6.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 40 N R 19 E 1/4 S 6 S 5 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
68.30	Graded road, 20 ft. wide, bears N. 50° E. and S. 50° W.
80.02	Point for the closing cor. of secs. 5 and 6, at intersection with the Tenth Standard Parallel North, on the N. bdy. of Tp.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 19 E S 31 ----- S 6 S 5 T 40 N R 19 E CC 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located on top of a levee, 3 ft. wide, 10 ft. base, 5 ft. high.
	From this cor. point, the stan. cor. of secs. 31 and 32, T. 41 N., R. 19 E., bears East, 15.17 chs. dist., hereinbefore described.
	From this same cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 41 N., R. 19 E., bears West, 24.83 chs. dist., hereinbefore described.
	Land, rolling. Soil, sand and sandy clay. No Timber; rabbit brush, sagebrush, yucca and native grasses.
	Point for the 1/4 sec. cor. of sec. 5 only, at midpoint on the N. bdy. of sec. 5.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 41 N R 19 E

1/4 S 5

T 40 N R 19 E

2010

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 32, T. 41 N., R. 19 E., bears East, 15.17 chs. dist., hereinbefore described.

From this same cor. point, the stan. cor. of secs. 31 and 32, T. 41 N., R. 19 E., bears West, 24.83 chs. dist., hereinbefore described.

Point for the 1/4 sec. cor. of sec. 6 only, T 40 N., R. 19 E., at 40.00 chs. in westing from the closing cor. of secs. 5 and 6, on the N. bdy. of sec. 6.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 41 N R 19 E

1/4 S 6

T 40 N R 19 E

2010

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 41 N., R. 19 E., bears East, 15.17 chs. dist., hereinbefore described.

From this same cor. point, the stan. cor. of Tps. 41 N., Rs. 18 and 19 E., bears West, 24.83 chs. dist., hereinbefore described.

**Subdivision of Section 1,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

From the 1/4 sec. cor. of secs. 1 and 12.

North, on the N and S. center line of sec. 1.

**Subdivision of Section 1,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over nearly level to rolling land.
40.00	Point for the center 1/4 sec. cor. of sec. 1, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 N R 19 E C 1/4 S 1 2010 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
70.25	Graded road, 20 ft. wide, bears S. 75° E. and N. 75° W.
80.01	The 1/4 sec. cor. of sec. 1 only, on the N. bdy. of sec. 1.
	<hr/>
	From the 1/4 sec. cor. of secs. 1 and 6, Tps. 40 N., Rs. 19 and 20 E., on the E. bdy. of Tp., monumented with a stainless steel post, firmly set, projecting 3 ins. above ground, with brass cap mkd. T40N R19E R20E 1/4 S1 S6 2008. Add the marks 2010 to the brass cap. West, on the E. and W. center line of sec. 1.
8.45	E. right-of-way fence of U. S. Highway 163, 5 strand barbed wire, parallels highway.
9.70	U.S. Highway 163, asphalt surface, 30 ft. wide, bears N. 25° E. and S. 25° W.
10.90	W. right-of-way fence of U. S Highway 163, 5 strand barbed wire, parallels highway.
40.00	The center 1/4 sec. cor. of sec. 1.
80.00	The 1/4 sec. cor. of secs. 1 and 2.
	<hr/>
	Subdivision of Section 12, T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona
	<hr/>
	From the 1/4 sec. cor. of secs. 12 and 13. North, on the N. and S. center line of sec. 12. Over rolling land.

**Subdivision of Section 12,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.45	Power line, 2 lines, bears S. 75° E. and N. 75° W.
40.00	Point for the center 1/4 sec. cor. of sec. 12, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 N R 19 E C 1/4 S 12 2010 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
42.05	Graded road, 30 ft. wide, bears S. 70° E. and N. 70° W.
80.00	The 1/4 sec. cor. of secs. 1 and 12.
	<hr/>
	From the 1/4 sec. cor. of secs. 7 and 12, Tps. 40 N., Rs. 19 and 20 E., on the E. bdy. of Tp., monumented with a stainless steel post, firmly set, projecting 3 ins above ground, with brass cap mkd. T40N R19E R20E 1/4 S12 S7 2008. Add the marks 2010 to the brass cap. West, on the E. and W. center line of sec. 12. Over rolling land.
40.00	The center 1/4 sec. cor. of sec. 12.
49.75	E. right-of-way fence of U. S. Highway 163, 5 strand barbed wire, parallels highway.
51.00	U.S. Highway 163, asphalt surface, 30 ft wide, bears N. 25° E. and S. 25° W.
52.30	W. right-of-way fence of U. S. Highway 163, 5 strand barbed wire, parallels highway.
80.00	The 1/4 sec. cor. of secs. 11 and 12.
	<hr/>
	Subdivision of Section 13, T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona
	<hr/>
	From the 1/4 sec. cor. of secs. 13 and 24. North, on the N. and S. center line of sec. 13.

**Subdivision of Section 13,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rugged and broken land.
40.00	Point for the center 1/4 sec. cor. of secs. 13, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in bedrock, with brass cap mkd. T 40 N R 19 E C 1/4 S 13 2010 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The 1/4 sec. cor. of secs. 12 and 13. <hr/>
	From the 1/4 sec. cor. of secs. 13 and 18, Tps. 40 N., Rs. 19 and 20 E., on the E. bdy. of the Tp., monumented with a stainless steel post, projecting 2 ins. above the ground, encircled in an embedded mound of stone, 3 ft. base to top, with brass cap mkd. T40N R19E R20E 1/4 S13 S18 2008. Add the marks 2010 to brass cap. West, on the E. and W. center line of sec. 13.
40.00	The center 1/4 sec. cor. of sec. 13.
80.00	The 1/4 sec. cor. of secs. 13 and 14. <hr/>
	Subdivision of Section 14, T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 14 and 23. N. 0°01' W., on the N. and S. center line of sec. 14. Over rolling land.
40.00	Point for the center 1/4 sec. cor. of secs. 14, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Subdivision of Section 14,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 40 N R 19 E C 1/4 S 14
	2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The 1/4 sec. cor. of secs. 11 and 14.
	<hr/>
	From the 1/4 sec. cor. of secs. 13 and 14.
	West, on the E and W. center line of sec. 14.
	Over rolling land.
12.00	E. right-of-way fence of U. S. Highway 163, 5 strand barbed wire, parallels highway.
13.30	U.S. Highway 163, asphalt surface, 30 ft. wide, bears N. 30° E. and S. 30° W.
14.60	W. right-of-way fence of U. S. Highway 163, 5 strand barbed wire, parallels highway.
15.70	Power line, 4 lines, bears N. 30° E. and S. 30° W.
40.00	The center 1/4 sec. cor. of sec. 14.
80.00	The 1/4 sec. cor. of secs. 14 and 15.
	<hr/>
	Subdivision of Section 23, T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona
	<hr/>
	From the 1/4 sec. cor. of secs. 23 and 26.
	N. 0°01' W., on the N. and S. center line of secs. 23.
	Over rolling and broken land.
40.00	Point for the center 1/4 sec. cor. of sec. 23, at the intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 N R 19 E C 1/4 S 23
	2010

**Subdivision of Section 23,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
66.95	E. right-of-way fence of U. S. Highway 163, 5 strand barbed wire, parallels highway.
69.45	U.S. Highway 163, asphalt surface, 30 ft. wide, N. 25° E. and S. 25° W.
71.95	W. right-of-way fence of U. S. Highway 163, 5 strand barbed wire, parallels highway.
73.80	Power line, 4 lines, bears N. 25° E. and S. 25° W.
80.00	The 1/4 sec. cor. of secs. 14 and 23.
<hr/>	
	From the 1/4 sec. cor. of secs. 23 and 24.
	West, on the E. and W. center line of sec. 23.
	rolling and broken land.
40.00	The center 1/4 sec. cor. of sec. 23.
53.70	E. right-of-way fence of U. S. Highway 163, 5 strand barbed wire, parallels highway.
54.95	U.S Highway 163, asphalt surface, 30 ft. wide, bears N. 25° E. and S. 25° W.
56.80	W. right-of-way fence of U. S. Highway 163, 5 strand barbed wire, parallels highway.
80.00	The 1/4 sec. cor. of secs. 22 and 23.
<hr/>	
Subdivision of Section 26, T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona	
<hr/>	
	From the 1/4 sec. cor. of secs. 26 and 35.
	N. 0°01' W., on the N. and S. center line of sec. 26.
	Over rolling and broken land.
1.85	Power line, 4 lines, bears S. 65° E. and N. 65° W.
3.05	S. right-of-way of U. S. Highway 163, 5 strand barbed wire, parallels highway.

Subdivision of Section 26,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
4.25	U. S. Highway 163, asphalt surface, 30 ft. wide, bears S. 75° E. and N. 75° W.
5.40	N. right-of-way of U. S. Highway 163, 5 strand barbed wire, parallels highway.
40.00	Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E. and W. center line. Set a brass tablet, 3 1/2 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, flush with the surface of sandstone bedrock, with top mkd. T 40 N R 19 E C 1/4 S 26 2010 Deposit a magnet, in a white plastic case, at the base of the brass tablet.
80.00	The 1/4 sec. cor. of secs. 23 and 26. <hr/> From the 1/4 sec. cor. of secs. 25 and 26. West, on the E. and W. center line of sec. 26. Over rolling and broken land.
25.50	E. rim of El Capitan Wash, 1000 ft. wide, 500 ft. deep, drains N. 55° W.
29.40	W. rim of El Capitan Wash, 1000 ft. wide, 500 ft. deep, drains N. 55° W.
40.00	The center 1/4 sec. cor. of sec. 26.
51.50	Wash, 25 ft. wide, 5 ft. deep, drains N. 50° W.
66.40	E. right-of-way of U. S. Highway 163, 5 strand barbed wire, parallels, highway.
67.70	U. S. Highway 163, asphalt surface, 30 ft. wide, bears S. 30° E. and N. 30° W.
69.10	W. right-of-way of U. S. Highway 163, 5 strand barbed wire, parallels highway.
69.20	Trail road, bears S. 35° E. and N. 35° W.
69.90	Power line, 4 lines, bears S. 30° E. and N. 30° W.

Subdivision of Section 26,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	The 1/4 sec. cor. of secs. 26 and 27.
	<hr/> <p>Subdivision of Section 35, T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona</p> <hr/>
	From the 1/4 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp, hereinbefore described.
	N. 0°01' W., on the N. and S. center line of sec. 35.
	Over rugged and broken land.
40.00	Point for the center 1/4 sec. cor. of sec. 35, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 40 N R 19 E C 1/4 S 35</p> <p>2010</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The 1/4 sec. cor. of secs. 26 and 35.
	<hr/>
	From the 1/4 sec. cor. of secs. 35 and 36.
	West, on the E. and W. center line of sec. 35.
	Over rugged and broken land.
40.00	The center 1/4 sec. cor. of sec. 35.
80.00	The true point for the 1/4 sec. cor. of secs. 34 and 35.
	<hr/>

Subdivision of Section 36,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	Subdivision of Section 36, T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona
	<p>From the 1/4 sec. cor. of secs. 1 and 36, on the S. bdy. of the TP., hereinbefore described.</p> <p>North, on the N. and S. center line of sec. 36.</p> <p>Over rolling and broken land.</p>
29.55	Power line, 4 lines, bears S. 40° E. and N. 40° W.
36.15	S. right-of-way fence of U. S. Highway 163, 5 strand barbed wire, parallels highway.
38.10	U. S. Highway 163, asphalt surface, 30 ft. wide, bears S. 40° E and N. 40° W.
39.90	N. right-of-way fence of U. S. Highway 163, 5 strand barbed wire, parallels highway.
40.00	Point for the center 1/4 sec. cor. of sec. 36, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 N R 19 E C 1/4 S 36
	2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The 1/4 sec. cor. of secs. 25 and 36.
	<p>From the 1/4 sec. cor. of secs. 31 and 36, Tps. 40 N., Rs. 19 and 20 E., on the E. bdy. of the Tp., monumented with a stainless steel post, firmly set, projecting 2 ins. above ground, with a mound of stone, 4 ft. base to top, with brass cap mkd. T40N R19E R20E 1/4 S36 S31 2008.</p> <p>Add the marks 2010 to the brass cap.</p> <p>West, on the E. and W. center line of sec. 36.</p>
22.95	Graded road, 30 ft. wide, bears N. 15° E. and S. 15° W.
37.15	Graded road, 25 ft. wide, bears N. 5° E. and S. 5° W.

Subdivision of Section 36,
T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
37.50	Trail road, bears S. 45° E. and N. 45° W.
40.05	E. right-of-way fence of U. S. Highway 163, 5 strand barbed wire, parallels highway.
40.75	Wash, 10 ft. wide, 6 ft. deep, drains N. 20° W.
41.60	U. S. Highway 163, asphalt surface, 30 ft. wide, bears S. 45° E. and N. 45° W.
43.20	W. right-of-way fence of U. S. Highway 163, 5 strand barbed wire, parallels highway.
50.05	Power line, 4 lines, bears S. 40° E. and N. 40° W.
80.00	The 1/4 sec. cor. of secs. 35 and 36.
<hr/> GENERAL DESCRIPTION <hr/>	
<p>The area surveyed is within the Navajo Indian Reservation and approximately 6 miles NNW of Kayenta, Az. The land is rolling, broken and extremely rugged. The southerly portion of the township is encompassed by the Tyende Mesa and the easterly portion of the township is encompassed by the Azansosi Mesa which consists of steep canyons. The drainage is NW with Oljeto Wash and El Capitan wash being the principal drainage.</p>	
<p>The elevation varies from 5000 ft. to 6500 feet. The soil is sand and sandy clay with sandstone outcrops. There is a moderate stand of juniper on the Tyende Mesa and throughout the township. Undergrowth principally consists of rabbit brush, sagebrush, Mormon Tea, yucca and native grasses.</p>	
<p>The principal access to the township is provided by Arizona State Highway 163, which enters the township in section 36 and extends northeasterly and exits in section 1. BIA Routes 6450, 6420, and 6430, all graded roads provide additional access. There are trail roads scattered throughout most of the township. There are numerous permanent residential homes throughout the township. Much of the area is used for grazing livestock. There is no mining activity in this township.</p>	
<p>The mean magnetic declination of 11° E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2010 for the dates of survey.</p> <hr/>	

CERTIFICATE OF SURVEY

I, Alvina A. Begaye, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 25th, day of January, 2010, I have surveyed a portion of the Tenth Standard Parallel North (north boundary), the south and west boundaries and the subdivisional lines, and subdivided certain sections, T. 40 N., R. 19 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

04/07/2011

(Date)

Alvina A. Begaye

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the survey of a portion of the Tenth Standard Parallel North (north boundary), the south and west boundaries and the subdivisional lines, and the subdivision of certain sections, T. 40 N., R. 19 E., Gila and Salt River Meridian, in the State of Arizona, executed by Alvina A. Begaye, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

6/2/2011

(Date)

Danny J. West

(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 40 N., R. 19 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~