

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
ESTABLISHMENT OF THE NORTHEAST TOWNSHIP CORNER
THE SURVEY OF THE WEST BOUNDARY
A PORTION OF THE NORTH BOUNDARY
A PORTION OF THE SUBDIVISIONAL LINES
AND
THE SUBDIVISION OF CERTAIN SECTIONS
TOWNSHIP 38 NORTH, RANGE 11 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

Fabian Yazzie, Cadastral Surveyor

Under Special Instructions dated October 5, 2012, approved October 5, 2012, which provided for the surveys included under Group No. 1106, and assignment instructions dated October 5, 2012.

Survey commenced October 23, 2012

Survey completed January 8, 2013

INDEX DIAGRAM

TOWNSHIP 38 NORTH RANGE 11 EAST
 GILA & SALT RIVER MERIDIAN, ARIZONA

| | | | | | |
|------|-------|-------|-------|----|----|
| 12 | 11 | 9 | | | 10 |
| 8 6 | 38 5 | 25 4 | 17 3 | 2 | 1 |
| 37 | 36 | 25 | | | |
| 8 7 | 36 8 | 24 9 | 17 10 | 11 | 12 |
| 35 | 34 | 23 | | | |
| 7 18 | 33 17 | 23 16 | 16 15 | 14 | 13 |
| 33 | 32 | 22 | | | |
| 6 19 | 31 20 | 21 21 | 15 22 | 23 | 24 |
| 30 | 30 | 21 | | | |
| 5 30 | 29 29 | 20 28 | 14 27 | 26 | 25 |
| 28 | 27 | 19 | | | |
| 4 31 | 26 32 | 18 33 | 13 34 | 35 | 36 |

Subdivision of Section 18 Pages 38-39
 Subdivision of Section 19 Pages 39-40
 Subdivision of Section 29 Pages 40-41
 Subdivision of Section 30 Pages 41-42
 Subdivision of Section 32 Pages 43-44
 Subdivision of Section 33 Pages 44-44

T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the establishment of the northeast township corner, the survey of the west boundary, a portion of the north boundary, and a portion of the subdivisional lines, and the subdivision of certain sections, Township 38 North, Range 11 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Geoffrey A. Graham surveyed the west and north boundaries of Township 37 North, Range 12 East in 2007-08. Fabian Yazzie surveyed the north boundary of Township 37 North, Range 11 East, under Group No. 1105, in 2012.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and the Special Instructions dated October 5, 2012, for Group Number 1106, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation R8 and 5700 model receivers.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) DK8419 AZPG CITY OF PAGE CORS, AI8805 FRED FREDONIA CORS, DI2245 P011 SPIDERROCKAZ2005 CORS, DJ8981 FST5 FLAGSTAFF 5 CORS, DN7504 SGU1 ST GEORGE PUTIL CORS, DI2242 P009 MARYSVALE_UT2006 CORS, DI3419 PO12 MONTICELLOUT2006 CORS, and DL1898 AZPS PRESCOTT CO. The NAD 83 (2011) (EPOCH: 2010), geographic position of the corner of Townships 38 and 39 North, Ranges 10 and 11 East, is as follows:

Latitude: 36°43'45.962" N. Longitude: 111°15'47.196" W.

The geographic position of the corner of Townships 37 and 38 North, Ranges 11 and 12 East, is as follows:

Latitude: 36°38'32.797" N. Longitude: 111°09'19.027" W.

The mean magnetic declination is 11° E.

Survey of the West Boundary,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Beginning at the cor. of Tps. 37 and 38 N., Rs. 10 and 11 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T38N R10E R11E S36 S31 S1 S6 T37N 2012.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over gently rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 38 N</p> <p>R 10 E R 11 E</p> <p>1/4</p> <p>S 36 S 31</p> <p>2012</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> |
| 80.00 | <p>Point for the cor. of secs. 25, 30, 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 38 N</p> <p>R 10 E R 11 E</p> <p>S 25 S 30</p> <p>S 36 S 31</p> <p>2012</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 48 lks. S. and 60 lks. W. of the W. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad, and 1.55 chs. S. and 1.85 chs. W. of the centerline of the Black Mesa and Lake Powell Railroad, 5 ft. bet. rails, bears S. 50° E. and N. 50° W., and 2.55 chs. S. and 2.95 chs. W. of the E. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.</p> |

Survey of the West Boundary,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS

Land, gently rolling.
Soil, sandy loam and sandstone rock outcrops.
Timber, scattered juniper.
Undergrowth, native grasses, salt brush and Mormon tea.

North, bet. secs. 25 and 30.

Over gently rolling land.

40.00 Point for the 1/4 sec. cor. of secs. 25 and 30.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

| | |
|--------|--------|
| T 38 N | |
| R 10 E | R 11 E |
| 1/4 | |
| S 25 | S 30 |

2012

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Set a steel fence post nearby.

Cor. is located 3.10 chs. W. of a barbed wire fence, bears
N. 10° E. and S. 10° W.

80.00 Point for the cor. of secs. 19, 24, 25 and 30.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

| | |
|--------|--------|
| T 38 N | |
| R 10 E | R 11 E |
| S 24 | S 19 |
| S 25 | S 30 |

2012

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Set a steel fence post nearby.

Land, gently rolling.
Soil, sandy loam and sandstone rock outcrops.
Timber, scattered juniper.
Undergrowth, native grasses, salt brush and Mormon tea.

Survey of the West Boundary,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | |
|--------|---|--------|--|--------|--------|------|------|------|------|
| | North, bet. secs. 19 and 24. | | | | | | | | |
| | Over gently rolling land. | | | | | | | | |
| 22.30 | Power line, 2 strand, bears N. 50° E. and S. 50° W. | | | | | | | | |
| 40.00 | Point for the 1/4 sec. cor. of secs. 19 and 24. | | | | | | | | |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd. | | | | | | | | |
| | <table style="margin: auto;"> <tr><td colspan="2">T 38 N</td></tr> <tr><td>R 10 E</td><td>R 11 E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="border-right: 1px solid black;">S 24</td><td>S 19</td></tr> </table> | T 38 N | | R 10 E | R 11 E | 1/4 | | S 24 | S 19 |
| T 38 N | | | | | | | | | |
| R 10 E | R 11 E | | | | | | | | |
| 1/4 | | | | | | | | | |
| S 24 | S 19 | | | | | | | | |
| | 2012 | | | | | | | | |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. | | | | | | | | |
| | Set a steel fence post nearby. | | | | | | | | |
| | Cor. is located 1.35 chs. S. of a barbed wire fence, bears N. 75° E. and S. 75° W. | | | | | | | | |
| 80.00 | Point for the cor. of secs. 13, 18, 19 and 24. | | | | | | | | |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. | | | | | | | | |
| | <table style="margin: auto;"> <tr><td colspan="2">T 38 N</td></tr> <tr><td>R 10 E</td><td>R 11 E</td></tr> <tr><td style="border-right: 1px solid black;">S 13</td><td>S 18</td></tr> <tr><td style="border-right: 1px solid black;">S 24</td><td>S 19</td></tr> </table> | T 38 N | | R 10 E | R 11 E | S 13 | S 18 | S 24 | S 19 |
| T 38 N | | | | | | | | | |
| R 10 E | R 11 E | | | | | | | | |
| S 13 | S 18 | | | | | | | | |
| S 24 | S 19 | | | | | | | | |
| | 2012 | | | | | | | | |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. | | | | | | | | |
| | Land, gently rolling. Soil, sandy loam. Timber, sparse juniper. Undergrowth, native grasses, rabbit brush and Mormon tea. | | | | | | | | |
| | North, bet. secs. 13 and 18. | | | | | | | | |
| | Over gently rolling land. | | | | | | | | |

Survey of the West Boundary,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 38 N</p> <p>R 10 E R 11 E</p> <p>1/4</p> <p>S 13 S 18</p> <p>2012</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> |
| 57.20 | <p>W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.</p> |
| 60.70 | <p>State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 25° E. and N. 25° W.</p> |
| 64.20 | <p>E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.</p> |
| 80.00 | <p>Point for the cor. of secs. 7, 12, 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 38 N</p> <p>R 10 E R 11 E</p> <p>S 12 S 7</p> <p>S 13 S 18</p> <p>2012</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, gently rolling and nearly level. Soil, sandy loam. No timber. Undergrowth, native grasses, rabbit brush and Mormon tea.</p> <hr/> <p>North, bet. secs. 7 and 12.</p> <p>Over nearly level land.</p> |

Survey of the West Boundary,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | |
|--------|---|--------|--|--------|--------|-----|-----|------|-----|
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 38 N</td></tr> <tr><td>R 10 E</td><td>R 11 E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S 12</td><td>S 7</td></tr> </table> <p>2012</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> | T 38 N | | R 10 E | R 11 E | 1/4 | | S 12 | S 7 |
| T 38 N | | | | | | | | | |
| R 10 E | R 11 E | | | | | | | | |
| 1/4 | | | | | | | | | |
| S 12 | S 7 | | | | | | | | |
| 80.00 | <p>Point for the cor. of secs. 1, 6, 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 38 N</td></tr> <tr><td>R 10 E</td><td>R 11 E</td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td>S 12</td><td>S 7</td></tr> </table> <p>2012</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, gently rolling and nearly level. Soil, sandy loam. No timber. Undergrowth, native grasses, rabbit brush and Mormon tea.</p> <hr/> <p>North, bet. secs. 1 and 6.</p> <p>Over nearly level land.</p> | T 38 N | | R 10 E | R 11 E | S 1 | S 6 | S 12 | S 7 |
| T 38 N | | | | | | | | | |
| R 10 E | R 11 E | | | | | | | | |
| S 1 | S 6 | | | | | | | | |
| S 12 | S 7 | | | | | | | | |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> | | | | | | | | |

**Survey of the West Boundary,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 38 N
R 10 E | R 11 E
1/4
S 1 | S 6

2012

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

80.00 Point for the cor. of Tps. 38 and 39 N., Rs. 10 and 11 E.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 39 N
R 10 E | R 11 E
S 36 | S 31
S 1 | S 6
T 38 N

2012

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

Land, gently rolling and nearly level.

Soil, sandy loam.

No timber.

Undergrowth, native grasses, rabbit brush and Mormon tea.

**Survey of a Portion of the North Boundary,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona**

From the point for the cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., established West, 240.00 chs. from the cor. of Tps. 38 and 39 N., Rs. 11 and 12 E.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of a Portion of the North Boundary,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS

| | |
|--------|--------|
| T 39 N | R 11 E |
| S 33 | S 34 |
| S 4 | S 3 |
| T 38 N | |

2012

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

From this cor. point, the point for the cor. of Tps. 38 and 39 N., Rs. 11 and 12 E., bears East, 240.00 chs. dist., established, North, 480.00 chs., from the cor. of Tps. 37 and 38 N., Rs. 11 and 12 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T38N R11E R12E S36 S31 S1 S6 T37N 2007 2012.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

| | |
|--------|--------|
| T 39 N | |
| R 11 E | R 12 E |
| S 36 | S 31 |
| S 1 | S 6 |
| T 38 N | |

2012

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

Cor. is located 79 lks. S. and 1.30 chs. W. of high voltage transmission line, bears S. 60° E. and N. 60° W.

West, bet. secs. 4 and 33.

Over nearly level land.

40.00

Point for the 1/4 sec. cor. of secs. 4 and 33.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

Survey of a Portion of the North Boundary,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | T 39 N R 11 E S 33 1/4 ——— S 4 T 38 N 2012 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. |
| 80.00 | Point for the cor. of secs. 4, 5, 32 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 39 N R 11 E S 32 S 33 ——— ——— S 5 S 4 T 38 N </div> 2012 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. Land, rolling. Soil, sandy loam and sandstone rock outcrops. Timber, scattered juniper. Undergrowth, native grasses, salt brush and Mormon tea. |
| | <hr/> West, bet. secs. 5 and 32. Over rolling land. |
| 35.05 | Dirt road, 11 ft. wide, bears N. 10° E. and S. 10° W. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 5 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |

**Survey of a Portion of the North Boundary,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona**

| CHAINS | |
|--------|--|
| | T 39 N R 11 E S 32 1/4 ——— S 5 T 38 N 2012 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, N. of cor. |
| 80.00 | Point for the cor. of secs. 5, 6, 31 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. |
| | T 39 N R 11 E S 31 S 32 S 6 S 5 T 38 N 2012 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Set a steel fence post nearby. |
| | Cor. is located 38 lks. S. of a trail road, bears N. 70° E. and N. 60° W. |
| | Land, gently rolling and nearly level. Soil, sandy loam. No timber. Undergrowth, native grasses, salt brush and Mormon tea. |
| | <hr/> West, bet. secs. 6 and 31. |
| | Over rolling land. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 6 and 31. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |

**Survey of a Portion of the North Boundary,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona**

| CHAINS | |
|--|---|
| | T 39 N R 11 E S 31 1/4 ——— S 6 T 38 N 2012 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. |
| 78.91 | The cor. of Tps. 38 and 39 N., Rs. 10 and 11 E., hereinbefore described. Land, nearly level to gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, salt brush and Mormon tea. |
| <hr/> Survey of a Portion of the Subdivisional Lines, T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona <hr/> | |
| | From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. T38N R11E S33 S34 S4 S3 T37N 2012. N. 0°02' W., bet. secs. 33 and 34. Over rolling land. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 33 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T 38 N R 11 E 1/4 S 33 S 34 2012 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. |
| 80.00 | Point for the cor. of secs. 27, 28, 33 and 34. |

Survey of a Portion of the Subdivisional Lines,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
25 ins. in the ground, with brass cap mkd.

| | |
|--------|--------|
| T 38 N | R 11 E |
| S 28 | S 27 |
| S 33 | S 34 |

2012

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Set a steel fence post nearby.

Land, rolling.

Soil, sandy loam.

Timber, juniper and piñon.

Undergrowth, native grasses, salt brush, yucca and Mormon tea.

N. 0°02' W., bet. secs. 27 and 28.

Over rolling land.

40.00

Point for the 1/4 sec. cor. of secs. 27 and 28.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
26 ins. in the ground, with brass cap mkd.

| | |
|--------|--------|
| T 38 N | R 11 E |
| 1/4 | |
| S 28 | S 27 |

2012

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Set a steel fence post nearby.

Cor. is located on top of N. edge of spur, 15 ft. wide, 8 ft.
high, bears N. 70° E. and S. 75° W.

80.00

Point for the cor. of secs. 21, 22, 27 and 28, located on the NW
steep face of sandstone outcrop, where it is impracticable to
set a permanent monument.

From this true point, the point selected for a witness cor. to
the cor. of secs. 21, 22, 27 and 28, bears N. 24°56' E., 33 lks.
dist.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
23 ins. in sandstone bedrock, with brass cap mkd.

Survey of a Portion of the Subdivisional Lines,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS

WC
T 38 N R 11 E
S 21 | S 22
S 28 | S 27
↙
2012

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Land, rolling.

Soil, sandy loam and sandstone rock outcrops.

Timber, juniper and piñon.

Undergrowth, native grasses, salt brush, yucca and Mormon tea.

N. 0°02' W., bet. secs. 21 and 22.

Over rolling land.

40.00 Point for the 1/4 sec. cor. of secs. 21 and 22.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 38 N R 11 E
1/4
S 21 | S 22
2012

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

Cor. is located on the bottom W. edge of the N. entrance of a sandstone inlet, 80 ft. deep, 30 ft. wide, 10 ft. high, bears S. 10° W.

80.00 Point for the cor. of secs. 15, 16, 21 and 22.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 38 N R 11 E
S 16 | S 15
S 21 | S 22
2012

Survey of a Portion of the Subdivisional Lines,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

Land, gently rolling.

Soil, sandy loam and sandstone rock outcrops.

Timber, scattered juniper.

Undergrowth, native grasses, salt brush, sage and Mormon tea.

N. 0°02' W., bet. secs. 15 and 16.

Over rolling land.

40.00 Point for the 1/4 sec. cor. of secs. 15 and 16.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in solid sandstone bedrock, with brass cap mkd.

T 38 N R 11 E

1/4

S 16 | S 15

2012

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

80.00 Point for the cor. of secs. 9, 10, 15 and 16.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 38 N R 11 E

S 9 | S 10

S 16 | S 15

2012

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

Land, gently rolling and broken.

Soil, sandy loam and sandstone rock outcrops.

Timber, juniper and sparse piñon.

Undergrowth, native grasses, greasewood, and Mormon tea.

Survey of a Portion of the Subdivisional Lines,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | |
|--------|---|--------|--------|-----|-----|-----|------|
| | N. 0°02' W., bet. secs. 9 and 10. | | | | | | |
| | Over rolling land. | | | | | | |
| 40.00 | Point for the 1/4 sec. cor. of secs. 9 and 10. | | | | | | |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. | | | | | | |
| | <table style="margin: auto;"> <tr><td>T 38 N</td><td>R 11 E</td></tr> <tr><td></td><td style="text-align: center;">1/4</td></tr> <tr><td>S 9</td><td style="border-left: 1px solid black;">S 10</td></tr> </table> | T 38 N | R 11 E | | 1/4 | S 9 | S 10 |
| T 38 N | R 11 E | | | | | | |
| | 1/4 | | | | | | |
| S 9 | S 10 | | | | | | |
| | 2012 | | | | | | |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. | | | | | | |
| | Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. | | | | | | |
| | Cor. is located 62 lks. S. of sandstone mesa ridge, 50 ft. high, bears S. 80° E. and S. 80° W. | | | | | | |
| 80.00 | Point for the cor. of secs. 3, 4, 9 and 10. | | | | | | |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. | | | | | | |
| | <table style="margin: auto;"> <tr><td>T 38 N</td><td>R 11 E</td></tr> <tr><td>S 4</td><td style="border-left: 1px solid black;">S 3</td></tr> <tr><td>S 9</td><td style="border-left: 1px solid black;">S 10</td></tr> </table> | T 38 N | R 11 E | S 4 | S 3 | S 9 | S 10 |
| T 38 N | R 11 E | | | | | | |
| S 4 | S 3 | | | | | | |
| S 9 | S 10 | | | | | | |
| | 2012 | | | | | | |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. | | | | | | |
| | Set a steel fence post nearby. | | | | | | |
| | Land, gently rolling and broken. | | | | | | |
| | Soil, sandy loam and sandstone rock outcrops. | | | | | | |
| | Timber, juniper. | | | | | | |
| | Undergrowth, native grasses, yucca, sage and Mormon tea. | | | | | | |
| | <hr/> | | | | | | |
| | N. 0°02' W., bet. secs. 3 and 4. | | | | | | |
| | Over rolling land. | | | | | | |
| 40.00 | Point for the 1/4 sec. cor. of secs. 3 and 4. | | | | | | |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. | | | | | | |

Survey of a Portion of the Subdivisional Lines,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | T 38 N R 11 E 1/4 S 4 S 3 2012 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. |
| 80.00 | The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described. Land, rolling and broken. Soil, sandy loam and sandstone rock outcrops. Timber, scattered juniper. Undergrowth, native grasses, salt brush, sage and Mormon tea. |
| | <hr/> From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T38N R11E S32 S33 S5 S4 T37N 2012. N. 0°03' W., bet. secs. 32 and 33. Over gently rolling land. |
| 20.20 | S. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway. |
| 21.65 | S. edge of State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 60° E. and N. 60° W. |
| 22.30 | N. edge of State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 60° E. and N. 60° W. |
| 23.75 | N. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 32 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T 38 N R 11 E 1/4 S 32 S 33 2012 |

Survey of a Portion of the Subdivisional Lines,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | |
|--------|---|--------|--------|------|------|------|------|------|--|
| 80.00 | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Point for the cor. of secs. 28, 29, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in solid sandstone bedrock, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 38 N</td><td>R 11 E</td></tr> <tr><td>S 29</td><td>S 28</td></tr> <tr><td>S 32</td><td>S 33</td></tr> </table> <p>2012</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Cor. is located 1.70 chs. E. of trail road, bears S. 20° E. and N. 30° W.</p> <p>Land, gently rolling. Soil, sandy loam and sandstone rock outcrops. Timber, juniper. Undergrowth, native grasses, salt brush, sage and Mormon tea.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>West, bet. secs. 28 and 33.</p> <p>Over rolling land.</p> | T 38 N | R 11 E | S 29 | S 28 | S 32 | S 33 | | |
| T 38 N | R 11 E | | | | | | | | |
| S 29 | S 28 | | | | | | | | |
| S 32 | S 33 | | | | | | | | |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 38 N</td><td>R 11 E</td></tr> <tr><td>S 28</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 33</td><td></td></tr> </table> <p>2012</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> | T 38 N | R 11 E | S 28 | | 1/4 | — | S 33 | |
| T 38 N | R 11 E | | | | | | | | |
| S 28 | | | | | | | | | |
| 1/4 | — | | | | | | | | |
| S 33 | | | | | | | | | |

Survey of a Portion of the Subdivisional Lines,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 80.00 | <p>The cor. of secs. 28, 29, 32 and 33.</p> <p>Land, rolling. Soil, sandy loam and sandstone rock outcrops. Timber, juniper. Undergrowth, native grasses, salt brush, yucca and Mormon tea.</p> <hr/> |
| | <p>N. 0°03' W., bet. secs. 28 and 29.</p> |
| | <p>Over rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in solid sandstone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 11 E 1/4 S 29 S 28</p> <p style="text-align: center;">2012</p> |
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> |
| 80.00 | <p>Point for the cor. of secs. 20, 21, 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 11 E S 20 S 21 S 29 S 28</p> <p style="text-align: center;">2012</p> |
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> |
| | <p>Set a steel fence post nearby.</p> |
| | <p>Land, rolling. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses, salt brush, yucca, rabbit brush and Mormon tea.</p> <hr/> |
| | <p>From the true point for the cor. of secs. 21, 22, 27 and 28.</p> |
| | <p>West, bet. secs. 21 and 28.</p> |

Survey of a Portion of the Subdivisional Lines,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | Over rolling land. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 21 and 28. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. |
| | <p style="text-align: center;">T 38 N R 11 E S 21 1/4 ——— S 28</p> |
| | 2012 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Set a steel fence post nearby. |
| 80.00 | The cor. of secs. 20, 21, 28 and 29. |
| | Land, rolling. |
| | Soil, sandy loam. |
| | Timber, juniper. |
| | Undergrowth, native grasses, salt brush, yucca and Mormon tea. |
| | N. 0°03' W., bet. secs. 20 and 21. |
| | Over gently rolling land. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 20 and 21. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | <p style="text-align: center;">T 38 N R 11 E 1/4 S 20 S 21</p> |
| | 2012 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Set a steel fence post nearby. |
| 80.00 | Point for the cor. of secs. 16, 17, 20 and 21. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |

Survey of a Portion of the Subdivisional Lines,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS

| | |
|---------------|------|
| T 38 N R 11 E | |
| S 17 | S 16 |
| S 20 | S 21 |

2012

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

Land, gently rolling and nearly level.

Soil, sandy loam.

Timber, juniper and piñon.

Undergrowth, native grasses, salt brush, yucca and Mormon tea.

From the cor. of secs. 15, 16, 21 and 22.

West, bet. secs. 16 and 21.

Over rolling land.

40.00 Point for the 1/4 sec. cor. of secs. 16 and 21.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

| | |
|---------------|------|
| T 38 N R 11 E | |
| | S 16 |
| 1/4 | — |
| | S 21 |

2012

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

47.35 Top of sandstone mesa rim, 350 ft. high, bears N. 15° E. and S. 15° W.

80.00 The cor. of secs. 16, 17, 20 and 21.

Land, rolling and broken.

Soil, sandy loam.

Timber, juniper and piñon.

Undergrowth, native grasses, salt brush, yucca and Mormon tea.

N. 0°03' W., bet. secs. 16 and 17.

Survey of a Portion of the Subdivisional Lines,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | Over gently rolling land. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 16 and 17. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., |
| | 23 ins. in the ground, with brass cap mkd. |
| | <p style="text-align: center;">T 38 N R 11 E 1/4 S 17 S 16</p> |
| | <p style="text-align: center;">2012</p> |
| | Deposit a magnet, in a white plastic case, at the base of the |
| | stainless steel post. |
| | Set a steel fence post nearby. |
| 80.00 | Point for the cor. of secs. 8, 9, 16 and 17. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., |
| | 23 ins. in the ground, with brass cap mkd. |
| | <p style="text-align: center;">T 38 N R 11 E S 8 S 9 S 17 S 16</p> |
| | <p style="text-align: center;">2012</p> |
| | Deposit a magnet, in a white plastic case, at the base of the |
| | stainless steel post. |
| | Set a steel fence post nearby. |
| | Land, gently rolling and broken. |
| | Soil, sandy loam and sandstone rock outcrops. |
| | Timber, juniper. |
| | Undergrowth, native grasses, sage and Mormon tea. |
| | <hr/> From the cor. of secs. 9, 10, 15 and 16. |
| | West, bet. secs. 9 and 16. |
| | Over gently rolling land. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 9 and 16. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., |
| | 24 ins. in the ground, with brass cap mkd. |

Survey of a Portion of the Subdivisional Lines,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 80.00 | <p style="text-align: center;">T 38 N R 11 E S 9 1/4 ——— S 16</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, sparse juniper. Undergrowth, native grasses, sage and Mormon tea.</p> <hr/> |
| 40.00 | <p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over gently rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| 80.00 | <p style="text-align: center;">T 38 N R 11 E 1/4 S 8 S 9</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> |
| 80.00 | <p>Point for the cor. of secs. 4, 5, 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 11 E S 5 S 4 S 8 S 9</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> |

Survey of a Portion of the Subdivisional Lines,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Set a steel fence post nearby.</p> <p>Land, gently rolling to rolling. Soil, sandy loam and sandstone rock outcrops. No timber. Undergrowth, native grasses, salt brush and Mormon tea.</p> <hr/> |
| | <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>West, bet. secs. 4 and 9.</p> <p>Over gently rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T 38 N R 11 E S 4 1/4 ——— S 9</p> <p style="text-align: center;">2012</p> |
| 80.00 | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>The cor. of secs. 4, 5, 8 and 9.</p> |
| | <p>Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, sage and Mormon tea.</p> <hr/> |
| 40.00 | <p>N. 0°03' W., bet. secs. 4 and 5.</p> <p>Over gently rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> |

Survey of a Portion of the Subdivisional Lines,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 80.00 | <p style="text-align: center;">T 38 N R 11 E 1/4 S 5 S 4 2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located on the N. slope of ridge, 80 ft. wide, 30 ft. high, bears S. 40° E. and N. 40° W.</p> <p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling and broken. Soil, sandy loam and sandstone rock outcrops. Timber, scattered juniper. Undergrowth, native grasses, salt brush, sage, yucca and Mormon tea.</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush with the surface of the ground, with brass cap mkd. T38N R11E S31 S32 S6 S5 T37N 2012.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over gently rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 11 E 1/4 S 31 S 32 2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> |
| 42.50 | <p>Power line, 2 strand, bears N. 40° E. and S. 40° W.</p> |
| 59.50 | <p>Power line, 2 strand, bears S. 50° E. and N. 50° W.</p> |

Survey of a Portion of the Subdivisional Lines,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | |
|--------|---|--------|--------|------|------|------|-------|--|------|
| 68.70 | Graded road, 35 ft. wide, bears N. 30° E. and S. 30° W. | | | | | | | | |
| 76.05 | Graded road, 25 ft. wide, bears N. 40° E. and S. 40° W. | | | | | | | | |
| 80.00 | Point for the cor. of secs. 29, 30, 31 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 38 N</td> <td>R 11 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 30</td> <td>S 29</td> </tr> <tr> <td style="border-right: 1px solid black;">S 31</td> <td>S 32</td> </tr> </table> <p>2012</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, gently rolling. Soil, sandy loam and scattered sandstone rock outcrops. Timber, scattered juniper and piñon. Undergrowth, native grasses, salt brush, sage and Mormon tea.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>West, bet. secs. 29 and 32.</p> <p>Over gently rolling land.</p> | T 38 N | R 11 E | S 30 | S 29 | S 31 | S 32 | | |
| T 38 N | R 11 E | | | | | | | | |
| S 30 | S 29 | | | | | | | | |
| S 31 | S 32 | | | | | | | | |
| 40.00 | Point for the 1/4 sec. cor. of secs. 29 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 38 N</td> <td>R 11 E</td> </tr> <tr> <td></td> <td>S 29</td> </tr> <tr> <td>1/4</td> <td style="border-top: 1px solid black;">_____</td> </tr> <tr> <td></td> <td>S 32</td> </tr> </table> <p>2012</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the nearest corner of a Hogan, 27 ft. diam., bears N. 27°23' E., 49.5 lks. dist.</p> | T 38 N | R 11 E | | S 29 | 1/4 | _____ | | S 32 |
| T 38 N | R 11 E | | | | | | | | |
| | S 29 | | | | | | | | |
| 1/4 | _____ | | | | | | | | |
| | S 32 | | | | | | | | |
| 71.85 | E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway. | | | | | | | | |

Survey of a Portion of the Subdivisional Lines,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 73.70 | State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 35° E. and N. 35° W. |
| 75.55 | W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway. |
| 76.55 | Four-way intersection of graded roads, 40 ft. wide, extending N. 35° E., S. 35° E., S. 5° E. and S. 45° W. |
| 80.00 | The cor. of secs. 29, 30, 31 and 32. Land, gently rolling. Soil, sandy loam and sandstone rock outcrops. Timber, juniper. Undergrowth, native grasses, salt brush, sage and Mormon tea. <hr/> |
| | West, bet. secs. 30 and 31. Over gently rolling land. |
| 23.55 | Power line, 2 strand, bears S. 50° E. and N. 50° W. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 30 and 31. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 38 N R 11 E S 30 1/4 ——— S 31 2012 </div> |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. |
| 79.36 | The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described. Land, gently rolling. Soil, sandy loam. Timber, juniper and piñon. Undergrowth, native grasses, sage and salt brush. <hr/> |
| | From the cor. of secs. 29, 30, 31 and 32. N. 0°03' W., bet. secs. 29 and 30. |

Survey of a Portion of the Subdivisional Lines,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | Over gently rolling land. |
| 6.00 | W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway. |
| 8.45 | State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 35° E. and N. 35° W. |
| 11.00 | E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 29 and 30. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | <div style="text-align: center;"> T 38 N R 11 E 1/4 S 30 S 29 </div> |
| | <div style="text-align: center;">2012</div> |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Set a steel fence post nearby. |
| 80.00 | Point for the cor. of secs. 19, 20, 29 and 30. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. |
| | <div style="text-align: center;"> T 38 N R 11 E S 19 S 20 S 30 S 29 </div> |
| | <div style="text-align: center;">2012</div> |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Set a steel fence post nearby. |
| | Land, gently rolling. |
| | Soil, sandy loam. |
| | Timber, juniper. |
| | Undergrowth, native grasses, salt brush, yucca and Mormon tea. |
| | From the cor. of secs. 20, 21, 28 and 29. |
| | West, bet. secs. 20 and 29. |

Survey of a Portion of the Subdivisional Lines,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | Over gently rolling land. |
| 36.30 | Base of sandstone rim, bears S. 5° E. and N. 5° W. |
| 37.00 | Top of sandstone rim, 20 ft. high, bears N. 5° E. and S. 5° W. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 20 and 29. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. |
| | <p style="text-align: center;">T 38 N R 11 E S 20 1/4 ——— S 29</p> <p style="text-align: center;">2012</p> |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Set a steel fence post nearby. |
| 80.00 | The cor. of secs. 19, 20, 29 and 30. |
| | <p>Land, gently rolling. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses, salt brush and Mormon tea.</p> <hr/> |
| | West, bet. secs. 19 and 30. |
| | Over gently rolling land. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 19 and 30. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | <p style="text-align: center;">T 38 N R 11 E S 19 1/4 ——— S 30</p> <p style="text-align: center;">2012</p> |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Set a steel fence post nearby. |

Survey of a Portion of the Subdivisional Lines,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | Cor. is located 1.23 chs. W. of trail road, bears S. 15° E. and N. 15° W., and 2.35 chs. E. of sandstone rim, 150 ft. high, bears S. 10° E. and N. 10° W. |
| 49.45 | E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway. |
| 51.05 | State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 20° E. and N. 20° W. |
| 52.60 | W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway. |
| 61.95 | Power line, 2 strand, bears N. 5° E. and S. 5° W. |
| 79.27 | The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described. |
| | <p>Land, gently rolling to rolling. Soil, sandy loam and sandstone rock outcrops. Timber, juniper. Undergrowth, native grasses, salt brush and Mormon tea.</p> <hr/> |
| | From the cor. of secs. 19, 20, 29 and 30. |
| | N. 0°03' W., bet. secs. 19 and 20. |
| | Over gently rolling land. |
| 22.25 | Power line, 2 strand, bears S. 40° E. and N. 40° W. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 19 and 20. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | <p style="text-align: center;">T 38 N R 11 E 1/4 S 19 S 20 2012</p> |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Set a steel fence post nearby. |
| 80.00 | Point for the cor. of secs. 17, 18, 19 and 20. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |

Survey of a Portion of the Subdivisional Lines,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p style="text-align: center;">T 38 N R 11 E S 18 S 17 S 19 S 20</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, gently rolling to nearly level. Soil, sandy loam. Timber, juniper and piñon. Undergrowth, native grasses, yucca, salt brush and Mormon tea.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>West, bet. secs. 17 and 20.</p> <p>Over rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 11 ins. in the ground, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 11 E S 17 1/4 ——— S 20</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> |
| 80.00 | <p>The cor. of secs. 17, 18, 19 and 20.</p> <p>Land, broken and nearly level. Soil, sandy loam. Timber, juniper and piñon. Undergrowth, native grasses, yucca, salt brush and Mormon tea.</p> <hr/> <p>West, bet. secs. 18 and 19.</p> <p>Over gently rolling land.</p> |

Survey of a Portion of the Subdivisional Lines,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 11 E S 18 1/4 ——— S 19</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> |
| 49.25 | E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway. |
| 50.90 | State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 25° E. and N. 25° W. |
| 52.55 | W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway. |
| 79.18 | <p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, nearly level. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, yucca, rabbit brush and Mormon tea.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°03' W., bet. secs. 17 and 18.</p> <p>Over gently rolling land.</p> |
| 36.70 | Sandstone mesa rim, 50 ft. high, bears N. 25° E. and S. 25° W. |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |

Survey of a Portion of the Subdivisional Lines,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p style="text-align: center;">T 38 N R 11 E 1/4 S 18 S 17 2012</p> |
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> |
| | <p>Set a steel fence post nearby.</p> |
| 80.00 | <p>Point for the cor. of secs. 7, 8, 17 and 18.</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T 38 N R 11 E S 7 S 8 ----- S 18 S 17 2012</p> |
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> |
| | <p>Set a steel fence post nearby.</p> |
| | <p>Cor. is located 23 lks. E. of trail road, bears N. 10° E. and S. 10° W., and 1.00 chs. W. and 1.65 chs. N. of barbed wire fence, bears N. 30° E. and S. 30° W.</p> |
| | <p>Land, gently rolling and broken. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, salt brush, rabbit brush and Mormon tea.</p> |
| | <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> |
| | <p>West, bet. secs. 8 and 17.</p> |
| | <p>Over gently rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |

Survey of a Portion of the Subdivisional Lines,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p style="text-align: center;">T 38 N R 11 E S 8 1/4 ——— S 17 2012</p> |
| 80.00 | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, gently rolling and broken. Soil, sandy loam and sandstone rock outcrops. Timber, juniper. Undergrowth, native grasses, sage and Mormon tea.</p> <hr/> |
| 40.00 | <p>West, bet. secs. 7 and 18.</p> <p>Over nearly level land.</p> <p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| 79.09 | <p style="text-align: center;">T 38 N R 11 E S 7 1/4 ——— S 18 2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, nearly level. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, salt brush, sage and Mormon tea.</p> <hr/> |
| | <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°03' W., bet. secs. 7 and 8.</p> |

Survey of a Portion of the Subdivisional Lines,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | Over nearly level land. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 7 and 8. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. |
| | <p style="text-align: center;">T 38 N R 11 E 1/4 S 7 S 8</p> |
| | 2012 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Set a steel fence post nearby. |
| | Cor. is located 26 lks. N. and 25 lks. W. of trail road, bears N. 35° E. and S. 35° W. |
| 80.00 | Point for the cor. of secs. 5, 6, 7 and 8. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. |
| | <p style="text-align: center;">T 38 N R 11 E S 6 S 5 S 7 S 8</p> |
| | 2012 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Set a steel fence post nearby. |
| | Land, nearly level. |
| | Soil, sandy loam. |
| | No timber. |
| | Undergrowth, native grasses, salt brush, yucca and Mormon tea. |
| | From the cor. of secs. 4, 5, 8 and 9. |
| | West, bet. secs. 5 and 8. |
| | Over gently rolling land. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 5 and 8. |

Survey of a Portion of the Subdivisional Lines,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 11 E S 5 1/4 ——— S 8</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> |
| 80.00 | <p>The cor. of secs. 5, 6, 7 and 8.</p> <p>Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, salt brush, yucca, sage and Mormon tea.</p> <hr/> |
| | <p>West, bet. secs. 6 and 7.</p> <p>Over nearly level land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 11 E S 6 1/4 ——— S 7</p> <p style="text-align: center;">2012</p> |
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> |
| 79.00 | <p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, nearly level land. Soil, sandy loam. No timber. Undergrowth, native grasses, salt brush and Mormon tea.</p> <hr/> |

Survey of a Portion of the Subdivisional Lines,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°03' W., bet. secs. 5 and 6.</p> <p>Over nearly level land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in solid sandstone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 11 E 1/4 S 6 S 5</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> |
| 80.00 | <p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, nearly level land. Soil, sandy loam and sandstone rock outcrops. Timber, scattered juniper. Undergrowth, native grasses, yucca, salt brush and Mormon tea.</p> <hr/> <p style="text-align: center;">Subdivision of Section 18, T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 18 and 19.</p> <p>N. 0°04' W., on the N. and S. center line of sec. 18.</p> <p>Over gently rolling land.</p> |
| 40.00 | <p>Point for the center 1/4 sec. cor. of sec. 18, at intersection with the E. and W. center line of sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 11 E C 1/4 S 18</p> <p style="text-align: center;">2012</p> |

**Subdivision of Section 18,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona**

| CHAINS | |
|--------|---|
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> |
| 80.00 | <p>The 1/4 sec. cor. of secs. 7 and 18.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 17 and 18.</p> <p>West, on the E. and W. center line of sec. 18.</p> <p>Over gently rolling land.</p> |
| 40.00 | <p>The center 1/4 sec. cor. of sec. 18.</p> |
| 67.95 | <p>E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.</p> |
| 69.60 | <p>State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 25° E. and N. 25° W.</p> |
| 71.20 | <p>W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.</p> |
| 79.14 | <p>The 1/4 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp.</p> <hr/> <p style="text-align: center;">Subdivision of Section 19, T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 30.</p> <p>N. 0°04' W., on the N. and S. center line of sec. 19.</p> <p>Over gently rolling land.</p> |
| 40.00 | <p>Point for the center 1/4 sec. cor. of sec. 19, at intersection with the E. and W. center line of sec. 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 11 E C 1/4 S 19</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> |

**Subdivision of Section 19,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona**

| CHAINS | |
|--------|--|
| | Cor. is located 13 lks. W. of wash, 10 ft. wide, 2 ft. deep, drains S. 25° W. |
| | From this cor. point, a right-of-way monument, monumented with a brass tablet, 2 1/2 ins. diam., set flush in a concrete cylinder, 6 ins. diam., firmly set, projecting 9 ins. above ground, mkd. BIA ROADS 1969, with an angle iron, firmly set, to the E., faintly mkd. HWY ROW 1204+, bears S. 75°50' W., 1.82 chs. dist. |
| 53.30 | Power line, 2 strand, bears N. 85° E. and S. 85° W. |
| 80.00 | The 1/4 sec. cor. of secs. 18 and 19. |
| | <hr/> |
| | From the 1/4 sec. cor. of secs. 19 and 20. |
| | West, on the E. and W. center line of sec. 19. |
| | Over rolling land. |
| 15.75 | Power line, 2 strand, bears S. 40° E. and N. 40° W. |
| 40.00 | The center 1/4 sec. cor. of sec. 19. |
| 41.65 | E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway. |
| 43.20 | State Highway 98, an asphalt surfaced road, 35 ft. wide, bears N. 20° E. and S. 20° W. |
| 44.80 | W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway. |
| 57.65 | Power line, 2 strand, bears N. 5° E. and S. 5° W. |
| 79.23 | The 1/4 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp. |
| | <hr/> |
| | Subdivision of Section 29, T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona |
| | <hr/> |
| | From the 1/4 sec. cor. of secs. 29 and 32. |
| | N. 0°03' W., on the N. and S. center line of sec. 29. |
| | Over rolling land. |
| 40.00 | Point for the center 1/4 sec. cor. of sec. 29, at intersection with the E. and W. center line of sec. 29. |

**Subdivision of Section 29,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona**

| CHAINS | |
|--------|---|
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 11 E C 1/4 S 29</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> |
| 80.00 | <p>The 1/4 sec. cor. of secs. 20 and 29.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 28 and 29.</p> <p>West, on the E. and W. center line of sec. 29.</p> <p>Over gently rolling land.</p> |
| 40.00 | <p>The center 1/4 sec. cor. of sec. 29.</p> |
| 80.00 | <p>The 1/4 sec. cor. of secs. 29 and 30.</p> <hr/> <p style="text-align: center;">Subdivision of Section 30, T. 38 N., R. 11 E Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 30 and 31.</p> <p>N. 0°04' W., on the N. and S. center line of sec. 30.</p> <p>Over gently rolling land.</p> |
| 14.35 | <p>Power line, 2 strand, bears S. 50° E. and N. 50° W.</p> |
| 40.00 | <p>Point for the center 1/4 sec. cor. of sec. 30, at intersection with the E. and W. center line of sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 11 E C 1/4 S 30</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> |

Subdivision of Section 30,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | Set a steel fence post nearby. |
| 60.00 | W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway. |
| 62.50 | State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 35° E. and N. 35° W. |
| 65.05 | E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway. |
| 80.00 | The 1/4 sec. cor. of secs. 19 and 30. |
| | <hr/> |
| | From the 1/4 sec. cor. of secs. 29 and 30. |
| | West, on the E. and W. center line of sec. 30. |
| | Over gently rolling land. |
| 20.85 | From this point, a right-of-way monument, bears S., 80.8 lks. dist., monumented with a brass tablet, 2 1/2 ins. diam., set flush in a concrete cylinder, 6 ins. diam., firmly set, projecting 3 ins. above ground, mkd. BIA ROADS 1969, with an angle iron, firmly set, projecting 31 ins. above ground, to the E., faintly mkd. HWY R of W. |
| 21.45 | E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway. |
| 23.30 | From this point, a right-of-way monument, bears S., 2.61 chs. dist., monumented with a brass tablet, 2 1/2 ins. diam., set flush in a concrete cylinder, 6 ins. diam., firmly set, projecting 5 ins. above ground, mkd. BIA ROADS 1969, with an angle iron, firmly set, projecting 27 ins. above ground, to the E., faintly mkd. 1265+47.88 HWY R of W. |
| 23.35 | State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 35° E. and N. 35° W. |
| 25.20 | W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway. |
| 40.00 | The center 1/4 sec. cor. of sec. 30. |
| 66.30 | Power line, 2 strand, bears N. 5° E. and S. 5° W. |
| 79.32 | The 1/4 sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp. |
| | <hr/> |

Subdivision of Section 32,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>From the 1/4 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T38N R11E S32 1/4 S5 T37N 2012.</p> <p>N. 0°03' W., on the N. and S. center line of sec. 32.</p> <p>Over gently rolling land.</p> |
| 28.25 | Power line, 2 strand, bears S. 50° E. and N. 50° W. |
| 40.00 | Point for the center 1/4 sec. cor. of sec. 32, at intersection with the E. and W. center line of sec. 32. |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in solid sandstone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 11 E C 1/4 S 32</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> |
| 46.25 | S. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway. |
| 48.05 | State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 55° E. and N. 55° W. |
| 49.85 | N. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway. |
| 80.00 | The 1/4 sec. cor. of secs. 29 and 32. |
| | <hr/> <p>From the 1/4 sec. cor. of secs. 32 and 33.</p> <p>West, on the E. and W. center line of sec. 32.</p> <p>Over gently rolling land.</p> |
| 24.85 | N. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway. |
| 27.10 | N. edge of State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 55° E. and N. 55° W. |
| 28.05 | S. edge of State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 55° E. and N. 55° W. |

Subdivision of Section 32,
T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|---|--|
| 30.30 | S. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway. |
| 40.00 | The center 1/4 sec. cor. of sec. 32. |
| 55.25 | Power line, 2 strand, bears S. 50° E. and N. 50° W. |
| 80.00 | The 1/4 sec. cor. of secs. 31 and 32. |
| <hr/> <p style="text-align: center;">Subdivision of Section 33, T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona</p> <hr/> | |
| | From the 1/4 sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T38N R11E S33 1/4 S4 T37N 2012. |
| | N. 0°02' W., on the N. and S. center line of sec. 33. |
| | Over gently rolling land. |
| 40.00 | Point for the center 1/4 sec. cor. of sec. 33, at intersection with the E. and W. center line of sec. 33. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T 38 N R 11 E C 1/4 S 33 |
| | 2012 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Set a steel fencepost nearby. |
| 80.00 | The 1/4 sec. cor. of secs. 28 and 33. |
| | <hr/> |
| | From the 1/4 sec. cor. of secs. 33 and 34. |
| | West, on the E. and W. center line of sec. 33. |
| | Over gently rolling land. |
| 40.00 | The center 1/4 sec. cor. of sec. 33. |
| 80.00 | The 1/4 sec. cor. of secs. 32 and 33. |
| | <hr/> |

T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

The area surveyed is within the Navajo Indian Reservation, is 9 miles northwest of the Kaibeto community, 17 miles southeast of the Lechee community, and 20 miles southeast of Page, Arizona. Primary access is along State Highway 98. Multiple unnamed main dirt roads and a series of trail roads provide access throughout the township. ATV's were required to access the majority of the areas within the township.

There are no major housing developments, only smaller housing clusters and single home units scattered throughout the township. The Black Mesa and Lake Powell Railroad that supplies coal to the Navajo power plant in Page, meanders through section 31, the southwest portion of the township.

The highest elevation of this survey, 5994 feet above sea level, is in the southwest portion of the township, atop the sandstone mesas. The lowest elevation, at 5500 feet is below the sandstone ridge in the northwest portion of the township.

The vegetation consists of scattered juniper and sparse piñon throughout the township and, nonexistent in the northwest part of the township. Sage brush, salt brush, Mormon tea and native grasses, are more prominent throughout the township. There is presence of grazing cattle, sheep and horses in the area. The soil is mostly sandy loam with a high coverage of sandstone rock outcrops.

The mean magnetic declination of 11° E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2010-2015 for the dates of survey.

CERTIFICATE OF SURVEY

I, Fabian Yazzie, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 5th day of October, 2012, I have established the northeast township corner, surveyed the west boundary, a portion of the north boundary, and a portion of the subdivisional lines, and the subdivision of certain sections, T. 38 N., R. 11 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and in specific manner described in the foregoing field notes.

4/15/2013

(Date)



(Cadastral Surveyor)


CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the establishment of the northeast township corner, the survey of the west boundary, a portion of the north boundary, and a portion of the subdivisional lines, and the subdivision of certain sections, T. 38 N., R. 11 E., Gila and Salt River Meridian, in the State of Arizona, executed by Fabian Yazzie, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

4/22/2013

(Date)



(Chief Cadastral Surveyor of Arizona)

 CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 38 N., R. 11 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.

 (Date)

 (Chief Cadastral Surveyor of Arizona)
